Study Questions (Chapter 03 – Part 6)

1. Question 3.29 on page 225: Some machines have a find-first-one instruction that counts the location of the first bit set to 1 within the word. Write an ARM sequence of instructions that takes the word in r0 and puts the locations of the first bit set to 1 in r1. Count from the left so that if bit 31 is set, the value returned should be 0. If bit 0 is set, the value returned is 31. If no bit is set, the value returned should be 32.

2. Write a suitable ARM assembly segment of code to implement the following code.

```
r0 = 255;
r1 = 1;
while(r0 >=0)
{ r1 += r1*8;
  r1 = r1 + r0 >> 2;
  if(r1 is odd)
  THEN  r0 = r0 - 64;
  ELSE  r0 = r0 - 96;
}
```

```
MOV R0, #FF
MOV R1, #1
while MOV R3, R1
MLA R1, R3, #8, R1
TST R1, #1
SUBEQ
SUBNE
TST R0, 0
BLT while
```

3. Explain what this fragment of code does. What are the values of registers at the end of the execution?

```
            MOV   R0, #255
            MOV   R1, #1
loop        CMP   R0,#0
            BLT   whileExit
            ADD   R1,R1,R1,LSL#3
            ADD   R1,R1,R0,ASR#2
            TST   R1,#1
odd         SUBNE R0,#64
even        SUBEQ R0,#96
            B     loop
whileExit
```

4. Write a suitable ARM assembly segment of code to implement the following code.

```
r0 = 255;
r1 = 1;
{
  r1 = r1*9;
  r1 = r1 + r0 >> 2;
  if(r1 is even)
  THEN  r0 = r0 - 64;
  ELSE  r0 = r0 - 96;
} until(r0 <=0)
```

5. Explain what this fragment of code does. What are the values of registers at the end of the execution?

```
            MOV   R0, #255
            MOV   R1, #1
repeat      ADD   R1,R1,R1,LSL#3
            ADD   R1,R1,R0,ASR#2
            TST   R1,#1
even        SUBEQ R0,#64
odd         SUBNE R0,#96
            CMP   R0,#0
            BGT   repeat
```

6. Write a suitable ARM code to implement the following code segment.

```
int total;
int i;

total = 0;
for (i = 10; i > 0; i--)
{
    total += i;
}
```

7. Explain what this fragment of code does. What are the values of registers at the end of the execution?

```
        MOV  R0, #0          ; R0 accumulates total
        MOV  R1, #10         ; R1 counts from 10 down to 1
for     ADD  R0, R0, R1
        SUBS R1, R1, #1
        BNE  for
```

8. Write a suitable ARM code to implement the following code segment.

```
    a = 40;
    b = 25;
    while (a != b) {
        if (a > b) a -= b;
        else       b -= a;
    }
```

9. Explain what this fragment of code does. What are the values of registers at the end of the execution?

```
        MOV   R0, #40      ; R0 is a
        MOV   R1, #25      ; R1 is b
while   CMP   R0, R1
        SUBGT R0, R0, R1
        SUBLT R1, R1, R0
        BNE   while
halt    B     halt
```

10. Write a suitable ARM code to implement the following code segment.

iters ← 0
while $n \neq 1$**:**
  iters ← *iters* + 1
  if n is odd**:**
    $n \leftarrow 3 \times n + 1$
  else:
    $n \leftarrow n / 2$

11. Explain what this fragment of code does. What are the values of registers at the end of the execution?

```
        MOV  R0, #5          ; R0 is the current number
        MOV  R1, #0          ; R1 is a count of the number of iterations
while   ADD  R1, R1, #1      ; increment number of iterations
        TST  R0, #1          ; test whether R0 is odd
        BEQ  even
        ADD  R0, R0, R0, LSL #1 ; if odd, set R0 = R0 + (R0 << 1) + 1
        ADD  R0, R0, #1      ; and repeat (guaranteed R0 > 1)
        B    while
even    MOV  R0, R0, ASR #1 ; if even, set R0 = R0 >> 1
        SUBS R7, R0, #1      ; and repeat if R0 != 1
        BNE  again
halt    B    halt            ; infinite loop to stop the computation
```