

- ▶ `document.getElementById(id);` ← Since id is unique,
- ▶ `document.getElementsByTagName(tag);`
- ▶ `document.getElementsByClassName(class);`

`md.style.width = "100px";` ← don't forget " " mark after each "="  
`md.style.margin = "5px";`

## camel Case

`fb.className = "box newbox"; // 2 classes.` : box ; newbox.

- ▶ Single class is usually a replacement.
- ▶ Multiple classes are usually additions.
  - ▶ Retain original class styles.
  - ▶ Additional class(es) provide new or modified styles.

key down/up : for a specific key.

key press : fire when any key is pressed.

text, password, textarea => `element.value`

radio buttons, checkboxes => `element.checked`.

- ▶ Easy to access elements by tag, class, and ID with jQuery.
- ▶ `$(".theClass")`
  - ▶ Similar to `getElementsByClassName()`
- ▶ `$("#theID")`
  - ▶ Similar to `getElementById()`
- ▶ `$("tag")`
  - ▶ Similar to `getElementsByTagName()`

## Parallax: onscroll

lab 9: parallax, scrollfire, transition	Asmt 4: business webpage: 4.
8: 3d bootstrap.	Asmt 3: restaurant webpage: 5
7:	Asmt 2: restaurant poster

dropdown menu - onchange

p with class info: p.info

img within divs: div img

circular div: border radius > d/2.

space inside HTML element: padding.

metadata => head.

HTML看清楚题目要的是什么!



mask gradient from white down to black.

remove large object: inpainting brush tool.

quick mask: selection tool.