These slides are being provided with permission from the copyright for CS2208 use only. The slides must not be reproduced or provided to anyone outside of the class.

All download copies of the slides and/or lecture recordings are for personal use only. Students must destroy these copies within 30 days after receipt of final course evaluations.

Tutorial 04: Rounding and Normalization

Computer Science Department

CS2208: Introduction to Computer Organization and Architecture

Fall 2022-2023

Instructor: Mahmoud R. El-Sakka

Office: MC-419

Email: elsakka@csd.uwo.ca

Phone: 519-661-2111 x86996



Rounding

- □ The rounding mechanisms include
 - Truncation (i.e., dropping unwanted bits) by rounding towards zero; a.k.a., rounding down
 - o Rounding towards positive or negative infinity: the nearest valid floating-point number in the direction of positive infinity (for positive values) or negative infinity (for negative values) is chosen to decide the rounding; a.k.a., rounding up.
 - Rounding to nearest: the closest valid floating-point number to the actual value is used.

Rounding

Example 1: Round to the nearest the following numbers to 8 digits after the binary point.

```
0.110101011001000 ==> 0.11010101
                                            0.110101001001000 ==> 0.11010100
                         0.0000001
                                                                  + 0.00000001
                         0.11010110
                                                                    = 0.11010101
                          is == case
                                                                     If it is == case.
                                                                     and this bit = 0.
                        you round up.
                                                                    you round down.
                                            0.11010100\overline{1}000000
0.11010101\overline{1000000}
                    ==> 0.11010101
                                                                 ==> 0.11010100
                     • + 0.0000001
                                                                   + 0.0000000
                                                   1000000
                       = 0.11010110
                                                                    = 0.11010100
                    Mid-way → round to even significand
                                                  100000
0.110101010_{xxxxxx} ==> 0.11010101
                                            0.110101000xxxxxx ==> 0.11010100
                         0.0000000
                                                                     0.0000000
   xxxxxx0
                         0.11010101
                                                                      0.11010100
                                                   0xxxxxx
   1000000
                                                  1000000
```

Normalization

■ <u>Example 2</u>: Convert the unsigned value AB.BA₁₆ to binary. <u>Normalize your answer</u>.

AB.BA₁₆

→ 10101011.10111010₂

After normalization,

 \rightarrow 1.010101110111010₂ × 2⁺⁷

In base b, a normalized number will have the form $\pm \ b_0 \ . \ b_1 \ b_2 \ b_3 ... \times b^n$ where $b_0 \neq 0$, and b_0 , b_1 , b_2 , b_3 ... are integers between 0 and b -1

$$0 = 0000$$

$$2 = 0010$$

$$3 = 0011$$

$$7 = 0111$$

$$A = 1010$$

$$C = 1100$$

Normalization and Rounding

Example 3: Consider the unsigned normalized binary value $1.0101011110111010_2 \times 2^{+1}$

```
limit it (using truncation / rounding down) to 6 bits (1 +
                                                               5 bits) in total
                                              to 6 bits (1 + 5 \text{ bits}) in total 4 = 0100
limit it (using rounding up)
limit it (using rounding to the nearest) to 6 bits (1 + 5 \text{ bits}) in total 5 = 0101
limit it (using truncation / rounding down) to 9 bits (1 + 8 bits) in total
                                     to 9 bits (1 + 8 \text{ bits}) in total
limit it (using rounding up)
                                                 9 bits (1 + 8 bits) in total 8 = 1000
limit it (using rounding to the nearest) to
limit it (using truncation / rounding down) to 14 bits (1 + 13 bits) in total
                                              to 14 bits (1 + 13 \text{ bits}) in total
limit it (using rounding up)
                                              to 14 bits (1 + 13 \text{ bits}) in total
limit it (using rounding to the nearest)
```

Calculate the rounding error in each case.

Note that: The binary value 1.010101110111010₂ \times 2⁺⁷ $= 10101011.101111010_{2} = AB.BA_{16}$ 0 = 0000

1 = 0001

2 = 0010

3 = 0011

9 = 1001

A = 1010

B = 1011

C = 1100

= 1101

E = 1110



Normalization and Rounding

- Limiting the answer to 6 bits (1 + 5) in total, $\rightarrow 1.0101011101111010_2 \times 2^{+7}$
- \rightarrow 1.01010₂ × 2⁺⁷ (using truncation / rounding down)
- ⇒ 10101000_{2} ⇒ $A8_{16}$ *Truncation* error = $AB.BA_{16} A8_{16} = 3.BA_{16}$
- $\rightarrow 1.01011_2 \times 2^{+7}$ (using rounding up) \rightarrow 1010110 $\overline{0}_{02}$ → AC₁₆
 - **Rounding up** error = AB.BA₁₆ AC₁₆ = -0.46_{16}
- \blacksquare As $11101111010_2 > 1000000000_2$
 - \rightarrow 1.01011₂ × 2⁺⁷ (using rounding to the nearest)
 - → 10101100_2 → AC_{16}
- **Rounding to the nearest** error = $AB.BA_{16} AC_{16} = -0.46_{16}$

- 0 = 00001 = 0001
- 2 = 0010
- 3 = 0011
- 4 = 0100
- 5 = 0101
- 6 = 0110
- 7 = 0111
- 8 = 1000
- 9 = 1001
- A = 1010
- B = 1011
- C = 1100
- D = 1101
- E = 1110
- F = 1111



Normalization and Rounding

- Limiting the answer to 9 bits (1 + 8) in total, $\rightarrow 1.0101011101111010_2 \times 2^{+7}$
- \rightarrow 1.01010111₂ × 2⁺⁷ (using truncation / rounding down)
 - $\rightarrow 10101011.1_{2}^{-} \rightarrow AB.8_{16}$
- **Truncation** error = $AB.BA_{16} AB.8_{16} = 0.3A_{16}$
- $\rightarrow 1.01011000_2 \times 2^{+7}$ (using rounding up)
 - → 10101100.0_{2} → AC_{16}
- **Rounding up** error = $AB.BA_{16} AC_{16} = -0.46_{16}$
- \blacksquare As $0111010_2 < 1000000_2$
 - \rightarrow 1.01010111₂ × 2⁺⁷ (using rounding to the nearest)
 - $\rightarrow 10101011.1_{2} \rightarrow AB.8_{16}$
- **Rounding to the nearest** error = $AB.BA_{16} AB.8_{16} = 0.3A_{16}$

- 0 = 0000
- 1 = 0001
- 2 = 0010
- 3 = 0011
- 4 = 0100
- 5 = 0101
- 6 = 0110
- 7 = 0111
- 8 = 1000
- 9 = 1001
- A = 1010
- B = 1011
- C = 1100
- D = 1101
- E = 1110



- Limiting the answer to 14 bits (1 + 13) in total,
- $\rightarrow 1.0101011110111010_2 \times 2^{+7}$
- - $\rightarrow 10101011.1011110_{2}^{2} \rightarrow AB.B8_{16}^{16}$
- **Truncation** error = $\overline{AB}.BA_{16} \overline{AB}.B8_{16} = 0.02_{16}$
- \rightarrow 1.01010111011111₂ × 2⁺⁷ (using rounding up)
- ⇒ 10101011.1011111 $_{2}$ → AB.BC $_{16}$ Rounding up error = AB.BA $_{16}$ AB.BC $_{16}$ = -0.02 $_{16}$
- \bullet As $10_2 == 10_2$
 - \rightarrow 1.0101011110110₂ × 2⁺⁷ (using rounding to the nearest)
 - $\rightarrow 10101011.110110_{2} \rightarrow AB.B8_{16}$
- **Rounding to the nearest** error $= \tilde{A}B.BA_{16} AB.B8_{16} = 0.02_{16}$
- Which **rounding mechanism** produces less error?

- 0 = 0000
- 1 = 0001

- 4 = 0100
- 5 = 0101
- 6 = 0110
- 7 = 0111
- 8 = 1000
- 9 = 1001
- A = 1010
- B = 1011
- C = 1100
- D = 1101
- E = 1110
- F = 1111