

These slides are being provided with permission from the copyright for CS2208 use only. The slides must not be reproduced or provided to anyone outside of the class.

All download copies of the slides and/or lecture recordings are for personal use only. Students must destroy these copies within 30 days after receipt of final course evaluations.

Tutorial 04: Rounding and Normalization

Computer Science Department

CS2208: Introduction to Computer Organization and Architecture

Fall 2022-2023

Instructor: Mahmoud R. El-Sakka

Office: MC-419

Email: elsakka@csd.uwo.ca

Phone: 519-661-2111 x86996

Rounding

□ The rounding mechanisms include

- *Truncation* (i.e., *dropping unwanted bits*) by *rounding towards zero*; a.k.a., *rounding down*
- *Rounding towards positive or negative infinity*: the *nearest valid floating-point number* in the direction of positive infinity (for positive values) or negative infinity (for negative values) is chosen to decide the rounding; a.k.a., *rounding up*.
- *Rounding to nearest*: the *closest valid floating-point number* to the actual value is used.

Rounding

□ *Example 1: Round to the nearest* the following numbers to 8 digits after the binary point.

$$0.110101011001000 \Rightarrow 0.11010101$$

$$\begin{array}{r} + 0.00000001 \\ \hline = 0.11010110 \end{array}$$

1001000
>
1000000

If it is == case,
and this bit = 1,
you round up.

$$0.110101011000000 \Rightarrow 0.11010101$$

$$\begin{array}{r} + 0.00000001 \\ \hline = 0.11010110 \end{array}$$

1000000
=
1000000

Mid-way → round to even significant

$$0.110101001001000 \Rightarrow 0.11010100$$

$$\begin{array}{r} + 0.00000001 \\ \hline = 0.11010101 \end{array}$$

1001000
>
1000000

If it is == case,
and this bit = 0,
you round down.

$$0.110101001000000 \Rightarrow 0.11010100$$

$$\begin{array}{r} + 0.00000000 \\ \hline = 0.11010100 \end{array}$$

1000000
=
1000000

$$0.110101010xxxxxx \Rightarrow 0.11010101$$

$$\begin{array}{r} + 0.00000000 \\ \hline = 0.11010101 \end{array}$$

0xxxxxx
<
1000000

$$0.110101000xxxxxx \Rightarrow 0.11010100$$

$$\begin{array}{r} + 0.00000000 \\ \hline = 0.11010100 \end{array}$$

0xxxxxx
<
1000000

Normalization

- Example 2: Convert the unsigned value $AB.BA_{16}$ to binary. Normalize your answer.

$AB.BA_{16}$

→ 10101011.10111010_2

After normalization,

→ $1.010101110111010_2 \times 2^{+7}$

0	=	0000
1	=	0001
2	=	0010
3	=	0011
4	=	0100
5	=	0101
6	=	0110
7	=	0111
8	=	1000
9	=	1001
A	=	1010
B	=	1011
C	=	1100
D	=	1101
E	=	1110
F	=	1111

In base b , a normalized number will have the form

$$\pm b_0 . b_1 b_2 b_3 \dots \times b^n$$

where $b_0 \neq 0$, and $b_0, b_1, b_2, b_3 \dots$ are integers between 0 and $b - 1$

Normalization and Rounding

■ Example 3: Consider the unsigned normalized binary value $1.010101110111010_2 \times 2^{+7}$

- limit it (using **truncation / rounding down**) to 6 bits (1 + 5 bits) in total
- limit it (using **rounding up**) to 6 bits (1 + 5 bits) in total
- limit it (using **rounding to the nearest**) to 6 bits (1 + 5 bits) in total
- limit it (using **truncation / rounding down**) to 9 bits (1 + 8 bits) in total
- limit it (using **rounding up**) to 9 bits (1 + 8 bits) in total
- limit it (using **rounding to the nearest**) to 9 bits (1 + 8 bits) in total
- limit it (using **truncation / rounding down**) to 14 bits (1 + 13 bits) in total
- limit it (using **rounding up**) to 14 bits (1 + 13 bits) in total
- limit it (using **rounding to the nearest**) to 14 bits (1 + 13 bits) in total

Calculate the rounding error in each case.

Note that: The binary value $1.010101110111010_2 \times 2^{+7}$
 $= 10101011.10111010_2 = \text{AB.BA}_{16}$

0 = 0000
 1 = 0001
 2 = 0010
 3 = 0011
 4 = 0100
 5 = 0101
 6 = 0110
 7 = 0111
 8 = 1000
 9 = 1001
 A = 1010
 B = 1011
 C = 1100
 D = 1101
 E = 1110
 F = 1111

Normalization and Rounding

- Limiting the answer to 6 bits (1 + 5) in total,
- $\rightarrow 1.010101110111010_2 \times 2^{+7}$
- $\rightarrow 1.01010_2 \times 2^{+7}$ (using **truncation / rounding down**)
 $\rightarrow 10101000_2 \rightarrow A8_{16}$
- **Truncation** error = $AB.BA_{16} - A8_{16} = 3.BA_{16}$
- $\rightarrow 1.01011_2 \times 2^{+7}$ (using **rounding up**)
 $\rightarrow 10101100_2 \rightarrow AC_{16}$
- **Rounding up** error = $AB.BA_{16} - AC_{16} = -0.46_{16}$
- As $1110111010_2 > 10000000000_2$
 $\rightarrow 1.01011_2 \times 2^{+7}$ (using **rounding to the nearest**)
 $\rightarrow 10101100_2 \rightarrow AC_{16}$
- **Rounding to the nearest** error = $AB.BA_{16} - AC_{16} = -0.46_{16}$

0	=	0000
1	=	0001
2	=	0010
3	=	0011
4	=	0100
5	=	0101
6	=	0110
7	=	0111
8	=	1000
9	=	1001
A	=	1010
B	=	1011
C	=	1100
D	=	1101
E	=	1110
F	=	1111

Normalization and Rounding

- Limiting the answer to 9 bits (1 + 8) in total,
- $\rightarrow 1.010101110111010_2 \times 2^{+7}$
- $\rightarrow 1.01010111_2 \times 2^{+7}$ (using **truncation / rounding down**)
 $\rightarrow 10101011.1_2 \rightarrow AB.8_{16}$
- **Truncation** error = $AB.BA_{16} - AB.8_{16} = 0.3A_{16}$
- $\rightarrow 1.01011000_2 \times 2^{+7}$ (using **rounding up**)
 $\rightarrow 10101100.0_2 \rightarrow AC_{16}$
- **Rounding up** error = $AB.BA_{16} - AC_{16} = -0.46_{16}$
- As $0111010_2 < 1000000_2$
 $\rightarrow 1.01010111_2 \times 2^{+7}$ (using **rounding to the nearest**)
 $\rightarrow 10101011.1_2 \rightarrow AB.8_{16}$
- **Rounding to the nearest** error = $AB.BA_{16} - AB.8_{16} = 0.3A_{16}$

0	=	0000
1	=	0001
2	=	0010
3	=	0011
4	=	0100
5	=	0101
6	=	0110
7	=	0111
8	=	1000
9	=	1001
A	=	1010
B	=	1011
C	=	1100
D	=	1101
E	=	1110
F	=	1111

Normalization and Rounding

- Limiting the answer to 14 bits (1 + 13) in total,
- $\rightarrow 1.010101110111010_2 \times 2^{+7}$
- $\rightarrow 1.0101011101110_2 \times 2^{+7}$ (using **truncation / rounding down**)
 $\rightarrow 10101011.101110_2 \rightarrow \text{AB.B8}_{16}$
- **Truncation** error = $\text{AB.BA}_{16} - \text{AB.B8}_{16} = 0.02_{16}$
- $\rightarrow 1.0101011101111_2 \times 2^{+7}$ (using **rounding up**)
 $\rightarrow 10101011.101111_2 \rightarrow \text{AB.BC}_{16}$
- **Rounding up** error = $\text{AB.BA}_{16} - \text{AB.BC}_{16} = -0.02_{16}$
- As $10_2 == 10_2$
 $\rightarrow 1.0101011101110_2 \times 2^{+7}$ (using **rounding to the nearest**)
 $\rightarrow 10101011.110110_2 \rightarrow \text{AB.B8}_{16}$
- **Rounding to the nearest** error = $\text{AB.BA}_{16} - \text{AB.B8}_{16} = 0.02_{16}$
round is even
- Which rounding mechanism produces less error?
nearest.

0	=	0000
1	=	0001
2	=	0010
3	=	0011
4	=	0100
5	=	0101
6	=	0110
7	=	0111
8	=	1000
9	=	1001
A	=	1010
B	=	1011
C	=	1100
D	=	1101
E	=	1110
F	=	1111