

University of Western Ontario  
Department of Computer Science  
Computer Science 1027b Midterm Exam  
March 8th, 2014, NS-1, 10am-noon, 2 hours

**PRINT YOUR NAME:**

**PRINT YOUR STUDENT NUMBER:**

**DO NOT TURN THIS PAGE UNTIL INSTRUCTED TO DO SO!**

## Instructions

- Fill in your name and student number above immediately.
- You have **2 hours** to complete the exam.
- Part 1 of the exam consists of Multiple Choice questions. Circle your answers on this exam paper.
- Part 2 consists of questions for which you will provide written answers. Write your answers in the spaces provided in this exam paper.
- Multiple choices question are worth 1 mark, unless indicated otherwise; other than that, the marks for each individual question are given. Allow approximately 1 minute per mark on average.
- There are pages for rough work at the back of the exam. You may detach them if you wish, but hand them in with the rest of the exam paper.
- Calculators are not allowed!

## Mark summary

1	2	3	4	5	6	total
/20	/20	/15	/15	/15	/15	/100

## Problem 1: true/false (20 marks)

Choose **one** answer for each question.

1. (1 mark) If Class A extends Class B (A ISA B), then Class A implements Class B.
  - (a) true
  - (b) false
2. (1 mark) A Java Class always has a constructor.
  - (a) true
  - (b) false
3. (1 mark) All Java Class methods can overload methods from the Object Class.
  - (a) true
  - (b) false
4. (1 mark) All the methods in a class A can see A's private variables.
  - (a) true
  - (b) false
5. (1 mark) Private variables are the same as Local variables.
  - (a) true
  - (b) false
6. (1 mark) If class A extends class B, then all the methods in A can see B's protected variables.
  - (a) true
  - (b) false
7. (1 mark) If class A extends class B, then all the methods in B can see A's protected variables.
  - (a) true
  - (b) false
8. (1 mark) If a class does not have a constructor method it uses the appropriate constructor method of a superclass with a constructor method in the class' ISA hierarchy.
  - (a) true
  - (b) false
9. (1 mark) A child class cannot override a parent method that is declared as public
  - (a) true
  - (b) false
10. (1 mark) The push, pop, peek and isEmpty methods of the StackADT class are  $O(1)$  operations.
  - (a) true
  - (b) false

11. (1 mark) An algorithm with time complexity  $O(2^n)$  runs in the same time as one with time complexity  $O(n^2)$ .
- (a) true
  - (b) false
12. (1 mark) Data encapsulation requires that local variables be declared as private variables.
- (a) true
  - (b) false
13. (1 mark) An interface can be used only if it is implemented by another class.
- (a) true
  - (b) false
14. (1 mark) An object of Class A can have its private variables set by methods in an unrelated Class B using setter methods defined in Class A.
- (a) true
  - (b) false
15. (1 mark) It is possible to have global variables in Java.
- (a) true
  - (b) false
16. (1 mark) Overloaded methods distinguish themselves by the number and type of their formal parameters.
- (a) true
  - (b) false
17. (1 mark) Method overriding is where a subclass adds additional implementations of one or more of its parent's methods.
- (a) true
  - (b) false
18. (1 mark) Polymorphism allows a reference variable to point to objects in a ISA hierarchy.
- (a) true
  - (b) false
19. (1 mark) dequeue is an  $O(n)$  operation for queues implemented using a linked list.
- (a) true
  - (b) false
20. (1 mark) dequeue is an  $O(n)$  operation for queues implemented using an array.
- (a) true
  - (b) false

## Problem 2 (20 marks)

Consider the following Java program:

```
1 public class midterm2014 {
2
3     // private variables
4     private StackADT<Integer> s = new LinkedStack<Integer>();
5     private StackADT<Integer> s2 = new LinkedStack<Integer>();
6
7     // Constructor
8     public midterm2014(Integer[] numbers){
9         for(int i=0;i<numbers.length;i++)
10            {
11                s2.push(new Integer(numbers[i]));
12            }
13     } // midterm2014 Constructor
14
15     // run method
16     public void run(){
17         s=whatDoesThisDo(s2);
18     } // run
19
20     public String toString(){
21         StackADT<Integer> c = whatDoesThisDo(s);
22         String stg;
23
24         if(c.isEmpty()) stg="Result stack is empty\n";
25         else
26         {
27             stg="Result stack: ";
28             while(!c.isEmpty())
29                 stg=stg+c.pop() + " ";
30         }
31         return stg;
32     } // toString
33
34     public StackADT<Integer> whatDoesThisDo(StackADT<Integer> s) {
35         StackADT<Integer> c = new LinkedStack<Integer>();
36         StackADT<Integer> c2 = new LinkedStack<Integer>();
37         Integer temp;
38         // Empty s and put contents in reverse order onto c
39         while(!s.isEmpty())
40         {
41             temp=s.pop();
42             c.push(temp);
43         }
44         // Empty c1 and put results in right order into s and c2
45         // Thus s is in its original state and c2 is a copy of it
46         while(!c.isEmpty())
47         {
48             temp=c.pop();
```

```

49     s.push(temp);
50     c2.push(temp);
51 }
52 return c2;
53 } // whatDoesThis Do
54
55 } // midterm2014 class
56
57 class Test2014 {
58     public static void main(String[] args) {
59         // allocate an array of 10 elements with no objects
60         Integer numbers[]=new Integer[10];
61         numbers[0]=new Integer(-9);
62         numbers[1]=new Integer(9);
63         numbers[2]=new Integer(-4);
64         numbers[3]=new Integer(4);
65         numbers[4]=new Integer(-29);
66         numbers[5]=new Integer(29);
67         numbers[6]=new Integer(-1024);
68         numbers[7]=new Integer(1024);
69         numbers[8]=new Integer(-1123);
70         numbers[9]=new Integer(1123);
71         System.out.println("Input:");
72         for(int i=0;i<10;i++)
73             System.out.print("number[" + i + "]= " + numbers[i] + "\n");
74         midterm2014 p = new midterm2014(numbers);
75         System.out.println(p.toString());
76         p.run();
77         System.out.println(p.toString());
78     }
79 } // Test2014

```

Answer the following questions:

(2a) (2 marks) What methods for stacks are used in this program?

(2b) (2 marks) When "java Test2014" is run, what does line 76 do?

(2c) (2 marks) What is `s` in line 4?

(2d) (2 marks) What does method `whatDoesThisDo` do?

(2e) (12%) Hand trace the program:

## Problem 3 (15 marks)

Consider the following java code:

```
class fct2014 {
    static void computeLoop(Integer q) {
        int sum=0;
        int n=100;
        for(int i=q;i<n & Math.abs(i)<=10;i=i*2) sum=sum+i;
        System.out.println("sum=" + sum + " for q=" + q);
    }

    public static void main(String[] args) {
        Integer p;
        p=new Integer(-2);
        computeLoop(p);
        p=new Integer(2);
        computeLoop(p);
        p=new Integer(-10);
        computeLoop(p);
        p=new Integer(10);
        computeLoop(p);
        p=new Integer(-100);
        computeLoop(p);
        p=new Integer(100);
        computeLoop(p);
        p=new Integer(0);
        computeLoop(p);
    }
}
```

1. (2%) What is `sum` for `p` being -2?
2. (2%) What is `sum` for `p` being 2?
3. (2%) What is `sum` for `p` being -10?

4. (2%) What is `sum` for `p` being 10?

5. (2%) What is `sum` for `p` being -100?

6. (2%) What is `sum` for `p` being 100?

7. (3%) What is `sum` for `p` being 0?



## Problem 4 (15 marks)

In each of the following situations, use big-O notation to express the amount of work being done in terms of  $n$ .

1. (2%) An element is inserted in an `ArrayStack` of size  $n$ , which had not reached full capacity.

**Answer:**

2. (2%) An element is inserted in a `LinkedList` of size  $n$

**Answer:**

3. (2%) We test whether a `LinkedList` of size  $n$  is empty using `isEmpty`

**Answer:**

4. (2%) An element is removed from a `LinkedList` of size  $n$

**Answer:**

5. (2%) We execute the following code segment

```
for (int i = 1; i < n; i++)
    for (int j = i; j <= i; j++)
        System.out.println(i+j);
```

**Answer:**

6. (3%) We execute the following code segment

```
int j = 1;
for (int i = 1; i < n; i++)
    j = j+1;
for (int i = 1; i < j; i++)
    System.out.println(i);
```

**Answer:**

7. (2%) We execute the following code segment

```
for (int i = 1; i < n*n+1000*n; i++)
    System.out.println(i);
```

**Answer:**

## Problem 5 (15 marks)

We use a stack to check whether an html file is well-formed. As input, we are given an array of `String`'s. Some of them are *tags*:

- A opening tag is a string of the form `<bla>`. The precise definition is that a string is an opening tag if and only if it has length at least 2, its first character is `<`, its last character is `>` and its second character is *not* `/`.
- A closing tag is a string of the form `</bla>`. Precisely, a string is a closing tag if and only if it has length at least 3, its first character is `<`, its second character is `/` and its last character is `>`.
- An opening tag such as `<bla>` and a closing tag such as `</bla>` are called a *match*.

If `s` is a string, `s.length()` gives its length and `s.charAt(i)` returns its *i*th character as a `char`. Calling `s.substring(i,j)` returns the substring starting at *i* and finishing at *j* − 1 (inclusive). For instance, if `s` is `<bla>`, `s.substring(1,4)` is `bla`.

Write the following methods:

1. (3%) `public static boolean isOpeningTag(String s)` that returns `true` if and only if `s` represents an opening tag.
2. (3%) `public static boolean isClosingTag(String s)` that returns `true` if and only if `s` represents a closing tag.

3. (4%) `public static boolean isMatch(String s, String t)` that returns `true` if and only if `s` is opening, `t` is closing and `s` and `t` are a match.

Now, we want to recognize whether a text is well-formed (all opening tags must be closed by a closing tag, forming a match). As input, we take an array of strings of length  $n$ , and we use the following algorithm. Create a stack of strings; for  $i = 0, \dots, n - 1$ , take the  $i$ th string from the array; call it `t`. If it is an opening tag, put it on the stack. If it is a closing tag, try to pop a string `s` from the stack (if the stack is empty, return `false`) and check whether `s,t` is a match; if true, continue, if not, return `false`. If `t` is neither an opening nor a closing tag, do nothing. If you finish the loop without exiting the method, return `true` if and only if the stack is empty.

(5%) Write a method `public static boolean check(String[] array)` that implements the algorithm above.

## Problem 6 (15 marks)

We consider two-dimensional arrays of `Integer`'s, such as for instance

1	3	7	4	0
9	9	3	1	2

These arrays will be represented by queues of `Integer`'s. The *row-major* representation stores one row after the other, so for our example it would be (1, 3, 7, 4, 0, 9, 9, 3, 1, 2), with 1 at the front and 2 at the rear. The *column-major* representation stores one column after the other, so in our example it would be (1, 9, 3, 9, 7, 3, 4, 1, 0, 2), with 1 at the front and 2 at the rear.

In this problem, you will write code to go from row-major to column-major (all the code should be written in the method `rowToColumn` that we give below). The input is the row-major queue, the number  $m$  of rows (2, in our example) and the number  $n$  of columns (5, in our example).

1. (2.5%) We give the code to create an array `queues` of queues of `Integer`'s of length  $n$ . Write a loop that initializes every queue in it.
2. (5%) write two nested loops (one of length  $m$ , one of length  $n$ ) that dequeue all elements from `rowMajor`, and enqueue them in `queues[0]`, ..., `queues[n-1]`, `queues[0]`, ..., `queues[n-1]`, ..., `queues[0]`, ..., `queues[n-1]`. In the previous example, they should enqueue 1 in `queues[0]`, then 3 in `queues[1]`, then 7 in `queues[2]`, then 4 in `queues[3]`, then 0 in `queues[4]`, then 9 in `queues[0]`, then 9 in `queues[1]`, then 3 in `queues[2]`, then 1 in `queues[3]`, then 2 in `queues[4]`. At the end, `rowMajor` is empty.
3. (2.5%) give the contents of all queues in the array `queues` at this stage, for our example (front on the left)
  - `queues[0]` =
  - `queues[1]` =
  - `queues[2]` =
  - `queues[3]` =
  - `queues[4]` =
4. (5%) write code that creates a new queue `columnMajor`, and uses two nested loops to dequeue all entries from `queues` and enqueue them in `columnMajor`. In our example, we would dequeue 1 from `queues[0]`, then 9 from `queues[0]`, then 3 from `queues[1]`, then 9 from `queues[1]`, then 7 from `queues[2]`, then 3 from `queues[2]`, then 4 from `queues[3]`, then 1 from `queues[3]`, then 0 from `queues[4]`, then 2 from `queues[4]`. Finally, add a `return` at the end.

```
public static LinkedList<Integer> rowToColumn(LinkedList<Integer> rowMajor, int m, int n){  
  
    LinkedList<Integer>[] queues = new LinkedList[n];
```

}

## Stacks and Queues Interfaces

```
public interface StackADT<T>{
    /** Adds one element to the top of this stack.
     * @param element element to be pushed onto stack */
    public void push (T element);

    /** Removes and returns the top element from this stack.
     * @return T element removed from the top of the stack */
    public T pop();

    /** Returns without removing the top element of this stack.
     * @return T element on top of the stack */
    public T peek();

    /** Returns true if this stack contains no elements.
     * @return boolean whether or not this stack is empty */
    public boolean isEmpty();

    /** Returns the number of elements in this stack.
     * @return int number of elements in this stack */
    public int size();

    /** Returns a string representation of this stack.
     * @return String representation of this stack */
    public String toString();
}
```

```

public interface QueueADT<T>{
    /**
     * Adds one element to the rear of this queue.
     * @param element the element to be added to the rear of this queue */
    public void enqueue (T element);

    /**
     * Removes and returns the element at the front of this queue.
     * @return the element at the front of this queue */
    public T dequeue();

    /**
     * Returns without removing the element at the front of this queue.
     * @return the first element in this queue */
    public T first();

    /**
     * Returns true if this queue contains no elements.
     * @return true if this queue is empty */
    public boolean isEmpty();

    /**
     * Returns the number of elements in this queue.
     * @return the integer representation of the size of this queue */
    public int size();

    /**
     * Returns a string representation of this queue
     * @return the string representation of this queue */
    Public String toString();
}

```

Rough work 1/4



Rough work 2/4

Rough work 3/4

Rough work 4/4