Chapter 4

multithread

benefits: 1) responsiveness 2) resource sharing

3) economy 4) scalability

parallelism: system can perform more than one task simultaneously



concurrency: support more than one task making progress

speed up in latency $(L_2, L_1) : \frac{L_1}{L_2}$.

speedup $\leq \frac{1}{S + \frac{(1-S)}{N}}$ S: serial (concurrency) portion N: core number

multithreading modes:

1) many-to-one: kernel is limiting parallelism

2) one-to-one: kernal may limit or run out of resource.

3) many-to-many: kernel needs to manage threads

asynchronous cancellation: terminates the target thread immediately

deferred cancellation: check periodically target thread should be terminate

Chapter 5

CPU-I/O Burst Cycle: process execution consist of a cycle of CPU execution and I/O wait

decision take place in:



preemptive vs nonpreemptive: a preemptive scheduling schene could terminate the process while running, and it might result in race condition

dispatch latency: time taken for stopping one process and start running another

Algorithm	schene	drawback
FCFS	non	convey effect: short processes stuck at the end of FCFS queue
LCFS	non	risk of starvation
SJF	non	unknown CPU burst time; risk of starvation

$$T_{n+1} = \underset{\text{usually } 1/2}{\alpha}\, \underset{\text{actual time}}{t_n} + (1-\alpha)\, \underset{\text{estimate time}}{T_n}$$

Round-Robin - preemptive if time quantum q is large, it is almost same as FCFS.

Priority - non risk of starvation