Caption Once, Ask Cheaply: What a Question-Blind Caption Index Buys a Video Reader

Anonymous ACL submission

Abstract

Captions written once per video window, without the questions, can serve as an index from which a cheaper text reader answers later questions. We ask when such an index lets a reader answer better than it does from the frames, why, and at what cost. The captioner sees exactly the reader's frames, which splits the effect of captions into source, visual budget, captioner and modality effects. On 297 TempCompass questions, with a pre-specified main test, a stronger captioner's captions raise a Claude Haiku reader's accuracy by 0.15 over Haiku's own captions of the same frames, by 0.08 at matched visual tokens, and by 0.06 within one model family at identical input; for an open-weights reader (Qwen2.5-VL-7B) the gain is 0.13. Turning frames into text does not help by itself: Haiku gains at most 0.09 from its own captions, and Claude Sonnet and Qwen lose 0.09 and 0.12. The index pays through the cheaper reader: Haiku on a stronger captioner's index costs 1/23 to 1/26 of Sonnet on frames per question, repays the captioning within 1.2–3.7 questions per video, and is 0–9 points less accurate. Question-blind captions lose the comparison between two copies of a clip shown at once, and the direction of reversed clips; 61–73% of wrong answers come from captions that do not decide the question.

1 Introduction

Many video question answering systems first caption the video and then reason over the text (Zhang et al., 2024; Wang et al., 2025; Zhang et al., 2026). When the captions are written once and reused for every later question, they act as an index: captioning is paid once, and each question costs only a text read. Recent work builds such indexes for long video (Cai et al., 2026; Liang et al., 2026; Chen et al., 2026). Two questions remain open. First, when a reader answers better from captions than from frames, the reason is unclear. The captioner may have seen more of the video, spent more visual tokens, or been a stronger model, or text may be easier for the reader than pixels. Second, whether the index pays depends on the full cost per question and on the one-time cost of captioning.

We hold the information fixed. The captioner receives exactly the frames the reader would see. A caption made from these frames cannot contain information about the video that the frames lack (Proposition 1), so an accuracy gain from captions is information that the reader can use more easily, not new information. Arms that change one thing at a time then split the effect of captions into four parts: the source the captioner sees (the video or the reader's frames), the visual tokens it spends, the captioner model, and the modality (a reader's own captions against its own frames). We use two model families: Claude Haiku and Sonnet read, and Haiku, Sonnet and Gemini caption. An open-weights model, Qwen2.5-VL-7B, reads the main arms and captions for itself. The data are 297 multiple-choice questions from TempCompass (Liu et al., 2024), on videos with a median length of 10 s. The main test was specified on a separate development set, before the test questions were run, and each follow-up was logged with a predicted value before it ran.

The captioner matters. With Haiku reading, Gemini's captions of the reader's frames beat Haiku's own captions of them by 0.15; at matched visual tokens the gain is 0.08, and Sonnet's captions of identical input give 0.06. The modality does not: Haiku is no more accurate on its own captions than on the frames they describe (+0.03, CI up to +0.09), and Sonnet is 0.09 less accurate on its own. Both results hold for an open-weights reader, Qwen2.5-VL-7B with greedy decoding: Sonnet's captions beat its own by 0.13, and its own cost it 0.12 against its frames. On Sonnet's captions both Claude readers score 0.71, so a question-blind caption bounds accuracy by what it contains, whatever

the reader. For one reader, Gemini's video captions save 18–30% per question against the frames. The saving that matters comes from switching to a cheaper reader: Haiku on a stronger captioner's index costs 1/23 to 1/26 of Sonnet on frames, and the index repays its captioning within 1.2–3.7 questions per video, at 0 to 9 points of accuracy. The losses are concentrated. When two copies of a clip play one above the other at different speeds, question-blind captions do not say which is faster, although the same model, shown the frames with the question, often answers correctly; on reversed clips they describe the forward event or do not state a direction.

Our contributions are:

1. A decomposition of the effect of captions into source, visual budget, captioner and modality effects, with arms that change one thing each, in two model families (§2.3).

2. A pre-specified test, a replication within one model family at identical input, and a replication with an open-weights reader. The captioner effect is positive, and the modality effect is at most +0.09 for a weak reader and negative for readers that see the frames better than their own captions hold (§4.1–4.2, §4.6).

3. A cost account per question, from input, output and thinking tokens at list price, and the break-even number of questions per video (§5).

4. An account of what question-blind captions lose, from minimal pairs, a question-aware control and an audit of wrong answers (§4.3–4.5).

The study is limited to short videos, multiple-choice questions and one benchmark.

2 Setup

2.1 Task and data

[Bullets.]

- **TempCompass** (Liu et al., 2024) multiple choice (CC BY-NC). Aspects: action, speed, direction, order, attribute change. Median video 10 s.

- **Development set:** 100 questions, used to set the hypotheses.

Arm: what the reader sees	Vis. tok./window
Question only: question and options	0
1 frame: the middle frame of each window	40
5 frames: all 5 frames of each window	200
5 frames, 448 px	720
Describe, then answer: 5 frames; one sentence per window, then the answer	200
Self-captions: the reader's own isolated caption of each window's 5 frames	— / 200
Sonnet captions: Sonnet's isolated caption of the same 5 frames	— / 200
Sonnet captions, 448 px: from the 448 px frames	— / 720
Sonnet whole-video captions: one caption of all of a video's frames	— / 200
Sonnet aspect-aware captions: the same, with one bullet naming the kinds of question	— / 200
Gemini frame-clip captions: the same 5 frames, played as a 1 fps clip	— / ≈ 280–330
Gemini frame captions: the same 5 frames, as images	— / ≈ 5,500
Gemini video captions: the video window	— / ≈ 330

Table 1: Arms. Visual tokens per 5 s window, for the reader / for the captioner.

- **Confirmatory set:** 300 questions sampled (60 per aspect, one per video, on videos the development set does not use), 297 after an amendment; pre-registered.

- **Video types:** plain (137), reversed (74), stacked (41), two-clip (45). They nearly determine the aspect. There are 156 clusters of videos that share a filmed clip.

- **Minimal pairs:** 193 confirmatory questions, each re-asked with the same wording on a sibling video whose correct option differs (107 reversal, 41 stacked, 45 two-clip). Chance pair accuracy is 0.093.

- **Windows:** 5 s; frames at 1 fps ($t = 5p + k$), 224 px long edge (40 Claude image tokens each). Videos are short: median 9.7 s, 1–7 windows (1: 16%, 2: 42%). One caption per video from the same frames does no better (§4.6); the per-window design is kept because it is what scales to long video.

2.2 Arms

- **Readers:** Claude Haiku 5.5 and Sonnet 5.5 (pinned IDs, effort medium), through `claude -p` with no tools, isolated per call. As an open-weights reader, Qwen2.5-VL-7B-Instruct (Bai et al., 2025) (float16, greedy decoding, on two T4 GPUs) reads the main arms (§4.6).

- **Captioners:** Haiku (self), Sonnet, Gemini 3.8 Flash, and Qwen for its own captions. Every caption is question-blind and window-isolated, and all use one prompt.

2.3 The four effects

- Sonnet − Gemini frame-clip captions is −0.017 [−0.071, +0.037]. At about equal visual tokens the two families' captioners are equally useful to Haiku.

- **Visual budget within Claude:** Sonnet's captions of 448 px frames − of 224 px frames, +0.003 [−0.037, +0.047]. Unlike Gemini's (+0.067), Claude's captioner gains nothing from 3.6× the visual tokens. The two budget changes differ in size (200 → 720 vs. ≈ 300 → 5,500), so say "in this range".

2.4 Statistics and pre-registration

- The main test was pre-registered: P1–P3 at 98.33% CIs (Bonferroni over three); secondary estimates at 95%.

- The follow-ups are exploratory. Each was logged with predictions before its first call, and each analysis was run once.

- Paired bootstrap over questions; clip-clustered bootstrap as a check.

- **Many exploratory terms** (≈ 30). The paper should say which were predicted directionally and report all of them in the appendix.

- [Wording depends on the pre-registration archive: "pre-specified and committed before each run; full history released".]

3 Theory

[Bullets.]

- **Proposition 1 (garbling bound).** A caption made from the reader's own frames cannot add information about the video, for an unbounded reader. For a fixed, bounded reader, it can add *usable* information (Xu et al., 2020), and that is what the captioner effect measures.

- **Retention**, (captions − question only) / (frames − question only), is the share of the frames' gain the index keeps. CIs are over clip clusters throughout. For Sonnet: Gemini video captions 0.98 [0.85, 1.13]; its own captions 0.77 [0.64, 0.90]. For Haiku, every index's point estimate exceeds 1 because Haiku on frames is below what the captions hold (§4.2). The CIs exclude 1 for every index but its own captions: self-captions 1.15 [0.91, 1.46]; Sonnet captions 1.47 [1.18, 1.95]; Gemini video captions 1.62 [1.33, 2.10]; Gemini frame captions 1.88 [1.53, 2.51]. The variants are in the appendix.

- **Corollary.** The total caption effect = source + captioner + modality, plus a visual budget term when the visual tokens differ.

- **Proposition 2 (break-even).** $Q^* = C(\tau)/(c_f - c_\tau)$: the captioning cost over the per-question saving. With a reader downgrade, c_τ is the cheap reader's cost.

- **Proposition 3 (price of being question-blind).** A question-aware description recovers what the question-blind caption omits (§4.5, claim of §4.3). [Prop. 4 in the plan; renumbered because the plan's Prop. 3 (routing headroom) is not used.]

- **Possible addition:** the cap of §4.2. The accuracy from a question-blind caption is bounded by what the caption holds, so readers above that bound lose and readers below it gain. This is informal; decide whether it needs a proposition.

4 Results

All results are on the 297 confirmatory questions, and no question is missing from any arm. P1–P3 were pre-registered and carry 98.33% CIs. Every other comparison is exploratory: it was written down with a predicted value before its first call, and its analysis was run once. These carry 95% paired bootstrap CIs over questions. "cl." marks a CI from resampling the 156 clusters of videos that share a filmed clip; the two kinds of CI agree throughout (Appendix D). Differences are in accuracy, so +0.064 is 6.4 points.

Table 3 lists every arm. Two rows anchor the rest. With the question and options alone, both readers score 0.41 (Haiku 0.411, Sonnet 0.414; difference +0.003 [−0.061, +0.064]), well above chance (≈ 0.30): the wording carries a strong prior, and the two readers share it. Given five frames per window, Sonnet scores 0.185 more than Haiku (0.798 vs. 0.613). Since the floor is shared, that

Effect	Arms compared	Claude chain	Gemini chain
Source	video captions − frame-clip captions	0 by design	+0.013 [−0.030, +0.061]
Visual budget	frame captions − frame-clip captions	0 by design (+0.003 at 448 px)	+0.067 [+0.030, +0.108]
Captioner	other captioner − self-captions, same pixels	+0.064 [+0.017, +0.111]	+0.081 [+0.030, +0.131]
Modality	self-captions − 5 frames	+0.030 [−0.034, +0.094] (P2)	(same)
Total	other captioner − 5 frames	+0.094 [+0.044, +0.148]	P3 + P2; frame captions: +0.178

Table 2: The four effects, with Haiku reading. Accuracy differences on 297 questions, 95% paired bootstrap CIs (P2 and P3: 98.33%).

whole gap comes from reading the input. Every index Haiku reads lands between these two points (0.643–0.791), and every index Sonnet reads lands below its frames (0.710–0.791).

4.1 Who writes the caption matters

Table 2 splits the caption effect into source, visual budget, captioner and modality effects. The pre-registered test is P3. With Haiku as the reader, Gemini's captions of exactly the reader's frames beat Haiku's own captions of them by +0.148 [+0.088, +0.209], 2.5× the predicted +0.06. The gain is positive in every aspect (+0.10 to +0.20) and in every video type (Appendix D).

P3 compares two captioners that spent different visual tokens on the same pixels. Gemini's image path encodes each 224 px frame at ≈ 1,100 tokens, ≈ 5,500 per window, against Haiku's 200. Captioning the same frames as a 1 fps clip through Gemini's video path (≈ 280–330 tokens per window, equal to the video arm's in 693 of 761 windows) splits P3 into two halves: a captioner effect at about matched visual tokens, +0.081 [+0.030, +0.131], cl. [+0.035, +0.125]; and a visual budget effect, +0.067 [+0.030, +0.108].

The source effect is near zero (+0.013 [−0.030, +0.061]): with captioner and visual tokens fixed, captions of the original video are no more useful than captions of the reader's 224 px frames. Gemini's video path reduces each frame to ≈ 66 tokens, so the source's resolution mostly does not reach the captioner. All four predictions for this split were within 0.02 of the results.

Within one model family, the match is exact. Sonnet captions the same five JPEGs per window, with the same prompt and effort as Haiku's self-captions. Every Claude model counts image tokens by the same rule, and Sonnet's caption calls took exactly 2 more input tokens than Haiku's in every window (876). Only the captioning model differs. Haiku reads Sonnet's captions more accurately than its own: **+0.064 [+0.017, +0.111]**, cl. [+0.011, +0.119]. The predicted +0.09 lies inside the CI. At about equal visual tokens, the two families' captioners are equally useful to Haiku (Sonnet − Gemini frame-clip captions, −0.017 [−0.071, +0.037]). On minimal pairs (§4.3), where a guess cannot score, the captioner effect is +0.104 [+0.017, +0.190] in pair accuracy. With an open-weights reader the effect is larger: Qwen reads Sonnet's captions of the same frames +0.125 [+0.074, +0.175], cl. [+0.070, +0.182], more accurately than its own (§4.6).

Unlike Gemini, Claude's captioner gains nothing from a larger visual budget in the range we tested. Sonnet's captions of 448 px frames (up to 720 visual tokens per window, 3.6× as many) are no more useful to Haiku than its captions of the 224 px frames: +0.003 [−0.037, +0.047], against a predicted +0.03. With power ≈ 0.25 for +0.03, this is weak evidence against a small effect, but the CI rules out more than about +0.045. The two budget changes also differ in size (200 → 720 tokens here, ≈ 300 → 5,500 for Gemini).

4.2 Text itself is not easier for the reader

The modality effect asks whether a reader does better on its own words than on the pixels they came from. For Haiku this is the pre-registered P2: self-captions − 5 frames = +0.030 [−0.034, +0.094]. Both the prediction (−0.08) and any gain above +0.09 lie outside the CI; IsoBench (Fu et al., 2024), by contrast, finds 15–29 points for exact text renderings of images. For Sonnet, its own captions cost accuracy: −0.088 [−0.135, −0.044], cl. [−0.140, −0.036], and −0.067 [−0.114, −0.024] when it captions the 448 px frames. The open 7B reader follows Sonnet, not Haiku: Qwen's own captions cost it −0.121 [−0.172, −0.071], cl. [−0.170, −0.074], because it reads frames better than Haiku (0.657 vs. 0.613) and captions worse than any other captioner (§4.6). The modality effect changes sign with the reader's strength on frames relative to its own captions, not with model size.

Reader, input	Acc.	In tok.	$/q	Index
H, question only	0.411	1,025	1.09	—
H, 1 frame	0.582	1,189	1.46	—
H, 5 frames	0.613	1,520	2.04	—
H, 5 frames 448 px	0.650	2,676	3.39	—
H, describe, answer	0.684	1,579	4.15	—
H, self-captions	0.643	1,283	1.89	0.58
H, Sonnet capt.	0.707	1,280	1.81	9.10
H, Gem. frame-clip	0.724	1,232	1.67	7.60
H, Gem. frame	0.791	1,229	1.67	14.61
H, Gem. video	0.737	1,236	1.68	7.26
H, Sonnet 448 px	0.710	1,279	1.80	11.67
H, Sonnet whole-video	0.721	1,194	1.56	4.92
H, Sonnet aspect-aware	0.747	1,213	1.62	5.27
S, question only	0.414	1,027	21.82	—
S, 5 frames	0.798	1,522	41.12	—
S, Sonnet capt.	0.710	1,282	30.89	9.10
S, Sonnet 448 px	0.731	1,281	31.03	11.67
S, Sonnet whole-video	0.721	1,196	28.49	4.92
S, Sonnet aspect-aware	0.761	1,215	28.97	5.27
S, Gem. video	0.791	1,238	28.68	7.26
Q, question only	0.397	121	—	—
Q, 5 frames	0.657	529	—	—
Q, Qwen capt.	0.535	268	—	—
Q, Sonnet capt.	0.660	295	—	9.10
Q, Gem. video	0.697	264	—	7.26

Table 3: Accuracy and list-price cost per question (297 questions; H = Haiku, S = Sonnet, Q = Qwen reading). Qwen runs on a free GPU, so it has no price; its input tokens have no CLI system prompt. Input tokens are the median per question and include the fixed reader prompt ($\approx$ 1,025 tokens). $/q is list-price dollars per question $\times 10^4$, including output and thinking tokens. Index is the one-time captioning cost in dollars per video $\times 10^3$, averaged over videos (§5).




Figure 1: Accuracy by reader for the question alone, 5 frames, and the two indexes both readers read. 95% CIs over clip clusters. The frames line crosses both index lines.

Figure 1 shows why. From Haiku to Sonnet, accuracy on frames rises from 0.613 to 0.798, while accuracy on Sonnet's captions stays flat (0.707 $\rightarrow$ 0.710; paired difference -0.003 [-0.047, +0.040]). Once the video is in these captions, a reader that costs 17$\times$ less per question loses nothing, and a stronger reader gains nothing. We read this as a cap: a question-blind caption bounds any reader's accuracy by what the caption holds. Haiku on frames is below the cap of Sonnet's captions and gains from them; Sonnet is above it and loses. A 7B open reader reaches the cap only at the edge: Qwen on Sonnet's captions scores 0.660, -0.047 [-0.094, +0.000] below Haiku, level on plain and reversed videos but -0.29 on two-clip and -0.17 on stacked ones, where the answer combines windows or the two copies. The cap depends on the index. Sonnet reads Gemini's video captions better than its own (0.791 vs. 0.710, +0.081 [+0.034, +0.128]), and keeps 0.98, cl. [0.85, 1.13], of its frames' gain over the question alone on them, against 0.77, cl. [0.64, 0.90], on its own captions (retention, §3). This pattern was not predicted, and it is exploratory.

Haiku's advantage on captions does not come from starving the frames. At 448 px, Haiku's frames take 2,676 input tokens per question, 1.76$\times$ the 224 px arm, and gain +0.037 [-0.010, +0.084]. Captions at $\approx$ 1,280 input tokens still beat them: Gemini frame captions by +0.141 [+0.088, +0.195], Gemini video captions by +0.088 [+0.037, +0.138], and Sonnet captions by +0.057 [+0.003, +0.111]. The advantage sits on two-clip videos (+0.31 to +0.38), and for Gemini frame captions also on plain and reversed ones. On stacked videos, every caption arm is within $\pm$0.07 of the 448 px frames.

4.3 Where captions lose: video types and minimal pairs

TempCompass builds most of its videos to defeat single-frame and wording shortcuts (§2.1): reversed clips, stacked copies of one clip at two speeds, and two clips in sequence or side by side. Built videos are 54% of the confirmatory set. The video type nearly determines the aspect (every stacked question is about speed, and every two-clip question about order), so we report by type. Figure 2 shows accuracy by type. On plain videos, the five arms lie within 0.09 of each other (0.80–0.89). They separate on the built videos.

Accuracy on one video cannot tell a representation that lost the fact from a reader that guessed. Minimal pairs can. Each of 193 confirmatory ques-




Figure 2: Accuracy by video type for five arms (297 questions; n per type in brackets).

Arm	All	Rev. (107)	Stack. (41)	2-clip (45)	Same ans.
H, 5 frames	0.233	0.28	0.17	0.18	0.54
H, self-captions	0.326	0.33	0.10	0.53	0.42
H, Sonnet capt.	0.430	0.38	0.17	0.78	0.43
H, Gem. video	0.482	0.47	0.20	0.78	0.37
S, 5 frames	0.606	0.56	0.51	0.80	0.28
S, Sonnet capt.	0.430	0.40	0.10	0.80	0.39

Table 4: Minimal pairs: pair accuracy by group, and the share of pairs with the same answer on both videos. Chance pair accuracy is 0.093.

tions is asked again, with the same wording and option order, on a sibling video built from the same filmed clip whose correct option differs: the plain and the reversed version of a clip (107 pairs); another stacked version at other speeds (41); another arrangement of the same two clips (45). An arm that does not receive the fact gives the same answer on both videos, and gets at most one of them right. Table 4 reports pair accuracy, the share of pairs answered correctly on both sides (chance 0.093), and the same-answer rate.

Two-clip: captions help a weak reader. From frames, Haiku must keep about ten small frames from two clips apart, and on two-clip pairs it is near chance (0.18). Its own captions raise pair accuracy to 0.53, a modality effect of +0.36 [+0.16, +0.56]; in accuracy, the modality effect on two-clip videos is +0.22 [+0.10, +0.35] (cl.). Sonnet's captions raise Haiku's accuracy over its frames by +0.33 [+0.20, +0.48] (cl.). Both directions were predicted. The mechanism is open. When Haiku describes each window before answering, in the same call, it gains only +0.09 [−0.06, +0.24] on two-clip videos, and stays below its self-captions (−0.13 [−0.30, +0.02]). This leans toward the separate caption call per window as the cause, without showing it.

Stacked: question-blind captions drop the comparison. A stacked video shows one clip twice, one copy above the other, at the same or different speeds, and the question asks which copy is faster. Sonnet on frames answers 0.51 of stacked pairs correctly on both sides. Every caption arm scores 0.10–0.20, near pair chance, and that includes Sonnet reading its own captions (0.10). Sonnet's pair accuracy on its own captions is 0.41 below its frames ([−0.62, −0.23]), and Haiku on Sonnet's captions is 0.34 below Sonnet on frames ([−0.60, −0.08]). Three of the four caption arms give the same answer on both videos of a pair more often than Sonnet on frames does (for example, Haiku on Sonnet captions +0.32 [+0.07, +0.55]). The captions do not say how the copies differ. For a man jumping rope in two copies (answer: the man above is faster), Gemini writes "An athletic man … jumps rope in a split-screen video", and Haiku's own captions describe one woman skipping rope. Sonnet sees the difference when it looks with the question in view, and loses it when it writes without the question. So the loss lies in what a question-blind captioner chooses to write.

Reversed: captions narrate forward, or do not commit. On reversed videos, the question alone points to the forward event: both readers score below chance on it (Haiku 0.16, Sonnet 0.18). Sonnet reading the frames recovers part of the reversal (0.64), but its question-blind captions carry little of it. Haiku on Sonnet's captions trails Sonnet on frames by −0.19 [−0.32, −0.07] (cl.), and Sonnet on its own captions trails its frames by −0.18 [−0.30, −0.05] (cl.). A stronger captioner does not help here. Sonnet's captions report reversals no more often than Haiku's (+0.01 [−0.08, +0.10] on reversed videos; +0.06 [−0.01, +0.13] on reversal pairs, where a positive effect was predicted). Gemini's captions do report them more often (+0.14 [+0.04, +0.24] on reversed videos). When a reader misses the reversal, it falls back to the prior. Among Sonnet's wrong answers on reversed videos, the share equal to its question-only answer is 0.59 with frames (27 wrong) and 0.65 with its own captions (40), against 0.43 if errors were uniform; for Haiku it is 0.67 with frames and 0.55 with self-captions. For a pile of salt played backwards (answer: shrinking), all five of Gemini's video captions describe salt pouring onto the pile, and Haiku's own captions say it "grows taller".

Reader arm	Reader err.	Misstat.	Omission	n
H, self-captions	0.08	0.28	0.63	106
H, Sonnet capt.	0.13	0.26	0.61	87
H, Gem. frame-clip	0.17	0.15	0.68	82
H, Gem. frame	0.10	0.18	0.73	62
H, Gem. video	0.10	0.21	0.69	78
S, Gem. video	0.05	0.24	0.71	62
S, Sonnet capt.	0.08	0.26	0.66	86

Table 5: Caption audit: share of each reader arm's wrong answers by the judge's label of the captions. Reader error = the captions state the correct option; misstatement = a wrong option; omission = neither. n = wrong answers.

4.4 Why caption arms fail: an audit

For every wrong answer from captions in seven reader arms (442 items), a judge (Sonnet) saw the captions, the question, the options and the correct answer. It labelled the captions as stating the correct option (so the error is the reader's), stating a wrong option (a misstatement), or deciding neither (an omission), and quoted the caption as evidence (prompt in Appendix A). Table 5 gives each label's share of each arm's wrong answers.

Omission dominates: 0.61–0.73 of every arm's wrong answers come from captions that do not decide the question. Misstatements are 0.15–0.28, and reader errors only 0.05–0.17, below the predicted 0.15–0.25. Once a fact is missing from the index, no reader can recover it; this is the cap of §4.2. By video type, the stacked prediction held: in every arm, 0.93–1.00 of stacked failures are omissions (predicted ≥ 0.70). The reversed prediction failed. Misstatement, that is forward narration, is 0.28–0.45 of reversed failures, below the predicted ≥ 0.50, and omission is 0.45–0.62. On reversed videos, captions narrate the forward event or do not commit to a direction.

The judge also wrote one of the caption sets it labels. As a check, one author labelled 40 items, stratified by the judge's label and blind to it. Agreement is 0.88, $\kappa = 0.81$ [0.64, 0.96], above the threshold of 0.6 set in advance, below which only the hand-labelled sample would have been reported. The judge agrees on all 22 items the author labelled "correct" or "wrong". All 5 disagreements are items the author left "silent" and the judge decided, so if anything Table 5 undercounts omission.

By video type (Appendix D): two-clip failures are few (1–8 per arm) and mostly reader errors, where the captions state the order and the reader still answers wrongly. Plain failures are 0.60–0.80 omission.

4.5 From question-blind to question-aware

Two arms move the captioner toward the question. Neither changes the confirmatory captioner prompt.

Describe, then answer. Haiku sees the 5 frames per window and the question, writes one sentence per window, and then answers, all in one call. It scores 0.684, +0.071 over the frames arm, cl. [+0.029, +0.114] (predicted +0.03). The gain is on reversed and stacked videos (+0.12 each). On stacked videos, this question-aware description beats the question-blind self-captions by **+0.22 [+0.09, +0.37]**. So the stacked loss is an omission caused by not seeing the question, not a limit of text (Proposition 3). This arm is not an index: it reads the frames at every question, and it costs 2× the frames arm per question ($0.000415 vs. $0.000204), mostly in thinking tokens.

Telling the captioner the kinds of question. Between question-blind and question-aware sits a task-aware index. Sonnet's whole-video captions (§4.6) get one added prompt bullet that names the five kinds of question to come (actions, speed, direction, order, attribute changes), but not how the benchmark builds its videos. Sonnet reading these captions gains +0.040 [+0.003, +0.081], cl. [+0.000, +0.081], over the whole-video captions, and Haiku +0.027 [−0.013, +0.067]; both match the predicted +0.03. This halves Sonnet's gap to its own frames (−0.077 → −0.037 [−0.081, +0.007]). It does not fix the stacked comparison. Against the per-window captions, Sonnet's stacked accuracy is unchanged (0.39 vs. 0.39), and Sonnet on frames stays 0.27 ahead. Mentions of reversal did not rise (4 of 74 reversed videos, against 6 without the bullet). The captions are 15% longer at the same length limit, so part of the gain may come from more words rather than the right words. Knowing the task buys a little; the stacked comparison needs the question itself (§7.1).

4.6 Robustness checks and nulls

An open-weights reader. The Claude readers run through a CLI, with its system prompt and no control of temperature. Qwen2.5-VL-7B-Instruct, with greedy decoding and the same reader prompts, reads eight arms on the 297 questions and captions every window from exactly the 5 frames, with the same caption prompt. Unparsed answers (49

of 2,376, all refusals) count as wrong; dropping them moves every term by 0.02 or less. Qwen uses the frames: they add +0.26 over the question alone (Haiku +0.20), and it beats Haiku on them (0.657 vs. 0.613). Its own captions are the weakest in the study, worse for it than Haiku's (-0.067 [-0.114, -0.020]), and lose most on reversed (0.26) and stacked (0.24) videos. The captioner effect replicates and is larger than for Haiku: Sonnet's captions of the same frames +0.125, cl. [+0.070, +0.182]; Gemini frame-clip captions +0.152 [+0.098, +0.205]. There is again no gain from the modality alone, but a cost, as for Sonnet: -0.121. On Sonnet's captions Qwen keeps all its frames' gain (retention 1.01, cl. [0.85, 1.20]), against 0.53 [0.34, 0.70] on its own. The predictions, made as if Qwen were a weaker Haiku, got the sign of the modality effect wrong (predicted -0.01) and overestimated the gain of Gemini's video captions over the frames (+0.040 [-0.010, +0.091], predicted +0.12). A reader that reads frames well gains less from any index.

Window length. Our videos are short (median 9.7 s; 58% have one or two windows), so we checked the per-window design against one Sonnet caption per video, from the same frames, with the length limit summed over the windows. Whole-video captions are no better: +0.013 [-0.027, +0.057] with Haiku reading, and +0.010 [-0.030, +0.051] with Sonnet (predicted +0.00 and +0.01). Splitting into 5 s windows thus costs at most $\approx$ 0.05–0.06, and helps by at most ≈ 0.03. On one-window videos, where the two captioning calls are identical, the difference is ≈ 0 for both readers (+0.02 and -0.02), as it should be. One by-type pattern was not predicted: Haiku gains +0.12 [+0.03, +0.23] on reversed videos from whole-video captions, while stacked videos lean the other way for both readers (-0.07 and -0.12; CIs include 0). The whole-video index costs about half as much (§5).

Resampling noise. On the 48 one-window videos, the captioning call is identical in both arms. None of the 48 caption pairs is identical, and the reader's answer changes on 10% (Haiku) to 17% (Sonnet) of those questions. That is as often as removing the split changes it on videos with two or more windows (17%). Per question, a caption is one sample, so comparisons between caption arms need many questions. The by-type terms above (41–137 questions per type) are noisy for that reason.




Figure 3: Accuracy against list-price $ per question (log scale), one point per arm, with the index cost spread over Q = 1, 10 and infinitely many questions per video. Circles are frame arms, and squares are index arms. The 448 px caption, whole-video and aspect-aware variants are in Table 3 only.

Aspects (P1, null). The pre-registered aspect contrast, that captions lose direction and speed but keep the discrete aspects, did not pass: -0.101 [-0.231, +0.028] for Sonnet, half the predicted -0.20. Speed is the only aspect where captions lose consistently (-0.10 for Sonnet). Aspect nearly coincides with video type, so the by-aspect tables are in Appendix D.

Thinking (not predicted). At effort medium, the model decides per call whether to think, so thinking is observed, not set. On Gemini's captions, thinking marks wrong answers: accuracy is 0.84–0.90 on calls without thinking and 0.62–0.65 on calls with it. For Haiku on frames it does not (0.61 both ways). Sonnet thinks 3.3$\times$ less on captions than on frames.

5 Cost and break-even

Accounting. We price every call at list price. Claude Haiku 5.5 costs \$0.10 / \$0.50 and Sonnet 5.5 \$2 / \$10 per million input / output tokens, with thinking billed as output; computed from the logged tokens, this equals the CLI's reported cost on every call. Gemini captioning is priced at \$0.50 / \$3.00, thinking included. A reader's cost per question, c, is the mean over the 297 questions. The index cost of a video, $C(\tau)$, is the cost of captioning all its windows once. By Proposition 2, an index τ that a reader answers from at c_τ per question repays its captioning, against a frame arm at c_f, after $Q^* = C(\tau)/(c_f - c_\tau)$ questions per video. CIs on Q^* resample questions, and so videos, since each video has one question.

For one reader, the index saves little. Against 5 frames, Gemini video captions save 18% per

question for Haiku and 30% for Sonnet. The fixed reader prompt (≈ 1,025 tokens) dominates the input: captions cut the video-content tokens to 43% of the frames', but the input tokens only to 81%. Sonnet also thinks 3.3× less on captions. So for one reader the index repays slowly. Sonnet on Gemini video captions repays after $Q^* = 5.8$ [5.2, 6.5], at equal accuracy (−0.007 [−0.054, +0.040]). Sonnet on its own captions repays after 8.9 [7.8, 10.2], at −0.088. Haiku on Gemini video captions repays only after 202 [156, 279], though it is also 0.125 more accurate than on its frames. Haiku on Sonnet captions is +0.057 more accurate than Haiku on 448 px frames and cheaper per question, and repays after 57.5 [53.3, 62.1].

The reader downgrade is what pays. Per question, Haiku on any index written by a stronger captioner costs 1/23 to 1/26 of Sonnet on frames (Table 3). The index then repays its captioning within 1.2–3.7 questions per video (Table 6). At Q = 10 questions per video (Figure 3, middle), every index Haiku reads costs less than half of Sonnet on frames, captioning included. What the downgrade costs in accuracy depends on the index:

- **Gemini frame captions** let Haiku match Sonnet on frames (−0.007 [−0.057, +0.044]). They are the most expensive index ($0.0146 per video), because Gemini's image path spends ≈ 5,500 visual tokens per window.
- **The Claude chain**, where Sonnet captions once and Haiku answers, is at −0.091 [−0.145, −0.040], with $Q^* = 2.3$.
- **One caption per video** instead of one per window halves the index cost ($0.0049 vs. $0.0091 per video) at the same accuracy (§4.6), and Q^* falls to 1.2.
- **Aspect-aware captions** (§4.5) bring the Claude chain to −0.051 [−0.104, +0.000] at $Q^* = 1.3$.

In short, a caption index trades 0–9 points of accuracy against the strong reader on frames for a 23–26× cheaper query, and repays itself within 1.2–3.7 questions per video.

Other costs. Latency does not favour captions: the median call on captions is 0.1–1.1 s slower than on frames with the same reader (CLI wall clock with start-up, not controlled for time of day). Thinking is 2–5% of reader tokens.

Index	Q^*	Acc. difference
Gemini video captions	1.8 [1.7, 2.0]	−0.061 [−0.111, −0.010]
Gemini frame-clip captions	1.9 [1.8, 2.1]	−0.074 [−0.125, −0.024]
Sonnet captions	2.3 [2.2, 2.4]	−0.091 [−0.145, −0.040]
Sonnet captions, 448 px	3.0 [2.8, 3.1]	−0.088 [−0.138, −0.037]
Sonnet whole-video	1.2 [1.2, 1.3]	−0.077 [−0.128, −0.027]
Sonnet aspect-aware	1.3 [1.3, 1.4]	−0.051 [−0.104, +0.000]
Gemini frame captions	3.7 [3.5, 4.0]	−0.007 [−0.057, +0.044]

Table 6: Reader downgrade: Haiku on an index against Sonnet on 5 frames. Q^* is the number of questions per video after which the index costs less in total (95% CI over questions).

6 Related work

[Bullets; literature pass done, no scoop found.]

- Caption-then-reason for video QA: LLoVi (Zhang et al., 2024) (the captioner matters: oracle captions +10.8), VideoTree (Wang et al., 2025), SiLVR (Zhang et al., 2026), Vamos (Wang et al., 2024) (text competitive with visual embeddings).
- Caption indexes and memories: CFD (Cai et al., 2026), CapMem (Liang et al., 2026), Sprout (Chen et al., 2026), VidCtx (Goulas et al., 2025) (question-aware captions +1–2 points; compare with the stacked +0.22).
- **A captioner in front of a fixed reader:** Prism (Qiao et al., 2024) (images; a 2B captioner + GPT-3.5 ≈ 10× larger VLMs), MetaCaptioner (Lei et al., 2025), CapRL (Xing et al., 2025) (caption utility as the RL reward). None has a self-caption control, matched visual tokens, or the reader's own view of the frames.
- Text vs. pixels for the same content: IsoBench (Fu et al., 2024) (text +15–29 points when the text is exact), TokenSwap (Hua et al., 2026). Our modality effect is ≤ +0.09, and negative for the strong reader.
- **A model reading its own description (images only):** Caption This, Reason That (Weng et al., 2025): own captions instead of the image give a weak 7B model +22 to +29 on synthetic location tasks, and GPT-4o +8 (not significant). GEASS (Li and Zhang, 2026): the model's own caption added to the image costs ≈ 10 points on HallusionBench. Seeing and Solving (Wang et al., 2026a): two-pass extract→solve beats direct answering on

charts, but a one-call "state first" prompt does not. Our framing: the sign depends on where the reader stands relative to what the question-blind caption holds.

- Minimal pairs as a design: TempCompass's conflicting videos (Liu et al., 2024), MotionBlind (Bhatia et al., 2026), TimeBlind **[PENDING: citation]**. We apply the pairs to representations, not to models.

- Motion and reversal from pixels: Lee et al. (2026), MotionBlind, Seeing the Arrow of Time (Xue et al., 2025), and Rahman (2026). Video models often fail direction, speed and reversal from frames too, which fits P1's null.

- Cost: no paper solves for break-even with a reader downgrade. Related: SAFE-Cascade (Dwivedi et al., 2026) (per-question routing), Sprout (lazy memory), MIT³ (Zhao et al., 2026) (parametric memory), Industrial ReMEmbR (Yammine et al., 2026) (caches vision tokens instead of captioning at write time). Accuracy–cost evaluation: Kapoor et al. (2024), FrugalGPT (Chen et al., 2023).

- Visual token budgets: LoHi (Dong et al., 2026), VEI (Guan et al., 2026).

- Caption utility judged by QA: CaptionQA (Yang et al., 2026), CapQuiz (Wang et al., 2026b), ViSIL (han Li et al., 2026).

- Temporal benchmarks: TempCompass, plus T3 (Li et al., 2024). Reversed-video shortcuts and the forward prior **[PENDING: citation]**.

7 Discussion: why a caption index is hard to beat and hard to evaluate

[Skeleton (bullets).]

A caption is a question-blind summary shaped by the captioner's prior. Its value lies in where the video departs from that prior, and those departures are what captioners write least, what similarity metrics detect least, and the only places where baselines fail.

7.1 What the benchmark tests when the captioner is also misled

- **The concern:** TempCompass's manipulated videos mislead models. The captioner is a model, so a low score may only mean that the captioner was fooled.

- **Answer:** the system under test is the whole index: a model writes once without the question, and the reader answers later. A captioner that can be misled is part of that system, not a confound. The arms separate the two causes, because the same model also reads the same pixels with the question in view.

- **Table 7** (descriptive; Sonnet as captioner and reader): perception shortfall = 1 − frames (the model fails even when it sees the question); index loss = frames − own captions (it saw the answer when asked but did not write it down blind); retention as in §3.

- **Reading:** on natural video (plain), the index keeps almost everything (0.95); the index loss is ≈ 0 on plain and two-clip videos, and its CIs exclude 0 only on reversed and stacked. On reversed videos, the model is misled even when it looks with the question in view (0.36 shortfall); writing blind loses another 0.18. On stacked videos, the model can see the comparison when asked (0.66), but blind captions keep little of it (0.21; the CI is wide). This is the price of being question-blind (Proposition 3).

- **Haiku version** (appendix table): the index loss is negative overall, -0.09 $[-0.15, -0.04]$, so the captions beat Haiku's own frames, mostly on two-clip videos (-0.33 $[-0.48, -0.20]$). Haiku's perception shortfall is 0.39 overall and ≈ 0.6 on reversed and stacked.

- **The captioner prompt is not changed.** A prompt that names the benchmark's tricks tells the index the test, and any gain from it would not generalize. The task-aware prompt (§4.5) is the middle point: question-blind → task-aware → question-aware is a gradient, and stacked sits at its far end.

7.2 Why the baselines are hard to beat

- **The prior is strong:** the question alone scores 0.41 for both readers; 0.61 on plain videos.

- **Errors fall back to the prior:** on reversed videos, Sonnet's wrong answers equal its question-only answer 0.59–0.74 of the time, across frames and caption arms (uniform

Type (n)	Question only	Frames	Own captions	Perception shortfall	Index loss	Retention
plain (137)	0.61	0.89	0.88	0.11 [0.06, 0.16]	+0.01 [−0.03, +0.06]	0.95 [0.79, 1.12]
two-clip (45)	0.29	0.91	0.91	0.09 [0.02, 0.17]	+0.00 [−0.07, +0.06]	1.00 [0.91, 1.12]
reversed (74)	0.18	0.64	0.46	0.36 [0.25, 0.48]	**+0.18** [+0.05, +0.30]	0.62 [0.35, 0.88]
stacked (41)	0.32	0.66	0.39	0.34 [0.17, 0.51]	**+0.27** [+0.09, +0.47]	0.21 [−0.27, 0.67]
all (297)	0.41	0.80	0.71	0.20 [0.15, 0.26]	+0.09 [+0.04, +0.14]	0.77 [0.64, 0.90]

Table 7: Where Sonnet's headroom goes, by video type (Sonnet as captioner and reader; 95% CIs over clip clusters).

0.43). The caption helps only where it contradicts the prior, and blind captioners rarely write that.

- **Omission dominates:** 0.61–0.73 of wrong answers on captions come from captions that are silent on the question.
- **More pixels do not help the Claude captioner:** +0.003 at 3.6× the visual tokens. The loss is in what gets written, not in what is seen.
- **The value depends on the reader** (Figure 1): the same index helps Haiku (retention 1.47 [1.18, 1.95]) and hurts Sonnet (0.77 [0.64, 0.90]). Whether an index "beats the baseline" depends on which reader the baseline uses.
- **Reconstruction phase:** continuity baselines were as strong as the models. An 8B LLM in-filling masked captions lost to copying the nearest caption. On forced-choice recognition (160 items), Haiku from captions was level with caption copy (51.2% vs. 45.6%), and frame copy (87.5%) was level with Opus (85.0%). [Decide whether this phase is in the paper.]

7.3 Why caption utility is hard to evaluate

- **No question-free reference:** a caption is right or wrong only relative to a question. The same caption is complete for "what happens" and silent for "which copy is faster".
- **Similarity metrics track style:** in the reconstruction phase, cosine similarity correlated with caption repetitiveness (Spearman ρ = +0.61), and per-second and order-free scoring gave opposite headlines.
- **"Silent" and "wrong" overlap:** the judge found forward narration in only 0.28–0.45 of reversed failures; a caption that never states a direction is consistent with both readings. All 5 judge/hand disagreements are captions the author left "silent" and the judge decided. The hard items fall into four kinds: a static description that fits a wrong option; a near-synonym of an option; a 1 s last window that contradicts the long first one; and an answer that needs knowledge of the task (debris "tumbling upward" means "rebuilding" only to a reader who knows clips may be reversed).
- **One caption is one sample:** re-captioning with identical input never gave the same caption (0 of 48), and answers changed on 10–17% of those questions. Only averages over many questions are stable.
- **The judge shares a family with the captioner:** κ against the hand labels is the check: 0.81.

7.4 What made it measurable

- Utility through a fixed reader on multiple-choice questions, not similarity to a reference caption.
- Controls: the self-caption control, the reader's own view of the frames, and question only. Without them, a "caption effect" mixes captioner, modality and prior.
- Minimal pairs: chance pair accuracy is 0.093, and a reader that falls back to the prior scores 0 on a pair.
- Reporting by video type: the overall number hides that the loss is concentrated in two types (Table 7).
- Many questions per comparison, because of resampling noise (§4.6).

8 Conclusion

[PENDING: not drafted]

Limitations

- One benchmark; short clips; multiple choice only.
- Closed readers run through a CLI: its system prompt is included, and there is no temperature control. Mitigations: pinned IDs, isolation checked on every call, released outputs, and an open-weights reader with greedy decoding that replicates the captioner and modality results (§4.6). It is one 7B model, and it runs with its own default system prompt.
- Claude reading Claude. Mitigations: the Gemini chain and the Qwen reader.
- Development → confirmatory drop of Haiku on frames (0.70 → 0.61); about half of it is the mix of video types.
- Questions share filmed clips. Mitigation: clustered CIs.
- Thinking is decided per call by the model (effort medium), so it is observed, not controlled.
- Question-blind captions drop what the question needs and the captioner did not think to say (stacked comparisons, reversals). This is a limit of question-blind indexes, not only of our captioners.
- Most claims beyond P1–P3 are exploratory, even though each was predicted in writing before its run (the cap was not predicted).
- The audit's judge (Sonnet) also wrote one of the caption sets it judges. Mitigation: the 40 hand labels and κ.
- 54% of the confirmatory videos are manipulated (reversed, stacked, two-clip), so overall accuracies mix natural video with stress tests; plain videos are reported separately (Table 7).

References

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, and 8 others. 2025. Qwen2.5-VL Technical Report. *Preprint*, arXiv:2502.13923.

Dhairya Bhatia, Bishoy Galoaa, Oliver Fritsche, Shahid Kamal, Muhammad Obaidullah Abdul Salam, Umer Saleem, Om Rastogi, Frania Felix Chettiar, Nesli Erdogmus, and Sarah Ostadabbas. 2026. Motion-Blind: Probing the Illusion of Motion Understanding in Video-LLMs. *Preprint*, arXiv:2609.09528.

Weitong Cai, Hang Zhang, Yukai Huang, Yiqiao Xie, Shan Gao, Jiankang Deng, Songcen Xu, Jifei Song, and Zhensong Zhang. 2026. Caption-once, Frames-on-Demand: Visual-Need Routing for Budget-Aware Agentic Long Video Understanding. *Preprint*, arXiv:2609.11899.

Lingjiao Chen, Matei Zaharia, and James Zou. 2023. FrugalGPT: How to Use Large Language Models While Reducing Cost and Improving Performance. *Preprint*, arXiv:2305.05176.

Wei Chen, Xuanyu Zheng, Yancheng Long, Haoyang Xu, Kaiyu Jiang, Bin Wen, Tingting Gao, Han Li, and Long Chen. 2026. Sprout: Building Dynamic Memory While Reasoning for Agentic Video Understanding. *Preprint*, arXiv:2609.35497.

Sixun Dong, Wei Li, Andong Deng, Qi Qian, Victor Zhu, Zhengping Ji, and Chen Chen. 2026. Rethinking Long-Video Efficiency: A Joint Allocation Perspective on Frames, Pixels, and Front-End Latency. *Preprint*, arXiv:2610.04318.

Ayush Dwivedi, Qixin Wang, Ashvi Soni, Ruoteng Wang, Han Li, Animesh Mahapatra, Neeraj Agrawal, and Xintao Wu. 2026. SAFE-Cascade: Cost-Adaptive Vision-Language Routing for Chart Question Answering. *Preprint*, arXiv:2606.19646.

Deqing Fu, Ruohao Guo, Ghazal Khalighinejad, Ollie Liu, Bhuwan Dhingra, Dani Yogatama, Robin Jia, and Willie Neiswanger. 2024. IsoBench: Benchmarking Multimodal Foundation Models on Isomorphic Representations. *Preprint*, arXiv:2404.01266.

Andreas Goulas, Vasileios Mezaris, and Ioannis Patras. 2025. VidCtx: Context-aware Video Question Answering with Image Models. *Preprint*, arXiv:2412.17415.

Haowen Guan, Shengzhi Li, and Shichao Pei. 2026. Video Evidence Indexing: Learning Where to Look from Video Previews for Token-Budgeted Long-Video Question Answering. *Preprint*, arXiv:2610.00757.

Po han Li, Shenghui Chen, Ufuk Topcu, and Sandeep Chinchali. 2026. ViSIL: Unified Evaluation of Information Loss in Multimodal Video Captioning. *Preprint*, arXiv:2601.09851.

Andong Hua, Colton Bishop, Igor Mordatch, Arian Hosseini, Jindong Gu, Aleksandra Faust, Rebecca Roelofs, and Yao Qin. 2026. TokenSwap: Benchmarking and Reducing the Modality Gap in Multimodal LLMs. *Preprint*, arXiv:2607.28640.

Sayash Kapoor, Benedikt Stroebl, Zachary S. Siegel, Nitya Nadgir, and Arvind Narayanan. 2024. AI Agents That Matter. *Preprint*, arXiv:2407.01502.

Jongseo Lee, Hyuntak Lee, Sunghun Kim, Sooa Kim, Jihoon Chung, and Jinwoo Choi. 2026. Which Way Did It Move? Diagnosing and Overcoming Directional Motion Blindness in Video-LLMs. *Preprint*, arXiv:2605.22823.

Zhenxin Lei, Zhangwei Gao, Changyao Tian, Erfei Cui, Guanzhou Chen, Danni Yang, Yuchen Duan, Zhaokai Wang, Wenhao Li, Weiyun Wang, Xiangyu Zhao, Jiayi Ji, Yu Qiao, Wenhai Wang, and Gen Luo. 2025. MetaCaptioner: Towards Generalist Visual Captioning with Open-source Suites. *Preprint*, arXiv:2510.12126.

Lei Li, Yuanxin Liu, Linli Yao, Peiyuan Zhang, Chenxin An, Lean Wang, Xu Sun, Lingpeng Kong, and Qi Liu. 2024. Temporal Reasoning Transfer from Text to Video. *Preprint*, arXiv:2410.06166.

Zeshang Li and Shuoyang Zhang. 2026. Query-Dependent Use of Generated Descriptions for Reliable Visual Question Answering. *Preprint*, arXiv:2605.01733.

Dingli Liang, Yiqiao Xie, Yukai Huang, Zhaokai Wang, Weitong Cai, Guangwen Feng, Jifei Song, Zhensong Zhang, and Hang Zhang. 2026. CapMem: A Benchmark for Caption-Based Episodic Memory in Egocentric Video. *Preprint*, arXiv:2609.17688.

Yuanxin Liu, Shicheng Li, Yi Liu, Yuxiang Wang, Shuhuai Ren, Lei Li, Sishuo Chen, Xu Sun, and Lu Hou. 2024. TempCompass: Do Video LLMs Really Understand Videos? *Preprint*, arXiv:2403.00476.

Yuxuan Qiao, Haodong Duan, Xinyu Fang, Junming Yang, Lin Chen, Songyang Zhang, Jiaqi Wang, Dahua Lin, and Kai Chen. 2024. Prism: A Framework for Decoupling and Assessing the Capabilities of VLMs. *Preprint*, arXiv:2406.14544.

Farrukh Rahman. 2026. What Does a Temporal Benchmark Score Measure? Decomposing Channel Use in Video VLM Evaluation. *Preprint*, arXiv:2607.12304.

Shijie Wang, Qi Zhao, Minh Quan Do, Nakul Agarwal, Kwonjoon Lee, and Chen Sun. 2024. Vamos: Versatile Action Models for Video Understanding. *Preprint*, arXiv:2311.13627.

Ziheng Wang, Mingxuan Xie, Yilin Liu, Dayan Wu, Yang Li, and Pengwen Dai. 2026a. Seeing and Solving Are Not Enough for Vision-Language Models. *Preprint*, arXiv:2609.33694.

Ziyang Wang, Shoubin Yu, Elias Stengel-Eskin, Jaehong Yoon, Feng Cheng, Gedas Bertasius, and Mohit Bansal. 2025. VideoTree: Adaptive Tree-based Video Representation for LLM Reasoning on Long Videos. *Preprint*, arXiv:2405.19209.

Zizhen Wang, Bo Feng, Zhengfeng Lai, Shiyu Li, Yang Lu, Meng Cao, Ping Huang, and Xiaoming Simon Wang. 2026b. Putting Captions to the Test: Evaluating Video Caption Quality through Multiple-Choice Question Answering. *Preprint*, arXiv:2609.09973.

Zihan Weng, Lucas Gomez, Taylor Whittington Webb, and Pouya Bashivan. 2025. Caption This, Reason That: VLMs Caught in the Middle. *Preprint*, arXiv:2505.21538.

Long Xing, Xiaoyi Dong, Yuhang Zang, Yuhang Cao, Jianze Liang, Qidong Huang, Jiaqi Wang, Feng Wu, and Dahua Lin. 2025. CapRL: Stimulating Dense Image Caption Capabilities via Reinforcement Learning. *Preprint*, arXiv:2509.22647.

Yilun Xu, Shengjia Zhao, Jiaming Song, Russell Stewart, and Stefano Ermon. 2020. A Theory of Usable Information Under Computational Constraints. *Preprint*, arXiv:2002.10689.

Zihui Xue, Mi Luo, and Kristen Grauman. 2025. Seeing the Arrow of Time in Large Multimodal Models. *Preprint*, arXiv:2506.03340.

Jad Yammine, Malek Wahidi, Abrar Anwar, Yan Chang, Mihir Acharya, and Anthony Rizk. 2026. Industrial ReMEmbR: Scaling Spatiotemporal Memory to Robot Fleets. *Preprint*, arXiv:2610.28624.

Shijia Yang, Yunong Liu, Bohan Zhai, Ximeng Sun, Zicheng Liu, Emad Barsoum, Manling Li, and Chenfeng Xu. 2026. CaptionQA: Is Your Caption as Useful as the Image Itself? *Preprint*, arXiv:2511.21025.

Ce Zhang, Yan-Bo Lin, Ziyang Wang, Mohit Bansal, and Gedas Bertasius. 2026. SiLVR: A Simple Language-based Video Reasoning Framework. *Preprint*, arXiv:2505.24869.

Ce Zhang, Taixi Lu, Md Mohaiminul Islam, Ziyang Wang, Shoubin Yu, Mohit Bansal, and Gedas Bertasius. 2024. A Simple LLM Framework for Long-Range Video Question-Answering. *Preprint*, arXiv:2312.17235.

Haonan Zhao, Jiaxuan Chen, Qingyang Liu, Shuochen Chang, Siyu Sun, Jiangtong Li, and Li Niu. 2026. Memory Internalization via Test-Time Training for Long-Video Understanding. *Preprint*, arXiv:2610.26910.

A Prompts

All prompts are given exactly as sent. Text in braces is filled in per call.

Caption prompt. Every captioner gets the same prompt. For frames (Haiku, Sonnet, and Gemini's frame and frame-clip captions), the first sentence is:

```
The attached images are {n} frames from a {d}-second video
    clip, taken one second apart and shown in time order.
    Describe what happens in the clip, in one or two
    sentences of at most 45 words in total.
```

For Gemini's video captions, it is "Describe what happens in the attached 5-second video clip, in one or two sentences of at most 45 words in total." The rest is the same for all:

```
* Start with what happens: what the people, animals or
      machines do, or, if nothing in the clip acts, how the
      scene or the camera view changes.
* Then add the details that set this moment apart: the key
      objects and any on-screen text, but do not transcribe
      subtitles, clocks, timestamps, dates or numbering (
      such as day, part or step numbers), and leave out
      watermarks and channel logos.
* Describe the setting in a few words at most.
* Mention camera movement only when the camera clearly moves.

* Describe what is seen, not what is heard.
* Include enough details so someone who hasn't seen the
      video could understand what's happening.
* If a description cannot be generated, write "ERROR".
```

The whole-video captions (§4.6) get all of a video's frames in one call, and the length clause scales with the number of windows (for two windows: "in at most 4 sentences of at most 90 words in total"). The aspect-aware captions (§4.5) add one bullet before the last:

```
* The description will be used later to answer questions
      about the actions, the speed of the movements, the
      direction of the movements, the order of the events,
      and changes in the attributes of things (such as size,
       colour, shape or state). State these whenever the
      frames show them.
```

Reader prompt.

```
Answer a multiple-choice question about a video clip that is
      {duration} seconds long. There is no sound.

{modality}

{evidence}

Question: {stem}
{options}

Answer with JSON only, in this format: {"answer": "<letter
      >"}, with one of the letters {letters}.
```

The evidence is the frames or the captions, each window labelled with its time span ("0-5 s:"). The modality sentence is, for frames:

```
The video was split into windows of 5 seconds (the last one
      may be shorter). Each window is shown as its frames
      taken one second apart, in time order.
```

for captions:

```
The video was split into windows of 5 seconds (the last one
      may be shorter). Each window is given as a short
      description of what can be seen in it, in time order.
      Each description was written by an AI model that
      watched only that one window, without sound, and knew
      nothing about the rest of the video.
```

for whole-video captions:

```
The video is given as a single description of what can be
      seen in it. The description was written by an AI model
       that watched the whole video, without sound.
```

for one frame per window, "… Each window is shown as one frame from its middle, in time order."; and for the question only, "You cannot see the video. Give your best guess from the question and options alone."

Describe, then answer. The reader prompt with frames, with the last paragraph replaced by:

```
First describe each window in one sentence, in time order:
      what can be seen in it and what happens. Then answer.
      Answer with JSON only, in this format: {"windows": ["<
      window 1>", "<window 2>", ...], "answer": "<letter>"},
       with one description per window and one of the
      letters {letters}.
```

Audit judge (§4.4).

```
You are checking whether written descriptions of a video
      contain the answer to a question about it.

The video is {duration} seconds long, without sound. It was
      split into windows of 5 seconds (the last one may be
      shorter). An AI model wrote one description per window,
       seeing only that one window and not the question:

{captions}

Question: {stem}
{options}

The correct answer is {answer}. {answer_text}

Judge the descriptions only, not what you think the video
      shows. Choose one label:
- "correct": the descriptions state the correct answer, or
      imply it clearly enough that a careful reader would
      choose it.
- "wrong": the descriptions state, or clearly imply, a
      different option.
- "silent": the descriptions do not decide between the
      options: the fact needed is missing or too vague.

Answer with JSON only, in this format: {"label": "<correct|
      wrong|silent>", "evidence": "<a short quote from the
      descriptions, or an empty string>"}
```

B Development phase and predictions

[PENDING: how the development set set the hypotheses; predictions against results]

C Amendments, deviations and term mapping

[PENDING: amendments and deviations.] Hand-label caveat: the labels were blind to the judge, but made in a session where Claude (Opus) pointed out caption details on 6 items; κ is 0.81 with the first-instinct labels too.

D Tables by aspect and by video type

Table 8 gives the accuracy of every arm by video type and by aspect. Every stacked question is about speed, and every two-clip question is about order, so the two breakdowns overlap.

[PENDING: effects by video type with clustered CIs, retention of the variants, the Haiku headroom table, all exploratory terms with their predictions]

Reader, input	plain (137)	two-clip (45)	reversed (74)	stacked (41)	action (60)	attr. (60)	direction (60)	order (57)	speed (60)	all (297)
Haiku, question only	0.60	0.31	0.16	0.34	0.63	0.37	0.28	0.37	0.40	0.41
Haiku, 1 frame	0.77	0.62	0.27	0.49	0.88	0.55	0.32	0.65	0.52	0.58
Haiku, 5 frames	0.80	0.60	0.38	0.41	0.93	0.67	0.28	0.65	0.53	0.61
Haiku, 5 frames, 448 px	0.82	0.62	0.43	0.49	0.98	0.68	0.38	0.65	0.55	0.65
Haiku, describe, then answer	0.82	0.69	0.50	0.54	0.90	0.73	0.47	0.72	0.60	0.68
Haiku, self-captions	0.80	0.82	0.43	0.32	0.90	0.70	0.38	0.82	0.42	0.64
Haiku, Sonnet captions	0.85	0.93	0.45	0.44	0.97	0.72	0.42	0.91	0.53	0.71
Haiku, Sonnet captions, 448 px	0.88	0.87	0.46	0.41	0.95	0.77	0.43	0.84	0.57	0.71
Haiku, Sonnet whole-video	0.85	0.89	0.57	0.37	0.97	0.83	0.43	0.89	0.48	0.72
Haiku, Sonnet aspect-aware	0.88	0.96	0.58	0.39	0.95	0.88	0.43	0.95	0.53	0.75
Haiku, Gemini frame-clip	0.88	0.87	0.57	0.34	0.98	0.85	0.43	0.88	0.48	0.72
Haiku, Gemini frame	0.92	1.00	0.64	0.41	1.00	0.90	0.55	1.00	0.52	0.79
Haiku, Gemini video	0.86	0.93	0.53	0.49	0.95	0.82	0.43	0.93	0.57	0.74
Sonnet, question only	0.61	0.29	0.18	0.32	0.70	0.38	0.23	0.40	0.35	0.41
Sonnet, 5 frames	0.89	0.91	0.64	0.66	0.97	0.82	0.58	0.91	0.72	0.80
Sonnet, Sonnet captions	0.88	0.91	0.46	0.39	0.97	0.73	0.43	0.89	0.53	0.71
Sonnet, Sonnet captions, 448 px	0.88	0.96	0.49	0.41	0.95	0.77	0.48	0.95	0.52	0.73
Sonnet, Sonnet whole-video	0.90	0.93	0.51	0.27	0.98	0.82	0.45	0.91	0.45	0.72
Sonnet, Sonnet aspect-aware	0.92	0.96	0.55	0.39	1.00	0.87	0.45	0.95	0.55	0.76
Sonnet, Gemini video	0.93	0.98	0.57	0.54	1.00	0.82	0.55	0.98	0.62	0.79
Qwen, question only	0.50	0.42	0.23	0.32	0.58	0.38	0.28	0.44	0.30	0.40
Qwen, 5 frames	0.86	0.58	0.45	0.44	0.93	0.75	0.38	0.67	0.55	0.66
Qwen, Haiku captions	0.81	0.58	0.45	0.22	0.90	0.70	0.42	0.63	0.37	0.60
Qwen, Sonnet captions	0.86	0.64	0.51	0.27	0.98	0.78	0.43	0.70	0.40	0.66
Qwen, Gemini frame-clip	0.88	0.67	0.54	0.32	0.95	0.85	0.45	0.72	0.47	0.69
Qwen, Gemini frame	0.91	0.71	0.58	0.32	0.98	0.87	0.50	0.75	0.47	0.71
Qwen, Gemini video	0.89	0.76	0.50	0.34	0.97	0.80	0.47	0.77	0.48	0.70
Qwen, Qwen captions	0.75	0.60	0.26	0.24	0.90	0.53	0.28	0.58	0.38	0.54

Table 8: Accuracy by video type and by aspect, every arm (297 confirmatory questions; n in brackets).

E Minimal-pair construction

[PENDING: construction and pair results by group]

F Release

We release the code, every caption, and every reader and judge output (prompt, raw answer, parsed answer and token counts per call), with the log of predictions written before each run. **[PENDING: anonymized link for review.]** The videos and questions are TempCompass's (Liu et al., 2024), under CC BY-NC 4.0; we do not redistribute the videos or frames, and the captions, which describe them, are released under the same licence.