

CVN-69 Milestone 6 — Printing Guide

Validated process

- Primary printer: Bambu Lab P2S. Also suitable for X1C, P1S, A1, and individual compact plates on A1 Mini where practical.
- PLA, 0.40 mm nozzle, three walls, 0.12 mm preferred layer; 0.16 mm is independently real-sliced.
- Print at 100%. Do not reduce the released 0.60–1.10 mm FDM-safe features.
- Assign materials by object name. No fixed AMS slot is required.

Production plates

Plate	Objects	0.12 / 0.16 mm
Print_Plate_00_First_Article.3mf	11	PASS / PASS
Print_Plate_01_Tow_Tractors.3mf	3	PASS / PASS
Print_Plate_02_Service_Carts.3mf	3	PASS / PASS
Print_Plate_03_Firefighting_Equipment.3mf	5	PASS / PASS
Print_Plate_04_Tow_Bars_Chocks.3mf	4	PASS / PASS
Print_Plate_05_Ladders_Maintenance.3mf	1	PASS / PASS
Print_Plate_06_Wheels_Inserts_Details.3mf	7	PASS / PASS

Acceptance

- Reject missing wheels, handles, ladder rungs, tow-bar forks, chocks, bottles, hose reel, turret/nozzle, or alignment-coupon edges.
- The validated command-line runs produced zero floating-region, empty-layer, and faulty-mesh warnings at both layer heights.
- Supports were not needed. Add only a local brim if the calibrated printer requires more adhesion.