REV	DATE	BY	DESCRIPTION
	2012.05.30	HuangFuMin	

性能参数表 parameter list

最大挂钩力 max.latch hook force F		⩽70T(包括风力作用)/每钩
最大侧向力max.side force Fc		⩽7T(包括风力作用)/每钩
最大侧向变形量max.distortion side X		18mm
杠杆比lever ratio(L1/L2)		1900/1300
推进器propeller	型号 type	EdA 800-140
	额定推力rating thrust	800N
	电源 power supply	380V,50HZ
配重weight		318kg
挂钩轴直径shaft diamter	φ(mm)	135
支座高度seat height	h/h1 (mm)	850/120(min.) ✓
		950/220

NO.	SUB-NO. OR STDD	VER	NAME & SIZE	MTRL	QTY	EACH(Kg)	TOTAL(Kg)	NOTE
B22	JISB0203		平头油嘴 PT1/4" Nipple	外购成品Pur.	4	0.0	0.0	*不锈钢*
B21	GB71-85		开槽锥端螺钉 M8×10 Screw	A2-70	8	0.0	0.0	
B20	GB97.1-85		平垫圈 8 Washer	A200	8	0.0	0.0	
B19	GB889-86		锁紧螺母 M8 Lock nut	A2-70	8	0.0	0.0	
B18	GB5782-86		螺栓 M8×35 Bolt	A2-70	8	0.0	0.0	
B17	GB/T91-2000		开口销 5×40 Split pin	Q235	4	0.0	0.0	
B16			自润轴套 JDB650202850 Flange bush	外购成品Pur.	2	0.0	0.0	
B15			自润轴套 JDB650202820 Flange bush	外购成品Pur.	4	0.0	0.0	
B14	GB97.1-85		平垫圈 20 Washer	100HV	8	0.0	0.0	*Dacro*
B13	GB32.1-88		螺栓 M20×35 Bolt	8.8	8	0.1	0.8	*Dacro*
B12	GB97.1-85		平垫圈 10 Washer	A200	16	0.0	0.0	
B11	GB889-86		锁紧螺母 M10 Lock nut	A2-70	16	0.0	0.0	
B10	GB819-85		螺钉 M10×45 Screw	A2-70	16	0.0	0.0	
B9			抬钩\进钩限位	外购成品Pur.	4	0.0	0.0	
B8			倍得上升极限(终点)限位	外购成品Pur.	4	0.0	0.0	
B7			电力液压推进器 Thruster		2	40.0	80.0	
B6	GB97.1-85		平垫圈 5 Washer	A200	16	0.0	0.0	
B5	GB889-86		锁紧螺母 M5 Lock nut	A2-70	16	0.0	0.0	
B4	GB5782-86		螺栓 M5×60 Bolt	A2-70	16	0.0	0.0	
B3	GB97.1-85		平垫圈 12 Washer	A200	12	0.0	0.0	
B2	GB889-86		锁紧螺母 M12 Lock nut	A2-70	12	0.0	0.0	
B1	GB5782-86		螺栓 M12×45 Bolt	A2-70	12	0.0	0.0	
20	GB709-88		钢板 8 F=85×200 Armor plate	Q235	2	1.0	2.0	
19	SB01-40	0	抗磨块200×40 Slap block	UHMWPE	4	1.3	5.2	
18	J526A6202	0	铜基铜合金自润滑轴承套 steel+cast bronze alloy (soild lubricant)	20#+高力黄铜+固体润滑剂	4	2.0	8.0	按图外购 outsourcing
17	GB4240-84		不锈钢丝 2.0 l=150 Stainless wire	0Cr18Ni9Ti	4	0.0	0.0	
16	BLH0115	0	楔块装置 chock	组件Ass.	2	2.6	5.2	
15	BLH0112	0	销 pin	45	2	0.5	1.0	
14	BLH0111	0	销 pin	45	2	0.4	0.8	
13	BLH0110-J526A62	0	轴 shaft	35CrMo	2	35.5	71.0	
12	BLH0109b	0	轴套 Bush	高力黄铜+固体润滑	4	0.5	2.0	按图外购 outsourcing
11	BLH0108	0	卡轴板 Plate	Q235	4	0.8	3.2	
10	J526A6201	0	配重箱 Balancing Box	焊接件	2	318.0	636.0	
9	GB9788-88	0	角钢 100×63×8 l=700 L-bar	Q235	2	6.9	13.8	
8	BLH0106 GB709-88	0	钢板 8 F=60×200 Armor plate	Q235	2	0.7	1.4	
7	BLH0105-J526A62	0	支座 Support	焊接件Wel.	2	346.0	692.0	
6	BLH0104	0	推进器底座下面顶起式 Thruster Support Thruster under Hook	焊接件Wel.	2	5.6	11.2	
5	GB9788-88		角钢 75×50×6 l=450 L-bar	Q235	2	2.6	5.2	具体长度现场可调 commissioning
4	BLH0103	0	调整垫板 plate	Q235	4	6.2	24.8	
3	ALS2-J526A62	0	可调式限位支架 adjustable limit switch support	铆件总图Ass.	1	10.1	10.1	
2	BLH0102	0	接块 block	焊接件Wel.	1	4.5	4.5	
1	BLH0301-J526A62	0	挂钩 hook	焊接件Wel.	2	432.5	865.0	

项目图号 item drawing	A(钩间距) hook's space between mm	B(梯形架中心距) distance to pylon centre mm	h(钩中心高) hook's centre high mm
J526A62	5750	2700	850

技术要求

1、装配前各运动关节应清除垃圾，并涂上润滑脂。

2、杠杆配重校正的方法：装推杆之前,利用配重箱杠杆配平,装上推进器顶起后，去除部分配重块,使钩头可以自动落钩即可，但每钩去除的配重块重量最多不得超过40kg.

3、各行程开关应在现场调试对准位置时安装

4、现场安装调试应保证推杆推出行程最大115mm,收回推出行程最小5mm时,钩体刚好接触到弹性块件4和19处,控制行程约110mm.

5、挂钩共2件,左右对称制作

6、调整钩体底座位置，让钩挂好之后，面大梁上的缓冲器离梯形架平台端面⩽100mm.

7、件6,7,8,9,16底座的高度总装时可现场调整,调整余量在零件图中已给出.

8.暴风状态时可以人工插入件17锲块，防止钩杆意外上抬脱钩.

Technical Requirement

1、Running points must be cleaned and lubricate before assembly.

2、Leveraged counterweight adjusting method :Before assembling the handspike, the lever should be balanced by Balancing Box. Then take off pieces of Balancing Blocks (less than 40 kg) after loading the thruster jack to make the hook auto-dropping.

3、Limit switch should be assembled on site.

4、When the thruster at the max.stroke 115mm and min. 5mm,the hook should just touch the Back Support on the plate(piece 4 and The actual stroke is about 110.19),

5、Two pieces of hook must be made symmetrically.

6、The dimension of X(as drawing) should less then 100mm (X⩽100)after the hook has been assembled.

7、The height of piece 6,7,8,9 and 16 can be adjusted on site according to the adjusting range shown in part drawing.

8.Piece 17 can be inserted by people when hurricane,and the staff can be avoided to fall off.

PROJECT: SliLanka CICT 12 STS Cranes				DESIGN STAGE:		SCALE: 1:10	
ITEM NAME: 大梁固定装置/安全钩 boom stowage device				DRAW NO: J526A62			
ZPMC	DSGN			TRACE		APP.	
	DRAW			CHCK		Q'TY/SET	
	CHCK			VER.		TOTAL WEIGHT	2483kg