

# Distributing the Heat Equation

Tom Cornebize

Yassine Hamoudi

Sunday, December 7th

## 1 Question 1

**Lemma 1.**  $N^2$  applications of function  $\delta$  are necessary to compute  $X^t$  from  $X^{t-1}$ .

*Proof.* Each cell  $X_{i,j}^t$  needs one application of  $\delta$  to be computed from  $X_{i,j}^{t-1}$ . There are  $N^2$  cells, so  $N^2$  applications of  $\delta$  are needed.  $\square$

**Property 2.**  $tN^2$  applications of function  $\delta$  are necessary to compute  $X^t$  on  $\llbracket 0, N-1 \rrbracket^2$ .

*Proof.*  $X^t$  is obtained after  $t$  applications of  $\delta^\dagger$  on  $X^0$ . Each application needs  $N^2$  calls to  $\delta$  according to lemma 1. The whole computation needs  $tN^2$  applications of  $\delta$ .  $\square$

## 2 Question 2

We associate one processor per cell ( $N^2$  processors are needed). Each processor  $p_{i,j}$  stores at time  $t$  the value of cell  $X_{i,j}^t$ .

At time  $t$ , each processor sends its value to its 8 neighbours and receives their values in parallel. Then each processor updates  $X_{i,j}^t$  to  $X_{i,j}^{t+1}$ .

→ à changer : (, le nombre de processeurs est un paramètre donné en entrée ( $< N^2$  à priori)