Stock Exchange

Facilitate matching buyers and sellers.
200 bill shares per day.

EDS:
- stocks only
- placing, cancelling
- normal trading hours
- trade 1 million shares in one day
- users should have sufficient funds

NFR:
- Availability 99.99 %
- Fault tolerance. Fast recovery.
- Latency. ms-level. 99% latency.
- KYC (Know your Client before new acc. opened)

BEE:
- 100 symbols
- 1 Mill orders/day
- M-F 9:30 - 4:00 PM EST (6.5h/day)
- QPS: $\frac{1\ \text{mill}}{6.5 \times 3{,}600\ (23{,}400)} \simeq 43.000$
- Peak QPS: 5 times × 43 000 = 215.000



HLD:
- Broker – friendly user interface
- Institutional clients – trade large volumes via software.
- Limit order – buy/sell with a fixed price
- Market order – doesn't specify a price.
- Market data levels:
  - L1: best bid price, quantities
  - L2: more than L1 price levels
  - L3: queued quantity at each price level
- Candlestick chart – Upper Shadow / Real body / Low Shadow
- Fix protocol [99].



API:

POST /v1/order — Auth requires.

Req:
- Symbol
- side
- price
- order Type
- quantity

ORDER

Resp:

Body:
- id:
- creation Time:
- filled Quantity:
- remain Quantity:
- status:

Code:
- 200: success
- 40x: params error
- 500: server error

EXECUTION

GET /v1/execution?symbol={:symbol}&orderId={:orderId}
&startTime={:startTime}
&endTime={:endTime}

Auth requires

Req. parameters:
- Symbol:
- orderId:
- start Time:
- end Time:

Resp:

Body:
- array with executions
- id:
- order Id:
- Symbol:
- side:
- price:
- order Type:

Code: 200, 400, 500.

Historical prices (candlestick charts)

GET /v1/market data/candles? symbol, resolution, start Time, end Time

Queries chart data

Data models:

1. Product, order, execution

↳ type, traded symbol, currency, lot size. (highly cacheable, Relational DB)
↳ inbound instruction for buy/sell
↳ outbound matched result (fill)



2. Order book (list of buy and sell orders) Data Structure

O(1) lookup time for matching
O(1) add/cancel/execute
Fast update & iterate through price levels




```
class PriceLevel {
    private Price limitPrice;
    private long totalVolume;
    private List<Order> orders;   // O(N)?  Doubly Linked List to cancel/match O(1)
}                                 // Double Linked List < Order > orders;

class Book <Side> {
    private Side side;
    private Map <Price, PriceLevel > limitMap;
}
class OrderBook {
    private Book <Buy > buyBook;
    private Book <Sell > sellBook;
    ...
}
```

3. Candlestick chart (processor to produce market data)

Data Structure:

```
class Candlestick {
    private long openPrice;
    private long closePrice;
    private long highPrice;
    private long lowPrice;
    private long volume;
    private long timeStamp;
    private long interval;
}

class CandlestickChart {
    private LinkedList < Candlestick > stick;
}
```

DDD:

99%

[Latency = $\sum$ exec. time Along Critical Path]

critical path:

gateway → order Manager → Sequencer → Matching Engine
1 2 3 4

! [500 ms]

according to network host access time and using disk to store date will have tens + miliseconds.

To get efficiently path use MMap.
Place all the elements on a single server:

To decrease latency-level delay:



Additionally we can pin each of components to run for a fix CPU core. Use Multi-threading.



MMap; all the components on one host;
latency == sub-microseconds; event sourcing.
↗ contains log of events immutable (source of truth)

High Availability:

4 nines 99.99 %

8.64 sec downtime per day.

- identify SPoF
- decision to failover to the backup instance should be fast.

Use heartbeat to detect potential problem in the primary.

Fault Tolerance:

- replicating core data to multiple location data centers

1. if primary goes down → decide failover to the backup?
2. how do we choose a leader among backup instances?
3. RTO (Time) ? Time of recovery?
4. What functionalities need to be recovered RPO (Point) ?

[Chaos engineering] ← use to gather all the necessary data to know all about pat the system to failover from backup instances.

Latency & Functional Determinism

1. 

2. In Latency time is matter. It is key for the business.

Multicast:

1. Unicast
2. Broadcast
3. Multicast

UDP - not reliable



DDos issues:

- isolate network to prevent
- good caching won't use/hit DataBase
- harden URL's
  /domain.com/endpoint/ ← !
- network gateway with blacklist network address
- Rate Limiting to defend against DDos.