



## COMP 2012H Honors Object-Oriented Programming and Data Structures

### Topic 6: Recursion

Dr. Desmond Tsoi

Department of Computer Science & Engineering  
The Hong Kong University of Science and Technology  
Hong Kong SAR, China



Rm 3553, desmond@ust.hk

COMP 2012H (Fall 2020)

1 / 24

## Recursion

- In programming, **recursion** means that a function calls **itself**!
- Although it looks strange in the beginning, solving a programming task by **recursion** renders the program
  - ▶ easier to **write**
  - ▶ easier to **read** (understand)
  - ▶ **shorter** (in codes).

### Implement a Recursive Solution

1. **Decompose** the **problem** into **sub-problems** — which are smaller examples of the same problem — plus some **additional work** that “**glues**” the solutions of the sub-problems together.
2. The **smallest sub-problem** has a **non-recursive** solution.

Rm 3553, desmond@ust.hk

COMP 2012H (Fall 2020)

2 / 24

### Example: Factorial Function

Definition of the **factorial function** you learn in high school:

$$n! = n \times (n-1) \times (n-2) \times \cdots \times 2 \times 1$$

#### Recursive Definition of Factorial Function

- $0! = 1$
- $n! = n \times (n-1)!$  if  $n > 0$
- To find the value of  $n!$ , first find the value of  $(n-1)!$  and then multiply the result with  $n$ .



Rm 3553, desmond@ust.hk

COMP 2012H (Fall 2020)

3 / 24

### Example: Factorial Recursive Function

```
int factorial(int n)    /* factorial.cpp */
{
    if (n < 0)           // Error checking
        return -1;
    else if (n == 0)     // Base case; ending case too!
        return 1;
    else                 // Recursive case
        return n * factorial(n-1);
}
```

Or, equivalently,

```
int factorial(int n)    /* factorial2.cpp */
{
    if (n < 0)           // Error checking
        return -1;
    if (n == 0)          // Base case; ending case too!
        return 1;
    return n * factorial(n-1); // Recursive case
}
```

Rm 3553, desmond@ust.hk

COMP 2012H (Fall 2020)

4 / 24

## How the Recursive Factorial Function Works?

factorial(3) :

```
3 < 0    false
3 == 0   false
3 * factorial(2)
```

```
factorial(2) :
2 < 0    false
2 == 0   false
2 * factorial(1)
```

```
factorial(1) :
1 < 0    false
1 == 0   false
1 * factorial(0)
```

```
factorial(0) :
0 < 0    false
0 == 0   true
return 1
```

return 1\*1 = 1

return 2\*1 = 2

return 3\*2 = 6

## Factorial Function: Recursive vs. Non-Recursive

```
int factorial(int n)    /* factorial.cpp */
{
    if (n < 0)           // Error checking
        return -1;
    else if (n == 0)     // Base case; ending case too!
        return 1;
    else                 // Recursive case
        return n * factorial(n-1);
}
```

```
int factorial(int n)    /* non-recursive-factorial.cpp */
{
    int result = 1;      // Default value for n = 0 or 1
    if (n < 0)           // Error checking
        return -1;

    for (int j = 2; j <= n; j++) // When n >= 2
        result *= j;
    return result;
}
```

## Infinite Recursion!


- We have to be careful that a recursion will eventually end up with a non-recursive base case.
- Otherwise, we will get infinite recursion!

```
int factorial(int n)
{
    // Forget the base case, which is the ending case too!
    return n * factorial(n-1);
}
```

```
int factorial(int n)
{
    // Forget checking if n < 0
    if (n == 0)
        return 1;

    // Infinite recursion for negative n
    return n * factorial(n-1);
}
```

## Binary Search



binary search for the value 9

## Example: Recursive Solution of Binary Search

```
const int NOT_FOUND = -1;      /* File: bsearch.cpp */
int bsearch(const int data[ ], // sorted in ascending order
            int first,         // lower bound index
            int last,          // upper bound index
            int value)         // value to search
{
    if (last < first)           // Base case #1
        return NOT_FOUND;

    int mid = (first + last)/2;

    if (data[mid] == value)
        return mid;            // Base case #2

    else if (data[mid] > value) // Search the lower half
        return bsearch(data, first, mid-1, value);

    else                        // Search the upper half
        return bsearch(data, mid+1, last, value);
}
```

## Example: Non-Recursive Solution of Binary Search

```
const int NOT_FOUND = -1;      /* File: non-recursive-bsearch.cpp */
int bsearch(const int data[ ], // sorted in ascending order
            int size,           // number of data in the array
            int value)          // value to search
{
    int first = 0;
    int last = size - 1;

    while (first <= last)
    {
        int mid = (first + last)/2;
        if (data[mid] == value)
            return mid;         // Value found!
        else if (data[mid] > value)
            last = mid - 1;      // Set up for searching the lower half
        else
            first = mid + 1;     // Set up for searching the upper half
    }

    return NOT_FOUND;
}
```

## Disadvantages of Recursion

- The greater programming productivity is achieved at the expenses of the more computing resources. To run recursion, it usually requires
  - ▶ more memory
  - ▶ more computational time
- The reason is that whenever a function is called, the computer
  - ▶ has to memorize its **current state**, and **passes control** from the **caller** to the **callee**.
  - ▶ sets up a new data structure (you may think of it as a scratch paper for rough work) called **activation record** which contains information such as
    - ★ where the **caller** stops
    - ★ what **actual parameters** are passed to the **callee**
    - ★ create new **local variables** required by the **callee** function
    - ★ the **return value** of the function at the end
  - ▶ removes the **activation record** of the **callee** when it finishes.
  - ▶ passes control back to the **caller**.

That's all!

Any questions?



## Further Reading



## Example: Fibonacci Numbers

0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89, 144, 233, 377, 610, 987, ...

**Fibonacci** (1202) investigated how fast rabbits could breed:

- A **newly-born** pair of rabbits, one male, one female, are put in a field.
- Rabbits **mate at the age of one month** so that at the **end of its 2nd month**, a female can **produce another pair** of rabbits.
- Suppose that our rabbits **never die**.
- Suppose the female always produces **one new pair** (one male, one female) **every month** from the 2nd month on.
- **How many pairs will there be in one year?**

**Question** : What is special with the above numbers?

**Answer** : Except for the first 2 numbers, each number is the **sum of the last 2 numbers** in the sequence.


## Example: Fibonacci Function as a Recursion

```
int fibonacci(int n)    /* File: fibonacci.cpp */
{
    if (n == 0)         // Base case #1
        return 0;

    if (n == 1)         // Base case #2
        return 1;

    return fibonacci(n-1) + fibonacci(n-2);
}
```

## Inefficiency of Recursive Fibonacci Function



## Example: Non-Recursive Fibonacci Function

```
int fibonacci(int n)      /* non-recursive-fibonacci.cpp */
{
    int fn;                // keep track of f(n)
    int fn_1 = 1;          // keep track of f(n-1)
    int fn_2 = 0;          // keep track of f(n-2)


    if (n == 0) return 0; // Base case #1
    if (n == 1) return 1; // Base case #2

    for (int j = 2; j <= n; j++)
    {
        fn = fn_1 + fn_2; // f(n) = f(n-1) + f(n-2)

        // Prepare for the calculation of the next fibonacci number
        fn_2 = fn_1;      // f(n-2) = f(n-1)
        fn_1 = fn;        // f(n-1) = f(n)
    }


    return fn;
}
```

## Example: Tower of Hanoi Game



- It consists of 3 **pegs**, and a stack of **discs of different sizes**.
- It **starts** with all discs stacked up on one peg with smaller discs sitting on top of bigger discs.
- The **goal** is to **move** the entire stack of discs to another peg, making use of the remaining peg.
- **Rules:**
  - ▶ only one disc may be moved at a time
  - ▶ no disc may be placed on top of a smaller disc

## Recursive Solution of Tower of Hanoi



## Example: Recursive Solution of Tower of Hanoi

```
#include <iostream>      /* File: toh.cpp */
using namespace std;

void tower_of_hanoi(int num_discs, char pegA, char pegB, char pegC)
{
    if (num_discs == 0) // Base case
        return;

    tower_of_hanoi(num_discs-1, pegA, pegC, pegB);

    cout << "move disc " << num_discs
          << " from peg " << pegA << " to peg " << pegC << endl;

    tower_of_hanoi(num_discs-1, pegB, pegA, pegC);
}
```

## Example: Counting Zeros in an Integer

- **Example:** for the integer 120809, there are 2 zeros.
- **Basic idea:**
  - ▶ Break down the number into **quotient** and **remainder**.
  - ▶ Count the number of zeros in **quotient** and **remainder**.

```
int num_zeros(int n)    /* File: num-zeros.cpp */
{
    if (n == 0)          // Base case #1
        return 1;

    else if (n < 10 && n > 0) // Base case #2
        return 0;


    else
        return num_zeros(n/10) + num_zeros(n%10);
}
```

## Example: Factoring

- **Goal:** find how many times **factor**  $m$  appears in the **integer**  $n$ .
- **Example:** if  $n = 48$  and  $m = 4$ , since  $48 = 4 \times 4 \times 3$ , the answer is 2.
- **Basic idea:**
  - ▶ Divide  $n$  by  $m$  **until** the remainder is non-zero.
  - ▶ **Increment** the count by 1 for every successful division.

```
int num_factors(int n, int m) /* File: factor.cpp */
{
    if (n % m != 0)           // Base case
        return 0;
    else
        return 1 + num_factors(n/m, m);
}
```

## Array and Recursion



- **Array** is a **recursive data structure** in nature.
- For many problems, one may define a recursion on an array of size  $N$  which
  - ▶ will call **itself** with only  $N - 1$  elements (either the top  $N - 1$  or the last  $N - 1$  elements),
  - ▶ with some **extra codes** to deal with the **remaining** element (last or first element).

## Example: Sum Up Array Elements

```
#include <iostream> /* File: array-sum.cpp */
using namespace std;

// Summing up x[0] + x[1] + ... + x[num_elements-1]
int array_sum(const int x[], int num_elements)
{
    if (num_elements <= 0) return 0; // Base case
    return array_sum(x, num_elements-1) + x[num_elements-1];
}

int main()
{
    int a[] = { 1, 2, 3, 4, 5, 6 };
    int n;           // #elements in an array to sum
    while (cin >> n)
        cout << array_sum(a, n) << endl;
    return 0;
}
```

**Question:** What happens if you pass a value bigger than the size of the array size to  $n$ ?