

Chapter 14 JavaFX Basics

Introduction to Java Programming by Y. Daniel Leung

Section 14.2 JavaFX vs Swing and AWT

14.1 Why is JavaFX preferred?

- ☒ A. JavaFX is much simpler to learn and use for new Java programmers.
- ☒ B. JavaFX provides a multi-touch support for touch-enabled devices such as tablets and smart phones.
- ☒ C. JavaFX has a built-in 3D, animation support, video and audio playback, and runs as a standalone application or from a browser.
- ☒ D. JavaFX incorporates modern GUI technologies to enable you to develop rich Internet applications.

Section 14.3 The Basic Structure of a JavaFX Program

14.2 Every JavaFX main class _____.

- ☐ A. implements javafx.application.Application
- ☒ B. extends javafx.application.Application
- ☒ C. overrides start(Stage s) method
- ☐ D. overrides start() method

14.3 Which of the following statements are true?

- ☒ A. A primary stage is automatically created when a JavaFX main class is launched.
- ☒ B. You can have multiple stages displayed in a JavaFX program.
- ☒ C. A stage is displayed by invoking the show() method on the stage.
- ☐ D. A scene is placed in the stage using the addScene method
- ☒ E. A scene is placed in the stage using the setScene method

14.4 What is the output of the following JavaFX program?

```
import javafx.application.Application;
import javafx.stage.Stage;

public class Test extends Application {
    public Test() {
        System.out.println("Test constructor is invoked.");
    }

    @Override // Override the start method in the Application class
    public void start(Stage primaryStage) {
```

```

        System.out.println("start method is invoked.");
    }

    public static void main(String[] args) {
        System.out.println("launch application.");
        Application.launch(args);
    }
}

```

- ☐ A. launch application. start method is invoked.
- ☐ B. start method is invoked. Test constructor is invoked.
- ☐ C. Test constructor is invoked. start method is invoked.
- ☐ D. launch application. start method is invoked. Test constructor is invoked.
- ☒ E. launch application. Test constructor is invoked. start method is invoked.

Section 14.4 Panes, UI Controls, and Shapes

14.5 Which of the following statements are true?

- ☐ A. A Scene is a Node.
- ☒ B. A Shape is a Node.
- ☐ C. A Stage is a Node.
- ☒ D. A Control is a Node.
- ☒ E. A Pane is a Node.

14.6 Which of the following statements are true?

- ☒ A. A Node can be placed in a Pane.
- ☐ B. A Node can be placed in a Scene.
- ☐ C. A Pane can be placed in a Control.
- ☐ D. A Shape can be placed in a Control.

14.7 Which of the following statements are correct?

- ☒ A. `new Scene(new Button("OK"));`
- ☐ B. `new Scene(new Circle());`
- ☐ C. `new Scene(new ImageView());`
- ☒ D. `new Scene(new Pane());`

14.8 To add a circle object into a pane, use _____.

- ☐ A. `pane.add(circle);`

- ☐ B. `pane.addAll(circle);`
- ☒ C. `pane.getChildren().add(circle);`
- ☒ D. `pane.getChildren().addAll(circle);`

14.9 Which of the following statements are correct?

- ☒ A. Every subclass of `Node` has a no-arg constructor.
- ☒ B. `Circle` is a subclass of `Node`.
- ☒ C. `Button` is a subclass of `Node`.
- ☒ D. `Pane` is a subclass of `Node`.
- ☐ E. `Scene` is a subclass of `Node`.

Section 14.5 Binding Properties

14.10 Which of the following are binding properties?

- ☐ A. `Integer`
- ☐ B. `Double`
- ☒ C. `IntegerProperty`
- ☒ D. `DoubleProperty`
- ☐ E. `String`

14.11 Which of the following can be used as a source for a binding properties?

- ☐ A. `Integer`
- ☐ B. `Double`
- ☒ C. `IntegerProperty`
- ☒ D. `DoubleProperty`
- ☐ E. `String`

Check Answer for Question 11

14.12 Suppose a JavaFX class has a binding property named `weight` of the type `DoubleProperty`. By convention, which of the following methods are defined in the class?

- ☒ A. `public double getWeight()`
- ☒ B. `public void setWeight(double v)`
- ☒ C. `public DoubleProperty weightProperty()`
- ☐ D. `public double weightProperty()`



E. `public DoubleProperty WeightProperty()`

14.13 What is the output of the following code?

```
import javafx.beans.property.IntegerProperty;
import javafx.beans.property.SimpleIntegerProperty;

public class Test {
    public static void main(String[] args) {
        IntegerProperty d1 = new SimpleIntegerProperty(1);
        IntegerProperty d2 = new SimpleIntegerProperty(2);
        d1.bind(d2);
        System.out.print("d1 is " + d1.getValue()
            + " and d2 is " + d2.getValue());
        d2.setValue(3);
        System.out.println(", d1 is " + d1.getValue()
            + " and d2 is " + d2.getValue());
    }
}
```



A. d1 is 2 and d2 is 2, d1 is 3 and d2 is 3



B. d1 is 2 and d2 is 2, d1 is 2 and d2 is 3



C. d1 is 1 and d2 is 2, d1 is 1 and d2 is 3



D. d1 is 1 and d2 is 2, d1 is 3 and d2 is 3

14.14 What is the output of the following code?

```
import javafx.beans.property.IntegerProperty;
import javafx.beans.property.SimpleIntegerProperty;

public class Test {
    public static void main(String[] args) {
        IntegerProperty d1 = new SimpleIntegerProperty(1);
        IntegerProperty d2 = new SimpleIntegerProperty(2);
        d1.bindBidirectional(d2);
        System.out.print("d1 is " + d1.getValue()
            + " and d2 is " + d2.getValue());
        d1.setValue(3);
        System.out.println(", d1 is " + d1.getValue()
            + " and d2 is " + d2.getValue());
    }
}
```



A. d1 is 2 and d2 is 2, d1 is 3 and d2 is 3



B. d1 is 2 and d2 is 2, d1 is 2 and d2 is 3



C. d1 is 1 and d2 is 2, d1 is 1 and d2 is 3



D. d1 is 1 and d2 is 2, d1 is 3 and d2 is 3

Section 14.6 Common Properties and Methods for Nodes

14.15 Which of the following statements correctly sets the fill color of circle to black?

- ☒ A. `circle.setFill(Color.BLACK);`
- ☐ B. `circle.setFill(Color.black);`
- ☒ C. `circle.setStyle("-fx-fill: black");`
- ☐ D. `circle.setStyle("fill: black");`
- ☐ E. `circle.setStyle("-fx-fill-color: black");`

14.16 Which of the following statements correctly rotates the button 45 degrees counterclockwise?

- ☐ A. `button.setRotate(45);`
- ☐ B. `button.setRotate(Math.toRadians(45));`
- ☒ C. `button.setRotate(360 - 45);`
- ☒ D. `button.setRotate(-45);`

Section 14.7 The Color Class

14.17 Which of the following statements correctly creates a Color object?

- ☐ A. `new Color(3, 5, 5, 1);`
- ☒ B. `new Color(0.3, 0.5, 0.5, 0.1);`
- ☐ C. `new Color(0.3, 0.5, 0.5);`
- ☒ D. `Color.color(0.3, 0.5, 0.5);`
- ☒ E. `Color.color(0.3, 0.5, 0.5, 0.1);`

Section 14.8 The Font Class

14.18 Which of the following statements correctly creates a Font object?

- ☒ A. `new Font(34);`
- ☒ B. `new Font("Times", 34);`
- ☒ C. `Font.font("Times", 34);`
- ☒ D. `Font.font("Times", FontWeight.NORMAL, 34);`
- ☒ E. `Font.font("Times", FontWeight.NORMAL, FontPosture.ITALIC, 34);`

14.19 Which of the following statements are correct?

- ☒ A. A Color object is immutable.
- ☒ B. A Font object is immutable.

- ☒ C. You cannot change the contents in a Color object once it is created.
- ☒ D. You cannot change the contents in a Font object once it is created.

Section 14.9 The Image and ImageView Classes

14.20 Which of the following statements correctly creates an ImageView object?

- ☒ A. `new ImageView("http://www.cs.armstrong.edu/liang/image/us.gif");`
- ☒ B. `new ImageView(new Image("http://www.cs.armstrong.edu/liang/image/us.gif"));`
- ☒ C. `new ImageView("image/us.gif");`
- ☒ D. `new ImageView(new Image("image/us.gif"));`

14.21 Analyze the following code:

```
import javafx.application.Application;
import javafx.scene.Scene;
import javafx.scene.layout.HBox;
import javafx.scene.layout.Pane;
import javafx.geometry.Insets;
import javafx.stage.Stage;
import javafx.scene.image.Image;
import javafx.scene.image.ImageView;

public class Test extends Application {
    @Override // Override the start method in the Application class
    public void start(Stage primaryStage) {
        // Create a pane to hold the image views
        Pane pane = new HBox(10);
        pane.setPadding(new Insets(5, 5, 5, 5));
        Image image = new Image("www.cs.armstrong.edu/liang/image/us.gif");
        pane.getChildren().addAll(new ImageView(image), new ImageView(image));

        // Create a scene and place it in the stage
        Scene scene = new Scene(pane);
        primaryStage.setTitle("ShowImage"); // Set the stage title
        primaryStage.setScene(scene); // Place the scene in the stage
        primaryStage.show(); // Display the stage
    }

    /**
     * The main method is only needed for the IDE with limited
     * JavaFX support. Not needed for running from the command line.
     */
    public static void main(String[] args) {
        launch(args);
    }
}
```

- ☐ A. The program runs fine and displays two images.

- ☒ B. `new Image("www.cs.armstrong.edu/liang/image/us.gif")` must be replaced by `new Image("http://www.cs.armstrong.edu/liang/image/us.gif")`.
- ☐ C. The image object cannot be shared by two `ImageViews`.
- ☐ D. The `addAll` method needs to be replaced by the `add` method.

Section 14.10 Layout Panes

14.22 To add a node into a pane, use _____.

- ☐ A. `pane.add(node);`
- ☐ B. `pane.addAll(node);`
- ☒ C. `pane.getChildren().add(node);`
- ☒ D. `pane.getChildren().addAll(node);`

14.23 To add two nodes `node1` and `node2` into a pane, use _____.

- ☐ A. `pane.add(node1, node2);`
- ☐ B. `pane.addAll(node1, node2);`
- ☐ C. `pane.getChildren().add(node1, node2);`
- ☒ D. `pane.getChildren().addAll(node1, node2);`

14.24 To remove a node from the pane, use _____.

- ☐ A. `pane.remove(node);`
- ☐ B. `pane.removeAll(node);`
- ☒ C. `pane.getChildren().remove(node);`
- ☒ D. `pane.getChildren().removeAll(node);`

14.25 To remove two nodes `node1` and `node2` from a pane, use _____.

- ☐ A. `pane.remove(node1, node2);`
- ☐ B. `pane.removeAll(node1, node2);`
- ☐ C. `pane.getChildren().remove(node1, node2);`
- ☒ D. `pane.getChildren().removeAll(node1, node2);`

14.26 Which of the following statements are correct to create a `FlowPane`?

- ☒ A. `new FlowPane()`
- ☒ B. `new FlowPane(4, 5)`
- ☒ C. `new FlowPane(Orientation.VERTICAL);`
- ☒ D. `new FlowPane(4, 5, Orientation.VERTICAL);`

14.27 To add a node to the the first row and second column in a GridPane pane, use _____.

- ☐ A. `pane.getChildren().add(node, 1, 2);`
- ☐ B. `pane.add(node, 1, 2);`
- ☐ C. `pane.getChildren().add(node, 0, 1);`
- ☐ D. `pane.add(node, 0, 1);`
- ☒ E. `pane.add(node, 1, 0);`

14.28 To add two nodes node1 and node2 to the the first row in a GridPane pane, use _____.

- ☒ A. `pane.add(node1, 0, 0); pane.add(node2, 1, 0);`
- ☐ B. `pane.add(node1, node2, 0);`
- ☒ C. `pane.addRow(0, node1, node2);`
- ☐ D. `pane.addRow(1, node1, node2);`
- ☐ E. `pane.add(node1, 0, 1); pane.add(node2, 1, 1);`

14.29 To place a node in the left of a BorderPane p, use _____.

- ☐ A. `p.setEast(node);`
- ☐ B. `p.placeLeft(node);`
- ☒ C. `p.setLeft(node);`
- ☐ D. `p.left(node);`

14.30 To place two nodes node1 and node2 in a HBox p, use _____.

- ☐ A. `p.add(node1, node2);`
- ☐ B. `p.addAll(node1, node2);`
- ☐ C. `p.getChildren().add(node1, node2);`
- ☒ D. `p.getChildren().addAll(node1, node2);`

14.31 Analyze the following code:

```
import javafx.application.Application;
import javafx.scene.Scene;
import javafx.stage.Stage;
import javafx.scene.layout.HBox;
import javafx.scene.shape.Circle;

public class Test extends Application {
    @Override // Override the start method in the Application class
    public void start(Stage primaryStage) {
```



```

HBox pane = new HBox(5);
Circle circle = new Circle(50, 200, 200);
pane.getChildren().addAll(circle);

circle.setCenterX(100);
circle.setCenterY(100);
circle.setRadius(50);
pane.getChildren().addAll(circle);

// Create a scene and place it in the stage
Scene scene = new Scene(pane);
primaryStage.setTitle("Test"); // Set the stage title
primaryStage.setScene(scene); // Place the scene in the stage
primaryStage.show(); // Display the stage
}

/**
 * The main method is only needed for the IDE with limited
 * JavaFX support. Not needed for running from the command line.
 */
public static void main(String[] args) {
    launch(args);
}
}

```

- ☐ A. The program has a compile error since the circle is added to a pane twice.
- ☐ B. The program has a runtime error since the circle is added to a pane twice.
- ☐ C. The program runs fine and displays one circle.
- ☐ D. The program runs fine and displays two circles.

Section 14.11 Shapes

14.32 The _____ properties are defined in the javafx.scene.shape.Shape class.

- ☒ A. stroke
- ☒ B. strokeWidth
- ☒ C. fill
- ☐ D. centerX

14.33 The _____ properties are defined in the javafx.scene.text.Text class.

- ☒ A. text
- ☒ B. x
- ☒ C. y
- ☒ D. underline

☒ E. strikethrough

14.34 The _____ properties are defined in the `javafx.scene.shape.Line` class.

☒ A. x1

☒ B. x2

☒ C. y1

☒ D. y2

☐ E. strikethrough

14.35 The _____ properties are defined in the `javafx.scene.shape.Rectangle` class.

☒ A. width

☒ B. x

☒ C. y

☒ D. height

☒ E. arcWidth

14.36 The _____ properties are defined in the `javafx.scene.shape.Ellipse` class.

☒ A. centerX

☒ B. centerY

☒ C. radiusX

☒ D. radiusY

14.37 To construct a Polygon with three points x1, y1, x2, y2, x3, and y3, use _____.

☒ A. `new Polygon(x1, y1, x2, y2, x3, y3)`

☐ B. `new Polygon(x1, y2, x3, y1, y2, y3)`

☒ C. `Polygon polygon = new Polygon(); polygon.getPoints().addAll(x1, y1, x2, y2, x3, y3)`

☐ D. `Polygon polygon = new Polygon(); polygon.getPoints().addAll(x1, y2, x3, y1, y2, y3)`

14.38 To construct a Polyline with three points x1, y1, x2, y2, x3, and y3, use _____.

☒ A. `new Polyline(x1, y1, x2, y2, x3, y3)`

- ☐ B. `new Polyline(x1, y2, x3, y1, y2, y3)`
- ☒ C. `Polyline polyline = new Polygon(); polyline.getPoints().addAll(x1, y1, x2, y2, x3, y3)`
- ☐ D. `Polyline polyline = new Polygon(); polyline.getPoints().addAll(x1, y2, x3, y1, y2, y3)`

14.39 Assume `p` is a `Polygon`, to add a point `(4, 5)` into `p`, use _____.

- ☐ A. `p.getPoints().add(4); p.getPoints().add(5);`
- ☒ B. `p.getPoints().add(4.0); p.getPoints().add(5.0);`
- ☐ C. `p.getPoints().addAll(4, 5);`
- ☒ D. `p.getPoints().addAll(4.0, 5.0);`