# **COMP 2012H Honors Object-Oriented Programming and Data Structures**

# **Supplementary Notes on Constructors and Destructor**

### Page 47: Cons / Destruction Order: Postoffice Has a Clock

```
// postoffice1.h
#include <iostream>
using namespace std;
class Clock {
 public:
   Clock() {
     cout << "Clock Constructor\n"; // Step 4</pre>
   ~Clock() {
     cout << "Clock Destructor\n"; // Step 8</pre>
class Postoffice {
   Clock clock; // Step 3
 public:
   Postoffice() {
      cout << "Postoffice Constructor\n"; // Step 5</pre>
   ~Postoffice() {
       cout << "Postoffice Destructor\n"; // Step 7</pre>
// postoffice1.cpp
#include <iostream>
#include "postoffice1.h"
using namespace std;
int main() {
 cout << "Beginning of main\n";</pre>
                                      // Step 1
 Postoffice x;
                                      // Step 2
 cout << "End of main\n";</pre>
                                      // Step 6
 return 0;
Output:
Beginning of main
                                      Step 1
Clock Constructor
                                       Step 4
Postoffice Constructor
                                      Step 5
End of main
Postoffice Destructor
                                      Step 7
Clock Destructor
                                       Step 8
```

### Page 49: Cons / Destruction Order: Postoffice Owns" a Clock

```
// postoffice2.h
#include <iostream>
using namespace std;
class Clock {
  public:
    Clock() {
      cout << "Clock Constructor\n"; // Step 5</pre>
    ~Clock() {
     cout << "Clock Destructor\n";
};
class Postoffice {
    Clock* clock; // Step 3
  public:
    Postoffice() {
     clock = new Clock; // Step 4
     cout << "Postoffice Constructor\n"; // Step 6</pre>
    ~Postoffice() {
       cout << "Postoffice Destructor\n"; // Step 8</pre>
};
// postoffice2.cpp
#include <iostream>
#include "postoffice2.h"
using namespace std;
int main() {
  cout << "Beginning of main\n";</pre>
                                       // Step 1
  Postoffice x;
                                       // Step 2
  cout << "End of main\n";</pre>
                                       // Step 7
  return 0;
Output:
Beginning of main
                                       Step 1
Clock Constructor
                                       Step 5
Postoffice Constructor
                                       Step 6
End of main
                                       Step 7
Postoffice Destructor
                                       Step 8
```

1

### Page 51: Cons / Destruction Order: Postoffice Owns" a Clock

```
// postoffice3.h
#include <iostream>
using namespace std;
class Clock {
 public:
   Clock() {
     cout << "Clock Constructor\n"; // Step 5</pre>
   ~Clock() {
     cout << "Clock Destructor\n"; // Step 10</pre>
};
class Postoffice {
   Clock* clock; // Step 3
 public:
   Postoffice() {
     clock = new Clock; // Step 4
     cout << "Postoffice Constructor\n"; // Step 6</pre>
   ~Postoffice() {
      cout << "Postoffice Destructor\n"; // Step 8</pre>
      delete clock; // Step 9
};
// postoffice3.cpp
#include <iostream>
#include "postoffice3.h"
using namespace std;
int main() {
 cout << "Beginning of main\n";</pre>
                                      // Step 1
 Postoffice x;
                                      // Step 2
 cout << "End of main\n";</pre>
                                     // Step 7
 return 0:
Output:
Beginning of main
                                       Step 1
Clock Constructor
                                      Step 5
Postoffice Constructor
                                      Step 6
End of main
                                       Step 7
Postoffice Destructor
                                       Step 8
Clock Destructor
                                       Step 10
```

#### Page 52: Cons / Destruction Order: PostofficeHasClock + Room

```
// postoffice4.h
#include <iostream>
using namespace std;
class Clock {
 private:
   int HHMM;
  public:
    Clock(): HHMM(0) // Step 6 {
     cout << "Clock Constructor\n"; // Step 7</pre>
    ~Clock() { cout << "Clock Destructor\n"; } // Step 11
};
class Room {
  public:
    Room() { cout << "Room Constructor\n"; } // Step 4</pre>
    ~Room() { cout << "Room Destructor\n"; } // Step 12
class Postoffice {
 private:
    Room room; // Step 3
    Clock clock; // Step 5
    Postoffice() { cout << "Postoffice Constructor\n"; } // Step 8
    ~Postoffice() { cout << "Postoffice Destructor\n"; } // Step 10
};
// postoffice4.cpp
#include <iostream>
#include "postoffice4.h"
using namespace std;
int main() {
 cout << "Beginning of main\n";</pre>
                                      // Step 1
                                      // Step 2
  Postoffice x;
  cout << "End of main\n";</pre>
                                      // Step 9
  return 0;
Output:
Beginning of main
                                      Step 1
Room Constructor
                                      Step 4
Clock Constructor
                                      Step 7
Postoffice Constructor
                                      Step 8
End of main
                                      Step 9
Postoffice Destructor
                                      Step 10
Clock Destructor
                                      Step 11
Room Destructor
                                      Step 12
```

### Page 53: Cons / Destruction Order: PostofficeMoves Clock to Room

```
// postoffice5.h
#include <iostream>
using namespace std;
class Clock {
 public:
   Clock() {
     cout << "Clock Constructor\n"; // Step 5</pre>
    ~Clock() { cout << "Clock Destructor\n"; } // Step 11
};
class Room {
 private:
   Clock clock; // Step 4
   Room() { cout << "Room Constructor\n"; } // Step 6</pre>
    ~Room() { cout << "Room Destructor\n"; } // Step 10
class Postoffice {
 private:
   Room room; // Step 3
 public:
   Postoffice() { cout << "Postoffice Constructor\n"; } // Step 7</pre>
   ~Postoffice() { cout << "Postoffice Destructor\n"; } // Step 9
// postoffice5.cpp
#include <iostream>
#include "postoffice5.h"
using namespace std;
int main() {
 cout << "Beginning of main\n";</pre>
                                      // Step 1
 Postoffice x;
                                      // Step 2
 cout << "End of main\n";</pre>
                                     // Step 8
 return 0;
Output:
Beginning of main
                                       Step 1
Clock Constructor
                                       Step 5
Room Constructor
                                       Step 6
Postoffice Constructor
                                       Step 7
End of main
                                       Step 8
Postoffice Destructor
                                       Step 9
Room Destructor
                                       Step 10
Clock Destructor
                                      Step 11
```

### Page 54: Cons / Destruction Order: Postofficew/ aTemporary Clock

```
// postoffice6.h
#include <iostream>
using namespace std;
class Clock {
  private:
    int HHMM;
  public:
    Clock(): HHMM(0) // Step 4 {
     cout << "Clock Constructor\n"; // Step 5</pre>
    Clock(int hhmm) : HHMM(hhmm) // Step 8 {
      cout << "Clock Constructor at " << HHMM << endl; // Step 9
      cout << "Clock Destructor at " << HHMM << endl; // Step 10, 13</pre>
};
class Postoffice {
 private:
    Clock clock; // Step 3
  public:
    Postoffice() {
      cout << "Postoffice Constructor\n"; // Step 6</pre>
      clock = Clock(800); // Step 7
    ~Postoffice() { cout << "Postoffice Destructor\n"; } // Step 12
};
// postoffice6.cpp
#include <iostream>
#include "postoffice6.h"
using namespace std;
int main() {
  cout << "Beginning of main\n";</pre>
                                      // Step 1
  Postoffice x:
                                      // Step 2
  cout << "End of main\n";
                                      // Step 11
  return 0;
Output:
Beginning of main
                                      Step 1
Clock Constructor
                                      Step 5
Postoffice Constructor
                                      Step 6
Clock Constructor at 800
                                      Step 9
Clock Destructor at 800
                                      Step 10
End of main
                                      Step 11
Postoffice Destructor
                                      Step 12
Clock Destructor at 800
                                      Step 13
```