

Contents

Enphase Monitor	2
Table of Contents	2
Quick Start	2
Features	2
Prerequisites	3
Installation	3
Step 1: Clone the Repository	3
Step 2: Install Dependencies	3
Step 3: Build the Application	3
Configuration	3
Initial Setup	3
Configuration Sections	4
Finding Your System IDs	5
OAuth Setup	5
Quick Setup	5
Detailed Guide	5
After OAuth Setup	6
API Configuration	6
What the Cloud API Provides	6
Rate Limits	6
Getting API Credentials	6
Usage	6
Run Once (Single Query)	6
Continuous Monitoring	7
Command-Line Options	7
Examples	7
Output Format	7
Metrics Explained	8
Combined Energy Report	8
Individual System Metrics	8
Color Customization	9
Troubleshooting	9
“API configuration required”	9
“API request failed with status 401”	9
“API request failed with status 404”	9
“rate limit exceeded (429)”	10
“API request failed with status 422”	10
No telemetry data returned	10
Caching and Rate Limits	10
Rate Limits	10
Caching Strategy	10
Cache File Format and Naming	11
Cache Management Commands	11
Best Practices	11
Documentation	11
For Getting Started	12

For Understanding the Codebase	12
Recommended Learning Path	12
Project Structure	12
Testing	13
Test Mode (Cache Only)	13
Setting Up Test Data	13
Expected Values Format	14
Validation Tolerance	14
License	14

Enphase Monitor

A Go application for monitoring and aggregating data from multiple Enphase solar systems via the Enphase Enlighten Cloud API v4.

New to Go? This codebase follows Go best practices and includes comprehensive documentation. See **GO_BEST_PRACTICES.md** for a guide to Go patterns and idioms, and **GO_CONCEPTS.md** for a reference of Go concepts used in the code.

Table of Contents

- Quick Start
- Features
- Installation
- Configuration
- OAuth Setup
- Usage
- Output Format
- API Configuration
- Caching and Rate Limits
- Testing
- Troubleshooting
- Documentation
- Project Structure

Quick Start

New to this project? Start here:

1. **QUICKSTART.md** - Get up and running in 5 minutes
2. **OAuth_SETUP.md** - Complete OAuth authentication (required for first-time setup)
3. Return here for detailed usage and configuration

Features

- **Multi-System Monitoring:** Query and combine metrics from multiple independent Enphase systems
- **Comprehensive Metrics:** Track production, consumption, battery usage, grid import/export, and net energy flow

- **Flexible Querying:** Query historical dates or monitor real-time with auto-refresh
- **Clean Display:** Formatted terminal output with customizable colors
- **API Caching:** Automatic caching of API responses to reduce API calls and enable offline validation
- **Color Customization:** Customize terminal colors using hex codes or ANSI escape codes
- **Cloud API v4:** Uses Enphase Enlighten Cloud API v4 for reliable data access
- **OAuth Support:** Full OAuth 2.0 support for developer plan authentication
- **Test Mode:** Validation mode for testing against expected values without making API calls

Prerequisites

- Go 1.21 or higher
- **Enphase Developer Portal Account:** Register at <https://developer-v4.enphase.com/>
- **OAuth Credentials:** Get `api_key`, `client_id`, and `client_secret` from the Developer Portal
- **System IDs:** Your Enphase system IDs (find these from Enlighten URLs - see “Finding Your System IDs” section)

Installation

Step 1: Clone the Repository

```
git clone <repository-url>
cd enphase-monitor
```

Or download and extract the project files.

Step 2: Install Dependencies

```
go mod download
```

Step 3: Build the Application

```
go build -o enphase-monitor
```

Configuration

Initial Setup

1. Copy the example configuration file:

```
cp config.yaml.example config.yaml
```

2. Edit `config.yaml` with your credentials:

```
api:
  key: "YOUR_API_KEY" # API Key from Enphase Developer Portal
  client_id: "YOUR_CLIENT_ID" # OAuth Client ID
  client_secret: "YOUR_CLIENT_SECRET" # OAuth Client Secret
  authorization_url: "https://api.enphaseenergy.com/oauth/token"
  redirect_uri: "http://localhost:8080/callback"
  refresh_token: "YOUR_REFRESH_TOKEN" # From OAuth setup (see below)
```

```

systems:
  - name: "Left Subpanel"
    id: "YOUR_SYSTEM_ID"  # Enlighten system ID

  - name: "Right Subpanel"
    id: "YOUR_OTHER_SYSTEM_ID"  # Different system ID

refresh_interval: 3600  # Refresh interval in seconds (1 hour recommended)

# Optional: Timezone for reporting/display
# If not specified, uses OS system timezone (or US/Pacific if OS is UTC)
timezone: "US/Pacific"  # Examples: "US/Pacific", "America/New_York", "Europe/London"

# Optional: Color customization
colors:
  production: "#f0b57c"      # Solar Production
  discharge: "#7acf38"       # Battery Discharge
  import: "#f63cb1"          # Grid Import
  export: "#06b6de"          # Grid Export
  net_import: "#f63cb1"      # Net Energy Flow (Import)
  net_export: "#06b6de"      # Net Energy Flow (Export)
  headers: "#f37320"         # Report Headers
  charge: "#7acf38"          # Battery Charge
  total_consumed: "#f37320"  # Total Consumed
  secondary_text: "#808080"  # Secondary Text
  primary_text: "#ffffff"    # Primary Text
  error: "#ff0000"          # Error Text

```

Implementation Details: See `config.go` for color conversion logic (hex → ANSI) and `display.go` for color usage in terminal output.

Configuration Sections

API Credentials You will need these from the Enphase Developer Portal: - `api.key`: Your API key - `api.client_id`: OAuth client ID - `api.client_secret`: OAuth client secret - `api.refresh_token`: Obtained from OAuth setup (see OAuth Setup below)

System Configuration Each system requires: - `name`: A friendly name for display - `id`: Your Enphase system ID (see Finding Your System IDs)

Optional Settings

- `refresh_interval`: How often to query the API in continuous mode (default: 3600 seconds = 1 hour)
 - **Important:** Only applies when running in continuous mode (without `--once` flag)
 - **Recommended:** Use 3600 seconds (1 hour) to respect API rate limits
 - **Rate Limit Consideration:** The API allows 10 requests per minute. With multiple systems, a low `refresh_interval` (e.g., 5 seconds) can quickly exceed this limit. For

2 systems, you would make 24 requests per minute (2 systems × 12 queries/minute), which exceeds the 10/minute limit.

- **Best Practice:** Use 3600 seconds (1 hour) or higher to stay well within rate limits
- **timezone:** Timezone for reporting and display (optional)
 - **Default:** Uses your OS system timezone, or US/Pacific if OS timezone is UTC
 - **Format:** IANA timezone identifier (e.g., "US/Pacific", "America/New_York", "Europe/London")
 - **Examples:**

```
timezone: "US/Pacific"           # Pacific Time
timezone: "America/New_York"    # Eastern Time
timezone: "Europe/London"       # GMT/BST
```
 - **Usage:** All date/time display and API queries use this timezone. If not specified, the application uses your OS system timezone, falling back to US/Pacific if the system timezone is UTC.
- **colors:** Customize terminal output colors (see Color Customization)

Finding Your System IDs

To find your System IDs:

1. Log into <https://enlighten.enphaseenergy.com>
2. Select one of your systems
3. Look at the URL - it will be: https://enlighten.enphaseenergy.com/systems/SYSTEM_ID/overview
4. The number in the URL is your System ID
5. Repeat for each system you want to monitor

OAuth Setup

Required for First-Time Setup

This application uses OAuth 2.0 for authentication. You must complete a one-time OAuth setup to get your refresh token.

Quick Setup

Run the interactive setup wizard:

```
./enphase-monitor --setup-oauth
```

This will guide you through: 1. Generating an authorization URL 2. Authorizing the application in your browser 3. Exchanging the authorization code for tokens 4. Adding the refresh token to your config

Detailed Guide

For a comprehensive explanation of OAuth 2.0, what each component does, and how authentication works, see:

OAUTH_SETUP.md - Complete OAuth guide with: - Explanation of OAuth 2.0 concepts - What the API server expects for authentication - How authorization works - Step-by-step setup instructions - Troubleshooting common issues

After OAuth Setup

Once you have your `refresh_token`, add it to your `config.yaml`:

```
api:
  refresh_token: YOUR_REFRESH_TOKEN  # From OAuth setup
```

The application will automatically use this token to get new access tokens when needed.

API Configuration

This application uses the **Enphase Enlighten Cloud API v4** exclusively to fetch energy data.

What the Cloud API Provides

- **Direct Daily Values:** The API returns pre-calculated daily totals - no need for state files or cumulative meter tracking
- **Historical Data:** Query any past date (not limited to today)
- **Real-time Updates:** Data is typically updated every 15 minutes
- **Reliable Access:** Works from anywhere with internet (no local network required)
- **Standardized Format:** Consistent JSON responses across all system types

Rate Limits

The free developer plan has the following limits: - **10 requests per minute** per API key - **1000 requests per month** total

The application automatically caches API responses to minimize API calls. The default refresh interval is 1 hour (3600 seconds) to stay well within these limits.

Getting API Credentials

1. **Register:** Create an account at <https://developer-v4.enphase.com/>
2. **Create Application:** Register a new application to get API credentials
3. **Get Credentials:** You will receive:
 - `api_key`: Your API key (used in all requests)
 - `client_id`: OAuth client ID
 - `client_secret`: OAuth client secret
4. **Complete OAuth Setup:** See OAuth Setup section above

Usage

Run Once (Single Query)

Query today's data and exit:

```
./enphase-monitor --once
```

Query a specific historical date:

```
./enphase-monitor --once --date 2026-01-15
```

Continuous Monitoring

Monitor with auto-refresh (uses `refresh_interval` from config):

```
./enphase-monitor
```

The application will query all systems at the configured `refresh_interval` (default: 3600 seconds = 1 hour) and display updated metrics.

Press **Ctrl+C** to stop.

Command-Line Options

- `--config <path>` - Path to configuration file (default: `config.yaml`)
- `--once` - Run once and exit instead of continuous monitoring
- `--date <YYYY-MM-DD>` - Query specific date instead of today (e.g., 2026-01-15)
- `--setup-oauth` - Run OAuth setup wizard (one-time for developer plan)
- `--test` - Test mode: use cache only, no live API calls, validate against expected values
- `--no-cache` - Bypass cache and make live API calls (falls back to cache on 429 rate limit)
- `--clear-cache` - Clear cached API responses for today's date only
- `--clear-all-cache` - Clear all cached API responses (all dates)
- `--list-cache` - List all cached API responses
- `--inspect-cache <hash|date>` - Inspect cached responses by hash or date (YYYY-MM-DD format)

Examples

```
# Use custom config file  
./enphase-monitor --config /path/to/my-config.yaml
```

```
# Query last week's data  
./enphase-monitor --once --date 2026-01-12
```

```
# Continuous monitoring with default settings  
./enphase-monitor
```

Output Format

The application displays:

```
=====
ENPHASE MULTI-SYSTEM MONITOR
=====
Query Range:    Tue Jan 20, 2026 12:00 AM
                to
                Tue Jan 20, 2026 11:59 PM

Last Updated:   Sat Jan 24, 2026 09:52:18 PM (cached)
=====

COMBINED ENERGY REPORT (kWh)
```

Produced:	33.4 kWh
Consumed:	48.6 kWh
Net Energy Flow:	19.1 kWh (import)

INDIVIDUAL SYSTEMS REPORT

[1] Right Subpanel (5525881)

Imported from the Grid:	23.1 kWh
Exported to the Grid:	3.8 kWh
Captured from the Sun:	14.6 kWh
Net Energy Flow:	19.3 kWh (import)
Charged to Battery:	8.5 kWh
Discharged from Battery:	6.8 kWh
Battery Charge Percentage:	63%
Total Consumed:	32.1 kWh

[2] Left Subpanel (5392556)

Imported from the Grid:	7.5 kWh
Exported to the Grid:	7.6 kWh
Captured from the Sun:	18.9 kWh
Net Energy Flow:	0.2 kWh (export)
Charged to Battery:	8.1 kWh
Discharged from Battery:	5.4 kWh
Battery Charge Percentage:	74%
Total Consumed:	16.4 kWh

=====

Note: Colors are customizable via `config.yaml` (see Color Customization section below).

Metrics Explained

Combined Energy Report

- **Produced:** Total solar generation from all systems (kWh)
- **Consumed:** Total household consumption from all systems (kWh)
- **Net Energy Flow:** Net energy imported from or exported to the grid
 - Positive value with “(import)” suffix: More energy imported than exported
 - Negative value with “(export)” suffix: More energy exported than imported
 - Calculation: Grid Imported - Grid Exported

Individual System Metrics

- **Imported from the Grid:** Energy purchased from utility for this system (kWh)
- **Exported to the Grid:** Energy sold back to utility from this system (kWh)
- **Captured from the Sun:** Solar generation for this system (kWh)
- **Net Energy Flow:** Net import/export for this system (kWh) with (import) or (export)

suffix

- **Charged to Battery:** Energy stored in batteries for this system (kWh)
- **Discharged from Battery:** Energy used from batteries for this system (kWh)
- **Battery Charge Percentage:** Current state of charge (SOC) of the battery system, displayed as a percentage (0-100%). This metric is shown per-system only and is not aggregated across multiple systems.
- **Total Consumed:** Total consumption for this system (kWh)

Color Customization

You can customize the colors used in the terminal output by adding a `colors` section to your `config.yaml`:

```
colors:
  production: "#f0b57c"      # Solar Production
  discharge: "#7acf38"       # Battery Discharge
  import: "#f63cb1"          # Grid Import
  export: "#06b6de"          # Grid Export
  net_import: "#f63cb1"      # Net Energy Flow (Import)
  net_export: "#06b6de"      # Net Energy Flow (Export)
  headers: "#f37320"         # Report Headers
  charge: "#7acf38"          # Battery Charge
  total_consumed: "#f37320"  # Total Consumed
  secondary_text: "#808080"   # Secondary Text
  primary_text: "#ffffff"     # Primary Text
  error: "#ff0000"           # Error Text
```

Color Format Options: - **Hex codes** (e.g., `#FF5733`): Automatically converted to ANSI color codes - **ANSI escape codes** (e.g., `\033[38;5;208m`): Used directly as-is

Note: Reset and Bold are constants defined in `constants.go` and cannot be customized.

Troubleshooting

“API configuration required”

- Make sure you have copied `config.yaml.example` to `config.yaml`
- Verify you have filled in `api.key`, `api.client_id`, and `api.client_secret`
- For developer plan, complete OAuth setup with `--setup-oauth` to get `refresh_token`

“API request failed with status 401”

- Your refresh token may have expired or been revoked
- Re-run OAuth setup: `./enphase-monitor --setup-oauth`
- Verify your API credentials are correct

“API request failed with status 404”

- Verify your System IDs are correct (check Enlighten URLs for each system)
- Check that you have access to all systems in Enlighten
- Ensure the system IDs are strings (quoted in YAML)

“rate limit exceeded (429)”

- The API has a rate limit of 10 calls per minute
- The program will display how many seconds to wait before retrying
- Consider increasing `refresh_interval` in your config
- Use `--test` mode to validate against cached data without making API calls

“API request failed with status 422”

- This usually means the requested date is in the future
- The program automatically caps dates to the current time
- Try querying a past date: `--date 2026-01-15`

No telemetry data returned

- Some data may not be available for very recent time periods (try querying yesterday’s data)
- Ensure your systems are actively reporting to Enlighten
- Check cache with `--list-cache` to see what data is available

Caching and Rate Limits

Rate Limits

The Enphase Enlighten Cloud API v4 enforces strict rate limits: - **10 requests per minute** per API key - **1000 requests per month** total (free developer plan)

Refresh Interval Recommendation:

The `refresh_interval` setting controls how often the application queries the API in continuous mode. To respect rate limits:

- **Recommended:** `refresh_interval: 3600` (1 hour)
- **Why:** Each system requires multiple API calls. With 2 systems, you might make 8-10 requests per query cycle. At 3600 seconds, that is ~20 requests per hour, well within limits.
- **Not Recommended:** Values below 60 seconds (e.g., `refresh_interval: 5`) can quickly exceed the 10 requests/minute limit, especially with multiple systems.
- **Calculation:** If you have N systems and each requires M API calls, you make $N \times M$ requests per cycle. At `refresh_interval: 5`, that is $N \times M \times 12$ requests per minute, which can easily exceed 10/minute.

Caching Strategy

To respect these limits, the application implements intelligent caching:

- **Automatic Disk Caching:** All API responses are cached in `test-data/cache/` directory
- **Cache-First for Past Dates:** When querying historical dates, cached data is used if available (no API call)
- **Default Refresh Interval:** 1 hour (3600 seconds) - queries each system once per hour
- **429 Error Handling:** If rate limited, the program displays wait time and exits gracefully

Cache File Format and Naming

Cache files are stored in the `test-data/cache/` directory with the following structure:

File Naming Scheme: - Each cached API response is stored as a JSON file - Filenames are SHA-256 hashes of the normalized API URL (including query parameters) - Format: `{hash}.json` where `{hash}` is a 64-character hexadecimal string - Example: `a1b2c3d4e5f6...{64 chars}.json`

Cache File Structure: Each cache file contains: - `status_code`: HTTP status code from the API response - `headers`: HTTP response headers (as key-value pairs) - `body`: Raw API response body (JSON bytes) - `cached_at`: Timestamp when the response was cached (ISO 8601 format) - `queried_date`: The date that was queried (YYYY-MM-DD format), if applicable

Cache Key Generation: - Cache keys are generated from normalized API URLs - URLs are normalized to ensure consistent caching (timestamps converted to date strings) - The same API query will always produce the same cache key, regardless of when it's made

Cache Lookup: - When making an API request, the application first checks for a cached response - If a cache file exists and is valid, the cached response is used (no API call) - For past dates, cached data is always preferred to avoid unnecessary API calls

Cache Management Commands

```
# View all cached responses
./enphase-monitor --list-cache

# Inspect a specific cached response (by hash or date)
./enphase-monitor --inspect-cache 2026-01-15

# Clear today's cache only (preserves historical data)
./enphase-monitor --clear-cache

# Clear all cached data
./enphase-monitor --clear-all-cache

# Disable caching (always make live API calls)
./enphase-monitor --no-cache

# Test mode (use cache only, no live API calls)
./enphase-monitor --test --date 2026-01-15
```

Best Practices

1. **Use Default Refresh Interval:** Use 1 hour to stay well within rate limits
2. **Leverage Caching:** Query past dates frequently - they use cached data (no API calls)
3. **Test Mode:** Use `--test` mode for validation against cached data without hitting API
4. **Monitor Cache:** Use `--list-cache` to see what data is available before querying

Documentation

This project includes comprehensive documentation for different learning paths:

For Getting Started

- **QUICKSTART.md** - Get up and running in 5 minutes
- **OAuth_SETUP.md** - Complete OAuth 2.0 setup guide with detailed explanations

For Understanding the Codebase

- **ARCHITECTURE.md** - System architecture, execution flow, and design patterns
- **GO_BEST_PRACTICES.md** - Go concepts and patterns used in this codebase
- **GO_CONCEPTS.md** - Quick reference for Go concepts used in the code, including channels and signals

Recommended Learning Path

1. **New Users:** Start with QUICKSTART.md
2. **OAuth Setup:** Follow OAuth_SETUP.md for authentication
3. **Understanding Go:** Read GO_BEST_PRACTICES.md for Go concepts
4. **System Design:** Study ARCHITECTURE.md to understand the codebase structure
5. **Advanced Topics:** Explore GO_CONCEPTS.md for channels, signals, and concurrency patterns

Project Structure

```
enphase-monitor/  
  main.go           # Application entry point and CLI handling  
  config.go         # Configuration loading, validation, and color conversion  
  constants.go      # Centralized constants repository (20+ constants)  
  cloud_client.go   # Enphase Cloud API v4 client  
  aggregator.go     # Data aggregation logic across systems  
  display.go        # Terminal output formatting and color display  
  api_cache.go      # API response caching and cache management  
  cache_cli.go      # Cache management CLI commands  
  oauth.go          # OAuth token management  
  setup_oauth.go    # OAuth setup wizard  
  timezone.go       # Timezone utilities  
  url_builder.go    # API URL construction helpers  
  response_parser.go # JSON parsing utilities  
  config.yaml.example # Example configuration with all options  
  config.yaml       # Your actual configuration (create from example)  
  test-data/  
    cache/          # Cached API responses  
    expected_values_*.json # Expected values for validation  
  validation.go     # Validation test code  
  go.mod            # Go module definition  
  go.sum            # Go module checksums  
  Makefile          # Build automation  
  generate-pdfs.sh  # Script to generate PDFs from markdown files  
  run-tests.sh      # Test runner script  
  README.md         # This file
```

QUICKSTART.md	# Quick start guide
OAUTH_SETUP.md	# OAuth setup documentation (detailed)
ARCHITECTURE.md	# Architecture documentation
GO_BEST_PRACTICES.md	# Go concepts guide
GO_CONCEPTS.md	# Go concepts reference (channels, signals, and more)
pdfs/	# Generated PDF documentation (created by generate-pdfs.sh)

Testing

The project includes a comprehensive test suite for validating metrics against expected values. This enables rapid iteration without hitting API rate limits.

Test Mode (Cache Only)

Run in test mode using only cached responses (no live API calls):

```
./enphase-monitor --once --test --date 2026-01-20
```

This will: 1. Use only cached API responses (no live calls) 2. Validate results against expected values 3. Show a detailed comparison report

Setting Up Test Data

IMPORTANT: The cache must contain data for the specific test date. Old cache files from different dates will cause incorrect results.

1. **Run all tests** (recommended):

```
./run-tests.sh
```

This script will:

- Check which test dates have cached responses
- Generate missing cache by making live API calls (waiting 60 seconds between calls to respect rate limits)
- Run validation tests for all dates (2026-01-14 through 2026-01-20)
- Display a summary of all test results

2. **Or manually generate cache for a specific date:**

```
./enphase-monitor --once --date 2026-01-20
```

This will make live API calls and cache the responses in `test-data/cache/`

3. **Update `expected_values_YYYY-MM-DD.json`** with the correct values from the Enphase app
4. **Now you can iterate rapidly using test mode** (uses cache only, no API calls):

```
./enphase-monitor --once --test --date 2026-01-20
```

Note: Test mode uses the cache from `test-data/cache/`. The `run-tests.sh` script ensures all test dates have cached responses available.

Expected Values Format

The expected values JSON file should have this structure:

```
{
  "date": "2026-01-20",
  "systems": [
    {
      "id": "5525881",
      "name": "Right Subpanel",
      "expected": {
        "grid_import": 23.4,
        "grid_export": 3.9,
        "production": 14.6,
        "battery_discharged": 6.8,
        "battery_charged": 8.6,
        "net_imported": 19.6,
        "consumption": 32.3
      }
    }
  ]
}
```

Validation Tolerance

The validation function compares actual vs expected values with a tolerance of **$\pm 10\%$ of the expected value**, with a minimum tolerance of **0.1 kWh** for small values. This means: - For large values (e.g., 20 kWh): tolerance is ± 2.0 kWh (10%) - For small values (e.g., 0.5 kWh): tolerance is ± 0.1 kWh (minimum)

Metrics that differ by more than the calculated tolerance will be marked as failed (). The validation report shows: - Expected value - Actual value - Difference - Percentage difference - Pass/fail status

License

This is a personal utility project. Use and modify as needed for your own Enphase monitoring needs. # enphase-monitor