



UN Comtrade Database

[Products](#)

[Profile](#)

[Sign out](#)

comtrade

[View changelog](#)

Version

v1

Download definition

Select definition type

APIs to get trade data and metadata. A subscription key is required. See examples at <https://bit.ly/42JNSaZ>. Learn more about our subscriptions at <https://uncomtrade.org/docs/subscriptions/>

get

Extract trade data in a basic layout. See the detailed description at <https://uncomtrade.org/docs/list-of-references-parameter-codes/>

Endpoint:

https://comtradeapi.un.org/data/v1/get/{typeCode}/{freqCode}/{clCode}[?reporterCode]

GET [&period][&partnerCode][&partner2Code][&cmdCode][&flowCode][&customsCode]

[&motCode][&aggregateBy][&breakdownMode][&includeDesc]

Try this operation

Request

Request parameters

Name	In	Required	Type	Description
typeCode	template	true	string	Type of trade: C for commodities and S for service
freqCode	template	true	string	Trade frequency: A for annual and M for monthly
clCode	template	true	string	Trade (IMTS) classifications: HS, SITC, BEC or EBOPS.
reporterCode	query	false	string	Reporter code (Possible values are M49 code of the countries separated by comma (,))
period	query	false	string	Year or month. Year should be 4 digit year. Month should be six digit

API

comtrade

Operations

Search

- GET get
- GET getDa
- GET getDaTariffline
- GET getLiveUpdate
- GET getMBS
- GET getMetadata
- GET getSUV
- GET getTariffline
- GET getTradeMatrix

					integer with the values of the form YYYYMM. Ex: 201002 for 2010 February. Multi value input should be in the form of csv (Codes separated by comma (,))
partnerCode	query	false	string	Partner code (Possible values are M49 code of the countries separated by comma (,))	
partner2Code	query	false	string	Second partner/consignme code (Possible values are M49 code of the countries separated by comma (,))	
cmdCode	query	false	string	Commodity code. Multi value input should be in	

				the form of csv (Codes separated by comma (,))
flowCode	query	false	string	Trade flow code. Multi value input should be in the form of csv (Codes separated by comma (,))
customsCode	query	false	string	Customs code. Multi value input should be in the form of csv (Codes separated by comma (,))
motCode	query	false	string	Mode of transport code. Multi value input should be in the form of csv (Codes separated by comma (,))
aggregateBy	query	false	csv	Add parameters in

Powered by Azure API Management .				csv list on which you want the results to be aggregated
breakdownM...	query	false	csv	Mode to choose from
includeDesc	query	false	boolean	Include descriptions of data variables

Response: 200 OK

null