Leveling agent WF-4012

Chemical Structure

Special surface-active agent polymer

Technical Index

Item	Standard
Appearance	Yellow to brown, slightly cloudy liquid
Solid Content, %	44.0-46.0%
PH Value (1% water solution)	6.0-7.0
Ionic	Anionic/Nonionic

Features and Advantages

A leveling agent for high-temperature and high-pressure dyeing of polyester disperse dyes, which has excellent retardation, migration and dispersion properties for disperse dyes. It is particularly suitable for rapid temperature increase processes, as well as for dyeing of ultra-fine polyester and low-bath-ratio disperse dyes.

1. Has excellent retardation, migration and dispersion properties for disperse dyes
2. Especially suitable for rapid temperature increase dyeing processes, ultra-fine polyester dyeing and low-bath-ratio dyeing.
3. Reduces the contamination of disperse dye floatation on fibers and reduces the burden of reductive cleaning.
4. Does not contain APEO, does not contain phosphorus, and complies with the requirements of OEKO-TEX 100 standard.

Application

0.3 - 0.8% by weight. High-efficiency and rapid dyeing accelerator WF-4012
X % by weight. Dispersed dyes
Yg/L Acetic acid, adjust the working solution pH to the required range
Start heating at 50℃, increase the temperature at 4℃/minute to 80℃, increase the temperature at 1-1.2℃/minute to 110℃, increase the temperature at 1.8 - 2℃/minute to 130 - 135℃, maintain at 30 - 60 minutes, decrease the temperature at 1.5 - 2.0℃/minute to 80℃, drain, water wash, reductive cleaning and post-treatment.

Package

120KG Plastic Drum or other packing on request. Sealed and light-proof storage.

ZHEJIANG WEIFENG NEW MATERIALS CO., LTD
Factory address: No.: 1, Ba'er Road, Jiangshan Economic Development Zone, Quzhou, Zhejiang, China
Website: www.wfchemistry.com
Email: info@wfchemie.com