Supplement: complete observations, mathematical comparisons and reproducibility

14 November 2026

Contents

Reading and source map . . . 2
Current detailed panel tables . . . 2
Breadth: complete two-sided endpoints . . . 2
Positive-resource GI-TBC operating points . . . 2
Objective weights: all methods and decompositions . . . 3
Limited Seed 1: complete main triplets . . . 4
Limited Seed 1 AM observations . . . 5
Seed 0 main mechanism comparison . . . 5
Seed 1 limited mechanism repeat . . . 6
Historical breadth/resource study: detailed interpretation . . . 13
Preserved historical supplement (R135 observations retained; headings nested and figure links pinned) 13
Round163 structural-stage evidence and prospective protocol . . . 34
Round163 completed configuration evidence . . . 35
Research navigation for saved C35 skeletons . . . 36
Round164 completed finite solver-Seed evidence . . . 36
All pre-frozen feasible-target availability intervals . . . 38
Round166 compact representation and certified decisions . . . 39

References **44**

The current tables contain every registered position. C means a performance-eligible qualified certificate; O means open; UEV means evidence outside formal performance eligibility. Open times are null, not the cap. Detailed full-precision arrays, physical operations, raw lifecycle/model evidence and source identities accompany the CSV/JSON authorities. Prior evidence below keeps its original version and denominators.

Reading and source map

The main paper and complete model/algorithm appendices are assembled from `paper_body.md` and `model_and_algorithm_appendices.md`. This supplement keeps complete breadth/resource/weight/AM/mechanism observations, useful historical mathematical comparisons, source provenance and the later cohort evidence. The mathematical companion distinguishes the relaxation objects and proof contracts. The current source manifest and document build receipt bind the current PDF to those components. Administrative author decisions are kept in the internal memo and are not part of the technical manuscript.

Current detailed panel tables

Complete panel observations accompany the compact question-led main text. Shared defaults retain their actual position identities.

Breadth: complete two-sided endpoints

Input	P: U / L	PS: U / L	GI-TBC: U / L
K-15-S	0.592265 / 0.527663	0.592265 / 0.520583	0.592265 / 0.592265
X-15-B	0 / 0	0 / 0	0 / 0
UC-B20-B	0.577333 / 0.577333	0.577333 / 0.577333	0.577333 / 0.577333
K-20-S	0.727702 / 0.541868	0.775213 / 0.541233	0.716807 / 0.705356
K-35-U	0.664747 / 0.335556	0.767457 / 0.331922	0.692854 / 0.565766
X-35-B	0 / 0	0 / 0	0 / 0
N-B15-B	0.250494 / 0.250494	0.250494 / 0.250494	0.250494 / 0.250494
N-X15-S	0.628986 / 0.628986	0.628986 / 0.628986	0.628986 / 0.628986
N-C20-U	0.248551 / 0.217719	0.252309 / 0.214733	0.245505 / 0.245505
N-X20-B	0 / 0	0 / 0	0 / 0
N-B35-S	0.844874 / 0.371908	0.486013 / 0.373343	0.450292 / 0.389311
N-C35-B	0 / 0	0 / 0	0 / 0

Positive-resource GI-TBC operating points

Configuration	G / P_{avg} / S	Returned units	Max duration / T	Status
R-B20-S-T1	0.216444 /0.264291 /17.2599	0	0.999851	C
R-B20-S-T2	0.0819181 /0.116555 /17.4317	0	0.999816	C
R-X20-S-T1	0.314652 /0.330673 /14.5762	1	0.999834	C
R-X20-S-T2	0.206001 /0.228795 /15.7226	0	0.997641	C
R-B35-S-T1	0.285367 /0.30615 /29.2099	2	0.994109	open
R-B35-S-T2	0.181545 /0.163098 /29.8127	3	0.996291	open
R-X35-S-T1	0.268135 /0.324055 /28.7591	1	0.999456	open
R-X35-S-T2	0.18255 /0.220722 /28.2238	0	0.998568	open

Objective weights: all methods and decompositions

Configuration	ρ	Method	G / P_{avg}	U / L	Certificate
R-B20-S-T1	1	P	0.239416 / 0.300668	0.540085 / 0.358158	open
R-B20-S-T1	1	PS	0.222348 / 0.264291	0.486639 / 0.365324	open
R-B20-S-T1	1	GI-TBC	0.216444 / 0.264291	0.480735 / 0.480735	C
R-X35-S-T2	1	PS	0.194085 / 0.210482	0.404567 / 0.203817	open
R-X35-S-T2	1	GI-TBC	0.18255 / 0.220722	0.403272 / 0.210887	open
R-X35-S-T2	1	P	0.205654 / 0.284863	0.490517 / 0.201288	open
R-B20-S-T1	0.5	P	0.223002 / 0.314774	0.380389 / 0.229542	open
R-B20-S-T1	0.5	PS	0.213456 / 0.268003	0.347458 / 0.240479	open
R-B20-S-T1	0.5	GI-TBC	0.213456 / 0.268003	0.347458 / 0.331864	open
R-B20-S-T1	2	P	0.232861 / 0.262064	0.756988 / 0.610312	open
R-B20-S-T1	2	PS	0.217549 / 0.263549	0.744646 / 0.616106	open
R-B20-S-T1	2	GI-TBC	0.217549 / 0.263549	0.744646 / 0.744646	C
R-X35-S-T2	0.5	PS	0.136611 / 0.242041	0.257631 / 0.108019	open
R-X35-S-T2	0.5	GI-TBC	0.137132 / 0.237386	0.255825 / 0.122332	open
R-X35-S-T2	0.5	P	0.141354 / 0.239248	0.260978 / 0.108223	open
R-X35-S-T2	2	PS	0.198468 / 0.206712	0.611892 / 0.363572	open
R-X35-S-T2	2	GI-TBC	0.148459 / 0.188047	0.524553 / 0.388438	open
R-X35-S-T2	2	P	0.203202 / 0.20862	0.620443 / 0.36178	open

Limited Seed 1: complete main triplets

Role	Method	Status	Own T_{cert} (s)	U / L	Production (s)
K-15-S	P	open	n/a	0.592265 /0.529115	571.412
K-15-S	PS	open	n/a	0.592265 /0.53228	571.362
K-15-S	GI-TBC	C	115.444	0.592265 /0.592265	115.444
R-B20-S-T1	P	open	n/a	0.493224 /0.354626	1171.09
R-B20-S-T1	PS	open	n/a	0.480735 /0.367482	1171.18
R-B20-S-T1	GI-TBC	C	656.734	0.480735 /0.480735	656.734
UC-B20-B	P	C	314.513	0.577333 /0.577333	314.513
UC-B20-B	PS	C	125.391	0.577333 /0.577333	125.391
UC-B20-B	GI-TBC	C	4.0999	0.577333 /0.577333	4.0999
K-35-U	P	open	n/a	0.758852 /0.330574	2371.17
K-35-U	PS	open	n/a	0.712648 /0.335095	2371.03
K-35-U	GI-TBC	open	n/a	0.668358 /0.55478	2371

Limited Seed 1 AM observations

Seed 1 limited AM repeat

Role	τ_{AM}	Max gate score	Actions	Production (s)
K-15-S	0.04	0.000356687	native-target:1, exact-close:1	114.938
K-15-S	0.08	0.000356687	native-target:1, exact-close:1	115.444
K-15-S	0.16	0.000356687	native-target:1, exact-close:1	115.503
UC-B20-B	0.04	0.00031863	split:3, native-target:1, exact-close:1	4.08256
UC-B20-B	0.08	0.00031863	split:3, native-target:1, exact-close:1	4.0999
UC-B20-B	0.16	0.00031863	split:3, native-target:1, exact-close:1	4.0657

Seed 0 main mechanism comparison

Contrast	Role	Root LP optimum	Production (s)	Status
GI-TBC	K-15-S	0.167137	112.769	C
GI-TBC-R	K-15-S	0.167137	112.649	C
minus A/B	K-15-S	0.167016	128.325	C
minus C_R	K-15-S	0.167137	75.1064	C
minus C_G	K-15-S	0.167137	143.15	C
GI-TBC	UC-B20-B	0.479076	4.14897	C
GI-TBC-R	UC-B20-B	0.479076	1.87206	C
minus A/B	UC-B20-B	0.479076	4.18619	C
minus C_R	UC-B20-B	0.479076	4.91775	C
minus C_G	UC-B20-B	0.479076	3.34912	C
GI-TBC	K-20-S	0.195149	1172.19	open
GI-TBC-R	K-20-S	0.195149	1172.22	open
minus A/B	K-20-S	0.193825	1172.12	open
minus C_R	K-20-S	0.195149	1171.91	open
minus C_G	K-20-S	0.195149	1171.96	open
GI-TBC	K-35-U	0.200178	2371.15	open
GI-TBC-R	K-35-U	0.200178	2370.99	open
minus A/B	K-35-U	0.200178	2372.38	open
minus C_R	K-35-U	0.200178	2370.97	open
minus C_G	K-35-U	0.200178	2370.98	open

Seed 1 limited mechanism repeat

Contrast	Role	Root LP optimum	Production (s)	Status
GI-TBC	K-15-S	0.167137	115.444	C
GI-TBC-R	K-15-S	0.167137	113.58	C
minus A/B	K-15-S	0.167016	93.6997	C
minus C_R	K-15-S	0.167137	132.475	C
minus C_G	K-15-S	0.167137	99.6006	C
GI-TBC	UC-B20-B	0.479076	4.0999	C
GI-TBC-R	UC-B20-B	0.479076	1.95408	C
minus A/B	UC-B20-B	0.479076	4.46646	C
minus C_R	UC-B20-B	0.479076	4.60284	C
minus C_G	UC-B20-B	0.479076	2.95877	C

Position / study	Input / Seed	Method	Status	U	L	Production / verification / total s
1 /B1	K-15-S /0	P	O	0.592265	0.527663	571.702 /142.568 /714.27
2 /B1	K-15-S /0	PS	O	0.592265	0.520583	571.245 /2.27522 /573.52
3 /B1	K-15-S /0	GI-TBC	C	0.592265	0.592265	112.769 /3.77037 /116.54
4 /B1	X-15-B /0	PS	C	0	0	2.46104 /0.365936 /2.82698
5 /B1	X-15-B /0	GI-TBC	C	0	0	2.55662 /0.645774 /3.2024
6 /B1	X-15-B /0	P	C	0	0	7.0233 /0.248991 /7.2723
7 /B1	UC-B20-B /0	GI-TBC	C	0.577333	0.577333	4.14897 /2.347 /6.49597
8 /B1	UC-B20-B /0	P	C	0.577333	0.577333	315.403 /1.24106 /316.644
9 /B1	UC-B20-B /0	PS	C	0.577333	0.577333	236.091 /1.30849 /237.399
10 /B1	K-20-S /0	P	O	0.727702	0.541868	1171.16 /1.44439 /1172.61
11 /B1	K-20-S /0	PS	O	0.775213	0.541233	1171.21 /1.5361 /1172.74
12 /B1	K-20-S /0	GI-TBC	O	0.716807	0.705356	1172.19 /61.1438 /1233.33
13 /B1	K-35-U /0	PS	O	0.767457	0.331922	2371 /1.72964 /2372.73
14 /B1	K-35-U /0	GI-TBC	O	0.692854	0.565766	2371.15 /3.80005 /2374.95
15 /B1	K-35-U /0	P	O	0.664747	0.335556	2371.06 /0.722418 /2371.78
16 /B1	X-35-B /0	GI-TBC	C	0	0	17.9046 /3.63609 /21.5407
17 /B1	X-35-B /0	P	C	0	0	158.585 /0.596178 /159.181
18 /B1	X-35-B /0	PS	C	0	0	7.45014 /1.38966 /8.8398
19 /B1	N-B15-B /0	P	C	0.250494	0.250494	279.663 /1.67388 /281.337
20 /B1	N-B15-B /0	PS	C	0.250494	0.250494	306.307 /1.67192 /307.979
21 /B1	N-B15-B /0	GI-TBC	C	0.250494	0.250494	24.0684 /0.790358 /24.8587

Position / study	Input / Seed	Method	Status	U	L	Production / verification / total s
22 /B1	N-X15-S /0	PS	C	0.628986	0.628986	401.931 /3.09583 /405.027
23 /B1	N-X15-S /0	GI-TBC	C	0.628986	0.628986	10.2683 /0.739441 /11.0077
24 /B1	N-X15-S /0	P	C	0.628986	0.628986	538.867 /3.46182 /542.329
25 /B1	N-C20-U /0	GI-TBC	C	0.245505	0.245505	265.529 /4.06871 /269.598
26 /B1	N-C20-U /0	P	O	0.248551	0.217719	1171.18 /1.83559 /1173.01
27 /B1	N-C20-U /0	PS	O	0.252309	0.214733	1171.14 /11.7494 /1182.89
28 /B1	N-X20-B /0	P	C	0	0	24.0892 /0.306578 /24.3958
29 /B1	N-X20-B /0	PS	C	0	0	6.08515 /0.486901 /6.57205
30 /B1	N-X20-B /0	GI-TBC	C	0	0	7.45537 /1.0786 /8.53397
31 /B1	N-B35-S /0	PS	O	0.486013	0.373343	2371.01 /1.74441 /2372.76
32 /B1	N-B35-S /0	GI-TBC	O	0.450292	0.389311	2370.98 /3.84726 /2374.82
33 /B1	N-B35-S /0	P	O	0.844874	0.371908	2371.11 /0.661396 /2371.77
34 /B1	N-C35-B /0	GI-TBC	C	0	0	59.6234 /3.71224 /63.3357
35 /B1	N-C35-B /0	P	C	0	0	397.807 /0.653354 /398.461
36 /B1	N-C35-B /0	PS	C	0	0	154.668 /1.42879 /156.097
37 /B2	R-B20-S-T1 /0	P	O	0.540085	0.358158	1171.18 /0.980204 /1172.16
38 /B2	R-B20-S-T1 /0	PS	O	0.486639	0.365324	1171.29 /1.3497 /1172.64
39 /B2	R-B20-S-T1 /0	GI-TBC	C	0.480735	0.480735	784.143 /18.1789 /802.322
40 /B2	R-B20-S-T2 /0	PS	O	0.208465	0.146203	1171.14 /1.19298 /1172.33
41 /B2	R-B20-S-T2 /0	GI-TBC	C	0.198473	0.198473	538.603 /5.73802 /544.341
42 /B2	R-B20-S-T2 /0	P	O	0.269095	0.141262	1171.19 /0.766113 /1171.96

Position / study	Input / Seed	Method	Status	U	L	Production / verification / total s
43 /B2	R-X20-S-T1 /0	GI-TBC	C	0.645325	0.645325	20.5065 /1.08205 /21.5885
44 /B2	R-X20-S-T1 /0	P	O	0.645325	0.589197	1171.57 /5.00163 /1176.57
45 /B2	R-X20-S-T1 /0	PS	O	0.645325	0.590359	1171.69 /4.9291 /1176.62
46 /B2	R-X20-S-T2 /0	P	O	0.476731	0.291101	1171.1 /0.410932 /1171.51
47 /B2	R-X20-S-T2 /0	PS	O	0.51972	0.28447	1171.18 /0.839506 /1172.02
48 /B2	R-X20-S-T2 /0	GI-TBC	C	0.434796	0.434796	337.305 /2.72864 /340.034
49 /B2	R-B35-S-T1 /0	PS	O	0.631765	0.334519	2371.04 /1.73506 /2372.77
50 /B2	R-B35-S-T1 /0	GI-TBC	O	0.591518	0.455904	2376.07 /5.60112 /2381.67
51 /B2	R-B35-S-T1 /0	P	O	0.606311	0.337002	2372.2 /0.733367 /2372.93
52 /B2	R-B35-S-T2 /0	GI-TBC	O	0.344643	0.218986	2371.04 /3.76611 /2374.8
53 /B2	R-B35-S-T2 /0	P	O	0.471637	0.154376	2371.07 /0.692204 /2371.77
54 /B2	R-B35-S-T2 /0	PS	O	0.438291	0.155416	2371.03 /1.71384 /2372.75
55 /B2	R-X35-S-T1 /0	P	O	0.655713	0.296009	2371.09 /0.694498 /2371.79
56 /B2	R-X35-S-T1 /0	PS	O	0.593231	0.298839	2371.01 /4.60794 /2375.62
57 /B2	R-X35-S-T1 /0	GI-TBC	O	0.59219	0.463358	2379.12 /3.67396 /2382.79
58 /B2	R-X35-S-T2 /0	PS	O	0.404567	0.203817	2370.99 /1.72903 /2372.71
59 /B2	R-X35-S-T2 /0	GI-TBC	O	0.403272	0.210887	2371.09 /3.72914 /2374.82
60 /B2	R-X35-S-T2 /0	P	O	0.490517	0.201288	2371.02 /0.664748 /2371.68
61 /B3	R-B20-S-T1-rho0.5 /0	P	O	0.380389	0.229542	1171.17 /0.87512 /1172.05
62 /B3	R-B20-S-T1-rho0.5 /0	PS	O	0.347458	0.240479	1171.16 /1.17614 /1172.33
63 /B3	R-B20-S-T1-rho0.5 /0	GI-TBC	O	0.347458	0.331864	1171.29 /5.89166 /1177.18

Position / study	Input / Seed	Method	Status	U	L	Production / verification / total s
64 /B3	R-B20-S-T1-rho2 /0	P	O	0.756988	0.610312	1171.15 /1.29992 /1172.45
65 /B3	R-B20-S-T1-rho2 /0	PS	O	0.744646	0.616106	1171.34 /1.7534 /1173.1
66 /B3	R-B20-S-T1-rho2 /0	GI-TBC	C	0.744646	0.744646	309.113 /8.59128 /317.704
67 /B3	R-X35-S-T2-rho0.5 /0	PS	O	0.257631	0.108019	2371.05 /1.73565 /2372.78
68 /B3	R-X35-S-T2-rho0.5 /0	GI-TBC	O	0.255825	0.122332	2371.1 /3.68103 /2374.78
69 /B3	R-X35-S-T2-rho0.5 /0	P	O	0.260978	0.108223	2371.1 /0.679667 /2371.78
70 /B3	R-X35-S-T2-rho2 /0	PS	O	0.611892	0.363572	2371.03 /1.71701 /2372.74
71 /B3	R-X35-S-T2-rho2 /0	GI-TBC	O	0.524553	0.388438	2370.96 /3.7818 /2374.74
72 /B3	R-X35-S-T2-rho2 /0	P	O	0.620443	0.36178	2371.09 /0.700077 /2371.79
73 /C1	K-15-S /0	AM .04	C	0.592265	0.592265	113.062 /3.77321 /116.835
74 /C1	K-15-S /0	AM .16	C	0.592265	0.592265	113.315 /3.74081 /117.056
75 /C1	K-20-S /0	AM .04	O	0.716807	0.705366	1172.26 /61.3126 /1233.57
76 /C1	K-20-S /0	AM .16	O	0.716807	0.705386	1172.26 /62.835 /1235.09
77 /C1	UC-B20-B /0	AM .04	C	0.577333	0.577333	4.21966 /2.27593 /6.49559
78 /C1	UC-B20-B /0	AM .16	C	0.577333	0.577333	4.08117 /2.26691 /6.34809
79 /C1	K-35-U /0	AM .04	O	0.692854	0.565893	2371.02 /3.76777 /2374.79
80 /C1	K-35-U /0	AM .16	O	0.692854	0.566106	2371.03 /3.79054 /2374.82
81 /C2	K-15-S /0	GI-TBC-R	C	0.592265	0.592265	112.649 /3.34597 /115.995
82 /C2	K-15-S /0	minus A/B	C	0.592265	0.592265	128.325 /3.61312 /131.938
83 /C2	K-15-S /0	minus C_R	C	0.592265	0.592265	75.1064 /2.39997 /77.5064
84 /C2	K-15-S /0	minus C_G	C	0.592265	0.592265	143.15 /4.47363 /147.624

Position / study	Input / Seed	Method	Status	U	L	Production / verification / total s
85 /C2	UC-B20-B /0	minus A/B	C	0.577333	0.577333	4.18619 /2.24829 /6.43448
86 /C2	UC-B20-B /0	minus C_R	C	0.577333	0.577333	4.91775 /2.28857 /7.20632
87 /C2	UC-B20-B /0	minus C_G	C	0.577333	0.577333	3.34912 /1.70325 /5.05237
88 /C2	UC-B20-B /0	GI-TBC-R	C	0.577333	0.577333	1.87206 /0.407894 /2.27996
89 /C2	K-20-S /0	minus C_R	O	0.716807	0.703444	1171.91 /36.6745 /1208.59
90 /C2	K-20-S /0	minus C_G	O	0.716807	0.705296	1171.96 /43.4998 /1215.46
91 /C2	K-20-S /0	GI-TBC-R	O	0.716807	0.706405	1172.22 /61.8919 /1234.12
92 /C2	K-20-S /0	minus A/B	O	0.716807	0.704128	1172.12 /41.7358 /1213.86
93 /C2	K-35-U /0	minus C_G	O	0.666262	0.55098	2370.98 /2.63835 /2373.62
94 /C2	K-35-U /0	GI-TBC-R	O	0.692854	0.566106	2370.99 /6.52797 /2377.52
95 /C2	K-35-U /0	minus A/B	O	0.654639	0.564355	2372.38 /3.79162 /2376.17
96 /C2	K-35-U /0	minus C_R	O	0.689763	0.536996	2370.97 /3.56291 /2374.53
97 /D2-main	K-15-S /1	P	O	0.592265	0.529115	571.412 /3.04329 /574.455
98 /D2-main	K-15-S /1	PS	O	0.592265	0.53228	571.362 /3.10724 /574.469
99 /D2-main	K-15-S /1	GI-TBC	C	0.592265	0.592265	115.444 /4.17556 /119.62
100 /D2-main	UC-B20-B /1	PS	C	0.577333	0.577333	125.391 /1.15372 /126.545
101 /D2-main	UC-B20-B /1	GI-TBC	C	0.577333	0.577333	4.0999 /2.28866 /6.38856
102 /D2-main	UC-B20-B /1	P	C	0.577333	0.577333	314.513 /1.42972 /315.943
103 /D2-main	R-B20-S-T1 /1	GI-TBC	C	0.480735	0.480735	656.734 /19.5677 /676.302
104 /D2-main	R-B20-S-T1 /1	P	O	0.493224	0.354626	1171.09 /0.941944 /1172.03
105 /D2-main	R-B20-S-T1 /1	PS	O	0.480735	0.367482	1171.18 /1.33337 /1172.51

Position / study	Input / Seed	Method	Status	U	L	Production / verification / total s
106 /D2-main	K-35-U /1	P	O	0.758852	0.330574	2371.17 /0.731285 /2371.91
107 /D2-main	K-35-U /1	PS	O	0.712648	0.335095	2371.03 /1.7395 /2372.77
108 /D2-main	K-35-U /1	GI-TBC	O	0.668358	0.55478	2371 /3.76418 /2374.76
109 /D2-AM	K-15-S /1	AM .04	C	0.592265	0.592265	114.938 /4.23062 /119.169
110 /D2-AM	K-15-S /1	AM .16	C	0.592265	0.592265	115.503 /4.18745 /119.691
115 /D2-AM	UC-B20-B /1	AM .04	C	0.577333	0.577333	4.08256 /2.29383 /6.37639
116 /D2-AM	UC-B20-B /1	AM .16	C	0.577333	0.577333	4.0657 /2.28894 /6.35465
111 /D2-mechanism	K-15-S /1	GI-TBC-R	C	0.592265	0.592265	113.58 /3.78707 /117.367
112 /D2-mechanism	K-15-S /1	minus A/B	C	0.592265	0.592265	93.6997 /2.95424 /96.654
113 /D2-mechanism	K-15-S /1	minus C_R	C	0.592265	0.592265	132.475 /4.49508 /136.97
114 /D2-mechanism	K-15-S /1	minus C_G	C	0.592265	0.592265	99.6006 /2.39181 /101.992
117 /D2-mechanism	UC-B20-B /1	GI-TBC-R	C	0.577333	0.577333	1.95408 /0.416184 /2.37026
118 /D2-mechanism	UC-B20-B /1	minus A/B	C	0.577333	0.577333	4.46646 /2.28714 /6.7536
119 /D2-mechanism	UC-B20-B /1	minus C_R	C	0.577333	0.577333	4.60284 /2.24667 /6.8495
120 /D2-mechanism	UC-B20-B /1	minus C_G	C	0.577333	0.577333	2.95877 /1.70396 /4.66273

Historical breadth/resource study: detailed interpretation

All 120 registered method observations appear above. The original fixed report retains the study's timing, native-effort, action and eligibility diagnostics. The current main text integrates its conclusions with later evidence without pooling the study denominators.

Preserved historical supplement (R135 observations retained; headings nested and figure links pinned)

Supplement: complete evidence and formulation analysis

This supplement retains complete numerical observations and separates evidence versions. C means a qualified certificate; O means open. No open cap is substituted for a certification time. Displayed bounds are original-objective values; gap is signed U-L. Full-precision CSV/JSON files and finite raw carriers are the numerical authorities.

S1. R134 final implementation: every method position

Position / problem	Seed / repeat	method	proof	U	L	production seconds
C01 SM-B10-B	0 / 1	P	native/outer	0.5358911	0.5358911	1.641208
C02 SM-B10-B	0 / 1	S2	native/outer	0.5358911	0.5358911	0.8573348
C03 SM-B10-B	0 / 2	S2	native/outer	0.5358911	0.5358911	0.774499
C04 SM-B10-B	0 / 2	P	native/outer	0.5358911	0.5358911	1.040874
C05 SM-B10-B	1 / 1	S2	native/outer	0.5358911	0.5358911	0.8048351
C06 SM-B10-B	1 / 1	P	native/outer	0.5358911	0.5358911	1.043295
C07 SM-B10-B	1 / 2	P	native/outer	0.5358911	0.5358911	1.016209
C08 SM-B10-B	1 / 2	S2	native/outer	0.5358911	0.5358911	0.7731281
C09 K-15-S	0 / 1	P	O	0.5922649	0.5274148	571.0901
C10 K-15-S	0 / 1	S2	native/outer	0.5922649	0.5922649	112.935
C11 K-15-S	0 / 1	PS	O	0.5922649	0.5202155	571.0177
C12 K-15-S	1 / 1	PS	O	0.5922649	0.5318726	571.178
C13 K-15-S	1 / 1	S2	native/outer	0.5922649	0.5922649	115.0206
C14 K-15-S	1 / 1	P	O	0.5922649	0.5289006	571.1291
C15 UC-B20-B	0 / 1	P	native/outer	0.5773331	0.5773331	319.06
C16 UC-B20-B	0 / 1	S2	native/outer	0.5773331	0.5773331	3.965715
C17 UC-B20-B	1 / 1	S2	native/outer	0.5773331	0.5773331	3.82069
C18 UC-B20-B	1 / 1	P	native/outer	0.5773331	0.5773331	318.3774
C19 K-35-U	0 / 1	P	O	0.6647466	0.3355012	2370.863
C20 K-35-U	0 / 1	S2	O	0.6928544	0.5649415	2370.942
C21 K-35-U	1 / 1	S2	O	0.6683583	0.554272	2370.785
C22 K-35-U	1 / 1	P	O	0.7588516	0.3305483	2370.844
C23 X-35-U	0 / 1	P	O	0.01626456	6.938894e-18	2370.864
C24 X-35-U	0 / 1	S2	independent zero	0	0	120.2567
C25 X-35-U	1 / 1	S2	independent zero	0	0	452.8414
C26 X-35-U	1 / 1	P	independent zero	0	0	2064.949
C27 X-35-B	0 / 1	P	independent zero	0	0	157.9542
C28 X-35-B	0 / 1	PS	independent zero	0	0	7.250546
C29 X-35-B	0 / 1	S2	independent zero	0	0	17.60603
C30 X-35-B	1 / 1	S2	independent zero	0	0	18.27745
C31 X-35-B	1 / 1	PS	independent zero	0	0	7.195779
C32 X-35-B	1 / 1	P	independent zero	0	0	50.15055

S2. R134 complete cost and paired outcomes

Position	production	postverification	total	certification
C01	1.641208	46.64563	48.28684	1.641208
C02	0.8573348	0.2301405	1.087475	0.8573348
C03	0.774499	0.2266129	1.001112	0.774499
C04	1.040874	0.2392841	1.280158	1.040874
C05	0.8048351	0.2269228	1.031758	0.8048351
C06	1.043295	0.2257164	1.269012	1.043295
C07	1.016209	0.2338855	1.250095	1.016209
C08	0.7731281	0.228319	1.001447	0.7731281
C09	571.0901	2.427311	573.5174	-
C10	112.935	3.758351	116.6933	112.935
C11	571.0177	2.21719	573.2349	-
C12	571.178	3.128258	574.3063	-
C13	115.0206	4.09868	119.1193	115.0206
C14	571.1291	2.978428	574.1075	-
C15	319.06	1.243415	320.3035	319.06
C16	3.965715	2.202237	6.167952	3.965715
C17	3.82069	2.235158	6.055848	3.82069
C18	318.3774	1.431066	319.8085	318.3774
C19	2370.863	0.7067805	2371.57	-
C20	2370.942	3.665049	2374.607	-
C21	2370.785	3.616341	2374.401	-
C22	2370.844	0.7103621	2371.554	-
C23	2370.864	0.5900696	2371.454	-
C24	120.2567	3.450335	123.707	120.2567
C25	452.8414	3.463397	456.3048	452.8414
C26	2064.949	0.590913	2065.54	2064.949
C27	157.9542	0.5901521	158.5443	157.9542
C28	7.250546	1.373965	8.624511	7.250546
C29	17.60603	3.549094	21.15513	17.60603
C30	18.27745	3.510039	21.78749	18.27745
C31	7.195779	1.370528	8.566307	7.195779
C32	50.15055	0.5871859	50.73773	50.15055

Problem / Seed / repeat	comparison	class	direction	substantive	S2/control cert seconds
SM-B10-B / 0 / 1	S2/P	BOTH_CERTIFIED	Win	False	0.8573348 / 1.641208
SM-B10-B / 0 / 2	S2/P	BOTH_CERTIFIED	Win	False	0.774499 / 1.040874
SM-B10-B / 1 / 1	S2/P	BOTH_CERTIFIED	Win	False	0.8048351 / 1.043295
SM-B10-B / 1 / 2	S2/P	BOTH_CERTIFIED	Win	False	0.7731281 / 1.016209
K-15-S / 0 / 1	S2/P	LEFT_ONLY_CERTIFIED	Win	-	112.935 / -
K-15-S / 0 / 1	S2/PS	LEFT_ONLY_CERTIFIED	Win	-	112.935 / -
K-15-S / 1 / 1	S2/P	LEFT_ONLY_CERTIFIED	Win	-	115.0206 / -
K-15-S / 1 / 1	S2/PS	LEFT_ONLY_CERTIFIED	Win	-	115.0206 / -
UC-B20-B / 0 / 1	S2/P	BOTH_CERTIFIED	Win	True	3.965715 / 319.06
UC-B20-B / 1 / 1	S2/P	BOTH_CERTIFIED	Win	True	3.82069 / 318.3774
K-35-U / 0 / 1	S2/P	BOTH_OPEN	UNDETERMINED	-	- / -
K-35-U / 1 / 1	S2/P	BOTH_OPEN	UNDETERMINED	-	- / -
X-35-U / 0 / 1	S2/P	LEFT_ONLY_CERTIFIED	Win	-	120.2567 / -
X-35-U / 1 / 1	S2/P	BOTH_CERTIFIED	Win	True	452.8414 / 2064.949
X-35-B / 0 / 1	S2/P	BOTH_CERTIFIED	Win	True	17.60603 / 157.9542
X-35-B / 0 / 1	S2/PS	BOTH_CERTIFIED	Lose	True	17.60603 / 7.250546
X-35-B / 1 / 1	S2/P	BOTH_CERTIFIED	Win	True	18.27745 / 50.15055
X-35-B / 1 / 1	S2/PS	BOTH_CERTIFIED	Lose	True	18.27745 / 7.195779

Every adverse direction is retained. In particular X-35-B favors independently paid-start compact at both Seeds. R134 C01 had one failed postreader metadata access, repaired read-only using the same sealed native run. Its real verification delay remains in the costs. Native-source rejection remains visible even when an independent zero argument certifies the original problem.

S3. Six within-instance weight points

Problem	lambda	effective rho	G	P average	F	U-L	certificate
K-15-S	0.075	0.7105028	0.2023697	0.276702	0.3989673	5.551115e-16	True
K-15-S	0.15	1.421006	0.2221466	0.2604622	0.5922649	3.017571e-09	True
K-15-S	0.3	2.842011	0.2254327	0.2585884	0.9603438	2.220446e-16	True
UC-B20-B	0.075	0.88725	0.1708331	0.2290786	0.3740831	1.110223e-16	True
UC-B20-B	0.15	1.7745	0.1708331	0.2290786	0.5773331	2.220446e-16	True
UC-B20-B	0.3	3.549	0.1708331	0.2290786	0.9838331	4.440892e-16	True

The same-feasible-set relations use accepted original-objective errors. Station inventories, target-under/equal/over counts, every vehicle operation, returns, prefix peaks and durations remain in the fixed R134 operations tables. No new weight run is added here.

S4. AP: preregistration, every entered position and stage decision The plan fixes seven inputs, 16 pairs and 32 arms: ten first-stage arms with 8,760 cap-seconds and 22 conditional arms with 14,760 cap-seconds. The two methods use the same PE and complete S2 algorithm; only the AP flag differs. Seeds, repeat orders, caps and inputs are fixed in experiment_plan.json and both matrix manifests before results. D13 uses the original physical input and T=3,600; historical subinterval times are not new whole-method controls.

Both preregistered stages were entered and all 32 positions completed, giving 16 matched pairs across seven known structural/protection inputs. The first-stage decision used all ten sealed positions and their original-objective endpoint signal. No position, Seed, order or cap was replaced after observing outcomes. The plan retained 8,760 plus 14,760 cap-seconds; actual costs are reported separately. Every ordinary adverse and open observation remains in the evidence.

Position / problem	Seed / repeat	variant	C/O	U	L	U-L	production
C01 SM-B10-B	0 / 1	S2	C	0.5358911	0.5358911	0	1.188632
C02 SM-B10-B	0 / 1	AP	C	0.5358911	0.5358911	0	0.8122061
C03 SM-B10-B	0 / 2	AP	C	0.5358911	0.5358911	0	0.8224663
C04 SM-B10-B	0 / 2	S2	C	0.5358911	0.5358911	0	0.8634327
C05 K-20-S	0 / 1	S2	O	0.7168065	0.705326	0.01148059	1171.98
C06 K-20-S	0 / 1	AP	O	0.7168065	0.7061352	0.01067133	1172.016
C07 K-35-U	0 / 1	AP	O	0.6536712	0.5589106	0.09476064	2370.804
C08 K-35-U	0 / 1	S2	O	0.6928544	0.5659761	0.1268782	2370.742
C09 R55-D13	0 / 1	S2	O	2.443403	2.392829	0.05057454	570.9143
C10 R55-D13	0 / 1	AP	O	2.443403	2.393284	0.05011877	570.7733
D01 K-20-S	1 / 1	AP	O	0.7168065	0.7062272	0.01057934	1171.918
D02 K-20-S	1 / 1	S2	O	0.7168065	0.7016355	0.01517106	1171.755
D03 K-35-U	1 / 1	S2	O	0.6683583	0.5547997	0.1135585	2370.842
D04 K-35-U	1 / 1	AP	O	0.6508356	0.5403999	0.1104357	2370.921
D05 R55-D13	1 / 1	AP	O	2.443403	2.391342	0.05206127	570.787
D06 R55-D13	1 / 1	S2	O	2.443403	2.397667	0.04573607	570.7295
D07 K-15-S	0 / 1	S2	C	0.5922649	0.5922649	3.017571e-09	112.1131
D08 K-15-S	0 / 1	AP	C	0.5922649	0.5922649	7.771561e-16	149.3096
D09 K-15-S	1 / 1	AP	C	0.5922649	0.5922649	5.440743e-10	115.3094
D10 K-15-S	1 / 1	S2	C	0.5922649	0.5922649	2.675637e-14	113.8503
D11 UC-B20-B	0 / 1	AP	C	0.5773331	0.5773331	2.220446e-16	4.2052
D12 UC-B20-B	0 / 1	S2	C	0.5773331	0.5773331	2.220446e-16	3.93096
D13 UC-B20-B	1 / 1	S2	C	0.5773331	0.5773331	2.220446e-16	3.868074
D14 UC-B20-B	1 / 1	AP	C	0.5773331	0.5773331	2.220446e-16	3.795526
D15 X-35-B	0 / 1	S2	C	0	0	0	17.5887
D16 X-35-B	0 / 1	AP	C	0	0	0	79.97383
D17 X-35-B	1 / 1	AP	C	0	0	0	17.46286
D18 X-35-B	1 / 1	S2	C	0	0	0	18.1777
D19 SM-B10-B	1 / 1	AP	C	0.5358911	0.5358911	0	0.7549884
D20 SM-B10-B	1 / 1	S2	C	0.5358911	0.5358911	0	0.7838148
D21 SM-B10-B	1 / 2	S2	C	0.5358911	0.5358911	0	0.7996461
D22 SM-B10-B	1 / 2	AP	C	0.5358911	0.5358911	0	0.7379351

Position	postverification	total	Work	nodes	root LP / child LP / MIP seconds	splits / target MIP
C01	0.2379024	1.426535	0.001649864	0	0.001999855 / 0 / 0	0 / 0
C02	0.2285397	1.040746	0.00176573	0	0 / 0 / 0	0 / 0
C03	0.2378315	1.060298	0.00176573	0	0 / 0 / 0	0 / 0
C04	0.2293777	1.09281	0.001649864	0	0.0150001 / 0 / 0	0 / 0
C05	60.42393	1232.404	1896.819	447343	0.1429999 / 0.1889999 / 1168.313	0 / 1
C06	56.82964	1228.845	1892.122	476720	0.1630001 / 0.2890003 / 1168.194	0 / 1
C07	3.863976	2374.668	5076.742	17193	1.123 / 2.62 / 2361.657	0 / 1
C08	3.79571	2374.538	5054.465	18947	0.3409998 / 0.6279998 / 2364.604	0 / 0
C09	1.491045	572.4053	1100.767	11576	0.1790001 / 0.4560001 / 567.911	0 / 1
C10	2.786274	573.5596	1110.557	12542	0.4390001 / 0.9610002 / 566.066	0 / 1
D01	49.69095	1221.609	1921.723	432818	0.198 / 0.296 / 1168.14	0 / 1
D02	33.35354	1205.109	1870.04	415820	0.132 / 0.2050002 / 1168.304	0 / 1
D03	3.740974	2374.583	5131.308	18687	0.2610002 / 0.582 / 2364.694	0 / 0
D04	3.857094	2374.778	4953.391	14623	1.35 / 2.791 / 2361.244	0 / 1
D05	1.533851	572.3209	1109.417	14028	0.214 / 0.4380002 / 567.915	0 / 1
D06	1.487932	572.2175	1074.049	13351	0.221 / 0.4369998 / 567.918	0 / 1
D07	3.737104	115.8502	160.9257	48701	0.07599998 / 0.1179998 / 110.159	0 / 1
D08	5.286434	154.5961	213.6619	60497	0.09599996 / 0.1199999 / 147.073	0 / 1
D09	3.854699	119.1641	168.8898	46417	0.1040001 / 0.1099999 / 113.26	0 / 1
D10	4.131817	117.9821	161.8277	42579	0.06700015 / 0.1040001 / 111.876	0 / 1
D11	2.267362	6.472562	1.177472	3	0.01699996 / 0.1159997 / 0.7329998	3 / 0
D12	2.273585	6.204545	0.9594441	2	0.01600003 / 0.1400001 / 0.4689999	3 / 1
D13	2.291663	6.159737	0.87248	2	0.01200008 / 0.1249998 / 0.4329998	3 / 1
D14	2.252971	6.048497	0.7558022	1	0.02799988 / 0.0940001 / 0.3959999	3 / 0

Position	postverification	total	Work	nodes	root LP / child LP / MIP seconds	splits / target MIP
D15	3.648402	21.2371	27.01372	1	0.4000001 / 0.7619998 / 10.74	0 / 0
D16	3.601761	83.57559	158.1958	681	0.503 / 0.987 / 72.767	0 / 0
D17	3.590207	21.05307	27.30886	1	0.599 / 0.9449999 / 10.26	0 / 0
D18	3.59368	21.77138	27.83273	3	0.3679998 / 0.6400001 / 11.497	0 / 0
D19	0.2254864	0.9804748	0.00176573	0	0.002000093 / 0 / 0	0 / 0
D20	0.2291984	1.013013	0.001649864	0	0.002000093 / 0 / 0	0 / 0
D21	0.2298623	1.029508	0.001649864	0	0 / 0 / 0	0 / 0
D22	0.2327738	0.9707089	0.00176573	0	0 / 0 / 0	0 / 0

Problem / Seed / repeat	class	AP-S2 cert seconds	AP-S2 U	AP-S2 L	AP-S2 gap
SM-B10-B / 0 / 1	BOTH_CERTIFIED	-0.3764262	0	0	0
SM-B10-B / 0 / 2	BOTH_CERTIFIED	-0.04096647	0	0	0
K-20-S / 0 / 1	BOTH_OPEN	-	0	0.0008092601	-0.0008092601
K-35-U / 0 / 1	BOTH_OPEN	-	-0.03918311	-0.007065539	-0.03211757
R55-D13 / 0 / 1	BOTH_OPEN	-	0	0.0004557676	-0.0004557676
K-20-S / 1 / 1	BOTH_OPEN	-	0	0.004591717	-0.004591717
K-35-U / 1 / 1	BOTH_OPEN	-	-0.01752265	-0.01439987	-0.003122772
R55-D13 / 1 / 1	BOTH_OPEN	-	0	-0.006325205	0.006325205
K-15-S / 0 / 1	BOTH_CERTIFIED	37.19652	0	3.017571e-09	-3.017571e-09
K-15-S / 1 / 1	BOTH_CERTIFIED	1.45907	0	-5.440476e-10	5.440476e-10
UC-B20-B / 0 / 1	BOTH_CERTIFIED	0.2742401	0	0	0
UC-B20-B / 1 / 1	BOTH_CERTIFIED	-0.07254772	0	0	0
X-35-B / 0 / 1	BOTH_CERTIFIED	62.38512	0	0	0
X-35-B / 1 / 1	BOTH_CERTIFIED	-0.7148365	0	0	0
SM-B10-B / 1 / 1	BOTH_CERTIFIED	-0.02882644	0	0	0
SM-B10-B / 1 / 2	BOTH_CERTIFIED	-0.06171107	0	0	0

All 32 preregistered positions completed, with 10/16 certificates for each method. K-20-S remains open with the same U at both Seeds; AP reduces the gaps by about 7% and 30%. K-35-U also remains open: AP improves U at both Seeds, but its qualified L is weaker at both. Its gaps are smaller by about 25% and 2.8%, so the result is a primal/dual trade-off rather than endpoint dominance or faster proof. On the original D13 input both methods remain open at the same U. AP slightly narrows the Seed0 gap but widens the Seed1 gap by about 14%. This is mixed protection evidence, despite the absence of a new certificate loss.

Among the ten both-certified pairs, AP has no substantive time advantage and two substantive adverse differences: K-15-S Seed0 takes 149.31 seconds versus 112.11 for S2, and X-35-B Seed0 takes 79.97 versus 17.59. Their Seed1 differences are small. UC-B20-B remains certified in about four seconds on both sides, and micro repetitions have small absolute differences. Most of the two slowdowns lies in native MIP time, accompanied by higher Work and node counts; LP setup is a small part of the added cost. Complete production, postverification and total clocks, every endpoint and the exposed root/child/MIP costs are retained in Supplement S4.

AP retains the intended numerical root strengthening and improves some complete-search endpoints, but it does not improve certification coverage or establish a reliable complete-time advantage. The substantial Seed0 slowdowns and mixed D13 protection outcome do not justify replacing the accepted S2 method. We retain AP as a default-off research option and keep S2 as the supported main algorithm. The projection result explains retained state information under its stated premises; it does not guarantee a faster native search.

S5. Two incremental AP LPs

Root	S2 reused	IND reused	AP new	AP-IND	AP construction / LP seconds	rows / columns / nonzeros
K-20-S	0.1951492	0.3187585	0.3187585	-5.551115e-17	0.0013385 / 0.1659999	6638 / 3096 / 38737
K-35-U	0.2001777	0.2738577	0.2738577	-6.106227e-16	0.0012526 / 1.416	23625 / 10007 / 164059

Root	AP slack	primal row violation	bound violation	dual violation	max row residual
K-20-S	-6.279699e-16	0	0	4.57967e-16	7.275958e-12
K-35-U	7.806256e-17	0	0	2.078113e-07	1.455192e-11

Each LP adds only the production-audited AP row to the inherited domain, frees all integer types and reoptimizes all auxiliaries. The old S2/IND optima are reused. No new integer solve, cutoff search or TC variation enters this fixed-root comparison. The construction column times Gurobipy row insertion and update; total model export and process costs remain in the qualification and fee records. All production C++ construction is included in the complete-method clocks. Saved physical Start checks are retained. Native OPTIMAL and residuals are numerical observations, not rational optimality proofs.

S6. AP validity, projection and the tested VD-J antecedent The accepted production reference is R134 S2 / ms2, including its own complete H, shared M-B inventory/service representation, VD-P, pair support, controller and proof rules. AP is a default-off research row. It is not a restoration of the older VD-J formulation.

1. State mixing and validity On a legal finite support, let $s_{iy} \geq 0$, $\sum_y s_{iy} = 1$, and $r_i = \sum_y \rho_{iy} s_{iy}$. In the ideal model $\rho_{iy} = y/D_i$. Define

$$\phi_i = \sum_y |\rho_{iy} - 1| s_{iy}, \quad a_i^+ = \sum_y (\rho_{iy} - 1)_+ s_{iy}, \quad a_i^- = \sum_y (1 - \rho_{iy})_+ s_{iy}.$$

Then $\phi_i = a_i^+ + a_i^-$, $r_i - 1 = a_i^+ - a_i^-$, and

$$\phi_i - |r_i - 1| = 2\min(a_i^+, a_i^-) \geq 0.$$

This is a finite convexity/Jensen calculation, not a new general theorem. The difference is zero on one-sided state mass. It measures cancellation at a given mixture, not the objective change after reoptimization. The saved base-point diagnostics reported cancellation at 20/20 K-20-S stations and 31/35 K-35-U stations; after IND, significant cancellation was reported at 0/20 and 3/35. These are reused point diagnostics, distinct from the full reoptimized objective values.

Write $P_e = \sum_i \omega_i e_i$ and $\Phi = \sum_i \omega_i \phi_i$, with nonnegative weights. The stationwise inequalities IND, $e_i \geq \phi_i$, imply the single AP row $P_e \geq \Phi$. Every integer physical fleet has an objective-preserving extension: select its integer inventory state and set $e_i = |Y_i/D_i - 1|$. Thus AP does not remove physical fleets or alter their original objective.

2. A conditional projection result Let x include every variable except e. On a fixed legal domain assume:

1. Outside its own local lower and upper bounds (including the two absolute-value inequalities), e occurs in constraints and the objective only through P_e.
2. Each state penalty is at least every applicable local lower bound and at most the actual finite local upper bound M_i.

Then the original model plus AP and the original model plus IND have identical projections onto (x, P_e).

Proof. IND implies AP. For an AP point define $C = \sum_i \omega_i(M_i - \phi_i)$. Original upper bounds and AP give $0 \leq P_e - \Phi \leq C$. If $C > 0$, set

$$t = (P_e - \Phi)/C, \qquad e_i' = \phi_i + t(M_i - \phi_i).$$

Now $0 \leq t \leq 1$, $\phi_i \leq e_i' \leq M_i$, and $\sum_i \omega_i e_i' = P_e$. All original local lower bounds hold by assumption; every other row and the objective sees the same x, P_e. If $C = 0$, AP and upper bounds give $P_e = \Phi$, so set $e_i' = \phi_i$. Zero weights are harmless in both cases. This constructs the IND extension. □

The conclusion concerns a projection, not each e_i coordinate, and not the VD-J equalities. Independent products $T_{SP,i} \simeq Se_i$, nonaggregate uses of individual e_i, or incompatible local bounds invalidate this proof. Aggregate $W_{SP} \simeq SP_e$ is compatible because the construction preserves P_e.

3. Actual domains and implementation boundary Pure parsing of both inherited roots finds seven global P-type rows and only local absolute-value/cutoff bounds for the other uses of e. No individual $T_{SP,i}$ product is active. Their ideal state supports are compatible with the cutoff bounds.

The actual ratio row loads the binary64 coefficient $c_i = 1/D_i$. AP uses $|c_i y - 1|$ with the same binary64 weights. Correctly rounded fma evaluates $c_i y - 1$ once; moving its absolute value one representable step toward zero supplies a lower bound. Multiplication by the weight and a second step toward zero preserve a lower bound on the exact weighted coefficient. RHS terms at most 10^{-12} may be omitted, which only weakens the row. AP coefficients are printed with full binary64 round-trip precision; the legacy near-one abbreviation is bypassed only for this new row. Construction takes place once while building each model, never as a node audit.

The mathematical theorem describes the ideal expression. In the loaded matrix, separately rounded P coefficients need not be exactly collinear as rational numbers. In K-20-S four local state-deviation maxima exceed the old

local $e_i \le 1$ bound by about 0.56 to 1.11×10^{-16}; K-35-U has no such exception. These do not justify claiming strict rational projection equality for the loaded matrix. The two incremental LPs instead confirm the intended numerical equality under the unchanged policy. No old bound, tolerance, product expression or certificate rule is rewritten.

Default-off exports are byte-identical to the inherited R134 matrices. AP exports differ only by the added row; bounds, types, objective and all other rows remain unchanged. All 990 state coefficients in the two roots pass an independent exact-Fraction downward check. The known complete physical startup fleets have valid selected-state extensions satisfying AP within the existing row tolerance. Every new production Start is additionally checked by the established full mapping/row audit, which includes AP. Existing native model reuse is per leaf and requires the identical canonical-model fingerprint; a changed fingerprint cannot silently reuse a model. Child domains are emitted through the same writer, and LP-to-MIP reuse retains AP while restoring the original variable types.

4. R55 is a tested adverse antecedent At fixed commit 06b4c0634cbb85d3440be88511c736dd3282fdc9, VD-J added stationwise joint ratio and penalty equalities to VD-P. It entered root, pilot and development. The complete R55 stages contain 108 root rows, 32 pilot rows and 42 development rows across candidates; these are not counts of distinct VD-J instances.

The original D13 input is reference/hard_stress/V20_M3/high_imbalance_seed3201.txt, SHA256 ce60fd4e74ad23174be2d4a08ca6e52c0043cee22f3c9b17153b9e8bbcfdbe42. In the old 300-second L0.1.0 subinterval comparison, VD-P certifies with Work 370.2633658; VD-J has no certificate, gap about 0.00772747 and Work 562.3032609. Stronger root bounds did not produce a faster MIP. Only the subsequent penalty-cover DP branch had zero live rows because its prerequisite failed.

R135 uses that same physical input with its original 3,600-second route horizon and the current complete S2 method. Its 600-second whole-method cap is distinct from the historical 300-second subinterval cap. New S2/AP whole-method results are compared only to each other. The later shared service representation and one-row lower bound distinguish AP from VD-J but do not predict its performance.

5. Finite decision Exactly two new continuous LPs compare AP to reused S2/IND values. The whole-method plan freezes 10 first-stage arms (8,760 cap-seconds) and 22 conditional remaining arms (14,760 cap-seconds), totaling 32 arms, 16 pairs and 23,520 cap-seconds. The hard new-computation ceiling is 28,800 seconds. Stage entry is decided by certification, complete time or original-objective endpoints, never by root bounds, Work or nodes alone. All entered adverse and open observations remain in the reports.

S7. Retained threshold-count research

6.1 Construction and validity Let the legal finite supports $\mathcal{Y}_i$ contain every physical stock in the applicable domain, including all donors and receivers. Put $m_i = \min \mathcal{Y}_i$ and $R = B - \sum_i m_i$. If $R < 0$, this inventory domain is empty. Otherwise sort the distinct allowed positive ratios as $0 = t_0 < t_1 < \cdots < t_L$, let $\Delta_\ell = t_\ell - t_{\ell-1}$, and define $K_\ell = \#\{i : Y_i/D_i \ge t_\ell\}$.

Proposition 3 (threshold identities and TC). At integer inventory points,

$$S = \sum_{\ell} \Delta_\ell K_\ell, \qquad A = \sum_{\ell} \Delta_\ell K_\ell (n - K_\ell).$$

For each threshold, count stations already above it at m_i. For every other station that can reach it, find the smallest actual allowed state $a_{i\ell}$ above it, with incremental inventory cost $a_{i\ell} - m_i > 0$. Let u_ℓ be the forced count plus the largest number of the cheapest increments that fit R. Then the following single aggregate row is valid:

$$\sum_{i<j} H_{ij} \geq \sum_{\ell} \Delta_\ell (n - u_\ell) \sum_{i} \sum_{y \in \mathcal{Y}_i :\, y/D_i \geq t_\ell} s_{iy}. \tag{TC}$$

Proof. A station contributes its ratio's height to the first sum. For a pair, the threshold levels between its two ratios contribute exactly their absolute difference; at a level there are $K_\ell(n - K_\ell)$ high/low pairs. Any active set pays at least its forced baseline plus the specified minimum increments, hence $K_\ell \leq u_\ell$. Therefore $K_\ell(n-K_\ell) \geq (n - u_\ell)K_\ell$. Sum over thresholds, use $\sum H \geq A$, and linearly extend the integer inequality through the state selectors. □

Here H_{ij} is a ratio-difference epigraph variable, not the startup H. The right side can be preaggregated to $\sum_{i,y} c_{iy} s_{iy}$, without new variables or a new combinatorial DP. Construction uses $O(Ln \log n)$ threshold-count work plus state lookup/coefficient accumulation on explicit supports. This is not an input-bit-complexity claim for binary-encoded capacities. A leaf-specific support gives a leaf-specific row and cannot be moved outside its valid domain. At $S = 0$ its right side is zero.

The integer identity does not identify fractional threshold counts computed from LP state marginals with the threshold counts of the mean inventory ratios. Heterogeneous targets are allowed. For a strict comparison on a loaded matrix, the construction uses the exact rational interpretation of its ratio coefficient $r_i = \widehat{c}_i Y_i$ and state ratio $\widehat{c}_i y$, rather than mixing independently rounded ideal ratios. Nonnegative state variables permit downward rounding of the aggregate TC and old state-penalty coefficients. Exact threshold decisions, loaded coefficients and actual written values are retained.

The threshold/CDF representation is an established way to express Gini dispersion (Yitzhaki and Schechtman 2013). The sorted-increment count is a knapsack cardinality bound; Yu and Ahmed use such budget-derived cardinality information in concave epigraph formulations (Yu and Ahmed 2017). The chord bound is elementary. Our claim concerns their specified inventory-state combination and the comparisons below, rather than first discovery of these tools or a completed literature priority claim.

6.2 Strict increment on two complete tiny references J2 and J3 have four stations, unit targets and weights, stock states $0, 1, 2$, budget $B = 3$, and actual g-interval $[0, 3/4]$. Their full common reference includes current S2 rows, complete per-vehicle service hulls, theta consistency, all tiny station-event ranks, cutset rows and complete fleet-pair service marginals. We additionally retain the old state-penalty lower bound and complete R88 pairwise CDF/product controls. This explicitly named reference is not the closure of every historical oracle.

The two threshold counts are bounded by 3 and 1, so TC is

$$\sum_{i<j} H_{ij} \geq \sum_{i} (s_{i1} + 4 s_{i2}).$$

Mix the four real fleets with inventories $(0,1,1,1), (1,0,1,1), (1,1,0,1), (1,1,1,0)$ equally. Their route, load, owner, theta and state extensions give $s_{i0} = 1/4, s_{i1} = 3/4, s_{i2} = 0$, $Y_i = r_i = 3/4$, $e_i = 1/4$. With $g = q = Z = H = W = 0$, this is a complete old-reference feasible point with objective $\widehat{\lambda}$, the exact loaded

binary64 value of .15. The old state penalty and complete CDF controls still hold. Sparse CDF and q-CDF prefix variables take their actual cumulative values; only their pairwise absolute-difference auxiliaries are zero.

More explicitly, define the state and product prefixes at stock threshold h as $\sum_{y\le h} s_{iy}$ and $\sum_{y\le h} q_{iy}$. At $h = 0, 1$, their two-value vectors are $(1/4, 1)$ and $(0, g)$ at every station, both for the old point and the attaining new point below. Every between-station difference of either prefix is therefore zero. The retained pairwise CDF/product controls admit zero absolute-difference auxiliaries; their cumulative prefix variables themselves keep these stated values. The explicit extension and actual old formulas are checked in the supporting mathematical record.

Put $a = \sum_i s_{i1}$, $b = \sum_i s_{i2}$. The stock budget gives $a + 2b \le 3$, and the old penalty gives $P \ge 4 - a$. From VD-P, $\sum_i Z_i \le 4g + \beta b$, with $\beta = 3/4 \le 1$. TC and the numerator row imply $a + 4b \le 4\sum_i Z_i$, hence $g \ge a/16$. Since $\widehat{\lambda} > 1/16$ and $a \le 3$,

$$F_{LP} \ge a/16 + \widehat{\lambda}(4 - a) \ge \widehat{\lambda} + 3/16.$$

Keep the balanced mixture and set $g = q_{i1} = Z_i = 3/16$, $q_{i0} = q_{i2} = 0$ and $H_{ij} = 1/2$. This attains the bound: both TC sides are 3. Complete exact rational checks pass all 583 actual rows and 284 variable bounds for J2, and all 583 rows and 298 bounds for J3; the old state-penalty and R88 CDF extensions also pass. These are actual-matrix checks plus explicit algebraic extensions, rather than a claim to have reexported every old control into one new native matrix.

The complete integer universe has optimum $1/4 + \widehat{\lambda}$. Thus the new exact LP value is $\widehat{\lambda} + 3/16 \approx .3375$, its increment is $3/16$, and the remaining gap is $1/16$. It closes 75% of the old 1/4 gap. The conclusion uses these actual intervals and supports; it is not a full-size performance guarantee.

The retained pairwise CDF controls see identical station marginals and give no positive numerator floor at the old point. TC uses the all-station stock budget to exclude that zero numerator. Its gain supplies missing objective information even though the service mixture already has a complete joint physical extension. This explains the strict tiny result without implying that the same row must bind a real-root LP optimum.

6.3 Historical mechanisms and real-root value State-weighted penalty was already present in R55's VD-J proposal. Its strict-improver penalty-budget covers and DP have a different premise; failure of a prerequisite gate did not prove them ineffective. R88 couples pairwise CDF/product marginals, R98 theta links vehicle and stock marginals, and R101/R103 use ranks/Hall and independent single-vehicle support. Those tiny common-reference structures are retained where specified. The older inventory DP, R118 stock-deficit/greedy penalty floor and R120 scalar g-envelope also remain separate references. R114 supplies the nonnegative/source rule, not the positive stock-deficit theorem. The supplement maps the exact read sources and the limited comparisons; no claim of dominance over all historical DP or joint closures is made.

The real-root comparison uses K-20-S/Seed0 and K-35-U/Seed0, with identical input, inventory support, interval and cutoff at all three layers: current S2 continuous LP, that LP plus the old state-penalty lower bound, and the latter plus TC. Non-comparison auxiliaries reoptimize freely. It uses no new integer solve or favorable-cutoff search, and does not rebuild every old oracle.

Both fixed root domains completed the three prescribed LP layers. K-20-S gives L0=0.1951491524, Lold=0.3187585426, Lold+TC=0.3187585426, with TC increment 0. K-35-U gives L0=0.2001776619, Lold=0.2738576813, Lold+TC=0.2738576813, with TC increment -1.665334537e-16. These are floating-point LP observations with recorded primal/dual quality and added-row residuals; the tiny result above is an exact rational theorem. No reliable positive TC increment is established on these real roots. The present exploration stops with the exact tiny result and this negative real-root evidence; it does not expand the root or Seed set.

Table S7.1. Identical root domain at three relaxation layers. Times are native LP seconds; all non-comparison auxiliaries are free.

Problem	L0	Lold	Lold+TC	TC increment	U / remaining gap	LP seconds 0 / old / TC
K-20-S	0.1951492	0.3187585	0.3187585	0	0.716807 / 0.398048	0.131 / 0.165 / 0.175
K-35-U	0.2001777	0.2738577	0.2738577	-1.665335e-16	0.692854 / 0.418997	0.322 / 1.122 / 0.876




Figure 1: Exact tiny-reference improvement and the separate numerical real-root comparison. Old state penalty is retained before TC is assessed on the real roots.

S8. Source provenance The experimental coordinates/capacities, generated operational fields and solver outcomes have separate origins. No field is described as observed demand unless its source actually provides it.

Source	Actual archived authority	Coordinates and capacities	Generated fields and experimental use
CITI	R57 source_station_table.csv, SHA256 9f9aad24e61d6619 71c24c6f5ec78a69081edf01 ffc433563e52a70b2eaca2d0	Row-aligned 443-entry local capacity and UTM18N coordinate lists from the sibling Hybrid GA project; one zero-capacity row remains in the source but is ineligible for service subsets	K-15-S/K-20-S and earlier CITI roles; positive targets, initial inventory, weights, centroid depot, horizons and fleets follow recorded recipes
CABI	Official station_information response captured 12 October 2026 05:32:01 UTC, SHA256 d4e664c3ecb8c580e95d3954 1555be9cf592666a515cb854 a857fb1d117ff0b8; 865 station rows	R116 request receipt, row decisions and source_station_ table.csv; EPSG:4326 to EPSG:32618, metre coordinates rounded to .001	K-35-U, UC-B20-B, SM-B10-B and other CABI roles; operating fields are synthetic, not the feed's live availability
DIVVY Chicago	Official station_information snapshot captured 23 October 2026 14:54:37 UTC, SHA256 abec7e9a784c78b55c1d1f19 bd4e49fd4776f87bf9b56fc4 8b2f2b107b9f2324	2,076 raw/2,062 qualified rows; EPSG:4326 to EPSG:32616, .001-metre rounding; missing/conflicting/virtual records handled by frozen rules	X roles including X-35-B; same generated inventory/target/weight mechanism on a third geographic source
R55 D13	Original high_imbalance_ seed3201.txt, SHA256 ce60fd4e74ad23174be2d4a0 8ca6e52c0043cee22f3c9b17 153b9e8bbcfdbe42	Deterministic three-cluster synthetic metric construction, seed 3201	Entirely synthetic capacities/inventories/targets/weights; 20 stations, three Q=30 vehicles, T=3,600 seconds; retained historical adverse-input role

The CITI capacity and coordinate files have SHA256 92ca9b05e66d1425bbc801be2dd9c0776b1a9707 e62a60b821d941aa98625ae1 and c5fd892cc82e07332d4796edb0527182d9c60883acc9b87a5410dab569f990d1. They contain no station IDs. Canonical identity is the zero-based source row; companion station names/IDs are annotations and do not re-pair coordinate/capacity rows. Their original download URL/date and the provenance of this earlier 443-row selection are not present in the inspected source record. Those are the specific remaining CITI author checks; the later CABI and Divvy acquisitions have actual request receipts.

The CABI original endpoint is https://gbfs.lyft.com/gbfs/2.3/dca-cabi/en/station_information.json. Divvy discovery uses https://gbfs.divvybikes.com/gbfs/2.3/gbfs.json and its recorded station_information member. Source rows require finite valid coordinates, a unique station ID when the source supplies one, nonvirtual physical status and integer capacity between 1 and 99. Identical duplicate records can be coalesced; conflicting duplicates are excluded. Snapshots and row decisions fix the actual results independently of later live-feed changes.

Selections use frozen hash-derived seeds, source-row tie breaking, compact nearest-station or regional farthest-first rules, and recorded exposure exclusions. A per-input selection record lists every source row. The landscape record links its source hash and selection to positive synthetic targets, initial stocks and generated weights. Targets follow the recorded capacity-fill rule; shortage/balance/surplus totals and local adjustments follow deterministic recipes. Current generated weights are max(0.1,(D_i/max_j D_j)^2), rounded to six decimals, with maximum 1; they are not sum-normalized. The legacy D13 weight construction retains its original file rather than adopting this later rule.

Depots are artificial centroids with parser compatibility placeholders. The fleet starts empty regardless of the depot's placeholder inventory. Serialized planar metre coordinates determine Euclidean travel time at 1.5 m/s;

per-unit pickup/drop handling is 60 seconds. Horizons and fleets are experiment design parameters. The min_ ratio field is compatibility metadata, not a service-floor constraint. No trip history or dynamic demand is used.

Public source material is attributed through the providers' system-data and license links and is used within the noncommercial research study. This round adds no standalone provider dataset and redistributes no private author manuscript. Published input derivatives and previously archived sources retain their fixed-commit records.

Machine-readable source and input hashes for the seven registered R135 roles are in the historical input provenance. Full historical source metadata remains pinned to the recorded R57/R116/R132 commits; no complete old campaign is restored.

S9. Source access and specific literature differences The model and decoder descend from the available HGA-TGBC author draft, *Equity-aware Bike Repositioning in Station-based Bike-sharing Systems*. The locally available May 2026 file was rechecked and matches the earlier inspected identity; it is not asserted to be the latest version. Private text is not redistributed. The bibliography attributes the actual available draft.

The targeted primary-source review records the formal Gupte §2.1 read, Köppe's author-version §2 read, inherited BRP model comparisons and access boundaries. McCormick/convexity tools remain standard background. The paper's single-product projection and state-penalty arguments are proved directly.

Qiao et al.'s publisher-indexed abstract/highlights describe task-duration fairness and coordinated inter-/intra-zone echelons. Caggiani et al.'s official institutional abstract describes availability/state-of-charge Gini, zonal targets, relocation and battery swapping with microsimulation. These read locations support the different equity objects stated in §1.1. Complete formulation relations are unknown: no equivalence, strict separation, dominance or priority claim is inferred. The openly listed Caggiani VoR could not be read: web content-size failure and one normal direct-download HTTP403 are recorded without a paywall diagnosis or configuration change.

The original CITI capture URL/date and station IDs remain unavailable. Archived row identity, coordinates/capacity and frozen selection bind the inputs; CABI/Divvy have their actual acquisition receipts. Current live feeds are provider references, not replacements for historical snapshots.

S10. Historical evidence and finite reproduction R132 breadth retains 17/24 S2, 9/24 P and 4/12 PS qualified certificates under its original policy. R133 retains fourteen exposed qualification positions and its four-pair old/new bridge. R134 retains S2 12/14, P 9/14 and PS 2/4 across 32 method positions. These layers are neither pooled as independent input samples nor relabelled by later source policies. Full older tables remain at their fixed commits, including the R134 scientific evidence, and the R132/R133 citations recorded there.

Current reproduction replays all entered R135 positions and the two AP root coefficient/residual records from exact source-byte and raw carriers. It invokes no Optimize, compiler or vendor DLL. Historical whole campaigns and unentered conditional positions are not reconstructed. Source/PE/DLL/input identity, all ordinary outcomes, failed attempts and measured costs remain separate from the authorship and journal-format checks required before actual submission.

S11. Maintained historical controls and equivalent-expression proofs MD-R version 1 is a research ablation, not another proposed algorithm. Historical supplement the R130 historical account Section 6.8 and the root contract define its same-H inclusive domain, semantic shortcut omission, mandatory actual own-Start pre-LP check, one LP plus one integer MIP, fixed cutoff and complete native optimal-root return obligation. It retains the physical and signed numerical evidence policy. TIME_LIMIT/INTERRUPTED may yield a qualified open endpoint with null T_cert; a near-equal bound alone cannot satisfy its missing optimal-return obligation. Its extra checks and complete costs are paid. These control-specific guards leave the frozen ordinary procedure and the historical evidence in this appendix unchanged.

B.13 Uniform support candidate confirmation (Round129) Round129 changes no production source, H, model generator, numerical policy or controller. It reuses original E2 modes mb/ms2/p. The sole candidate MS2 suppresses triple support for every input while retaining pairs, ordered supply and the shared enumeration order/cap. The five fixed candidate rules and thirty complete paid observations are in the R130 historical account Section 6.9. At the R129 selection stage, MS2 was the proposed candidate and full M-B was the then-current frozen method. That historical distinction and all tables remain; R130 adopted S2/MS2 as the sole paper method, unchanged through Round132. The independent finite review and public recovery are evidence checks, not new native solves or rational proofs of all matrices.

B.14 Historical pair-support adoption and attribution controls The sole paper method retains the historical E2 `ms2` identity, called S2. Historical E3 retains that version's source behavior and adds the off-by-default unique `s2-root` identity plus PS parameter evidence readback. E2 is retained unchanged. PS reuses the full original-compact mapper/validator; S2R reuses R128 inclusive-root semantics with triple emission disabled. Historical supplement the R130 historical account Section 6.10 states the paid workflows, exact cutoff complement, nonzero LP/MIP obligations, source/return/coverage requirements, actual exposure and attribution limits. No individual cut, H, threshold or native parameter is optimized here. The passed R129 candidate selection is not rerun.

Appendix C. Equivalent-expression proofs and actual-model conditions

C.3. Projection of the three geometry row families Delete only H-spread, variable-S centering and fixed-S centering. Keep all H absolute-value lower bounds, individual bounds, total cap/floor, original Gini epigraph, scalar/SP estimators, cutoff, real domains and domain-generation rules. For $n \geq 2$ the ideal three families are

$$(n-1)H_{ij} \leq n\beta S, \quad \pm(n-1)(r_i - r_j) \leq n\beta S, \quad \pm(r_i - r_j) \leq \frac{n\beta \bar{S}}{n-1}.$$

Let $H_\Sigma = \sum_{i<j} H_{ij}$. The retained original epigraph is $H_\Sigma \leq n \sum_i Z_i/D_i$. Nonnegative states and $q_{iy} \leq \beta s_{iy}$ give $Z_i \leq \beta Y_i$, hence $H_\Sigma \leq n\beta S$. Triangle inequalities give $A \geq (n-1)|r_i - r_j|$: for each third station t, $|r_i - r_t| + |r_t - r_j| \geq |r_i - r_j|$, together with the pair itself; unused pair distances are nonnegative. Thus both centering families follow from the retained inequalities and $S \leq \bar{S}$.

Root interval When $\alpha = 0$, replace every H_{ij} by $|r_i - r_j|$. This decreases the sum, respects its upper bounds and all individual upper bounds under the audited conditions, and the floor reduces to nonnegativity. The new H satisfies H-spread and leaves all non-H variables and the objective unchanged. Reverse inclusion follows by adding constraints. Thus projecting away all H gives equal LP sets and equal ideal LP objective values. Because H is continuous, the same extension preserves any remaining integer restrictions.

Positive lower endpoint Assume $0 \leq \alpha \leq \beta$, $r_i \geq 0$, $S \leq \bar{S}$; individual H upper bounds $U_{ij} = c_i + c_j$ with $c_i \geq 0$ and $r_i \leq c_i$; and outside the deleted families H appears only in absolute lower bounds, individual bounds, a total floor/cap and other uniform total upper bounds. It has zero objective coefficient and no additional individual positive lower bounds or nonuniform linear uses.

Fix every non-H variable in a feasible point of the deletion model. Put $d_{ij} = |r_i - r_j|$, $A = \sum_{i<j} d_{ij}$, $L = n\alpha S$ and $t = n\beta S/(n-1)$. Let B be the smallest retained total upper bound, including the implied $n\beta S$. Feasibility gives

$$T^* = \max(A, L) \leq \min\left(B, \sum_{i<j} U_{ij}\right).$$

The triangle argument gives $d_{ij} \leq t$. Set $U'_{ij} = \min(c_i + c_j, t)$. For $C = \sum_i c_i > 0$, the function $f(\mathbf{c}) = \sum_{i<j} \min(c_i + c_j, t)$ is concave on the nonnegative simplex of sum C. With e_i^{unit} denoting the standard unit vector, write $\mathbf{c} = \sum_i (c_i/C) C e_i^{\text{unit}}$. Concavity gives

$$\sum_{i<j} U'_{ij} = f(\mathbf{c}) \geq (n-1)\min(C, t) = \min\left(\sum_{i<j} U_{ij}, n\beta S\right) \geq T^*.$$

If $\sum_{i<j} U'_{ij} > A$, set

$$\theta = \frac{T^* - A}{\sum_{i<j} U'_{ij} - A}, \qquad H'_{ij} = d_{ij} + \theta(U'_{ij} - d_{ij}).$$

Then $0 \leq \theta \leq 1$; every individual bound and spread bound holds, $\sum_{i<j} H'_{ij} = T^* \leq B$, and the floor holds. The centering rows already follow without H. All non-H variables and their objective remain unchanged. If the

denominator vanishes, $T^* = A$ and $H' = d$ suffices. If $C = 0$, all c, r, S, A, L vanish and $H' = 0$. If $S = 0$, nonnegative ratios vanish and $H' = 0$. For $n = 1$ none of these three families is generated. This proves both projected inclusions, including the nonzero-floor case in which setting $H = d$ alone can fail.

Actual-model application and numerical boundary The current shared canonical factory generates the named three families, and the frozen paper profile disables local/subset nonuniform H uses. The Cplex writer sets H upper bounds to $\mathrm{fl}(C_i/D_i + C_j/D_j)$, with zero objective coefficients. The independent reviewer inspected an actual saved S12 S2R matrix: 66 H bounds, five uniform full-H rows and 198 individual-H rows. W appears in five rows, as required below. This is a canonical-model result, not a theorem about arbitrary native node cuts.

The exact additive upper-bound hypothesis concerns real algebra. In the saved S12 matrix, 41 of 66 serialized H bounds differ from the exact rational sum of the two serialized r upper bounds at roughly 10^{-16}. Therefore the ideal theorem is not asserted as strict rational equality for every serialized floating matrix. Necessary actual coefficient/domain checks and extension residuals accompany the research comparisons. In that frozen R132 expression study the production S2 bytes were unchanged and no hidden outward correction was applied. The later candidate's explicit inclusive-cutoff repair has a separate identity and is not attributed to expression deletion. Equal projections do not imply identical presolve, native cuts, search paths or elapsed time, and do not make the entire C_G package redundant.

C.4. Exact elimination of W, including its real bounds In the active shared model $W = W_{\mathrm{SP}}$ is continuous, has zero objective coefficient and is used by four MC rows, one SP cutoff and its own box. No other use is present in the qualified canonical scope. Preserve all W-free original rows, variable types and bounds, particularly $g + \lambda P \le c$, which a cross-multiplied row cannot replace at $S = 0$.

For actual W bounds w_l, w_u and MC parameters s_l, s_u, p_l, p_u, define

$$L_0 = w_l, \quad L_1 = s_l P + p_l S - s_l p_l, \quad L_2 = s_u P + p_u S - s_u p_u,$$
$$U_0 = w_u, \quad U_1 = s_u P + p_l S - s_u p_l, \quad U_2 = s_l P + p_u S - s_l p_u.$$

The original system is $L_j \le W \le U_k$ and $H_\Sigma + n\lambda W \le ncS$. For $\lambda > 0$, its complete projection is all nine compatibility rows $L_j \le U_k$ and all three lower-cutoff rows $H_\Sigma + n\lambda L_j \le ncS$. Necessity is immediate. Conversely, $W = \max_j L_j$ satisfies every upper bound and the SP cutoff, proving sufficiency. This is standard one-variable Fourier-Motzkin elimination applied to this formulation, not a new linearization theorem or an exact continuous product identity.

Only after proving the same explicit nonnegative rectangle $0 \le s_l \le S \le s_u$, $0 \le p_l \le P \le p_u$, and that the actual W box is no tighter than the product box, may compatibility and box rows be removed. The true product SP is then an extension for MC feasibility. Since $L_1 - s_l p_l = s_l(P - p_l) + p_l(S - s_l) \ge 0$ and $w_l \le s_l p_l$, the constant lower plane is dominated. The two lower-plane cutoffs then suffice, with $W = \max(L_1, L_2)$. Current inflated e can violate the tight physical P upper estimate; that estimate cannot simply be assumed to bound the whole epigraph.

For positive width $s_u > s_l$, MC lower/upper pairings imply $P \ge p_l$ and $P \le p_u$ after cancellation. These consequences must survive projection. For example, $s_l = 1, s_u = 2, p_l = 0, p_u = 1, S = 1, P = 2, H_\Sigma = 0$ and sufficiently large c satisfy both lower-plane cutoffs, but $L_2 = 3 > U_2 = 2$, so no original W exists. Two cutoffs alone would incorrectly enlarge the domain.

When S is fixed, derive compatibility directly rather than dividing by its width. At $S = 0$, $W = 0$ need not imply $P \le p_u$. The full pair system handles that case without adding an unauthorized P bound. When $\lambda = 0$,

retain $H_\Sigma \le ncS$ and every W-feasibility compatibility row; removing the whole block would again change its projection. Zero-width P and simultaneous degeneracy are also covered by the pair construction.

Implemented research expression The research writer reads the actual shared canonical row coefficients, normalizes their senses, includes the exact actual W box, and combines every lower/upper pair. There are three lower rows and four upper rows including the SP row: 12 projected rows. It retains even constant or duplicate compatibility rows. All remaining original rows, objective, bounds and integer types stay intact; only the W column and its rows are replaced. Its physical Start is mapped to the remaining actual columns and validated before use.

The independent checker reconstructs these combinations with exact rational arithmetic on source binary64 coefficients. It separately bounds the output coefficient-serialization residual over actual remaining-variable bounds. The candidate binary64 output is qualified as numerically consistent, not asserted to equal the exact rational projected matrix. `C_matrix_wording_addendum.json` makes this distinction explicit. Four saved interval/input configurations have equal canonical all-continuous LP objectives within the inherited 10^{-7} policy. These finite observations check implementation and numerical behavior; they do not replace the general projection proof.

C.5. Qualification and relation to costs The research default-off writer and original E3 produce identical complete canonical LP bytes on the qualified small and medium fixtures, at a root interval and a positive lower endpoint. Actual S12 CLI runs bridge original E3 to research default-off, and validate independent H and full Start submission for both candidates. Each uses the legal inclusive-root LP then restored-integer MIP workflow. Default-off equivalence is a semantic/matrix bridge; the two executable byte strings are different and are never described as identical.

All 24 admitted C workflows are now sealed. Geometry deletion gives 2 Win, 4 Lose and 2 UNDETERMINED; full W projection gives 3 Win, 3 Lose and 2 UNDETERMINED against the same-build inclusive-root baseline. All 16 candidate/baseline comparisons have identical complete realized H, matching root intervals/cutoffs and actual native exposure. The continuous root objectives agree within the original numerical policy, while Work/nodes and complete costs vary in both directions. This supports mixed expression costs, not a stronger ideal relaxation or automatic production replacement. D remains the original frozen algorithm and its measurements do not come from this research build.

Round163 structural-stage evidence and prospective protocol

The original R132/R134/R137 observations above retain their measured versions, Seeds, budgets and denominators. They are not concatenated with Round163 as independent samples. The frozen B/E+/P comparison has six new configurations, 18 separately paid arms, one Gurobi Seed and no result-dependent redraw or candidate switch. It is prospective confirmation on archived-source station data with synthetic inventories/targets/weights, not new cities or independent observed-demand validation. All six become exposed after this study.

The fixed recipe, six-input identities, source overlap disclosure and 18 complete commands preserve the pre-performance protocol. The stage synthesis gives the inherited-conclusion/evidence/new-increment/inference-boundary table; its source map binds all 25 directly read files to fixed commits and byte hashes. The expanded mathematical analysis states the actual helper epigraph objective, nested-domain premises, coverage/cutoff contracts and gap identity. No previous producer or full historical raw carrier is replayed.

The three methods share the actually hashed R162 complete_v2 C++ executable and Gurobi 13.0.2. E+ additionally invokes the unchanged historical Python RN16384 inventory helper on its own canonical root; its mixed implementation and complete paid cost are explicit. Every arm has one production deadline. The ordinary C++ methods, helper, stable profiles, complete physical objective, loaded-return convention and numerical

qualification remain fixed. The final tables and algorithm choice are appended only after all 18 arms and their original-objective audits close.

Round163 completed configuration evidence

All six first-valid inputs and all 18 qualified endpoints are retained. The complete table, binary64 endpoints, three comparisons and helper/fee interpretation give the full denominator, original gap policy, T_cert/T_produce/T_verify/T_total, actual Native Work/nodes, own-H and helper costs. Stage choice, closed fees and science identities separate the paper algorithm, frozen research implementation and released main.

Retain uniform GI-TBC/B as the paper's main algorithm. Keep uniform E+ as a separately named, limited proof enhancement, with its genuine X35 gain and earlier qualified R154/R156 gains preserved. This complete panel does not justify replacing B as the main recommendation; the current broad-promotion attempt ends here. No per-input best-of-B/E+ method or released-default change is made.

Both B and E+ certify 3/6 configurations, versus cold P 1/6. B/E+ have identical verified physical U on all six. E+ raises X35's final qualified L from B's .3949882559151472 to .42319954961578576 at U=.45747531701601785; the original relative gap falls from 13.659110945800548% to 7.492375244155952%. The other five final proof endpoints are equal. E+'s X35 raw search L is .39492875817006656, slightly below B's; the improvement is the separate qualified proof source, not an improved raw AM/Native bound. No additional certificate or primal improvement is observed.

The three both-certified E+/B paid T_cert ratios are 1.130665945756784, 1.3357446355323432 and 1.0515856109492556. The absolute increases are about 26.10 s, 1.70 s and 6.18 s on C20, B20 and X20. Only C20 meets the existing substantive scale max(10 s, 10% of the faster time); the two other numerical directions remain recorded as nonmaterial. E+ pays 256.7365551 helper seconds inside the original deadlines. Aggregate audit-inclusive T_total is 7506.416129835416 s for E+ and 7451.303745185491 s for B, a 55.112384649924934 s increase; helper time is already included. The genuine X35 proof gain and all equal physical upper endpoints make uniform E+ a reasonable alternative when proof information is prioritized. The paper's choice of B balances certificate count, paid time and both endpoints; it is not a dominance theorem or a requirement that every input improve.

B and E+ each have lower U than P on three configurations, higher U on C35-U, and equal U on two. Each has substantively higher proof L than P on five configurations and equal qualified endpoints on the remaining certified B20 case. On C35-U, P's U=.09331934374779818 is strictly better than B/E+'s .12956638965196035, while B/E+ have stronger L; this opposition is retained. The one joint-CERT B/P or E+/P time ratio conditions on B20 alone. No full-panel time superiority or universal P-GRB dominance is inferred from a single Seed.

C20, B20 and X20 finish with search L beyond their qualified inventory value uppers. C35's inventory result is numerically near zero, not an exact-zero physical proof. B35 and X35 prices stop at RN16384 with widths .014387103336740467 and .02295563610060769. B35's returned floor is below final search L but its inventory upper is above it; X35's floor contributes to the final proof while its price remains unresolved. Old R156's small same-domain remainder therefore cannot be generalized to these new prices. No larger capacity, alternate price, Seed or candidate is tried.

The master-table receipt appends only verified B/P pairs to the existing CSV copies; E+ is separately labelled throughout. The final report and delivery/recovery status link independent review identities and the bounded new-only public recovery. Original source-row overlaps and retrospective master-table reconciliation are disclosed without changing the frozen generation or selecting on outcomes.

Maintained body, appendices, mathematical companion, bibliography and figures are the current sources. The manuscript and supplement PDFs are regenerated by the current component-only build; the Git history retains the earlier snapshots.

Research navigation for saved C35 skeletons

The former main-body §7.1 diagnostic work list is retained in research navigation. It reconciles the existing complete R96 fixed-ownership/relative-order quantity object, parent containment and full physical/epigraph qualifications. No such restricted model, route oracle, feedback candidate or new producer is executed in the solver-Seed confirmation. The known feasible P target, an unserved-station penalty floor and an inventory-only target vector do not by themselves determine the complete saved-skeleton optimum. R62/R96/R97/R160 retain their original positive, mixed and adverse evidence.

Round164 completed finite solver-Seed evidence

All 24 registered new B/P positions complete at Seeds1/2, keyed on input, Seed, method and actual repeat1. Twelve new pairs and six qualified historical Seed0 pairs form six within-input groups. The complete full-precision evidence tables report all 36 own-run physical U, raw/qualified search L, final proof L, original gaps, certificate states, paid clocks, own-H and Native effort. The new 24-arm CSV, paired differences, within-input summaries and finite report retain every OPEN observation and both endpoint directions. No E+ floor is included in B.

Historical Seed0 reuses the same input/physical/method/PE/DLL/deadline and numerical contracts. Its selected original physical fleets and all Native Seed settings are reread; live OS module/affinity records and original native CPU/Windows/Gurobi headers match both new Seeds. The reuse qualification does not assert identical incidental OS load or statistical exchangeability. The identity audit binds all 24 fresh serial lifecycles and independently paid fixed-seed H.

Descriptive within-input summaries

The medians and ranges below summarize three differences, not a new feasible solution, proof endpoint or independent sample. Full binary64 values and tolerance-qualified signs remain in the linked machine reports.

Input	Median ΔU [minimum, maximum]	Median ΔL [minimum, maximum]
R163-C20-S	0 [-0.05927393, 0]	0.03369846 [0.03104638, 0.03941158]
R163-B20-B	0 [0, 0]	3.885781e-16 [5.551115e-17, 2.090347e-10]
R163-X20-S	-0.01320014 [-0.01721348, -0.01320014]	0.1948245 [0.186098, 0.1974955]
R163-C35-U	-0.03868052 [-0.05019445, 0.03624705]	0.01155073 [0.009334378, 0.01347433]
R163-B35-S	-0.101716 [-0.13296, -0.0549627]	0.004752414 [0.004661458, 0.006254594]
R163-X35-S	-0.06178785 [-0.08405536, -0.06065283]	0.04442013 [0.03201682, 0.04660159]

Joint-CERT paid time intersection

The intersection is exactly B20, 1/6 inputs at each Seed (three within-input pairs overall). Every listed difference exceeds its 10 s substantive scale. OPEN observations supply no convergence time and are not removed to infer a full-panel acceleration.

Seed	B20 B T_cert	B20 P T_cert	ΔT=B−P /s	B/P	Substantive scale /s
0	5.058292	235.8555	-230.7972	0.02144657	10
1	4.963643	303.0334	-298.0697	0.01637986	10
2	5.277053	266.8006	-261.5235	0.01977902	10

Offline saved-feasible targets and clocks

The six targets were frozen before any new Optimize from min(two historical qualified physical U). They enter no argv, Start, cutoff or stop. The all-36 records apply one rule to every input/method/Seed. Each saved journal fleet is physically replayed. Its conservative paid upper is the observed availability plus T_produce minus the matching supervisor wrapper duration, including prelaunch. The global earliest-save lower is unknown and conservatively zero; receipt-qualified journal availability has a separately recorded lower bound. Other full-fleet emitters may precede a journal receipt, so these are not exact first-find times. Endpoint-only records would supply producer-close uppers; no attainment observed is right-censored at that run's own producer close. The source clock contract binds the original C++ receipt order and matching supervisor time origin.

Bounded C35 witness explanation

All C35 H values equal .17449020363402973 with the same fixed H seed, each recomputed and paid. The six final fleets decompose as follows.

Seed	Method	G	Weighted penalty	Physical U
0	P	0.04494125	0.0483781	0.09331934
0	B	0.06783155	0.06173484	0.1295664
1	P	0.07730508	0.08031924	0.1576243
1	B	0.0521821	0.05524777	0.1074299
2	B	0.05487224	0.0532117	0.1080839
2	P	0.08498105	0.06178341	0.1467645

The saved-fleet synthesis retains routes, operations, travel/handling times, prefix peaks, loaded returns and native improvement events. In the Seed0 B/P comparison, 26 common stations change vehicle ownership, 15 common stations change service amount/direction and 15 co-served pairs reverse relative order. None of those reversals occurs among stations keeping the same vehicle label; the broader co-served comparison records simultaneous owner/order changes and does not isolate an order effect.

The unserved station18 contributes .011402553447730399, below P's known feasible objective. Setting all other saved visited stocks to target gives the inventory objective .03359254619609878, but route0 peaks at32 against capacity20 and all three route times exceed10800 s (12501.7845/11130.8908/10939.8293 s). This point is infeasible, not a restricted-domain optimum or proof that every legal quantity choice fails. No R96 restricted MIP, route oracle or feedback producer is executed. Earlier R62/R96/R97/R160 evidence retains its actual mixed scope.

Reproduction and maintained format

The immutable numeric source is `b93a8a01ff1b7f3cbee67807be3ac6591db4767f`; original instance metadata remains the fixed R163 manifest. The historical member map and source map bind finite old reads by commit/member/SHA. The execution dispositions retain a prelaunch-only idle-screen failure and an analysis-only overstrong order assertion; no healthy formal producer is repeated. The cost report pays nonoverlapping outer processes and final independent review without adding nested Native/H counters. Main CSV reconciliation, real review identities and publication/ new-only recovery are linked from the final report.

All pre-frozen feasible-target availability intervals

These are the original 36 `primal_target_arrival` records, displayed at six significant digits in seconds on each run's paid clock. An interval is a conservative saved-witness availability window, with unknown earliest-find lower bound zero. Censoring is at that run's producer close; it means no qualifying target attainment was observed. Targets were frozen from Seed0 feasible endpoints and entered no Start, cutoff or online stop. The full original JSON retains full precision, receipt-specific availability bounds and provenance.

Configuration	Method	Frozen u_ref	Seed 0 (s)	Seed 1 (s)	Seed 2 (s)
R163-C20-S	B	0.1912806	[0, 94.4044]	[0, 109.373]	[0, 143.294]
R163-C20-S	P	0.1912806	[0, 786.721]	[0, 1010.22]	censored at 1171.52
R163-B20-B	B	0.4232322	[0, 4.94829]	[0, 4.82264]	[0, 5.21405]
R163-B20-B	P	0.4232322	[0, 52.7465]	[0, 13.1894]	[0, 15.0346]
R163-X20-S	B	0.4477476	[0, 89.1714]	[0, 74.6706]	[0, 86.9072]
R163-X20-S	P	0.4477476	censored at 1171.33	censored at 1171.46	censored at 1171.39
R163-C35-U	B	0.09331934	censored at 2371.45	censored at 2372.83	censored at 2371.35
R163-C35-U	P	0.09331934	[0, 1835.36]	censored at 2371.29	censored at 2371.44
R163-B35-S	B	0.1942903	[0, 2127.48]	[0, 742.865]	[0, 121.471]
R163-B35-S	P	0.1942903	censored at 2371.41	censored at 2371.36	censored at 2371.37
R163-X35-S	B	0.4574753	[0, 2023.1]	censored at 2371.32	censored at 2371.26
R163-X35-S	P	0.4574753	censored at 2371.38	censored at 2371.28	censored at 2371.29

Round166 compact representation and certified decisions

The new study changes the common inventory representation while retaining the complete GI-TBC/B algorithm, own H, physical rows, e epigraph and native parameters. Its mathematical object and exactness conditions appear in Appendix A.9; the full constructive proof, counterexamples and symbolic size formulas are in compression_theory.md. It uses standard disjunction and product tools. C166 is default off and is never relabelled as B. Historical measurements retain their original source and executable identities.

Qualification and actual matrix sizes

The C++ qualification has 96 actual Optimize calls within 539.080771 s: 64 local fixed-objective LPs, 16 paired full-model LPs, 8 boundary/tiny calls and 8 nonzero complete-controller calls. Independent zero controllers, finite exact enumeration, algebra and export/readers add zero calls. The nonzero tiny optimum has inventory(1,1), one unit returned loaded, objective .15 and an interior non-breakpoint donor stock. Complete semantic Starts, LP-to-MIP type recovery, original rows/objective and incompatible-mode rejection are checked. Two reader failures retain their healthy raw runs; only the readers are repaired. The diagnostic and formal costs are separate.

The eight LP pairs below use identical offline fixture incumbents/cutoffs within each pair. These fixtures enter no formal startup. “Build” is the qualification driver’s pre-native pipeline from input/parent parsing and physical verification through writing the canonical model, not an isolated writer microbenchmark. Counts describe the emitted full model, before solver cuts; binary counts are the declared integer model types before relaxing the qualification LP.

Scope	B LP	C166−B LP	B cols / C166	B binary / C166	B rows / C166	B nnz / C166	Build B / C166 (s)
B20-B_child	0.3638283	-1.11e-16	2488 / 2482	1067 / 1006	6049 / 6513	34844 / 35652	0.23669 / 0.24327
B20-B_root	0.3488928	0	2488 / 2482	1067 / 1006	6049 / 6513	34844 / 35652	0.23974 / 0.24281
B35-S_root	0.1078591	1.388e-17	10629 / 9615	4840 / 4167	24234 / 24175	168063 / 165766	1.1698 / 1.1263
C20-S_child	0.1177464	0	3142 / 2596	1394 / 1021	6683 / 6682	38618 / 37443	0.29408 / 0.25216
C20-S_root	0.1177464	9.714e-17	3142 / 2596	1394 / 1021	6683 / 6682	38618 / 37443	0.2626 / 0.25748
C35-U_root	0	0	10937 / 9643	4994 / 4174	24542 / 24238	169324 / 165977	1.1904 / 1.1262
X20-S_root	0.1656086	0	2692 / 2534	1169 / 998	6233 / 6505	36686 / 36848	0.2502 / 0.24696
X35-S_root	0.3033443	-3.331e-16	9445 / 9381	4248 / 4087	23050 / 23541	163163 / 163909	1.1361 / 1.1075

All twelve complete endpoints and costs

The order was frozen before the first launch and alternates the first method by input, independently of historical performance. All twelve positions finish with qualified numerical endpoints. T_cert is empty for OPEN; T_produce and T_verify retain their original meanings. Same-input own-H semantic and fleet hashes agree, with each run paying independently.

Position / input	Method	State	U	L	Signed U−L	T_cert (s)	T_produce (s)	T_verify (s)	Native calls
1 / C20-S	B	CERT	0.1912806	0.1912806	-7.49401e-16	210.4145	210.4145	1.919934	4
2 / C20-S	C166	OPEN	0.1912806	0.186598	0.00468254	-	1171.439	4.675597	4
3 / B20-B	C166	CERT	0.4232322	0.4232322	5.55112e-17	5.661224	5.661224	1.623963	9
4 / B20-B	B	CERT	0.4232322	0.4232322	1.55431e-15	5.096442	5.096442	1.415442	9
5 / X20-S	B	CERT	0.4477476	0.4477476	1.29341e-14	125.29992	125.29992	1.254961	5
6 / X20-S	C166	CERT	0.4477476	0.4477476	6.66134e-16	544.90213	544.90213	5.691091	5
7 / C35-U	C166	OPEN	0.1210433	0.01420654	0.106837	-	2371.2042	2.929806	4
8 / C35-U	B	OPEN	0.1295664	0.0198375	0.109729	-	2371.2838	2.734756	4
9 / B35-S	B	OPEN	0.1942903	0.120234	0.0740563	-	2371.1024	4.471638	4
10 / B35-S	C166	OPEN	0.1792896	0.1160533	0.0632364	-	2372.2253	2.864775	4
11 / X35-S	C166	OPEN	0.4758712	0.3866997	0.0891714	-	2371.0992	2.940782	5
12 / X35-S	B	OPEN	0.4574753	0.3949883	0.0624871	-	2371.1383	4.403796	5

The next table is explanatory accounting inside those same paid clocks. “Writer” and “read” are accumulated canonical writer and native model-read seconds over the actual reached path, whose number of models can change. Runtime, Work and nodes sum returned native calls. These nested quantities are never added to T_produce/T_verify as extra scientific fees.

Input	Method	H (s)	Writer (s)	Read (s)	Native Runtime (s)	Native Work	Native nodes
C20-S	B	1.55034	0.7682781	0.0403299	206.681	356.904567	21388
C20-S	C166	1.55008	0.7223505	0.0371658	1167.525	2213.987822	82766
B20-B	C166	0.0227025	1.663858	0.0849502	2.391	3.417207	293
B20-B	B	0.0227777	1.615594	0.0823967	1.922	2.524355	160
X20-S	B	0.237089	0.7213828	0.0366268	122.891	220.964	8842
X20-S	C166	0.208752	0.7238595	0.037919	542.289	992.2141	66425
C35-U	C166	10.2317	3.279759	0.159748	2355.681	4844.834749	2312
C35-U	B	9.85137	3.284695	0.158911	2356.053	5584.923796	6616
B35-S	B	9.47853	3.311271	0.158117	2356.459	5920.218137	2659
B35-S	C166	9.48554	3.164148	0.152466	2356.616	5457.014587	2318
X35-S	C166	0.980233	3.146774	0.1509	2365.076	5948.871843	7752
X35-S	B	0.984681	3.134779	0.150354	2365.102	5733.542928	3404

The first continuous canonical LP below is distinct from the first Native MIP root after integer presolve. The latter is transcribed at the log's printed precision and is not used as a qualified global bound. Its presolved size/relaxation can differ between integer encodings with the same original continuous projection. An absent root line is retained as absent. AM actions are the actual decision sequence, not a claim that equal configured policy must realize equal paths.

Input	Method	First raw LP	First MIP root (log)	Presolved rows / cols / nnz	AM sequence
C20-S	B	0.1177464	0.1177464	5299 / 3120 / 38475	exact-close
C20-S	C166	0.1177464	0.1189427	5288 / 2574 / 37594	exact-close
B20-B	C166	0.3488928	0.3917953	1679 / 802 / 8884	native-target, exact-close
B20-B	B	0.3488928	0.4033865	1642 / 899 / 10523	native-target, exact-close
X20-S	B	0.1656086	0.1656086	4938 / 2536 / 32997	native-target, exact-close
X20-S	C166	0.1656086	0.1721899	5061 / 2364 / 32296	native-target, exact-close
C35-U	C166	0	0	19968 / 9608 / 213700	exact-close
C35-U	B	0	0	20146 / 10906 / 239293	exact-close
B35-S	B	0.1078591	0.1078591	19976 / 10564 / 234200	exact-close
B35-S	C166	0.1078591	0.1078591	19916 / 9538 / 203858	exact-close
X35-S	C166	0.3029771	0.3029806	19358 / 9131 / 183454	native-target, exact-close
X35-S	B	0.3029771	0.3030105	19127 / 9228 / 188212	native-target, exact-close

There are 2 joint-CERT pairs. Their C166/B time ratios are B20-B: 1.1108 (below the substantive scale); X20-S: 4.3488 (substantive). The other pairs carry no certificate-time ratio. Aggregate T_produce is 7454.335378 s for B and 8836.531014 s for C166; separate T_verify is 16.200527 s and20.726015 s. The fresh-wrapper outer total is 16328.458215 s; its small management difference from summed produce/verify remains charged. Reservations of 25200 s and watchdog settings are not reported as consumed costs.

Continuous-weight archive and two-sided resource value

All 50 complete fleet records are recovered and physically checked: 32 weight observations and 24 resource observations with six shared records. The four families preserve the exact physical domain and normalized weight vector. Every source owner, dominated fleet, original objective and clock remains available. Archive improvement is offline and supplies no free formal Start, bound or cutoff. Main Section 5.3 and Appendix A.10 explain the concavity/finite-intersection argument and safety margins.

Family	Actual covered rho (display)	Runs / distinct lines / supported	Max archive regret upper	Best fixed-plan regret upper
R134:K-15-S	0.710502825 to 2.8420113	8 / 3 / 3	0.00235628186320	0.00823859197838
R134:UC-B20-B	0.88725 to 3.549	6 / 1 / 1	0.000000100001000329	0.000000100001000329
R137:R-B20-S-T1	0.5 to 2	9 / 7 / 3	0.0155942686044	0.0155942686044
R137:R-X35-S-T2	0.5 to 2	9 / 9 / 1	0.136115161565	0.136115161565

The parameter regret bounds above are rounded upward. The resource intervals below use qualified global lowers reduced by 1e-7 and exact feasible objectives increased by 1e-12, then round endpoints outward to ten decimal places. Width is the displayed interval width; exact rational arithmetic and original source endpoints remain in the machine-readable data.

Pair / T1→T2 (s)	Safe improvement lower	Safe improvement upper	Displayed width
R-B20-S / 3300→5100	0.2822618761	0.2822620892	0.0000002131
R-X20-S / 4800→7200	0.2105292995	0.2105295021	0.0000002026
R-B35-S / 4800→7200	0.1112611656	0.3725317852	0.2612706196
R-X35-S / 4200→6300	0.0600858983	0.3813035291	0.3212176308

Pair	Pickup units	Drop units	Loaded return units	Final station inventory
R-B20-S	30→43	30→43	0→0	143→143
R-X20-S	16→22	15→22	1→0	64→65
R-B35-S	41→60	39→57	2→3	234→233
R-X35-S	29→42	28→42	1→0	145→146

All four larger-horizon witnesses improve both G and normalized penalty. B35's returned stock rises from 2 to 3 while X35 falls from 1 to 0. More pickup and a lower objective therefore do not imply less loaded return. Full route-level travel/handling/unloading, prefix loads, inventory distribution and duration utilization remain in the complete archive. These are physical descriptions, not proofs of a binding optimal time constraint or causal mechanism.

The existing high-weight X35 fleet has feasible objective.3365058164688021 at the original unit-weight coordinate, versus.40327199886285475 for the old unit-weight fleet, a known feasible improvement.06676618239405259. This changes no historical incumbent or certificate clock. The broad X35 continuous quality band remains an explicit limitation.

References

Yitzhaki, Shlomo, and Edna Schechtman. 2013. "More Than a Dozen Alternative Ways of Spelling Gini." In *The Gini Methodology*, vol. 272. Springer Series in Statistics. Springer. https://doi.org/10.1007/978-1-4614-4720-7_2.

Yu, Jiajin, and Shabbir Ahmed. 2017. "Polyhedral Results for a Class of Cardinality Constrained Submodular Minimization Problems." *Discrete Optimization* 24: 87–102. https://doi.org/10.1016/j.disopt.2015.07.005.