

Question 4

Consider a binary communication channel with input $X \sim \text{Bern}(p)$, output $Y \sim \text{Bern}(q)$, and crossover (error) probability ε . It is known that

$$q = p + \varepsilon - 2\varepsilon p.$$

The channel capacity is

$$C = \max_{0 \leq p \leq 1} I(X; Y).$$

Find the value of p that maximises C (i.e. maximises $I(X; Y)$).

Solution

The mutual information can be written

$$I(X; Y) = H(Y) - H(Y | X) = H(q) - H(\varepsilon),$$

where $H(\varepsilon) = -\varepsilon \log_2 \varepsilon - (1 - \varepsilon) \log_2 (1 - \varepsilon)$ is constant in p , and

$$q(p) = p + \varepsilon - 2\varepsilon p = (1 - 2\varepsilon)p + \varepsilon.$$

Differentiate with respect to p :

$$\frac{dI}{dp} = \frac{d}{dp} H(q) = (1 - 2\varepsilon) [-\log_2 q + \log_2 (1 - q)] \stackrel{!}{=} 0.$$

Hence

$$\log_2 \frac{1 - q}{q} = 0 \implies q = \frac{1}{2}.$$

Solving $q = (1 - 2\varepsilon)p + \varepsilon = \frac{1}{2}$ gives

$$(1 - 2\varepsilon)p = \frac{1}{2} - \varepsilon \implies p = \frac{\frac{1}{2} - \varepsilon}{1 - 2\varepsilon} = \frac{1}{2},$$

for all $\varepsilon \neq \frac{1}{2}$.

Answer

$$\boxed{p = \frac{1}{2}}.$$