Ask Small VLMs Only What They Can See: A Semantic-to-Metric Agent for Embodied Navigation

Anonymous ICCV submission

Paper ID *****

Abstract

Multimodal LLM agents navigate by giving one model every role: it reads the image and its own history, keeps track of the room, and writes the plan. Small open VLMs, the models a robot can run on board, fail in this role. With the EB-Navigation benchmark's agent, Qwen3-VL-4B solves 55.0% of the test episodes, and 25.0% when the target starts behind it. A controlled diagnosis rules out motion planning, since a geometric planner given the target position solves 91.3% of the same episodes, and recognition, since the model boxes a visible target in 69.3–78.7% of single views. What fails is keeping spatial state in generated text. We therefore recast the VLM from planner to sensor. S2M (Semantic-to-Metric) is a training-free navigation agent that asks the VLM only what the current image can answer, whether the target is visible and where, and keeps all state in metric form. Its hypothesis memory lifts each answer with depth and pose, accumulates evidence across distinct viewpoints, and withdraws it when a hypothesis should be visible but is not detected; a search policy and an occupancy-map planner turn the memory into actions. With this model at 4-bit on one 8 GB GPU, S2M reaches 79.4% (+24.4 pp), 82.1% on Long-horizon episodes, and 76.5% from RGB alone, which is still above both fine-tuned 4B agents and seven of ten training-free agents built on larger models. With Qwen2.5-VL-3B it lifts success from 20.3% to 70.0%. On RoboTHOR ObjectNav, which requires an explicit stop, it reaches 59.6%, above ten published zero-shot agents.

1. Introduction

Multimodal LLM (MLLM) agents follow open navigation instructions by giving one model every role: at each step it reads the image and the text history, infers where the target is, and writes the next actions [1]. This design works at frontier scale. On EB-Navigation, GPT-4o succeeds in 57.7% of the episodes, while open models with at most 8B parameters reach 14.0–29.3% overall and 0–5% on the Long-horizon subset, in which the target starts behind the agent. Yet these small models are the ones a robot can run on board or on a consumer GPU.

Existing remedies leave the model in charge. Training-free agents surround it with memory, reflection, skill libraries, scene graphs, or tools [2–6], but the model still writes the plan, and the reported gains rely on 8B to frontier-scale models. Fine-tuned 4B agents [7, 8] require training and remain below 60%. Modular object-navigation systems keep a metric map [9–11] but depend on dedicated detectors.

We first ask what breaks when a small VLM drives the agent. Motion planning does not: a geometric planner given the target position solves 91.3% of the test episodes. Recognition is imperfect but usable: Qwen3-VL-4B boxes a visible target in 69.3–78.7% of single views. The failure lies in the role the model is given. Asked for a plan at every step, it must carry where the target was and which way it faces through generated text (Fig. 1a), and nothing checks this text against the world. Prompted agents therefore lose targets they have seen, collide with furniture, and never turn toward a target behind them (Sec. 3).

A small VLM is thus a good semantic sensor and a poor state keeper, so we build the agent around the model rather than inside it. S2M (Semantic-to-Metric, Fig. 1b) is a training-free navigation agent with three parts. *Perception* asks the VLM two questions per frame, whether the target is visible and where it is in the image, and spends a magnified crop or a tiled view only when the answer is weak. *Memory* lifts each answer with depth and pose into a metric target hypothesis, accumulates evidence only from distinct viewpoints, and withdraws it when a hypothesis should be visible but is not detected. *Action* commits to a confident hypothesis or otherwise searches in the order of an optimal-search index, and an occupancy-map planner computes every move. Each part removes one diagnosed failure: the memory keeps a seen target, the map prevents collisions, and the look-around finds a target behind the agent.

Changing the model's role changes the outcome (Fig. 2), with the profile that the diagnosis predicts. With Qwen3-VL-4B at 4-bit, S2M succeeds in 79.4% of the EB-




Figure 1. **(a)** The EB prompt maps I_t, the instruction ℓ, and the history h_t to a text plan $u_{t:t+m}$ with the VLM f. **(b)** S2M asks f for the presence π_t and box b_t of the phrase s, lifts them with depth D_t and pose p_t into hypotheses μ_k with evidence w_k, selects $k^\star$, and plans u_t on the map M_t. Thumbnails: a Long-horizon test episode; the target (orange) passes the commit threshold (dashed) and two look-alikes (grey) fall below zero.




Figure 2. EB-Navigation test success with the same local model. The benchmark's agent (grey) against S2M (orange) and S2M without a depth sensor or simulator pose (light orange). Ticks: geometric planner given the true target position.

Navigation test episodes, +24.4 pp over the benchmark's agent with the same model, and in 82.1% of the Long-horizon episodes. With Qwen2.5-VL-3B [12] the gain grows to +49.7 pp. On RoboTHOR ObjectNav [13], which requires an explicit stop, S2M reaches 59.6%.

Contributions.

- **Diagnosis.** Small VLMs fail as navigation agents because they must keep spatial state in text, not because they cannot recognize the target or plan a path.
- **The VLM as a sensor, not a planner.** S2M inverts the control of MLLM agents: a metric controller asks the VLM only questions that the current image can settle, and the VLM never sees the history, the map, or the plan.
- **Evidence fusion for a generative sensor.** A metric hypothesis memory accumulates the model's presence and box answers over distinct viewpoints and withdraws them under negative evidence, turning unreliable single answers into a stable target; a generic modular agent with the same model trails S2M by 14.4 pp.
- **RGB-only operation.** A per-frame ground-plane scale for monocular depth raises RGB-only success from 53.0% to 76.5%, within 2.9 pp of a depth sensor.
- **Results.** On the full EB-Navigation and RoboTHOR splits, a 4-bit 4B model without training and from RGB alone outperforms both fine-tuned 4B agents and seven of ten training-free agents built on 8B to frontier-scale models, and the agent loses far less than the benchmark's agent when the model shrinks.

2. Related Work

MLLM agents for embodied tasks. EmbodiedBench [1] evaluates multimodal LLMs on high- and low-level embodied tasks through a standardized action interface; related benchmarks probe embodied decision making and navigation reasoning [14, 15]. Agents are improved by embodied pre-training, online reinforcement learning, or policy-level

reasoning [16–19], or at test time with reflection, experience, memory, or tools [2–4, 20–25]. On EB-Navigation, models of 8B and more also call mapping tools [4] or read a bird's-eye view [26]. All of these agents keep the model as the planner and the reader of its own memory. In S2M the VLM is only a sensor: its answers feed an explicit metric estimator and planner, which is what lets a 4B model drive the agent.

Zero-shot object navigation and semantic memory. Modular zero-shot ObjectNav combines open-vocabulary perception, a map, and a planner, from CoW's frontier exploration [9] to value maps [10], LLM-reasoned scene and goal graphs [11, 27, 28], world models [29], cognitive state machines [30], and VLM-queried structures [31]; instruction-following agents ground language in maps and scene graphs [32–34]. 3D scene graphs, semantic maps, language fields, and embodied memories attach semantics to geometry [35–42]. Closest to our memory, ApexNav fuses target-centric detections over time [43], and AECNav treats expected but absent detections as negative evidence [44]. S2M shares the modular structure of these systems but differs in three ways: a small generative VLM is its only perception model, so it reads open instructions instead of a fixed category list; that model is never asked where to explore, which follows geometric rules; and its memory is a short list of metric target hypotheses built to absorb the false boxes of a generative model.

Verification and search. Spatial prompting, verification, test-time computation, and calibrated uncertainty improve VLM decisions in embodied tasks [45–53]. S2M spends extra queries, a magnified crop or a tiled view, only where the evidence is weak, and chooses among candidate targets with the probability-to-cost index of optimal sequential search [54].

Geometry from images. Learned reconstruction and depth priors recover geometry from RGB [55–60], and sensors can change embodied conclusions [61–63]. S2M applies the ground-plane scale of monocular visual odometry [64] to every frame of a metric depth network. Concurrently, Li *et al*. [65] run Qwen3-VL-4B zero-shot and accumulate its answers as per-direction scores in a bird's-eye field for vision-language navigation; S2M lifts boxes to metric target hypotheses for object navigation.

3. Problem and Diagnosis

Task. An episode gives an instruction ℓ that identifies one object with floor position $x^\star \in \mathbb{R}^2$. At step t the agent observes an RGB frame I_t, depth D_t, a pose $p_t = (x_t, \theta_t, \phi_t)$ of floor position, heading, and camera tilt, and the success flag o_{t-1} of its last action, and it chooses $u_t \in \mathcal{U}$: four 0.25 m translations, two 90° turns, and two 30° tilts. The episode is successful if

$$\exists\, t \le T : \ \|x_t - x^\star\| \le 1\,\mathrm{m}, \qquad T = 20. \tag{1}$$

EB-Navigation [1] poses this task in single AI2-THOR rooms [66]; its test set has five subsets of 60 episodes. *Base* names the category, *Common* describes the object by its use, *Complex* embeds it in a longer instruction, *Visual* describes only its appearance, and *Long* repeats Base with the agent turned away from the target.

The benchmark's agent. The benchmark's own agent, the *EB prompt*, maps the image and its text history $h_t = (u_{0:t-1}, o_{0:t-1})$ directly to a plan,

$$(u_t, \dots, u_{t+m}) = f(I_t, \ell, h_t), \tag{2}$$

which is executed until an action fails. All spatial state, where the target was, what the room contains, and how the agent has turned, must be carried by h_t and the generated reasoning. S2M factorizes the same decision:

$$\begin{gathered}(\pi_t, b_t) = f(I_t, s),\\ \mathcal{B}_t = g(\mathcal{B}_{t-1}, \pi_t, b_t, D_t, p_t), \qquad u_t = \rho(\mathcal{B}_t, p_t),\end{gathered} \tag{3}$$

where s is a target phrase, f answers only questions about I_t, and the metric belief $\mathcal{B}_t$ and the planner ρ hold all state and every decision (Sec. 4 and Fig. 3). The configuration of S2M was fixed on a development split of 150 episodes that we built with the benchmark's generator on 30 iTHOR rooms not used by the test set.

Planning is not the bottleneck. Replacing the target belief of S2M by the true $x^\star$, with the same occupancy map and planner, solves 91.3% of the 300 test episodes (93.3% on each of the first four subsets and 83.3% on Long).

Single views are informative but unreliable. For each test episode of the first four subsets we render the start view and the three other 90° headings and query the VLM with the phrase s. Qwen3-VL-4B places a box with IoU$\ge$0.3 on the visible target in 78.7, 69.3, 77.3, and 49.3% of the views on Base, Common, Complex, and Visual (75 visible instances each). It also errs the other way: on views that do not show the target it still places a box in 15–19% of the cases for named categories and in 41% for appearance-only phrases. A single answer is therefore evidence, not a decision.

The prompted agent loses spatial state. We label each failed episode by its first matching outcome: *never seen*, *near miss* (within 1.5 m), *lost after seen* (out of view in the last five steps), *blocked* (30% of actions rejected), oscillation, or approach failure. Of the 135 episodes that the EB prompt fails with Qwen3-VL-4B, 43 lose a target that was in view, 26 are blocked by collisions, and 34 end within 1.5 m (Fig. 4b); in 12 Long episodes the agent never brings the target into view.

What the diagnosis predicts. If small VLMs fail because their role makes them carry spatial state through text,




Figure 3. One step of S2M. The frozen VLM f gives the presence π_t and box b_t of the phrase s on the frame I_t; a weak answer is checked on a crop or on tiles, which sets its weight a_t. The box is lifted to a floor point q_t with depth D_t and pose p_t and fused into a hypothesis μ_k within r, or starts one; $\gamma_t < 1$ discounts a repeated view, and a hypothesis that should be seen but is not loses λ of its evidence w_k. Above τ_c a hypothesis is committed, and the agent goes to $\mu_{k^\star}$; A* on the map M_t gives the action u_t.

an agent that keeps this state outside the model, with the same model and the same actions, should (i) remove the never-seen and blocked failures and reduce the lost-after-seen ones; (ii) gain most on Long, where the target must be remembered across turns; (iii) gain least on Visual, where single-view recognition is weakest and stays the limit; and (iv) depend far less on the size of the model, which no longer plans (Sec. 5).

4. Semantic-to-Metric Navigation

S2M is a navigation agent that instantiates the factorization of Eq. (3): the VLM is its semantic sensor, and the agent owns all state and every decision. The belief $\mathcal{B}_t = (\mathcal{H}_t, M_t)$ consists of a list of target hypotheses $\mathcal{H}_t$ and an occupancy map M_t; Fig. 3 shows one step in full.

4.1. Per-image questions

At the start of an episode the VLM f rewrites ℓ into a target phrase s: the category when the instruction names or implies one, and the appearance words when it describes only how the object looks. At every step two queries about the current frame run in parallel. The presence probability is read from the first answer token,

$$\pi_t = \frac{P_f(\mathit{yes} \mid I_t, s)}{P_f(\mathit{yes} \mid I_t, s) + P_f(\mathit{no} \mid I_t, s)}, \tag{4}$$

and the second query returns a box b_t for s or none. Neither query contains the action history, the map, or earlier answers, so every answer can be checked against the image alone.

Lifting. A box with centre $c(b_t) = (u, v)$ is lifted with the median depth $\tilde{d}_t$ over its central half (half its width and half its height). With focal length φ and principal point (u_0, v_0) of the pinhole camera, tilt ϕ_t, and the forward and right unit vectors $e_f(\theta_t), e_r(\theta_t)$ of the heading,

$$q_t = x_t + \tilde{d}_t \Big[\big(\cos\phi_t - \tfrac{v-v_0}{\varphi} \sin\phi_t \big)\, e_f(\theta_t) + \tfrac{u-u_0}{\varphi}\, e_r(\theta_t) \Big], \tag{5}$$

which we write $q_t = \Pi_{p_t}^{-1}(c(b_t), \tilde{d}_t)$; lifts with $\tilde{d}_t > 6\,\mathrm{m}$ are discarded. The same back-projection, with the known camera height, labels each depth pixel as floor (height below 0.10 m) or obstacle (0.10–1.9 m) in a 5 cm occupancy grid M_t.

Observation weight. A lifted box enters the memory with weight

$$a_t = \begin{cases} \pi_t & \text{if the target is named and } \pi_t \ge \tfrac{1}{2}, \\ \pi_t^z & \text{otherwise, if } \pi_t^z \ge \tfrac{1}{2}, \\ 0.2\,\pi_t^z & \text{otherwise,} \end{cases} \tag{6}$$

where π_t^z is the presence probability of a *crop check*, a square crop of 2.5 times the box's longer side resized to 448 px. The crop is queried only when presence and box disagree or when the goal is appearance-only, so the extra cost is paid where the evidence is weak.

4.2. Metric hypothesis memory

Each hypothesis k stores a floor position μ_k, evidence w_k, and the poses V_k from which it was seen. An observation (q_t, a_t) is associated with the first hypothesis within $r = 0.5$ m. If there is one, then

$$\mu_k \leftarrow \frac{n_k \mu_k + q_t}{n_k + 1}, \qquad w_k \leftarrow w_k + \gamma_t\, a_t, \tag{7}$$

with n_k the number of fused observations and $\gamma_t = 0.25$ if some $v \in V_k$ has the heading of p_t and a position within 0.2 m of it, else $\gamma_t = 1$; otherwise a new hypothesis $(\mu, w) = (q_t, a_t)$ is created. Through γ_t, evidence grows with the number of distinct viewpoints rather than with the number of frames.

Negative evidence. A hypothesis that the current frame should show but that receives no detection loses evidence:

$$w_k \leftarrow w_k - \lambda \mathbb{1}\big[\mathrm{vis}_t(\mu_k)\big], \qquad \mathrm{vis}_t(\mu) \Leftrightarrow \bar{u} \in \Omega,\ \ d \le 6\,\mathrm{m},\ \ D_t(\bar{u}) + 0.3 \ge d, \tag{8}$$

for every hypothesis without a detection within r, where $(\bar{u}, d) = \Pi_{p_t}(\mu)$ are its pixel and planar depth, Ω is the image shrunk by 20 px, and $\lambda = 0.4$; the last condition rules out occlusion. Hypotheses with $w_k \le -1$ are removed; absence outside the view is never counted.

Commitment and exhaustion. The agent commits to a hypothesis once $w_k \ge \tau_c = 0.8$ and keeps it while $w_k \ge \tau_k = 0.4$; the hysteresis prevents one missed detection from abandoning a well-supported target. When the agent stands within 0.9 m of a committed hypothesis and the episode continues, which on EB-Navigation means that it is not the target, the hypothesis is marked exhausted. It stays in memory, so later detections of the same look-alike merge into it instead of creating a new target.

4.3. Search and control

Selection. Among the committed hypotheses $\mathcal{C}_t$ the agent visits

$$k^\star = \arg\max_{k \in \mathcal{C}_t} \frac{1 - e^{-w_k}}{c_k + 1}, \qquad c_k = \frac{\|\mu_k - x_t\|}{0.25\,\mathrm{m}}. \tag{9}$$

The numerator is the probability of at least one detection under a Poisson model with mean w_k, and the denominator counts the steps to reach and check μ_k; inspecting in decreasing order of this ratio is optimal for fixed costs [54], and S2M applies it greedily from the current position. With nothing committed, the agent first completes a 360° look-around, then approaches the strongest hypothesis with $w_k \ge 0.35$, and otherwise moves to the observed free cell 0.75–3 m away that is farthest from all visited positions.

Planning. Actions come from A* over (position, heading) on M_t, whose edges are the benchmark's translations and turns. An edge costs 1 plus 0.15 for each of four sampled points on it that is unobserved; edges through inflated obstacles are removed, and a move that the simulator has rejected becomes a forbidden edge.

Magnified search. When a view yields no observation with $a_t \ge 0.5$ and nothing is committed, the frame is split into 3×3 overlapping tiles, each upsampled to 448 px and queried for a box; up to four tile boxes are crop-checked, and those with $\pi^z \ge 0.5$ enter the memory. This finds small or distant targets once per view, at the cost of VLM calls rather than environment steps.

4.4. RGB-only and explicit-stop variants

Monocular metric depth networks err mostly by a frame-dependent scale. Let $\hat{D}_t$ be the raw prediction and $\kappa(v) = \sin\phi_t + \frac{v - v_0}{\varphi}\cos\phi_t$ the downward component of the ray through row v per unit of planar depth. A pixel on the floor satisfies $\sigma \hat{D}_t(u,v)\,\kappa(v) = h$ for the camera height h, and an object standing on the floor gives a larger σ. Over the pixels $\mathcal{F}_t$ whose rays point at least 15° below the horizontal, S2M takes the mode

$$\sigma_t = \operatorname*{mode}_{(u,v)\in\mathcal{F}_t} \frac{h}{\hat{D}_t(u,v)\,\kappa(v)}, \qquad D_t = \sigma_t\,\hat{D}_t, \tag{10}$$

with the mode taken over values in $[\bar{\sigma}/1.33,\ 1.33\,\bar{\sigma}]$, where $\bar{\sigma}$ is one global scale fitted on development frames; it keeps $\bar{\sigma}$ when fewer than 10% of the pixels in $\mathcal{F}_t$ fall in this window. This is the ground-plane constraint of monocular visual odometry [64] applied per frame. Pose comes from dead reckoning over the executed actions,

$$\hat{x}_{t+1} = \hat{x}_t + 0.25\,o_t\big(\alpha_f e_f(\hat{\theta}_t) + \alpha_r e_r(\hat{\theta}_t)\big), \tag{11}$$

with $(\alpha_f, \alpha_r) \in \{(\pm 1, 0), (0, \pm 1)\}$ the translation of u_t, and heading and tilt advanced by the turn or tilt of u_t when $o_t = 1$.

Explicit stopping. EB-Navigation ends an episode on success; RoboTHOR requires a Stop action. There the agent stops only when it is within 0.9 m of a committed hypothesis, has turned within 20° of it and tilted it into view, and a fresh presence query exceeds 0.5; otherwise the hypothesis is exhausted. Because RoboTHOR episodes last up to 500 steps, negative evidence counts only within 3 m and once per view, and exploration goes to the nearest frontier.

5. Experiments

Setup. We evaluate on the full EB-Navigation test set (300 episodes, official environment, actions, and success test) and on the full RoboTHOR ObjectNav validation split [13] (1800 episodes, 15 apartments, 12 categories; stochastic LoCoBot actuation, 30° turns, 500 steps, and a Stop that succeeds within 1 m of a visible target-category object). The models are Qwen3-VL-4B-Instruct [70] and Qwen2.5-VL-3B-Instruct, served with vLLM [71] at temperature 0 on one 8 GB RTX 5060 that also renders the simulator; S2M uses their 4-bit AWQ checkpoints. The EB prompt uses the benchmark's prompts, three examples, parser, and plan execution. Monocular depth comes from Depth Anything V2 Metric-Indoor-Base [59] on the CPU. *Protocol.* S2M was run four times and the RGB-only configuration twice, each entering with its per-episode mean. All comparisons are paired over the 300 episodes, with bootstrap 95% CIs and sign-flip permutation tests, Holm-corrected over the ten variants of Sec. 5.2.

5.1. Main results

With Qwen3-VL-4B, S2M succeeds in 79.4% of the episodes against 55.0% for the EB prompt (Tab. 1), a paired gain of +24.4 pp (CI [+18.0, +30.8], $p<10^{-5}$). The gain

Table 1. Success rate (%) on EB-Navigation test. Top: reported results. Bottom: our runs on one 8 GB GPU, with S2M at 4-bit. ±: std. over test runs. Bold: best per model.

Method	Model	Base	Common	Complex	Visual	Long	Avg.	95% CI
Prompted MLLMs (EmbodiedBench)								
EB prompt [1]	GPT-4o	55.0	60.0	58.3	60.0	55.0	57.7	–
EB prompt [1]	InternVL3-78B	66.7	63.3	61.7	45.0	31.7	53.7	–
EB prompt [1]	Gemini-2.0-flash	63.3	65.0	50.0	51.7	13.3	48.7	–
EB prompt [1]	Claude-3.7-Sonnet	50.0	61.7	50.0	36.7	26.7	45.0	–
EB prompt [1]	Qwen2.5-VL-72B	46.7	46.7	46.7	26.7	33.3	40.0	–
EB prompt [1]	InternVL3-8B	38.3	30.0	40.0	33.3	5.0	29.3	–
EB prompt [1]	Qwen2.5-VL-7B	20.0	26.7	38.3	16.7	0.0	20.3	–
Training-free agents								
MOSAIC (module graph) [67]	Qwen3-VL-8B	60.0	46.7	45.6	51.1	46.7	50.0	–
ESCA (scene graph) [5]	GPT-4o	66.7	62.0	63.3	55.0	26.7	54.7	–
EmbodiSkill (skills) [6]	Qwen3-VL-32B	65.0	68.0	73.0	67.0	33.0	61.3	–
HODAgent (agent loop) [68]	Qwen3.6-35B-A3B	76.7	55.0	68.3	55.0	36.7	58.3	–
RoboFoundry (self-evolving) [69]	Qwen3.8-27B	76.7	85.0	73.3	63.3	43.3	68.3	–
BrainMem (memory) [3]	GPT-4o	73.3	71.7	80.0	66.6	63.3	71.0	–
EMHO (harness) [2]	Qwen3.8-27B	86.7	76.7	73.3	76.7	63.3	75.3	–
RoboFoundry (self-evolving) [69]	GPT-6 Astra	90.0	85.0	86.7	73.3	66.7	80.3	–
Tool library [4]	Qwen3-VL-8B	85.0	85.0	77.0	75.0	77.0	80.0	–
Tool library [4]	GPT-4o	80.0	85.0	85.0	80.0	83.0	83.0	–
Fine-tuned								
SVA (Q-model) [7]	Qwen3.5-4B	54.2	41.7	45.8	41.7	50.0	46.7	–
MuSix (world models) [8]	Qwen3-VL-4B	63.2	63.2	57.6	62.4	43.2	57.9	–
Ours (one 8 GB GPU)								
EB prompt	Qwen3-VL-4B	66.7	65.0	65.0	**53.3**	25.0	55.0	[49.3, 60.7]
Modular, single view[§]	Qwen3-VL-4B	73.3	63.3	63.3	51.7	73.3	65.0	[59.7, 70.3]
S2M [§]	Qwen3-VL-4B	**89.6**	**84.2**	**88.3**	52.9	**82.1**	**79.4** ±0.5	[75.0, 83.7]
S2M, RGB only[†]	Qwen3-VL-4B	85.0	80.8	85.8	52.5	78.3	76.5 ±0.2	[71.8, 81.0]
EB prompt	Qwen2.5-VL-3B	21.7	21.7	28.3	20.0	10.0	20.3	[16.0, 25.0]
S2M [§]	Qwen2.5-VL-3B	**78.3**	**71.7**	**71.7**	**53.3**	**75.0**	**70.0**	[64.7, 75.0]
Oracle target[‡]	–	93.3	93.3	93.3	93.3	83.3	91.3	[88.0, 94.3]

[§]Depth sensor and simulator pose. [†]RGB only: monocular depth and pose from the executed actions (Sec. 5.3); the comparisons with reported results use this row. [‡]Geometric planner given the true target position: an upper bound.

follows the predictions of Sec. 3. It is largest where the target starts behind the agent (ii): on Long, S2M succeeds in 82.1% against 25.0% (Fig. 5a), 1.3 pp below the oracle, and it is +22.9, +19.2, and +23.3 pp on Base, Common, and Complex. On Visual, the smallest gain with both models, the two agents are level (iii; −0.4 pp, CI $[-15.0, +14.6]$, p=1.00; Sec. 5.4). With Qwen2.5-VL-3B, S2M reaches 70.0% against 20.3% (+49.7 pp, CI [+43.0, +56.3]): the smaller model costs S2M 9.4 pp and the EB prompt 34.7 pp (iv).

Efficiency. On the 140 episodes that both agents solve in every run, S2M needs 11.1 steps against 12.6 (p=1.9×10^{-4}); within ten steps it solves 28.2% of the episodes against 16.0% (Fig. 4a).

Comparison with published agents. With a 4B model, no training, and RGB alone (76.5%), S2M exceeds every prompted MLLM up to GPT-4o and the training-free agents built on GPT-4o and 8–35B models [2, 3, 5, 6, 67–69], and MuSix and SVA, which train extra models around a 4B policy [7, 8]. Only the tool-library agents [4] and RoboFoundry on GPT-6 Astra score higher (Fig. 6).

Where the gain comes from. The diagnosed failure modes largely disappear (i). Per run, S2M never sees the target in 0.8 episodes (EB prompt: 12), is blocked in 0.5 (26), loses a seen target in 28.5 (43), and ends near it in 9.8 (34) (Fig. 4b, Fig. 5).

5.2. Components

Generic modular agent. The same model in a generic modular agent, which acts on single-view detections with the same map, planner, look-around, and exploration, reaches 65.0% (Tab. 1): +10.0 pp over the EB prompt (p=0.01), but 14.4 pp below S2M (CI [+9.0, +19.9], p<10^{-5}). Moving the state out of the model gives part of the gain, and the evidence design for a generative sensor the rest. Table 2 changes one element at a time. Disabling multi-view fusion,




Figure 4. EB-Navigation test, Qwen3-VL-4B. **(a)** Episodes solved within a step budget, averaged over runs. **(b)** Failed episodes by outcome (first matching rule, Sec. 3; mean over the runs of S2M). **(c)** Lifted range divided by true range for detections within 1 m of the target, with medians (dashed), for S2M with the depth sensor and with monocular depth under a global and a per-frame floor scale (Eq. (10)).

Table 2. Components and sensing on EB-Navigation test (Qwen3-VL-4B). Δ: paired difference from the full model; p: sign-flip permutation test, Holm-corrected. Bold: significant.

Variant	Base	Common	Complex	Visual	Long	Avg.	Δ (95% CI)		p
S2M (full)	89.6	84.2	88.3	52.9	82.1	79.4	–		–
Components									
w/o fusion	78.3	70.0	75.0	41.7	80.0	69.0	**−10.4**	[−15.0, −6.0]	8.1×10^{-5}
w/o look-around	95.0	91.7	91.7	71.7	48.3	79.7	+0.2	[−4.2, +4.8]	1.00
w/o exhaustion	88.3	85.0	88.3	46.7	83.3	78.3	−1.1	[−2.5, +0.2]	0.89
w/o neg. evidence	93.3	83.3	88.3	58.3	81.7	81.0	+1.6	[−1.2, +4.5]	1.00
w/o tiled search	86.7	80.0	85.0	60.0	80.0	78.3	−1.1	[−4.5, +2.4]	1.00
w/o crop check	85.0	80.0	83.3	51.7	83.3	76.7	−2.8	[−5.7, +0.1]	0.57
strongest first	90.0	85.0	90.0	55.0	83.3	80.7	+1.2	[−0.3, +2.9]	0.89
Sensing									
odometry noise (5%, 2°)	91.7	81.7	90.0	50.0	83.3	79.3	−0.1	[−3.1, +2.9]	1.00
RGB only, global scale	56.7	58.3	60.0	36.7	53.3	53.0	**−26.4**	[−32.4, −20.5]	$<10^{-5}$
RGB only, floor scale	85.0	80.8	85.8	52.5	78.3	76.5	−2.9	[−6.3, +0.3]	0.67

so that each detection replaces the earlier hypotheses, lowers success by 10.4 pp (Holm p=8.1×10^{-5}), the only component whose removal survives the correction. Fusion does not help the agent find the target; it keeps the target once found: 74% of single lifted detections lie within 0.5 m of it, and a hypothesis there reaches commitment in 264 episodes without fusion and 258 with it. Without fusion, each detection, including the false boxes of Sec. 3, replaces the committed hypothesis, and lost targets rise from 28.5 to 42 episodes and near misses from 9.8 to 20. Removing the look-around leaves the average unchanged (0.2 pp) but trades one subset against the others: Long changes by −33.7 pp because the agent no longer turns to find a target behind it, while the other subsets gain the steps that the turn no longer costs (+3.3 to +18.8 pp). Negative evidence, tiled search, the crop check, and the search index each change success by less than 3 pp, none significantly. They cost no environment steps and matter when candidates compete, which EB-Navigation's single rooms rarely produce.

5.3. Sensing

Pose. Dead reckoning (Eq. (11)) is exact in heading and tilt and errs by 0.10 m in position on average, from the simulator's grid snapping. Accumulated odometry noise of 5% per translation and 2° per turn changes success by −0.1 pp (Tab. 2).

Depth. Monocular depth with one global scale $\bar{\sigma}$ is not enough: with pose from the executed actions, S2M reaches 53.0%, level with the EB prompt (−2.0 pp, p=0.65). The global scale places target detections at a median 0.90 of their true range (Fig. 4c) and lifts 42.5% of the nearby floor above the obstacle threshold, so the agent walks to a point short of the target: 66 failures exhaust a hypothesis within 1 m of it, none with the sensor. The per-frame floor scale (Eq. (10)) lowers the falsely blocked floor to 9.9% and moves the range ratio to 0.93 (sensor: 0.97); success rises to 76.5%, +21.5 pp over the EB prompt ($p<10^{-5}$) and 2.9 pp below the depth sensor (Holm p=0.67).




Figure 5. Trajectories on three EB-Navigation test episodes (Qwen3-VL-4B), with the hypotheses of S2M at the end of the episode sized by evidence. Grey: reachable floor.




Figure 6. EB-Navigation success against model size (Tab. 1). Arrows: gain of S2M over the EB prompt.




Figure 7. S2M on RoboTHOR validation by target category.

5.4. Remaining gap: appearance-only goals

Visual accounts for 68% of the gap to the oracle and is the only subset on which S2M does not exceed the EB prompt. The failure is recognition: a candidate comes within 0.5 m of the target in 93–98% of the episodes of every other subset but in 63–67% of the Visual ones, and 65 of the 113 Visual failures never produce one.

Table 3. RoboTHOR ObjectNav validation (1800 episodes). Bold: best; underlined: second. §From SG-Nav [11].

Method	Input	Year	SR	SPL
Zero-shot				
CoW [9]	RGB-D	2022	26.7	16.9
LGX [72]	RGB-D	2024	35.0	21.9
ESC [73]	RGB-D	2023	38.1	22.2
L3MVN§ [74]	RGB-D	2023	41.2	22.5
VLFM§ [10]	RGB-D	2023	42.3	23.0
OpenFMNav§ [75]	RGB-D	2024	44.1	23.3
SG-Nav [11]	RGB-D	2024	47.5	24.0
UniGoal [28]	RGB-D	2025	48.0	24.2
CogNav [30]	RGB-D	2024	54.6	24.3
MVP-Nav [76]	RGB	2026	57.5	26.8
ForesightNav [77]	RGB-D	2026	62.5	32.9
STRIVE [31]	RGB-D	2025	**68.1**	**36.3**
Trained for the task				
ProcTHOR [9, 78]	RGB	2022	<u>66.4</u>	27.4
S2M (Qwen3-VL-4B)	RGB-D	–	59.6	<u>35.9</u>

5.5. RoboTHOR ObjectNav

On the full RoboTHOR validation split, S2M reaches 59.6% success and 35.9% SPL. Among zero-shot methods (Tab. 3) its SR is below only ForesightNav (12B [77]) and STRIVE (Gemini-2.0-flash [31]), and its SPL only below STRIVE. Figure 7 gives each category.

6. Conclusion

Small VLMs fail as navigators when agents make them keep spatial state in text. Used as a semantic sensor whose answers enter a metric memory, a training-free 4B model on one 8 GB GPU matches agents built on far larger ones. The controller is specific to reaching one object; appearance-only goals, whole houses, and real robots remain open.

References

[1] Rui Yang, Hanyang Chen, Junyu Zhang, Mark Zhao, Cheng Qian, Kangrui Wang, Qineng Wang, Teja Venkat Koripella, Marziyeh Movahedi, Manling Li, Heng Ji, Huan Zhang, and Tong Zhang. EmbodiedBench: Comprehensive Benchmarking Multi-modal Large Language Models for Vision-Driven Embodied Agents, 2025. ICML 2025, arXiv:2502.09560. 1, 2, 3, 6

[2] Hyun Jung Lee, Jungtaek Kim, Jongwon Jeong, Tae-Eui Kam, Donghyun Kim, and Yong Jae Lee. EMHO: EMbodied Agent Harness Optimization via Experience Traces, 2026. arXiv preprint arXiv:2610.08432. 1, 3, 6

[3] Xiaoyu Ma, Lianyu Hu, Wenbing Tang, Zixuan Hu, Zeqin Liao, Zhizhen Wu, and Yang Liu. BrainMem: Brain-Inspired Evolving Memory for Embodied Agent Task Planning, 2026. arXiv preprint arXiv:2604.16331. 6

[4] Xueyang Zhou, Zijia Wang, Qianjiang Li, Yibo Hu, Guiyao Tie, Li Wan, Yidan Liu, Pan Zhou, Lichao Sun, and Yongchao Chen. Enabling Extensible Embodied Capabilities with Tools, 2026. arXiv preprint arXiv:2605.26637. 3, 6

[5] Jiani Huang, Amish Sethi, Matthew Kuo, Mayank Keoliya, Neelay Velingker, JungHo Jung, Ser-Nam Lim, Ziyang Li, and Mayur Naik. ESCA: Contextualizing embodied agents via scene-graph generation. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025. 6

[6] Ruofei Ju, Xinrui Wang, Xin Ding, Yifan Yang, Hao Wu, Shiqi Jiang, Qianxi Zhang, Hao Wen, Xiangyu Li, Weijun Wang, Kun Li, Yunxin Liu, Haipeng Dai, Wei Wang, and Ting Cao. EmbodiSkill: Skill-aware reflection for self-evolving embodied agents, 2026. arXiv preprint arXiv:2605.10332. 1, 6

[7] Xinyi Xie, Zican Hu, Zhanyu Liu, Yicheng Dong, Wenhao Wu, Zhenhong Sun, Haoran Li, Chunlin Chen, Zhi Wang, and Pichao Wang. Look before you leap: Distilling tree search into action evaluation for frozen VLA models, 2026. arXiv preprint arXiv:2607.03751. 1, 6

[8] Jinwoo Jang, Daniel J. Rho, Sihyung Yoon, Hyunsuk Cho, and Honguk Woo. Multi-scale mixture of world models for embodied agents in evolving environments, 2026. arXiv preprint arXiv:2607.00457. 1, 6

[9] Samir Yitzhak Gadre, Mitchell Wortsman, Gabriel Ilharco, Ludwig Schmidt, and Shuran Song. CoWs on Pasture: Baselines and Benchmarks for Language-Driven Zero-Shot Object Navigation, 2023. CVPR 2023, arXiv:2203.10421. 1, 3, 8

[10] Naoki Yokoyama, Sehoon Ha, Dhruv Batra, Jiuguang Wang, and Bernadette Bucher. VLFM: Vision-Language Frontier Maps for Zero-Shot Semantic Navigation, 2024. ICRA 2024, arXiv:2312.03275. 3, 8

[11] Hang Yin, Xiuwei Xu, Zhenyu Wu, Jie Zhou, and Jiwen Lu. SG-Nav: Online 3D Scene Graph Prompting for LLM-based Zero-shot Object Navigation, 2024. NeurIPS 2024, arXiv:2410.08189. 1, 3, 8

[12] Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, et al. Qwen2.5-VL Technical Report, 2025. arXiv preprint arXiv:2502.13923. 2

[13] Matt Deitke, Winson Han, Alvaro Herrasti, Aniruddha Kembhavi, Eric Kolve, Roozbeh Mottaghi, Jordi Salvador, Dustin Schwenk, Eli VanderBilt, Matthew Wallingford, Luca Weihs, Mark Yatskar, and Ali Farhadi. RoboTHOR: An Open Simulation-to-Real Embodied AI Platform, 2020. CVPR 2020, arXiv:2004.06799. 2, 5

[14] Manling Li, Shiyu Zhao, Qineng Wang, Kangrui Wang, Yu Zhou, Sanjana Srivastava, Cem Gokmen, Tony Lee, Li Erran Li, Ruohan Zhang, Weiyu Liu, Percy Liang, Li Fei-Fei, Jiayuan Mao, and Jiajun Wu. Embodied Agent Interface: Benchmarking LLMs for Embodied Decision Making, 2024. NeurIPS 2024 Datasets & Benchmarks, arXiv:2410.07166. 2

[15] Yanyuan Qiao, Haodong Hong, Wenqi Lyu, Dong An, Siqi Zhang, Yutong Xie, Xinyu Wang, and Qi Wu. NavBench: Probing Multimodal Large Language Models for Embodied Navigation, 2025. arXiv preprint arXiv:2506.01031. 2

[16] Hanyang Chen, Mark Zhao, Rui Yang, Qinwei Ma, Ke Yang, Jiarui Yao, Kangrui Wang, Hao Bai, Zhenhailong Wang, Rui Pan, Mengchao Zhang, Jose Barreiros, Aykut Onol, ChengXiang Zhai, Heng Ji, Manling Li, Huan Zhang, and Tong Zhang. ERA: Transforming VLMs into Embodied Agents via Embodied Prior Learning and Online Reinforcement Learning, 2025. arXiv preprint arXiv:2510.12693. 3

[17] Kangrui Wang, Pingyue Zhang, Zihan Wang, Yaning Gao, Linjie Li, Qineng Wang, Hanyang Chen, Chi Wan, Yiping Lu, Zhengyuan Yang, Lijuan Wang, Ranjay Krishna, Jiajun Wu, Li Fei-Fei, Yejin Choi, and Manling Li. VAGEN: Reinforcing World Model Reasoning for Multi-Turn VLM Agents, 2025. NeurIPS 2025, arXiv:2510.16907.

[18] Wenqi Zhang, Mengna Wang, Gangao Liu, Xu Huixin, Yiwei Jiang, Yongliang Shen, Guiyang Hou, Zhe Zheng, Hang Zhang, Xin Li, Weiming Lu, Peng Li, and Yueting Zhuang. Embodied-Reasoner: Synergizing Visual Search, Reasoning, and Action for Embodied Interactive Tasks, 2025. arXiv preprint arXiv:2503.21696.

[19] Jinrui Liu, Bingyan Nie, Boyu Li, Yaran Chen, Yuze Wang, Shunsen He, and Haoran Li. RoboGPT-R1: Enhancing Robot Task Planning with Reinforcement Learning, 2026. AAMAS 2026, arXiv:2510.14828. 3

[20] Noah Shinn, Federico Cassano, Edward Berman, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language Agents with Verbal Reinforcement Learning, 2023. NeurIPS 2023, arXiv:2303.11366. 3

[21] Andrew Zhao, Daniel Huang, Quentin Xu, Matthieu Lin, Yong-Jin Liu, and Gao Huang. ExpeL: LLM Agents Are Experiential Learners, 2024. AAAI 2024, arXiv:2308.10144.

[22] Minghao Chen, Yihang Li, Yanting Yang, Shiyu Yu, Binbin Lin, and Xiaofei He. AutoManual: Constructing Instruction Manuals by LLM Agents via Interactive Environmental Learning, 2024. NeurIPS 2024, arXiv:2405.16247.

[23] Zora Zhiruo Wang, Jiayuan Mao, Daniel Fried, and Graham Neubig. Agent Workflow Memory, 2024. arXiv preprint arXiv:2409.07429.

[24] Mingcong Lei, Honghao Cai, Yuyuan Yang, Yimou Wu, Jinke Ren, Zezhou Cui, Liangchen Tan, Junkun Hong, Gehan Hu, Shuangyu Zhu, Shaohan Jiang, Ge Wang, Junyuan Tan, Zhenglin Wan, Zheng Li, Zhen Li, Shuguang Cui, Yiming

Zhao, and Yatong Han. RoboMemory: A Brain-inspired Multi-memory Agentic Framework for Interactive Environmental Learning in Physical Embodied Systems, 2025. arXiv preprint arXiv:2508.01415.

[25] Nishad Singhi, Christian Bialas, Snehal Jauhri, Vignesh Prasad, Georgia Chalvatzaki, Marcus Rohrbach, and Anna Rohrbach. Think Twice, Act Once: Verifier-Guided Action Selection For Embodied Agents, 2026. CVPR 2026 Findings, arXiv:2605.12620. 3

[26] Zhengcheng Wang, Zichuan Lin, Yijun Yang, Haobo Fu, and Deheng Ye. SeeNav-Agent: Enhancing Vision-Language Navigation with Visual Prompt and Step-Level Policy Optimization, 2025. arXiv preprint arXiv:2512.02631. 3

[27] Xun Huang, Shijia Zhao, Yunxiang Wang, Xin Lu, Wanfa Zhang, Rongsheng Qu, Weixin Li, Yunhong Wang, and Chenglu Wen. MSGNav: Unleashing the Power of Multimodal 3D Scene Graph for Zero-Shot Embodied Navigation, 2026. CVPR 2026, arXiv:2511.10376. 3

[28] Hang Yin, Xiuwei Xu, Lingqing Zhao, Ziwei Wang, Jie Zhou, and Jiwen Lu. UniGoal: Towards Universal Zero-shot Goal-oriented Navigation, 2025. CVPR 2025, arXiv:2503.10630. 3, 8

[29] Dujun Nie, Xianda Guo, Yiqun Duan, Ruijun Zhang, and Long Chen. WMNav: Integrating Vision-Language Models into World Models for Object Goal Navigation, 2025. IROS 2025, arXiv:2503.02247. 3

[30] Yihan Cao, Jiazhao Zhang, Zhinan Yu, Shuzhen Liu, Zheng Qin, Qin Zou, Bo Du, and Kai Xu. CogNav: Cognitive Process Modeling for Object Goal Navigation with LLMs, 2025. ICCV 2025, arXiv:2412.10439. 3, 8

[31] Haokun Zhu, Zongtai Li, Zhixuan Liu, Wenshan Wang, Ji Zhang, Jonathan Francis, and Jean Oh. STRIVE: Structured Representation Integrating VLM Reasoning for Efficient Object Navigation, 2025. arXiv preprint arXiv:2505.06729. 3, 8

[32] Yuxing Long, Wenzhe Cai, Hongcheng Wang, Guanqi Zhan, and Hao Dong. InstructNav: Zero-shot System for Generic Instruction Navigation in Unexplored Environment, 2024. arXiv preprint arXiv:2406.04882. 3

[33] Krishan Rana, Jesse Haviland, Sourav Garg, Jad Abou-Chakra, Ian Reid, and Niko Suenderhauf. SayPlan: Grounding Large Language Models using 3D Scene Graphs for Scalable Robot Task Planning, 2023. CoRL 2023, arXiv:2307.06135.

[34] Abdelrhman Werby, Chenguang Huang, Martin Büchner, Abhinav Valada, and Wolfram Burgard. Hierarchical Open-Vocabulary 3D Scene Graphs for Language-Grounded Robot Navigation, 2024. RSS 2024, arXiv:2403.17846. 3

[35] Qiao Gu, Alihusein Kuwajerwala, Sacha Morin, Krishna Murthy Jatavallabhula, Bipasha Sen, Aditya Agarwal, Corban Rivera, William Paul, Kirsty Ellis, Rama Chellappa, Chuang Gan, Celso Miguel de Melo, Joshua B. Tenenbaum, Antonio Torralba, Florian Shkurti, and Liam Paull. ConceptGraphs: Open-Vocabulary 3D Scene Graphs for Perception and Planning, 2024. ICRA 2024, arXiv:2309.16650. 3

[36] Jiajun Jiang, Yiming Zhu, Zirui Wu, and Jie Song. DualMap: Online Open-Vocabulary Semantic Mapping for Natural Language Navigation in Dynamic Changing Scenes, 2025. IEEE RA-L 2025, arXiv:2506.01950.

[37] Minghan Qin, Wanhua Li, Jiawei Zhou, Haoqian Wang, and Hanspeter Pfister. LangSplat: 3D Language Gaussian Splatting, 2024. CVPR 2024, arXiv:2312.16084.

[38] Saimouli Katragadda, Cho-Ying Wu, Yuliang Guo, Xinyu Huang, Guoquan Huang, and Liu Ren. Online Language Splatting, 2025. arXiv preprint arXiv:2503.09447.

[39] Seungjun Lee, Zihan Wang, Yunsong Wang, and Gim Hee Lee. EmbodiedSplat: Online Feed-Forward Semantic 3DGS for Open-Vocabulary 3D Scene Understanding, 2026. CVPR 2026, arXiv:2603.04254.

[40] Yuncong Yang, Han Yang, Jiachen Zhou, Peihao Chen, Hongxin Zhang, Yilun Du, and Chuang Gan. 3D-Mem: 3D Scene Memory for Embodied Exploration and Reasoning, 2025. CVPR 2025, arXiv:2411.17735.

[41] Abrar Anwar, John Welsh, Joydeep Biswas, Soha Pouya, and Yan Chang. ReMEmbR: Building and Reasoning Over Long-Horizon Spatio-Temporal Memory for Robot Navigation, 2025. ICRA 2025, arXiv:2409.13682.

[42] Muhammad Fadhil Ginting, Dong-Ki Kim, Xiangyun Meng, Andrzej Reinke, Bandi Jai Krishna, Navid Kayhani, Oriana Peltzer, David D. Fan, Amirreza Shaban, Sung-Kyun Kim, Mykel J. Kochenderfer, Ali akbar Agha-mohammadi, and Shayegan Omidshafiei. Enter the Mind Palace: Reasoning and Planning for Long-term Active Embodied Question Answering, 2025. arXiv preprint arXiv:2507.12846. 3

[43] Mingjie Zhang, Yuheng Du, Chengkai Wu, Jinni Zhou, Zhenchao Qi, Jun Ma, and Boyu Zhou. ApexNav: An Adaptive Exploration Strategy for Zero-Shot Object Navigation with Target-centric Semantic Fusion, 2025. IEEE RA-L 2025, arXiv:2504.14478. 3

[44] Guanlin Liu, Shaobin Ling, Renyuan Liu, Zeying Gong, and Junjie Hu. AECNav: Active Evidence Consolidation for Efficient Zero-Shot Open-Vocabulary Object Navigation, 2026. arXiv preprint arXiv:2608.10817. 3

[45] Jianwei Yang, Hao Zhang, Feng Li, Xueyan Zou, Chunyuan Li, and Jianfeng Gao. Set-of-Mark Prompting Unleashes Extraordinary Visual Grounding in GPT-4V, 2023. arXiv preprint arXiv:2310.11441. 3

[46] Soroush Nasiriany, Fei Xia, Wenhao Yu, Ted Xiao, Jacky Liang, Ishita Dasgupta, Annie Xie, Danny Driess, Ayzaan Wahid, Zhuo Xu, Quan Vuong, Tingnan Zhang, Tsang-Wei Edward Lee, Kuang-Huei Lee, Peng Xu, Sean Kirmani, Yuke Zhu, Andy Zeng, Karol Hausman, Nicolas Heess, Chelsea Finn, Sergey Levine, and Brian Ichter. PIVOT: Iterative Visual Prompting Elicits Actionable Knowledge for VLMs, 2024. arXiv preprint arXiv:2402.07872.

[47] Dylan Goetting, Himanshu Gaurav Singh, and Antonio Loquercio. End-to-End Navigation with Vision Language Models: Transforming Spatial Reasoning into Question-Answering, 2024. arXiv preprint arXiv:2411.05755.

[48] Jacky Kwok, Christopher Agia, Rohan Sinha, Matt Foutter, Shulu Li, Ion Stoica, Azalia Mirhoseini, and Marco Pavone. RoboMonkey: Scaling Test-Time Sampling and Verification for Vision-Language-Action Models, 2025. arXiv preprint arXiv:2506.17811.

[49] Jadelynn Dao, Milan Ganai, Yasmina Abukhadra, Ajay Sridhar, Mozhgan Nasr Azadani, Katie Luo, Clark Barrett, Jiajun Wu, Chelsea Finn, and Marco Pavone. DIRECT: When and Where Should You Allocate Test-Time Compute in Embodied Planners?, 2026. arXiv preprint arXiv:2606.12402.

[50] Hyeonbeom Choi, Daechul Ahn, Youhan Lee, Taewook Kang, Seongwon Cho, and Jonghyun Choi. SCALE: Self-uncertainty Conditioned Adaptive Looking and Execution for Vision-Language-Action Models, 2026. ICML 2026, arXiv:2602.04208.

[51] Allen Z. Ren, Anushri Dixit, Alexandra Bodrova, Sumeet Singh, Stephen Tu, Noah Brown, Peng Xu, Leila Takayama, Fei Xia, Jake Varley, Zhenjia Xu, Dorsa Sadigh, Andy Zeng, and Anirudha Majumdar. Robots That Ask For Help: Uncertainty Alignment for Large Language Model Planners, 2023. CoRL 2023, arXiv:2307.01928.

[52] Kaiqu Liang, Zixu Zhang, and Jaime Fernández Fisac. Introspective Planning: Aligning Robots' Uncertainty with Inherent Task Ambiguity, 2024. NeurIPS 2024, arXiv:2402.06529.

[53] Allen Z. Ren, Jaden Clark, Anushri Dixit, Masha Itkina, Anirudha Majumdar, and Dorsa Sadigh. Explore until Confident: Efficient Exploration for Embodied Question Answering, 2024. RSS 2024, arXiv:2403.15941. 3

[54] Joseph B. Kadane and Herbert A. Simon. Optimal Strategies for a Class of Constrained Sequential Problems. *The Annals of Statistics*, 5(2):237–255, 1977. 3, 5

[55] Jianyuan Wang, Minghao Chen, Nikita Karaev, Andrea Vedaldi, Christian Rupprecht, and David Novotny. VGGT: Visual Geometry Grounded Transformer, 2025. CVPR 2025, arXiv:2503.11651. 3

[56] Riku Murai, Eric Dexheimer, and Andrew J. Davison. MASt3R-SLAM: Real-Time Dense SLAM with 3D Reconstruction Priors, 2025. CVPR 2025, arXiv:2412.12392.

[57] Dominic Maggio, Hyungtae Lim, and Luca Carlone. VGGT-SLAM: Dense RGB SLAM Optimized on the SL(4) Manifold, 2025. NeurIPS 2025, arXiv:2505.12549.

[58] Bowen Wen, Matthew Trepte, Joseph Aribido, Jan Kautz, Orazio Gallo, and Stan Birchfield. FoundationStereo: Zero-Shot Stereo Matching, 2025. CVPR 2025, arXiv:2501.09898.

[59] Lihe Yang, Bingyi Kang, Zilong Huang, Zhen Zhao, Xiaogang Xu, Jiashi Feng, and Hengshuang Zhao. Depth Anything V2, 2024. NeurIPS 2024, arXiv:2406.09414. 5

[60] Haotong Lin, Sili Chen, Junhao Liew, Donny Y. Chen, Zhenyu Li, Guang Shi, Jiashi Feng, and Bingyi Kang. Depth Anything 3: Recovering the Visual Space from Any Views, 2025. arXiv preprint arXiv:2511.10647. 3

[61] Roberto Corlito, Fabian Schmidt, Nils Seibert, Markus Enzweiler, Abhinav Valada, and Arne Roennau. Sensor Configuration Matters: A Systematic Evaluation of Multimodal SLAM on Quadruped Robots, 2026. arXiv preprint arXiv:2606.19067. 3

[62] Liuyi Wang, Xinyuan Xia, Hui Zhao, Hanqing Wang, Tai Wang, Yilun Chen, Chengju Liu, Qijun Chen, and Jiangmiao Pang. Rethinking the Embodied Gap in Vision-and-Language Navigation: A Holistic Study of Physical and Visual Disparities, 2025. ICCV 2025, arXiv:2507.13019.

[63] Wenzhe Cai, Jiaqi Peng, Yuqiang Yang, Yujian Zhang, Meng Wei, Hanqing Wang, Yilun Chen, Tai Wang, and Jiangmiao Pang. NavDP: Learning Sim-to-Real Navigation Diffusion Policy with Privileged Information Guidance, 2026. ICRA 2026, arXiv:2505.08712. 3

[64] Shiyu Song and Manmohan Chandraker. Robust Scale Estimation in Real-Time Monocular SFM for Autonomous Driving. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2014. 3, 5

[65] Zeqi Li, Xunyi Zhao, Zerui Li, Sihao Lin, Qi Wu, and ShiJie Li. Structure over Reasoning: Unified Zero-Shot Navigation with a Small Vision-Language Model, 2026. arXiv preprint arXiv:2610.25130. 3

[66] Eric Kolve, Roozbeh Mottaghi, Winson Han, Eli VanderBilt, Luca Weihs, Alvaro Herrasti, Matt Deitke, Kiana Ehsani, Daniel Gordon, Yuke Zhu, Aniruddha Kembhavi, Abhinav Gupta, and Ali Farhadi. AI2-THOR: An Interactive 3D Environment for Visual AI, 2017. arXiv preprint arXiv:1712.05474. 3

[67] Anonymous. MOSAIC: The right modules for each task in embodied agents, 2026. OpenReview, https://openreview.net/forum?id=pF9wISLUYo. 6

[68] Wang Warren Chen, Jiahao Zhang, Zhenjiang Li, Mingxu Wang, Lei Yi, Yuchen Kang, Shuo Sun, Ziping Chen, and Jie Chen. HODAgent: Towards on-demand, responsive humanoids for physical world human interaction, 2026. arXiv preprint arXiv:2608.17584. 6

[69] Jingsong Liang, Shuhao Liao, Shizhe Zhang, Diyuan Hou, Yuxin Cai, Xinjian Deng, Chengyang He, Wenhui Huang, Runjia Tan, Zhidong Wang, Lan Yu, Xuesong Tian, Guillaume Sartoretti, Jie Luo, Yao Mu, Wenjun Wu, Wanhua Li, and Chen Lv. RoboFoundry: System-as-policy evolution for self-learning embodied agents, 2026. arXiv preprint arXiv:2609.32862. 6

[70] Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, et al. Qwen3-VL Technical Report, 2025. arXiv preprint arXiv:2511.21631. 5

[71] Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. Efficient Memory Management for Large Language Model Serving with PagedAttention, 2023. SOSP 2023, arXiv:2309.06180. 5

[72] Vishnu Sashank Dorbala, James F. Mullen, and Dinesh Manocha. Can an embodied agent find your "cat-shaped mug"? LLM-guided exploration for zero-shot object navigation. *IEEE Robotics and Automation Letters*, 9(5):4083–4090, 2024. 8

[73] Kaiwen Zhou, Kaizhi Zheng, Connor Pryor, Yilin Shen, Hongxia Jin, Lise Getoor, and Xin Eric Wang. ESC: Exploration with soft commonsense constraints for zero-shot object navigation. In *International Conference on Machine Learning (ICML)*, 2023. 8

[74] Bangguo Yu, Hamidreza Kasaei, and Ming Cao. L3MVN: Leveraging large language models for visual target navigation. In *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2023. 8

[75] Yuxuan Kuang, Hai Lin, and Meng Jiang. OpenFMNav: Towards open-set zero-shot object navigation via vision-

language foundation models. In *Findings of the Association for Computational Linguistics: NAACL*, 2024. 8

[76] Wenyuan Xie, Shaokai Wu, Yijin Zhou, Yanbiao Ji, Guodong Zhang, Bayram Bayramli, Qiuchang Li, Xunchu Zhou, Yue Ding, and Hongtao Lu. MVP-Nav: Multi-layer Value Map Planner Navigator, 2026. arXiv preprint arXiv:2606.31919. 8

[77] Yu Liu, Chengjie Fang, and Likun Lu. ForesightNav: Adaptive semantic-geometric planning for universal zero-shot goal-oriented navigation. *IEEE Access*, 14, 2026. 8

[78] Matt Deitke, Eli VanderBilt, Alvaro Herrasti, Luca Weihs, Jordi Salvador, Kiana Ehsani, Winson Han, Eric Kolve, Ali Farhadi, Aniruddha Kembhavi, and Roozbeh Mottaghi. ProcTHOR: Large-scale embodied AI using procedural generation. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022. 8