the value of π is 3.1416, and the function to read a table is read.table().

```
rnorm(10)
```

```
##  [1] -0.56048 -0.23018  1.55871  0.07051  0.12929  1.71506
##  [7]  0.46092 -1.26506 -0.68685 -0.44566
```

```
getOption("width")
```

```
## [1] 60
```

```
x = 1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1
```

```
getOption("width")
```

```
## [1] 60
```

```
x = 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 +
    1 + 1 + 1 + 1 + 1 + 1
```

You can also tell knitr not to touch your source code using the chunk option tidy=FALSE, so that you can format the source code in any way you want:

```
1 + 1 +
  1+1+
  1
```

```
## [1] 5
```

```
f = function() {
  paste('I want to break the line',
        'here!')
}
```

Compare the above chunk to the default behavior (tidy=TRUE):

```
1 + 1 + 1 + 1 + 1
```

```
## [1] 5
```

```
f = function() {
    paste("I want to break the line", "here!")
}
```

I only mentioned how to control the width of source code. For the width of output, it is much trickier; see `http://yihui.org/knitr/demo/output/`.