

# Package ‘fdasrvf’

December 21, 2023

**Type** Package

**Title** Elastic Functional Data Analysis

**Version** 2.1.2

**Date** 2023-12-20

**Description** Performs alignment, PCA, and modeling of multidimensional and unidimensional functions using the square-root velocity framework (Srivastava et al., 2011 <[arXiv:1103.3817](#)> and Tucker et al., 2014 <[DOI:10.1016/j.csda.2012.12.001](#)>). This framework allows for elastic analysis of functional data through phase and amplitude separation.

**License** GPL-3

**LazyData** TRUE

**Imports** cli, coda, doParallel, fields, foreach, lpSolve, Matrix, mvtnorm, Rcpp, rlang, tolerance, viridisLite

**Suggests** covr, interp, plot3D, plot3Drgl, rgl, testthat (>= 3.0.0), withr

**Depends** R (>= 4.1.0),

**RoxygenNote** 7.2.3

**Encoding** UTF-8

**Config/testthat/edition** 3

**LinkingTo** Rcpp, RcppArmadillo

**URL** [https://github.com/jdtuck/fdasrvf\\_R](https://github.com/jdtuck/fdasrvf_R)

**BugReports** [https://github.com/jdtuck/fdasrvf\\_R/issues](https://github.com/jdtuck/fdasrvf_R/issues)

**NeedsCompilation** yes

**Author** J. Derek Tucker [aut, cre] (<<https://orcid.org/0000-0001-8844-2169>>), Aymeric Stamm [ctb] (<<https://orcid.org/0000-0002-8725-3654>>)

**Maintainer** J. Derek Tucker <jdtuck@sandia.gov>

**Repository** CRAN

**Date/Publication** 2023-12-21 12:00:04 UTC

**R topics documented:**

align_fPCA . . . . .	3
beta . . . . .	5
bootTB . . . . .	5
boxplot.fdawarp . . . . .	6
calc_shape_dist . . . . .	8
curve_geodesic . . . . .	9
curve_karcher_cov . . . . .	9
curve_karcher_mean . . . . .	10
curve_pair_align . . . . .	12
curve_principal_directions . . . . .	13
curve_srvf_align . . . . .	14
curve_to_q . . . . .	15
elastic.depth . . . . .	15
elastic.distance . . . . .	16
elastic.logistic . . . . .	17
elastic.lpcr.regression . . . . .	19
elastic.mlogistic . . . . .	20
elastic.mlpcr.regression . . . . .	21
elastic.pcr.regression . . . . .	22
elastic.prediction . . . . .	24
elastic.regression . . . . .	25
elastic_amp_change_ff . . . . .	26
elastic_change_fpca . . . . .	27
elastic_ph_change_ff . . . . .	29
fdasrvf . . . . .	30
function_group_warp_bayes . . . . .	31
function_mean_bayes . . . . .	32
f_to_srvf . . . . .	33
gam_to_v . . . . .	34
gauss_model . . . . .	35
gradient . . . . .	36
growth_vel . . . . .	37
horizFPCA . . . . .	37
im . . . . .	38
invertGamma . . . . .	39
inv_exp_map . . . . .	39
jointFPCA . . . . .	40
joint_gauss_model . . . . .	41
kmeans_align . . . . .	42
LongRunCovMatrix . . . . .	44
multiple_align_functions . . . . .	45
optimum.reparam . . . . .	46
outlier.detection . . . . .	48
pair_align_functions . . . . .	49
pair_align_functions_bayes . . . . .	50
pair_align_functions_expomap . . . . .	52

pair_align_image . . . . .	54
pcaTB . . . . .	55
predict.lpcr . . . . .	56
predict.mlpcr . . . . .	57
predict.pcr . . . . .	58
q_to_curve . . . . .	58
reparam_curve . . . . .	59
reparam_image . . . . .	60
resamplecurve . . . . .	61
rgam . . . . .	62
sample_shapes . . . . .	62
simu_data . . . . .	63
simu_warp . . . . .	64
simu_warp_median . . . . .	64
smooth.data . . . . .	65
SqrtMean . . . . .	66
SqrtMeanInverse . . . . .	67
SqrtMedian . . . . .	67
srvf_to_f . . . . .	68
time_warping . . . . .	69
toy_data . . . . .	71
toy_warp . . . . .	72
vertFPCA . . . . .	72
v_to_gam . . . . .	73
warp_f_gamma . . . . .	74
warp_q_gamma . . . . .	75

<b>Index</b>	<b>76</b>
--------------	-----------

---

align_fPCA	<i>Group-wise function alignment and PCA Extractions</i>
------------	--

---

## Description

This function aligns a collection of functions while extracting principal components.

## Usage

```
align_fPCA(
  f,
  time,
  num_comp = 3L,
  showplot = TRUE,
  smooth_data = FALSE,
  sparam = 25L,
  parallel = FALSE,
  cores = NULL,
  max_iter = 51L,
```

```

    lambda = 0
)

```

### Arguments

<code>f</code>	A numeric matrix of shape $M \times N$ specifying a sample of $N$ 1-dimensional curves observed on a grid of size $M$ .
<code>time</code>	A numeric vector of length $M$ specifying the grid on which functions <code>f</code> have been evaluated.
<code>num_comp</code>	An integer value specifying the number of principal components to extract. Defaults to 3L.
<code>showplot</code>	A boolean specifying whether to display plots along the way. Defaults to TRUE.
<code>smooth_data</code>	A boolean specifying whether to smooth data using box filter. Defaults to FALSE.
<code>sparam</code>	An integer value specifying the number of times to apply box filter. Defaults to 25L. This argument is only used if <code>smooth_data == TRUE</code> .
<code>parallel</code>	A boolean specifying whether computations should run in parallel. Defaults to FALSE.
<code>cores</code>	An integer value specifying the number of cores to use for parallel computations. Defaults to NULL in which case it uses all available cores but one. This argument is only used when <code>parallel == TRUE</code> .
<code>max_iter</code>	An integer value specifying the maximum number of iterations. Defaults to 51L.
<code>lambda</code>	A numeric value specifying the elasticity. Defaults to $0.0$ .

### Value

A list with the following components:

- `f0`: A numeric matrix of shape  $M \times N$  storing the original functions;
- `fn`: A numeric matrix of the same shape as `f0` storing the aligned functions;
- `qn`: A numeric matrix of the same shape as `f0` storing the aligned SRSFs;
- `q0`: A numeric matrix of the same shape as `f0` storing the SRSFs of the original functions;
- `mqn`: A numeric vector of length  $M$  storing the mean SRSF;
- `gam`: A numeric matrix of the same shape as `f0` storing the estimated warping functions;
- `vf pca`: A list storing information about the vertical PCA with the following components:
  - `q_pca`: A numeric matrix of shape  $(M + 1) \times 5 \times \text{num\_comp}$  storing the first 3 principal directions in SRSF space; the first dimension is  $M + 1$  because, in SRSF space, the original functions are represented by the SRSF and the initial value of the functions.
  - `f_pca`: A numeric matrix of shape  $M \times 5 \times \text{num\_comp}$  storing the first 3 principal directions in original space;
  - `latent`: A numeric vector of length  $M + 1$  storing the singular values of the SVD decomposition in SRSF space;
  - `coef`: A numeric matrix of shape  $N \times \text{num\_comp}$  storing the scores of the  $N$  original functions on the first `num_comp` principal components;

- U: A numeric matrix of shape  $(M + 1) \times (M + 1)$  storing the eigenvectors associated with the SVD decomposition in SRSF space.
- Dx: A numeric vector of length `max_iter` storing the value of the cost function at each iteration.

## References

Tucker, J. D., Wu, W., Srivastava, A., Generative models for functional data using phase and amplitude separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

## Examples

```
## Not run:
out <- align_fPCA(simu_data$f, simu_data$time)

## End(Not run)
```

---

beta	<i>MPEG7 Curve Dataset</i>
------	----------------------------

---

## Description

Contains the MPEG7 curve data set.

## Usage

beta

## Format

beta:

An array of shape  $2 \times 100 \times 65 \times 20$  storing a sample of 20 curves from  $R$  to  $R^2$  distributed in 65 different classes, evaluated on a grid of size 100.

---

bootTB	<i>Tolerance Bound Calculation using Bootstrap Sampling</i>
--------	---

---

## Description

This function computes tolerance bounds for functional data containing phase and amplitude variation using bootstrap sampling

## Usage

```
bootTB(f, time, a = 0.05, p = 0.99, B = 500, no = 5, Nsamp = 100, parallel = T)
```

**Arguments**

f	matrix of functions
time	vector describing time sampling
a	confidence level of tolerance bound (default = 0.05)
p	coverage level of tolerance bound (default = 0.99)
B	number of bootstrap samples (default = 500)
no	number of principal components (default = 5)
Nsamp	number of functions per bootstrap (default = 100)
parallel	enable parallel processing (default = T)

**Value**

Returns a list containing

amp	amplitude tolerance bounds
ph	phase tolerance bounds

**References**

- J. D. Tucker, J. R. Lewis, C. King, and S. Kurtsek, "A Geometric Approach for Computing Tolerance Bounds for Elastic Functional Data," *Journal of Applied Statistics*, 10.1080/02664763.2019.1645818, 2019.
- Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, *Computational Statistics and Data Analysis* (2012), 10.1016/j.csda.2012.12.001.
- Jung, S. L. a. S. (2016). "Combined Analysis of Amplitude and Phase Variations in Functional Data." arXiv:1603.01775.

**Examples**

```
## Not run:
out1 <- bootTB(simu_data$f, simu_data$time)

## End(Not run)
```

---

boxplot.fdawarp

---

*Functional Boxplot*


---

**Description**

This function computes the required statistics for building up a boxplot of the aligned functional data. Since the process of alignment provides separation of phase and amplitude variability, the computed boxplot can focus either on amplitude variability or phase variability.

**Usage**

```
## S3 method for class 'fdawarp'
boxplot(
  x,
  variability_type = c("amplitude", "phase"),
  alpha = 0.05,
  range = 1,
  what = c("plot", "stats", "plot+stats"),
  ...
)

## S3 method for class 'ampbox'
boxplot(x, ...)

## S3 method for class 'phbox'
boxplot(x, ...)
```

**Arguments**

<code>x</code>	An object of class <code>fdawarp</code> typically produced by <code>time_warping()</code> or of class <code>ampbox</code> or <code>phbox</code> typically produced by <code>boxplot.fdawarp()</code> .
<code>variability_type</code>	A string specifying which kind of variability should be displayed in the boxplot. Choices are "amplitude" or "phase". Defaults to "amplitude".
<code>alpha</code>	A numeric value specifying the quantile value. Defaults to 0.05 which uses the 95% quantile.
<code>range</code>	A positive numeric value specifying how far the plot whiskers extend out from the box. The whiskers extend to the most extreme data point which is no more than <code>range</code> times the interquartile range from the box. Defaults to 1.0.
<code>what</code>	A string specifying what the function should return. Choices are "plot", "stats" or "plot+stats". Defaults to "plot".
<code>...</code>	Unused here.

**Details**

The function `boxplot.fdawarp()` returns optionally an object of class either `ampbox` if `variability_type = "amplitude"` or `phbox` if `variability_type = "phase"`. S3 methods specialized for objects of these classes are provided as well to avoid re-computation of the boxplot statistics.

**Value**

If `what` contains `stats`, a list containing the computed statistics necessary for drawing the boxplot. Otherwise, the function simply draws the boxplot and no object is returned.

**Examples**

```
## Not run:
out <- time_warping(simu_data$f, simu_data$time)
```

```
boxplot(out, what = "stats")

## End(Not run)
```

---

calc_shape_dist	<i>Elastic Shape Distance</i>
-----------------	-------------------------------

---

### Description

Calculate elastic shape distance between two curves beta1 and beta2

### Usage

```
calc_shape_dist(beta1, beta2, mode = "O", scale = F)
```

### Arguments

beta1	array describing curve1 (n,T)
beta2	array describing curve
mode	Open ("O") or Closed ("C") curves
scale	Include scale (default =F)

### Value

Returns a list containing

d	geodesic distance
dx	phase distance

### References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

### Examples

```
out <- calc_shape_dist(beta[, , 1, 1], beta[, , 1, 4])
```



---

curve_geodesic	<i>Form geodesic between two curves</i>
----------------	---

---

**Description**

Form geodesic between two curves using Elastic Method

**Usage**

```
curve_geodesic(beta1, beta2, k = 5)
```

**Arguments**

beta1	array describing curve 1 (n,T)
beta2	array describing curve 2 (n,T)
k	number of curves along geodesic (default 5)

**Value**

a list containing

geod	curves along geodesic (n,T,k)
geod_q	srvf's along geodesic

**References**

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

**Examples**

```
out <- curve_geodesic(beta[, , 1, 1], beta[, , 1, 5])
```

---

curve_karcher_cov	<i>Curve Karcher Covariance</i>
-------------------	---------------------------------

---

**Description**

Calculate Karcher Covariance of a set of curves

**Usage**

```
curve_karcher_cov(v, len = NA)
```

**Arguments**

`v`                      array (n,T,N) for N number of shooting vectors  
`len`                    lengths of curves (default=NA)

**Value**

K covariance matrix

**References**

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

**Examples**

```
out <- curve_karcher_mean(beta[, , 1, 1:2], maxit = 2)
# note: use more shapes, small for speed
K <- curve_karcher_cov(out$v)
```

---

curve_karcher_mean	<i>Karcher Mean of Curves</i>
--------------------	-------------------------------

---

**Description**

Calculates Karcher mean or median of a collection of curves using the elastic square-root velocity (srvf) framework.

**Usage**

```
curve_karcher_mean(
  beta,
  mode = "O",
  rotated = T,
  scale = F,
  lambda = 0,
  maxit = 20,
  ms = "mean"
)
```

**Arguments**

`beta`                      array (n,T,N) for N number of curves  
`mode`                    Open ("O") or Closed ("C") curves  
`rotated`                Optimize over rotation (default = T)  
`scale`                   Include scale (default = F)

lambda	A numeric value specifying the elasticity. Defaults to 0.0.
maxit	maximum number of iterations
ms	string defining whether the Karcher mean ("mean") or Karcher median ("median") is returned (default = "mean")

## Value

Returns a list containing

mu	mean srvf
beta	centered data
betamean	mean or median curve
type	string indicating whether mean or median is returned
v	shooting vectors
q	array of srvfs
gam	array of warping functions
cent	centers of original curves
len	length of curves
len_q	length of srvfs
mean_scale	mean length
mean_scale_q	mean length srvf
E	energy
qun	cost function

## References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

## Examples

```
out <- curve_karcher_mean(beta[, , 1, 1:2], maxit = 2)
# note: use more shapes, small for speed
```

---

curve_pair_align	<i>Pairwise align two curves</i>
------------------	----------------------------------

---

**Description**

This function aligns to curves using Elastic Framework

**Usage**

```
curve_pair_align(beta1, beta2, mode = "O")
```

**Arguments**

beta1	array describing curve 1 (n,T)
beta2	array describing curve 2 (n,T)
mode	Open ("O") or Closed ("C") curves

**Value**

a list containing

beta2n	aligned curve 2 to 1
q2n	aligned srvf 2 to 1
gam	warping function
q1	srvf of curve 1
beta1	centered curve 1
beta2	centered curve 2

**References**

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

**Examples**

```
out <- curve_pair_align(beta[, , 1, 1], beta[, , 1, 5])
```

---

curve\_principal\_directions  
*Curve PCA*

---

### Description

Calculate principal directions of a set of curves

### Usage

```
curve_principal_directions(v, K, mu, len = NA, no = 3, N = 5, mode = "O")
```

### Arguments

v	array (n,T,N1) of shooting vectors
K	array (nT,nT) covariance matrix
mu	array (n,T) of mean srvf
len	length of original curves (default NA)
no	number of components
N	number of samples on each side of mean
mode	Open ("O") or Closed ("C") curves

### Value

Returns a list containing

s	singular values
U	singular vectors
coef	principal coefficients
pd	principal directions

### References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

### Examples

```
out <- curve_karcher_mean(beta[, , 1, 1:2], maxit = 2)
# note: use more shapes, small for speed
K <- curve_karcher_cov(out$v)
out <- curve_principal_directions(out$v, K, out$mu)
```

---

curve_srvf_align	<i>Align Curves</i>
------------------	---------------------

---

## Description

Aligns a collection of curves using the elastic square-root velocity (srvf) framework.

## Usage

```
curve_srvf_align(
    beta,
    mode = "O",
    rotated = T,
    scale = F,
    lambda = 0,
    maxit = 20,
    ms = "mean"
)
```

## Arguments

beta	array (n,T,N) for N number of curves
mode	Open ("O") or Closed ("C") curves
rotated	Optimize over rotation (default = T)
scale	Include scale (default = F)
lambda	A numeric value specifying the elasticity. Defaults to 0.0.
maxit	maximum number of iterations
ms	string defining whether the Karcher mean ("mean") or Karcher median ("median") is returned (default = "mean")

## Value

Returns a list containing

betan	aligned curves
qn	aligned srvfs
betamean	mean curve
q_mu	mean SRVFs

## References

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

**Examples**

```
data("mpeg7")
# note: use more shapes and iterations, small for speed
out = curve_srvf_align(beta[, , 1:2], maxit=2)
```

---

curve_to_q	<i>Convert to SRVF space</i>
------------	------------------------------

---

**Description**

This function converts curves to SRVF

**Usage**

```
curve_to_q(beta)
```

**Arguments**

beta                      array describing curve (n,T)

**Value**

q array describing srvf

**References**

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

**Examples**

```
q <- curve_to_q(beta[, , 1, 1])$q
```

---

elastic.depth	<i>Calculates elastic depth</i>
---------------	---------------------------------

---

**Description**

This functions calculates the elastic depth between set of functions

**Usage**

```
elastic.depth(f, time, lambda = 0, pen = "roughness", parallel = FALSE)
```

**Arguments**

f	matrix of N function of M time points (MxN)
time	sample points of functions
lambda	controls amount of warping (default = 0)
pen	alignment penalty (default="roughness") options are second derivative ("roughness"), geodesic distance from id ("geodesic"), and norm from id ("norm")
parallel	run computation in parallel (default = T)

**Value**

Returns a list containing

amp	amplitude depth
phase	phase depth

**References**

T. Harris, J. D. Tucker, B. Li, and L. Shand, "Elastic depths for detecting shape anomalies in functional data," *Technometrics*, 10.1080/00401706.2020.1811156, 2020.

**Examples**

```
depths <- elastic.depth(simu_data$f[, 1:4], simu_data$time)
```

---

elastic.distance	<i>Calculates two elastic distance</i>
------------------	--

---

**Description**

This functions calculates the distances between functions,  $D_y$  and  $D_x$ , where function 1 is aligned to function 2

**Usage**

```
elastic.distance(f1, f2, time, lambda = 0, pen = "roughness")
```

**Arguments**

f1	sample function 1
f2	sample function 2
time	sample points of functions
lambda	controls amount of warping (default = 0)
pen	alignment penalty (default="roughness") options are second derivative ("roughness"), geodesic distance from id ("geodesic"), and norm from id ("norm")



**Value**

Returns a list containing

Dy	amplitude distance
Dx	phase distance

**References**

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

**Examples**

```
distances <- elastic.distance(  
  f1 = simu_data$f[, 1],  
  f2 = simu_data$f[, 2],  
  time = simu_data$time  
)
```

---

elastic.logistic	<i>Elastic Logistic Regression</i>
------------------	------------------------------------

---

**Description**

This function identifies a logistic regression model with phase-variability using elastic methods

**Usage**

```
elastic.logistic(  
  f,  
  y,  
  time,  
  B = NULL,  
  df = 20,  
  max_itr = 20,  
  smooth_data = FALSE,  
  sparam = 25,  
  parallel = FALSE,  
  cores = 2  
)
```

**Arguments**

<code>f</code>	matrix ( $N \times M$ ) of $M$ functions with $N$ samples
<code>y</code>	vector of size $M$ labels (1/-1)
<code>time</code>	vector of size $N$ describing the sample points
<code>B</code>	matrix defining basis functions (default = NULL)
<code>df</code>	scalar controlling degrees of freedom if <code>B=NULL</code> (default=20)
<code>max_itr</code>	scalar number of iterations (default=20)
<code>smooth_data</code>	smooth data using box filter (default = F)
<code>sparam</code>	number of times to apply box filter (default = 25)
<code>parallel</code>	enable parallel mode using <code>foreach()</code> and <code>doParallel</code> package
<code>cores</code>	set number of cores to use with <code>doParallel</code> (default = 2)

**Value**

Returns a list containing

<code>alpha</code>	model intercept
<code>beta</code>	regressor function
<code>fn</code>	aligned functions - matrix ( $N \times M$ ) of $M$ functions with $N$ samples
<code>qn</code>	aligned srvfs - similar structure to <code>fn</code>
<code>gamma</code>	warping functions - similar structure to <code>fn</code>
<code>q</code>	original srvf - similar structure to <code>fn</code>
<code>B</code>	basis matrix
<code>b</code>	basis coefficients
<code>Loss</code>	logistic loss
<code>type</code>	model type ('logistic')

**References**

Tucker, J. D., Wu, W., Srivastava, A., Elastic Functional Logistic Regression with Application to Physiological Signal Classification, Electronic Journal of Statistics (2014), submitted.

---

elastic.lpcr.regression

*Elastic logistic Principal Component Regression*


---

## Description

This function identifies a logistic regression model with phase-variability using elastic pca

## Usage

```
elastic.lpcr.regression(
  f,
  y,
  time,
  pca.method = "combined",
  no = 5,
  smooth_data = FALSE,
  sparam = 25
)
```

## Arguments

f	matrix ( $N \times M$ ) of $M$ functions with $N$ samples
y	vector of size $M$ labels
time	vector of size $N$ describing the sample points
pca.method	string specifying pca method (options = "combined", "vert", or "horiz", default = "combined")
no	scalar specify number of principal components (default=5)
smooth_data	smooth data using box filter (default = F)
sparam	number of times to apply box filter (default = 25)

## Value

Returns a lpcr object containing

alpha	model intercept
b	regressor vector
y	label vector
warp_data	fdawarp object of aligned data
pca	pca object of principal components
Loss	logistic loss
pca.method	string specifying pca method used

## References

J. D. Tucker, J. R. Lewis, and A. Srivastava, “Elastic Functional Principal Component Regression,” Statistical Analysis and Data Mining, 10.1002/sam.11399, 2018.

---

elastic.mlogistic	<i>Elastic Multinomial Logistic Regression</i>
-------------------	--

---

## Description

This function identifies a multinomial logistic regression model with phase-variability using elastic methods

## Usage

```
elastic.mlogistic(
  f,
  y,
  time,
  B = NULL,
  df = 20,
  max_itr = 20,
  smooth_data = FALSE,
  sparam = 25,
  parallel = FALSE,
  cores = 2
)
```

## Arguments

f	matrix ( $N \times M$ ) of $M$ functions with $N$ samples
y	vector of size $M$ labels (1,2,...,m) for m classes
time	vector of size $N$ describing the sample points
B	matrix defining basis functions (default = NULL)
df	scalar controlling degrees of freedom if B=NULL (default=20)
max_itr	scalar number of iterations (default=20)
smooth_data	smooth data using box filter (default = F)
sparam	number of times to apply box filter (default = 25)
parallel	enable parallel mode using <a href="#">foreach()</a> and doParallel package
cores	set number of cores to use with doParallel (default = 2)

**Value**

Returns a list containing

alpha	model intercept
beta	regressor function
fn	aligned functions - matrix ( $N \times M$ ) of $M$ functions with $N$ samples
qn	aligned srvfs - similar structure to fn
gamma	warping functions - similar structure to fn
q	original srvf - similar structure to fn
B	basis matrix
b	basis coefficients
Loss	logistic loss
type	model type ('mlogistic')

**References**

Tucker, J. D., Wu, W., Srivastava, A., Elastic Functional Logistic Regression with Application to Physiological Signal Classification, Electronic Journal of Statistics (2014), submitted.

---

elastic.mlpcr.regression

*Elastic Multinomial logistic Principal Component Regression*

---

**Description**

This function identifies a multinomial logistic regression model with phase-variability using elastic pca

**Usage**

```
elastic.mlpcr.regression(  
  f,  
  y,  
  time,  
  pca.method = "combined",  
  no = 5,  
  smooth_data = FALSE,  
  sparam = 25  
)
```

**Arguments**

<code>f</code>	matrix ( $N \times M$ ) of $M$ functions with $N$ samples
<code>y</code>	vector of size $M$ labels
<code>time</code>	vector of size $N$ describing the sample points
<code>pca.method</code>	string specifying pca method (options = "combined", "vert", or "horiz", default = "combined")
<code>no</code>	scalar specify number of principal components (default=5)
<code>smooth_data</code>	smooth data using box filter (default = F)
<code>sparam</code>	number of times to apply box filter (default = 25)

**Value**

Returns a `mlpcr` object containing

<code>alpha</code>	model intercept
<code>b</code>	regressor vector
<code>y</code>	label vector
<code>Y</code>	Coded labels
<code>warp_data</code>	fdawarp object of aligned data
<code>pca</code>	pca object of principal components
<code>Loss</code>	logistic loss
<code>pca.method</code>	string specifying pca method used

**References**

J. D. Tucker, J. R. Lewis, and A. Srivastava, "Elastic Functional Principal Component Regression," Statistical Analysis and Data Mining, 10.1002/sam.11399, 2018.

---

elastic.pcr.regression

*Elastic Linear Principal Component Regression*

---

**Description**

This function identifies a regression model with phase-variability using elastic pca

**Usage**

```
elastic.pcr.regression(
  f,
  y,
  time,
  pca.method = "combined",
  no = 5,
  smooth_data = FALSE,
  sparam = 25,
  parallel = F,
  C = NULL
)
```

**Arguments**

<code>f</code>	matrix ( $N \times M$ ) of $M$ functions with $N$ samples
<code>y</code>	vector of size $M$ responses
<code>time</code>	vector of size $N$ describing the sample points
<code>pca.method</code>	string specifying pca method (options = "combined", "vert", or "horiz", default = "combined")
<code>no</code>	scalar specify number of principal components (default = 5)
<code>smooth_data</code>	smooth data using box filter (default = F)
<code>sparam</code>	number of times to apply box filter (default = 25)
<code>parallel</code>	run in parallel (default = F)
<code>C</code>	scale balance parameter for combined method (default = NULL)

**Value**

Returns a pcr object containing

<code>alpha</code>	model intercept
<code>b</code>	regressor vector
<code>y</code>	response vector
<code>warp_data</code>	fdawarp object of aligned data
<code>pca</code>	pca object of principal components
<code>SSE</code>	sum of squared errors
<code>pca.method</code>	string specifying pca method used

**References**

J. D. Tucker, J. R. Lewis, and A. Srivastava, "Elastic Functional Principal Component Regression," Statistical Analysis and Data Mining, 10.1002/sam.11399, 2018.

---

elastic.prediction	<i>Elastic Prediction from Regression Models</i>
--------------------	--

---

## Description

This function performs prediction from an elastic regression model with phase-variability

## Usage

```
elastic.prediction(f, time, model, y = NULL, smooth_data = FALSE, sparam = 25)
```

## Arguments

f	matrix ( $N \times M$ ) of $M$ functions with $N$ samples
time	vector of size $N$ describing the sample points
model	list describing model from elastic regression methods
y	responses of test matrix f (default=NULL)
smooth_data	smooth data using box filter (default = F)
sparam	number of times to apply box filter (default = 25)

## Value

Returns a list containing

y_pred	predicted values of f or probabilities depending on model
SSE	sum of squared errors if linear
y_labels	labels if logistic model
PC	probability of classification if logistic

## References

Tucker, J. D., Wu, W., Srivastava, A., Elastic Functional Logistic Regression with Application to Physiological Signal Classification, Electronic Journal of Statistics (2014), submitted.



---

elastic.regression	<i>Elastic Linear Regression</i>
--------------------	----------------------------------

---

**Description**

This function identifies a regression model with phase-variability using elastic methods

**Usage**

```
elastic.regression(
  f,
  y,
  time,
  B = NULL,
  lam = 0,
  df = 20,
  max_itr = 20,
  smooth_data = FALSE,
  sparam = 25,
  parallel = FALSE,
  cores = 2
)
```

**Arguments**

f	matrix ( $N \times M$ ) of $M$ functions with $N$ samples
y	vector of size $M$ responses
time	vector of size $N$ describing the sample points
B	matrix defining basis functions (default = NULL)
lam	scalar regularization parameter (default=0)
df	scalar controlling degrees of freedom if B=NULL (default=20)
max_itr	scalar number of iterations (default=20)
smooth_data	smooth data using box filter (default = F)
sparam	number of times to apply box filter (default = 25)
parallel	enable parallel mode using <a href="#">foreach()</a> and doParallel package
cores	set number of cores to use with doParallel (default = 2)

**Value**

Returns a list containing

alpha	model intercept
beta	regressor function
fn	aligned functions - matrix ( $N \times M$ ) of $M$ functions with $N$ samples

qn	aligned srvfs - similar structure to fn
gamma	warping functions - similar structure to fn
q	original srvf - similar structure to fn
B	basis matrix
b	basis coefficients
SSE	sum of squared errors
type	model type ('linear')

## References

Tucker, J. D., Wu, W., Srivastava, A., Elastic Functional Logistic Regression with Application to Physiological Signal Classification, Electronic Journal of Statistics (2014), submitted.

---

elastic\_amp\_change\_ff *Elastic Amplitude Changepoint Detection*

---

## Description

This function identifies a amplitude changepoint using a fully functional approach

## Usage

```
elastic_amp_change_ff(
  f,
  time,
  d = 1000,
  h = 0,
  smooth_data = FALSE,
  sparam = 25,
  showplot = TRUE
)
```

## Arguments

f	matrix ( $N \times M$ ) of $M$ functions with $N$ samples
time	vector of size $N$ describing the sample points
d	number of monte carlo iterations of Brownian Bridge (default = 1000)
h	window selection of long range covariance function (default = 0)
smooth_data	smooth data using box filter (default = F)
sparam	number of times to apply box filter (default = 25)
showplot	show results plots (default = T)

**Value**

Returns a list object containing

pvalue	p value
change	indice of changepoint
DataBefore	functions before changepoint
DataAfter	functions after changepoint
MeanBefore	mean function before changepoint
MeanAfter	mean function after changepoint
WarpingBefore	warping functions before changepoint
WarpingAfter	warping functions after changepoint
WarpingMeanBefore	mean warping function before changepoint
WarpingMeanAfter	mean warping function after changepoint
change_fun	amplitude change function
Sn	test statistic values
mu	mean srsfs
mu_f	mean functions

**References**

J. D. Tucker and D. Yarger, “Elastic Functional Changepoint Detection of Climate Impacts from Localized Sources”, *Envirometrics*, 10.1002/env.2826, 2023.

---

elastic\_change\_fpca     *Elastic Changepoint Detection*

---

**Description**

This function identifies changepoints using a functional PCA

**Usage**

```
elastic_change_fpca(
  f,
  time,
  pca.method = "combined",
  pc = 0.95,
  d = 1000,
  n_pcs = 5,
  smooth_data = FALSE,
  sparam = 25,
  showplot = TRUE
)
```

**Arguments**

<code>f</code>	matrix ( $N \times M$ ) of $M$ functions with $N$ samples
<code>time</code>	vector of size $N$ describing the sample points
<code>pca.method</code>	string specifying pca method (options = "combined", "vert", or "horiz", default = "combined")
<code>pc</code>	percentage of cummulation explained variance (default = 0.95)
<code>d</code>	number of monte carlo iterations of Brownian Bridge (default = 1000)
<code>n_pcs</code>	scalar specify number of principal components (default = 5)
<code>smooth_data</code>	smooth data using box filter (default = F)
<code>sparam</code>	number of times to apply box filter (default = 25)
<code>showplot</code>	show results plots (default = T)

**Value**

Returns a list object containing

<code>pvalue</code>	p value
<code>change</code>	indice of changepoint
<code>DataBefore</code>	functions before changepoint
<code>DataAfter</code>	functions after changepoint
<code>MeanBefore</code>	mean function before changepoint
<code>MeanAfter</code>	mean function after changepoint
<code>WarpingBefore</code>	warping functions before changepoint
<code>WarpingAfter</code>	warping functions after changepoint
<code>WarpingMeanBefore</code>	mean warping function before changepoint
<code>WarpingMeanAfter</code>	mean warping function after changepoint
<code>change_fun</code>	amplitude change function
<code>Sn</code>	test statistic values

**References**

J. D. Tucker and D. Yarger, “Elastic Functional Changepoint Detection of Climate Impacts from Localized Sources”, *Envirometrics*, 10.1002/env.2826, 2023.

---

elastic\_ph\_change\_ff    *Elastic Phase Changepoint Detection*


---

## Description

This function identifies a phase changepoint using a fully functional approach

## Usage

```
elastic_ph_change_ff(
  f,
  time,
  d = 1000,
  h = 0,
  smooth_data = FALSE,
  sparam = 25,
  showplot = TRUE
)
```

## Arguments

f	matrix ( $N \times M$ ) of $M$ functions with $N$ samples
time	vector of size $N$ describing the sample points
d	number of monte carlo iterations of Brownian Bridge (default = 1000)
h	window selection of long range covariance function (default = 0)
smooth_data	smooth data using box filter (default = F)
sparam	number of times to apply box filter (default = 25)
showplot	show results plots (default = T)

## Value

Returns a list object containing

pvalue	p value
change	indice of changepoint
DataBefore	functions before changepoint
DataAfter	functions after changepoint
MeanBefore	mean function before changepoint
MeanAfter	mean function after changepoint
WarpingBefore	warping functions before changepoint
WarpingAfter	warping functions after changepoint
WarpingMeanBefore	mean warping function before changepoint

WarpingMeanAfter	mean warping function after changepoint
change_fun	amplitude change function
Sn	test statistic values
mu	mean shooting vectors

## References

J. D. Tucker and D. Yarger, "Elastic Functional Changepoint Detection of Climate Impacts from Localized Sources", *Envirometrics*, 10.1002/env.2826, 2023.

---

fdasrvf

*Elastic Functional Data Analysis*

---

## Description

A library for functional data analysis using the square root velocity framework which performs pair-wise and group-wise alignment as well as modeling using functional component analysis.

## References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using Fisher-Rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative models for functional data using phase and amplitude separation, *Computational Statistics and Data Analysis* (2012), 10.1016/j.csda.2012.12.001.

J. D. Tucker, W. Wu, and A. Srivastava, Phase-amplitude separation of proteomics data using extended Fisher-Rao metric, *Electronic Journal of Statistics*, Vol 8, no. 2. pp 1724-1733, 2014.

J. D. Tucker, W. Wu, and A. Srivastava, "Analysis of signals under compositional noise with applications to SONAR data," *IEEE Journal of Oceanic Engineering*, Vol 29, no. 2. pp 318-330, Apr 2014.

Tucker, J. D. 2014, Functional Component Analysis and Regression using Elastic Methods. Ph.D. Thesis, Florida State University.

Robinson, D. T. 2012, Function Data Analysis and Partial Shape Matching in the Square Root Velocity Framework. Ph.D. Thesis, Florida State University.

Huang, W. 2014, Optimization Algorithms on Riemannian Manifolds with Applications. Ph.D. Thesis, Florida State University.

Cheng, W., Dryden, I. L., and Huang, X. (2016). Bayesian registration of functions and curves. *Bayesian Analysis*, 11(2), 447-475.

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. *Pattern Analysis and Machine Intelligence*, IEEE Transactions on 33 (7), 1415-1428.

Cheng, W., Dryden, I. L., and Huang, X. (2016). Bayesian registration of functions and curves. *Bayesian Analysis*, 11(2), 447-475.

- W. Xie, S. Kurtek, K. Bharath, and Y. Sun, A geometric approach to visualization of variability in functional data, *Journal of American Statistical Association* 112 (2017), pp. 979-993.
- Lu, Y., R. Herbei, and S. Kurtek, 2017: Bayesian registration of functions with a Gaussian process prior. *Journal of Computational and Graphical Statistics*, 26, no. 4, 894–904.
- Lee, S. and S. Jung, 2017: Combined analysis of amplitude and phase variations in functional data. *arXiv:1603.01775*, 1–21.
- J. D. Tucker, J. R. Lewis, and A. Srivastava, “Elastic Functional Principal Component Regression,” *Statistical Analysis and Data Mining*, vol. 12, no. 2, pp. 101-115, 2019.
- J. D. Tucker, J. R. Lewis, C. King, and S. Kurtek, “A Geometric Approach for Computing Tolerance Bounds for Elastic Functional Data,” *Journal of Applied Statistics*, 10.1080/02664763.2019.1645818, 2019.
- T. Harris, J. D. Tucker, B. Li, and L. Shand, "Elastic depths for detecting shape anomalies in functional data," *Technometrics*, 10.1080/00401706.2020.1811156, 2020.
- J. D. Tucker and D. Yarger, “Elastic Functional Changepoint Detection of Climate Impacts from Localized Sources”, *Envirometrics*, 10.1002/env.2826, 2023.

---

function\_group\_warp\_bayes

*Bayesian Group Warping*


---

## Description

This function aligns a set of functions using Bayesian SRSF framework

## Usage

```
function_group_warp_bayes(
  f,
  time,
  iter = 50000,
  powera = 1,
  times = 5,
  tau = ceiling(times * 0.04),
  gp = seq(dim(f)[2]),
  showplot = TRUE
)
```

## Arguments

f	matrix ( $N \times M$ ) of $M$ functions with $N$ samples
time	sample points of functions
iter	number of iterations (default = 150000)
powera	Dirichlet prior parameter (default 1)
times	factor of length of subsample points to look at (default = 5)

tau	standard deviation of Normal prior for increment (default $\text{ceil}(\text{times} \times .4)$ )
gp	number of colors in plots (defaults $\text{seq}(\text{dim}(f)[2])$ )
showplot	shows plots of functions (default = T)

**Value**

Returns a list containing

f0	original functions
f_q	f aligned quotient space
gam_q	warping functions quotient space
f_a	f aligned ambient space
gam_a	warping ambient space
qmn	mean srsf

**References**

Cheng, W., Dryden, I. L., and Huang, X. (2016). Bayesian registration of functions and curves. *Bayesian Analysis*, 11(2), 447-475.

**Examples**

```
## Not run:
  out <- function_group_warp_bayes(simu_data$f, simu_data$time)

## End(Not run)
```

---

function_mean_bayes	<i>Bayesian Karcher Mean Calculation</i>
---------------------	--

---

**Description**

This function calculates karcher mean of functions using Bayesian method

**Usage**

```
function_mean_bayes(f, time, times = 5, group = 1:dim(f)[2], showplot = TRUE)
```

**Arguments**

f	matrix ( $N \times M$ ) of $M$ functions with $N$ samples
time	sample points of functions
times	factor of length of subsample points to look at (default = 5)
group	(defaults $1:\text{dim}(f)[2]$ )
showplot	shows plots of functions (default = T)



**Value**

Returns a list containing

distfamily	dist matrix
match.matrix	matrix of warping functions
position	position
mu_5	function mean
rtmatrix	rtmatrix
sumdist	sumdist
qt.fitted	aligned srsf functions
estimator	estimator
estimator2	estimator2
regfuncs	registered functions

**References**

Cheng, W., Dryden, I. L., and Huang, X. (2016). Bayesian registration of functions and curves. *Bayesian Analysis*, 11(2), 447-475.

**Examples**

```
## Not run:
out <- function_mean_bayes(simu_data$f, simu_data$time)

## End(Not run)
```

---

f_to_srvf	<i>Transformation to SRSF Space</i>
-----------	-------------------------------------

---

**Description**

This function transforms curves from their original functional space to the SRVF space.

**Usage**

```
f_to_srvf(f, time, multidimensional = FALSE)
```

**Arguments**

- f** Either a numeric vector of a numeric matrix or a numeric array specifying the functions that need to be transformed.
- If a vector, it must be of shape  $M$  and it is interpreted as a single 1-dimensional curve observed on a grid of size  $M$ .

- If a matrix and `multidimensional == FALSE`, it must be of shape  $M \times N$ . In this case, it is interpreted as a sample of  $N$  curves observed on a grid of size  $M$ , unless  $M = 1$  in which case it is interpreted as a single 1-dimensional curve observed on a grid of size  $M$ .
  - If a matrix and `multidimensional == TRUE`, it must be of shape  $L \times M$  and it is interpreted as a single  $L$ -dimensional curve observed on a grid of size  $M$ .
  - If a 3D array, it must be of shape  $L \times M \times N$  and it is interpreted as a sample of  $N$   $L$ -dimensional curves observed on a grid of size  $M$ .
- `time` A numeric vector of length  $M$  specifying the grid on which the curves are evaluated.
- `multidimensional` A boolean specifying if the curves are multi-dimensional. This is useful when `f` is provided as a matrix to determine whether it is a single multi-dimensional curve or a collection of uni-dimensional curves. Defaults to `FALSE`.

### Value

A numeric array of the same shape as the input array `f` storing the SRSFs of the original curves.

### References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using Fisher-Rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative models for functional data using phase and amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

### Examples

```
q <- f_to_srvf(simu_data$f, simu_data$time)
```

---

gam\_to\_v

*map warping function to tangent space at identity*

---

### Description

map warping function to tangent space at identity

### Usage

```
gam_to_v(gam, smooth = TRUE)
```

### Arguments

`gam` Either a numeric vector of a numeric matrix or a numeric array specifying the warping functions

`smooth` Apply smoothing before gradient

**Value**

A numeric array of the same shape as the input array `gamma` storing the shooting vectors of `gamma` obtained via finite differences.

---

`gauss_model`*Gaussian model of functional data*

---

**Description**

This function models the functional data using a Gaussian model extracted from the principal components of the `srvfs`

**Usage**

```
gauss_model(warp_data, n = 1, sort_samples = FALSE)
```

**Arguments**

<code>warp_data</code>	fdawarp object from <a href="#">time_warping</a> of aligned data
<code>n</code>	number of random samples ( $n = 1$ )
<code>sort_samples</code>	sort samples (default = F)

**Value**

Returns a fdawarp object containing

<code>fs</code>	random aligned samples
<code>gams</code>	random warping function samples
<code>ft</code>	random function samples

**References**

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

**Examples**

```
out1 <- gauss_model(simu_warp, n = 10)
```

gradient

*Gradient using finite differences***Description**

This function computes the gradient of  $f$  using finite differences.

**Usage**

```
gradient(f, binsize, multidimensional = FALSE)
```

**Arguments**

- |                  |   |
|------------------|---|
| $f$              | <p>Either a numeric vector of a numeric matrix or a numeric array specifying the curve(s) that need to be differentiated.</p> <ul style="list-style-type: none"> <li>• If a vector, it must be of shape <math>M</math> and it is interpreted as a single 1-dimensional curve observed on a grid of size <math>M</math>.</li> <li>• If a matrix and <code>multidimensional == FALSE</code>, it must be of shape <math>M \times N</math>. In this case, it is interpreted as a sample of <math>N</math> curves observed on a grid of size <math>M</math>, unless <math>M = 1</math> in which case it is interpreted as a single 1-dimensional curve observed on a grid of size <math>M</math>.</li> <li>• If a matrix and <code>multidimensional == TRUE</code>, it must be of shape <math>L \times M</math> and it is interpreted as a single <math>L</math>-dimensional curve observed on a grid of size <math>M</math>.</li> <li>• If a 3D array, it must be of shape <math>L \times M \times N</math> and it is interpreted as a sample of <math>N</math> <math>L</math>-dimensional curves observed on a grid of size <math>M</math>.</li> </ul> |
| binsize          | A numeric value specifying the size of the bins for computing finite differences.   |
| multidimensional | A boolean specifying if the curves are multi-dimensional. This is useful when $f$ is provided as a matrix to determine whether it is a single multi-dimensional curve or a collection of uni-dimensional curves. Defaults to FALSE.   |

**Value**

A numeric array of the same shape as the input array  $f$  storing the gradient of  $f$  obtained via finite differences.

**Examples**

```
out <- gradient(simu_data$f[, 1], mean(diff(simu_data$time)))
```

---

growth_vel	<i>Berkeley Growth Velocity Dataset</i>
------------	---

---

**Description**

Combination of both boys and girls growth velocity from the Berkley dataset.

**Usage**

```
growth_vel
```

**Format**

growth\_vel:

A list with two components:

- f: A numeric matrix of shape  $69 \times 93$  storing a sample of size  $N = 93$  of curves evaluated on a grid of size  $M = 69$ .
- time: A numeric vector of size  $M = 69$  storing the grid on which the curves f have been evaluated.

---

horizFPCA	<i>Horizontal Functional Principal Component Analysis</i>
-----------	---

---

**Description**

This function calculates vertical functional principal component analysis on aligned data

**Usage**

```
horizFPCA(warp_data, no, ci = c(-1, 0, 1), showplot = TRUE)
```

**Arguments**

warp_data	fdawarp object from <a href="#">time_warping</a> of aligned data
no	number of principal components to extract
ci	geodesic standard deviations (default = c(-1,0,1))
showplot	show plots of principal directions (default = T)

**Value**

Returns a `hfpca` object containing

<code>gam_pca</code>	warping functions principal directions
<code>psi_pca</code>	srvf principal directions
<code>latent</code>	latent values
<code>U</code>	eigenvectors
<code>vec</code>	shooting vectors
<code>mu</code>	Karcher Mean

**References**

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

**Examples**

```
hfpca <- horizFPCA(simu_warp, no = 3)
```

---

<code>im</code>	<i>Example Image Data set</i>
-----------------	-------------------------------

---

**Description**

Contains two simulated images for registration.

**Usage**

```
im
```

**Format**

`im`:

A list with two components:

- I1: A numeric matrix of shape  $64 \times 64$  storing the 1st image;
- I2: A numeric matrix of shape  $64 \times 64$  storing the 2nd image.

---

invertGamma	<i>Invert Warping Function</i>
-------------	--------------------------------

---

**Description**

This function calculates the inverse of gamma

**Usage**

```
invertGamma(gam)
```

**Arguments**

gam	vector of $N$ samples
-----	-----------------------

**Value**

Returns gamI inverted vector

**References**

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

**Examples**

```
out <- invertGamma(simu_warp$warping_functions[, 1])
```

---

inv_exp_map	<i>map square root of warping function to tangent space</i>
-------------	---

---

**Description**

map square root of warping function to tangent space

**Usage**

```
inv_exp_map(Psi, psi)
```

**Arguments**

Psi	vector describing psi function at center of tangent space
psi	vector describing psi function to map to tangent space

**Value**

A numeric array of the same length as the input array `psi` storing the shooting vector of `psi`

---

jointFPCA	<i>Joint Vertical and Horizontal Functional Principal Component Analysis</i>
-----------	--

---

**Description**

This function calculates amplitude and phase joint functional principal component analysis on aligned data

**Usage**

```
jointFPCA(
  warp_data,
  no,
  id = round(length(warp_data$time)/2),
  C = NULL,
  ci = c(-1, 0, 1),
  showplot = T
)
```

**Arguments**

<code>warp_data</code>	fdawarp object from <a href="#">time_warping</a> of aligned data
<code>no</code>	number of principal components to extract
<code>id</code>	integration point for <code>f0</code> (default = midpoint)
<code>C</code>	balance value (default = NULL)
<code>ci</code>	geodesic standard deviations (default = <code>c(-1,0,1)</code> )
<code>showplot</code>	show plots of principal directions (default = T)

**Value**

Returns a list containing

<code>q_pca</code>	srvf principal directions
<code>f_pca</code>	f principal directions
<code>latent</code>	latent values
<code>coef</code>	coefficients
<code>U</code>	eigenvectors
<code>mu_psi</code>	mean psi function
<code>mu_g</code>	mean g function
<code>id</code>	point use for <code>f(0)</code>
<code>C</code>	optimized phase amplitude ratio



## References

- Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.
- Jung, S. L. a. S. (2016). "Combined Analysis of Amplitude and Phase Variations in Functional Data." arXiv:1603.01775.
- Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

## Examples

```
jfpca <- jointFPCA(simu_warp, no = 3)
```

---

joint_gauss_model	<i>Gaussian model of functional data using joint Model</i>
-------------------	--

---

## Description

This function models the functional data using a Gaussian model extracted from the principal components of the srvfs using the joint model

## Usage

```
joint_gauss_model(warp_data, n = 1, no = 5)
```

## Arguments

warp_data	fdawarp object from <a href="#">time_warping</a> of aligned data
n	number of random samples (n = 1)
no	number of principal components (n=4)

## Value

Returns a fdawarp object containing

fs	random aligned samples
gams	random warping function samples
ft	random function samples
qs	random srvf samples

## References

- Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.
- Jung, S. L. a. S. (2016). "Combined Analysis of Amplitude and Phase Variations in Functional Data." arXiv:1603.01775.

## Examples

```
out1 <- joint_gauss_model(simu_warp, n = 10)
```

---

kmeans\_align

*K-Means Clustering and Alignment*


---

## Description

This function clusters functions and aligns using the elastic square-root slope function (SRSF) framework.

## Usage

```
kmeans_align(
  f,
  time,
  K = 1L,
  seeds = NULL,
  centroid_type = c("mean", "medoid"),
  nonempty = 0L,
  lambda = 0,
  showplot = FALSE,
  smooth_data = FALSE,
  sparam = 25L,
  parallel = FALSE,
  alignment = TRUE,
  omethod = c("DP", "DP2", "RBFGS"),
  max_iter = 50L,
  thresh = 0.01,
  use_verbose = FALSE
)
```

## Arguments

f	Either a numeric matrix or a numeric 3D array specifying the functions that need to be jointly clustered and aligned. <ul style="list-style-type: none"> <li>• If a matrix, it must be of shape <math>M \times N</math>. In this case, it is interpreted as a sample of <math>N</math> curves observed on a grid of size <math>M</math>.</li> <li>• If a 3D array, it must be of shape <math>L \times M \times N</math> and it is interpreted as a sample of <math>N</math> <math>L</math>-dimensional curves observed on a grid of size <math>M</math>.</li> </ul>
time	A numeric vector of length $M$ specifying the grid on which the curves are evaluated.
K	An integer value specifying the number of clusters. Defaults to 1L.
seeds	An integer vector of length K specifying the indices of the curves in f which will be chosen as initial centroids. Defaults to NULL in which case such indices are randomly chosen.

centroid_type	A string specifying the type of centroid to compute. Choices are "mean" or "medoid". Defaults to "mean".
nonempty	An integer value specifying the minimum number of curves per cluster during the assignment step. Set it to a positive value to avoid the problem of empty clusters. Defaults to 0L.
lambda	A numeric value specifying the elasticity. Defaults to 0.0.
showplot	A boolean specifying whether to show plots. Defaults to FALSE.
smooth_data	A boolean specifying whether to smooth data using a box filter. Defaults to FALSE.
sparam	An integer value specifying the number of box filters applied. Defaults to 25L.
parallel	A boolean specifying whether parallel mode (using <code>foreach::foreach()</code> and the <b>doParallel</b> package) should be activated. Defaults to FALSE.
alignment	A boolean specifying whether to perform alignment. Defaults to TRUE.
omethod	A string specifying which method should be used to solve the optimization problem that provides estimated warping functions. Choices are "DP" or "RBFSGS". Defaults to "DP".
max_iter	An integer value specifying the maximum number of iterations. Defaults to 50L.
thresh	A numeric value specifying a threshold on the cost function below which convergence is assumed. Defaults to 0.01.
use_verbose	A boolean specifying whether to display information about the calculations in the console. Defaults to FALSE.

## Value

An object of class `fdakma` which is a list containing:

- `f0`: the original functions;
- `q0`: the original SRSFs;
- `fn`: the aligned functions as matrices or a 3D arrays of the same shape than `f0` by clusters in a list;
- `qn`: the aligned SRSFs as matrices or a 3D arrays of the same shape than `f0` separated in clusters in a list;
- `labels`: the cluster memberships as an integer vector;
- `templates`: the centroids in the original functional space;
- `templates.q`: the centroids in SRSF space;
- `distances_to_center`: A numeric vector storing the distances of each observed curve to its center;
- `gam`: the warping functions as matrices or a 3D arrays of the same shape than `f0` by clusters in a list;
- `qun`: cost function value.

## References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using Fisher-Rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative models for functional data using phase and amplitude separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Sangalli, L. M., et al. (2010). "k-mean alignment for curve clustering." Computational Statistics & Data Analysis 54(5): 1219-1233.

## Examples

```
## Not run:
  out <- kmeans_align(growth_vel$f, growth_vel$time, K = 2)

## End(Not run)
```

---

LongRunCovMatrix

---

*Long Run Covariance Matrix Estimation for Multivariate Time Series*


---

## Description

This function estimates the long run covariance matrix of a given multivariate data sample.

## Usage

```
LongRunCovMatrix(mdobj, h = 0, kern_type = "bartlett")
```

## Arguments

mdobj	A multivariate data object
h	The bandwidth parameter. It is strictly non-zero. Choosing the bandwidth parameter to be zero is identical to estimating covariance matrix assuming iid data.
kern_type	Kernel function to be used for the estimation of the long run covariance matrix. The choices are c("BT", "PR", "SP", "FT") which are respectively, bartlett, parzen, simple and flat-top kernels. By default the function uses a "bartlett" kernel.

## Value

Returns long run covariance matrix

---

multiple\_align\_functions

*Group-wise function alignment to specified mean*


---

## Description

This function aligns a collection of functions using the elastic square-root slope (srsf) framework.

## Usage

```
multiple_align_functions(
  f,
  time,
  mu,
  lambda = 0,
  pen = "roughness",
  showplot = TRUE,
  smooth_data = FALSE,
  sparam = 25,
  parallel = FALSE,
  omethod = "DP",
  MaxItr = 20,
  iter = 2000
)
```

## Arguments

f	matrix ( $N \times M$ ) of $M$ functions with $N$ samples
time	vector of size $N$ describing the sample points
mu	vector of size $N$ that $f$ is aligned to
lambda	controls the elasticity (default = 0)
pen	alignment penalty (default="roughness") options are second derivative ("roughness"), geodesic distance from id ("geodesic"), and norm from id ("norm")
showplot	shows plots of functions (default = T)
smooth_data	smooth data using box filter (default = F)
sparam	number of times to apply box filter (default = 25)
parallel	enable parallel mode using <a href="#">foreach()</a> and doParallel package (default=F)
omethod	optimization method (DP,DP2,RBFGS,dBayes,expBayes)
MaxItr	maximum number of iterations
iter	bayesian number of mcmc samples (default 2000)

**Value**

Returns a fdawarp object containing

f0	original functions
fn	aligned functions - matrix ( $N \times M$ ) of $M$ functions with $N$ samples
qn	aligned SRSFs - similar structure to fn
q0	original SRSF - similar structure to fn
fmean	function mean or median - vector of length $N$
mqn	SRSF mean or median - vector of length $N$
gam	warping functions - similar structure to fn
orig.var	Original Variance of Functions
amp.var	Amplitude Variance
phase.var	Phase Variance
qun	Cost Function Value

**References**

Srivastava, A., Wu, W., Kurtsek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

---

optimum.reparam	<i>Align two functions</i>
-----------------	----------------------------

---

**Description**

This function aligns the SRSFs of two functions defined on an interval  $[t_{\min}, t_{\max}]$  using dynamic programming or RBFGS

**Usage**

```
optimum.reparam(
  Q1,
  T1,
  Q2,
  T2,
  lambda = 0,
  pen = "roughness",
  method = c("DP", "DPo", "SIMUL", "RBFGS"),
  f1o = 0,
  f2o = 0,
  nbhd_dim = 7
)
```

**Arguments**

Q1	A numeric matrix of shape <code>n_points</code> x <code>n_dimensions</code> specifying the SRSF of the 1st <code>n_dimensions</code> -dimensional function evaluated on a grid of size <code>n_points</code> of its univariate domain.
T1	A numeric vector of size <code>n_points</code> specifying the grid on which the 1st SRSF is evaluated.
Q2	A numeric matrix of shape <code>n_points</code> x <code>n_dimensions</code> specifying the SRSF of the 2nd <code>n_dimensions</code> -dimensional function evaluated on a grid of size <code>n_points</code> of its univariate domain.
T2	A numeric vector of size <code>n_points</code> specifying the grid on which the 1st SRSF is evaluated.
lambda	A numeric value specifying the amount of warping. Defaults to <code>0.0</code> .
pen	alignment penalty (default="roughness") options are second derivative ("roughness"), geodesic distance from id ("geodesic"), and norm from id ("l2gam"), srvf norm from id ("l2psi")
method	A string specifying the optimization method. Choices are "DP", "DPo", "SIMUL", or "RBFGRS". Defaults to "DP".
f1o	A numeric vector of size <code>n_dimensions</code> specifying the value of the 1st function at $t = t_{\min}$ . Defaults to <code>rep(0, n_dimensions)</code> .
f2o	A numeric vector of size <code>n_dimensions</code> specifying the value of the 2nd function at $t = t_{\min}$ . Defaults to <code>rep(0, n_dimensions)</code> .
nbhd_dim	size of the grid (default = 7)

**Value**

A numeric vector of size `n_points` storing discrete evaluations of the estimated boundary-preserving warping diffeomorphism on the initial grid.

**References**

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using Fisher-Rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative models for functional data using phase and amplitude separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

**Examples**

```
q <- f_to_srvf(simu_data$f, simu_data$time)
gam <- optimum.reparam(q[, 1], simu_data$time, q[, 2], simu_data$time)
```

---

outlier.detection      *Outlier Detection*


---

## Description

This function calculates outlier's using geodesic distances of the SRVFs from the median

## Usage

```
outlier.detection(q, time, mq, k = 1.5)
```

## Arguments

q	matrix ( $N \times M$ ) of $M$ SRVF functions with $N$ samples
time	vector of size $N$ describing the sample points
mq	median calculated using <code>time_warping()</code>
k	cutoff threshold (default = 1.5)

## Value

q_outlier	outlier functions
-----------	-------------------

## References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

## Examples

```
q_outlier <- outlier.detection(
  q = toy_warp$q0,
  time = toy_data$time,
  mq = toy_warp$mqn,
  k = .1
)
```



---

pair\_align\_functions    *Align two functions*

---

### Description

This function aligns two functions using SRSF framework. It will align f2 to f1

### Usage

```
pair_align_functions(  
  f1,  
  f2,  
  time,  
  lambda = 0,  
  pen = "roughness",  
  method = "DP",  
  w = 0.01,  
  iter = 2000  
)
```

### Arguments

f1	function 1
f2	function 2
time	sample points of functions
lambda	controls amount of warping (default = 0)
pen	alignment penalty (default="roughness") options are second derivative ("roughness"), geodesic distance from id ("geodesic"), and norm from id ("norm")
method	controls which optimization method (default="DP") options are Dynamic Programming ("DP"), Coordinate Descent ("DP2"), Riemannian BFGS ("RBFGS"), Simultaneous Alignment ("SIMUL"), Dirichlet Bayesian ("dBayes"), and Expo-Map Bayesian ("expBayes")
w	controls LRBFGS (default = 0.01)
iter	number of mcmc iterations for mcmc method (default 2000)

### Value

Returns a list containing

f2tilde	aligned f2
gam	warping function

## References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

Cheng, W., Dryden, I. L., and Huang, X. (2016). Bayesian registration of functions and curves. Bayesian Analysis, 11(2), 447-475.

Lu, Y., Herbei, R., and Kurtek, S. (2017). Bayesian registration of functions with a Gaussian process prior. Journal of Computational and Graphical Statistics, DOI: 10.1080/10618600.2017.1336444.

## Examples

```
out <- pair_align_functions(
  f1 = simu_data$f[, 1],
  f2 = simu_data$f[, 2],
  time = simu_data$time
)
```

---

```
pair_align_functions_bayes
      Align two functions
```

---

## Description

This function aligns two functions using Bayesian SRSF framework. It will align f2 to f1

## Usage

```
pair_align_functions_bayes(
  f1,
  f2,
  timet,
  iter = 15000,
  times = 5,
  tau = ceiling(times * 0.4),
  powera = 1,
  showplot = TRUE,
  extrainfo = FALSE
)
```

## Arguments

f1	function 1
f2	function 2
timet	sample points of functions

iter	number of iterations (default = 15000)
times	factor of length of subsample points to look at (default = 5)
tau	standard deviation of Normal prior for increment (default $\text{ceil}(\text{times} \cdot .4)$ )
powera	Dirichlet prior parameter (default 1)
showplot	shows plots of functions (default = T)
extrainfo	T/F whether additional information is returned

### Value

Returns a list containing

f1	function 1
f2_q	registered function using quotient space
gam_q	warping function quotient space
f2_a	registered function using ambient space
q2_a	warping function ambient space
match_collect	posterior samples from warping function (returned if extrainfo=TRUE)
dist_collect	posterior samples from the distances (returned if extrainfo=TRUE)
kappa_collect	posterior samples from kappa (returned if extrainfo=TRUE)
log_collect	log-likelihood of each sample (returned if extrainfo=TRUE)
pct_accept	vector of acceptance ratios for the warping function (returned if extrainfo=TRUE)

### References

Cheng, W., Dryden, I. L., and Huang, X. (2016). Bayesian registration of functions and curves. *Bayesian Analysis*, 11(2), 447-475.

### Examples

```
out <- pair_align_functions_bayes(
  f1 = simu_data$f[, 1],
  f2 = simu_data$f[, 2],
  timet = simu_data$time
)
```

---

pair\_align\_functions\_expomap

*Align two functions using geometric properties of warping functions*


---

## Description

This function aligns two functions using Bayesian framework. It will align f2 to f1. It is based on mapping warping functions to a hypersphere, and a subsequent exponential mapping to a tangent space. In the tangent space, the Z-mixture pCN algorithm is used to explore both local and global structure in the posterior distribution.

## Usage

```
pair_align_functions_expomap(
  f1,
  f2,
  timet,
  iter = 20000,
  burnin = min(5000, iter/2),
  alpha0 = 0.1,
  beta0 = 0.1,
  zpcn = list(betas = c(0.5, 0.05, 0.005, 1e-04), probs = c(0.1, 0.1, 0.7, 0.1)),
  propvar = 1,
  init.coef = rep(0, 2 * 10),
  npoints = 200,
  extrainfo = FALSE
)
```

## Arguments

f1	observed data, numeric vector
f2	observed data, numeric vector
timet	sample points of functions
iter	length of the chain
burnin	number of burnin MCMC iterations
alpha0, beta0	IG parameters for the prior of sigma1
zpcn	list of mixture coefficients and prior probabilities for Z-mixture pCN algorithm of the form list(betas, probs), where betas and probs are numeric vectors of equal length
propvar	variance of proposal distribution
init.coef	initial coefficients of warping function in exponential map; length must be even
npoints	number of sample points to use during alignment
extrainfo	T/F whether additional information is returned

## Details

The Z-mixture pCN algorithm uses a mixture distribution for the proposal distribution, controlled by input parameter `zpcn`. The `zpcn$betas` must be between 0 and 1, and are the coefficients of the mixture components, with larger coefficients corresponding to larger shifts in parameter space. The `zpcn$probs` give the probability of each shift size.

## Value

Returns a list containing

<code>f2_warped</code>	<code>f2</code> aligned to <code>f1</code>
<code>gamma</code>	Posterior mean gamma function
<code>g.coef</code>	matrix with iter columns, posterior draws of <code>g.coef</code>
<code>psi</code>	Posterior mean psi function
<code>sigma1</code>	numeric vector of length iter, posterior draws of <code>sigma1</code>
<code>accept</code>	Boolean acceptance for each sample (if <code>extrainfo=TRUE</code> )
<code>betas.ind</code>	Index of <code>zpcn</code> mixture component for each sample (if <code>extrainfo=TRUE</code> )
<code>logl</code>	numeric vector of length iter, posterior loglikelihood (if <code>extrainfo=TRUE</code> )
<code>gamma_mat</code>	Matrix of all posterior draws of gamma (if <code>extrainfo=TRUE</code> )
<code>gamma_q025</code>	Lower 0.025 quantile of gamma (if <code>extrainfo=TRUE</code> )
<code>gamma_q975</code>	Upper 0.975 quantile of gamma (if <code>extrainfo=TRUE</code> )
<code>sigma_eff_size</code>	Effective sample size of sigma (if <code>extrainfo=TRUE</code> )
<code>psi_eff_size</code>	Vector of effective sample sizes of psi (if <code>extrainfo=TRUE</code> )
<code>xdist</code>	Vector of posterior draws from <code>xdist</code> between registered functions (if <code>extrainfo=TRUE</code> )
<code>ydist</code>	Vector of posterior draws from <code>ydist</code> between registered functions (if <code>extrainfo=TRUE</code> )

## References

Lu, Y., Herbei, R., and Kurtsek, S. (2017). Bayesian registration of functions with a Gaussian process prior. *Journal of Computational and Graphical Statistics*, DOI: 10.1080/10618600.2017.1336444.

## Examples

```
## Not run:
# This is an MCMC algorithm and takes a long time to run
myzpcn <- list(
  betas = c(0.1, 0.01, 0.005, 0.0001),
  probs = c(0.2, 0.2, 0.4, 0.2)
)
out <- pair_align_functions_expomap(
  f1 = simu_data$f[, 1],
  f2 = simu_data$f[, 2],
  timet = simu_data$time,
  zpcn = myzpcn,
  extrainfo = TRUE
)
```

```

# overall acceptance ratio
mean(out$accept)
# acceptance ratio by zpcn coefficient
with(out, tapply(accept, myzpcn$betas[betas.ind], mean))

## End(Not run)

```

---

pair_align_image	<i>Pairwise align two images This function aligns to images using the q-map framework</i>
------------------	---

---

### Description

Pairwise align two images This function aligns to images using the q-map framework

### Usage

```

pair_align_image(
  I1,
  I2,
  M = 5,
  ortho = TRUE,
  basis_type = "t",
  resize_i = FALSE,
  N = 64,
  stepsize = 1e-05,
  itermax = 1000
)

```

### Arguments

I1	reference image
I2	image to warp
M	number of basis elements (default=5)
ortho	orthonormalize basis (default=TRUE)
basis_type	("t","s","i","o"; default="t")
resize_i	resize image (default=TRUE)
N	size of resized image (default=64)
stepsize	gradient stepsize (default=1e-5)
itermax	maximum number of iterations (default=1000)

### Value

Returns a list containing

Inew	aligned I2
gam	warping function

## References

Q. Xie, S. Kurtsek, E. Klassen, G. E. Christensen and A. Srivastava. Metric-based pairwise and multiple image registration. IEEE European Conference on Computer Vision (ECCV), September, 2014

## Examples

```
## Not run:
# This is a gradient descent algorithm and takes a long time to run
out <- pair_align_image(im$I1, im$I2)

## End(Not run)
```

---

pcaTB

*Tolerance Bound Calculation using Elastic Functional PCA*

---

## Description

This function computes tolerance bounds for functional data containing phase and amplitude variation using principal component analysis

## Usage

```
pcaTB(f, time, m = 4, B = 1e+05, a = 0.05, p = 0.99)
```

## Arguments

f	matrix of functions
time	vector describing time sampling
m	number of principal components (default = 4)
B	number of monte carlo iterations
a	confidence level of tolerance bound (default = 0.05)
p	coverage level of tolerance bound (default = 0.99)

## Value

Returns a list containing

pca	pca output
tol	tolerance factor

## References

- J. D. Tucker, J. R. Lewis, C. King, and S. Kurtek, "A Geometric Approach for Computing Tolerance Bounds for Elastic Functional Data," *Journal of Applied Statistics*, 10.1080/02664763.2019.1645818, 2019.
- Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, *Computational Statistics and Data Analysis* (2012), 10.1016/j.csda.2012.12.001.
- Jung, S. L. a. S. (2016). "Combined Analysis of Amplitude and Phase Variations in Functional Data." arXiv:1603.01775.

## Examples

```
## Not run:
  out1 <- pcaTB(simu_data$f, simu_data$time)

## End(Not run)
```

---

predict.lpcr

*Elastic Prediction for functional logistic PCR Model*

---

## Description

This function performs prediction from an elastic logistic fPCR regression model with phase-variability

## Usage

```
## S3 method for class 'lpcr'
predict(object, newdata = NULL, y = NULL, ...)
```

## Arguments

object	Object of class inheriting from "elastic.pcr.regression"
newdata	An optional matrix in which to look for variables with which to predict. If omitted, the fitted values are used.
y	An optional vector of labels to calculate PC. If omitted, PC is NULL
...	additional arguments affecting the predictions produced

## Value

Returns a list containing

y_pred	predicted probabilities of the class of newdata
y_labels	class labels of newdata
PC	probability of classification



## References

J. D. Tucker, J. R. Lewis, and A. Srivastava, “Elastic Functional Principal Component Regression,” Statistical Analysis and Data Mining, 10.1002/sam.11399, 2018.

---

predict.mlpcr

*Elastic Prediction for functional multinomial logistic PCR Model*

---

## Description

This function performs prediction from an elastic multinomial logistic fPCR regression model with phase-variability

## Usage

```
## S3 method for class 'mlpcr'
predict(object, newdata = NULL, y = NULL, ...)
```

## Arguments

object	Object of class inheriting from "elastic.pcr.regression"
newdata	An optional matrix in which to look for variables with which to predict. If omitted, the fitted values are used.
y	An optional vector of labels to calculate PC. If omitted, PC is NULL
...	additional arguments affecting the predictions produced

## Value

Returns a list containing

y_pred	predicted probabilities of the class of newdata
y_labels	class labels of newdata
PC	probability of classification per class
PC.comb	total probability of classification

## References

J. D. Tucker, J. R. Lewis, and A. Srivastava, “Elastic Functional Principal Component Regression,” Statistical Analysis and Data Mining, 10.1002/sam.11399, 2018.

---

predict.pcr

Elastic Prediction for functional PCR Model

---

### Description

This function performs prediction from an elastic pcr regression model with phase-variability

### Usage

```
## S3 method for class 'pcr'
predict(object, newdata = NULL, y = NULL, ...)
```

### Arguments

object	Object of class inheriting from "elastic.pcr.regression"
newdata	An optional matrix in which to look for variables with which to predict. If omitted, the fitted values are used.
y	An optional vector of responses to calculate SSE. If omitted, SSE is NULL
...	additional arguments affecting the predictions produced

### Value

Returns a list containing

y_pred	predicted values of newdata
SSE	sum of squared errors

### References

J. D. Tucker, J. R. Lewis, and A. Srivastava, "Elastic Functional Principal Component Regression," Statistical Analysis and Data Mining, 10.1002/sam.11399, 2018.

---

q\_to\_curve

Convert to curve space

---

### Description

This function converts SRVFs to curves

### Usage

```
q_to_curve(q, scale = 1)
```

**Arguments**

q                      array describing SRVF (n,T)  
 scale                scale of original beta (default 1)

**Value**

beta array describing curve

**References**

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

**Examples**

```
q <- curve_to_q(beta[, , 1, 1])$q
beta1 <- q_to_curve(q)
```

---

reparam_curve	<i>Align two curves</i>
---------------	-------------------------

---

**Description**

This function aligns two SRVF functions using Dynamic Programming

**Usage**

```
reparam_curve(
  beta1,
  beta2,
  lambda = 0,
  method = "DP",
  w = 0.01,
  rotated = T,
  isclosed = F,
  mode = "0"
)
```

**Arguments**

beta1                array defining curve 1  
 beta2                array defining curve 1  
 lambda              controls amount of warping (default = 0)  
 method              controls which optimization method (default="DP") options are Dynamic Programming ("DP")

w	controls LRBFGS (default = 0.01)
rotated	boolean if rotation is desired
isclosed	boolean if curve is closed
mode	Open ("O") or Closed ("C") curves

**Value**

return a List containing	
gam	warping function
R	rotation matrix
tau	seed point

**References**

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

**Examples**

```
gam <- reparam_curve(beta[, , 1, 1], beta[, , 1, 5])$gam
```

---

reparam_image	<i>Find optimum reparameterization between two images</i>
---------------	---

---

**Description**

Finds the optimal warping function between two images using the elastic framework

**Usage**

```
reparam_image(It, Im, gam, b, stepsize = 1e-05, itermax = 1000, lmark = FALSE)
```

**Arguments**

It	template image matrix
Im	test image matrix
gam	initial warping array
b	basis matrix
stepsize	gradient stepsize (default=1e-5)
itermax	maximum number of iterations (default=1000)
lmark	use landmarks (default=FALSE)

**Value**

Returns a list containing

gamnew	final warping
Inew	aligned image
H	energy
stepsize	final stepsize

**References**

Q. Xie, S. Kurtsek, E. Klassen, G. E. Christensen and A. Srivastava. Metric-based pairwise and multiple image registration. IEEE European Conference on Computer Vision (ECCV), September, 2014

---

resamplecurve	<i>Resample Curve</i>
---------------	-----------------------

---

**Description**

This function resamples a curve to a number of points

**Usage**

```
resamplecurve(x, N = 100, mode = "O")
```

**Arguments**

x	matrix defining curve (n,T)
N	Number of samples to re-sample curve, N usually is > T
mode	Open ("O") or Closed ("C") curves

**Value**

xn matrix defining resampled curve

**References**

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

**Examples**

```
xn <- resamplecurve(beta[, , 1, 1], 200)
```

---

rgam	<i>Random Warping</i>
------	-----------------------

---

**Description**

Generates random warping functions

**Usage**

```
rgam(N, sigma, num)
```

**Arguments**

N	length of warping function
sigma	variance of warping functions
num	number of warping functions

**Value**

gam warping functions

**References**

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

**Examples**

```
gam = rgam(N=101, sigma=.01, num=35)
```

---

sample_shapes	<i>Sample shapes from model</i>
---------------	---------------------------------

---

**Description**

Sample shapes from model

**Usage**

```
sample_shapes(mu, K, mode = "0", no = 3, numSamp = 10)
```

**Arguments**

mu	array (n,T) of mean srvf
K	array (2T,2T) covariance matrix
mode	Open ("O") or Closed ("C") curves
no	number of principal components
numSamp	number of samples

**Value**

samples list of sample curves

**References**

Srivastava, A., Klassen, E., Joshi, S., Jermyn, I., (2011). Shape analysis of elastic curves in euclidean spaces. Pattern Analysis and Machine Intelligence, IEEE Transactions on 33 (7), 1415-1428.

**Examples**

```
out <- curve_karcher_mean(beta[, , 1, 1:2], maxit = 2)
# note: use more shapes, small for speed
K <- curve_karcher_cov(out$v)
samples <- sample_shapes(out$mu, K)
```

---

simu_data	<i>Simulated two Gaussian Dataset</i>
-----------	---------------------------------------

---

**Description**

A functional dataset where the individual functions are given by:  $y_i(t) = z_{i,1}e^{-(t-1.5)^2/2} + z_{i,2}e^{-(t+1.5)^2/2}$ ,  $t \in [-3, 3]$ ,  $i = 1, 2, \dots, 21$ , where  $z_{i,1}$  and  $z_{i,2}$  are *i.i.d.* normal with mean one and standard deviation 0.25. Each of these functions is then warped according to:  $\gamma_i(t) = 6\left(\frac{e^{a_i(t+3)/6}-1}{e^{a_i}-1}\right) - 3$  if  $a_i \neq 0$ , otherwise  $\gamma_i = \gamma_{id}$  ( $\gamma_{id}(t) = t$  is the identity warping). The variables are as follows: f containing the 21 functions of 101 samples and time which describes the sampling.

**Usage**

```
simu_data
```

**Format**

simu\_data:

A list with 2 components:

- f: A numeric matrix of shape  $101 \times 21$  storing a sample of size  $N = 21$  of curves evaluated on a grid of size  $M = 101$ .
- time: A numeric vector of size  $M = 101$  storing the grid on which the curves f have been evaluated.

---

simu\_warp

*Aligned Simulated two Gaussian Dataset*

---

**Description**

A functional dataset where the individual functions are given by:  $y_i(t) = z_{i,1}e^{-(t-1.5)^2/2} + z_{i,2}e^{-(t+1.5)^2/2}$ ,  $t \in [-3, 3]$ ,  $i = 1, 2, \dots, 21$ , where  $z_{i,1}$  and  $z_{i,2}$  are *i.i.d.* normal with mean one and standard deviation 0.25. Each of these functions is then warped according to:  $\gamma_i(t) = 6\left(\frac{e^{a_i(t+3)/6}-1}{e^{a_i}-1}\right) - 3$  if  $a_i \neq 0$ , otherwise  $\gamma_i = \gamma_{id}$  ( $\gamma_{id}(t) = t$  is the identity warping). The variables are as follows: f containing the 21 functions of 101 samples and time which describes the sampling which has been aligned.

**Usage**

simu\_warp

**Format**

simu\_warp:

A list which contains the output of the `time_warping()` function applied on the data set simu\_data.

---

simu\_warp\_median

*Aligned Simulated two Gaussian Dataset using Median*

---

**Description**

A functional dataset where the individual functions are given by:  $y_i(t) = z_{i,1}e^{-(t-1.5)^2/2} + z_{i,2}e^{-(t+1.5)^2/2}$ ,  $t \in [-3, 3]$ ,  $i = 1, 2, \dots, 21$ , where  $z_{i,1}$  and  $z_{i,2}$  are *i.i.d.* normal with mean one and standard deviation 0.25. Each of these functions is then warped according to:  $\gamma_i(t) = 6\left(\frac{e^{a_i(t+3)/6}-1}{e^{a_i}-1}\right) - 3$  if  $a_i \neq 0$ , otherwise  $\gamma_i = \gamma_{id}$  ( $\gamma_{id}(t) = t$  is the identity warping). The variables are as follows: f containing the 21 functions of 101 samples and time which describes the sampling which has been aligned.

**Usage**

simu\_warp\_median



**Format**

simu\_warp\_median:

A list which contains the output of the `time_warping()` function finding the median applied on the data set `simu_data`.

---

smooth.data

*Smooth Functions*

---

**Description**

This function smooths functions using standard box filter

**Usage**

```
smooth.data(f, sparam)
```

**Arguments**

f	matrix ( $N \times M$ ) of $M$ functions with $N$ samples
sparam	number of times to run box filter

**Value**

fo smoothed functions

**References**

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

**Examples**

```
fo <- smooth.data(simu_data$f, 25)
```

---

SqrtMean	<i>SRVF transform of warping functions</i>
----------	--

---

## Description

This function calculates the srvf of warping functions with corresponding shooting vectors and finds the mean

## Usage

```
SqrtMean(gam)
```

## Arguments

gam	matrix ( $N \times M$ ) of $M$ warping functions with $N$ samples
-----	---

## Value

Returns a list containing

mu	Karcher mean psi function
gam_mu	Karcher mean warping function
psi	srvf of warping functions
vec	shooting vectors

## References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

## Examples

```
out <- SqrtMean(simu_warp$warping_functions)
```

---

SqrtMeanInverse	<i>SRVF transform of warping functions</i>
-----------------	--

---

**Description**

This function calculates the srvf of warping functions with corresponding shooting vectors and finds the inverse of mean

**Usage**

```
SqrtMeanInverse(gam)
```

**Arguments**

gam                      matrix ( $N \times M$ ) of  $M$  warping functions with  $N$  samples

**Value**

gamI inverse of Karcher mean warping function

**References**

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

**Examples**

```
gamI <- SqrtMeanInverse(simu_warp$warping_functions)
```

---

SqrtMedian	<i>SRVF transform of warping functions</i>
------------	--

---

**Description**

This function calculates the srvf of warping functions with corresponding shooting vectors and finds the median

**Usage**

```
SqrtMedian(gam)
```

**Arguments**

gam                      matrix ( $N \times M$ ) of  $M$  warping functions with  $N$  samples

**Value**

Returns a list containing

median	Karcher median psi function
gam_median	Karcher mean warping function
psi	srvf of warping functions
vec	shooting vectors

**References**

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

**Examples**

```
out <- SqrtMedian(simu_warp_median$warping_functions)
```

---

srvf_to_f	<i>Transformation from SRSF Space</i>
-----------	---------------------------------------

---

**Description**

This function transforms SRVFs back to the original functional space.

**Usage**

```
srvf_to_f(q, time, f0 = 0, multidimensional = FALSE)
```

**Arguments**

- q
- Either a numeric vector of a numeric matrix or a numeric array specifying the SRSFs that need to be transformed.
- If a vector, it must be of shape  $M$  and it is interpreted as a single 1-dimensional curve observed on a grid of size  $M$ .
  - If a matrix and `multidimensional == FALSE`, it must be of shape  $M \times N$ . In this case, it is interpreted as a sample of  $N$  curves observed on a grid of size  $M$ , unless  $M = 1$  in which case it is interpreted as a single 1-dimensional curve observed on a grid of size  $M$ .
  - If a matrix and `multidimensional == TRUE`, it must be of shape  $L \times M$  and it is interpreted as a single  $L$ -dimensional curve observed on a grid of size  $M$ .
  - If a 3D array, it must be of shape  $L \times M \times N$  and it is interpreted as a sample of  $N$   $L$ -dimensional curves observed on a grid of size  $M$ .

time	A numeric vector of length $M$ specifying the grid on which SRSFs are evaluated.
f0	Either a numeric value or a numeric vector or a numeric matrix specifying the initial value of the curves in the original functional space. It must be: <ul style="list-style-type: none"> <li>• a value if <math>q</math> represents a single 1-dimensional SRSF.</li> <li>• a vector of length <math>L</math> if <math>q</math> represents a single <math>L</math>-dimensional SRSF.</li> <li>• a vector of length <math>N</math> if <math>q</math> represents a sample of <math>N</math> 1-dimensional SRSFs.</li> <li>• a matrix of shape <math>L \times M</math> if <math>q</math> represents a sample of <math>N</math> <math>L</math>-dimensional SRSFs.</li> </ul>
multidimensional	A boolean specifying if the curves are multi-dimensional. This is useful when $q$ is provided as a matrix to determine whether it is a single multi-dimensional curve or a collection of uni-dimensional curves. Defaults to FALSE.

### Value

A numeric array of the same shape as the input  $q$  storing the transformation of the SRSFs  $q$  back to the original functional space.

### References

Srivastava, A., Wu, W., Kurtsek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative models for functional data using amplitude and phase separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

### Examples

```
q <- f_to_srvf(simu_data$f, simu_data$time)
f <- srvf_to_f(q, simu_data$time, simu_data$f[1, ])
```

---

time_warping	<i>Alignment of univariate functional data</i>
--------------	--

---

### Description

This function aligns a collection of 1-dimensional curves that are observed on the same grid.

### Usage

```
time_warping(
  f,
  time,
  lambda = 0,
  penalty_method = c("roughness", "geodesic", "norm"),
  centroid_type = c("mean", "median"),
  center_warpings = TRUE,
```

```

smooth_data = FALSE,
sparam = 25L,
parallel = FALSE,
optim_method = c("DP", "DPo", "DP2", "RBFGS"),
max_iter = 20L
)

```

### Arguments

<code>f</code>	A numeric matrix of shape $M \times N$ specifying a sample of $N$ curves observed on a grid of size $M$ .
<code>time</code>	A numeric vector of length $M$ specifying the common grid on which all curves <code>f</code> have been observed.
<code>lambda</code>	A numeric value specifying the elasticity. Defaults to $0.0$ .
<code>penalty_method</code>	A string specifying the penalty term used in the formulation of the cost function to minimize for alignment. Choices are "roughness" which uses the norm of the second derivative, "geodesic" which uses the geodesic distance to the identity and "norm" which uses the Euclidean distance to the identity. Defaults to "roughness".
<code>centroid_type</code>	A string specifying the type of centroid to align to. Choices are "mean" or "median". Defaults to "mean".
<code>center_warpings</code>	A boolean specifying whether to center the estimated warping functions. Defaults to TRUE.
<code>smooth_data</code>	A boolean specifying whether to smooth curves using a box filter. Defaults to FALSE.
<code>sparam</code>	An integer value specifying the number of times to apply the box filter. Defaults to 25L. This is used only when <code>smooth_data = TRUE</code> .
<code>parallel</code>	A boolean specifying whether to run calculations in parallel. Defaults to FALSE.
<code>optim_method</code>	A string specifying the algorithm used for optimization. Choices are "DP", "DPo", and "RBFGS". Defaults to "DP".
<code>max_iter</code>	An integer value specifying the maximum number of iterations. Defaults to 20L.

### Value

An object of class `fdawarp` which is a list with the following components:

- `time`: a numeric vector of length  $M$  storing the original grid;
- `f0`: a numeric matrix of shape  $M \times N$  storing the original sample of  $N$  functions observed on a grid of size  $M$ ;
- `q0`: a numeric matrix of the same shape as `f0` storing the original SRSFs;
- `fn`: a numeric matrix of the same shape as `f0` storing the aligned functions;
- `qn`: a numeric matrix of the same shape as `f0` storing the aligned SRSFs;
- `fmean`: a numeric vector of length  $M$  storing the mean or median curve;
- `mqn`: a numeric vector of length  $M$  storing the mean or median SRSF;

- `warping_functions`: a numeric matrix of the same shape as `f0` storing the estimated warping functions;
- `original_variance`: a numeric value storing the variance of the original sample;
- `amplitude_variance`: a numeric value storing the variance in amplitude of the aligned sample;
- `phase_variance`: a numeric value storing the variance in phase of the aligned sample;
- `qun`: a numeric vector of maximum length `max_iter + 2` storing the values of the cost function after each iteration;
- `lambda`: the input parameter `lambda` which specifies the elasticity;
- `centroid_type`: the input centroid type;
- `optim_method`: the input optimization method;
- `inverse_average_warping_function`: the inverse of the mean estimated warping function;
- `rsamps`: TO DO.

## References

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using Fisher-Rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative models for functional data using phase and amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

## Examples

```
## Not run:
out <- time_warping(simu_data$f, simu_data$time)

## End(Not run)
```

---

toy\_data

*Distributed Gaussian Peak Dataset*


---

## Description

A functional dataset where the individual functions are given by a Gaussian peak with locations along the  $x$ -axis. The variables are as follows: `f` containing the 29 functions of 101 samples and `time` which describes the sampling.

## Usage

```
toy_data
```

**Format**

toy\_data:

A list with two components:

- f: A numeric matrix of shape  $101 \times 29$  storing a sample of size  $N = 29$  of curves evaluated on a grid of size  $M = 101$ .
- time: A numeric vector of size  $M = 101$  storing the grid on which the curves f have been evaluated.

---

toy\_warp

*Aligned Distributed Gaussian Peak Dataset*

---

**Description**

A functional dataset where the individual functions are given by a Gaussian peak with locations along the  $x$ -axis. The variables are as follows: f containing the 29 functions of 101 samples and time which describes the sampling which as been aligned.

**Usage**

toy\_warp

**Format**

toy\_warp:

A list which contains the output of the `time_warping()` function applied on the data set toy\_data.

---

vertFPCA

*Vertical Functional Principal Component Analysis*

---

**Description**

This function calculates vertical functional principal component analysis on aligned data

**Usage**

```
vertFPCA(
  warp_data,
  no,
  id = round(length(warp_data$time)/2),
  ci = c(-1, 0, 1),
  showplot = TRUE
)
```



**Arguments**

warp_data	fdawarp object from <a href="#">time_warping</a> of aligned data
no	number of principal components to extract
id	point to use for $f(0)$ (default = midpoint)
ci	geodesic standard deviations (default = $c(-1,0,1)$ )
showplot	show plots of principal directions (default = T)

**Value**

Returns a vfPCA object containing

q_pca	srvf principal directions
f_pca	f principal directions
latent	latent values
coef	coefficients
U	eigenvectors
id	point used for $f(0)$

**References**

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

**Examples**

```
vfPCA <- vertFPCA(simu_warp, no = 3)
```

---

v_to_gam	<i>map shooting vector to warping function at identity</i>
----------	--

---

**Description**

map shooting vector to warping function at identity

**Usage**

```
v_to_gam(v)
```

**Arguments**

v	Either a numeric vector of a numeric matrix or a numeric array specifying the shooting vectors
---	--

**Value**

A numeric array of the same shape as the input array  $v$  storing the shooting vectors of  $v$  obtained via finite differences.

---

warp_f_gamma	<i>Warp Function</i>
--------------	----------------------

---

**Description**

This function warps function  $f$  by  $\gamma$

**Usage**

```
warp_f_gamma(f, time, gamma, spl.int = FALSE)
```

**Arguments**

<code>f</code>	vector function
<code>time</code>	time
<code>gamma</code>	vector warping function
<code>spl.int</code>	use spline interpolation (default F)

**Value**

fnew warped function

**References**

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

**Examples**

```
fnew <- warp_f_gamma(
  f = simu_data$f[, 1],
  time = simu_data$time,
  gamma = seq(0, 1, length.out = 101)
)
```

---

warp\_q\_gamma

---

*Warp SRSF***Description**

This function warps srsf  $q$  by  $\gamma$

**Usage**

```
warp_q_gamma(q, time, gamma, spl.int = FALSE)
```

**Arguments**

<code>q</code>	vector
<code>time</code>	time
<code>gamma</code>	vector warping function
<code>spl.int</code>	use spline interpolation (default F)

**Value**

qnew warped function

**References**

Srivastava, A., Wu, W., Kurtek, S., Klassen, E., Marron, J. S., May 2011. Registration of functional data using fisher-rao metric, arXiv:1103.3817v2.

Tucker, J. D., Wu, W., Srivastava, A., Generative Models for Function Data using Phase and Amplitude Separation, Computational Statistics and Data Analysis (2012), 10.1016/j.csda.2012.12.001.

**Examples**

```
q <- f_to_srvf(simu_data$f, simu_data$time)
qnew <- warp_q_gamma(q[, 1], simu_data$time, seq(0, 1, length.out = 101))
```

# Index

## \* alignment

- curve\_geodesic, 9
- curve\_karcher\_cov, 9
- curve\_karcher\_mean, 10
- curve\_pair\_align, 12
- curve\_principal\_directions, 13
- curve\_srvf\_align, 14
- curve\_to\_q, 15
- elastic.logistic, 17
- elastic.lpcr.regression, 19
- elastic.mlogistic, 20
- elastic.mlpcr.regression, 21
- elastic.pcr.regression, 22
- elastic.prediction, 24
- elastic.regression, 25
- elastic\_amp\_change\_ff, 26
- elastic\_change\_fPCA, 27
- elastic\_ph\_change\_ff, 29
- f\_to\_srvf, 33
- gam\_to\_v, 34
- gradient, 36
- horizFPCA, 37
- inv\_exp\_map, 39
- invertGamma, 39
- jointFPCA, 40
- kmeans\_align, 42
- multiple\_align\_functions, 45
- optimum.reparam, 46
- pair\_align\_functions, 49
- pair\_align\_image, 54
- predict.lpcr, 56
- predict.mlpcr, 57
- predict.pcr, 58
- q\_to\_curve, 58
- reparam\_curve, 59
- reparam\_image, 60
- resamplecurve, 61
- sample\_shapes, 62
- smooth.data, 65

- SqrtMean, 66

- SqrtMeanInverse, 67

- SqrtMedian, 67

- srvf\_to\_f, 68

- time\_warping, 69

- v\_to\_gam, 73

- vertFPCA, 72

- warp\_f\_gamma, 74

- warp\_q\_gamma, 75

## \* bayesian

- function\_group\_warp\_bayes, 31

- function\_mean\_bayes, 32

- pair\_align\_functions\_bayes, 50

## \* bootstrap

- bootTB, 5

## \* bounds

- bootTB, 5

## \* changepoint

- elastic\_amp\_change\_ff, 26

- elastic\_change\_fPCA, 27

- elastic\_ph\_change\_ff, 29

## \* clustering

- kmeans\_align, 42

## \* datasets

- beta, 5

- growth\_vel, 37

- im, 38

- simu\_data, 63

- simu\_warp, 64

- simu\_warp\_median, 64

- toy\_data, 71

- toy\_warp, 72

## \* depth

- elastic.depth, 15

## \* detection

- outlier.detection, 48

## \* diffeomorphism

- rgam, 62

## \* distances

- calc\_shape\_dist, 8
- elastic.distance, 16
- \* **function**
  - rgam, 62
- \* **image**
  - pair\_align\_image, 54
  - reparam\_image, 60
- \* **outlier**
  - outlier.detection, 48
- \* **pca tolerance bounds**
  - pcaTB, 55
- \* **pca**
  - align\_fPCA, 3
  - gauss\_model, 35
  - joint\_gauss\_model, 41
- \* **regression**
  - elastic.logistic, 17
  - elastic.lpcr.regression, 19
  - elastic.mlogistic, 20
  - elastic.mlpcr.regression, 21
  - elastic.pcr.regression, 22
  - elastic.prediction, 24
  - elastic.regression, 25
  - predict.lpcr, 56
  - predict.mlpcr, 57
  - predict.pcr, 58
- \* **srsf alignment**
  - function\_group\_warp\_bayes, 31
  - function\_mean\_bayes, 32
  - pair\_align\_functions\_bayes, 50
- \* **srsf**
  - f\_to\_srvf, 33
  - kmeans\_align, 42
  - multiple\_align\_functions, 45
  - optimum.reparam, 46
  - pair\_align\_functions, 49
  - srvf\_to\_f, 68
  - time\_warping, 69
- \* **srvf alignment**
  - align\_fPCA, 3
  - elastic.depth, 15
  - elastic.distance, 16
- \* **srvf**
  - curve\_geodesic, 9
  - curve\_karcher\_cov, 9
  - curve\_karcher\_mean, 10
  - curve\_pair\_align, 12
  - curve\_principal\_directions, 13
  - curve\_srvf\_align, 14
  - curve\_to\_q, 15
  - elastic.logistic, 17
  - elastic.lpcr.regression, 19
  - elastic.mlogistic, 20
  - elastic.mlpcr.regression, 21
  - elastic.pcr.regression, 22
  - elastic.prediction, 24
  - elastic.regression, 25
  - elastic\_amp\_change\_ff, 26
  - elastic\_change\_fpca, 27
  - elastic\_ph\_change\_ff, 29
  - gam\_to\_v, 34
  - gradient, 36
  - horizFPCA, 37
  - inv\_exp\_map, 39
  - invertGamma, 39
  - jointFPCA, 40
  - outlier.detection, 48
  - predict.lpcr, 56
  - predict.mlpcr, 57
  - predict.pcr, 58
  - q\_to\_curve, 58
  - reparam\_curve, 59
  - resamplecurve, 61
  - sample\_shapes, 62
  - smooth.data, 65
  - SqrtMean, 66
  - SqrtMeanInverse, 67
  - SqrtMedian, 67
  - v\_to\_gam, 73
  - vertFPCA, 72
  - warp\_f\_gamma, 74
  - warp\_q\_gamma, 75
- \* **tolerance**
  - bootTB, 5
- \* **warping**
  - rgam, 62
- align\_fPCA, 3
- beta, 5
- bootTB, 5
- boxplot.ampbox (boxplot.fdawarp), 6
- boxplot.fdawarp, 6
- boxplot.fdawarp(), 7
- boxplot.phbox (boxplot.fdawarp), 6
- calc\_shape\_dist, 8

curve\_geodesic, 9  
curve\_karcher\_cov, 9  
curve\_karcher\_mean, 10  
curve\_pair\_align, 12  
curve\_principal\_directions, 13  
curve\_srvf\_align, 14  
curve\_to\_q, 15  
  
elastic.depth, 15  
elastic.distance, 16  
elastic.logistic, 17  
elastic.lpcr.regression, 19  
elastic.mlogistic, 20  
elastic.mlpcr.regression, 21  
elastic.pcr.regression, 22  
elastic.prediction, 24  
elastic.regression, 25  
elastic\_amp\_change\_ff, 26  
elastic\_change\_fPCA, 27  
elastic\_ph\_change\_ff, 29  
  
f\_to\_srvf, 33  
fdasrvf, 30  
fdasrvf-package (fdasrvf), 30  
foreach(), 18, 20, 25, 45  
foreach::foreach(), 43  
function\_group\_warp\_bayes, 31  
function\_mean\_bayes, 32  
  
gam\_to\_v, 34  
gauss\_model, 35  
gradient, 36  
growth\_vel, 37  
  
horizFPCA, 37  
  
im, 38  
inv\_exp\_map, 39  
invertGamma, 39  
  
joint\_gauss\_model, 41  
jointFPCA, 40  
  
kmeans\_align, 42  
  
LongRunCovMatrix, 44  
  
multiple\_align\_functions, 45  
  
optimum.reparam, 46  
  
outlier.detection, 48  
  
pair\_align\_functions, 49  
pair\_align\_functions\_bayes, 50  
pair\_align\_functions\_expomap, 52  
pair\_align\_image, 54  
pcaTB, 55  
predict.lpcr, 56  
predict.mlpcr, 57  
predict.pcr, 58  
  
q\_to\_curve, 58  
  
reparam\_curve, 59  
reparam\_image, 60  
resamplecurve, 61  
rgam, 62  
  
sample\_shapes, 62  
simu\_data, 63  
simu\_warp, 64  
simu\_warp\_median, 64  
smooth.data, 65  
SqrtMean, 66  
SqrtMeanInverse, 67  
SqrtMedian, 67  
srvf\_to\_f, 68  
  
time\_warping, 35, 37, 40, 41, 69, 73  
time\_warping(), 7, 48, 64, 65, 72  
toy\_data, 71  
toy\_warp, 72  
  
v\_to\_gam, 73  
vertFPCA, 72  
  
warp\_f\_gamma, 74  
warp\_q\_gamma, 75