

---

# Amazon Cloud Directory

## API Reference



## **Amazon Cloud Directory: API Reference**

Copyright © 2019 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

## Table of Contents

Welcome .....	1
Actions .....	2
AddFacetToObject .....	4
Request Syntax .....	4
URI Request Parameters .....	4
Request Body .....	4
Response Syntax .....	5
Response Elements .....	5
Errors .....	5
Examples .....	6
See Also .....	7
ApplySchema .....	8
Request Syntax .....	8
URI Request Parameters .....	8
Request Body .....	8
Response Syntax .....	8
Response Elements .....	8
Errors .....	9
Examples .....	10
See Also .....	10
AttachObject .....	12
Request Syntax .....	12
URI Request Parameters .....	12
Request Body .....	12
Response Syntax .....	13
Response Elements .....	13
Errors .....	13
Examples .....	14
See Also .....	15
AttachPolicy .....	16
Request Syntax .....	16
URI Request Parameters .....	16
Request Body .....	16
Response Syntax .....	16
Response Elements .....	16
Errors .....	17
Examples .....	18
See Also .....	18
AttachToIndex .....	19
Request Syntax .....	19
URI Request Parameters .....	19
Request Body .....	19
Response Syntax .....	19
Response Elements .....	20
Errors .....	20
Examples .....	21
See Also .....	22
AttachTypedLink .....	23
Request Syntax .....	23
URI Request Parameters .....	23
Request Body .....	23
Response Syntax .....	24
Response Elements .....	24
Errors .....	25

Examples .....	26
See Also .....	27
BatchRead .....	28
Request Syntax .....	28
URI Request Parameters .....	31
Request Body .....	31
Response Syntax .....	31
Response Elements .....	35
Errors .....	35
Examples .....	36
See Also .....	37
BatchWrite .....	38
Request Syntax .....	38
URI Request Parameters .....	42
Request Body .....	42
Response Syntax .....	42
Response Elements .....	43
Errors .....	43
Examples .....	44
See Also .....	45
CreateDirectory .....	46
Request Syntax .....	46
URI Request Parameters .....	46
Request Body .....	46
Response Syntax .....	46
Response Elements .....	47
Errors .....	47
Examples .....	48
See Also .....	49
CreateFacet .....	50
Request Syntax .....	50
URI Request Parameters .....	50
Request Body .....	50
Response Syntax .....	51
Response Elements .....	51
Errors .....	51
Examples .....	53
See Also .....	53
CreateIndex .....	54
Request Syntax .....	54
URI Request Parameters .....	54
Request Body .....	54
Response Syntax .....	55
Response Elements .....	55
Errors .....	55
Examples .....	56
See Also .....	57
CreateObject .....	58
Request Syntax .....	58
URI Request Parameters .....	58
Request Body .....	58
Response Syntax .....	59
Response Elements .....	59
Errors .....	59
Examples .....	61
See Also .....	61
CreateSchema .....	63

Request Syntax .....	63
URI Request Parameters .....	63
Request Body .....	63
Response Syntax .....	63
Response Elements .....	63
Errors .....	64
Examples .....	65
See Also .....	65
CreateTypedLinkFacet .....	66
Request Syntax .....	66
URI Request Parameters .....	66
Request Body .....	66
Response Syntax .....	67
Response Elements .....	67
Errors .....	67
Examples .....	68
See Also .....	69
DeleteDirectory .....	70
Request Syntax .....	70
URI Request Parameters .....	70
Request Body .....	70
Response Syntax .....	70
Response Elements .....	70
Errors .....	70
Examples .....	71
See Also .....	72
DeleteFacet .....	73
Request Syntax .....	73
URI Request Parameters .....	73
Request Body .....	73
Response Syntax .....	73
Response Elements .....	73
Errors .....	73
Examples .....	74
See Also .....	75
DeleteObject .....	76
Request Syntax .....	76
URI Request Parameters .....	76
Request Body .....	76
Response Syntax .....	76
Response Elements .....	76
Errors .....	76
Examples .....	77
See Also .....	78
DeleteSchema .....	79
Request Syntax .....	79
URI Request Parameters .....	79
Request Body .....	79
Response Syntax .....	79
Response Elements .....	79
Errors .....	79
Examples .....	80
See Also .....	81
DeleteTypedLinkFacet .....	82
Request Syntax .....	82
URI Request Parameters .....	82
Request Body .....	82

Response Syntax .....	82
Response Elements .....	82
Errors .....	82
Examples .....	83
See Also .....	84
DetachFromIndex .....	85
Request Syntax .....	85
URI Request Parameters .....	85
Request Body .....	85
Response Syntax .....	85
Response Elements .....	86
Errors .....	86
Examples .....	87
See Also .....	88
DetachObject .....	89
Request Syntax .....	89
URI Request Parameters .....	89
Request Body .....	89
Response Syntax .....	89
Response Elements .....	90
Errors .....	90
Examples .....	91
See Also .....	92
DetachPolicy .....	93
Request Syntax .....	93
URI Request Parameters .....	93
Request Body .....	93
Response Syntax .....	93
Response Elements .....	93
Errors .....	94
Examples .....	95
See Also .....	95
DetachTypedLink .....	96
Request Syntax .....	96
URI Request Parameters .....	96
Request Body .....	96
Response Syntax .....	97
Response Elements .....	97
Errors .....	97
Examples .....	98
See Also .....	99
DisableDirectory .....	100
Request Syntax .....	100
URI Request Parameters .....	100
Request Body .....	100
Response Syntax .....	100
Response Elements .....	100
Errors .....	100
Examples .....	101
See Also .....	102
EnableDirectory .....	103
Request Syntax .....	103
URI Request Parameters .....	103
Request Body .....	103
Response Syntax .....	103
Response Elements .....	103
Errors .....	103

Examples .....	104
See Also .....	105
GetAppliedSchemaVersion .....	106
Request Syntax .....	106
URI Request Parameters .....	106
Request Body .....	106
Response Syntax .....	106
Response Elements .....	106
Errors .....	106
See Also .....	107
GetDirectory .....	109
Request Syntax .....	109
URI Request Parameters .....	109
Request Body .....	109
Response Syntax .....	109
Response Elements .....	109
Errors .....	109
Examples .....	110
See Also .....	111
GetFacet .....	112
Request Syntax .....	112
URI Request Parameters .....	112
Request Body .....	112
Response Syntax .....	112
Response Elements .....	113
Errors .....	113
Examples .....	114
See Also .....	114
GetLinkAttributes .....	116
Request Syntax .....	116
URI Request Parameters .....	116
Request Body .....	116
Response Syntax .....	117
Response Elements .....	117
Errors .....	118
See Also .....	119
GetObjectAttributes .....	120
Request Syntax .....	120
URI Request Parameters .....	120
Request Body .....	120
Response Syntax .....	121
Response Elements .....	121
Errors .....	121
See Also .....	122
GetObjectInformation .....	124
Request Syntax .....	124
URI Request Parameters .....	124
Request Body .....	124
Response Syntax .....	124
Response Elements .....	125
Errors .....	125
Examples .....	126
See Also .....	127
GetSchemaAsJson .....	128
Request Syntax .....	128
URI Request Parameters .....	128
Request Body .....	128

Response Syntax .....	128
Response Elements .....	128
Errors .....	129
Examples .....	129
See Also .....	131
GetTypedLinkFacetInformation .....	132
Request Syntax .....	132
URI Request Parameters .....	132
Request Body .....	132
Response Syntax .....	132
Response Elements .....	132
Errors .....	133
Examples .....	134
See Also .....	134
ListAppliedSchemaArns .....	136
Request Syntax .....	136
URI Request Parameters .....	136
Request Body .....	136
Response Syntax .....	137
Response Elements .....	137
Errors .....	137
Examples .....	138
See Also .....	139
ListAttachedIndices .....	140
Request Syntax .....	140
URI Request Parameters .....	140
Request Body .....	140
Response Syntax .....	141
Response Elements .....	141
Errors .....	141
Examples .....	142
See Also .....	143
ListDevelopmentSchemaArns .....	144
Request Syntax .....	144
URI Request Parameters .....	144
Request Body .....	144
Response Syntax .....	144
Response Elements .....	144
Errors .....	145
Examples .....	146
See Also .....	146
ListDirectories .....	148
Request Syntax .....	148
URI Request Parameters .....	148
Request Body .....	148
Response Syntax .....	148
Response Elements .....	149
Errors .....	149
Examples .....	150
See Also .....	151
ListFacetAttributes .....	152
Request Syntax .....	152
URI Request Parameters .....	152
Request Body .....	152
Response Syntax .....	153
Response Elements .....	153
Errors .....	153



Examples .....	154
See Also .....	158
ListFacetNames .....	159
Request Syntax .....	159
URI Request Parameters .....	159
Request Body .....	159
Response Syntax .....	159
Response Elements .....	160
Errors .....	160
Examples .....	161
See Also .....	161
ListIncomingTypedLinks .....	163
Request Syntax .....	163
URI Request Parameters .....	163
Request Body .....	163
Response Syntax .....	164
Response Elements .....	165
Errors .....	165
Examples .....	166
See Also .....	168
ListIndex .....	169
Request Syntax .....	169
URI Request Parameters .....	169
Request Body .....	170
Response Syntax .....	170
Response Elements .....	171
Errors .....	171
Examples .....	172
See Also .....	173
ListManagedSchemaArns .....	174
Request Syntax .....	174
URI Request Parameters .....	174
Request Body .....	174
Response Syntax .....	174
Response Elements .....	175
Errors .....	175
See Also .....	176
ListObjectAttributes .....	177
Request Syntax .....	177
URI Request Parameters .....	177
Request Body .....	177
Response Syntax .....	178
Response Elements .....	178
Errors .....	179
Examples .....	180
See Also .....	181
ListObjectChildren .....	182
Request Syntax .....	182
URI Request Parameters .....	182
Request Body .....	182
Response Syntax .....	183
Response Elements .....	183
Errors .....	183
Examples .....	184
See Also .....	185
ListObjectParentPaths .....	186
Request Syntax .....	186

URI Request Parameters .....	186
Request Body .....	186
Response Syntax .....	187
Response Elements .....	187
Errors .....	187
See Also .....	188
ListObjectParents .....	189
Request Syntax .....	189
URI Request Parameters .....	189
Request Body .....	189
Response Syntax .....	190
Response Elements .....	190
Errors .....	191
See Also .....	192
ListObjectPolicies .....	193
Request Syntax .....	193
URI Request Parameters .....	193
Request Body .....	193
Response Syntax .....	194
Response Elements .....	194
Errors .....	194
See Also .....	195
ListOutgoingTypedLinks .....	196
Request Syntax .....	196
URI Request Parameters .....	196
Request Body .....	196
Response Syntax .....	197
Response Elements .....	198
Errors .....	198
See Also .....	199
ListPolicyAttachments .....	201
Request Syntax .....	201
URI Request Parameters .....	201
Request Body .....	201
Response Syntax .....	202
Response Elements .....	202
Errors .....	202
See Also .....	203
ListPublishedSchemaArns .....	205
Request Syntax .....	205
URI Request Parameters .....	205
Request Body .....	205
Response Syntax .....	205
Response Elements .....	206
Errors .....	206
See Also .....	207
ListTagsForResource .....	208
Request Syntax .....	208
URI Request Parameters .....	208
Request Body .....	208
Response Syntax .....	208
Response Elements .....	209
Errors .....	209
See Also .....	210
ListTypedLinkFacetAttributes .....	211
Request Syntax .....	211
URI Request Parameters .....	211

Request Body .....	211
Response Syntax .....	212
Response Elements .....	212
Errors .....	212
See Also .....	213
ListTypedLinkFacetNames .....	215
Request Syntax .....	215
URI Request Parameters .....	215
Request Body .....	215
Response Syntax .....	215
Response Elements .....	216
Errors .....	216
See Also .....	217
LookupPolicy .....	218
Request Syntax .....	218
URI Request Parameters .....	218
Request Body .....	218
Response Syntax .....	219
Response Elements .....	219
Errors .....	219
See Also .....	220
PublishSchema .....	222
Request Syntax .....	222
URI Request Parameters .....	222
Request Body .....	222
Response Syntax .....	223
Response Elements .....	223
Errors .....	223
See Also .....	224
PutSchemaFromJson .....	225
Request Syntax .....	225
URI Request Parameters .....	225
Request Body .....	225
Response Syntax .....	225
Response Elements .....	225
Errors .....	226
See Also .....	226
RemoveFacetFromObject .....	228
Request Syntax .....	228
URI Request Parameters .....	228
Request Body .....	228
Response Syntax .....	228
Response Elements .....	228
Errors .....	229
See Also .....	230
TagResource .....	231
Request Syntax .....	231
URI Request Parameters .....	231
Request Body .....	231
Response Syntax .....	231
Response Elements .....	231
Errors .....	231
See Also .....	232
UntagResource .....	234
Request Syntax .....	234
URI Request Parameters .....	234
Request Body .....	234

Response Syntax .....	234
Response Elements .....	234
Errors .....	234
See Also .....	235
UpdateFacet .....	237
Request Syntax .....	237
URI Request Parameters .....	237
Request Body .....	238
Response Syntax .....	238
Response Elements .....	238
Errors .....	238
See Also .....	239
UpdateLinkAttributes .....	241
Request Syntax .....	241
URI Request Parameters .....	241
Request Body .....	242
Response Syntax .....	242
Response Elements .....	242
Errors .....	242
See Also .....	243
UpdateObjectAttributes .....	244
Request Syntax .....	244
URI Request Parameters .....	244
Request Body .....	244
Response Syntax .....	245
Response Elements .....	245
Errors .....	245
See Also .....	246
UpdateSchema .....	247
Request Syntax .....	247
URI Request Parameters .....	247
Request Body .....	247
Response Syntax .....	247
Response Elements .....	247
Errors .....	248
See Also .....	249
UpdateTypedLinkFacet .....	250
Request Syntax .....	250
URI Request Parameters .....	250
Request Body .....	250
Response Syntax .....	251
Response Elements .....	251
Errors .....	251
See Also .....	252
UpgradeAppliedSchema .....	254
Request Syntax .....	254
URI Request Parameters .....	254
Request Body .....	254
Response Syntax .....	254
Response Elements .....	255
Errors .....	255
See Also .....	256
UpgradePublishedSchema .....	257
Request Syntax .....	257
URI Request Parameters .....	257
Request Body .....	257
Response Syntax .....	258

Response Elements .....	258
Errors .....	258
See Also .....	259
Data Types .....	260
AttributeKey .....	263
Contents .....	263
See Also .....	263
AttributeKeyAndValue .....	264
Contents .....	264
See Also .....	264
AttributeNameAndValue .....	265
Contents .....	265
See Also .....	265
BatchAddFacetToObject .....	266
Contents .....	266
See Also .....	266
BatchAddFacetToObjectResponse .....	267
Contents .....	267
See Also .....	267
BatchAttachObject .....	268
Contents .....	268
See Also .....	268
BatchAttachObjectResponse .....	269
Contents .....	269
See Also .....	269
BatchAttachPolicy .....	270
Contents .....	270
See Also .....	270
BatchAttachPolicyResponse .....	271
Contents .....	271
See Also .....	271
BatchAttachToIndex .....	272
Contents .....	272
See Also .....	272
BatchAttachToIndexResponse .....	273
Contents .....	273
See Also .....	273
BatchAttachTypedLink .....	274
Contents .....	274
See Also .....	274
BatchAttachTypedLinkResponse .....	275
Contents .....	275
See Also .....	275
BatchCreateIndex .....	276
Contents .....	276
See Also .....	276
BatchCreateIndexResponse .....	278
Contents .....	278
See Also .....	278
BatchCreateObject .....	279
Contents .....	279
See Also .....	279
BatchCreateObjectResponse .....	281
Contents .....	281
See Also .....	281
BatchDeleteObject .....	282
Contents .....	282

See Also .....	282
BatchDeleteObjectResponse .....	283
Contents .....	283
See Also .....	283
BatchDetachFromIndex .....	284
Contents .....	284
See Also .....	284
BatchDetachFromIndexResponse .....	285
Contents .....	285
See Also .....	285
BatchDetachObject .....	286
Contents .....	286
See Also .....	286
BatchDetachObjectResponse .....	287
Contents .....	287
See Also .....	287
BatchDetachPolicy .....	288
Contents .....	288
See Also .....	288
BatchDetachPolicyResponse .....	289
Contents .....	289
See Also .....	289
BatchDetachTypedLink .....	290
Contents .....	290
See Also .....	290
BatchDetachTypedLinkResponse .....	291
Contents .....	291
See Also .....	291
BatchGetLinkAttributes .....	292
Contents .....	292
See Also .....	292
BatchGetLinkAttributesResponse .....	293
Contents .....	293
See Also .....	293
BatchGetObjectAttributes .....	294
Contents .....	294
See Also .....	294
BatchGetObjectAttributesResponse .....	295
Contents .....	295
See Also .....	295
BatchGetObjectInformation .....	296
Contents .....	296
See Also .....	296
BatchGetObjectInformationResponse .....	297
Contents .....	297
See Also .....	297
BatchListAttachedIndices .....	298
Contents .....	298
See Also .....	298
BatchListAttachedIndicesResponse .....	299
Contents .....	299
See Also .....	299
BatchListIncomingTypedLinks .....	300
Contents .....	300
See Also .....	300
BatchListIncomingTypedLinksResponse .....	302
Contents .....	302

See Also .....	302
BatchListIndex .....	303
Contents .....	303
See Also .....	303
BatchListIndexResponse .....	304
Contents .....	304
See Also .....	304
BatchListObjectAttributes .....	305
Contents .....	305
See Also .....	305
BatchListObjectAttributesResponse .....	306
Contents .....	306
See Also .....	306
BatchListObjectChildren .....	307
Contents .....	307
See Also .....	307
BatchListObjectChildrenResponse .....	308
Contents .....	308
See Also .....	308
BatchListObjectParentPaths .....	309
Contents .....	309
See Also .....	309
BatchListObjectParentPathsResponse .....	310
Contents .....	310
See Also .....	310
BatchListObjectParents .....	311
Contents .....	311
See Also .....	311
BatchListObjectParentsResponse .....	312
Contents .....	312
See Also .....	312
BatchListObjectPolicies .....	313
Contents .....	313
See Also .....	313
BatchListObjectPoliciesResponse .....	314
Contents .....	314
See Also .....	314
BatchListOutgoingTypedLinks .....	315
Contents .....	315
See Also .....	315
BatchListOutgoingTypedLinksResponse .....	317
Contents .....	317
See Also .....	317
BatchListPolicyAttachments .....	318
Contents .....	318
See Also .....	318
BatchListPolicyAttachmentsResponse .....	319
Contents .....	319
See Also .....	319
BatchLookupPolicy .....	320
Contents .....	320
See Also .....	320
BatchLookupPolicyResponse .....	321
Contents .....	321
See Also .....	321
BatchReadException .....	322
Contents .....	322

See Also .....	322
BatchReadOperation .....	323
Contents .....	323
See Also .....	324
BatchReadOperationResponse .....	326
Contents .....	326
See Also .....	326
BatchReadSuccessfulResponse .....	327
Contents .....	327
See Also .....	328
BatchRemoveFacetFromObject .....	330
Contents .....	330
See Also .....	330
BatchRemoveFacetFromObjectResponse .....	331
Contents .....	331
See Also .....	331
BatchUpdateLinkAttributes .....	332
Contents .....	332
See Also .....	332
BatchUpdateLinkAttributesResponse .....	333
Contents .....	333
See Also .....	333
BatchUpdateObjectAttributes .....	334
Contents .....	334
See Also .....	334
BatchUpdateObjectAttributesResponse .....	335
Contents .....	335
See Also .....	335
BatchWriteOperation .....	336
Contents .....	336
See Also .....	337
BatchWriteOperationResponse .....	339
Contents .....	339
See Also .....	340
Directory .....	342
Contents .....	342
See Also .....	342
Facet .....	343
Contents .....	343
See Also .....	343
FacetAttribute .....	344
Contents .....	344
See Also .....	344
FacetAttributeDefinition .....	345
Contents .....	345
See Also .....	345
FacetAttributeReference .....	346
Contents .....	346
See Also .....	346
FacetAttributeUpdate .....	347
Contents .....	347
See Also .....	347
IndexAttachment .....	348
Contents .....	348
See Also .....	348
LinkAttributeAction .....	349
Contents .....	349



See Also .....	349
LinkAttributeUpdate .....	350
Contents .....	350
See Also .....	350
ObjectAttributeAction .....	351
Contents .....	351
See Also .....	351
ObjectAttributeRange .....	352
Contents .....	352
See Also .....	352
ObjectAttributeUpdate .....	353
Contents .....	353
See Also .....	353
ObjectIdentifierAndLinkNameTuple .....	354
Contents .....	354
See Also .....	354
ObjectReference .....	355
Contents .....	355
See Also .....	355
PathToObjectIdentifiers .....	356
Contents .....	356
See Also .....	356
PolicyAttachment .....	357
Contents .....	357
See Also .....	357
PolicyToPath .....	358
Contents .....	358
See Also .....	358
Rule .....	359
Contents .....	359
See Also .....	359
SchemaFacet .....	360
Contents .....	360
See Also .....	360
Tag .....	361
Contents .....	361
See Also .....	361
TypedAttributeValue .....	362
Contents .....	362
See Also .....	362
TypedAttributeValueRange .....	363
Contents .....	363
See Also .....	363
TypedLinkAttributeDefinition .....	364
Contents .....	364
See Also .....	365
TypedLinkAttributeRange .....	366
Contents .....	366
See Also .....	366
TypedLinkFacet .....	367
Contents .....	367
See Also .....	367
TypedLinkFacetAttributeUpdate .....	368
Contents .....	368
See Also .....	368
TypedLinkSchemaAndFacetName .....	369
Contents .....	369

See Also .....	369
TypedLinkSpecifier .....	370
Contents .....	370
See Also .....	370
Arn Examples .....	371
Schema Arns .....	371
Directory Arns .....	372
CloudTrail Logging .....	373
Cloud Directory Information in CloudTrail .....	373
Understanding Cloud Directory Log File Entries .....	374
Common Parameters .....	377
Common Errors .....	379
Document History .....	381

# Welcome to the Amazon Cloud Directory API Reference

Amazon Cloud Directory is a highly scalable, high performance, multitenant directory service in the cloud. Its web-based directories make it easy for you to organize and manage application resources such as users, groups, locations, devices, policies, and the rich relationships between them. Cloud Directory is a foundational building block for developers to create directory-based solutions easily and without having to worry about deployment, global scale, availability, and performance.

With Cloud Directory, you can organize directory objects into multiple hierarchies to support multiple organizational pivots and relationships across directory information. For example, a directory of users could provide a hierarchical view based on reporting structure, location, and project affiliation. Similarly, a directory of devices might have multiple hierarchical views based on its manufacturer, current owner, and physical location. For more information, see [Amazon Cloud Directory](#) in the *AWS Directory Service Admin Guide*.

This guide describes the Cloud Directory operations that you can call programmatically and includes detailed information on data types and errors.

**Note**

AWS provides SDKs that consist of libraries and sample code for various programming languages and platforms (Java, Ruby, .Net, iOS, Android, etc.). The SDKs provide a convenient way to create programmatic access to AWS Directory Service and other AWS services. For more information about the AWS SDKs, including how to download and install them, see [Tools for Amazon Web Services](#).

# Actions

The following actions are supported:

- [AddFacetToObject](#) (p. 4)
- [ApplySchema](#) (p. 8)
- [AttachObject](#) (p. 12)
- [AttachPolicy](#) (p. 16)
- [AttachToIndex](#) (p. 19)
- [AttachTypedLink](#) (p. 23)
- [BatchRead](#) (p. 28)
- [BatchWrite](#) (p. 38)
- [CreateDirectory](#) (p. 46)
- [CreateFacet](#) (p. 50)
- [CreateIndex](#) (p. 54)
- [CreateObject](#) (p. 58)
- [CreateSchema](#) (p. 63)
- [CreateTypedLinkFacet](#) (p. 66)
- [DeleteDirectory](#) (p. 70)
- [DeleteFacet](#) (p. 73)
- [DeleteObject](#) (p. 76)
- [DeleteSchema](#) (p. 79)
- [DeleteTypedLinkFacet](#) (p. 82)
- [DetachFromIndex](#) (p. 85)
- [DetachObject](#) (p. 89)
- [DetachPolicy](#) (p. 93)
- [DetachTypedLink](#) (p. 96)
- [DisableDirectory](#) (p. 100)
- [EnableDirectory](#) (p. 103)
- [GetAppliedSchemaVersion](#) (p. 106)
- [GetDirectory](#) (p. 109)
- [GetFacet](#) (p. 112)
- [GetLinkAttributes](#) (p. 116)
- [GetObjectAttributes](#) (p. 120)
- [GetObjectInformation](#) (p. 124)
- [GetSchemaAsJson](#) (p. 128)
- [GetTypedLinkFacetInformation](#) (p. 132)
- [ListAppliedSchemaArns](#) (p. 136)
- [ListAttachedIndices](#) (p. 140)
- [ListDevelopmentSchemaArns](#) (p. 144)
- [ListDirectories](#) (p. 148)
- [ListFacetAttributes](#) (p. 152)
- [ListFacetNames](#) (p. 159)
- [ListIncomingTypedLinks](#) (p. 163)

- [ListIndex](#) (p. 169)
- [ListManagedSchemaArns](#) (p. 174)
- [ListObjectAttributes](#) (p. 177)
- [ListObjectChildren](#) (p. 182)
- [ListObjectParentPaths](#) (p. 186)
- [ListObjectParents](#) (p. 189)
- [ListObjectPolicies](#) (p. 193)
- [ListOutgoingTypedLinks](#) (p. 196)
- [ListPolicyAttachments](#) (p. 201)
- [ListPublishedSchemaArns](#) (p. 205)
- [ListTagsForResource](#) (p. 208)
- [ListTypedLinkFacetAttributes](#) (p. 211)
- [ListTypedLinkFacetNames](#) (p. 215)
- [LookupPolicy](#) (p. 218)
- [PublishSchema](#) (p. 222)
- [PutSchemaFromJson](#) (p. 225)
- [RemoveFacetFromObject](#) (p. 228)
- [TagResource](#) (p. 231)
- [UntagResource](#) (p. 234)
- [UpdateFacet](#) (p. 237)
- [UpdateLinkAttributes](#) (p. 241)
- [UpdateObjectAttributes](#) (p. 244)
- [UpdateSchema](#) (p. 247)
- [UpdateTypedLinkFacet](#) (p. 250)
- [UpgradeAppliedSchema](#) (p. 254)
- [UpgradePublishedSchema](#) (p. 257)

# AddFacetToObject

Adds a new [Facet \(p. 343\)](#) to an object. An object can have more than one facet applied on it.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/object/facets HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json
```

```
{
  "ObjectAttributeList": [
    {
      "Key": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ],
  "ObjectReference": {
    "Selector": "string"
  },
  "SchemaFacet": {
    "FacetName": "string",
    "SchemaArn": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [DirectoryArn \(p. 4\)](#)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#) where the object resides. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### [ObjectAttributeList \(p. 4\)](#)

Attributes on the facet that you are adding to the object.

Type: Array of [AttributeKeyAndValue \(p. 264\)](#) objects

Required: No

### ObjectReference (p. 4)

A reference to the object you are adding the specified facet to.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### SchemaFacet (p. 4)

Identifiers for the facet that you are adding to the object. See [SchemaFacet \(p. 360\)](#) for details.

Type: [SchemaFacet \(p. 360\)](#) object

Required: Yes

## Response Syntax

`HTTP/1.1 200`

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### FacetValidationException

The [Facet \(p. 343\)](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

### InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

### RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/object/facets HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 232
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=2cf0b34e6e7305c27f7ec762255196d937ef036d0e665e452a0e1bd79ae25106
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
X-Amz-Date: 20171009T164125Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ObjectReference": {
    "Selector": "$AQGG_ADlfNZBzYHY_JgDt3TWmspn1fxfQmSQaaVKSbvEiQ"
  },
  "SchemaFacet": {
    "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY/schema/org/1",
    "FacetName": "node1"
  }
}
```

### Example Response

```
HTTP/1.1 200 OK
```



```
x-amzn-RequestId: b21ee371-ad10-11e7-9e13-5b6a00750e59  
Date: Mon, 09 Oct 2017 16:41:26 GMT  
x-amzn-RequestId: b21ee371-ad10-11e7-9e13-5b6a00750e59  
Content-Type: application/json  
Content-Length: 2
```

```
{}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ApplySchema

Copies the input published schema, at the specified version, into the [Directory \(p. 342\)](#) with the same name and version as that of the published schema.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema/apply HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "PublishedSchemaArn": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### DirectoryArn (p. 8)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#) into which the schema is copied. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### PublishedSchemaArn (p. 8)

Published schema Amazon Resource Name (ARN) that needs to be copied. For more information, see [Arn Examples \(p. 371\)](#).

Type: String

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AppliedSchemaArn": "string",
  "DirectoryArn": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **AppliedSchemaArn (p. 8)**

The applied schema ARN that is associated with the copied schema in the [Directory \(p. 342\)](#). You can use this ARN to describe the schema information applied on this directory. For more information, see [Arn Examples \(p. 371\)](#).

Type: String

### **DirectoryArn (p. 8)**

The ARN that is associated with the [Directory \(p. 342\)](#). For more information, see [Arn Examples \(p. 371\)](#).

Type: String

## **Errors**

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidAttachmentException**

Indicates that an attempt to make an attachment was invalid. For example, attaching two nodes with a link type that is not applicable to the nodes or attempting to apply a schema to a directory a second time.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have

time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

#### **SchemaAlreadyExistsException**

Indicates that a schema could not be created due to a naming conflict. Please select a different name and then try again.

HTTP Status Code: 400

#### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/schema/apply HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 94
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171003/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=ac58e3d2d25b85cd1869f7a845a0e97cebfce28d15e8f8df34c0ee89a197f042
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AfMr4qym1kZTvwqOafAYfqI
X-Amz-Date: 20171003T201513Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "PublishedSchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:schema/published/
org/1"
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 90d60895-a877-11e7-81c0-7b48a7696e76
Date: Tue, 03 Oct 2017 20:15:13 GMT
x-amzn-RequestId: 90d60895-a877-11e7-81c0-7b48a7696e76
Content-Type: application/json
Content-Length: 212

{
  "AppliedSchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AfMr4qym1kZTvwqOafAYfqI/schema/org/1",
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AfMr4qym1kZTvwqOafAYfqI"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# AttachObject

Attaches an existing object to another object. An object can be accessed in two ways:

1. Using the path
2. Using `ObjectIdentifier`

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/object/attach HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "ChildReference": {
    "Selector": "string"
  },
  "LinkName": "string",
  "ParentReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [DirectoryArn \(p. 12\)](#)

Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#) where both objects reside. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### [ChildReference \(p. 12\)](#)

The child object reference to be attached to the object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### [LinkName \(p. 12\)](#)

The link name with which the child object is attached to the parent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[^\[\]\(\):\\{\}\#\@!\?\s\\;]+`

Required: Yes

### ParentReference (p. 12)

The parent object reference.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AttachedObjectIdentifier": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### AttachedObjectIdentifier (p. 13)

The attached `ObjectIdentifier`, which is the child `ObjectIdentifier`.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### FacetValidationException

The [Facet \(p. 343\)](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

### InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

**InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

**InvalidAttachmentException**

Indicates that an attempt to make an attachment was invalid. For example, attaching two nodes with a link type that is not applicable to the nodes or attempting to apply a schema to a directory a second time.

HTTP Status Code: 400

**LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

**LinkNameAlreadyInUseException**

Indicates that a link could not be created due to a naming conflict. Choose a different name and then try again.

HTTP Status Code: 400

**ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/object/attach HTTP/1.1
```



```
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 188
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171003/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=2ce97afc4ac4d1fd4826861fa366d6d8674d1399b1a666e59cc53b8310aacf6a
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mAO3dNY
X-Amz-Date: 20171003T195605Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ParentReference": {
    "Selector": "$AQGG_ADlfNZBzYHY_JgDt3TWcU7IARvOTear09zme1sVsw"
  },
  "LinkName": "link2",
  "ChildReference": {
    "Selector": "$AQGG_ADlfNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
  }
}
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: e4be5146-a874-11e7-a169-c5bf0acd39f4
Date: Tue, 03 Oct 2017 19:56:06 GMT
x-amzn-RequestId: e4be5146-a874-11e7-a169-c5bf0acd39f4
Content-Type: application/json
Content-Length: 77

{
  "AttachedObjectIdentifier": "AQGG_ADlfNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# AttachPolicy

Attaches a policy object to a regular object. An object can have a limited number of attached policies.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/policy/attach HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "ObjectReference": {
    "Selector": "string"
  },
  "PolicyReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### DirectoryArn (p. 16)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#) where both objects reside. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### ObjectReference (p. 16)

The reference that identifies the object to which the policy will be attached.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### PolicyReference (p. 16)

The reference that is associated with the policy object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **NotPolicyException**

Indicates that the requested operation can only operate on policy objects.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/policy/attach HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 168
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
cloudirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=d6ba55fbae53295150b69a92946e542ad08f7557492c5862d70d6a8c62fa24b0
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
X-Amz-Date: 20171017T185436Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "PolicyReference": {
    "Selector": "$AQGG_ADlfNZBzYHY_JgDt3TWgcBsTVmcQEWS6jlygfhuew"
  },
  "ObjectReference": {
    "Selector": "$AQGG_ADlfNZBzYHY_JgDt3TWQoovm1s3Ts2v0NKrzdVnPw"
  }
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 9ff9d709-b36c-11e7-843e-9fad359f817f
Date: Tue, 17 Oct 2017 18:54:37 GMT
x-amzn-RequestId: 9ff9d709-b36c-11e7-843e-9fad359f817f
Content-Type: application/json
Content-Length: 2

{}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# AttachToIndex

Attaches the specified object to the specified index.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/index/attach HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "IndexReference": {
    "Selector": "string"
  },
  "TargetReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [DirectoryArn \(p. 19\)](#)

The Amazon Resource Name (ARN) of the directory where the object and index exist.

## Request Body

The request accepts the following data in JSON format.

### [IndexReference \(p. 19\)](#)

A reference to the index that you are attaching the object to.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### [TargetReference \(p. 19\)](#)

A reference to the object that you are attaching to the index.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AttachedObjectIdentifier": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **AttachedObjectIdentifier** (p. 19)

The `ObjectIdentifier` of the object that was attached to the index.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **IndexedAttributeMissingException**

An object has been attempted to be attached to an object that does not have the appropriate attribute value.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidAttachmentException**

Indicates that an attempt to make an attachment was invalid. For example, attaching two nodes with a link type that is not applicable to the nodes or attempting to apply a schema to a directory a second time.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **LinkNameAlreadyInUseException**

Indicates that a link could not be created due to a naming conflict. Choose a different name and then try again.

HTTP Status Code: 400

### **NotIndexException**

Indicates that the requested operation can only operate on index objects.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.

### **Example Request**

```
PUT /amazonclouddirectory/2017-01-11/index/attach HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 167
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170927/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=78d785ce666b33aa8624c62c59be1dca60c49062f91eb216909450ea214c5a56
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
X-Amz-Date: 20170927T171118Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "IndexReference": {
    "Selector": "$AQGG_ADlfnZBzYHY_JgDt3TW45F26R1HTY2z-stwKBte_Q"
  },
  "TargetReference": {
    "Selector": "$AQGG_ADlfnZBzYHY_JgDt3TWcU7IARvOTeaR09zme1sVsw"
  }
}
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: e1458e29-a3a6-11e7-a169-c5bf0acd39f4
Date: Wed, 27 Sep 2017 17:11:18 GMT
x-amzn-RequestId: e1458e29-a3a6-11e7-a169-c5bf0acd39f4
Content-Type: application/json
Content-Length: 77

{
  "AttachedObjectIdentifier": "AQGG_ADlfNZBzYHY_JgDt3TWcU7IARvOTeaR09zmelsVsw"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)



# AttachTypedLink

Attaches a typed link to a specified source and target object. For more information, see [Typed Links](#).

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/typedlink/attach HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "Attributes": [
    {
      "AttributeName": "string",
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ],
  "SourceObjectReference": {
    "Selector": "string"
  },
  "TargetObjectReference": {
    "Selector": "string"
  },
  "TypedLinkFacet": {
    "SchemaArn": "string",
    "TypedLinkName": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### DirectoryArn (p. 23)

The Amazon Resource Name (ARN) of the directory where you want to attach the typed link.

## Request Body

The request accepts the following data in JSON format.

### Attributes (p. 23)

A set of attributes that are associated with the typed link.

Type: Array of [AttributeNameAndValue \(p. 265\)](#) objects

Required: Yes

### SourceObjectReference (p. 23)

Identifies the source object that the typed link will attach to.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

#### **TargetObjectReference (p. 23)**

Identifies the target object that the typed link will attach to.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

#### **TypedLinkFacet (p. 23)**

Identifies the typed link facet that is associated with the typed link.

Type: [TypedLinkSchemaAndFacetName \(p. 369\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "TypedLinkSpecifier": {
    "IdentityAttributeValues": [
      {
        "AttributeName": "string",
        "Value": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    ],
    "SourceObjectReference": {
      "Selector": "string"
    },
    "TargetObjectReference": {
      "Selector": "string"
    },
    "TypedLinkFacet": {
      "SchemaArn": "string",
      "TypedLinkName": "string"
    }
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

#### **TypedLinkSpecifier (p. 24)**

Returns a typed link specifier as output.

Type: [TypedLinkSpecifier](#) (p. 370) object

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **FacetValidationException**

The [Facet](#) (p. 343) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidAttachmentException**

Indicates that an attempt to make an attachment was invalid. For example, attaching two nodes with a link type that is not applicable to the nodes or attempting to apply a schema to a directory a second time.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have

time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

#### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

#### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/typedlink/attach HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 422
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170928/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=d1b63e72fd13cafb5af77d621891a58849c146c2654d046366d420527a659b48
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
X-Amz-Date: 20170928T003543Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "SourceObjectReference": {
    "Selector": "$AQGG_ADlfNZBzYHY_JgDt3TWSvfueNdqTdmeCuTs6YBNUA"
  },
  "Attributes": [{
    "AttributeName": "22",
    "Value": {
      "BinaryValue": "c3Ry"
    }
  }],
  "TargetObjectReference": {
    "Selector": "$AQGG_ADlfNZBzYHY_JgDt3TWcU7IARvOTear09zme1sVsw"
  },
  "TypedLinkFacet": {
    "TypedLinkName": "exampletypedlink8",
    "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY/schema/org/1"
  }
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 28 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
```

Content-Type: application/json  
Content-Length: 521

```
{
  "TypedLinkSpecifier": {
    "IdentityAttributeValues": [{
      "AttributeName": "22",
      "Value": {
        "BinaryValue": "c3Ry",
        "BooleanValue": null,
        "DatetimeValue": null,
        "NumberValue": null,
        "StringValue": null
      }
    }],
    "SourceObjectReference": {
      "Selector": "$AQGG_ADlfnZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
    },
    "TargetObjectReference": {
      "Selector": "$AQGG_ADlfnZBzYHY_JgDt3TWcU7IARvOTeaR09zme1sVsw"
    },
    "TypedLinkFacet": {
      "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/AYb8AOV81kHNgdj8mA03dNY/schema/org/1",
      "TypedLinkName": "exampletypedlink8"
    }
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# BatchRead

Performs all the read operations in a batch.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/batchread HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json
```

```
{
  "Operations": [
    {
      "GetLinkAttributes": {
        "AttributeNames": [ "string" ],
        "TypedLinkSpecifier": {
          "IdentityAttributeValues": [
            {
              "AttributeName": "string",
              "Value": {
                "BinaryValue": blob,
                "BooleanValue": boolean,
                "DatetimeValue": number,
                "NumberValue": "string",
                "StringValue": "string"
              }
            }
          ]
        },
        "SourceObjectReference": {
          "Selector": "string"
        },
        "TargetObjectReference": {
          "Selector": "string"
        },
        "TypedLinkFacet": {
          "SchemaArn": "string",
          "TypedLinkName": "string"
        }
      },
      "GetObjectAttributes": {
        "AttributeNames": [ "string" ],
        "ObjectReference": {
          "Selector": "string"
        },
        "SchemaFacet": {
          "FacetName": "string",
          "SchemaArn": "string"
        }
      },
      "GetObjectInformation": {
        "ObjectReference": {
          "Selector": "string"
        }
      },
      "ListAttachedIndices": {
        "MaxResults": number,
        "NextToken": "string",
        "TargetReference": {
          "Selector": "string"
        }
      }
    },
  ],
}
```

```

"ListIncomingTypedLinks": {
  "FilterAttributeRanges": [
    {
      "AttributeName": "string",
      "Range": {
        "EndMode": "string",
        "EndValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "StartMode": "string",
        "StartValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    }
  ],
  "FilterTypedLink": {
    "SchemaArn": "string",
    "TypedLinkName": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
},
"ListIndex": {
  "IndexReference": {
    "Selector": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "RangesOnIndexedValues": [
    {
      "AttributeKey": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Range": {
        "EndMode": "string",
        "EndValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "StartMode": "string",
        "StartValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    }
  ]
}

```

```

    ],
    "ListObjectAttributes": {
        "FacetFilter": {
            "FacetName": "string",
            "SchemaArn": "string"
        },
        "MaxResults": number,
        "NextToken": "string",
        "ObjectReference": {
            "Selector": "string"
        }
    },
    "ListObjectChildren": {
        "MaxResults": number,
        "NextToken": "string",
        "ObjectReference": {
            "Selector": "string"
        }
    },
    "ListObjectParentPaths": {
        "MaxResults": number,
        "NextToken": "string",
        "ObjectReference": {
            "Selector": "string"
        }
    },
    "ListObjectParents": {
        "MaxResults": number,
        "NextToken": "string",
        "ObjectReference": {
            "Selector": "string"
        }
    },
    "ListObjectPolicies": {
        "MaxResults": number,
        "NextToken": "string",
        "ObjectReference": {
            "Selector": "string"
        }
    },
    "ListOutgoingTypedLinks": {
        "FilterAttributeRanges": [
            {
                "AttributeName": "string",
                "Range": {
                    "EndMode": "string",
                    "EndValue": {
                        "BinaryValue": blob,
                        "BooleanValue": boolean,
                        "DatetimeValue": number,
                        "NumberValue": "string",
                        "StringValue": "string"
                    },
                    "StartMode": "string",
                    "StartValue": {
                        "BinaryValue": blob,
                        "BooleanValue": boolean,
                        "DatetimeValue": number,
                        "NumberValue": "string",
                        "StringValue": "string"
                    }
                }
            }
        ]
    },
    "FilterTypedLink": {

```



```
        "SchemaArn": "string",
        "TypedLinkName": "string"
      },
      "MaxResults": number,
      "NextToken": "string",
      "ObjectReference": {
        "Selector": "string"
      }
    },
    "ListPolicyAttachments": {
      "MaxResults": number,
      "NextToken": "string",
      "PolicyReference": {
        "Selector": "string"
      }
    },
    "LookupPolicy": {
      "MaxResults": number,
      "NextToken": "string",
      "ObjectReference": {
        "Selector": "string"
      }
    }
  }
}
]
```

## URI Request Parameters

The request requires the following URI parameters.

### ConsistencyLevel (p. 28)

Represents the manner and timing in which the successful write or update of an object is reflected in a subsequent read operation of that same object.

Valid Values: `SERIALIZABLE` | `EVENTUAL`

### DirectoryArn (p. 28)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#). For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### Operations (p. 28)

A list of operations that are part of the batch.

Type: Array of [BatchReadOperation \(p. 323\)](#) objects

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Responses": [
    {
      "ExceptionResponse": {
        "Message": "string",
        "Type": "string"
      },
      "SuccessfulResponse": {
        "GetLinkAttributes": {
          "Attributes": [
            {
              "Key": {
                "FacetName": "string",
                "Name": "string",
                "SchemaArn": "string"
              },
              "Value": {
                "BinaryValue": blob,
                "BooleanValue": boolean,
                "DatetimeValue": number,
                "NumberValue": "string",
                "StringValue": "string"
              }
            }
          ]
        },
        "GetObjectAttributes": {
          "Attributes": [
            {
              "Key": {
                "FacetName": "string",
                "Name": "string",
                "SchemaArn": "string"
              },
              "Value": {
                "BinaryValue": blob,
                "BooleanValue": boolean,
                "DatetimeValue": number,
                "NumberValue": "string",
                "StringValue": "string"
              }
            }
          ]
        },
        "GetObjectInformation": {
          "ObjectIdentifier": "string",
          "SchemaFacets": [
            {
              "FacetName": "string",
              "SchemaArn": "string"
            }
          ]
        },
        "ListAttachedIndices": {
          "IndexAttachments": [
            {
              "IndexedAttributes": [
                {
                  "Key": {
                    "FacetName": "string",
                    "Name": "string",
                    "SchemaArn": "string"
                  },
                  "Value": {
                    "BinaryValue": blob,
```

```

        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
    }
}
],
"ObjectIdentifier": "string"
}
],
"NextToken": "string"
},
"ListIncomingTypedLinks": {
    "LinkSpecifiers": [
        {
            "IdentityAttributeValues": [
                {
                    "AttributeName": "string",
                    "Value": {
                        "BinaryValue": blob,
                        "BooleanValue": boolean,
                        "DatetimeValue": number,
                        "NumberValue": "string",
                        "StringValue": "string"
                    }
                }
            ],
            "SourceObjectReference": {
                "Selector": "string"
            },
            "TargetObjectReference": {
                "Selector": "string"
            },
            "TypedLinkFacet": {
                "SchemaArn": "string",
                "TypedLinkName": "string"
            }
        }
    ],
    "NextToken": "string"
},
"ListIndex": {
    "IndexAttachments": [
        {
            "IndexedAttributes": [
                {
                    "Key": {
                        "FacetName": "string",
                        "Name": "string",
                        "SchemaArn": "string"
                    },
                    "Value": {
                        "BinaryValue": blob,
                        "BooleanValue": boolean,
                        "DatetimeValue": number,
                        "NumberValue": "string",
                        "StringValue": "string"
                    }
                }
            ],
            "ObjectIdentifier": "string"
        }
    ],
    "NextToken": "string"
},
"ListObjectAttributes": {

```

```

"Attributes": [
  {
    "Key": {
      "FacetName": "string",
      "Name": "string",
      "SchemaArn": "string"
    },
    "Value": {
      "BinaryValue": blob,
      "BooleanValue": boolean,
      "DatetimeValue": number,
      "NumberValue": "string",
      "StringValue": "string"
    }
  }
],
"NextToken": "string"
},
"ListObjectChildren": {
  "Children": {
    "string": "string"
  },
  "NextToken": "string"
},
"ListObjectParentPaths": {
  "NextToken": "string",
  "PathToObjectIdentifiersList": [
    {
      "ObjectIdentifiers": [ "string" ],
      "Path": "string"
    }
  ]
},
"ListObjectParents": {
  "NextToken": "string",
  "ParentLinks": [
    {
      "LinkName": "string",
      "ObjectIdentifier": "string"
    }
  ]
},
"ListObjectPolicies": {
  "AttachedPolicyIds": [ "string" ],
  "NextToken": "string"
},
"ListOutgoingTypedLinks": {
  "NextToken": "string",
  "TypedLinkSpecifiers": [
    {
      "IdentityAttributeValues": [
        {
          "AttributeName": "string",
          "Value": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          }
        }
      ]
    }
  ],
  "SourceObjectReference": {
    "Selector": "string"
  },
  "TargetObjectReference": {

```

```
        "Selector": "string"
      },
      "TypedLinkFacet": {
        "SchemaArn": "string",
        "TypedLinkName": "string"
      }
    ]
  },
  "ListPolicyAttachments": {
    "NextToken": "string",
    "ObjectIdentifiers": [ "string " ]
  },
  "LookupPolicy": {
    "NextToken": "string",
    "PolicyToPathList": [
      {
        "Path": "string",
        "Policies": [
          {
            "ObjectIdentifier": "string",
            "PolicyId": "string",
            "PolicyType": "string"
          }
        ]
      }
    ]
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## Responses (p. 31)

A list of all the responses for each batch read.

Type: Array of [BatchReadOperationResponse](#) (p. 326) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

## AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

## DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.

### **Example Request**

```
POST /amazonclouddirectory/2017-01-11/batchread HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 18
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
x-amz-consistency-level: EVENTUAL
X-Amz-Date: 20170922T233414Z
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170922/
us-west-2/clouddirectory/aws4_request, SignedHeaders=host;x-
amz-consistency-level;x-amz-data-partition;x-amz-date,
Signature=dcf33d791a3f742d04edde6107c4795918d7e034c32f0029a49c95a9fe79cd40

{
  "Operations": [ ]
}
```

### **Example Response**

```
HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 22 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521

{
  "Responses": [ ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# BatchWrite

Performs all the write operations in a batch. Either all the operations succeed or none.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/batchwrite HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json
```

```
{
  "Operations": [
    {
      "AddFacetToObject": {
        "ObjectAttributeList": [
          {
            "Key": {
              "FacetName": "string",
              "Name": "string",
              "SchemaArn": "string"
            },
            "Value": {
              "BinaryValue": blob,
              "BooleanValue": boolean,
              "DatetimeValue": number,
              "NumberValue": "string",
              "StringValue": "string"
            }
          }
        ],
        "ObjectReference": {
          "Selector": "string"
        },
        "SchemaFacet": {
          "FacetName": "string",
          "SchemaArn": "string"
        }
      },
      "AttachObject": {
        "ChildReference": {
          "Selector": "string"
        },
        "LinkName": "string",
        "ParentReference": {
          "Selector": "string"
        }
      },
      "AttachPolicy": {
        "ObjectReference": {
          "Selector": "string"
        },
        "PolicyReference": {
          "Selector": "string"
        }
      },
      "AttachToIndex": {
        "IndexReference": {
          "Selector": "string"
        },
        "TargetReference": {
          "Selector": "string"
        }
      }
    },
  ],
}
```



```

"AttachTypedLink": {
  "Attributes": [
    {
      "AttributeName": "string",
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ],
  "SourceObjectReference": {
    "Selector": "string"
  },
  "TargetObjectReference": {
    "Selector": "string"
  },
  "TypedLinkFacet": {
    "SchemaArn": "string",
    "TypedLinkName": "string"
  }
},
"CreateIndex": {
  "BatchReferenceName": "string",
  "IsUnique": boolean,
  "LinkName": "string",
  "OrderedIndexedAttributeList": [
    {
      "FacetName": "string",
      "Name": "string",
      "SchemaArn": "string"
    }
  ],
  "ParentReference": {
    "Selector": "string"
  }
},
"CreateObject": {
  "BatchReferenceName": "string",
  "LinkName": "string",
  "ObjectAttributeList": [
    {
      "Key": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ],
  "ParentReference": {
    "Selector": "string"
  },
  "SchemaFacet": [
    {
      "FacetName": "string",
      "SchemaArn": "string"
    }
  ]
}

```

```

    ],
  },
  "DeleteObject": {
    "ObjectReference": {
      "Selector": "string"
    }
  },
  "DetachFromIndex": {
    "IndexReference": {
      "Selector": "string"
    },
    "TargetReference": {
      "Selector": "string"
    }
  },
  "DetachObject": {
    "BatchReferenceName": "string",
    "LinkName": "string",
    "ParentReference": {
      "Selector": "string"
    }
  },
  "DetachPolicy": {
    "ObjectReference": {
      "Selector": "string"
    },
    "PolicyReference": {
      "Selector": "string"
    }
  },
  "DetachTypedLink": {
    "TypedLinkSpecifier": {
      "IdentityAttributeValues": [
        {
          "AttributeName": "string",
          "Value": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          }
        }
      ],
      "SourceObjectReference": {
        "Selector": "string"
      },
      "TargetObjectReference": {
        "Selector": "string"
      },
      "TypedLinkFacet": {
        "SchemaArn": "string",
        "TypedLinkName": "string"
      }
    }
  },
  "RemoveFacetFromObject": {
    "ObjectReference": {
      "Selector": "string"
    },
    "SchemaFacet": {
      "FacetName": "string",
      "SchemaArn": "string"
    }
  },
  "UpdateLinkAttributes": {

```

```

"AttributeUpdates": [
  {
    "AttributeAction": {
      "AttributeActionType": "string",
      "AttributeUpdateValue": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    },
    "AttributeKey": {
      "FacetName": "string",
      "Name": "string",
      "SchemaArn": "string"
    }
  }
],
"TypedLinkSpecifier": {
  "IdentityAttributeValues": [
    {
      "AttributeName": "string",
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ],
  "SourceObjectReference": {
    "Selector": "string"
  },
  "TargetObjectReference": {
    "Selector": "string"
  },
  "TypedLinkFacet": {
    "SchemaArn": "string",
    "TypedLinkName": "string"
  }
},
"UpdateObjectAttributes": {
  "AttributeUpdates": [
    {
      "ObjectAttributeAction": {
        "ObjectAttributeActionType": "string",
        "ObjectAttributeUpdateValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      },
      "ObjectAttributeKey": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      }
    }
  ],
  "ObjectReference": {
    "Selector": "string"
  }
}

```

```
}
  }
}
]
```

## URI Request Parameters

The request requires the following URI parameters.

### DirectoryArn (p. 38)

The Amazon Resource Name (ARN) that is associated with the [Directory](#) (p. 342). For more information, see [Arn Examples](#) (p. 371).

## Request Body

The request accepts the following data in JSON format.

### Operations (p. 38)

A list of operations that are part of the batch.

Type: Array of [BatchWriteOperation](#) (p. 336) objects

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Responses": [
    {
      "AddFacetToObject": {
      },
      "AttachObject": {
        "attachedObjectIdentifier": "string"
      },
      "AttachPolicy": {
      },
      "AttachToIndex": {
        "AttachedObjectIdentifier": "string"
      },
      "AttachTypedLink": {
        "TypedLinkSpecifier": {
          "IdentityAttributeValues": [
            {
              "AttributeName": "string",
              "Value": {
                "BinaryValue": blob,
                "BooleanValue": boolean,
                "DatetimeValue": number,
                "NumberValue": "string",
                "StringValue": "string"
              }
            }
          ]
        }
      }
    ]
  }
```

```

        "SourceObjectReference": {
            "Selector": "string"
        },
        "TargetObjectReference": {
            "Selector": "string"
        },
        "TypedLinkFacet": {
            "SchemaArn": "string",
            "TypedLinkName": "string"
        }
    },
    "CreateIndex": {
        "ObjectIdentifier": "string"
    },
    "CreateObject": {
        "ObjectIdentifier": "string"
    },
    "DeleteObject": {
    },
    "DetachFromIndex": {
        "DetachedObjectIdentifier": "string"
    },
    "DetachObject": {
        "detachedObjectIdentifier": "string"
    },
    "DetachPolicy": {
    },
    "DetachTypedLink": {
    },
    "RemoveFacetFromObject": {
    },
    "UpdateLinkAttributes": {
    },
    "UpdateObjectAttributes": {
        "ObjectIdentifier": "string"
    }
}
]
}

```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Responses (p. 42)

A list of all the responses for each batch write.

Type: Array of [BatchWriteOperationResponse \(p. 339\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

#### **BatchWriteException**

A BatchWrite exception has occurred.

HTTP Status Code: 400

#### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

#### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

#### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

#### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

#### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

#### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/batchwrite HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 18
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170922/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=e539506cd67ac7a753fa37aa58272f4c7bda369fc0f6b4f7bff6bea0f0fcd4af
```

```
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
X-Amz-Date: 20170922T232444Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Operations": []
}
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 22 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521

{
  "Responses": []
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# CreateDirectory

Creates a [Directory](#) (p. 342) by copying the published schema into the directory. A directory cannot be created without a schema.

You can also quickly create a directory using a managed schema, called the `QuickStartSchema`. For more information, see [Managed Schema](#) in the *Amazon Cloud Directory Developer Guide*.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/directory/create HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "Name": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [SchemaArn](#) (p. 46)

The Amazon Resource Name (ARN) of the published schema that will be copied into the data [Directory](#) (p. 342). For more information, see [Arn Examples](#) (p. 371).

## Request Body

The request accepts the following data in JSON format.

### [Name](#) (p. 46)

The name of the [Directory](#) (p. 342). Should be unique per account, per region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AppliedSchemaArn": "string",
  "DirectoryArn": "string",
  "Name": "string",
  "ObjectIdentifier": "string"
}
```



## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **AppliedSchemaArn (p. 46)**

The ARN of the published schema in the [Directory \(p. 342\)](#). Once a published schema is copied into the directory, it has its own ARN, which is referred to as applied schema ARN. For more information, see [Arn Examples \(p. 371\)](#).

Type: String

### **DirectoryArn (p. 46)**

The ARN that is associated with the [Directory \(p. 342\)](#). For more information, see [Arn Examples \(p. 371\)](#).

Type: String

### **Name (p. 46)**

The name of the [Directory \(p. 342\)](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9.\_]*$`

### **ObjectIdentifier (p. 46)**

The root object node of the created directory.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **DirectoryAlreadyExistsException**

Indicates that a [Directory \(p. 342\)](#) could not be created due to a naming conflict. Choose a different name and try again.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.

### **Example Request**

```
PUT /amazonclouddirectory/2017-01-11/directory/create HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 22
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170922/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=f347d3f8d6ceccbfd47738ab11fe0194b5efd329b4e0431f7221ee80c672fd9a
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:schema/published/
person/1
X-Amz-Date: 20170922T220642Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Name": "ExampleCD"
}
```

### **Example Response**

```
HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 22 Sep 2017 00:35:44 GMT
```

```
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521

{
  "AppliedSchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AfMr4qym1kZTvwqOafAYfqi/schema/person/1",
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AfMr4qym1kZTvwqOafAYfqi",
  "Name": "ExampleCD",
  "ObjectIdentifier": "AQHzK-KsptZGU78KjmnwGH6i-4guCM3uQFOTA9_NjeHDrq"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# CreateFacet

Creates a new [Facet](#) (p. 343) in a schema. Facet creation is allowed only in development or applied schemas.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/facet/create HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json
```

```
{
  "Attributes": [
    {
      "AttributeDefinition": {
        "DefaultValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "IsImmutable": boolean,
        "Rules": {
          "string" : {
            "Parameters": {
              "string" : "string"
            },
            "Type": "string"
          }
        },
        "Type": "string"
      },
      "AttributeReference": {
        "TargetAttributeName": "string",
        "TargetFacetName": "string"
      },
      "Name": "string",
      "RequiredBehavior": "string"
    }
  ],
  "FacetStyle": "string",
  "Name": "string",
  "ObjectType": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### SchemaArn (p. 50)

The schema ARN in which the new [Facet](#) (p. 343) will be created. For more information, see [Arn Examples](#) (p. 371).

## Request Body

The request accepts the following data in JSON format.

### Attributes (p. 50)

The attributes that are associated with the [Facet \(p. 343\)](#).

Type: Array of [FacetAttribute \(p. 344\)](#) objects

Required: No

### FacetStyle (p. 50)

There are two different styles that you can define on any given facet, `Static` and `Dynamic`. For static facets, all attributes must be defined in the schema. For dynamic facets, attributes can be defined during data plane operations.

Type: String

Valid Values: `STATIC` | `DYNAMIC`

Required: No

### Name (p. 50)

The name of the [Facet \(p. 343\)](#), which is unique for a given schema.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

### ObjectType (p. 50)

Specifies whether a given object created from this facet is of type node, leaf node, policy or index.

- Node: Can have multiple children but one parent.
- Leaf node: Cannot have children but can have multiple parents.
- Policy: Allows you to store a policy document and policy type. For more information, see [Policies](#).
- Index: Can be created with the Index API.

Type: String

Valid Values: `NODE` | `LEAF_NODE` | `POLICY` | `INDEX`

Required: No

## Response Syntax

`HTTP/1.1 200`

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **FacetAlreadyExistsException**

A facet with the same name already exists.

HTTP Status Code: 400

### **FacetValidationException**

The [Facet](#) (p. 343) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidRuleException**

Occurs when any of the rule parameter keys or values are invalid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/facet/create HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 39
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170922/us-west-2/
cloudirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=d6b41d921e64be7413abf9bd9036289cb34ace20275ed17dee45e594622ced4b
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY/schema/org/1
X-Amz-Date: 20170922T214008Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Name": "node1",
  "ObjectType": "NODE"
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 22 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521

{}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# CreateIndex

Creates an index object. See [Indexing and search](#) for more information.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/index HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "IsUnique": boolean,
  "LinkName": "string",
  "OrderedIndexedAttributeList": [
    {
      "FacetName": "string",
      "Name": "string",
      "SchemaArn": "string"
    }
  ],
  "ParentReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [DirectoryArn \(p. 54\)](#)

The ARN of the directory where the index should be created.

## Request Body

The request accepts the following data in JSON format.

### [IsUnique \(p. 54\)](#)

Indicates whether the attribute that is being indexed has unique values or not.

Type: Boolean

Required: Yes

### [LinkName \(p. 54\)](#)

The name of the link between the parent object and the index object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[^\\/[\\]\\(\\):\\{\\}#@!?!\\s\\;]+`

Required: No



### **OrderedIndexedAttributeList (p. 54)**

Specifies the attributes that should be indexed on. Currently only a single attribute is supported.

Type: Array of [AttributeKey \(p. 263\)](#) objects

Required: Yes

### **ParentReference (p. 54)**

A reference to the parent object that contains the index object.

Type: [ObjectReference \(p. 355\)](#) object

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ObjectIdentifier": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **ObjectIdentifier (p. 55)**

The `ObjectIdentifier` of the index created by this operation.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **FacetValidationException**

The [Facet \(p. 343\)](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

**InternalServerErrorException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

**InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

**LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

**LinkNameAlreadyInUseException**

Indicates that a link could not be created due to a naming conflict. Choose a different name and then try again.

HTTP Status Code: 400

**ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**UnsupportedIndexTypeException**

Indicates that the requested index type is not supported.

HTTP Status Code: 400

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/index HTTP/1.1
```

```
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 290
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170913/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=dc93fb34cd655e125aa748b8747d99bef78c7c5785e30327cf151d74accbbcf0
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDxvdgkOWktRXV4HnRa8
X-Amz-Date: 20170913T012153Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ParentReference":{
    "Selector":"/"
  },
  "OrderedIndexedAttributeList":[
    {
      "SchemaArn":"arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDxvdgkOWktRXV4HnRa8/schema/Examplepersonschema/1",
      "FacetName":"Organization_Person",
      "Name":"manager"
    }
  ],
  "IsUnique":true,
  "LinkName":"Examplelink"
}
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 13 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521

{
  "ObjectIdentifier":"AQF0Fw173YJDlpLUV1eB50Wv4vU99HjyQIShCCUeVob2fw"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# CreateObject

Creates an object in a [Directory](#) (p. 342). Additionally attaches the object to a parent, if a parent reference and `LinkName` is specified. An object is simply a collection of [Facet](#) (p. 343) attributes. You can also use this API call to create a policy object, if the facet from which you create the object is a policy facet.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/object HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json
```

```
{
  "LinkName": "string",
  "ObjectAttributeList": [
    {
      "Key": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ],
  "ParentReference": {
    "Selector": "string"
  },
  "SchemaFacets": [
    {
      "FacetName": "string",
      "SchemaArn": "string"
    }
  ]
}
```

## URI Request Parameters

The request requires the following URI parameters.

### DirectoryArn (p. 58)

The Amazon Resource Name (ARN) that is associated with the [Directory](#) (p. 342) in which the object will be created. For more information, see [Arn Examples](#) (p. 371).

## Request Body

The request accepts the following data in JSON format.

### LinkName (p. 58)

The name of link that is used to attach this object to a parent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [ ^\[/\[ \] \(\) : \{ \} # @ ! ? \s \\ ; ] +

Required: No

#### **ObjectAttributeList (p. 58)**

The attribute map whose attribute ARN contains the key and attribute value as the map value.

Type: Array of [AttributeKeyAndValue \(p. 264\)](#) objects

Required: No

#### **ParentReference (p. 58)**

If specified, the parent reference to which this object will be attached.

Type: [ObjectReference \(p. 355\)](#) object

Required: No

#### **SchemaFacets (p. 58)**

A list of schema facets to be associated with the object. Do not provide minor version components. See [SchemaFacet \(p. 360\)](#) for details.

Type: Array of [SchemaFacet \(p. 360\)](#) objects

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ObjectIdentifier": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

#### **ObjectIdentifier (p. 59)**

The identifier that is associated with the object.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

**AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

**DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

**FacetValidationException**

The [Facet](#) (p. 343) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

**InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

**InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

**LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

**LinkNameAlreadyInUseException**

Indicates that a link could not be created due to a naming conflict. Choose a different name and then try again.

HTTP Status Code: 400

**ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**UnsupportedIndexTypeException**

Indicates that the requested index type is not supported.

HTTP Status Code: 400

### ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/object HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 196
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170912/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=af5780db69f39c02593f384e0ad70528f9c833e67d47e8e37ac456c10c994aa0
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDxvdgkOWktRXV4HnRa8
X-Amz-Date: 20170912T184134Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "SchemaFacets": [
    {
      "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDxvdgkOWktRXV4HnRa8/schema/Examplepersonschema/1",
      "FacetName": "Organization_Person"
    }
  ]
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 12 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521

{
  "ObjectIdentifier": "AQF0Fw173YJDlpLUV1eB50WvP1K49muETy2xCqhXZK2s-A"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)

- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)



# CreateSchema

Creates a new schema in a development state. A schema can exist in three phases:

- *Development*: This is a mutable phase of the schema. All new schemas are in the development phase. Once the schema is finalized, it can be published.
- *Published*: Published schemas are immutable and have a version associated with them.
- *Applied*: Applied schemas are mutable in a way that allows you to add new schema facets. You can also add new, nonrequired attributes to existing schema facets. You can apply only published schemas to directories.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema/create HTTP/1.1
Content-type: application/json

{
  "Name": "string"
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### Name (p. 63)

The name that is associated with the schema. This is unique to each account and in each region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "SchemaArn": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

**SchemaArn (p. 63)**

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples \(p. 371\)](#).

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

**AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

**AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

**InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

**InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

**LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**SchemaAlreadyExistsException**

Indicates that a schema could not be created due to a naming conflict. Please select a different name and then try again.

HTTP Status Code: 400

### ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/schema/create HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 21
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170927/
us-west-2/clouddirectory/aws4_request, SignedHeaders=host;x-amz-date,
Signature=92b2be88dd90f3e789ff651f5ae897b35f601e2f6a4d08addb07993ef8399e29
X-Amz-Date: 20170927T164420Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Name": "Customers"
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 2c3050f1-a3a3-11e7-bd9d-f9e3493b0666
Date: Wed, 27 Sep 2017 16:44:47 GMT
x-amzn-RequestId: 2c3050f1-a3a3-11e7-bd9d-f9e3493b0666
Content-Type: application/json
Content-Length: 90

{
  "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:schema/development/
Customers"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# CreateTypedLinkFacet

Creates a [TypedLinkFacet](#) (p. 367). For more information, see [Typed Links](#).

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/typedlink/facet/create HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "Facet": {
    "Attributes": [
      {
        "DefaultValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "IsImmutable": boolean,
        "Name": "string",
        "RequiredBehavior": "string",
        "Rules": {
          "string" : {
            "Parameters": {
              "string" : "string"
            },
            "Type": "string"
          }
        },
        "Type": "string"
      }
    ],
    "IdentityAttributeOrder": [ "string" ],
    "Name": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [SchemaArn](#) (p. 66)

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples](#) (p. 371).

## Request Body

The request accepts the following data in JSON format.

### [Facet](#) (p. 66)

[Facet](#) (p. 343) structure that is associated with the typed link facet.

Type: [TypedLinkFacet](#) (p. 367) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **FacetAlreadyExistsException**

A facet with the same name already exists.

HTTP Status Code: 400

### **FacetValidationException**

The [Facet \(p. 343\)](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidRuleException**

Occurs when any of the rule parameter keys or values are invalid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

### RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/typedlink/facet/create HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 156
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170923/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=b174c239b7f8e0ef63f16c7755d3655a16f7b812e2f93008eb0447fb611cfefa
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:schema/development/
typedlinkschema
X-Amz-Date: 20170923T004008Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Facet": {
    "Attributes": [{
      "RequiredBehavior": "REQUIRED_ALWAYS",
      "Type": "BINARY",
      "Name": "1"
    }],
    "IdentityAttributeOrder": ["1"],
    "Name": "FacetExample"
  }
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Date: Thu, 23 Sep 2017 00:35:44 GMT
x-amzn-RequestId: f6f0b320-a3e4-11e7-b86b-239c40918c06
Content-Type: application/json
Content-Length: 521
```

```
{ }
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# DeleteDirectory

Deletes a directory. Only disabled directories can be deleted. A deleted directory cannot be undone. Exercise extreme caution when deleting directories.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/directory HTTP/1.1
x-amz-data-partition: DirectoryArn
```

## URI Request Parameters

The request requires the following URI parameters.

### DirectoryArn (p. 70)

The ARN of the directory to delete.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DirectoryArn": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### DirectoryArn (p. 70)

The ARN of the deleted directory.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.



HTTP Status Code: 403

**DirectoryDeletedException**

A directory that has been deleted and to which access has been attempted. Note: The requested resource will eventually cease to exist.

HTTP Status Code: 400

**DirectoryNotDisabledException**

An operation can only operate on a disabled directory.

HTTP Status Code: 400

**InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

**InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

**LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

**ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/directory HTTP/1.1
```

```
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=671e5a6db08c16becf5a59a956690cbdf3da4a089022e919d1f185ae3365c46a
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDXvdgkOWktRXV4HnRa8
X-Amz-Date: 20171009T173437Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 2061f3c0-ad18-11e7-8502-0566a31305cf
Date: Mon, 09 Oct 2017 17:34:39 GMT
x-amzn-RequestId: 2061f3c0-ad18-11e7-8502-0566a31305cf
Content-Type: application/json
Content-Length: 98

{
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDXvdgkOWktRXV4HnRa8"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# DeleteFacet

Deletes a given [Facet \(p. 343\)](#). All attributes and [Rule \(p. 359\)](#)s that are associated with the facet will be deleted. Only development schema facets are allowed deletion.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/facet/delete HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "Name": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [SchemaArn \(p. 73\)](#)

The Amazon Resource Name (ARN) that is associated with the [Facet \(p. 343\)](#). For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### [Name \(p. 73\)](#)

The name of the facet to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **FacetInUseException**

Occurs when deleting a facet that contains an attribute that is a target to an attribute reference in a different facet.

HTTP Status Code: 400

### **FacetNotFoundException**

The specified [Facet](#) (p. 343) could not be found.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.

## Example Request

```
PUT /amazonclouddirectory/2017-01-11/facet/delete HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 24
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=67a330fb824e90451da06dd85e94ac37865044e9c933657a298457bd46660b07
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:schema/development/
exampleorgtest
X-Amz-Date: 20171009T182210Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Name": "Organization"
}
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: c4f739ec-ad1e-11e7-a6de-b54884d62153
Date: Mon, 09 Oct 2017 18:22:11 GMT
x-amzn-RequestId: c4f739ec-ad1e-11e7-a6de-b54884d62153
Content-Type: application/json
Content-Length: 2

{}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# DeleteObject

Deletes an object and its associated attributes. Only objects with no children and no parents can be deleted. The maximum number of attributes that can be deleted during an object deletion is 30. For more information, see [Amazon Cloud Directory Limits](#).

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/object/delete HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "ObjectReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### DirectoryArn (p. 76)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#) where the object resides. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### ObjectReference (p. 76)

A reference that identifies the object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ObjectNotDetachedException**

Indicates that the requested operation cannot be completed because the object has not been detached from the tree.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.

## Example Request

```
PUT /amazonclouddirectory/2017-01-11/object/delete HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 84
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=7b16ec6d1d54f36672cb2d39f1e975925e522208ff8c6a8cd4e1a63dd17df70
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AfMr4qym1kZTvwqOafAYfqi
X-Amz-Date: 20171009T183947Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ObjectReference": {
    "Selector": "$AQHzK-KsptZGU78KjmnwGH6i8H-voMZDSNCqfx-frUCBFg"
  }
}
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 3b1928f3-ad21-11e7-81c0-7b48a7696e76
Date: Mon, 09 Oct 2017 18:39:48 GMT
x-amzn-RequestId: 3b1928f3-ad21-11e7-81c0-7b48a7696e76
Content-Type: application/json
Content-Length: 2

{}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)



# DeleteSchema

Deletes a given schema. Schemas in a development and published state can only be deleted.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema HTTP/1.1
x-amz-data-partition: SchemaArn
```

## URI Request Parameters

The request requires the following URI parameters.

### SchemaArn (p. 79)

The Amazon Resource Name (ARN) of the development schema. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "SchemaArn": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### SchemaArn (p. 79)

The input ARN that is returned as part of the response. For more information, see [Arn Examples \(p. 371\)](#).

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

#### **InternalServerErrorException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

#### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

#### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

#### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

#### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

#### **StillContainsLinksException**

The object could not be deleted because links still exist. Remove the links and then try the operation again.

HTTP Status Code: 400

#### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/schema HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=f2ac3f0780f6e0fa9115c1a7e19353dbc607eac30420fceacba09a189d057b44
```

```
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:schema/development/
exampleorgtest
X-Amz-Date: 20171009T185055Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: c92b705e-ad22-11e7-8502-0566a31305cf
Date: Mon, 09 Oct 2017 18:50:57 GMT
x-amzn-RequestId: c92b705e-ad22-11e7-8502-0566a31305cf
Content-Type: application/json
Content-Length: 95

{
  "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:schema/development/
exampleorgtest"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# DeleteTypedLinkFacet

Deletes a [TypedLinkFacet](#) (p. 367). For more information, see [Typed Links](#).

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/typedlink/facet/delete HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "Name": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [SchemaArn](#) (p. 82)

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples](#) (p. 371).

## Request Body

The request accepts the following data in JSON format.

### [Name](#) (p. 82)

The unique name of the typed link facet.

Type: String

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

#### **FacetNotFoundException**

The specified [Facet \(p. 343\)](#) could not be found.

HTTP Status Code: 400

#### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

#### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

#### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

#### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

#### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

#### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.

### **Example Request**

```
PUT /amazonclouddirectory/2017-01-11/typedlink/facet/delete HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 24
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=a8d2e25d4f3051fb3820effa2fc21cfe3327bea088e45c53199a5d2a2db9e1d6
```

```
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:schema/development/typedlinkschematest
X-Amz-Date: 20171009T190948Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Name": "ExampleFacet"
}
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 6cbc3bb3-ad25-11e7-98a0-81d6fbb0fa15
Date: Mon, 09 Oct 2017 19:09:50 GMT
x-amzn-RequestId: 6cbc3bb3-ad25-11e7-98a0-81d6fbb0fa15
Content-Type: application/json
Content-Length: 2

{}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# DetachFromIndex

Detaches the specified object from the specified index.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/index/detach HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "IndexReference": {
    "Selector": "string"
  },
  "TargetReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [DirectoryArn \(p. 85\)](#)

The Amazon Resource Name (ARN) of the directory the index and object exist in.

## Request Body

The request accepts the following data in JSON format.

### [IndexReference \(p. 85\)](#)

A reference to the index object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### [TargetReference \(p. 85\)](#)

A reference to the object being detached from the index.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DetachedObjectIdentifier": "string"
}
```

```
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **DetachedObjectIdentifier** (p. 85)

The `ObjectIdentifier` of the object that was detached from the index.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **NotIndexException**

Indicates that the requested operation can only operate on index objects.

HTTP Status Code: 400

### **ObjectAlreadyDetachedException**

Indicates that the object is not attached to the index.

HTTP Status Code: 400



### ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

### RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/index/detach HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 167
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=78a7d77e2d49bc312be21f048fd10742dc50c838314696f2f58e99658137773b
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdJ8mA03dNY
X-Amz-Date: 20171009T195357Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "IndexReference": {
    "Selector": "$AQGG_ADlfNZBzYHY_JgDt3TW45F26R1HTY2z-stwKBte_Q"
  },
  "TargetReference": {
    "Selector": "$AQGG_ADlfNZBzYHY_JgDt3TWcU7IARvOTear09zme1sVsw"
  }
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 9746ae70-ad2b-11e7-81c0-7b48a7696e76
Date: Mon, 09 Oct 2017 19:53:59 GMT
x-amzn-RequestId: 9746ae70-ad2b-11e7-81c0-7b48a7696e76
Content-Type: application/json
Content-Length: 77

{
  "DetachedObjectIdentifier": "AQGG_ADlfNZBzYHY_JgDt3TWcU7IARvOTear09zme1sVsw"
```

}

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# DetachObject

Detaches a given object from the parent object. The object that is to be detached from the parent is specified by the link name.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/object/detach HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "LinkName": "string",
  "ParentReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### DirectoryArn (p. 89)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#) where objects reside. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### LinkName (p. 89)

The link name associated with the object that needs to be detached.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [ ^\[\]\(\):\\{\}#@!\?\\s\\; ]+

Required: Yes

### ParentReference (p. 89)

The parent reference from which the object with the specified link name is detached.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "DetachedObjectIdentifier": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **DetachedObjectIdentifier** (p. 89)

The `ObjectIdentifier` that was detached from the object.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **NotNodeException**

Occurs when any invalid operations are performed on an object that is not a node, such as calling `ListObjectChildren` for a leaf node object.

HTTP Status Code: 400

### ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

### RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/object/detach HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 105
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171016/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=e994ca925acaa6fc6d03c9bc505e5f634fc0847563f32025ed500ea05bc5f389
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
X-Amz-Date: 20171016T231940Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ParentReference": {
    "Selector": "$AQGG_ADlfnZBzYHY_JgDt3TWcU7IARvOTear09zme1sVsw"
  },
  "LinkName": "link2"
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 7d42c361-b2c8-11e7-81c0-7b48a7696e76
Date: Mon, 16 Oct 2017 23:19:41 GMT
x-amzn-RequestId: 7d42c361-b2c8-11e7-81c0-7b48a7696e76
Content-Type: application/json
Content-Length: 77

{
  "DetachedObjectIdentifier": "AQGG_ADlfnZBzYHY_JgDt3TWSvfueNdqTdmeCuTs6YBNUA"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# DetachPolicy

Detaches a policy from an object.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/policy/detach HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "ObjectReference": {
    "Selector": "string"
  },
  "PolicyReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### DirectoryArn (p. 93)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#) where both objects reside. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### ObjectReference (p. 93)

Reference that identifies the object whose policy object will be detached.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### PolicyReference (p. 93)

Reference that identifies the policy object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **NotPolicyException**

Indicates that the requested operation can only operate on policy objects.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400



## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/policy/detach HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 168
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
cloudirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=c4e16e1a1fae26ec2a5531e95ea261c6f7255e5639438bd56af0c0ce9dafc700
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
X-Amz-Date: 20171017T185834Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "PolicyReference": {
    "Selector": "$AQGG_ADlfNZBzYHY_JgDt3TWgcBsTVmcQEWS6jlygfhuew"
  },
  "ObjectReference": {
    "Selector": "$AQGG_ADlfNZBzYHY_JgDt3TWQoovm1s3Ts2v0NKrzdVnPw"
  }
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 2d7a5bcf-b36d-11e7-81c0-7b48a7696e76
Date: Tue, 17 Oct 2017 18:58:34 GMT
x-amzn-RequestId: 2d7a5bcf-b36d-11e7-81c0-7b48a7696e76
Content-Type: application/json
Content-Length: 2

{}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# DetachTypedLink

Detaches a typed link from a specified source and target object. For more information, see [Typed Links](#).

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/typedlink/detach HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "TypedLinkSpecifier": {
    "IdentityAttributeValues": [
      {
        "AttributeName": "string",
        "Value": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    ],
    "SourceObjectReference": {
      "Selector": "string"
    },
    "TargetObjectReference": {
      "Selector": "string"
    },
    "TypedLinkFacet": {
      "SchemaArn": "string",
      "TypedLinkName": "string"
    }
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [DirectoryArn \(p. 96\)](#)

The Amazon Resource Name (ARN) of the directory where you want to detach the typed link.

## Request Body

The request accepts the following data in JSON format.

### [TypedLinkSpecifier \(p. 96\)](#)

Used to accept a typed link specifier as input.

Type: [TypedLinkSpecifier \(p. 370\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **FacetValidationException**

The [Facet \(p. 343\)](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE"

consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/typedlink/detach HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 459
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20170927/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=f2b55a0895ed644a5acfa07e793f5b2d25166c91c5f3be765004cd0b1c1613c1
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
X-Amz-Date: 20170927T191638Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "TypedLinkSpecifier": {
    "SourceObjectReference": {
      "Selector": "$AQGG_ADlfnZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
    },
    "IdentityAttributeValues": [{
      "AttributeName": "22",
      "Value": {
        "BinaryValue": "c3Ry"
      }
    }],
    "TargetObjectReference": {
      "Selector": "$AQGG_ADlfnZBzYHY_JgDt3TWcU7IARvOTeaR09zme1sVsw"
    },
    "TypedLinkFacet": {
      "TypedLinkName": "exampltypedlink8",
      "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY/schema/org/1"
    }
  }
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 6340a418-a3b8-11e7-8502-0566a31305cf
Date: Wed, 27 Sep 2017 19:16:38 GMT
x-amzn-RequestId: 6340a418-a3b8-11e7-8502-0566a31305cf
Content-Type: application/json
Content-Length: 0
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# DisableDirectory

Disables the specified directory. Disabled directories cannot be read or written to. Only enabled directories can be disabled. Disabled directories may be reenabled.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/directory/disable HTTP/1.1
x-amz-data-partition: DirectoryArn
```

## URI Request Parameters

The request requires the following URI parameters.

### DirectoryArn (p. 100)

The ARN of the directory to disable.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DirectoryArn": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### DirectoryArn (p. 100)

The ARN of the directory that has been disabled.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

#### **DirectoryDeletedException**

A directory that has been deleted and to which access has been attempted. Note: The requested resource will eventually cease to exist.

HTTP Status Code: 400

#### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

#### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

#### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

#### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

#### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

#### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/directory/disable HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171006/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=2d3c51c700aee56ce68f0c2981c6dc08a413cd771ec9349b5190519c2c2d8a87
```

```
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/  
AXQXDXvdgkOWktRXV4HnRa8  
X-Amz-Date: 20171006T011145Z  
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

## Example Response

```
HTTP/1.1 200 OK  
x-amzn-RequestId: 51db4cc5-aa33-11e7-98a0-81d6fbb0fa15  
Date: Fri, 06 Oct 2017 01:11:45 GMT  
x-amzn-RequestId: 51db4cc5-aa33-11e7-98a0-81d6fbb0fa15  
Content-Type: application/json  
Content-Length: 98
```

```
{  
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/  
AXQXDXvdgkOWktRXV4HnRa8"  
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)



# EnableDirectory

Enables the specified directory. Only disabled directories can be enabled. Once enabled, the directory can then be read and written to.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/directory/enable HTTP/1.1
x-amz-data-partition: DirectoryArn
```

## URI Request Parameters

The request requires the following URI parameters.

### DirectoryArn (p. 103)

The ARN of the directory to enable.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DirectoryArn": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### DirectoryArn (p. 103)

The ARN of the enabled directory.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

#### **DirectoryDeletedException**

A directory that has been deleted and to which access has been attempted. Note: The requested resource will eventually cease to exist.

HTTP Status Code: 400

#### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

#### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

#### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

#### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

#### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

#### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
PUT /amazonclouddirectory/2017-01-11/directory/enable HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171006/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=1399f0fdfbed70640c9d5f2ddd91f8722645721bb30cbd9f6487d091de54bda0
```

```
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDXvdgkOWktRXV4HnRa8
X-Amz-Date: 20171006T011313Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 85ee2468-aa33-11e7-98a0-81d6fbb0fa15
Date: Fri, 06 Oct 2017 01:13:12 GMT
x-amzn-RequestId: 85ee2468-aa33-11e7-98a0-81d6fbb0fa15
Content-Type: application/json
Content-Length: 98
```

```
{
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDXvdgkOWktRXV4HnRa8"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# GetAppliedSchemaVersion

Returns current applied schema version ARN, including the minor version in use.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/schema/getappliedschema HTTP/1.1
Content-type: application/json

{
  "SchemaArn": "string"
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### SchemaArn (p. 106)

The ARN of the applied schema.

Type: String

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AppliedSchemaArn": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### AppliedSchemaArn (p. 106)

Current applied schema ARN, including the minor version in use if one was provided.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V2](#)

# GetDirectory

Retrieves metadata about a directory.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/directory/get HTTP/1.1
x-amz-data-partition: DirectoryArn
```

## URI Request Parameters

The request requires the following URI parameters.

### [DirectoryArn \(p. 109\)](#)

The ARN of the directory.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Directory": {
    "CreationDateTime": number,
    "DirectoryArn": "string",
    "Name": "string",
    "State": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [Directory \(p. 109\)](#)

Metadata about the directory.

Type: [Directory \(p. 342\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.

### **Example Request**

```
POST /amazonclouddirectory/2017-01-11/directory/get HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171005/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=255eceb681267d8e41de7eb8983269fb61aa76fe56e2b36a4d0c4f855d9ae237
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
X-Amz-Date: 20171005T202329Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```



## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 0d9489ee-aa0b-11e7-a169-c5bf0acd39f4
Date: Thu, 05 Oct 2017 20:23:30 GMT
x-amzn-RequestId: 0d9489ee-aa0b-11e7-a169-c5bf0acd39f4
Content-Type: application/json
Content-Length: 185

{
  "Directory": {
    "CreationDateTime": 1.506115781186E9,
    "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdJ8mA03dNY",
    "Name": "ExampleCD",
    "State": "ENABLED"
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# GetFacet

Gets details of the [Facet \(p. 343\)](#), such as facet name, attributes, [Rule \(p. 359\)s](#), or `ObjectType`. You can call this on all kinds of schema facets -- published, development, or applied.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/facet HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "Name": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### **SchemaArn (p. 112)**

The Amazon Resource Name (ARN) that is associated with the [Facet \(p. 343\)](#). For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### **Name (p. 112)**

The name of the facet to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Facet": {
    "FacetStyle": "string",
    "Name": "string",
    "ObjectType": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Facet (p. 112)

The [Facet \(p. 343\)](#) structure that is associated with the facet.

Type: [Facet \(p. 343\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### FacetNotFoundException

The specified [Facet \(p. 343\)](#) could not be found.

HTTP Status Code: 400

### InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### ResourceNotFoundException

The specified resource could not be found.

HTTP Status Code: 404

### RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
POST /amazonclouddirectory/2017-01-11/facet HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 17
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171005/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=70251faa630aeb0c6ca6375eefddef5fb0f956289eaf4a6fbb48ad7a34926aa6
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mAO3dNY/schema/org/1
X-Amz-Date: 20171005T195712Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Name": "node2"
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 614b09f0-aa07-11e7-843e-9fad359f817f
Date: Thu, 05 Oct 2017 19:57:13 GMT
x-amzn-RequestId: 614b09f0-aa07-11e7-843e-9fad359f817f
Content-Type: application/json
Content-Length: 46

{
  "Facet": {
    "Name": "node2",
    "ObjectType": "NODE"
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# GetLinkAttributes

Retrieves attributes that are associated with a typed link.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/typedlink/attributes/get HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json
```

```
{
  "AttributeNames": [ "string" ],
  "ConsistencyLevel": "string",
  "TypedLinkSpecifier": {
    "IdentityAttributeValues": [
      {
        "AttributeName": "string",
        "Value": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    ],
    "SourceObjectReference": {
      "Selector": "string"
    },
    "TargetObjectReference": {
      "Selector": "string"
    },
    "TypedLinkFacet": {
      "SchemaArn": "string",
      "TypedLinkName": "string"
    }
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### **DirectoryArn** (p. 116)

The Amazon Resource Name (ARN) that is associated with the Directory where the typed link resides. For more information, see [Arn Examples](#) (p. 371) or [Typed Links](#).

## Request Body

The request accepts the following data in JSON format.

### **AttributeNames** (p. 116)

A list of attribute names whose values will be retrieved.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

Required: Yes

#### **ConsistencyLevel** (p. 116)

The consistency level at which to retrieve the attributes on a typed link.

Type: String

Valid Values: `SERIALIZABLE` | `EVENTUAL`

Required: No

#### **TypedLinkSpecifier** (p. 116)

Allows a typed link specifier to be accepted as input.

Type: [TypedLinkSpecifier](#) (p. 370) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Attributes": [
    {
      "Key": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

#### **Attributes** (p. 117)

The attributes that are associated with the typed link.

Type: Array of [AttributeKeyAndValue](#) (p. 264) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **FacetValidationException**

The [Facet \(p. 343\)](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400



## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# GetObjectAttributes

Retrieves attributes within a facet that are associated with an object.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/attributes/get HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json

{
  "AttributeNames": [ "string" ],
  "ObjectReference": {
    "Selector": "string"
  },
  "SchemaFacet": {
    "FacetName": "string",
    "SchemaArn": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### ConsistencyLevel (p. 120)

The consistency level at which to retrieve the attributes on an object.

Valid Values: `SERIALIZABLE` | `EVENTUAL`

### DirectoryArn (p. 120)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#) where the object resides.

## Request Body

The request accepts the following data in JSON format.

### AttributeNames (p. 120)

List of attribute names whose values will be retrieved.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

Required: Yes

### ObjectReference (p. 120)

Reference that identifies the object whose attributes will be retrieved.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

#### [SchemaFacet \(p. 120\)](#)

Identifier for the facet whose attributes will be retrieved. See [SchemaFacet \(p. 360\)](#) for details.

Type: [SchemaFacet \(p. 360\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Attributes": [
    {
      "Key": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

#### [Attributes \(p. 121\)](#)

The attributes that are associated with the object.

Type: Array of [AttributeKeyAndValue \(p. 264\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

#### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

#### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

#### **FacetValidationException**

The [Facet \(p. 343\)](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

#### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

#### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

#### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

#### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

#### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

#### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# GetObjectInformation

Retrieves metadata about an object.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/information HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json

{
  "ObjectReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### ConsistencyLevel (p. 124)

The consistency level at which to retrieve the object information.

Valid Values: `SERIALIZABLE` | `EVENTUAL`

### DirectoryArn (p. 124)

The ARN of the directory being retrieved.

## Request Body

The request accepts the following data in JSON format.

### ObjectReference (p. 124)

A reference to the object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ObjectIdentifier": "string",
  "SchemaFacets": [
    {
      "FacetName": "string",
      "SchemaArn": "string"
    }
  ]
}
```

```
} ]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **ObjectIdentifier** (p. 124)

The `ObjectIdentifier` of the specified object.

Type: String

### **SchemaFacets** (p. 124)

The facets attached to the specified object. Although the response does not include minor version information, the most recently applied minor version of each Facet is in effect. See [GetAppliedSchemaVersion](#) (p. 106) for details.

Type: Array of [SchemaFacet](#) (p. 360) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
POST /amazonclouddirectory/2017-01-11/object/information HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 84
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171005/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=6afad99dfe7c5c8152ec38e7ff206dc0c6c6060ed24624ea5654f24ab1392086
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdJ8mA03dNY
X-Amz-Date: 20171005T182528Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ObjectReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWmspn1fxfQmSQaaVKSbvEiQ"
  }
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 90f2f915-a9fa-11e7-bd9d-f9e3493b0666
Date: Thu, 05 Oct 2017 18:25:29 GMT
x-amzn-RequestId: 90f2f915-a9fa-11e7-bd9d-f9e3493b0666
Content-Type: application/json
Content-Length: 215

{
  "ObjectIdentifier": "AQGG_AD1fNZBzYHY_JgDt3TWmspn1fxfQmSQaaVKSbvEiQ",
  "SchemaFacets": [{
    "FacetName": "node2",
    "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdJ8mA03dNY/schema/org/1"
  }]
}
```



## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# GetSchemaAsJson

Retrieves a JSON representation of the schema. See [JSON Schema Format](#) for more information.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/schema/json HTTP/1.1
x-amz-data-partition: SchemaArn
```

## URI Request Parameters

The request requires the following URI parameters.

### [SchemaArn \(p. 128\)](#)

The ARN of the schema to retrieve.

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Document": "string",
  "Name": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [Document \(p. 128\)](#)

The JSON representation of the schema document.

Type: String

### [Name \(p. 128\)](#)

The name of the retrieved schema.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^[a-zA-Z0-9._-]*$`

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
POST /amazonclouddirectory/2017-01-11/schema/json HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171005/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=1cac388e2c4c4fb13c1fa5d0dfceaffc827acddf559c1706168a5fd84932e4d6
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdjmAO3dNY/schema/org/1
X-Amz-Date: 20171005T204308Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: cc541a4e-aa0d-11e7-9e13-5b6a00750e59
Date: Thu, 05 Oct 2017 20:43:09 GMT
x-amzn-RequestId: cc541a4e-aa0d-11e7-9e13-5b6a00750e59
Content-Type: application/json
Content-Length: 6938

{
  "Document": "{\n\"sourceSchemaArn\": \"arn:aws:clouddirectory:us-west-2:45132example:schema/
published/org/1\", \"facets\": {\n\"node2\": {\n\"facetAttributes\": {}, \"objectType\": \"NODE
\"}, \"Organization\": {\n\"facetAttributes\": {\n\"account_id\": {\n\"attributeDefinition\":
{\n\"attributeType\": \"STRING\", \"isImmutable\": false, \"attributeRules\": {\n\"nameLength
\": {\n\"parameters\": {\n\"min\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}},
\n\"requiredBehavior\": \"NOT_REQUIRED\"}, \"account_name\": {\n\"attributeDefinition\":
{\n\"attributeType\": \"STRING\", \"isImmutable\": false, \"attributeRules\": {\n\"nameLength
\": {\n\"parameters\": {\n\"min\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}},
\n\"requiredBehavior\": \"NOT_REQUIRED\"}, \"telephone_number\": {\n\"attributeDefinition\":
{\n\"attributeType\": \"STRING\", \"isImmutable\": false, \"attributeRules\": {\n\"nameLength
\": {\n\"parameters\": {\n\"min\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}},
\n\"requiredBehavior\": \"NOT_REQUIRED\"}, \"description\": {\n\"attributeDefinition\":
{\n\"attributeType\": \"STRING\", \"isImmutable\": false, \"attributeRules\": {\n\"nameLength
\": {\n\"parameters\": {\n\"min\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}},
\n\"requiredBehavior\": \"NOT_REQUIRED\"}, \"mailing_address (country)\": {\n\"attributeDefinition
\": {\n\"attributeType\": \"STRING\", \"isImmutable\": false, \"attributeRules\": {\n\"nameLength
\": {\n\"parameters\": {\n\"min\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}},
\n\"requiredBehavior\": \"NOT_REQUIRED\"}, \"mailing_address (state)\": {\n\"attributeDefinition
\": {\n\"attributeType\": \"STRING\", \"isImmutable\": false, \"attributeRules\": {\n\"nameLength
\": {\n\"parameters\": {\n\"min\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}},
\n\"requiredBehavior\": \"NOT_REQUIRED\"}, \"mailing_address (street2)\": {\n\"attributeDefinition
\": {\n\"attributeType\": \"STRING\", \"isImmutable\": false, \"attributeRules\": {\n\"nameLength
\": {\n\"parameters\": {\n\"min\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}},
\n\"requiredBehavior\": \"NOT_REQUIRED\"}, \"mailing_address (street1)\": {\n\"attributeDefinition
\": {\n\"attributeType\": \"STRING\", \"isImmutable\": false, \"attributeRules\": {\n\"nameLength
\": {\n\"parameters\": {\n\"min\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}},
\n\"requiredBehavior\": \"NOT_REQUIRED\"}, \"web_site\": {\n\"attributeDefinition\":
{\n\"attributeType\": \"STRING\", \"isImmutable\": false, \"attributeRules\": {\n\"nameLength
\": {\n\"parameters\": {\n\"min\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}},
\n\"requiredBehavior\": \"NOT_REQUIRED\"}, \"email\": {\n\"attributeDefinition\": {\n\"attributeType
\": \"STRING\", \"isImmutable\": false, \"attributeRules\": {\n\"nameLength\": {\n\"parameters\":
{\n\"min\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}}, \"requiredBehavior\":
\n\"NOT_REQUIRED\"}, \"mailing_address (city)\": {\n\"attributeDefinition\": {\n\"attributeType
\": \"STRING\", \"isImmutable\": false, \"attributeRules\": {\n\"nameLength\": {\n\"parameters\":
{\n\"min\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}}, \"requiredBehavior
\": \"NOT_REQUIRED\"}, \"organization_status\": {\n\"attributeDefinition\": {\n\"attributeType
\": \"STRING\", \"isImmutable\": false, \"attributeRules\": {\n\"nameLength\": {\n\"parameters\":
{\n\"min\": \"1\", \"max\": \"1024\"}, \"ruleType\": \"STRING_LENGTH\"}}}, \"requiredBehavior
\": \"NOT_REQUIRED\"}, \"mailing_address (postal_code)\": {\n\"attributeDefinition\":
{\n\"attributeType\": \"STRING\", \"isImmutable\": false, \"attributeRules\": {\n\"nameLength
```

```
{
  "parameters": {
    "min": "1",
    "max": "1024"
  },
  "ruleType": "STRING_LENGTH",
  "requiredBehavior": "NOT_REQUIRED",
  "objectType": "LEAF_NODE",
  "nodex": {
    "facetAttributes": {
      "objectType": "NODE",
      "Legal_Entity": {
        "facetAttributes": {
          "industry_vertical": {
            "attributeDefinition": {
              "attributeType": "STRING",
              "isImmutable": false,
              "attributeRules": {
                "nameLength": {
                  "parameters": {
                    "min": "1",
                    "max": "1024"
                  },
                  "ruleType": "STRING_LENGTH"
                }
              },
              "requiredBehavior": "NOT_REQUIRED",
              "registered_company_name": {
                "attributeDefinition": {
                  "attributeType": "STRING",
                  "isImmutable": false,
                  "attributeRules": {
                    "nameLength": {
                      "parameters": {
                        "min": "1",
                        "max": "1024"
                      },
                      "ruleType": "STRING_LENGTH"
                    }
                  },
                  "requiredBehavior": "NOT_REQUIRED"
                },
                "billing_currency": {
                  "attributeDefinition": {
                    "attributeType": "STRING",
                    "isImmutable": false,
                    "attributeRules": {
                      "nameLength": {
                        "parameters": {
                          "min": "1",
                          "max": "1024"
                        },
                        "ruleType": "STRING_LENGTH"
                      }
                    },
                    "requiredBehavior": "NOT_REQUIRED"
                  },
                  "mailing_address (country)": {
                    "attributeDefinition": {
                      "attributeType": "STRING",
                      "isImmutable": false,
                      "attributeRules": {
                        "nameLength": {
                          "parameters": {
                            "min": "1",
                            "max": "1024"
                          },
                          "ruleType": "STRING_LENGTH"
                        }
                      },
                      "requiredBehavior": "NOT_REQUIRED"
                    },
                    "mailing_address (state)": {
                      "attributeDefinition": {
                        "attributeType": "STRING",
                        "isImmutable": false,
                        "attributeRules": {
                          "nameLength": {
                            "parameters": {
                              "min": "1",
                              "max": "1024"
                            },
                              "ruleType": "STRING_LENGTH"
                            }
                          },
                          "requiredBehavior": "NOT_REQUIRED"
                        },
                        "mailing_address (street1)": {
                          "attributeDefinition": {
                            "attributeType": "STRING",
                            "isImmutable": false,
                            "attributeRules": {
                              "nameLength": {
                                "parameters": {
                                  "min": "1",
                                  "max": "1024"
                                },
                                  "ruleType": "STRING_LENGTH"
                                }
                              },
                              "requiredBehavior": "NOT_REQUIRED"
                            },
                            "mailing_address (street2)": {
                              "attributeDefinition": {
                                "attributeType": "STRING",
                                "isImmutable": false,
                                "attributeRules": {
                                  "nameLength": {
                                    "parameters": {
                                      "min": "1",
                                      "max": "1024"
                                    },
                                      "ruleType": "STRING_LENGTH"
                                    }
                                  },
                                  "requiredBehavior": "NOT_REQUIRED"
                                },
                                "mailing_address": {
                                  "attributeDefinition": {
                                    "attributeType": "STRING",
                                    "isImmutable": false,
                                    "attributeRules": {
                                      "nameLength": {
                                        "parameters": {
                                          "min": "1",
                                          "max": "1024"
                                        },
                                          "ruleType": "STRING_LENGTH"
                                        }
                                      },
                                      "requiredBehavior": "NOT_REQUIRED"
                                    },
                                    "tax_id": {
                                      "attributeDefinition": {
                                        "attributeType": "STRING",
                                        "isImmutable": false,
                                        "attributeRules": {
                                          "nameLength": {
                                            "parameters": {
                                              "min": "1",
                                              "max": "1024"
                                            },
                                              "ruleType": "STRING_LENGTH"
                                            }
                                          },
                                          "requiredBehavior": "NOT_REQUIRED"
                                        },
                                        "mailing_address (city)": {
                                          "attributeDefinition": {
                                            "attributeType": "STRING",
                                            "isImmutable": false,
                                            "attributeRules": {
                                              "nameLength": {
                                                "parameters": {
                                                  "min": "1",
                                                  "max": "1024"
                                                },
                                                  "ruleType": "STRING_LENGTH"
                                                }
                                              },
                                              "requiredBehavior": "NOT_REQUIRED"
                                            },
                                            "mailing_address (postal_code)": {
                                              "attributeDefinition": {
                                                "attributeType": "STRING",
                                                "isImmutable": false,
                                                "attributeRules": {
                                                  "nameLength": {
                                                    "parameters": {
                                                      "min": "1",
                                                      "max": "1024"
                                                    },
                                                      "ruleType": "STRING_LENGTH"
                                                    }
                                                  },
                                                  "requiredBehavior": "NOT_REQUIRED"
                                                },
                                                  "objectType": "LEAF_NODE",
                                                  "policyfacet": {
                                                    "facetAttributes": {
                                                      "objectType": "POLICY",
                                                      "node1": {
                                                        "facetAttributes": {
                                                          "1": {
                                                            "attributeDefinition": {
                                                              "attributeType": "BINARY",
                                                              "isImmutable": false,
                                                              "attributeRules": {
                                                                "requiredBehavior": "REQUIRED_ALWAYS"
                                                              },
                                                              "identityAttributeOrder": [
                                                                "1"
                                                              ],
                                                              "exempltypedlink8": {
                                                                "facetAttributes": {
                                                                  "22": {
                                                                    "attributeDefinition": {
                                                                      "attributeType": "BINARY",
                                                                      "isImmutable": false,
                                                                      "attributeRules": {
                                                                        "requiredBehavior": "REQUIRED_ALWAYS"
                                                                      },
                                                                      "identityAttributeOrder": [
                                                                        "22"
                                                                      ]
                                                                    }
                                                                  }
                                                                }
                                                              }
                                                            }
                                                          }
                                                        }
                                                      }
                                                    }
                                                  }
                                                }
                                              }
                                            }
                                          }
                                        }
                                      }
                                    }
                                  }
                                }
                              }
                            }
                          }
                        }
                      }
                    }
                  }
                }
              }
            }
          }
        }
      }
    }
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# GetTypedLinkFacetInformation

Returns the identity attribute order for a specific [TypedLinkFacet](#) (p. 367). For more information, see [Typed Links](#).

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/typedlink/facet/get HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "Name": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [SchemaArn](#) (p. 132)

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples](#) (p. 371).

## Request Body

The request accepts the following data in JSON format.

### [Name](#) (p. 132)

The unique name of the typed link facet.

Type: String

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "IdentityAttributeOrder": [ "string" ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **IdentityAttributeOrder (p. 132)**

The order of identity attributes for the facet, from most significant to least significant. The ability to filter typed links considers the order that the attributes are defined on the typed link facet. When providing ranges to typed link selection, any inexact ranges must be specified at the end. Any attributes that do not have a range specified are presumed to match the entire range. Filters are interpreted in the order of the attributes on the typed link facet, not the order in which they are supplied to any API calls. For more information about identity attributes, see [Typed Links](#).

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

## **Errors**

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **FacetNotFoundException**

The specified [Facet \(p. 343\)](#) could not be found.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
POST /amazonclouddirectory/2017-01-11/typedlink/facet/get HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 29
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171006/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=6561b457b066c8458961d43944ad116fc7d3a8b2fdb1a07a08cb4a5273a10b14
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY/schema/org/1
X-Amz-Date: 20171006T005026Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Name": "exampletypedlink8"
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 57471e31-aa30-11e7-8502-0566a31305cf
Date: Fri, 06 Oct 2017 00:50:25 GMT
x-amzn-RequestId: 57471e31-aa30-11e7-8502-0566a31305cf
Content-Type: application/json
Content-Length: 33

{
  "IdentityAttributeOrder": ["22"]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)



- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListAppliedSchemaArns

Lists schema major versions applied to a directory. If SchemaArn is provided, lists the minor version.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/schema/applied HTTP/1.1
Content-type: application/json

{
  "DirectoryArn": "string",
  "MaxResults": number,
  "NextToken": "string",
  "SchemaArn": "string"
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### DirectoryArn (p. 136)

The ARN of the directory you are listing.

Type: String

Required: Yes

### MaxResults (p. 136)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken (p. 136)

The pagination token.

Type: String

Required: No

### SchemaArn (p. 136)

The response for ListAppliedSchemaArns when this parameter is used will list all minor version ARNs for a major version.

Type: String

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "SchemaArns": [ "string" ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **NextToken** (p. 137)

The pagination token.

Type: String

### **SchemaArns** (p. 137)

The ARNs of schemas that are applied to the directory.

Type: Array of strings

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

#### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

#### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

#### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
POST /amazonclouddirectory/2017-01-11/schema/applied HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 99
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171016/
us-west-2/clouddirectory/aws4_request, SignedHeaders=host;x-amz-date,
Signature=9263dc9a99c8cd1178f6305dfb28c6d95f9c273b4d7cab78aaf1d7934b1dce9f
X-Amz-Date: 20171016T225524Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY"
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 1920f0d5-b2c5-11e7-a973-b71cf1107b43
Date: Mon, 16 Oct 2017 22:55:25 GMT
x-amzn-RequestId: 1920f0d5-b2c5-11e7-a973-b71cf1107b43
Content-Type: application/json
Content-Length: 128

{
  "NextToken": null,
  "SchemaArns": [ "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY/schema/org/1" ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListAttachedIndices

Lists indices attached to the specified object.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/indices HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string",
  "TargetReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### ConsistencyLevel (p. 140)

The consistency level to use for this operation.

Valid Values: `SERIALIZABLE` | `EVENTUAL`

### DirectoryArn (p. 140)

The ARN of the directory.

## Request Body

The request accepts the following data in JSON format.

### MaxResults (p. 140)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken (p. 140)

The pagination token.

Type: String

Required: No

### TargetReference (p. 140)

A reference to the object that has indices attached.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "IndexAttachments": [
    {
      "IndexedAttributes": [
        {
          "Key": {
            "FacetName": "string",
            "Name": "string",
            "SchemaArn": "string"
          },
          "Value": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          }
        }
      ],
      "ObjectIdentifier": "string"
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **IndexAttachments** (p. 141)

The indices attached to the specified object.

Type: Array of [IndexAttachment](#) (p. 348) objects

### **NextToken** (p. 141)

The pagination token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

#### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

#### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

#### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

#### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

#### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

#### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

#### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
POST /amazonclouddirectory/2017-01-11/object/indices HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 84
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171009/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=0dd23d46d0aa37f61649857fafdafa5a9d52305b03bcda0de2027c074efce9d1
```



```
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
X-Amz-Date: 20171009T194908Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "TargetReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARvOTeaR09zme1sVsw"
  }
}
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: eb40bf46-ad2a-11e7-9e13-5b6a00750e59
Date: Mon, 09 Oct 2017 19:49:10 GMT
x-amzn-RequestId: eb40bf46-ad2a-11e7-9e13-5b6a00750e59
Content-Type: application/json
Content-Length: 132

{
  "IndexAttachments": [{
    "IndexedAttributes": [],
    "ObjectIdentifier": "AQGG_AD1fNZBzYHY_JgDt3TW45F26R1HTY2z-stwKBte_Q"
  }],
  "NextToken": null
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListDevelopmentSchemaArns

Retrieves each Amazon Resource Name (ARN) of schemas in the development state.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/schema/development HTTP/1.1
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string"
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### MaxResults (p. 144)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken (p. 144)

The pagination token.

Type: String

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "SchemaArns": [ "string" ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [NextToken \(p. 144\)](#)

The pagination token.

Type: String

### [SchemaArns \(p. 144\)](#)

The ARNs of retrieved development schemas.

Type: Array of strings

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
POST /amazonclouddirectory/2017-01-11/schema/development HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171016/
us-west-2/clouddirectory/aws4_request, SignedHeaders=host;x-amz-date,
Signature=ff097f28605d8f60239f2ae4c0c3600741e772e10dfef76c61b2a16a8f36a8fe
X-Amz-Date: 20171016T233712Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: f01c6580-b2ca-11e7-81c0-7b48a7696e76
Date: Mon, 16 Oct 2017 23:37:13 GMT
x-amzn-RequestId: f01c6580-b2ca-11e7-81c0-7b48a7696e76
Content-Type: application/json
Content-Length: 510

{
  "NextToken": null,
  "SchemaArns": [
    "arn:aws:clouddirectory:us-west-2:45132example:schema/development/typedlinkschematest",
    "arn:aws:clouddirectory:us-west-2:45132example:schema/development/asdfsdfdf",
    "arn:aws:clouddirectory:us-west-2:45132example:schema/development/Customers",
    "arn:aws:clouddirectory:us-west-2:45132example:schema/development/CourseCatalog",
    "arn:aws:clouddirectory:us-west-2:45132example:schema/development/Consumers",
    "arn:aws:clouddirectory:us-west-2:45132example:schema/development/exampleorg"
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V2](#)

# ListDirectories

Lists directories created within an account.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/directory/list HTTP/1.1
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string",
  "state": "string"
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### MaxResults (p. 148)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken (p. 148)

The pagination token.

Type: String

Required: No

### state (p. 148)

The state of the directories in the list. Can be either Enabled, Disabled, or Deleted.

Type: String

Valid Values: `ENABLED` | `DISABLED` | `DELETED`

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Directories": [
    {
      "CreationDateTime": number,
      "DirectoryArn": "string",
      "Name": "string",
      "State": "string"
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **Directories (p. 148)**

Lists all directories that are associated with your account in pagination fashion.

Type: Array of [Directory \(p. 342\)](#) objects

### **NextToken (p. 148)**

The pagination token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### LimitExceededException

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### RetryableConflictException

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
POST /amazonclouddirectory/2017-01-11/directory/list HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171016/
us-west-2/clouddirectory/aws4_request, SignedHeaders=host;x-amz-date,
Signature=3e25d9a79eca5d22f81ae7ef6ed3d3b1a7280201839584196e680029893b8694
X-Amz-Date: 20171016T233810Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 12ade21c-b2cb-11e7-bd9d-f9e3493b0666
Date: Mon, 16 Oct 2017 23:38:11 GMT
x-amzn-RequestId: 12ade21c-b2cb-11e7-bd9d-f9e3493b0666
Content-Type: application/json
Content-Length: 893

{
  "Directories": [{
    "CreationDateTime": 1.506121791167E9,
    "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
Ae89hOKmw0bRpvYgW8EAsus",
    "Name": "ExampleCD4",
    "State": "ENABLED"
  }, {
    "CreationDateTime": 1.485473189746E9,
    "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AXQXDxvdgkOWktRXV4HnRa8",
    "Name": "testCD",
```



```
    "State": "DELETED"
  }, {
    "CreationDateTime": 1.506115781186E9,
    "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/AYb8AOV81kHNgdj8mA03dNY",
    "Name": "ExampleCD",
    "State": "ENABLED"
  }, {
    "CreationDateTime": 1.506118003859E9,
    "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/AfMr4qym1kZTvwqOafAYfqI",
    "Name": "ExampleCD2",
    "State": "ENABLED"
  }, {
    "CreationDateTime": 1.485477107925E9,
    "DirectoryArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/AWeIlyjiB0SylWVTvQklCD0",
    "Name": "testCD2",
    "State": "DELETED"
  }],
  "NextToken": null
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListFacetAttributes

Retrieves attributes attached to the facet.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/facet/attributes HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "MaxResults": number,
  "Name": "string",
  "NextToken": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### **SchemaArn** (p. 152)

The ARN of the schema where the facet resides.

## Request Body

The request accepts the following data in JSON format.

### **MaxResults** (p. 152)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### **Name** (p. 152)

The name of the facet whose attributes will be retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

### **NextToken** (p. 152)

The pagination token.

Type: String

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Attributes": [
    {
      "AttributeDefinition": {
        "DefaultValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "IsImmutable": boolean,
        "Rules": {
          "string" : {
            "Parameters": {
              "string" : "string"
            },
            "Type": "string"
          }
        },
        "Type": "string"
      },
      "AttributeReference": {
        "TargetAttributeName": "string",
        "TargetFacetName": "string"
      },
      "Name": "string",
      "RequiredBehavior": "string"
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Attributes (p. 153)

The attributes attached to the facet.

Type: Array of [FacetAttribute \(p. 344\)](#) objects

### NextToken (p. 153)

The pagination token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **FacetNotFoundException**

The specified [Facet](#) (p. 343) could not be found.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.

## Example Request

```
POST /amazonclouddirectory/2017-01-11/facet/attributes HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 24
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=729cd6edffd57814ab2e2a671da29fc3c57f277c440cc331c2dfd2a3dd35f71b
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mAO3dNY/schema/org/1
X-Amz-Date: 20171017T202437Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "Name": "Organization"
}
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 330cefed-b379-11e7-a6de-b54884d62153
Date: Tue, 17 Oct 2017 20:24:38 GMT
x-amzn-RequestId: 330cefed-b379-11e7-a6de-b54884d62153
Content-Type: application/json
Content-Length: 2628

{
  "Attributes": [{
    "AttributeDefinition": {
      "DefaultValue": null,
      "IsImmutable": false,
      "Rules": {
        "nameLength": {
          "Parameters": {
            "max": "1024",
            "min": "1"
          },
          "Type": "STRING_LENGTH"
        }
      },
      "Type": "STRING"
    },
    "AttributeReference": null,
    "Name": "account_id",
    "RequiredBehavior": "NOT_REQUIRED"
  }, {
    "AttributeDefinition": {
      "DefaultValue": null,
      "IsImmutable": false,
      "Rules": {
        "nameLength": {
          "Parameters": {
            "max": "1024",
            "min": "1"
          },
          "Type": "STRING_LENGTH"
        }
      },
      "Type": "STRING"
    },
    "AttributeReference": null,
    "Name": "account_name",
```

```

    "RequiredBehavior": "NOT_REQUIRED"
  }, {
    "AttributeDefinition": {
      "DefaultValue": null,
      "IsImmutable": false,
      "Rules": {
        "nameLength": {
          "Parameters": {
            "max": "1024",
            "min": "1"
          }
        },
        "Type": "STRING_LENGTH"
      }
    },
    "Type": "STRING"
  },
  "AttributeReference": null,
  "Name": "description",
  "RequiredBehavior": "NOT_REQUIRED"
}, {
  "AttributeDefinition": {
    "DefaultValue": null,
    "IsImmutable": false,
    "Rules": {
      "nameLength": {
        "Parameters": {
          "max": "1024",
          "min": "1"
        }
      },
      "Type": "STRING_LENGTH"
    }
  },
  "Type": "STRING"
},
  "AttributeReference": null,
  "Name": "email",
  "RequiredBehavior": "NOT_REQUIRED"
}, {
  "AttributeDefinition": {
    "DefaultValue": null,
    "IsImmutable": false,
    "Rules": {
      "nameLength": {
        "Parameters": {
          "max": "1024",
          "min": "1"
        }
      },
      "Type": "STRING_LENGTH"
    }
  },
  "Type": "STRING"
},
  "AttributeReference": null,
  "Name": "mailing_address (city)",
  "RequiredBehavior": "NOT_REQUIRED"
}, {
  "AttributeDefinition": {
    "DefaultValue": null,
    "IsImmutable": false,
    "Rules": {
      "nameLength": {
        "Parameters": {
          "max": "1024",
          "min": "1"
        }
      },
      "Type": "STRING_LENGTH"
    }
  },
  "Type": "STRING_LENGTH"
}

```

```

    },
    "Type": "STRING"
  },
  "AttributeReference": null,
  "Name": "mailing_address (country)",
  "RequiredBehavior": "NOT_REQUIRED"
}, {
  "AttributeDefinition": {
    "DefaultValue": null,
    "Immutable": false,
    "Rules": {
      "nameLength": {
        "Parameters": {
          "max": "1024",
          "min": "1"
        },
        "Type": "STRING_LENGTH"
      }
    },
    "Type": "STRING"
  },
  "AttributeReference": null,
  "Name": "mailing_address (postal_code)",
  "RequiredBehavior": "NOT_REQUIRED"
}, {
  "AttributeDefinition": {
    "DefaultValue": null,
    "Immutable": false,
    "Rules": {
      "nameLength": {
        "Parameters": {
          "max": "1024",
          "min": "1"
        },
        "Type": "STRING_LENGTH"
      }
    },
    "Type": "STRING"
  },
  "AttributeReference": null,
  "Name": "mailing_address (state)",
  "RequiredBehavior": "NOT_REQUIRED"
}, {
  "AttributeDefinition": {
    "DefaultValue": null,
    "Immutable": false,
    "Rules": {
      "nameLength": {
        "Parameters": {
          "max": "1024",
          "min": "1"
        },
        "Type": "STRING_LENGTH"
      }
    },
    "Type": "STRING"
  },
  "AttributeReference": null,
  "Name": "mailing_address (street1)",
  "RequiredBehavior": "NOT_REQUIRED"
}, {
  "AttributeDefinition": {
    "DefaultValue": null,
    "Immutable": false,
    "Rules": {

```

```
"nameLength": {
  "Parameters": {
    "max": "1024",
    "min": "1"
  },
  "Type": "STRING_LENGTH"
},
"Type": "STRING"
},
"AttributeReference": null,
"Name": "mailing_address (street2)",
"RequiredBehavior": "NOT_REQUIRED"
}],
"NextToken": "V0b3JnYW5pemF0aW9uX3N0YXR1cw=="
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)



# ListFacetNames

Retrieves the names of facets that exist in a schema.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/facet/list HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### **SchemaArn** (p. 159)

The Amazon Resource Name (ARN) to retrieve facet names from.

## Request Body

The request accepts the following data in JSON format.

### **MaxResults** (p. 159)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### **NextToken** (p. 159)

The pagination token.

Type: String

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "FacetNames": [ "string" ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **FacetNames** (p. 159)

The names of facets that exist within the schema.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

### **NextToken** (p. 159)

The pagination token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
POST /amazonclouddirectory/2017-01-11/facet/list HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 0
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=e29fa5e564697e1912f34bd1d1437f78be8e8ebbd4f31f3ce6d300f5be5c814bd
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY/schema/org/1
X-Amz-Date: 20171017T202730Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 9a69f750-b379-11e7-bd9d-f9e3493b0666
Date: Tue, 17 Oct 2017 20:27:32 GMT
x-amzn-RequestId: 9a69f750-b379-11e7-bd9d-f9e3493b0666
Content-Type: application/json
Content-Length: 101

{
  "FacetNames": ["Legal_Entity", "Organization", "node1", "node2", "nodex", "policyfacet"],
  "NextToken": null
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListIncomingTypedLinks

Returns a paginated list of all the incoming [TypedLinkSpecifier](#) (p. 370) information for an object. It also supports filtering by typed link facet and identity attributes. For more information, see [Typed Links](#).

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/typedlink/incoming HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json
```

```
{
  "ConsistencyLevel": "string",
  "FilterAttributeRanges": [
    {
      "AttributeName": "string",
      "Range": {
        "EndMode": "string",
        "EndValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "StartMode": "string",
        "StartValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    }
  ],
  "FilterTypedLink": {
    "SchemaArn": "string",
    "TypedLinkName": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### DirectoryArn (p. 163)

The Amazon Resource Name (ARN) of the directory where you want to list the typed links.

## Request Body

The request accepts the following data in JSON format.

### ConsistencyLevel (p. 163)

The consistency level to execute the request at.

Type: String

Valid Values: `SERIALIZABLE` | `EVENTUAL`

Required: No

### FilterAttributeRanges (p. 163)

Provides range filters for multiple attributes. When providing ranges to typed link selection, any inexact ranges must be specified at the end. Any attributes that do not have a range specified are presumed to match the entire range.

Type: Array of [TypedLinkAttributeRange \(p. 366\)](#) objects

Required: No

### FilterTypedLink (p. 163)

Filters are interpreted in the order of the attributes on the typed link facet, not the order in which they are supplied to any API calls.

Type: [TypedLinkSchemaAndFacetName \(p. 369\)](#) object

Required: No

### MaxResults (p. 163)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken (p. 163)

The pagination token.

Type: String

Required: No

### ObjectReference (p. 163)

Reference that identifies the object whose attributes will be listed.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "LinkSpecifiers": [
    {
```

```
    "IdentityAttributeValues": [
      {
        "AttributeName": "string",
        "Value": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    ],
    "SourceObjectReference": {
      "Selector": "string"
    },
    "TargetObjectReference": {
      "Selector": "string"
    },
    "TypedLinkFacet": {
      "SchemaArn": "string",
      "TypedLinkName": "string"
    }
  }
],
"NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### LinkSpecifiers (p. 164)

Returns one or more typed link specifiers as output.

Type: Array of [TypedLinkSpecifier](#) (p. 370) objects

### NextToken (p. 164)

The pagination token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **FacetValidationException**

The [Facet \(p. 343\)](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.

### **Example Request**

```
POST /amazonclouddirectory/2017-01-11/typedlink/incoming HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
```



```
Accept-Encoding: identity
Content-Length: 84
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=fc13e2c9fb358918b87ada72c9dca32938fc33cf83e7774394fce55d755001dc
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
X-Amz-Date: 20171017T204458Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ObjectReference": {
    "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARvOTeaR09zme1sVsw"
  }
}
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 0b1ebdf5-b37c-11e7-9e13-5b6a00750e59
Date: Tue, 17 Oct 2017 20:45:00 GMT
x-amzn-RequestId: 0b1ebdf5-b37c-11e7-9e13-5b6a00750e59
Content-Type: application/json
Content-Length: 1530

{
  "LinkSpecifiers": [{
    "IdentityAttributeValues": [{
      "AttributeName": "22",
      "Value": {
        "BinaryValue": "",
        "BooleanValue": null,
        "DatetimeValue": null,
        "NumberValue": null,
        "StringValue": null
      }
    }],
    "SourceObjectReference": {
      "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
    },
    "TargetObjectReference": {
      "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARvOTeaR09zme1sVsw"
    },
    "TypedLinkFacet": {
      "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY/schema/org/1",
      "TypedLinkName": "exampletypedlink8"
    }
  }, {
    "IdentityAttributeValues": [{
      "AttributeName": "22",
      "Value": {
        "BinaryValue": "MA==",
        "BooleanValue": null,
        "DatetimeValue": null,
        "NumberValue": null,
        "StringValue": null
      }
    }],
    "SourceObjectReference": {
      "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
    },
    "TargetObjectReference": {
      "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARvOTeaR09zme1sVsw"
    }
  }
}
```

```
    },
    "TypedLinkFacet": {
      "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY/schema/org/1",
      "TypedLinkName": "exampletypedlink8"
    }
  }, {
    "IdentityAttributeValues": [{
      "AttributeName": "22",
      "Value": {
        "BinaryValue": "c3Ry",
        "BooleanValue": null,
        "DatetimeValue": null,
        "NumberValue": null,
        "StringValue": null
      }
    }
  ],
    "SourceObjectReference": {
      "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
    },
    "TargetObjectReference": {
      "Selector": "$AQGG_AD1fNZBzYHY_JgDt3TWcU7IARvOTeaR09zme1sVsw"
    },
    "TypedLinkFacet": {
      "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY/schema/org/1",
      "TypedLinkName": "exampletypedlink8"
    }
  }
],
  "NextToken": null
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListIndex

Lists objects attached to the specified index.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/index/targets HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json
```

```
{
  "IndexReference": {
    "Selector": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "RangesOnIndexedValues": [
    {
      "AttributeKey": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Range": {
        "EndMode": "string",
        "EndValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "StartMode": "string",
        "StartValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    }
  ]
}
```

## URI Request Parameters

The request requires the following URI parameters.

### **ConsistencyLevel** (p. 169)

The consistency level to execute the request at.

Valid Values: `SERIALIZABLE` | `EVENTUAL`

### **DirectoryArn** (p. 169)

The ARN of the directory that the index exists in.

## Request Body

The request accepts the following data in JSON format.

### **IndexReference** (p. 169)

The reference to the index to list.

Type: [ObjectReference](#) (p. 355) object

Required: Yes

### **MaxResults** (p. 169)

The maximum number of objects in a single page to retrieve from the index during a request. For more information, see [Amazon Cloud Directory Limits](#).

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### **NextToken** (p. 169)

The pagination token.

Type: String

Required: No

### **RangesOnIndexedValues** (p. 169)

Specifies the ranges of indexed values that you want to query.

Type: Array of [ObjectAttributeRange](#) (p. 352) objects

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "IndexAttachments": [
    {
      "IndexedAttributes": [
        {
          "Key": {
            "FacetName": "string",
            "Name": "string",
            "SchemaArn": "string"
          },
          "Value": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          }
        }
      ]
    }
  ]
}
```

```
    ],  
    "ObjectIdentifier": "string"  
  }  
],  
"NextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **IndexAttachments (p. 170)**

The objects and indexed values attached to the index.

Type: Array of [IndexAttachment \(p. 348\)](#) objects

### **NextToken (p. 170)**

The pagination token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **FacetValidationException**

The [Facet \(p. 343\)](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **NotIndexException**

Indicates that the requested operation can only operate on index objects.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.

### **Example Request**

```
POST /amazonclouddirectory/2017-01-11/index/targets HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 83
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=e10557e84c0fb9fd30e6a018a02b51ecbac72a389e2dd20090e516d3023872e4
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
X-Amz-Date: 20171017T221341Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "IndexReference": {
    "Selector": "$AQGG_ADlfNZBzYHY_JgDt3TW45F26R1HTY2z-stwKBte_Q"
  }
}
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 2920690c-b38d-11e7-bd9d-f9e3493b0666
Date: Tue, 17 Oct 2017 22:47:31 GMT
x-amzn-RequestId: 2920690c-b38d-11e7-bd9d-f9e3493b0666
Content-Type: application/json
Content-Length: 404

{
  "IndexAttachments": [{
    "IndexedAttributes": [{
      "Key": {
        "FacetName": "Organization",
        "Name": "description",
        "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY/schema/org/1"
      },
      "Value": {
        "BinaryValue": null,
        "BooleanValue": null,
        "DatetimeValue": null,
        "NumberValue": null,
        "StringValue": null
      }
    }],
    "ObjectIdentifier": "AQGG_AD1fNZBzYHY_JgDt3TwcU7IARvOTeaR09zme1sVsw"
  }],
  "NextToken": null
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListManagedSchemaArns

Lists the major version families of each managed schema. If a major version ARN is provided as SchemaArn, the minor version revisions in that family are listed instead.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/schema/managed HTTP/1.1
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string",
  "SchemaArn": "string"
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### MaxResults (p. 174)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken (p. 174)

The pagination token.

Type: String

Required: No

### SchemaArn (p. 174)

The response for ListManagedSchemaArns. When this parameter is used, all minor version ARNs for a major version are listed.

Type: String

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```



```
{  
  "NextToken": "string",  
  "SchemaArns": [ "string" ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **NextToken** (p. 174)

The pagination token.

Type: String

### **SchemaArns** (p. 174)

The ARNs for all AWS managed schemas.

Type: Array of strings

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListObjectAttributes

Lists all attributes that are associated with an object.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/attributes HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json

{
  "FacetFilter": {
    "FacetName": "string",
    "SchemaArn": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### ConsistencyLevel (p. 177)

Represents the manner and timing in which the successful write or update of an object is reflected in a subsequent read operation of that same object.

Valid Values: `SERIALIZABLE` | `EVENTUAL`

### DirectoryArn (p. 177)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#) where the object resides. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### FacetFilter (p. 177)

Used to filter the list of object attributes that are associated with a certain facet.

Type: [SchemaFacet \(p. 360\)](#) object

Required: No

### MaxResults (p. 177)

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

#### **NextToken (p. 177)**

The pagination token.

Type: String

Required: No

#### **ObjectReference (p. 177)**

The reference that identifies the object whose attributes will be listed.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Attributes": [
    {
      "Key": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      },
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

#### **Attributes (p. 178)**

Attributes map that is associated with the object. `AttributeArn` is the key, and attribute value is the value.

Type: Array of [AttributeKeyAndValue \(p. 264\)](#) objects

#### **NextToken (p. 178)**

The pagination token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **FacetValidationException**

The [Facet \(p. 343\)](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### ValidationException

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## Examples

The following examples are formatted for legibility.

### Example Request

```
POST /amazonclouddirectory/2017-01-11/object/attributes HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 84
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=192bfef84370989cc0ccc0760a138e2e49e4454e467f2247d98112507bee7ed7
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
X-Amz-Date: 20171017T221819Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ObjectReference": {
    "Selector": "$AQGG_ADlfNZBzYHY_JgDt3TW45F26R1HTY2z-stwKBte_Q"
  }
}
```

### Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 151ad236-b389-11e7-a6de-b54884d62153
Date: Tue, 17 Oct 2017 22:18:19 GMT
x-amzn-RequestId: 151ad236-b389-11e7-a6de-b54884d62153
Content-Type: application/json
Content-Length: 725

{
  "Attributes": [{
    "Key": {
      "FacetName": "INDEX",
      "Name": "index_is_unique",
      "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY/schema/CloudDirectory/1.0"
    },
    "Value": {
      "BinaryValue": null,
      "BooleanValue": true,
      "DatetimeValue": null,
      "NumberValue": null,
      "StringValue": null
    }
  }, {
    "Key": {
      "FacetName": "INDEX",
      "Name": "ordered_indexed_attributes",
      "SchemaArn": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY/schema/CloudDirectory/1.0"
```

```
    },
    "Value": {
      "BinaryValue": null,
      "BooleanValue": null,
      "DatetimeValue": null,
      "NumberValue": null,
      "StringValue": "arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY/schema/org/1*Organization*description"
    }
  },
  "NextToken": null
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListObjectChildren

Returns a paginated list of child objects that are associated with a given object.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/children HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### ConsistencyLevel (p. 182)

Represents the manner and timing in which the successful write or update of an object is reflected in a subsequent read operation of that same object.

Valid Values: `SERIALIZABLE` | `EVENTUAL`

### DirectoryArn (p. 182)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#) where the object resides. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### MaxResults (p. 182)

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken (p. 182)

The pagination token.

Type: String

Required: No



### [ObjectReference \(p. 182\)](#)

The reference that identifies the object for which child objects are being listed.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Children": {
    "string" : "string"
  },
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [Children \(p. 183\)](#)

Children structure, which is a map with key as the `LinkName` and `ObjectIdentifier` as the value.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Key Pattern: `[^\\/[\\]\\\\\\):\\{\\}#@!\\.?\\s\\;]+`

### [NextToken \(p. 183\)](#)

The pagination token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **InternalServerErrorException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **NotNodeException**

Occurs when any invalid operations are performed on an object that is not a node, such as calling `ListObjectChildren` for a leaf node object.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **Examples**

The following examples are formatted for legibility.

### **Example Request**

```
POST /amazonclouddirectory/2017-01-11/object/children HTTP/1.1
Host: clouddirectory.us-west-2.amazonaws.com
```

```
Accept-Encoding: identity
Content-Length: 84
Authorization: AWS4-HMAC-SHA256 Credential=AKIAI7E3BYXS3example/20171017/us-west-2/
clouddirectory/aws4_request, SignedHeaders=host;x-amz-data-partition;x-amz-date,
Signature=8c56f415f53f259c6c7a7ba5c5d8b9924ba5341dbb17eb84e23235f5fd3eca0e
x-amz-data-partition: arn:aws:clouddirectory:us-west-2:45132example:directory/
AYb8AOV81kHNgdj8mA03dNY
X-Amz-Date: 20171017T223103Z
User-Agent: aws-cli/1.11.150 Python/2.7.9 Windows/8 botocore/1.7.8

{
  "ObjectReference": {
    "Selector": "$AQGG_ADlfNZBzYHY_JgDt3TWcU7IARvOTeaR09zme1sVsw"
  }
}
```

## Example Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: dcafb249-b38a-11e7-a973-b71cf1107b43
Date: Tue, 17 Oct 2017 22:31:04 GMT
x-amzn-RequestId: dcafb249-b38a-11e7-a973-b71cf1107b43
Content-Type: application/json
Content-Length: 88

{
  "Children": {
    "link2": "AQGG_ADlfNZBzYHY_JgDt3TWSvfuEnDqTdmeCuTs6YBNUA"
  },
  "NextToken": null
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListObjectParentPaths

Retrieves all available parent paths for any object type such as node, leaf node, policy node, and index node objects. For more information about objects, see [Directory Structure](#).

Use this API to evaluate all parents for an object. The call returns all objects from the root of the directory up to the requested object. The API returns the number of paths based on user-defined `MaxResults`, in case there are multiple paths to the parent. The order of the paths and nodes returned is consistent among multiple API calls unless the objects are deleted or moved. Paths not leading to the directory root are ignored from the target object.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/parentpaths HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [DirectoryArn \(p. 186\)](#)

The ARN of the directory to which the parent path applies.

## Request Body

The request accepts the following data in JSON format.

### [MaxResults \(p. 186\)](#)

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### [NextToken \(p. 186\)](#)

The pagination token.

Type: String

Required: No

### [ObjectReference \(p. 186\)](#)

The reference that identifies the object whose parent paths are listed.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "PathToObjectIdentifiersList": [
    {
      "ObjectIdentifiers": [ "string" ],
      "Path": "string"
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **NextToken (p. 187)**

The pagination token.

Type: String

### **PathToObjectIdentifiersList (p. 187)**

Returns the path to the `ObjectIdentifiers` that are associated with the directory.

Type: Array of [PathToObjectIdentifiers \(p. 356\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

**InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

**InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

**LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

**ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListObjectParents

Lists parent objects that are associated with a given object in pagination fashion.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/parent HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json

{
  "IncludeAllLinksToEachParent": boolean,
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### ConsistencyLevel (p. 189)

Represents the manner and timing in which the successful write or update of an object is reflected in a subsequent read operation of that same object.

Valid Values: `SERIALIZABLE` | `EVENTUAL`

### DirectoryArn (p. 189)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#) where the object resides. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### IncludeAllLinksToEachParent (p. 189)

When set to True, returns all [ListObjectParents:ParentLinks \(p. 190\)](#). There could be multiple links between a parent-child pair.

Type: Boolean

Required: No

### MaxResults (p. 189)

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### [NextToken \(p. 189\)](#)

The pagination token.

Type: String

Required: No

### [ObjectReference \(p. 189\)](#)

The reference that identifies the object for which parent objects are being listed.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "ParentLinks": [
    {
      "LinkName": "string",
      "ObjectIdentifier": "string"
    }
  ],
  "Parents": {
    "string" : "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [NextToken \(p. 190\)](#)

The pagination token.

Type: String

### [ParentLinks \(p. 190\)](#)

Returns a list of parent reference and LinkName Tuples.

Type: Array of [ObjectIdentifierAndLinkNameTuple \(p. 354\)](#) objects

### [Parents \(p. 190\)](#)

The parent structure, which is a map with key as the `ObjectIdentifier` and `LinkName` as the value.

Type: String to string map

Value Length Constraints: Minimum length of 1. Maximum length of 64.



Value Pattern: [ ^\[/\[ \] \ ( \ ) : \ { \ } # @ ! ? \ \$ % \ ; \ ] +

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **CannotListParentOfRootException**

Cannot list the parents of a [Directory \(p. 342\)](#) root.

HTTP Status Code: 400

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListObjectPolicies

Returns policies attached to an object in pagination fashion.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/object/policy HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### ConsistencyLevel (p. 193)

Represents the manner and timing in which the successful write or update of an object is reflected in a subsequent read operation of that same object.

Valid Values: `SERIALIZABLE` | `EVENTUAL`

### DirectoryArn (p. 193)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#) where objects reside. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### MaxResults (p. 193)

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken (p. 193)

The pagination token.

Type: String

Required: No

### [ObjectReference \(p. 193\)](#)

Reference that identifies the object for which policies will be listed.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AttachedPolicyIds": [ "string" ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [AttachedPolicyIds \(p. 194\)](#)

A list of policy `ObjectIdentifiers`, that are attached to the object.

Type: Array of strings

### [NextToken \(p. 194\)](#)

The pagination token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

**InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

**InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

**LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

**ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListOutgoingTypedLinks

Returns a paginated list of all the outgoing [TypedLinkSpecifier](#) (p. 370) information for an object. It also supports filtering by typed link facet and identity attributes. For more information, see [Typed Links](#).

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/typedlink/outgoing HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json
```

```
{
  "ConsistencyLevel": "string",
  "FilterAttributeRanges": [
    {
      "AttributeName": "string",
      "Range": {
        "EndMode": "string",
        "EndValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "StartMode": "string",
        "StartValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    }
  ],
  "FilterTypedLink": {
    "SchemaArn": "string",
    "TypedLinkName": "string"
  },
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [DirectoryArn](#) (p. 196)

The Amazon Resource Name (ARN) of the directory where you want to list the typed links.

## Request Body

The request accepts the following data in JSON format.

### ConsistencyLevel (p. 196)

The consistency level to execute the request at.

Type: String

Valid Values: `SERIALIZABLE` | `EVENTUAL`

Required: No

### FilterAttributeRanges (p. 196)

Provides range filters for multiple attributes. When providing ranges to typed link selection, any inexact ranges must be specified at the end. Any attributes that do not have a range specified are presumed to match the entire range.

Type: Array of [TypedLinkAttributeRange \(p. 366\)](#) objects

Required: No

### FilterTypedLink (p. 196)

Filters are interpreted in the order of the attributes defined on the typed link facet, not the order they are supplied to any API calls.

Type: [TypedLinkSchemaAndFacetName \(p. 369\)](#) object

Required: No

### MaxResults (p. 196)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken (p. 196)

The pagination token.

Type: String

Required: No

### ObjectReference (p. 196)

A reference that identifies the object whose attributes will be listed.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "TypedLinkSpecifiers": [
```

```
{
  "IdentityAttributeValues": [
    {
      "AttributeName": "string",
      "Value": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": "string",
        "StringValue": "string"
      }
    }
  ],
  "SourceObjectReference": {
    "Selector": "string"
  },
  "TargetObjectReference": {
    "Selector": "string"
  },
  "TypedLinkFacet": {
    "SchemaArn": "string",
    "TypedLinkName": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### NextToken (p. 197)

The pagination token.

Type: String

### TypedLinkSpecifiers (p. 197)

Returns a typed link specifier as output.

Type: Array of [TypedLinkSpecifier \(p. 370\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400



### **FacetValidationException**

The [Facet](#) (p. 343) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListPolicyAttachments

Returns all of the `ObjectIdentifiers` to which a given policy is attached.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/policy/attachment HTTP/1.1
x-amz-data-partition: DirectoryArn
x-amz-consistency-level: ConsistencyLevel
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string",
  "PolicyReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### ConsistencyLevel (p. 201)

Represents the manner and timing in which the successful write or update of an object is reflected in a subsequent read operation of that same object.

Valid Values: `SERIALIZABLE` | `EVENTUAL`

### DirectoryArn (p. 201)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#) where objects reside. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### MaxResults (p. 201)

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken (p. 201)

The pagination token.

Type: String

Required: No

### PolicyReference (p. 201)

The reference that identifies the policy object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "ObjectIdentifiers": [ "string" ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### NextToken (p. 202)

The pagination token.

Type: String

### ObjectIdentifiers (p. 202)

A list of `ObjectIdentifiers` to which the policy is attached.

Type: Array of strings

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### DirectoryNotEnabledException

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

**InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

**InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

**LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

**NotPolicyException**

Indicates that the requested operation can only operate on policy objects.

HTTP Status Code: 400

**ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)



# ListPublishedSchemaArns

Lists the major version families of each published schema. If a major version ARN is provided as `SchemaArn`, the minor version revisions in that family are listed instead.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/schema/published HTTP/1.1
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string",
  "SchemaArn": "string"
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### MaxResults (p. 205)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken (p. 205)

The pagination token.

Type: String

Required: No

### SchemaArn (p. 205)

The response for `ListPublishedSchemaArns` when this parameter is used will list all minor version ARNs for a major version.

Type: String

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
  "NextToken": "string",  
  "SchemaArns": [ "string" ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **NextToken** (p. 205)

The pagination token.

Type: String

### **SchemaArns** (p. 205)

The ARNs of published schemas.

Type: Array of strings

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.



HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListTagsForResource

Returns tags for a resource. Tagging is currently supported only for directories with a limit of 50 tags per directory. All 50 tags are returned for a given directory with this API call.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/tags HTTP/1.1
Content-type: application/json
```

```
{
  "MaxResults": number,
  "NextToken": "string",
  "ResourceArn": "string"
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### MaxResults (p. 208)

The `MaxResults` parameter sets the maximum number of results returned in a single page. This is for future use and is not supported currently.

Type: Integer

Valid Range: Minimum value of 50.

Required: No

### NextToken (p. 208)

The pagination token. This is for future use. Currently pagination is not supported for tagging.

Type: String

Required: No

### ResourceArn (p. 208)

The Amazon Resource Name (ARN) of the resource. Tagging is only supported for directories.

Type: String

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
```

```
"NextToken": "string",
"Tags": [
  {
    "Key": "string",
    "Value": "string"
  }
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **NextToken** (p. 208)

The token to use to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

### **Tags** (p. 208)

A list of tag key value pairs that are associated with the response.

Type: Array of [Tag](#) (p. 361) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidTaggingRequestException**

Can occur for multiple reasons such as when you tag a resource that doesn't exist or if you specify a higher number of tags for a resource than the allowed limit. Allowed limit is 50 tags per resource.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

**ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# ListTypedLinkFacetAttributes

Returns a paginated list of all attribute definitions for a particular [TypedLinkFacet](#) (p. 367). For more information, see [Typed Links](#).

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/typedlink/facet/attributes HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "MaxResults": number,
  "Name": "string",
  "NextToken": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [SchemaArn](#) (p. 211)

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples](#) (p. 371).

## Request Body

The request accepts the following data in JSON format.

### [MaxResults](#) (p. 211)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### [Name](#) (p. 211)

The unique name of the typed link facet.

Type: String

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

### [NextToken](#) (p. 211)

The pagination token.

Type: String

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Attributes": [
    {
      "DefaultValue": {
        "BinaryValue": blob,
        "BooleanValue": boolean,
        "DatetimeValue": number,
        "NumberValue": string,
        "StringValue": string
      },
      "IsImmutable": boolean,
      "Name": string,
      "RequiredBehavior": string,
      "Rules": {
        string : {
          "Parameters": {
            string : string
          },
          "Type": string
        }
      },
      "Type": string
    },
    ...
  ],
  "NextToken": string
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Attributes (p. 212)

An ordered set of attributes associate with the typed link.

Type: Array of [TypedLinkAttributeDefinition \(p. 364\)](#) objects

### NextToken (p. 212)

The pagination token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **FacetNotFoundException**

The specified [Facet](#) (p. 343) could not be found.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)

- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)



# ListTypedLinkFacetNames

Returns a paginated list of `TypedLink` facet names for a particular schema. For more information, see [Typed Links](#).

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/typedlink/facet/list HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### **SchemaArn** (p. 215)

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples](#) (p. 371).

## Request Body

The request accepts the following data in JSON format.

### **MaxResults** (p. 215)

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### **NextToken** (p. 215)

The pagination token.

Type: String

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "FacetNames": [ "string" ],
  "NextToken": "string"
}
```

```
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **FacetNames (p. 215)**

The names of typed link facets that exist within the schema.

Type: Array of strings

Pattern: `^[a-zA-Z0-9._-]*$`

### **NextToken (p. 215)**

The pagination token.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# LookupPolicy

Lists all policies from the root of the [Directory \(p. 342\)](#) to the object specified. If there are no policies present, an empty list is returned. If policies are present, and if some objects don't have the policies attached, it returns the `ObjectIdentifier` for such objects. If policies are present, it returns `ObjectIdentifier`, `policyId`, and `policyType`. Paths that don't lead to the root from the target object are ignored. For more information, see [Policies](#).

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/policy/lookup HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "MaxResults": number,
  "NextToken": "string",
  "ObjectReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [DirectoryArn \(p. 218\)](#)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#). For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### [MaxResults \(p. 218\)](#)

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### [NextToken \(p. 218\)](#)

The token to request the next page of results.

Type: String

Required: No

### [ObjectReference \(p. 218\)](#)

Reference that identifies the object whose policies will be looked up.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "PolicyToPathList": [
    {
      "Path": "string",
      "Policies": [
        {
          "ObjectIdentifier": "string",
          "PolicyId": "string",
          "PolicyType": "string"
        }
      ]
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **NextToken** (p. 219)

The pagination token.

Type: String

### **PolicyToPathList** (p. 219)

Provides list of path to policies. Policies contain `PolicyId`, `ObjectIdentifier`, and `PolicyType`. For more information, see [Policies](#).

Type: Array of [PolicyToPath](#) (p. 358) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **InternalServerErrorException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidNextTokenException**

Indicates that the `NextToken` value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)



# PublishSchema

Publishes a development schema with a major version and a recommended minor version.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema/publish HTTP/1.1
x-amz-data-partition: DevelopmentSchemaArn
Content-type: application/json

{
  "MinorVersion": "string",
  "Name": "string",
  "Version": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [DevelopmentSchemaArn \(p. 222\)](#)

The Amazon Resource Name (ARN) that is associated with the development schema. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### [MinorVersion \(p. 222\)](#)

The minor version under which the schema will be published. This parameter is recommended. Schemas have both a major and minor version associated with them.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: No

### [Name \(p. 222\)](#)

The new name under which the schema will be published. If this is not provided, the development schema is considered.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: No

### [Version \(p. 222\)](#)

The major version under which the schema will be published. Schemas have both a major and minor version associated with them.



Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "PublishedSchemaArn": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **PublishedSchemaArn** (p. 223)

The ARN that is associated with the published schema. For more information, see [Arn Examples](#) (p. 371).

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

**ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**SchemaAlreadyPublishedException**

Indicates that a schema is already published.

HTTP Status Code: 400

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# PutSchemaFromJson

Allows a schema to be updated using JSON upload. Only available for development schemas. See [JSON Schema Format](#) for more information.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema/json HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "Document": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [SchemaArn \(p. 225\)](#)

The ARN of the schema to update.

## Request Body

The request accepts the following data in JSON format.

### [Document \(p. 225\)](#)

The replacement JSON schema.

Type: String

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [Arn \(p. 225\)](#)

The ARN of the schema to update.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidRuleException**

Occurs when any of the rule parameter keys or values are invalid.

HTTP Status Code: 400

### **InvalidSchemaDocException**

Indicates that the provided SchemaDoc value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# RemoveFacetFromObject

Removes the specified facet from the specified object.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/object/facets/delete HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json

{
  "ObjectReference": {
    "Selector": "string"
  },
  "SchemaFacet": {
    "FacetName": "string",
    "SchemaArn": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [DirectoryArn \(p. 228\)](#)

The ARN of the directory in which the object resides.

## Request Body

The request accepts the following data in JSON format.

### [ObjectReference \(p. 228\)](#)

A reference to the object to remove the facet from.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### [SchemaFacet \(p. 228\)](#)

The facet to remove. See [SchemaFacet \(p. 360\)](#) for details.

Type: [SchemaFacet \(p. 360\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **FacetValidationException**

The [Facet \(p. 343\)](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)



# TagResource

An API operation for adding tags to a resource.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/tags/add HTTP/1.1
Content-type: application/json

{
  "ResourceArn": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### ResourceArn (p. 231)

The Amazon Resource Name (ARN) of the resource. Tagging is only supported for directories.

Type: String

Required: Yes

### Tags (p. 231)

A list of tag key-value pairs.

Type: Array of [Tag \(p. 361\)](#) objects

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **InvalidTaggingRequestException**

Can occur for multiple reasons such as when you tag a resource that doesn't exist or if you specify a higher number of tags for a resource than the allowed limit. Allowed limit is 50 tags per resource.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# UntagResource

An API operation for removing tags from a resource.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/tags/remove HTTP/1.1
Content-type: application/json

{
  "ResourceArn": "string",
  "TagKeys": [ "string" ]
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### ResourceArn (p. 234)

The Amazon Resource Name (ARN) of the resource. Tagging is only supported for directories.

Type: String

Required: Yes

### TagKeys (p. 234)

Keys of the tag that need to be removed from the resource.

Type: Array of strings

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

#### **InternalServerErrorException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

#### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

#### **InvalidTaggingRequestException**

Can occur for multiple reasons such as when you tag a resource that doesn't exist or if you specify a higher number of tags for a resource than the allowed limit. Allowed limit is 50 tags per resource.

HTTP Status Code: 400

#### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

#### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

#### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

#### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# UpdateFacet

Does the following:

1. Adds new Attributes, Rules, or ObjectTypes.
2. Updates existing Attributes, Rules, or ObjectTypes.
3. Deletes existing Attributes, Rules, or ObjectTypes.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/facet HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json
```

```
{
  "AttributeUpdates": [
    {
      "Action": "string",
      "Attribute": {
        "AttributeDefinition": {
          "DefaultValue": {
            "BinaryValue": blob,
            "BooleanValue": boolean,
            "DatetimeValue": number,
            "NumberValue": "string",
            "StringValue": "string"
          },
          "IsImmutable": boolean,
          "Rules": {
            "string": {
              "Parameters": {
                "string": "string"
              },
              "Type": "string"
            }
          },
          "Type": "string"
        },
        "AttributeReference": {
          "TargetAttributeName": "string",
          "TargetFacetName": "string"
        },
        "Name": "string",
        "RequiredBehavior": "string"
      }
    }
  ],
  "Name": "string",
  "ObjectType": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### SchemaArn (p. 237)

The Amazon Resource Name (ARN) that is associated with the [Facet \(p. 343\)](#). For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### **AttributeUpdates** (p. 237)

List of attributes that need to be updated in a given schema [Facet](#) (p. 343). Each attribute is followed by `AttributeAction`, which specifies the type of update operation to perform.

Type: Array of [FacetAttributeUpdate](#) (p. 347) objects

Required: No

### **Name** (p. 237)

The name of the facet.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

### **ObjectType** (p. 237)

The object type that is associated with the facet. See [CreateFacet:ObjectType](#) (p. 51) for more details.

Type: String

Valid Values: `NODE` | `LEAF_NODE` | `POLICY` | `INDEX`

Required: No

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

### **FacetNotFoundException**

The specified [Facet](#) (p. 343) could not be found.



HTTP Status Code: 400

#### **FacetValidationException**

The [Facet \(p. 343\)](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

#### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

#### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

#### **InvalidFacetUpdateException**

An attempt to modify a [Facet \(p. 343\)](#) resulted in an invalid schema exception.

HTTP Status Code: 400

#### **InvalidRuleException**

Occurs when any of the rule parameter keys or values are invalid.

HTTP Status Code: 400

#### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

#### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

#### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

#### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# UpdateLinkAttributes

Updates a given typed link's attributes. Attributes to be updated must not contribute to the typed link's identity, as defined by its `IdentityAttributeOrder`.

## Request Syntax

```
POST /amazonclouddirectory/2017-01-11/typedlink/attributes/update HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json
```

```
{
  "AttributeUpdates": [
    {
      "AttributeAction": {
        "AttributeActionType": "string",
        "AttributeUpdateValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      },
      "AttributeKey": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      }
    }
  ],
  "TypedLinkSpecifier": {
    "IdentityAttributeValues": [
      {
        "AttributeName": "string",
        "Value": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      }
    ],
    "SourceObjectReference": {
      "Selector": "string"
    },
    "TargetObjectReference": {
      "Selector": "string"
    },
    "TypedLinkFacet": {
      "SchemaArn": "string",
      "TypedLinkName": "string"
    }
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### **DirectoryArn (p. 241)**

The Amazon Resource Name (ARN) that is associated with the Directory where the updated typed link resides. For more information, see [Arn Examples \(p. 371\)](#) or [Typed Links](#).

## **Request Body**

The request accepts the following data in JSON format.

### **AttributeUpdates (p. 241)**

The attributes update structure.

Type: Array of [LinkAttributeUpdate \(p. 350\)](#) objects

Required: Yes

### **TypedLinkSpecifier (p. 241)**

Allows a typed link specifier to be accepted as input.

Type: [TypedLinkSpecifier \(p. 370\)](#) object

Required: Yes

## **Response Syntax**

```
HTTP/1.1 200
```

## **Response Elements**

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## **Errors**

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **FacetValidationException**

The [Facet \(p. 343\)](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

### **InternalServerErrorException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# UpdateObjectAttributes

Updates a given object's attributes.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/object/update HTTP/1.1
x-amz-data-partition: DirectoryArn
Content-type: application/json
```

```
{
  "AttributeUpdates": [
    {
      "ObjectAttributeAction": {
        "ObjectAttributeActionType": "string",
        "ObjectAttributeUpdateValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        }
      },
      "ObjectAttributeKey": {
        "FacetName": "string",
        "Name": "string",
        "SchemaArn": "string"
      }
    }
  ],
  "ObjectReference": {
    "Selector": "string"
  }
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [DirectoryArn \(p. 244\)](#)

The Amazon Resource Name (ARN) that is associated with the [Directory \(p. 342\)](#) where the object resides. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### [AttributeUpdates \(p. 244\)](#)

The attributes update structure.

Type: Array of [ObjectAttributeUpdate \(p. 353\)](#) objects

Required: Yes

### [ObjectReference \(p. 244\)](#)

The reference that identifies the object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ObjectIdentifier": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [ObjectIdentifier \(p. 245\)](#)

The `ObjectIdentifier` of the updated object.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **DirectoryNotEnabledException**

Operations are only permitted on enabled directories.

HTTP Status Code: 400

### **FacetValidationException**

The [Facet \(p. 343\)](#) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

**LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

**LinkNameAlreadyInUseException**

Indicates that a link could not be created due to a naming conflict. Choose a different name and then try again.

HTTP Status Code: 400

**ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)



# UpdateSchema

Updates the schema name with a new name. Only development schema names can be updated.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema/update HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json

{
  "Name": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### SchemaArn (p. 247)

The Amazon Resource Name (ARN) of the development schema. For more information, see [Arn Examples \(p. 371\)](#).

## Request Body

The request accepts the following data in JSON format.

### Name (p. 247)

The name of the schema.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "SchemaArn": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [SchemaArn \(p. 247\)](#)

The ARN that is associated with the updated schema. For more information, see [Arn Examples \(p. 371\)](#).

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### **InternalServiceException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### **InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### **LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

### **ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

### **RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

### **SchemaAlreadyExistsException**

Indicates that a schema could not be created due to a naming conflict. Please select a different name and then try again.

HTTP Status Code: 400

### **ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# UpdateTypedLinkFacet

Updates a [TypedLinkFacet](#) (p. 367). For more information, see [Typed Links](#).

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/typedlink/facet HTTP/1.1
x-amz-data-partition: SchemaArn
Content-type: application/json
```

```
{
  "AttributeUpdates": [
    {
      "Action": "string",
      "Attribute": {
        "DefaultValue": {
          "BinaryValue": blob,
          "BooleanValue": boolean,
          "DatetimeValue": number,
          "NumberValue": "string",
          "StringValue": "string"
        },
        "IsImmutable": boolean,
        "Name": "string",
        "RequiredBehavior": "string",
        "Rules": {
          "string" : {
            "Parameters": {
              "string" : "string"
            },
            "Type": "string"
          }
        },
        "Type": "string"
      }
    }
  ],
  "IdentityAttributeOrder": [ "string" ],
  "Name": "string"
}
```

## URI Request Parameters

The request requires the following URI parameters.

### [SchemaArn](#) (p. 250)

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples](#) (p. 371).

## Request Body

The request accepts the following data in JSON format.

### [AttributeUpdates](#) (p. 250)

Attributes update structure.

Type: Array of [TypedLinkFacetAttributeUpdate](#) (p. 368) objects

Required: Yes

#### **IdentityAttributeOrder** (p. 250)

The order of identity attributes for the facet, from most significant to least significant. The ability to filter typed links considers the order that the attributes are defined on the typed link facet. When providing ranges to a typed link selection, any inexact ranges must be specified at the end. Any attributes that do not have a range specified are presumed to match the entire range. Filters are interpreted in the order of the attributes on the typed link facet, not the order in which they are supplied to any API calls. For more information about identity attributes, see [Typed Links](#).

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

Required: Yes

#### **Name** (p. 250)

The unique name of the typed link facet.

Type: String

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

## Response Syntax

`HTTP/1.1 200`

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 379).

#### **AccessDeniedException**

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories](#) (p. 148) and check your permissions.

HTTP Status Code: 403

#### **FacetNotFoundException**

The specified [Facet](#) (p. 343) could not be found.

HTTP Status Code: 400

#### **FacetValidationException**

The [Facet](#) (p. 343) that you provided was not well formed or could not be validated with the schema.

HTTP Status Code: 400

**InternalServerErrorException**

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

**InvalidArnException**

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

**InvalidFacetUpdateException**

An attempt to modify a [Facet \(p. 343\)](#) resulted in an invalid schema exception.

HTTP Status Code: 400

**InvalidRuleException**

Occurs when any of the rule parameter keys or values are invalid.

HTTP Status Code: 400

**LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

**ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# UpgradeAppliedSchema

Upgrades a single directory in-place using the `PublishedSchemaArn` with schema updates found in `MinorVersion`. Backwards-compatible minor version upgrades are instantaneously available for readers on all objects in the directory. Note: This is a synchronous API call and upgrades only one schema on a given directory per call. To upgrade multiple directories from one schema, you would need to call this API on each directory.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema/upgradeapplied HTTP/1.1
Content-type: application/json

{
  "DirectoryArn": "string",
  "DryRun": boolean,
  "PublishedSchemaArn": "string"
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### [DirectoryArn \(p. 254\)](#)

The ARN for the directory to which the upgraded schema will be applied.

Type: String

Required: Yes

### [DryRun \(p. 254\)](#)

Used for testing whether the major version schemas are backward compatible or not. If schema compatibility fails, an exception would be thrown else the call would succeed but no changes will be saved. This parameter is optional.

Type: Boolean

Required: No

### [PublishedSchemaArn \(p. 254\)](#)

The revision of the published schema to upgrade the directory to.

Type: String

Required: Yes

## Response Syntax

```
HTTP/1.1 200
```



```
Content-type: application/json

{
  "DirectoryArn": "string",
  "UpgradedSchemaArn": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### DirectoryArn (p. 254)

The ARN of the directory that is returned as part of the response.

Type: String

### UpgradedSchemaArn (p. 254)

The ARN of the upgraded schema that is returned as part of the response.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### IncompatibleSchemaException

Indicates a failure occurred while performing a check for backward compatibility between the specified schema and the schema that is currently applied to the directory.

HTTP Status Code: 400

### InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### InvalidAttachmentException

Indicates that an attempt to make an attachment was invalid. For example, attaching two nodes with a link type that is not applicable to the nodes or attempting to apply a schema to a directory a second time.

HTTP Status Code: 400

**ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**SchemaAlreadyExistsException**

Indicates that a schema could not be created due to a naming conflict. Please select a different name and then try again.

HTTP Status Code: 400

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# UpgradePublishedSchema

Upgrades a published schema under a new minor version revision using the current contents of DevelopmentSchemaArn.

## Request Syntax

```
PUT /amazonclouddirectory/2017-01-11/schema/upgradepublished HTTP/1.1
Content-type: application/json

{
  "DevelopmentSchemaArn": "string",
  "DryRun": boolean,
  "MinorVersion": "string",
  "PublishedSchemaArn": "string"
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### DevelopmentSchemaArn (p. 257)

The ARN of the development schema with the changes used for the upgrade.

Type: String

Required: Yes

### DryRun (p. 257)

Used for testing whether the Development schema provided is backwards compatible, or not, with the publish schema provided by the user to be upgraded. If schema compatibility fails, an exception would be thrown else the call would succeed. This parameter is optional and defaults to false.

Type: Boolean

Required: No

### MinorVersion (p. 257)

Identifies the minor version of the published schema that will be created. This parameter is NOT optional.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

### PublishedSchemaArn (p. 257)

The ARN of the published schema to be upgraded.

Type: String

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "UpgradedSchemaArn": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### UpgradedSchemaArn (p. 258)

The ARN of the upgraded schema that is returned as part of the response.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 379\)](#).

### AccessDeniedException

Access denied or directory not found. Either you don't have permissions for this directory or the directory does not exist. Try calling [ListDirectories \(p. 148\)](#) and check your permissions.

HTTP Status Code: 403

### IncompatibleSchemaException

Indicates a failure occurred while performing a check for backward compatibility between the specified schema and the schema that is currently applied to the directory.

HTTP Status Code: 400

### InternalServiceException

Indicates a problem that must be resolved by Amazon Web Services. This might be a transient error in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) site to see if there are any operational issues with the service.

HTTP Status Code: 500

### InvalidArnException

Indicates that the provided ARN value is not valid.

HTTP Status Code: 400

### InvalidAttachmentException

Indicates that an attempt to make an attachment was invalid. For example, attaching two nodes with a link type that is not applicable to the nodes or attempting to apply a schema to a directory a second time.

HTTP Status Code: 400

**LimitExceededException**

Indicates that limits are exceeded. See [Limits](#) for more information.

HTTP Status Code: 400

**ResourceNotFoundException**

The specified resource could not be found.

HTTP Status Code: 404

**RetryableConflictException**

Occurs when a conflict with a previous successful write is detected. For example, if a write operation occurs on an object and then an attempt is made to read the object using "SERIALIZABLE" consistency, this exception may result. This generally occurs when the previous write did not have time to propagate to the host serving the current request. A retry (with appropriate backoff logic) is the recommended response to this exception.

HTTP Status Code: 409

**ValidationException**

Indicates that your request is malformed in some manner. See the exception message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

# Data Types

The Amazon CloudDirectory API contains several data types that various actions use. This section describes each data type in detail.

**Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AttributeKey](#) (p. 263)
- [AttributeKeyAndValue](#) (p. 264)
- [AttributeNameAndValue](#) (p. 265)
- [BatchAddFacetToObject](#) (p. 266)
- [BatchAddFacetToObjectResponse](#) (p. 267)
- [BatchAttachObject](#) (p. 268)
- [BatchAttachObjectResponse](#) (p. 269)
- [BatchAttachPolicy](#) (p. 270)
- [BatchAttachPolicyResponse](#) (p. 271)
- [BatchAttachToIndex](#) (p. 272)
- [BatchAttachToIndexResponse](#) (p. 273)
- [BatchAttachTypedLink](#) (p. 274)
- [BatchAttachTypedLinkResponse](#) (p. 275)
- [BatchCreateIndex](#) (p. 276)
- [BatchCreateIndexResponse](#) (p. 278)
- [BatchCreateObject](#) (p. 279)
- [BatchCreateObjectResponse](#) (p. 281)
- [BatchDeleteObject](#) (p. 282)
- [BatchDeleteObjectResponse](#) (p. 283)
- [BatchDetachFromIndex](#) (p. 284)
- [BatchDetachFromIndexResponse](#) (p. 285)
- [BatchDetachObject](#) (p. 286)
- [BatchDetachObjectResponse](#) (p. 287)
- [BatchDetachPolicy](#) (p. 288)
- [BatchDetachPolicyResponse](#) (p. 289)
- [BatchDetachTypedLink](#) (p. 290)
- [BatchDetachTypedLinkResponse](#) (p. 291)
- [BatchGetLinkAttributes](#) (p. 292)
- [BatchGetLinkAttributesResponse](#) (p. 293)
- [BatchGetObjectAttributes](#) (p. 294)
- [BatchGetObjectAttributesResponse](#) (p. 295)
- [BatchGetObjectInformation](#) (p. 296)
- [BatchGetObjectInformationResponse](#) (p. 297)
- [BatchListAttachedIndices](#) (p. 298)
- [BatchListAttachedIndicesResponse](#) (p. 299)

- [BatchListIncomingTypedLinks](#) (p. 300)
- [BatchListIncomingTypedLinksResponse](#) (p. 302)
- [BatchListIndex](#) (p. 303)
- [BatchListIndexResponse](#) (p. 304)
- [BatchListObjectAttributes](#) (p. 305)
- [BatchListObjectAttributesResponse](#) (p. 306)
- [BatchListObjectChildren](#) (p. 307)
- [BatchListObjectChildrenResponse](#) (p. 308)
- [BatchListObjectParentPaths](#) (p. 309)
- [BatchListObjectParentPathsResponse](#) (p. 310)
- [BatchListObjectParents](#) (p. 311)
- [BatchListObjectParentsResponse](#) (p. 312)
- [BatchListObjectPolicies](#) (p. 313)
- [BatchListObjectPoliciesResponse](#) (p. 314)
- [BatchListOutgoingTypedLinks](#) (p. 315)
- [BatchListOutgoingTypedLinksResponse](#) (p. 317)
- [BatchListPolicyAttachments](#) (p. 318)
- [BatchListPolicyAttachmentsResponse](#) (p. 319)
- [BatchLookupPolicy](#) (p. 320)
- [BatchLookupPolicyResponse](#) (p. 321)
- [BatchReadException](#) (p. 322)
- [BatchReadOperation](#) (p. 323)
- [BatchReadOperationResponse](#) (p. 326)
- [BatchReadSuccessfulResponse](#) (p. 327)
- [BatchRemoveFacetFromObject](#) (p. 330)
- [BatchRemoveFacetFromObjectResponse](#) (p. 331)
- [BatchUpdateLinkAttributes](#) (p. 332)
- [BatchUpdateLinkAttributesResponse](#) (p. 333)
- [BatchUpdateObjectAttributes](#) (p. 334)
- [BatchUpdateObjectAttributesResponse](#) (p. 335)
- [BatchWriteOperation](#) (p. 336)
- [BatchWriteOperationResponse](#) (p. 339)
- [Directory](#) (p. 342)
- [Facet](#) (p. 343)
- [FacetAttribute](#) (p. 344)
- [FacetAttributeDefinition](#) (p. 345)
- [FacetAttributeReference](#) (p. 346)
- [FacetAttributeUpdate](#) (p. 347)
- [IndexAttachment](#) (p. 348)
- [LinkAttributeAction](#) (p. 349)
- [LinkAttributeUpdate](#) (p. 350)
- [ObjectAttributeAction](#) (p. 351)
- [ObjectAttributeRange](#) (p. 352)
- [ObjectAttributeUpdate](#) (p. 353)
- [ObjectIdentifierAndLinkNameTuple](#) (p. 354)
- [ObjectReference](#) (p. 355)

- [PathToObjectIdentifiers](#) (p. 356)
- [PolicyAttachment](#) (p. 357)
- [PolicyToPath](#) (p. 358)
- [Rule](#) (p. 359)
- [SchemaFacet](#) (p. 360)
- [Tag](#) (p. 361)
- [TypedAttributeValue](#) (p. 362)
- [TypedAttributeValueRange](#) (p. 363)
- [TypedLinkAttributeDefinition](#) (p. 364)
- [TypedLinkAttributeRange](#) (p. 366)
- [TypedLinkFacet](#) (p. 367)
- [TypedLinkFacetAttributeUpdate](#) (p. 368)
- [TypedLinkSchemaAndFacetName](#) (p. 369)
- [TypedLinkSpecifier](#) (p. 370)



# AttributeKey

A unique identifier for an attribute.

## Contents

### FacetName

The name of the facet that the attribute exists within.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

### Name

The name of the attribute.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

Required: Yes

### SchemaArn

The Amazon Resource Name (ARN) of the schema that contains the facet and attribute.

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# AttributeKeyAndValue

The combination of an attribute key and an attribute value.

## Contents

### Key

The key of the attribute.

Type: [AttributeKey](#) (p. 263) object

Required: Yes

### Value

The value of the attribute.

Type: [TypedAttributeValue](#) (p. 362) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# AttributeNameAndValue

Identifies the attribute name and value for a typed link.

## Contents

### AttributeName

The attribute name of the typed link.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

Required: Yes

### Value

The value for the typed link.

Type: [TypedAttributeValue](#) (p. 362) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchAddFacetToObject

Represents the output of a batch add facet to object operation.

## Contents

### **ObjectAttributeList**

The attributes to set on the object.

Type: Array of [AttributeKeyAndValue](#) (p. 264) objects

Required: Yes

### **ObjectReference**

A reference to the object being mutated.

Type: [ObjectReference](#) (p. 355) object

Required: Yes

### **SchemaFacet**

Represents the facet being added to the object.

Type: [SchemaFacet](#) (p. 360) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchAddFacetToObjectResponse

The result of a batch add facet to object operation.

## Contents

The members of this structure are context-dependent.

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchAttachObject

Represents the output of an [AttachObject \(p. 12\)](#) operation.

## Contents

### ChildReference

The child object reference that is to be attached to the object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### LinkName

The name of the link.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [ ^\[/\[ \] \ ( \ ) : \ { \ } # @ ! ? \ s \ \ ; ] +

Required: Yes

### ParentReference

The parent object reference.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchAttachObjectResponse

Represents the output batch [AttachObject](#) (p. 12) response operation.

## Contents

### **attachedObjectIdentifier**

The `ObjectIdentifier` of the object that has been attached.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchAttachPolicy

Attaches a policy object to a regular object inside a [BatchRead \(p. 28\)](#) operation. For more information, see [AttachPolicy \(p. 16\)](#) and [BatchRead:Operations \(p. 31\)](#).

## Contents

### ObjectReference

The reference that identifies the object to which the policy will be attached.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### PolicyReference

The reference that is associated with the policy object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# BatchAttachPolicyResponse

Represents the output of an [AttachPolicy \(p. 16\)](#) response operation.

## Contents

The members of this structure are context-dependent.

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchAttachToIndex

Attaches the specified object to the specified index inside a [BatchRead \(p. 28\)](#) operation. For more information, see [AttachToIndex \(p. 19\)](#) and [BatchRead:Operations \(p. 31\)](#).

## Contents

### IndexReference

A reference to the index that you are attaching the object to.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### TargetReference

A reference to the object that you are attaching to the index.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchAttachToIndexResponse

Represents the output of a [AttachToIndex](#) (p. 19) response operation.

## Contents

### **AttachedObjectIdentifier**

The `ObjectIdentifier` of the object that was attached to the index.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchAttachTypedLink

Attaches a typed link to a specified source and target object inside a [BatchRead \(p. 28\)](#) operation. For more information, see [AttachTypedLink \(p. 23\)](#) and [BatchRead:Operations \(p. 31\)](#).

## Contents

### Attributes

A set of attributes that are associated with the typed link.

Type: Array of [AttributeNameAndValue \(p. 265\)](#) objects

Required: Yes

### SourceObjectReference

Identifies the source object that the typed link will attach to.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### TargetObjectReference

Identifies the target object that the typed link will attach to.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### TypedLinkFacet

Identifies the typed link facet that is associated with the typed link.

Type: [TypedLinkSchemaAndFacetName \(p. 369\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchAttachTypedLinkResponse

Represents the output of a [AttachTypedLink \(p. 23\)](#) response operation.

## Contents

### TypedLinkSpecifier

Returns a typed link specifier as output.

Type: [TypedLinkSpecifier \(p. 370\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchCreateIndex

Creates an index object inside of a [BatchRead \(p. 28\)](#) operation. For more information, see [CreateIndex \(p. 54\)](#) and [BatchRead:Operations \(p. 31\)](#).

## Contents

### BatchReferenceName

The batch reference name. See [Transaction Support](#) for more information.

Type: String

Required: No

### IsUnique

Indicates whether the attribute that is being indexed has unique values or not.

Type: Boolean

Required: Yes

### LinkName

The name of the link between the parent object and the index object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [ ^\[/\[ \] \ ( \ ) : \ { \ } # @ ! ? \ s \ \ ; \ ] +

Required: No

### OrderedIndexedAttributeList

Specifies the attributes that should be indexed on. Currently only a single attribute is supported.

Type: Array of [AttributeKey \(p. 263\)](#) objects

Required: Yes

### ParentReference

A reference to the parent object that contains the index object.

Type: [ObjectReference \(p. 355\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# BatchCreateIndexResponse

Represents the output of a [CreateIndex \(p. 54\)](#) response operation.

## Contents

### **ObjectIdentifier**

The `ObjectIdentifier` of the index created by this operation.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# BatchCreateObject

Represents the output of a [CreateObject \(p. 58\)](#) operation.

## Contents

### BatchReferenceName

The batch reference name. See [Transaction Support](#) for more information.

Type: String

Required: No

### LinkName

The name of the link.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [ ^\[\]\(\): \{\} #@! ? \s \\ ; ] +

Required: No

### ObjectAttributeList

An attribute map, which contains an attribute ARN as the key and attribute value as the map value.

Type: Array of [AttributeKeyAndValue \(p. 264\)](#) objects

Required: Yes

### ParentReference

If specified, the parent reference to which this object will be attached.

Type: [ObjectReference \(p. 355\)](#) object

Required: No

### SchemaFacet

A list of `FacetArns` that will be associated with the object. For more information, see [Arn Examples \(p. 371\)](#).

Type: Array of [SchemaFacet \(p. 360\)](#) objects

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# BatchCreateObjectResponse

Represents the output of a [CreateObject \(p. 58\)](#) response operation.

## Contents

### **ObjectIdentifier**

The ID that is associated with the object.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchDeleteObject

Represents the output of a [DeleteObject \(p. 76\)](#) operation.

## Contents

### ObjectReference

The reference that identifies the object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchDeleteObjectResponse

Represents the output of a [DeleteObject \(p. 76\)](#) response operation.

## Contents

The members of this structure are context-dependent.

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchDetachFromIndex

Detaches the specified object from the specified index inside a [BatchRead \(p. 28\)](#) operation. For more information, see [DetachFromIndex \(p. 85\)](#) and [BatchRead:Operations \(p. 31\)](#).

## Contents

### IndexReference

A reference to the index object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### TargetReference

A reference to the object being detached from the index.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchDetachFromIndexResponse

Represents the output of a [DetachFromIndex \(p. 85\)](#) response operation.

## Contents

### **DetachedObjectIdentifier**

The `ObjectIdentifier` of the object that was detached from the index.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchDetachObject

Represents the output of a [DetachObject \(p. 89\)](#) operation.

## Contents

### BatchReferenceName

The batch reference name. See [Transaction Support](#) for more information.

Type: String

Required: No

### LinkName

The name of the link.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [ ^\[/\[ \] \ ( \ ) : \ { \ } # @ ! ? \ s \ \ ; ] +

Required: Yes

### ParentReference

Parent reference from which the object with the specified link name is detached.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# BatchDetachObjectResponse

Represents the output of a [DetachObject \(p. 89\)](#) response operation.

## Contents

### **detachedObjectIdentifier**

The `ObjectIdentifier` of the detached object.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchDetachPolicy

Detaches the specified policy from the specified directory inside a [BatchWrite \(p. 38\)](#) operation. For more information, see [DetachPolicy \(p. 93\)](#) and [BatchWrite:Operations \(p. 42\)](#).

## Contents

### ObjectReference

Reference that identifies the object whose policy object will be detached.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### PolicyReference

Reference that identifies the policy object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchDetachPolicyResponse

Represents the output of a [DetachPolicy \(p. 93\)](#) response operation.

## Contents

The members of this structure are context-dependent.

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchDetachTypedLink

Detaches a typed link from a specified source and target object inside a [BatchRead](#) (p. 28) operation. For more information, see [DetachTypedLink](#) (p. 96) and [BatchRead:Operations](#) (p. 31).

## Contents

### TypedLinkSpecifier

Used to accept a typed link specifier as input.

Type: [TypedLinkSpecifier](#) (p. 370) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchDetachTypedLinkResponse

Represents the output of a [DetachTypedLink \(p. 96\)](#) response operation.

## Contents

The members of this structure are context-dependent.

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchGetLinkAttributes

Retrieves attributes that are associated with a typed link inside a [BatchRead](#) (p. 28) operation. For more information, see [GetLinkAttributes](#) (p. 116) and [BatchRead:Operations](#) (p. 31).

## Contents

### AttributeNames

A list of attribute names whose values will be retrieved.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

Required: Yes

### TypedLinkSpecifier

Allows a typed link specifier to be accepted as input.

Type: [TypedLinkSpecifier](#) (p. 370) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchGetLinkAttributesResponse

Represents the output of a [GetLinkAttributes](#) (p. 116) response operation.

## Contents

### Attributes

The attributes that are associated with the typed link.

Type: Array of [AttributeKeyAndValue](#) (p. 264) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchGetObjectAttributes

Retrieves attributes within a facet that are associated with an object inside an [BatchRead \(p. 28\)](#) operation. For more information, see [GetObjectAttributes \(p. 120\)](#) and [BatchRead:Operations \(p. 31\)](#).

## Contents

### AttributeNames

List of attribute names whose values will be retrieved.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

Required: Yes

### ObjectReference

Reference that identifies the object whose attributes will be retrieved.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### SchemaFacet

Identifier for the facet whose attributes will be retrieved. See [SchemaFacet \(p. 360\)](#) for details.

Type: [SchemaFacet \(p. 360\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# BatchGetObjectAttributesResponse

Represents the output of a [GetObjectAttributes](#) (p. 120) response operation.

## Contents

### Attributes

The attribute values that are associated with an object.

Type: Array of [AttributeKeyAndValue](#) (p. 264) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchGetObjectInformation

Retrieves metadata about an object inside a [BatchRead](#) (p. 28) operation. For more information, see [GetObjectInformation](#) (p. 124) and [BatchRead:Operations](#) (p. 31).

## Contents

### ObjectReference

A reference to the object.

Type: [ObjectReference](#) (p. 355) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchGetObjectInformationResponse

Represents the output of a [GetObjectInformation](#) (p. 124) response operation.

## Contents

### **ObjectIdentifier**

The `ObjectIdentifier` of the specified object.

Type: String

Required: No

### **SchemaFacets**

The facets attached to the specified object.

Type: Array of [SchemaFacet](#) (p. 360) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListAttachedIndices

Lists indices attached to an object inside a [BatchRead \(p. 28\)](#) operation. For more information, see [ListAttachedIndices \(p. 140\)](#) and [BatchRead:Operations \(p. 31\)](#).

## Contents

### MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken

The pagination token.

Type: String

Required: No

### TargetReference

A reference to the object that has indices attached.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListAttachedIndicesResponse

Represents the output of a [ListAttachedIndices](#) (p. 140) response operation.

## Contents

### IndexAttachments

The indices attached to the specified object.

Type: Array of [IndexAttachment](#) (p. 348) objects

Required: No

### NextToken

The pagination token.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListIncomingTypedLinks

Returns a paginated list of all the incoming [TypedLinkSpecifier](#) (p. 370) information for an object inside a [BatchRead](#) (p. 28) operation. For more information, see [ListIncomingTypedLinks](#) (p. 163) and [BatchRead:Operations](#) (p. 31).

## Contents

### FilterAttributeRanges

Provides range filters for multiple attributes. When providing ranges to typed link selection, any inexact ranges must be specified at the end. Any attributes that do not have a range specified are presumed to match the entire range.

Type: Array of [TypedLinkAttributeRange](#) (p. 366) objects

Required: No

### FilterTypedLink

Filters are interpreted in the order of the attributes on the typed link facet, not the order in which they are supplied to any API calls.

Type: [TypedLinkSchemaAndFacetName](#) (p. 369) object

Required: No

### MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken

The pagination token.

Type: String

Required: No

### ObjectReference

The reference that identifies the object whose attributes will be listed.

Type: [ObjectReference](#) (p. 355) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)

- [AWS SDK for Ruby V2](#)

# BatchListIncomingTypedLinksResponse

Represents the output of a [ListIncomingTypedLinks \(p. 163\)](#) response operation.

## Contents

### LinkSpecifiers

Returns one or more typed link specifiers as output.

Type: Array of [TypedLinkSpecifier \(p. 370\)](#) objects

Required: No

### NextToken

The pagination token.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# BatchListIndex

Lists objects attached to the specified index inside a [BatchRead \(p. 28\)](#) operation. For more information, see [ListIndex \(p. 169\)](#) and [BatchRead:Operations \(p. 31\)](#).

## Contents

### IndexReference

The reference to the index to list.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken

The pagination token.

Type: String

Required: No

### RangesOnIndexedValues

Specifies the ranges of indexed values that you want to query.

Type: Array of [ObjectAttributeRange \(p. 352\)](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListIndexResponse

Represents the output of a [ListIndex \(p. 169\)](#) response operation.

## Contents

### IndexAttachments

The objects and indexed values attached to the index.

Type: Array of [IndexAttachment \(p. 348\)](#) objects

Required: No

### NextToken

The pagination token.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListObjectAttributes

Represents the output of a [ListObjectAttributes \(p. 177\)](#) operation.

## Contents

### FacetFilter

Used to filter the list of object attributes that are associated with a certain facet.

Type: [SchemaFacet \(p. 360\)](#) object

Required: No

### MaxResults

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken

The pagination token.

Type: String

Required: No

### ObjectReference

Reference of the object whose attributes need to be listed.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListObjectAttributesResponse

Represents the output of a [ListObjectAttributes](#) (p. 177) response operation.

## Contents

### Attributes

The attributes map that is associated with the object. `AttributeArn` is the key; attribute value is the value.

Type: Array of [AttributeKeyAndValue](#) (p. 264) objects

Required: No

### NextToken

The pagination token.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListObjectChildren

Represents the output of a [ListObjectChildren](#) (p. 182) operation.

## Contents

### MaxResults

Maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken

The pagination token.

Type: String

Required: No

### ObjectReference

Reference of the object for which child objects are being listed.

Type: [ObjectReference](#) (p. 355) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListObjectChildrenResponse

Represents the output of a [ListObjectChildren](#) (p. 182) response operation.

## Contents

### Children

The children structure, which is a map with the key as the `LinkName` and `ObjectIdentifier` as the value.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Key Pattern: `[^\\/[\\]\\(\\):\\{\\}#@!\\.?\\s\\;]+`

Required: No

### NextToken

The pagination token.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListObjectParentPaths

Retrieves all available parent paths for any object type such as node, leaf node, policy node, and index node objects inside a [BatchRead \(p. 28\)](#) operation. For more information, see [ListObjectParentPaths \(p. 186\)](#) and [BatchRead:Operations \(p. 31\)](#).

## Contents

### MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken

The pagination token.

Type: String

Required: No

### ObjectReference

The reference that identifies the object whose attributes will be listed.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListObjectParentPathsResponse

Represents the output of a [ListObjectParentPaths](#) (p. 186) response operation.

## Contents

### **NextToken**

The pagination token.

Type: String

Required: No

### **PathToObjectIdentifiersList**

Returns the path to the `ObjectIdentifiers` that are associated with the directory.

Type: Array of [PathToObjectIdentifiers](#) (p. 356) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# BatchListObjectParents

Lists parent objects that are associated with a given object in pagination fashion.

## Contents

### MaxResults

The maximum number of items to be retrieved in a single call. This is an approximate number.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken

The pagination token.

Type: String

Required: No

### ObjectReference

The reference that identifies an object.

Type: [ObjectReference](#) (p. 355) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListObjectParentsResponse

Represents the output of a [ListObjectParents \(p. 189\)](#) response operation.

## Contents

### NextToken

The pagination token.

Type: String

Required: No

### ParentLinks

Returns a list of parent reference and LinkName Tuples.

Type: Array of [ObjectIdentifierAndLinkNameTuple \(p. 354\)](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListObjectPolicies

Returns policies attached to an object in pagination fashion inside a [BatchRead \(p. 28\)](#) operation. For more information, see [ListObjectPolicies \(p. 193\)](#) and [BatchRead:Operations \(p. 31\)](#).

## Contents

### MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken

The pagination token.

Type: String

Required: No

### ObjectReference

The reference that identifies the object whose attributes will be listed.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListObjectPoliciesResponse

Represents the output of a [ListObjectPolicies](#) (p. 193) response operation.

## Contents

### **AttachedPolicyIds**

A list of policy `ObjectIdentifiers`, that are attached to the object.

Type: Array of strings

Required: No

### **NextToken**

The pagination token.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListOutgoingTypedLinks

Returns a paginated list of all the outgoing [TypedLinkSpecifier](#) (p. 370) information for an object inside a [BatchRead](#) (p. 28) operation. For more information, see [ListOutgoingTypedLinks](#) (p. 196) and [BatchRead:Operations](#) (p. 31).

## Contents

### FilterAttributeRanges

Provides range filters for multiple attributes. When providing ranges to typed link selection, any inexact ranges must be specified at the end. Any attributes that do not have a range specified are presumed to match the entire range.

Type: Array of [TypedLinkAttributeRange](#) (p. 366) objects

Required: No

### FilterTypedLink

Filters are interpreted in the order of the attributes defined on the typed link facet, not the order they are supplied to any API calls.

Type: [TypedLinkSchemaAndFacetName](#) (p. 369) object

Required: No

### MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken

The pagination token.

Type: String

Required: No

### ObjectReference

The reference that identifies the object whose attributes will be listed.

Type: [ObjectReference](#) (p. 355) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)

- [AWS SDK for Ruby V2](#)

# BatchListOutgoingTypedLinksResponse

Represents the output of a [ListOutgoingTypedLinks \(p. 196\)](#) response operation.

## Contents

### **NextToken**

The pagination token.

Type: String

Required: No

### **TypedLinkSpecifiers**

Returns a typed link specifier as output.

Type: Array of [TypedLinkSpecifier \(p. 370\)](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchListPolicyAttachments

Returns all of the `ObjectIdentifiers` to which a given policy is attached inside a [BatchRead \(p. 28\)](#) operation. For more information, see [ListPolicyAttachments \(p. 201\)](#) and [BatchRead:Operations \(p. 31\)](#).

## Contents

### MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken

The pagination token.

Type: String

Required: No

### PolicyReference

The reference that identifies the policy object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# BatchListPolicyAttachmentsResponse

Represents the output of a [ListPolicyAttachments](#) (p. 201) response operation.

## Contents

### **NextToken**

The pagination token.

Type: String

Required: No

### **ObjectIdentifiers**

A list of `ObjectIdentifiers` to which the policy is attached.

Type: Array of strings

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchLookupPolicy

Lists all policies from the root of the Directory to the object specified inside a [BatchRead \(p. 28\)](#) operation. For more information, see [LookupPolicy \(p. 218\)](#) and [BatchRead:Operations \(p. 31\)](#).

## Contents

### MaxResults

The maximum number of results to retrieve.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### NextToken

The pagination token.

Type: String

Required: No

### ObjectReference

Reference that identifies the object whose policies will be looked up.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchLookupPolicyResponse

Represents the output of a [LookupPolicy \(p. 218\)](#) response operation.

## Contents

### NextToken

The pagination token.

Type: String

Required: No

### PolicyToPathList

Provides list of path to policies. Policies contain `PolicyId`, `ObjectIdentifier`, and `PolicyType`. For more information, see [Policies](#).

Type: Array of [PolicyToPath \(p. 358\)](#) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchReadException

The batch read exception structure, which contains the exception type and message.

## Contents

### Message

An exception message that is associated with the failure.

Type: String

Required: No

### Type

A type of exception, such as `InvalidArnException`.

Type: String

Valid Values: `ValidationException` | `InvalidArnException` | `ResourceNotFoundException` | `InvalidNextTokenException` | `AccessDeniedException` | `NotNodeException` | `FacetValidationException` | `CannotListParentOfRootException` | `NotIndexException` | `NotPolicyException` | `DirectoryNotEnabledException` | `LimitExceededException` | `InternalServiceException`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchReadOperation

Represents the output of a BatchRead operation.

## Contents

### **GetLinkAttributes**

Retrieves attributes that are associated with a typed link.

Type: [BatchGetLinkAttributes \(p. 292\)](#) object

Required: No

### **GetObjectAttributes**

Retrieves attributes within a facet that are associated with an object.

Type: [BatchGetObjectAttributes \(p. 294\)](#) object

Required: No

### **GetObjectInformation**

Retrieves metadata about an object.

Type: [BatchGetObjectInformation \(p. 296\)](#) object

Required: No

### **ListAttachedIndices**

Lists indices attached to an object.

Type: [BatchListAttachedIndices \(p. 298\)](#) object

Required: No

### **ListIncomingTypedLinks**

Returns a paginated list of all the incoming [TypedLinkSpecifier \(p. 370\)](#) information for an object. It also supports filtering by typed link facet and identity attributes. For more information, see [Typed Links](#).

Type: [BatchListIncomingTypedLinks \(p. 300\)](#) object

Required: No

### **ListIndex**

Lists objects attached to the specified index.

Type: [BatchListIndex \(p. 303\)](#) object

Required: No

### **ListObjectAttributes**

Lists all attributes that are associated with an object.

Type: [BatchListObjectAttributes \(p. 305\)](#) object

Required: No

### ListObjectChildren

Returns a paginated list of child objects that are associated with a given object.

Type: [BatchListObjectChildren \(p. 307\)](#) object

Required: No

### ListObjectParentPaths

Retrieves all available parent paths for any object type such as node, leaf node, policy node, and index node objects. For more information about objects, see [Directory Structure](#).

Type: [BatchListObjectParentPaths \(p. 309\)](#) object

Required: No

### ListObjectParents

Lists parent objects that are associated with a given object in pagination fashion.

Type: [BatchListObjectParents \(p. 311\)](#) object

Required: No

### ListObjectPolicies

Returns policies attached to an object in pagination fashion.

Type: [BatchListObjectPolicies \(p. 313\)](#) object

Required: No

### ListOutgoingTypedLinks

Returns a paginated list of all the outgoing [TypedLinkSpecifier \(p. 370\)](#) information for an object. It also supports filtering by typed link facet and identity attributes. For more information, see [Typed Links](#).

Type: [BatchListOutgoingTypedLinks \(p. 315\)](#) object

Required: No

### ListPolicyAttachments

Returns all of the `ObjectIdentifiers` to which a given policy is attached.

Type: [BatchListPolicyAttachments \(p. 318\)](#) object

Required: No

### LookupPolicy

Lists all policies from the root of the [Directory \(p. 342\)](#) to the object specified. If there are no policies present, an empty list is returned. If policies are present, and if some objects don't have the policies attached, it returns the `ObjectIdentifier` for such objects. If policies are present, it returns `ObjectIdentifier`, `policyId`, and `policyType`. Paths that don't lead to the root from the target object are ignored. For more information, see [Policies](#).

Type: [BatchLookupPolicy \(p. 320\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchReadOperationResponse

Represents the output of a BatchRead response operation.

## Contents

### ExceptionResponse

Identifies which operation in a batch has failed.

Type: [BatchReadException](#) (p. 322) object

Required: No

### SuccessfulResponse

Identifies which operation in a batch has succeeded.

Type: [BatchReadSuccessfulResponse](#) (p. 327) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# BatchReadSuccessfulResponse

Represents the output of a BatchRead success response operation.

## Contents

### **GetLinkAttributes**

The list of attributes to retrieve from the typed link.

Type: [BatchGetLinkAttributesResponse](#) (p. 293) object

Required: No

### **GetObjectAttributes**

Retrieves attributes within a facet that are associated with an object.

Type: [BatchGetObjectAttributesResponse](#) (p. 295) object

Required: No

### **GetObjectInformation**

Retrieves metadata about an object.

Type: [BatchGetObjectInformationResponse](#) (p. 297) object

Required: No

### **ListAttachedIndices**

Lists indices attached to an object.

Type: [BatchListAttachedIndicesResponse](#) (p. 299) object

Required: No

### **ListIncomingTypedLinks**

Returns a paginated list of all the incoming [TypedLinkSpecifier](#) (p. 370) information for an object. It also supports filtering by typed link facet and identity attributes. For more information, see [Typed Links](#).

Type: [BatchListIncomingTypedLinksResponse](#) (p. 302) object

Required: No

### **ListIndex**

Lists objects attached to the specified index.

Type: [BatchListIndexResponse](#) (p. 304) object

Required: No

### **ListObjectAttributes**

Lists all attributes that are associated with an object.

Type: [BatchListObjectAttributesResponse](#) (p. 306) object

Required: No

### ListObjectChildren

Returns a paginated list of child objects that are associated with a given object.

Type: [BatchListObjectChildrenResponse](#) (p. 308) object

Required: No

### ListObjectParentPaths

Retrieves all available parent paths for any object type such as node, leaf node, policy node, and index node objects. For more information about objects, see [Directory Structure](#).

Type: [BatchListObjectParentPathsResponse](#) (p. 310) object

Required: No

### ListObjectParents

The list of parent objects to retrieve.

Type: [BatchListObjectParentsResponse](#) (p. 312) object

Required: No

### ListObjectPolicies

Returns policies attached to an object in pagination fashion.

Type: [BatchListObjectPoliciesResponse](#) (p. 314) object

Required: No

### ListOutgoingTypedLinks

Returns a paginated list of all the outgoing [TypedLinkSpecifier](#) (p. 370) information for an object. It also supports filtering by typed link facet and identity attributes. For more information, see [Typed Links](#).

Type: [BatchListOutgoingTypedLinksResponse](#) (p. 317) object

Required: No

### ListPolicyAttachments

Returns all of the `ObjectIdentifiers` to which a given policy is attached.

Type: [BatchListPolicyAttachmentsResponse](#) (p. 319) object

Required: No

### LookupPolicy

Lists all policies from the root of the [Directory](#) (p. 342) to the object specified. If there are no policies present, an empty list is returned. If policies are present, and if some objects don't have the policies attached, it returns the `ObjectIdentifier` for such objects. If policies are present, it returns `ObjectIdentifier`, `policyId`, and `policyType`. Paths that don't lead to the root from the target object are ignored. For more information, see [Policies](#).

Type: [BatchLookupPolicyResponse](#) (p. 321) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchRemoveFacetFromObject

A batch operation to remove a facet from an object.

## Contents

### **ObjectReference**

A reference to the object whose facet will be removed.

Type: [ObjectReference](#) (p. 355) object

Required: Yes

### **SchemaFacet**

The facet to remove from the object.

Type: [SchemaFacet](#) (p. 360) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchRemoveFacetFromObjectResponse

An empty result that represents success.

## Contents

The members of this structure are context-dependent.

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchUpdateLinkAttributes

Updates a given typed link's attributes inside a [BatchRead \(p. 28\)](#) operation. Attributes to be updated must not contribute to the typed link's identity, as defined by its `IdentityAttributeOrder`. For more information, see [UpdateLinkAttributes \(p. 241\)](#) and [BatchRead:Operations \(p. 31\)](#).

## Contents

### AttributeUpdates

The attributes update structure.

Type: Array of [LinkAttributeUpdate \(p. 350\)](#) objects

Required: Yes

### TypedLinkSpecifier

Allows a typed link specifier to be accepted as input.

Type: [TypedLinkSpecifier \(p. 370\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchUpdateLinkAttributesResponse

Represents the output of a [UpdateLinkAttributes \(p. 241\)](#) response operation.

## Contents

The members of this structure are context-dependent.

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchUpdateObjectAttributes

Represents the output of a `BatchUpdate` operation.

## Contents

### AttributeUpdates

Attributes update structure.

Type: Array of [ObjectAttributeUpdate \(p. 353\)](#) objects

Required: Yes

### ObjectReference

Reference that identifies the object.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# BatchUpdateObjectAttributesResponse

Represents the output of a `BatchUpdate` response operation.

## Contents

### **ObjectIdentifier**

ID that is associated with the object.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchWriteOperation

Represents the output of a `BatchWrite` operation.

## Contents

### **AddFacetToObject**

A batch operation that adds a facet to an object.

Type: [BatchAddFacetToObject \(p. 266\)](#) object

Required: No

### **AttachObject**

Attaches an object to a [Directory \(p. 342\)](#).

Type: [BatchAttachObject \(p. 268\)](#) object

Required: No

### **AttachPolicy**

Attaches a policy object to a regular object. An object can have a limited number of attached policies.

Type: [BatchAttachPolicy \(p. 270\)](#) object

Required: No

### **AttachToIndex**

Attaches the specified object to the specified index.

Type: [BatchAttachToIndex \(p. 272\)](#) object

Required: No

### **AttachTypedLink**

Attaches a typed link to a specified source and target object. For more information, see [Typed Links](#).

Type: [BatchAttachTypedLink \(p. 274\)](#) object

Required: No

### **CreateIndex**

Creates an index object. See [Indexing and search](#) for more information.

Type: [BatchCreateIndex \(p. 276\)](#) object

Required: No

### **CreateObject**

Creates an object.

Type: [BatchCreateObject \(p. 279\)](#) object

Required: No

### **DeleteObject**

Deletes an object in a [Directory \(p. 342\)](#).

Type: [BatchDeleteObject \(p. 282\)](#) object

Required: No

#### **DetachFromIndex**

Detaches the specified object from the specified index.

Type: [BatchDetachFromIndex \(p. 284\)](#) object

Required: No

#### **DetachObject**

Detaches an object from a [Directory \(p. 342\)](#).

Type: [BatchDetachObject \(p. 286\)](#) object

Required: No

#### **DetachPolicy**

Detaches a policy from a [Directory \(p. 342\)](#).

Type: [BatchDetachPolicy \(p. 288\)](#) object

Required: No

#### **DetachTypedLink**

Detaches a typed link from a specified source and target object. For more information, see [Typed Links](#).

Type: [BatchDetachTypedLink \(p. 290\)](#) object

Required: No

#### **RemoveFacetFromObject**

A batch operation that removes a facet from an object.

Type: [BatchRemoveFacetFromObject \(p. 330\)](#) object

Required: No

#### **UpdateLinkAttributes**

Updates a given object's attributes.

Type: [BatchUpdateLinkAttributes \(p. 332\)](#) object

Required: No

#### **UpdateObjectAttributes**

Updates a given object's attributes.

Type: [BatchUpdateObjectAttributes \(p. 334\)](#) object

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# BatchWriteOperationResponse

Represents the output of a `BatchWrite` response operation.

## Contents

### AddFacetToObject

The result of an add facet to object batch operation.

Type: [BatchAddFacetToObjectResponse](#) (p. 267) object

Required: No

### AttachObject

Attaches an object to a [Directory](#) (p. 342).

Type: [BatchAttachObjectResponse](#) (p. 269) object

Required: No

### AttachPolicy

Attaches a policy object to a regular object. An object can have a limited number of attached policies.

Type: [BatchAttachPolicyResponse](#) (p. 271) object

Required: No

### AttachToIndex

Attaches the specified object to the specified index.

Type: [BatchAttachToIndexResponse](#) (p. 273) object

Required: No

### AttachTypedLink

Attaches a typed link to a specified source and target object. For more information, see [Typed Links](#).

Type: [BatchAttachTypedLinkResponse](#) (p. 275) object

Required: No

### CreateIndex

Creates an index object. See [Indexing and search](#) for more information.

Type: [BatchCreateIndexResponse](#) (p. 278) object

Required: No

### CreateObject

Creates an object in a [Directory](#) (p. 342).

Type: [BatchCreateObjectResponse](#) (p. 281) object

Required: No

### DeleteObject

Deletes an object in a [Directory](#) (p. 342).

Type: [BatchDeleteObjectResponse](#) (p. 283) object

Required: No

#### **DetachFromIndex**

Detaches the specified object from the specified index.

Type: [BatchDetachFromIndexResponse](#) (p. 285) object

Required: No

#### **DetachObject**

Detaches an object from a [Directory](#) (p. 342).

Type: [BatchDetachObjectResponse](#) (p. 287) object

Required: No

#### **DetachPolicy**

Detaches a policy from a [Directory](#) (p. 342).

Type: [BatchDetachPolicyResponse](#) (p. 289) object

Required: No

#### **DetachTypedLink**

Detaches a typed link from a specified source and target object. For more information, see [Typed Links](#).

Type: [BatchDetachTypedLinkResponse](#) (p. 291) object

Required: No

#### **RemoveFacetFromObject**

The result of a batch remove facet from object operation.

Type: [BatchRemoveFacetFromObjectResponse](#) (p. 331) object

Required: No

#### **UpdateLinkAttributes**

Represents the output of a `BatchWrite` response operation.

Type: [BatchUpdateLinkAttributesResponse](#) (p. 333) object

Required: No

#### **UpdateObjectAttributes**

Updates a given object's attributes.

Type: [BatchUpdateObjectAttributesResponse](#) (p. 335) object

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# Directory

Directory structure that includes the directory name and directory ARN.

## Contents

### **CreationDateTime**

The date and time when the directory was created.

Type: Timestamp

Required: No

### **DirectoryArn**

The Amazon Resource Name (ARN) that is associated with the directory. For more information, see [Arn Examples \(p. 371\)](#).

Type: String

Required: No

### **Name**

The name of the directory.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: No

### **State**

The state of the directory. Can be either `Enabled`, `Disabled`, or `Deleted`.

Type: String

Valid Values: `ENABLED` | `DISABLED` | `DELETED`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# Facet

A structure that contains Name, ARN, Attributes, [Rule \(p. 359\)](#)s, and ObjectTypes. See [Facets](#) for more information.

## Contents

### FacetStyle

There are two different styles that you can define on any given facet, `Static` and `Dynamic`. For static facets, all attributes must be defined in the schema. For dynamic facets, attributes can be defined during data plane operations.

Type: String

Valid Values: `STATIC` | `DYNAMIC`

Required: No

### Name

The name of the [Facet \(p. 343\)](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: No

### ObjectType

The object type that is associated with the facet. See [CreateFacet:ObjectType \(p. 51\)](#) for more details.

Type: String

Valid Values: `NODE` | `LEAF_NODE` | `POLICY` | `INDEX`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# FacetAttribute

An attribute that is associated with the [Facet](#) (p. 343).

## Contents

### AttributeDefinition

A facet attribute consists of either a definition or a reference. This structure contains the attribute definition. See [Attribute References](#) for more information.

Type: [FacetAttributeDefinition](#) (p. 345) object

Required: No

### AttributeReference

An attribute reference that is associated with the attribute. See [Attribute References](#) for more information.

Type: [FacetAttributeReference](#) (p. 346) object

Required: No

### Name

The name of the facet attribute.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

Required: Yes

### RequiredBehavior

The required behavior of the `FacetAttribute`.

Type: String

Valid Values: `REQUIRED_ALWAYS` | `NOT_REQUIRED`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# FacetAttributeDefinition

A facet attribute definition. See [Attribute References](#) for more information.

## Contents

### DefaultValue

The default value of the attribute (if configured).

Type: [TypedAttributeValue](#) (p. 362) object

Required: No

### Immutable

Whether the attribute is mutable or not.

Type: Boolean

Required: No

### Rules

Validation rules attached to the attribute definition.

Type: String to [Rule](#) (p. 359) object map

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Key Pattern: `^[a-zA-Z0-9._-]*$`

Required: No

### Type

The type of the attribute.

Type: String

Valid Values: `STRING` | `BINARY` | `BOOLEAN` | `NUMBER` | `DATETIME` | `VARIANT`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# FacetAttributeReference

The facet attribute reference that specifies the attribute definition that contains the attribute facet name and attribute name.

## Contents

### TargetAttributeName

The target attribute name that is associated with the facet reference. See [Attribute References](#) for more information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

Required: Yes

### TargetFacetName

The target facet name that is associated with the facet reference. See [Attribute References](#) for more information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# FacetAttributeUpdate

A structure that contains information used to update an attribute.

## Contents

### Action

The action to perform when updating the attribute.

Type: String

Valid Values: `CREATE_OR_UPDATE` | `DELETE`

Required: No

### Attribute

The attribute to update.

Type: [FacetAttribute](#) (p. 344) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# IndexAttachment

Represents an index and an attached object.

## Contents

### **IndexedAttributes**

The indexed attribute values.

Type: Array of [AttributeKeyAndValue](#) (p. 264) objects

Required: No

### **ObjectIdentifier**

In response to [ListIndex](#) (p. 169), the `ObjectIdentifier` of the object attached to the index. In response to [ListAttachedIndices](#) (p. 140), the `ObjectIdentifier` of the index attached to the object. This field will always contain the `ObjectIdentifier` of the object on the opposite side of the attachment specified in the query.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# LinkAttributeAction

The action to take on a typed link attribute value. Updates are only supported for attributes which don't contribute to link identity.

## Contents

### AttributeActionType

A type that can be either `UPDATE_OR_CREATE` or `DELETE`.

Type: String

Valid Values: `CREATE_OR_UPDATE` | `DELETE`

Required: No

### AttributeUpdateValue

The value that you want to update to.

Type: [TypedAttributeValue \(p. 362\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# LinkAttributeUpdate

Structure that contains attribute update information.

## Contents

### **AttributeAction**

The action to perform as part of the attribute update.

Type: [LinkAttributeAction](#) (p. 349) object

Required: No

### **AttributeKey**

The key of the attribute being updated.

Type: [AttributeKey](#) (p. 263) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# ObjectAttributeAction

The action to take on the object attribute.

## Contents

### **ObjectAttributeActionType**

A type that can be either `Update` or `Delete`.

Type: String

Valid Values: `CREATE_OR_UPDATE` | `DELETE`

Required: No

### **ObjectAttributeUpdateValue**

The value that you want to update to.

Type: [TypedAttributeValue \(p. 362\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# ObjectAttributeRange

A range of attributes.

## Contents

### AttributeKey

The key of the attribute that the attribute range covers.

Type: [AttributeKey](#) (p. 263) object

Required: No

### Range

The range of attribute values being selected.

Type: [TypedAttributeValueRange](#) (p. 363) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# ObjectAttributeUpdate

Structure that contains attribute update information.

## Contents

### **ObjectAttributeAction**

The action to perform as part of the attribute update.

Type: [ObjectAttributeAction](#) (p. 351) object

Required: No

### **ObjectAttributeKey**

The key of the attribute being updated.

Type: [AttributeKey](#) (p. 263) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# ObjectIdentifierAndLinkNameTuple

A pair of ObjectIdentifier and LinkName.

## Contents

### LinkName

The name of the link between the parent and the child object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [ ^\[/\[ \] \ ( \ ) : \ { \ } # @ ! ? \ \$ \ \ ; \ ] +

Required: No

### ObjectIdentifier

The ID that is associated with the object.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# ObjectReference

The reference that identifies an object.

## Contents

### Selector

A path selector supports easy selection of an object by the parent/child links leading to it from the directory root. Use the link names from each parent/child link to construct the path. Path selectors start with a slash (/) and link names are separated by slashes. For more information about paths, see [Access Objects](#). You can identify an object in one of the following ways:

- *\$ObjectIdentifier* - An object identifier is an opaque string provided by Amazon Cloud Directory. When creating objects, the system will provide you with the identifier of the created object. An object's identifier is immutable and no two objects will ever share the same object identifier
- */some/path* - Identifies the object based on path
- *#SomeBatchReference* - Identifies the object in a batch call

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# PathToObjectIdentifiers

Returns the path to the `ObjectIdentifiers` that is associated with the directory.

## Contents

### **ObjectIdentifiers**

Lists `ObjectIdentifiers` starting from directory root to the object in the request.

Type: Array of strings

Required: No

### **Path**

The path that is used to identify the object starting from directory root.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# PolicyAttachment

Contains the `PolicyType`, `PolicyId`, and the `ObjectIdentifier` to which it is attached. For more information, see [Policies](#).

## Contents

### **ObjectIdentifier**

The `ObjectIdentifier` that is associated with `PolicyAttachment`.

Type: String

Required: No

### **PolicyId**

The ID of `PolicyAttachment`.

Type: String

Required: No

### **PolicyType**

The type of policy that can be associated with `PolicyAttachment`.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# PolicyToPath

Used when a regular object exists in a [Directory](#) (p. 342) and you want to find all of the policies that are associated with that object and the parent to that object.

## Contents

### Path

The path that is referenced from the root.

Type: String

Required: No

### Policies

List of policy objects.

Type: Array of [PolicyAttachment](#) (p. 357) objects

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# Rule

Contains an Amazon Resource Name (ARN) and parameters that are associated with the rule.

## Contents

### Parameters

The minimum and maximum parameters that are associated with the rule.

Type: String to string map

Required: No

### Type

The type of attribute validation rule.

Type: String

Valid Values: `BINARY_LENGTH` | `NUMBER_COMPARISON` | `STRING_FROM_SET` | `STRING_LENGTH`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# SchemaFacet

A facet.

## Contents

### FacetName

The name of the facet. If this value is set, SchemaArn must also be set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: No

### SchemaArn

The ARN of the schema that contains the facet with no minor component. See [Arn Examples \(p. 371\)](#) and [In-Place Schema Upgrade](#) for a description of when to provide minor versions. If this value is set, FacetName must also be set.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# Tag

The tag structure that contains a tag key and value.

## Contents

### Key

The key that is associated with the tag.

Type: String

Required: Yes

### Value

The value that is associated with the tag.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# TypedAttributeValue

Represents the data for a typed attribute. You can set one, and only one, of the elements. Each attribute in an item is a name-value pair. Attributes have a single value.

## Contents

### **BinaryValue**

A binary data value.

Type: Base64-encoded binary data object

Required: No

### **BooleanValue**

A Boolean data value.

Type: Boolean

Required: No

### **DatetimeValue**

A date and time value.

Type: Timestamp

Required: No

### **NumberValue**

A number data value.

Type: String

Required: No

### **StringValue**

A string data value.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# TypedAttributeValueRange

A range of attribute values. For more information, see [Range Filters](#).

## Contents

### EndMode

The inclusive or exclusive range end.

Type: String

Valid Values: `FIRST` | `LAST` | `LAST_BEFORE_MISSING_VALUES` | `INCLUSIVE` | `EXCLUSIVE`

Required: Yes

### EndValue

The attribute value to terminate the range at.

Type: [TypedAttributeValue \(p. 362\)](#) object

Required: No

### StartMode

The inclusive or exclusive range start.

Type: String

Valid Values: `FIRST` | `LAST` | `LAST_BEFORE_MISSING_VALUES` | `INCLUSIVE` | `EXCLUSIVE`

Required: Yes

### StartValue

The value to start the range at.

Type: [TypedAttributeValue \(p. 362\)](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# TypedLinkAttributeDefinition

A typed link attribute definition.

## Contents

### DefaultValue

The default value of the attribute (if configured).

Type: [TypedAttributeValue](#) (p. 362) object

Required: No

### Immutable

Whether the attribute is mutable or not.

Type: Boolean

Required: No

### Name

The unique name of the typed link attribute.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

### RequiredBehavior

The required behavior of the `TypedLinkAttributeDefinition`.

Type: String

Valid Values: `REQUIRED_ALWAYS` | `NOT_REQUIRED`

Required: Yes

### Rules

Validation rules that are attached to the attribute definition.

Type: String to [Rule](#) (p. 359) object map

Key Length Constraints: Minimum length of 1. Maximum length of 64.

Key Pattern: `^[a-zA-Z0-9._-]*$`

Required: No

### Type

The type of the attribute.

Type: String

Valid Values: `STRING` | `BINARY` | `BOOLEAN` | `NUMBER` | `DATETIME` | `VARIANT`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# TypedLinkAttributeRange

Identifies the range of attributes that are used by a specified filter.

## Contents

### AttributeName

The unique name of the typed link attribute.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

Required: No

### Range

The range of attribute values that are being selected.

Type: [TypedAttributeValueRange](#) (p. 363) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)



# TypedLinkFacet

Defines the typed links structure and its attributes. To create a typed link facet, use the [CreateTypedLinkFacet \(p. 66\)](#) API.

## Contents

### Attributes

A set of key-value pairs associated with the typed link. Typed link attributes are used when you have data values that are related to the link itself, and not to one of the two objects being linked. Identity attributes also serve to distinguish the link from others of the same type between the same objects.

Type: Array of [TypedLinkAttributeDefinition \(p. 364\)](#) objects

Required: Yes

### IdentityAttributeOrder

The set of attributes that distinguish links made from this facet from each other, in the order of significance. Listing typed links can filter on the values of these attributes. See [ListOutgoingTypedLinks \(p. 196\)](#) and [ListIncomingTypedLinks \(p. 163\)](#) for details.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 230.

Pattern: `^[a-zA-Z0-9._:-]*$`

Required: Yes

### Name

The unique name of the typed link facet.

Type: String

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# TypedLinkFacetAttributeUpdate

A typed link facet attribute update.

## Contents

### Action

The action to perform when updating the attribute.

Type: String

Valid Values: `CREATE_OR_UPDATE` | `DELETE`

Required: Yes

### Attribute

The attribute to update.

Type: [TypedLinkAttributeDefinition](#) (p. 364) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# TypedLinkSchemaAndFacetName

Identifies the schema Amazon Resource Name (ARN) and facet name for the typed link.

## Contents

### SchemaArn

The Amazon Resource Name (ARN) that is associated with the schema. For more information, see [Arn Examples \(p. 371\)](#).

Type: String

Required: Yes

### TypedLinkName

The unique name of the typed link facet.

Type: String

Pattern: `^[a-zA-Z0-9._-]*$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# TypedLinkSpecifier

Contains all the information that is used to uniquely identify a typed link. The parameters discussed in this topic are used to uniquely specify the typed link being operated on. The [AttachTypedLink \(p. 23\)](#) API returns a typed link specifier while the [DetachTypedLink \(p. 96\)](#) API accepts one as input. Similarly, the [ListIncomingTypedLinks \(p. 163\)](#) and [ListOutgoingTypedLinks \(p. 196\)](#) API operations provide typed link specifiers as output. You can also construct a typed link specifier from scratch.

## Contents

### IdentityAttributeValues

Identifies the attribute value to update.

Type: Array of [AttributeNameAndValue \(p. 265\)](#) objects

Required: Yes

### SourceObjectReference

Identifies the source object that the typed link will attach to.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### TargetObjectReference

Identifies the target object that the typed link will attach to.

Type: [ObjectReference \(p. 355\)](#) object

Required: Yes

### TypedLinkFacet

Identifies the typed link facet that is associated with the typed link.

Type: [TypedLinkSchemaAndFacetName \(p. 369\)](#) object

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

# Arn Examples

The following examples are separated by ARN types and show how they can be constructed for each schema state (where applicable). A schema can exist in three states:

- *Development*: This is a mutable state of the schema. All new schemas are in the development state. Once the schema is finalized, it can be published. All development schemas are under the development sub root of the schema metadata container.
- *Published*: Published schemas are immutable and have a version associated with them. All published schemas are under the published sub root of the schema container.
- *Applied*: Applied schemas are mutable in a way that allows you to add new schema facets. However, existing schema facets cannot be changed. You can apply only published schemas to directories. You can't apply schemas at the node level, but only at the directory root level.

## Schema Arns

State	Format or Example	Schema Arn
Development	Format	arn:aws:clouddirectory:us-west-2: <b>accountId</b> :schema/development/ <i>SchemaName</i>
	Example	arn:aws:clouddirectory:us-west-2:12345678910:schema/development/cognito
Published	Format	arn:aws:clouddirectory:us-west-2: <b>accountId</b> :schema/published/ <i>SchemaName</i> / <i>SchemaVersion</i>
	Example	arn:aws:clouddirectory:us-west-2:12345678910:schema/published/cognito/1.0
	Format	arn:aws:clouddirectory:us-west-2: <b>accountId</b> :schema/published/ <i>SchemaName</i> / <i>SchemaVersion</i> / <i>SchemaMinorVersion</i>
	Example	arn:aws:clouddirectory:us-west-2:12345678910:schema/published/cognito/1.0/XYZ
Applied	Format	arn:aws:clouddirectory:us-west-2: <b>accountId</b> :directory/ <i>directoryId</i> / <i>SchemaName</i> / <i>SchemaVersion</i>
	Example	arn:aws:clouddirectory:us-west-2:12345678910:directory/ARIqk1HD-UjdtmcIrJHEvPI/schema/cognito/1.0
	Format	arn:aws:clouddirectory:us-west-2: <b>accountId</b> :directory/ <i>directoryId</i> / <i>SchemaName</i> / <i>SchemaVersion</i> / <i>SchemaMinorVersion</i>

State	Format or Example	Schema Arn
	Example	<code>arn:aws:clouddirectory:us-west-2:12345678910:directory/ARIqk1HD-UjdtmcIrJHEvPI/schema/cognito/1.0/XYZ</code>

## Directory Arns

Arn Type	Format or example	Arn
Directory Arn	Format	<code>arn:aws:clouddirectory:us-west-2:<i>Directory owner accountId</i>:directory/<i>directoryId</i></code>
	Example	<code>arn:aws:clouddirectory:us-west-2:12345678910:directory/ARIqk1HD-UjdtmcIrJHEvPI</code>

# Logging Cloud Directory API Calls with CloudTrail

Amazon Cloud Directory is integrated with AWS CloudTrail, a service that captures all of the Cloud Directory API calls and delivers the log files to an Amazon S3 bucket that you specify. CloudTrail captures API calls from the Cloud Directory section of the AWS Directory Service console or from your code to the Cloud Directory APIs. Using the information collected by CloudTrail, you can determine the request that was made to Cloud Directory, the source IP address from which the request was made, who made the request, when it was made, and so on. To learn more about CloudTrail, see the [AWS CloudTrail User Guide](#).

## Cloud Directory Information in CloudTrail

CloudTrail is enabled on your AWS account when you create the account. When supported event activity occurs in Cloud Directory, that activity is recorded in a CloudTrail event along with other AWS service events in **Event history**. You can view, search, and download recent events in your AWS account. For more information, see [Viewing Events with CloudTrail Event History](#).

For an ongoing record of events in your AWS account, including events for Cloud Directory, create a trail. A *trail* enables CloudTrail to deliver log files to an Amazon S3 bucket. By default, when you create a trail in the console, the trail applies to all AWS Regions. The trail logs events from all Regions in the AWS partition and delivers the log files to the Amazon S3 bucket that you specify. Additionally, you can configure other AWS services to further analyze and act upon the event data collected in CloudTrail logs. For more information, see the following:

- [Overview for Creating a Trail](#)
- [CloudTrail Supported Services and Integrations](#)
- [Configuring Amazon SNS Notifications for CloudTrail](#)
- [Receiving CloudTrail Log Files from Multiple Regions](#) and [Receiving CloudTrail Log Files from Multiple Accounts](#)

When CloudTrail logging is enabled in your AWS account, API calls made to Cloud Directory actions are tracked in CloudTrail log files, where they are written with other AWS service records. CloudTrail determines when to create and write to a new file based on a time period and file size.

The following Cloud Directory actions are logged by CloudTrail and are documented in this API Reference guide.

- [ApplySchema](#) (p. 8)
- [CreateDirectory](#) (p. 46)
- [CreateFacet](#) (p. 50)
- [CreateSchema](#) (p. 63)
- [DeleteDirectory](#) (p. 70)
- [DeleteFacet](#) (p. 73)
- [DeleteSchema](#) (p. 79)
- [DisableDirectory](#) (p. 100)
- [EnableDirectory](#) (p. 103)

- [GetDirectory](#) (p. 109)
- [GetFacet](#) (p. 112)
- [GetSchemaAsJson](#) (p. 128)
- [ListAppliedSchemaArns](#) (p. 136)
- [ListDevelopmentSchemaArns](#) (p. 144)
- [ListDirectories](#) (p. 148)
- [ListFacetAttributes](#) (p. 152)
- [ListFacetNames](#) (p. 159)
- [ListManagedSchemaArns](#) (p. 174)
- [ListPublishedSchemaArns](#) (p. 205)
- [ListTagsForResource](#) (p. 208)
- [PublishSchema](#) (p. 222)
- [PutSchemaFromJson](#) (p. 225)
- [TagResource](#) (p. 231)
- [UpdateFacet](#) (p. 237)
- [UpdateSchema](#) (p. 247)
- [UntagResource](#) (p. 234)

For example, calls to the **ApplySchema**, **ListDirectories** and **CreateSchema** sections generate entries in the CloudTrail log files.

Every log entry contains information about who generated the request. The user identity information in the log entry helps you determine the following:

- Whether the request was made with root or IAM user credentials
- Whether the request was made with temporary security credentials for a role or federated user
- Whether the request was made by another AWS service

For more information, see the [CloudTrail userIdentity Element](#).

You can store your log files in your Amazon S3 bucket for as long as you want, but you can also define Amazon S3 lifecycle rules to archive or delete log files automatically. By default, your log files are encrypted with Amazon S3 server-side encryption (SSE).

If you want to be notified upon log file delivery, you can configure CloudTrail to publish Amazon SNS notifications when new log files are delivered. For more information, see [Configuring Amazon SNS Notifications for CloudTrail](#).

You can also aggregate Cloud Directory log files from multiple AWS regions and multiple AWS accounts into a single Amazon S3 bucket. For more information, see [Receiving CloudTrail Log Files from Multiple Regions](#) and [Receiving CloudTrail Log Files from Multiple Accounts](#).

## Understanding Cloud Directory Log File Entries

CloudTrail log files can contain one or more log entries. Each entry lists multiple JSON-formatted events. A log entry represents a single request from any source and includes information about the requested action, the date and time of the action, request parameters, and so on. Log entries are not an ordered stack trace of the public API calls, so they do not appear in any specific order.

Sensitive information, such as passwords, authentication tokens, file comments, and file contents are redacted in the log entries.



The following example shows a CloudTrail log entry that demonstrates the following Cloud Directory actions:

- ApplySchema
- ListDirectories
- CreateSchema

```
ApplySchema:
{
  "eventVersion": "1.05",
  "userIdentity": {
    "type": "IAMUser",
    "principalId": "ASDFLKJHEXAMPLE1QWERT",
    "arn": "arn:aws:iam::11223Example:user/nickpi",
    "accountId": "11223Example",
    "accessKeyId": "ALSJDJFHGQPWExample",
    "userName": "nickpi"
  },
  "eventTime": "2017-01-06T00:09:08Z",
  "eventSource": "clouddirectory.amazonaws.com",
  "eventName": "ApplySchema",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.92",
  "userAgent": "Apache-HttpClient/4.3 (java 1.5)",
  "requestParameters": {
    "directoryArn": "arn:aws:clouddirectory:us-east-1:11223Example:directory/
AsCGClGIlkIqweR836u9pyU",
    "publishedSchemaArn": "arn:aws:clouddirectory:us-east-1:11223Example:schema/
published/simple_org-123456/1.0"
  },
  "responseElements": {
    "directoryArn": "arn:aws:clouddirectory:us-east-1:11223Example:directory/
AsCGClGIlkIqweR836u9pyU",
    "appliedSchemaArn": "arn:aws:clouddirectory:us-east-1:11223Example:directory/
AsCGClGIlkIqweR836u9pyU/schema/simple_org-123456/1.0"
  },
  "requestID": "12j45lk0-a1s2-00ie-b180-2b70510bd66f",
  "eventID": "733409ba-a869-4e7b-95a1-4d5d204e697c",
  "eventType": "AwsApiCall",
  "recipientAccountId": "11223Example"
}

ListDirectories:
{
  "eventVersion": "1.05",
  "userIdentity": {
    "type": "IAMUser",
    "principalId": "ASDFLKJHEXAMPLE1QWERT",
    "arn": "arn:aws:iam::11223Example:user/nickpi",
    "accountId": "11223Example",
    "accessKeyId": "ALSJDJFHGQPWExample",
    "userName": "nickpi"
  },
  "eventTime": "2017-01-06T00:09:54Z",
  "eventSource": "clouddirectory.amazonaws.com",
  "eventName": "ListDirectories",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.92",
  "userAgent": "Apache-HttpClient/4.3 (java 1.5)",
  "requestParameters": {
    "maxResults": 10
  },
  "responseElements": null,
}
```

```
"requestID": "56j45100-a1s2-00ie-b180-2b70660bd66f",
"eventID": "uwjdf8-f003-4ef7-b15d-8a34149479ac",
"eventType": "AwsApiCall",
"recipientAccountId": "11223Example"
}

CreateSchema:
{
  "eventVersion": "1.05",
  "userIdentity": {
    "type": "IAMUser",
    "principalId": "ASDFLKJHEXAMPLE1QWERT",
    "arn": "arn:aws:iam::11223Example:user/nickpi",
    "accountId": "11223Example",
    "accessKeyId": "ALSKDJFHGQPWOExample",
    "userName": "nickpi"
  },
  "eventTime": "2017-01-06T00:08:54Z",
  "eventSource": "clouddirectory.amazonaws.com",
  "eventName": "CreateSchema",
  "awsRegion": "us-east-1",
  "sourceIPAddress": "192.0.2.92",
  "userAgent": "Apache-HttpClient/4.3 (java 1.5)",
  "requestParameters": {
    "name": "newName-111"
  },
  "responseElements": {
    "schemaArn": "arn:aws:clouddirectory:us-east-1:11223Example:schema/development/
newName-111"
  },
  "requestID": "4jshkjsg-d3a4-11e6-b180-dfhkasdh",
  "eventID": "skdjf-0acb-426c-b64b-fsaj",
  "eventType": "AwsApiCall",
  "recipientAccountId": "11223Example"
}
```

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signature Version 4 Signing Process](#) in the *Amazon Web Services General Reference*.

**Action**

The action to be performed.

Type: string

Required: Yes

**Version**

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

**X-Amz-Algorithm**

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

**X-Amz-Credential**

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: `access_key/YYYYMMDD/region/service/aws4_request`.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

**X-Amz-Date**

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'THHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is

not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

**X-Amz-Security-Token**

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS Security Token Service, go to [AWS Services That Work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

**X-Amz-Signature**

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

**X-Amz-SignedHeaders**

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

# Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

**AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

**IncompleteSignature**

The request signature does not conform to AWS standards.

HTTP Status Code: 400

**InternalFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

**InvalidAction**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

**InvalidClientTokenId**

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

**InvalidParameterCombination**

Parameters that must not be used together were used together.

HTTP Status Code: 400

**InvalidParameterValue**

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

**InvalidQueryParameter**

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

**MalformedQueryString**

The query string contains a syntax error.

HTTP Status Code: 404

**MissingAction**

The request is missing an action or a required parameter.

HTTP Status Code: 400

**MissingAuthenticationToken**

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

**MissingParameter**

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

**OptInRequired**

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

**RequestExpired**

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

**ServiceUnavailable**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

**ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

**ValidationError**

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

# Document History

The following table describes the important changes to the documentation in this release of the Amazon Cloud Directory API Reference.

- **Latest documentation update:** May 23, 2018

Change	Description	Release Date
Typed links	Added the <a href="#">GetLinkAttributes (p. 116)</a> and <a href="#">UpdateLinkAttributes (p. 241)</a> APIs for <a href="#">Typed Links</a> .	May 23, 2018
New API	Added the <a href="#">GetObjectAttributes (p. 120)</a> API.	April 10, 2018
In-Place Schema Upgrade	Added new APIs to support <a href="#">In-Place Schema Upgrade</a> feature.	December 6, 2017
Batch updates	Added several new Read and Write batch operation APIs	July 25, 2017
Typed links	Additional APIs for new <a href="#">Typed Links</a> feature	May 31, 2017
New guide	This is the first release of the Amazon Cloud Directory API Reference Guide.	January 26, 2017