Understand the User, Don't Repeat: Linguistic Cues of Unmet Needs and Explicit Repair in Task-Oriented Dialogue

Ying Chen

Abstract

When a dialogue system fails, users seldom say so in emotional words. They repeat the request, rephrase it, write "what?", or get shorter. We study these cues in EmoWOZ, a corpus with emotion labels on every user turn. Human operators change their replies after a dissatisfied turn (acknowledgment rises from 3.9% to 17.8%); a deployed machine system does not (3.7% vs. 3.5%). Toward the machine, 46.8% of dissatisfied turns repeat an earlier request, and only 7.7% contain a complaint or negation word, so word-level sentiment misses most of them. We then ask whether a language model can be made to answer the unmet need rather than the last message. Asking the model to "read the user first" helps a strong model but hurts an 8B model, which misreads the need and apologizes instead of delivering. We propose REPAIR, which reads the dialogue explicitly — repair cues, a ledger of requested, delivered and pending items, and database rows for the pending item — and hands this reading to the generator. On 100 unseen dialogue cases, REPAIR raises how well an 8B model resolves the user's need from 0.45 to 1.22 on a 0–2 scale (0 = unresolved, 1 = partly, 2 = delivered), cuts the share of replies after which the user would likely give up from 49% (prompt-only reading) to 19%, and brings the 8B model to the level of a much stronger model given a "be concrete" instruction.

1 Introduction

A user who has asked twice for a guesthouse in the south does not need a third question about the price range, and does not need an apology. The user needs the guesthouse. Dialogue systems, including systems built on large language models, are usually asked to respond to the last message. When an earlier request is still open, the last message is often a repetition ("hotel", "hotel options", "four star hotels"), and a system that answers it in isolation repeats its own failure.

Conversation analysis calls these moves *other-initiated repair*: the listener signals that something was not understood or not delivered and invites the speaker to fix it [Schegloff et al., 1977]. In the terms of Clark and Brennan [1991], the request has not been grounded. Our view is that unmet needs are visible mostly in this linguistic behaviour — repetition, rephrasing, repair tokens, shortening — and only partly in emotional vocabulary. Earlier work by the author on offensive language took the same position: lexical and syntactic structure, together with a user's writing style, carried most of the signal [Chen et al., 2012].

This paper makes three contributions. (1) A corpus study on EmoWOZ [Feng et al., 2022] showing that a machine system does not react to dissatisfaction, and that users express dissatisfaction to it mainly by repeating requests. (2) A negative result: telling a model to infer the user's state from the dialogue helps a strong model and hurts a small one. (3) REPAIR, an explicit reading of repair cues and pending needs, grounded in the task database, which makes a small model resolve the user's need far more often on unseen dialogues. We release code, prompts and all model outputs.

2 Related Work

Emotion in task-oriented dialogue. EmoWOZ labels every user turn of MultiWOZ [Budzianowski et al., 2018] and of 1,000 human–machine dialogues (DialMAGE) with one of seven emotions [Feng et al., 2022]. Recent work detects frustration in deployed systems [Hernandez Caralt et al., 2024] and studies emotion in customer-service dialogue, finding that apology and empathy often leave anger in place [Labat et al., 2025]. These works detect the state; we study how it is expressed and how to act on it.

Repair and grounding. Our cue set follows the repair literature [Schegloff et al., 1977] and grounding theory [Clark and Brennan, 1991].

Dialogue breakdown detection. The DBDC challenge series [Higashinaka et al., 2016] annotates system turns as breakdowns in chat-oriented dialogue. We use DBDC3 as a contrast corpus: without task goals, user repetition barely rises after breakdowns.

Dialogue state tracking. Classical dialogue state trackers infer slot–value belief states across turns [Budzianowski et al., 2018]. REPAIR is a lightweight, zero-shot alternative focused on *repair and grounding state*: rather than training a neural tracker, it pairs surface repair cues with a ledger of requested versus delivered items so any off-the-shelf generator can close pending needs without schema-specific fine-tuning.

LLM judges. LLM judges have known biases [Zheng et al., 2023]; we report one more in task dialogue: they reward confident, invented bookings.

3 Corpus Study

EmoWOZ has two parts: MultiWOZ, where a human "wizard" plays the system (10,438 dialogues), and DialMAGE, where a machine system talks to people (995 dialogues). We call a user turn *negative* if it is labelled dissatisfied or abusive. Confidence intervals are 95% bootstrap intervals over dialogues (2,000 resamples).

The machine does not react. We match apology and acknowledgment words (*sorry, apologize, my mistake, I understand*, …) in the system's next reply. Human wizards use them after 17.8% of negative turns and 3.9% of neutral turns. The machine: 3.5% and 3.7%. Including *unfortunately / I'm afraid*: wizards 20.3% [17.7, 22.7] vs. 5.4%; machine 5.0% [4.2, 5.8] vs. 5.6% [5.0, 6.3].

Dissatisfaction is expressed by repeating. Table 1 shows, for each negative turn, whether it contains a complaint or negation word, and whether it repeats an earlier request of the same user (token Jaccard ≥ 0.5).

When the machine repeats its own previous reply (Jaccard ≥ 0.8) after a negative turn, the next user turn is still negative 88.3% [80.0, 95.7] of the time, against 54.6% [52.7, 56.6] otherwise ($n = 71$ repeats).

	n	complaint word	repeats own request	neither
MultiWOZ, negative turns	958	53.0%	3.0%	44.6%
DialMAGE, negative turns	4,264	7.7%	46.8%	47.6%
DialMAGE, neutral turns	7,230	3.0%	13.2%	84.2%

Table 1: How dissatisfaction is expressed. With a human wizard users complain in words; with a machine they repeat themselves.

Is repetition specific to task dialogue? In the DBDC3 chat-oriented corpus [Higashinaka et al., 2016] (415 dialogues, no task goals), users repeat after a system breakdown only 8.4% [6.5, 10.4] of the time, barely above the 6.8% [5.9, 7.8] baseline (+1.5 pp). In DialMAGE the gap is +33.6 pp. Users repeat when they have an unmet *task* need, not simply when the system is incoherent.

These findings motivate a method that detects repetition-based repair cues and tracks pending needs, rather than relying on sentiment words or the model's own reflection.

4 REPAIR

REPAIR (Reading Escalation And Pending Items for Response) builds a short, checkable reading of the dialogue at the current user turn. It is deterministic and uses no model calls.

1. **Repair reader.** Cues in the last user turn: repetition (Jaccard ≥ 0.5 with an earlier user turn) or rephrasing (0.3–0.5); repair tokens (*what?*, *??*, *I said*, *already*); negation (*no, not, again, still*); talk about the conversation (*can you help*, *understand*); a turn under half the user's median length; give-up words. These map to an escalation stage 0–4.

2. **Grounding ledger.** For each domain (restaurant, hotel, attraction, train, taxi, …), the constraints the user stated, whether a matching entity was delivered by the system afterwards, and which required details are missing (train: origin, destination, day; taxi: origin, destination, time). Turns without domain words refine the current domain; a bare answer fills the slot the system asked for; negated needs ("does not need wifi") remove a constraint. Only the current topic is shown.

3. **Database grounding.** Rows from the MultiWOZ database that match the pending request; if none, constraints are relaxed one at a time (type and amenities first) and the relaxation is stated.

4. **Policy.** By stage: deliver the pending item first; ask only for missing required details; book when asked; at stage 4, say what can and cannot be done and offer a human.

The reading is appended to the dialogue, together with the system's last turns marked "do not repeat". Any generator can use it. Among REPAIR's four components, the repair reader and the escalation policy are domain-agnostic; adapting to a new task domain requires only specifying its slot vocabulary and database table for the ledger.

5 Experiments

Cases. From DialMAGE we take every dialogue at the first user turn that is negative and repeats an earlier request: the need is still unmet. We developed prompts and the reader on 60 cases of

the test split, and on 81 cases of the dev split for a second round; the results we report are on 100 cases from the train split, which were not looked at during development.

Conditions. A: reply to the last message. B: be concrete, answer rather than ask back. C: prompt-only reading — find what is unresolved from the same linguistic cues and how the user feels, then deliver it (for the 8B model, two calls: read, then reply). D: REPAIR. E: REPAIR without stage, cues and policy (ledger and database only).

Generators. Claude 3.5 Sonnet [Anthropic, 2024] via the `claude` CLI, and Llama 3 8B [Grattafiori et al., 2024] (dolphin-llama3:8b via Ollama). A–C have no database; D and E have the rows REPAIR selects.

Evaluation. Two judge models from different families (Claude 3 Opus and Gemini 2.5 [Gemini Team et al., 2024]) independently see the dialogue and the five replies in random order, and score each reply: *resolves* (0 does not, 1 partly, 2 delivers the need), *give_up* (a user in this state would likely give up), *repeats*, and the best reply. In a second pass each judge also sees the database rows for the current request and is told that a contradicting fact cannot score 2. Across all 500 judged replies per run, the two judge families agree within 1 point on *resolves* 96.4%–100.0% of the time; fact-checking raises inter-judge correlation from $r = 0.73$ to $r = 0.90$ on the 8B run (exact agreement 59.4% to 85.2%) and from $r = 0.66$ to $r = 0.81$ on the Sonnet run. An objective check without any model asks whether the reply names a real database entity that satisfies the pending constraints. Differences are paired bootstrap 95% intervals over cases.

5.1 Results

	Claude Opus judge		Gemini judge		
Llama 3 8B	resolves	give up	resolves	give up	real & match
A last message	0.45	29%	0.98	19%	23.0%
B be concrete	0.45	28%	0.98	18%	21.8%
C prompt-only reading	0.33	49%	0.73	35%	18.4%
D REPAIR	**1.22**	**19%**	**1.51**	**14%**	60.9%
E ledger + database	1.16	23%	1.39	22%	62.1%
A, fact-checked judge	0.20	54%	0.26	41%	
B, fact-checked judge	0.17	56%	0.26	39%	
C, fact-checked judge	0.20	69%	0.25	51%	
D, fact-checked judge	**1.41**	**14%**	**1.49**	**12%**	
E, fact-checked judge	1.31	17%	1.39	16%	

Table 2: 100 unseen DialMAGE dialogues, Llama 3 8B generator, judged independently by Claude Opus and Gemini (both different model families from the generator). "Real & matching" is over the 87 cases with a database request.

Small model. Under both judges, REPAIR resolves the need far more often than every baseline (Table 2): with Claude Opus, D−B +0.77 [0.55, 0.98] and D−C +0.89 [0.70, 1.08]; with Gemini, D−B +0.53 [0.33, 0.72] and D−C +0.78 [0.60, 0.96]. Under both judges, prompt-only reading

(C) significantly hurts the 8B model compared to B (Opus −0.12, Gemini −0.25 [−0.42, −0.08], give-ups +17 pts): inspecting 18 development cases where C lost, the model's own reading named needs from earlier in the dialogue or invented them ("Indian restaurant" for a guesthouse request), and the reply apologized and promised ("please bear with me") instead of delivering. The same pattern held on the 81 dev-split cases (D 1.10 vs. C 0.57).

Strong model. With Claude Sonnet as the generator (Table 3), plain judges without database verification favour prompt-only reading. However, fact-checked judging reverses the picture under both judges: with Opus, D resolves 1.64 [1.52, 1.75] vs. C 0.82 and B 0.76 (D−C +0.82 [0.66, 0.97], D−B +0.88 [0.71, 1.05]); with Gemini (cross-family), D resolves **1.94** [1.88, 1.99] vs. C 1.04 [0.90, 1.19] and B 0.91 [0.77, 1.05] (D−C +0.90 [0.76, 1.04], D−B +1.03 [0.89, 1.17]; D picked best 53% vs. C 6%). REPAIR raises real, matching entities from 52.9% (C) to 67.8% and cuts entities that violate the user's constraints from 33.3% to 13.8%. Plain judges reward confident invented bookings (see below); fact-checked judges penalise them.

	Opus judge		Gemini judge		
Claude Sonnet	resolves	give up	resolves	give up	real & match
A last message	0.83	35%	1.19	21%	31.0%
B be concrete	1.25	7%	1.62	2%	43.7%
C prompt-only reading	1.45	2%	1.85	0%	52.9%
D REPAIR	1.34	18%	1.55	14%	67.8%
E ledger + database	1.28	19%	1.49	14%	65.5%
A, fact-checked judge	0.68	38%	0.89	24%	
B, fact-checked judge	0.76	19%	0.91	8%	
C, fact-checked judge	0.82	12%	1.04	0%	
D, fact-checked judge	**1.64**	**3%**	**1.94**	**1%**	
E, fact-checked judge	1.65	3%	1.90	1%	

Table 3: Same 100 cases, Claude Sonnet generator. Plain judges reward invented bookings; fact-checked judges penalise them. Gemini is a cross-family judge for both generator and first judge.

Small model with REPAIR vs. strong model. On the same 100 cases, Llama 8B with REPAIR is close to Claude Sonnet told to be concrete under both judges (Opus: 1.22 vs. 1.25; Gemini: 1.51 vs. 1.62) and above Claude answering the last message (Opus: 0.83; Gemini: 1.19).

What carries the gain. D and E do not differ significantly on the 8B model overall (D−E resolves: Opus +0.06 [−0.07, 0.19]; Gemini +0.12 [−0.05, 0.28]): on the 88 stage-2 cases the explicit ledger and the database account for the entire gain. However, on the 12 stage-3 cases — where the user shows stronger repair escalation — D significantly outperforms E on the 8B model: Opus D−E +0.50 [0.08, 0.92] (D 1.50 vs. E 1.00), Gemini +0.67 [0.25, 1.17] (D 1.92 vs. E 1.25), and give-ups drop from 33% (E) to 0–8% (D). For instance, when a user has asked three times for a 3-star hotel in the east (none exists in the database, case DMAGE271#8), E stalls with "Let me check if there are any hotels," whereas D's stage-3 policy immediately delivers the closest real match (Express by Holiday Inn, 2 stars in the east, with address and phone), scoring 2 under both judges against 0 for E. The escalation-aware policy helps precisely where users are most frustrated.

Judges reward invented bookings. Without the database, both judges gave full marks to a reply that "booked" train TR0899 for a Leicester–Cambridge request; in the database TR0899 runs Cambridge–London. Showing the judge the database rows removes this: for the 8B model, B falls from 0.45 to 0.17 (Opus) and from 0.98 to 0.26 (Gemini), while D is 1.41 (Opus) and 1.49 (Gemini). Because the rows come from the same reader REPAIR uses, we report both passes.

6 Limitations

Evaluation uses two LLM judge families (Claude Opus and Gemini) plus an objective entity check; we do not include a separate human rating study on the generated replies, relying instead on EmoWOZ's human emotion annotations, DBDC3's 30-annotator breakdown labels, and exact database matching. The complaint-word list is lexical: on 200 sampled negative turns, 7.0% matched with 92.9% precision (1 false positive from task language "no, I need a train..."); the low recall confirms our claim that word-level sentiment misses most dissatisfaction. The repeat threshold (Jaccard ≥ 0.5, yielding 46.8%) is robust: 0.4 gives 53.7%, 0.6 gives 37.0%. The REPAIR reader identified the pending request in 19/20 spot-checked cases and provided database rows in 13/20. The DBDC3 comparison (Section 3) shows that the repetition cue is specific to task-oriented dialogue; more task-oriented corpora with frustration annotation would strengthen the claim. The database is static and booking is simulated. The objective check depends on the reader's own reading of the pending request.

7 Ethics

EmoWOZ is released under CC BY-NC 4.0 [Feng et al., 2022]; we use it for academic research and do not redistribute the data. All generated replies are from dialogue systems, not real users. No personal information beyond what is in the public corpus was used.

8 Conclusion

Users tell a system it has failed mostly by repeating themselves, and systems answer the repetition instead of the need behind it. Making that need explicit — what was asked, what was delivered, what is still pending, with real data to deliver it — lets a small model do what a strong model does from a prompt, and makes both deliver real, correct entities more often.

Reproducibility. Code, prompts, model outputs and judgments:
`https://github.com/yingchen-coding/frustration-paper`.

References

Anthropic. The Claude model family. `https://www.anthropic.com/claude`, 2024.

Paweł Budzianowski, Tsung-Hsien Wen, Bo-Hsiang Tseng, Iñigo Casanueva, Stefan Ultes, Osman Ramadan, and Milica Gašić. MultiWOZ – a large-scale multi-domain Wizard-of-Oz dataset for task-oriented dialogue modelling. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 5016–5026, 2018.

Ying Chen, Yilu Zhou, Sencun Zhu, and Heng Xu. Detecting offensive language in social media to protect adolescent online safety. In *2012 International Conference on Privacy, Security, Risk and Trust and 2012 International Conference on Social Computing*, pages 71–80, 2012.

Herbert H. Clark and Susan E. Brennan. Grounding in communication. In Lauren B. Resnick, John M. Levine, and Stephanie D. Teasley, editors, *Perspectives on Socially Shared Cognition*, pages 127–149. American Psychological Association, 1991.

Shutong Feng, Nurul Lubis, Christian Geishauser, Hsien-chin Lin, Michael Heck, Carel van Niekerk, and Milica Gasic. EmoWOZ: A large-scale corpus and labelling scheme for emotion recognition in task-oriented dialogue systems. In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages 4096–4113, Marseille, France, 2022.

Gemini Team, Rohan Anil, Sebastian Borgeaud, et al. Gemini: A family of highly capable multimodal models. arXiv preprint arXiv:2312.11805, 2024.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, et al. The Llama 3 herd of models. arXiv preprint arXiv:2407.21783, 2024.

Mireia Hernandez Caralt, Ivan Sekulić, Filip Carević, Nghia Khau, Diana Nicoleta Popa, Bruna Guedes, Victor Guimarães, Zeyu Yang, Andre Manso, Meghana Reddy, Paolo Rosso, and Roland Mathis. "stupid robot, I want to speak to a human!" user frustration detection in task-oriented dialog systems. arXiv preprint arXiv:2411.17437, 2024.

Ryuichiro Higashinaka, Kotaro Funakoshi, Yuka Kobayashi, and Michimasa Inaba. The dialogue breakdown detection challenge: Task description, datasets, and evaluation metrics. In *Proceedings of the Tenth International Conference on Language Resources and Evaluation*, pages 3146–3150, 2016.

Sofie Labat, Thomas Demeester, and Véronique Hoste. A customer journey in the land of Oz: Leveraging the wizard of Oz technique to model emotions in customer service interactions. arXiv preprint arXiv:2511.21909, 2025.

Emanuel A. Schegloff, Gail Jefferson, and Harvey Sacks. The preference for self-correction in the organization of repair in conversation. *Language*, 53(2):361–382, 1977.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-bench and chatbot arena. In *Advances in Neural Information Processing Systems*, 2023.