

Challenge-2

Liu Yingzhe

2023-08-23

Welcome! Hope you have watched the lecture videos and followed the instructions in code-along. Go through the steps described below, *carefully*. It is totally fine to get stuck - ASK FOR HELP; reach out to your friends, TAs, or the discussion forum on Canvas.

Here is what you have to do,

1. Pair with a neighbor and work
2. Download the `Challenge-2.Rmd` and `playlist_data.csv` files from Canvas
3. Move the downloaded files to the folder, “Week-2”
4. Set it as the working directory
5. Edit content wherever indicated
6. Remember to set `eval=TRUE` after completing the code to generate the output
7. Ensure that `echo=TRUE` so that the code is rendered in the final document
8. Inform the tutor/instructor upon completion
9. Submit the document on Canvas after they approve
10. Attendance will be marked only after submission
11. Once again, do not hesitate to reach out to the tutors/instructor, if you are stuck

I. Exploring music preferences

A. Background

Imagine that you have been hired as a data analyst by a radio station to analyze music preferences of their DJs. They have provided you with a dataset, `playlist_data.csv`, containing information about DJs, their preferred music genres, song titles, and ratings.

Using the data-set you are required to complete some tasks that are listed subsequently. All these tasks are based on the concepts taught in the video lectures. The questions may not be entirely covered in the lectures; To complete them, you are encouraged to use Google and the resources therein.

B.Tasks

Task-1 In the lecture, we used two data-sets, `starwars` and `anscombe's quartet` that were readily available with the packages, `tidyverse` and `Tmisc`, respectively. When we have to use custom-made data-sets or the ones like we downloaded from Canvas, we have to import it using the R commands before using them. All the questions below are related to this task.

Question 1.1: What does the term “CSV” in `playlist_data.csv` stand for, and why is it a popular format for storing tabular data?

Solution: *Comma separated values, it is broadly compatible and is able to be easily read and processed.*

Question 1.2: load the `tidyverse` package to work with `.csv` files in R.

Solution:

```
# Load the necessary package to work with CSV files in R.
library(tidyverse)

## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
## v dplyr      1.1.2      v readr      2.1.4
## v forcats    1.0.0      v stringr   1.5.0
## v ggplot2    3.4.3      v tibble    3.2.1
## v lubridate  1.9.2      v tidyr     1.3.0
## v purrr      1.0.2
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

Question 1.3: Import the data-set, `playlist_data.csv`

Solution:

```
# Import the "playlist_data.csv" dataset into R
read_csv("playlist_data.csv")

## Rows: 26 Columns: 7
## -- Column specification -----
## Delimiter: ","
## chr (4): DJ_Name, Music_Genre, Experience, Location
## dbl (3): Rating, Age, Plays_Per_Week
##
## i Use 'spec()' to retrieve the full column specification for this data.
## i Specify the column types or set 'show_col_types = FALSE' to quiet this message.

## # A tibble: 26 x 7
##   DJ_Name Music_Genre Rating Experience      Age Location Plays_Per_Week
##   <chr>    <chr>      <dbl> <chr>      <dbl> <chr>      <dbl>
## 1 DJ A     Pop          4.2 Advanced    28 City X         80
## 2 DJ B     Rock          3.8 Intermediate 24 City Y         60
## 3 DJ C     Electronic    4.5 Advanced    30 City Z        100
## 4 DJ D     Pop           4 Intermediate 22 City X         70
## 5 DJ E     Electronic    4.8 Advanced    27 City Y         90
```

```
## 6 DJ F      Rock      3.6 Intermediate    25 City Z      55
## 7 DJ G      Pop       4.3 Advanced      29 City X      85
## 8 DJ H      Electronic 4.1 Intermediate    23 City Y      75
## 9 DJ I      Rock      3.9 Advanced      31 City Z      70
## 10 DJ J     Pop       4.4 Intermediate    26 City X      95
## # i 16 more rows
```

Question 1.4: Assign the data-set to a variable, `playlist_data`

Solution:

```
# Assign the variable to a dataset
```

```
playlist_data <- read_csv("playlist_data.csv")
```

```
## Rows: 26 Columns: 7
## -- Column specification -----
## Delimiter: ","
## chr (4): DJ_Name, Music_Genre, Experience, Location
## dbl (3): Rating, Age, Plays_Per_Week
##
## i Use 'spec()' to retrieve the full column specification for this data.
## i Specify the column types or set 'show_col_types = FALSE' to quiet this message.
```

From now on, you can use the name of the variable to view the contents of the data-set

Question 1.5: Get more information about `read_csv()` command and provide a screenshot of the information displayed in the “Help” tab of the “Files” pane

Solution:

```
# More information about the R command, complete the code
```

```
?read_csv(playlist_data)
```

```
knitr::include_graphics("C:/Users/angel/OneDrive/Pictures/Screenshots/Screenshot (150).png")
```

Question 1.6: What does the `skip` argument in the `read_csv()` function do?

Solution: *It skips the rows with missing values.*

Question 1.7: Display the contents of the data-set

Solution:

```
# Type the name of the variable, to see what it contains
```

```
playlist_data
```

```
## # A tibble: 26 x 7
##   DJ_Name Music_Genre Rating Experience    Age Location Plays_Per_Week
##   <chr>    <chr>      <dbl> <chr>      <dbl> <chr>      <dbl>
## 1 DJ A      Pop         4.2 Advanced    28 City X         80
## 2 DJ B      Rock         3.8 Intermediate 24 City Y         60
## 3 DJ C      Electronic 4.5 Advanced    30 City Z        100
## 4 DJ D      Pop          4 Intermediate 22 City X         70
```




Figure 1: SS of files pane

```
## 5 DJ E      Electronic      4.8 Advanced      27 City Y      90
## 6 DJ F      Rock           3.6 Intermediate  25 City Z      55
## 7 DJ G      Pop           4.3 Advanced      29 City X      85
## 8 DJ H      Electronic      4.1 Intermediate  23 City Y      75
## 9 DJ I      Rock           3.9 Advanced      31 City Z      70
## 10 DJ J     Pop           4.4 Intermediate  26 City X      95
## # i 16 more rows
```

Question 1.8: Assume you have a CSV file named `sales_data.csv` containing information about sales transactions. How would you use the `read_csv()` function to import this file into R and store it in a variable named `sales_data`?

Solution:

```
# No output is required for this code
# Only the list of commands that execute the task mentioned in the question are required
library(tidyverse)
read_csv(sales_data)
sales_data <- read_csv(sales_data.csv)
```

Task-2 After learning to import a data-set, let us explore the contents of the data-set through the following questions

Question 2.1: Display the first few rows of the data-set to get an overview of its structure

Solution:

```
# Type the name of the variable we assigned the data-set to
head(playlist_data)
```

```
## # A tibble: 6 x 7
##   DJ_Name Music_Genre Rating Experience      Age Location Plays_Per_Week
##   <chr>    <chr>      <dbl> <chr>      <dbl> <chr>      <dbl>
## 1 DJ A      Pop          4.2 Advanced      28 City X          80
## 2 DJ B      Rock          3.8 Intermediate  24 City Y          60
## 3 DJ C      Electronic    4.5 Advanced      30 City Z         100
## 4 DJ D      Pop           4 Intermediate  22 City X          70
## 5 DJ E      Electronic    4.8 Advanced      27 City Y          90
## 6 DJ F      Rock          3.6 Intermediate  25 City Z          55
```

Question 2.2: Display all the columns of the variable stacked one below another

Solution:

```
# Stack columns of playlist_data
glimpse(playlist_data)
```

```
## Rows: 26
## Columns: 7
## $ DJ_Name      <chr> "DJ A", "DJ B", "DJ C", "DJ D", "DJ E", "DJ F", "DJ G", ~
## $ Music_Genre  <chr> "Pop", "Rock", "Electronic", "Pop", "Electronic", "Rock~
## $ Rating       <dbl> 4.2, 3.8, 4.5, 4.0, 4.8, 3.6, 4.3, 4.1, 3.9, 4.4, 4.6, ~
## $ Experience    <chr> "Advanced", "Intermediate", "Advanced", "Intermediate", ~
## $ Age          <dbl> 28, 24, 30, 22, 27, 25, 29, 23, 31, 26, 32, 28, 29, 25, ~
## $ Location     <chr> "City X", "City Y", "City Z", "City X", "City Y", "City~
## $ Plays_Per_Week <dbl> 80, 60, 100, 70, 90, 55, 85, 75, 70, 95, 110, 75, 60, 8~
```

Question 2.3: How many columns are there in the dataset?

Solution:

```
# Number of columns  
ncol(playlist_data)
```

```
## [1] 7
```

Question 2.4: What is the total count of DJs?

Solution:

```
# Number of DJs  
nrow(playlist_data)
```

```
## [1] 26
```

Question 2.5: Display all the location of all the DJs

Solution:

```
# Location of DJs  
playlist_data$Location
```

```
## [1] "City X" "City Y" "City Z" "City X" "City Y" "City Z" "City X" "City Y"  
## [9] "City Z" "City X" "City Y" "City Z" "City X" "City Y" "City Z" "City X"  
## [17] "City Y" "City Z" "City X" "City Y" "City Z" "City X" "City Y" "City Z"  
## [25] "City X" "City Y"
```

Question 2.6: Display the age of the DJs

Solution:

```
# Age of DJs  
playlist_data$Age
```


```
## [1] 28 24 30 22 27 25 29 23 31 26 32 28 29 25 31 26 27 24 29 23 28 24 30 22 27  
## [26] 25
```

Task-3 Let us plot the data to get more insights about the DJs.

Question 3.1: Create a plot to visualize the relationship between DJs' ages and their ratings.

Solution:

```
# complete the code to generate the plot  
ggplot(playlist_data) + aes(x=Age,y=Rating)
```




Question 3.2: Label the x-axis as “Age” and the y-axis as “Rating.”

Solution:

```
# complete the code to generate the plot
```

```
ggplot(playlist_data) + aes(x=Age,y=Rating) + labs(x="Age",y="Rating")
```




Question 3.3: Represent data using points

Solution:

complete the code to generate the plot

```
ggplot(playlist_data) + aes(x=Age,y=Rating) + labs(x="Age",y="Rating") + geom_point()
```





Question 3.4: Can you change the points represented by dots/small circles to any other shape of your liking?

Solution:

```
# complete the code to generate the plot
```

```
ggplot(playlist_data) + aes(x=Age,y=Rating) + labs(x="Age",y="Rating") + geom_point(shape = 17)
```




Question 3.5: Insert a suitable title and briefly provide your insights in the caption

Solution:

```
# complete the code to generate the plot
```

```
ggplot(playlist_data) + aes(x=Age,y=Rating) + geom_point(shape = 17) + labs(x="Age",y="Rating",title="P
```

Plot of DJs' age and ratings



There is no direct relationship between the age of DJs and their ratings.