

# Enhanced Battle City



Guangkai Chen  
([guangkai22@vt.edu](mailto:guangkai22@vt.edu))  
Mehdi Esmaili ([mesmaili@vt.edu](mailto:mesmaili@vt.edu))

# Background

**Battle City** is a multi-directional shooter video game for the [Family Computer](#) produced and published in 1985 by [Namco](#) [1]. It is a successor to Namco's 1980 [Tank Battalion](#), and would be succeeded itself by the 1991 [Tank Force](#).

The Game itself is based on NES(Nintendo Entertainment System)



- <https://bandainamco-am.co.jp>

# Problem Definition

Enemy tanks follow random moves,  
They are not “smart” enough.

**Given:** Map, Enemy Tanks' Position,  
Walls, Player's position

**Design:** A new version of the tank  
moves which makes the life of the  
player harder.

```
def rand_direction(self):  
    num = random.randint(1, 4)  
    if num == 1:  
        return 'u'  
    elif num == 2:  
        return 'd'  
    elif num == 3:  
        return 'l'  
    elif num == 4:  
        return 'r'
```

# Original Approaches

1. Random Directions
  - a. Limited by the NES machine.
  - b. Limited by the chip.
2. Scripts
  - a. Hard-coded events.
  - b. Limit flexibility based on waypoints.

```
def rand_direction(self):  
    num = random.randint(1, 4)  
    if num == 1:  
        return 'u'  
    elif num == 2:  
        return 'd'  
    elif num == 3:  
        return 'l'  
    elif num == 4:  
        return 'r'
```

# Our Approaches

## A\* search

- a. Heuristic - Manhattan distance
- b. Construct a possible route for the agent(enemy tanks)

We need to do a limited A\* search –

- The world(map) setup and the search algorithm makes the calculation costly
- Limit the number of runs can improve framerate

# Our Approaches

Script – If A\* search can't return any valid route, enemy tank will have to follow the scripts.

- Have “jiggle” moving pattern and “charge” moving pattern
  - “Jiggle” means the enemy tank will take a flanking route
  - “Charge” means the enemy tank will choose the closest path towards player
- Acting as a supplementary to A\* star search

And we assume the enemy tanks knows where the player is.

# Experiments

We suppose that a bot plays the game with random moves as a player. We run the game with 3 enemy tanks in a single map for 100 times.

- The average lifetime of the bot when enemy tanks move randomly = 37 seconds
- The average lifetime of the bot when enemy tanks move by A\* search toward the bot = 10 seconds

# Lessons Learned

- When number of tanks grow up, using efficient algorithms become super important, since we need to find the best path for each agent. Therefore, although BFS approach for finding a path for a single agent is acceptable, it is not efficient enough when we have multiple agents.
- How the map setup will heavily affect game performance, and most important, affect how the agent(NPC) perform and execute.



# Future Work

- Use Reinforcement learning
- Designing a new approach when we have multiple players.
- Designing an approach when the enemy tanks do not know the position of the player tank.
- Apply MDP and scoring to improve agent(enemy tanks) performance
- Add back more elements to the game(Base, water, destructible obstacles, etc.)
- Makes every enemy tank do a double limited A\* search for more diverse attack route

# Questions

Thank you!