Claude's Func-Localization Trajectory (7 steps)

[#0] planning (planning) & repo-discovery (check-dir)
`run: find /workspace/open-mmlab__mmdeploy__eed6...`

[#1] file-locate (key-search) & line-locate (infile-search)
`run: grep -r "def " --include="*.py" /`
Output: 20+ Files

[#2] file-locate (key-search) & line-locate (infile-search)
`run: grep -r "node" --include="*.py" /workspace`
Output: 6 Files

[#3] line-locate (file-reading)
`read: core/optimizers/function_marker.py`

[#4] solution-implementation (initial-solution)
`edit: core/optimizers/function_marker.py.`

[#5] solution-verification (code-search)
`run: grep -r "import mmdeploy.core.optimizers.f...`

[#6] solution-verification (reasoning)
`think: Now I have a good understanding of the f...`

Qwen32B's Func-Localization Trajectory (4 steps)

[#0] file-locate (key-search) & line-locate (infile-search)

`run: grep -rnw '/workspace/open-mml`
Output: 1771 Files

[#1] file-locate (key-search) & line-locate (infile-search)

`run: grep -rnw '/workspace/open-mmla`
Output: 105 Files

[#2] line-locate (file-reading)

`read: core/optimizers/function_marker.py`

[#3] solution-implementation (initial-solution)

`edit: core/optimizers/function_marker.py.`