

SCC201: Databases

Week5-Continue: SQL and Advanced SQL Scripts

By

Uraz C Turker

Aggregate Operators

```
COUNT (*)  
COUNT ( [DISTINCT] A)  
SUM ( [DISTINCT] A)  
AVG ( [DISTINCT] A)  
MAX (A)  
MIN (A)
```

- Significant extension of relational algebra.
- They are used to write statistical queries
- Mainly used for reporting, such as
 - the total sales in 2004,
 - average, max, min income of employees
 - Total number of employees hired/fired in 2004

Aggregate Operators

The total number of sailors in the club?

```
SELECT COUNT (*)  
FROM Sailors S;
```

COUNT (*)
COUNT ([DISTINCT] A)
SUM ([DISTINCT] A)
AVG ([DISTINCT] A)
MAX (A)
MIN (A)

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

Figure 4.15 An Instance *S3* of Sailors

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/98
22	102	10/10/98
22	103	10/8/98
22	104	10/7/98
31	102	11/10/98
31	103	11/6/98
31	104	11/12/98
64	101	9/5/98
64	102	9/8/98
74	103	9/8/98

Figure 4.16 An Instance *R2* of Reserves

<i>bid</i>	<i>bname</i>	<i>color</i>
101	Interlake	blue
102	Interlake	red
103	Clipper	green
104	Marine	red

Figure 4.17 An Instance *B1* of Boats

Aggregate Operators

Average age of sailors in the club
Whose rating is 10?

```
SELECT AVG (S.age)
FROM Sailors S
WHERE S.rating=10;
```

COUNT (*)
COUNT ([DISTINCT] A)
SUM ([DISTINCT] A)
AVG ([DISTINCT] A)
MAX (A)
MIN (A)

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

Figure 4.15 An Instance *S3* of Sailors

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/98
22	102	10/10/98
22	103	10/8/98
22	104	10/7/98
31	102	11/10/98
31	103	11/6/98
31	104	11/12/98
64	101	9/5/98
64	102	9/8/98
74	103	9/8/98

Figure 4.16 An Instance *R2* of Reserves

<i>bid</i>	<i>bname</i>	<i>color</i>
101	Interlake	blue
102	Interlake	red
103	Clipper	green
104	Marine	red

Figure 4.17 An Instance *B1* of Boats

Aggregate Operators

COUNT (*)
COUNT ([DISTINCT] A)
SUM ([DISTINCT] A)
AVG ([DISTINCT] A)
MAX (A)
MIN (A)

Average distinct ages of sailors
Whose rating is 10?

```
SELECT AVG ( DISTINCT S.age )  
FROM Sailors S  
WHERE S.rating=10;
```

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

Figure 4.15 An Instance *S3* of Sailors

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/98
22	102	10/10/98
22	103	10/8/98
22	104	10/7/98
31	102	11/10/98
31	103	11/6/98
31	104	11/12/98
64	101	9/5/98
64	102	9/8/98
74	103	9/8/98

Figure 4.16 An Instance *R2* of Reserves

<i>bid</i>	<i>bname</i>	<i>color</i>
101	Interlake	blue
102	Interlake	red
103	Clipper	green
104	Marine	red

Figure 4.17 An Instance *B1* of Boats

Aggregate Operators

Names of sailors whose rating is equal to the maximum rating in the club.

```
SELECT S.sname
FROM Sailors S
WHERE S.rating= (SELECT MAX(S2.rating)
                FROM Sailors S2);
```

COUNT (*)
COUNT ([DISTINCT] A)
SUM ([DISTINCT] A)
AVG ([DISTINCT] A)
MAX (A)
MIN (A)

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

Figure 4.15 An Instance S3 of Sailors

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/98
22	102	10/10/98
22	103	10/8/98
22	104	10/7/98
31	102	11/10/98
31	103	11/6/98
31	104	11/12/98
64	101	9/5/98
64	102	9/8/98
74	103	9/8/98

Figure 4.16 An Instance R2 of Reserves

<i>bid</i>	<i>bname</i>	<i>color</i>
101	Interlake	blue
102	Interlake	red
103	Clipper	green
104	Marine	red

Figure 4.17 An Instance B1 of Boats

Aggregate Operators

COUNT (*)
COUNT ([DISTINCT] A)
SUM ([DISTINCT] A)
AVG ([DISTINCT] A)
MAX (A)
MIN (A)



Number of sailors whose rating is equal to the maximum rating in the club.

```
SELECT COUNT(S.sid)
FROM Sailors S
WHERE S.rating= (SELECT MAX(S2.rating)
                FROM Sailors S2)
```

sid	sname	rating	age
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

Figure 4.15 An Instance S3 of Sailors

sid	bid	day
22	101	10/10/98
22	102	10/10/98
22	103	10/8/98
22	104	10/7/98
31	102	11/10/98
31	103	11/6/98
31	104	11/12/98
64	101	9/5/98
64	102	9/8/98
74	103	9/8/98

Figure 4.16 An Instance R2 of Reserves

bid	bname	color
101	Interlake	blue
102	Interlake	red
103	Clipper	green
104	Marine	red

Figure 4.17 An Instance B1 of Boats

Aggregate Operators

COUNT (*)
COUNT ([DISTINCT] A)
SUM ([DISTINCT] A)
AVG ([DISTINCT] A)
MAX (A)
MIN (A)



How many different ratings are there in the club?

```
SELECT COUNT (S.rating)
AS Res FROM Sailors S;
```

Above query is not correct. Think why!

```
SELECT COUNT (DISTINCT S.rating)
AS Res FROM Sailors S;
```

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

Figure 4.15 An Instance *S3* of Sailors

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/98
22	102	10/10/98
22	103	10/8/98
22	104	10/7/98
31	102	11/10/98
31	103	11/6/98
31	104	11/12/98
64	101	9/5/98
64	102	9/8/98
74	103	9/8/98

Figure 4.16 An Instance *R2* of Reserves

<i>bid</i>	<i>bname</i>	<i>color</i>
101	Interlake	blue
102	Interlake	red
103	Clipper	green
104	Marine	red

Figure 4.17 An Instance *B1* of Boats

Find name and age of the oldest sailor(s)

- This query is correct and it is allowed in the SQL/92 standard, but is not supported in some systems.

```
SELECT S.sname, S.age
FROM Sailors S
WHERE S.age =
    (SELECT MAX (S2.age)
     FROM Sailors S2);
```

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

Figure 4.15 An Instance *S3* of Sailors

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/98
22	102	10/10/98
22	103	10/8/98
22	104	10/7/98
31	102	11/10/98
31	103	11/6/98
31	104	11/12/98
64	101	9/5/98
64	102	9/8/98
74	103	9/8/98

Figure 4.16 An Instance *R2* of Reserves

<i>bid</i>	<i>bname</i>	<i>color</i>
101	Interlake	blue
102	Interlake	red
103	Clipper	green
104	Marine	red

Figure 4.17 An Instance *B1* of Boats

Find name and age of the oldest sailor(s)

- This query is valid for all systems .

```
SELECT S.sname, S.age
FROM Sailors S
WHERE (SELECT MAX (S2.age)
      FROM Sailors S2)
      = S.age;
```

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

Figure 4.15 An Instance S3 of Sailors

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/98
22	102	10/10/98
22	103	10/8/98
22	104	10/7/98
31	102	11/10/98
31	103	11/6/98
31	104	11/12/98
64	101	9/5/98
64	102	9/8/98
74	103	9/8/98

Figure 4.16 An Instance R2 of Reserves

<i>bid</i>	<i>bname</i>	<i>color</i>
101	Interlake	blue
102	Interlake	red
103	Clipper	green
104	Marine	red

Figure 4.17 An Instance B1 of Boats

GROUP BY and HAVING

- So far, we've applied aggregate operators to all (qualifying) tuples. Sometimes, we want to apply them to each of several *groups* of tuples.

Consider: *Find the age of the youngest sailor for each rating level.*

In general, we don't know how many rating levels exist and what the rating values for these levels are!

- Suppose we know that rating values go from 1 to 10; we can write 10 queries that look like this (!):

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

Figure 4.15 An Instance *S3* of Sailors

For $i = 1, 2, \dots, 10$:

```
SELECT MIN (S.age)
FROM Sailors S
WHERE S.rating = i
```

Queries With GROUP BY and HAVING

SELECT	[DISTINCT]	<i>target-list</i>
FROM		<i>relation-list</i>
WHERE		<i>qualification</i>
GROUP BY		<i>grouping-list</i>
HAVING		<i>group-qualification</i>


- The *target-list* contains (i) attribute list **(ii) terms with aggregate operations (e.g., MIN (S.age)).**

Conceptual Evaluation


- The cross-product of *relation-list* is computed, tuples that fail *qualification* are discarded, 'unnecessary' fields are deleted, and the remaining tuples are partitioned into groups by the value of attributes in *grouping-list*.
- The *group-qualification* is then applied to eliminate some groups. Expressions in *group-qualification* must have a single value per group!
- One answer tuple is generated per qualifying group.

SELECT	[DISTINCT] <i>target-list</i>
FROM	<i>relation-list</i>
WHERE	<i>qualification</i>
GROUP BY	<i>grouping-list</i>
HAVING	<i>group-qualification</i>

Conceptual Evaluation





```
SELECT target-list
FROM   relation-list
WHERE  qualification
```




```
GROUP BY grouping-list
```

gr1



gr2



gr3



gr4




gr5



--

```
HAVING group-qualification
```

RESULT




```
SELECT    [DISTINCT] target-list
FROM      relation-list
WHERE     qualification
GROUP BY  grouping-list
HAVING    group-qualification
```

Conceptual Evaluation

Find the sailors with age ≥ 18 , for each rating with at least 2 such sailors

```
SELECT S.rating
FROM Sailors S
WHERE S.age >= 18
```

Age = 20
Age = 25
Age = 19
Age=70
Age = 60
Age = 40
Age = 33
Age = 32
Age = 18
Age = 22
Age = 39

Rating = 4
Rating = 2
Rating = 3
Rating=2
Rating=3
Rating=5
Rating=1
Rating=4
Rating=3
Rating=4
Rating=1

GROUP BY
S.rating

gr1

Rating=1
Rating=1

gr2

Rating=2
Rating=2

gr3

Rating=3
Rating=3
Rating=3

gr4

Rating=4
Rating=4
Rating=4

gr5

Rating=5

HAVING COUNT (*) > 1

RESULT

Rating = 1
Rating = 2
Rating = 3
Rating = 4

```
SELECT S.rating
FROM Sailors S
WHERE S.age >= 18
GROUP BY S.rating
HAVING COUNT (*) > 1
```


Find the age of the youngest sailor with age ≥ 18 , for
each rating with at least 2 such sailors

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
71	zorba	10	16.0
64	horatio	7	35.0
29	brutus	1	33.0
58	rusty	10	35.0

Find the age of the youngest sailor **with age ≥ 18** , for
each rating with at least 2 such sailors

```
SELECT S.rating  
FROM Sailors S  
WHERE S.age >= 18
```

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
71	zorba	10	16.0
64	horatio	7	35.0
29	brutus	1	33.0
58	rusty	10	35.0

Find the age of the youngest sailor **with age ≥ 18 , for**
each rating with at least 2 such sailors

```
SELECT S.rating  
FROM Sailors S  
WHERE S.age >= 18  
GROUP BY S.rating
```

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
71	zorba	10	16.0
64	horatio	7	35.0
29	brutus	1	33.0
58	rusty	10	35.0

Find the age of the youngest sailor **with age ≥ 18 , for**
each rating with at least 2 such sailors

```
SELECT S.rating  
FROM Sailors S  
WHERE S.age >= 18  
GROUP BY S.rating  
HAVING COUNT(*)>1
```

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
71	zorba	10	16.0
64	horatio	7	35.0
29	brutus	1	33.0
58	rusty	10	35.0

Find the age of the youngest sailor **with age ≥ 18 , for**
each rating with at least 2 such sailors

```
SELECT S.rating
FROM Sailors S
WHERE S.age >= 18
GROUP BY S.rating
HAVING COUNT(*) > 1
```

Minimum AGE ?

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
71	zorba	10	16.0
64	horatio	7	35.0
29	brutus	1	33.0
58	rusty	10	35.0

Find the age of the youngest sailor with age ≥ 18 , for each rating with at least 2 such sailors

```
SELECT S.rating
FROM Sailors S
WHERE S.age >= 18
GROUP BY S.rating
HAVING COUNT(*) > 1
```

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
71	zorba	10	16.0
64	horatio	7	35.0
29	brutus	1	33.0
58	rusty	10	35.0

Minimum AGE ?

So, introduce a new attribute in the solution that selects the youngest age..

Find the age of the youngest sailor **with age ≥ 18 , for**
each rating with at least 2 such sailors

```
SELECT S.rating, Min(age)
FROM Sailors S
WHERE S.age >= 18
GROUP BY S.rating
HAVING COUNT(*)>1
```

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
71	zorba	10	16.0
64	horatio	7	35.0
29	brutus	1	33.0
58	rusty	10	35.0

Find the age of the youngest sailor **with age ≥ 18 , for**
each rating with at least 2 such sailors

```
SELECT S.rating, Min(age)
FROM Sailors S
WHERE S.age >= 18
GROUP BY S.rating
HAVING COUNT(*)>1
```

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
71	zorba	10	16.0
64	horatio	7	35.0
29	brutus	1	33.0
58	rusty	10	35.0

rating	age
1	33.0
7	45.0
7	35.0
8	55.5
10	35.0

Find the age of the youngest sailor with age ≥ 18 , for each rating with at least 2 such sailors

```
SELECT S.rating, MIN (S.age)
FROM Sailors S
WHERE S.age >= 18
GROUP BY S.rating
HAVING COUNT (*) > 1
```

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
71	zorba	10	16.0
64	horatio	7	35.0
29	brutus	1	33.0
58	rusty	10	35.0

rating	age
1	33.0
7	45.0
7	35.0
8	55.5
10	35.0

rating	
7	35.0

- Only S.rating and S.age are mentioned in the SELECT, GROUP BY or HAVING clauses;
- 2nd column of result is unnamed. (Use AS to name it.)

Find the age of the youngest sailor with age ≥ 18 , for each rating with at least 2 such sailors

```
SELECT S.rating, ag=MIN (S.age)
FROM Sailors S
WHERE S.age >= 18
GROUP BY S.rating
HAVING COUNT (*) > 1;
```

<u>sid</u>	sname	rating	age
22	dustin	7	45.0
31	lubber	8	55.5
71	zorba	10	16.0
64	horatio	7	35.0
29	brutus	1	33.0
58	rusty	10	35.0

rating	age
1	33.0
7	45.0
7	35.0
8	55.5
10	35.0

rating	ag
7	35.0

Answer relation

- Only S.rating and S.age are mentioned in the SELECT, GROUP BY or HAVING clauses;
- 2nd column of result is unnamed. (Use AS to name it.)

For each red boat, find the number of reservations for this boat

<i>sid</i>	<i>sname</i>	<i>rating</i>	<i>age</i>
22	Dustin	7	45.0
29	Brutus	1	33.0
31	Lubber	8	55.5
32	Andy	8	25.5
58	Rusty	10	35.0
64	Horatio	7	35.0
71	Zorba	10	16.0
74	Horatio	9	35.0
85	Art	3	25.5
95	Bob	3	63.5

Figure 4.15 An Instance *S3* of Sailors

<i>sid</i>	<i>bid</i>	<i>day</i>
22	101	10/10/98
22	102	10/10/98
22	103	10/8/98
22	104	10/7/98
31	102	11/10/98
31	103	11/6/98
31	104	11/12/98
64	101	9/5/98
64	102	9/8/98
74	103	9/8/98

Figure 4.16 An Instance *R2* of Reserves

<i>bid</i>	<i>bname</i>	<i>color</i>
101	Interlake	blue
102	Interlake	red
103	Clipper	green
104	Marine	red


Figure 4.17 An Instance *B1* of Boats

For each **red** boat, find the number of reservations for this boat

```
SELECT B.bid, COUNT (*) AS scount
FROM Boats B, Reserves R
WHERE R.bid=B.bid AND B.color='red'
GROUP BY B.bid
```

Example

- *“We are running an instrument store in Uxbridge, London. We want to create a database that keeps transaction information with transaction date, ProductID (customer purchased), and amount_purchased, transactionID. Moreover we have products with unique ProductID, and name, price, product picture, and amount_in_Store.*
- *We can issue one transaction per product, and we will not keep records of a transaction if the purchased product is deleted (removed from the store).”*
- Draw ERD, Reveal Relational Schema and Integrity Constraints and write SQL code to create the database.



Product(ProductID INTEGER, name TEXT, price REAL,
picture BLOB, amount_in_Store INTEGER);
IC: Primary Key ProductID

TransactionIsRelated(ProductID INTEGER, Amount REAL,
Date TEXT, P_ProductID INTEGER, TransactionID
INTEGER)

IC: Primary Key (P_ProductID, transactionID)
IC: Foreign Key (P_ProductID) References Product ON
DELETE CASCADE

```
CREATE TABLE Product(ProductID INTEGER,... PRIMARY KEY(ProductID));
```

```
CREATE TABLE TransactionIsRelated(ProductID INTEGER, Amount REAL, Date TEXT, P_ProductID
INTEGER, TransactionID INTEGER,Primary Key (ProductID,TransactionID), Foreign Key (P_ProductID)
References Product(ProductID) ON DELETE CASCADE
);
```


Summary

- SQL is a very powerful declarative scripting language.
- Unfortunately, there are many ways of writing an SQL script for a given query.
 - Bad ones will consume CPU time and memory.
 - Good ones are hardware and time friendly.
 - Relational algebra is the key to deriving optimum SQL queries.

Summary

- SQL is a very powerful declarative scripting language.
- Unfortunately, there are many ways of writing an SQL script for a given query.
 - Bad ones will consume CPU time and memory.
 - Good ones are hardware and time friendly.
 - Relational algebra is the key to deriving optimum SQL queries.