


Unix File-System

Dr Andrew Scott

a.scott@lancaster.ac.uk


1

Typical Unix *inode* Structure





2

Reference Count and Hard Links




3



File Lookup: `/home/acs/211`

- Often
 - Search from last directory entry read
 - Processes typically scan directories sequentially
 - Use filename caches to speed up access



7

Block Size and Efficiency/ Waste

- Values taken off 1.2GB 4.3BSD Unix file-system
 - Wastage as percentage of disk space
 - Larger block sizes allow for larger files
 - More links per index block
 - More data in each referenced data block


Space Used (Mbyte)	%age Waste	Structure
775.2	0.0	(control value) Just the raw data
828.7	6.9	Data & inodes with 512 byte blocks
866.5	11.8	Data & inodes with 1024 byte blocks
948.5	22.4	Data & inodes with 2048 byte blocks
1128.3	45.6	Data & inodes with 4096 byte blocks

8

Block Fragments

- Efficiency best when block and file sizes matched, but
 - Small blocks tend to suit small files
 - Large blocks tend to suit large files
- Tended to move to larger blocks as file sizes increased
 - Media files, etc.
- Some file-systems can allocate fragments of blocks
 - i.e. 4 x 1K fragments from a single 4K disk block
- Blocks must be multiple of disk sector size

9



10
