

**Part II**

**COMPUTING AND COMMUNICATIONS – On-line Assessment**

**Available Time** [23 Hours]

**Recommended Completion Time** [3 Hours]

**SCC.312 Languages and Compilation**

---

*Candidates are asked to answer **THREE** questions from **FOUR**; each question is worth a total of 25 marks.*

## Question 1

**1.a** Copy this table and complete the classification of phrase structure grammars and machines by filling in the blank cells.

Type	Grammars	Machines
0		
1		
2		
3		

[4 marks]

**1.b** Give the name for the classification scheme invented by an American linguist.

[1 mark]

**1.c** Consider the following set of Backus–Naur Form (BNF) production rules. Generate a parse tree for the sentence “The footballer scores a goal”:

```
<simple_sentence> ::= <noun_phrase> <verb> <noun_phrase>
<noun_phrase> ::= <article> <noun>
<noun> ::= footballer | ball | goal
<article> ::= the | a
<verb> ::= tackles | kicks | scores
```

[5 marks]

**1.d** Derive a syntactically valid sentence from the grammar in part **1.c** whose meaning is nonsensical in English.

[1 mark]

**1.e** What type is the grammar in **1.c** according to the classification in the table that you completed in part **1.a**? Explain your answer in no more than 40 words.

[3 marks]

Question 1 continues on next page...

**Question 1 continued.**

**1.f** In the process of coding a Universal Turing Machine (UTM), describe what is contained in each quintuple.

**[2 marks]**

**1.g** What two restrictions are placed upon type 1 grammar rules that are not placed on type 0 grammar rules?


**[3 marks]**

**1.h** Assume you have just been awarded a PhD degree and want to change your title in all of your documents into Dr (no dot to follow). Design a Turing machine that transforms titles such as Mrs, Miss, Ms, Mx and Mr into Dr. A possible input tape for a TM is (the Bs are blank symbols):



...BBBMissBB

Your Turing machine should be able to process this and subsequently end up with a tape containing a Dr title as in:



...BBBDrBBB

Your answer should include:


- a diagram of the Turing Machine itself (a screenshot from JFlap is recommended)
- Your TM should not accept strings other than Mrs, Miss, Ms, Mx and Mr. **Do not include a dot.** Strings such as 'Mrrrr', 'Missss', or 'Mi' should be rejected.

**[6 marks]**

**[Total 25 marks]**

## Question 2

**2.a** Generate the grammar associated with this finite state recogniser (FSR):



[2 marks]

**2.b** Using the grammar in part **2.a**, give two examples of valid sentences and two examples of sentences that are not valid.

[2 marks]

**2.c** The FSR in part **2.a** is non-deterministic. Mention which states are non-deterministic

[1 mark]

**2.d** Using set definition notation, describe the set of valid sentences accepted by the FSR in part **2.a** above.

[2 marks]

**2.e** Using the subset construction algorithm, generate a deterministic FSR from the above non-deterministic one.

[3 marks]

**2.f** Consider the following grammar:

$S \rightarrow cA \mid bA$

$A \rightarrow a \mid aA \mid tB \mid aAA$

$B \rightarrow s \mid sS$

Classify this grammar by explaining what type of grammar it is and why.

[2 marks]

Question 2 continues on next page...

**Question 2 continued.**

**2.g** Show that the grammar in part **2.f** is ambiguous. Illustrate your answer by providing two possible parse trees for the sentence: 'caats'

**[4 marks]**

**2.h** Give two examples of sentences (words) that are accepted by this grammar and three sentences that are rejected.

**[2 marks]**

**2.i** Generate a non-deterministic push-down automata (PDA) directly from the grammar in part **2.f** above.

**[5 marks]**

**2.j** Define the halting problem and briefly explain (maximum one paragraph) the implications of the halting problem for a Universal Turing Machine simulating a Turing Machine.

**[2 marks]**

**[Total 25 marks]**

### Question 3

**3.a** When designing a split compiler with an Intermediate Language (IL) you may encounter problems when using multiple front-end languages (say, C vs Java front-ends). State one of the problems you might encounter, explain why this is a problem, and propose a solution.

[5 marks]

**3.b.**

i. Using the following grammar and input string, show each step of a bottom-up (LR) parse to attain a single <value>. Starting with an empty stack, at each step of the parse show the state of the stack, and the cursor location in the input stream.

Grammar:   <value> ::= <number> | <expression>  
              <number> ::= { any integer number }  
              <expression> ::= <value> \* <value> | <value> / <value>  
              <expression> ::= <value> + <value> | <value> - <value>

Input:       2 + 3 \* 4

[16 marks]

ii. What answer does this expression interpreter produce from the input string above, and what might be incorrect about this result? Demonstrate your answer with examples.

[4 marks]

[Total 25 marks]

#### Question 4

**4.a** Draw the parse tree for the following expression; remember the order of operations:

$$a + b * c$$

[2 Marks]

**4.b** Using the parse tree for **4.a**, produce for each node of the tree a code and result (CR) block. Start at the leaves of the tree and write out each in order to reach a complete block for the root of your parse tree.

[10 Marks]

**4.c.**

- i. Rewrite the following code/result block to optimize it for memory efficiency, while still adhering to the Three-address code (TAC) methods.

<b>C</b>	<pre>t1 = st[a] + st[b] t2 = st[c] + st[d] t3 = st[e] + st[f] t4 = t1 + t2 t5 = t3 / 4</pre>
<b>R</b>	t4

[3 Marks]

- ii. Explain why the a compiler might want to do this? In your answer state a type of machine that might benefit from this output style.

[2 Marks]

- iii. In a language using structure equivalence to determine type equality, explain how the following pseudocode definition might cause problems.

```
type node is record
  value : integer
  next : pointer to node
end record
```

[4 Marks]

**4.d** State and provide an example for each form of type coercion

[4 marks]

[Total 25 marks]