

# Faster Dual Lattice Attacks by Using Coding Theory

Kevin Carrier, Yixin Shen and Jean-Pierre Tillich

ETIS Laboratory, CY Cergy-Paris University  
Royal Holloway, University of London  
Project COSMIQ, Inria de Paris

November 21, 2022



# Learning with errors (LWE)

Let  $n = 4$ ,  $m = 6$  and  $q = 17$ .

**secret**

$$A \in \mathbb{Z}_q^{m \times n} \quad s \in \mathbb{Z}_q^n \quad b \in \mathbb{Z}_q^m$$

14	12	2	5
5	3	1	7
14	7	2	5
0	9	8	4
8	11	5	12
5	1	3	14

 $\times$ 


 $=$ 

11
5
14
6
12
13

Given  $A$  and  $b$ , find  $s$ .

# Learning with errors (LWE)

Let  $n = 4$ ,  $m = 6$  and  $q = 17$ .

**secret**

$$A \in \mathbb{Z}_q^{m \times n} \quad s \in \mathbb{Z}_q^n \quad b \in \mathbb{Z}_q^m$$

14	12	2	5
5	3	1	7
14	7	2	5
0	9	8	4
8	11	5	12
5	1	3	14

 $\times$ 

1
2
1
5

 $=$ 

11
5
14
6
12
13

Given  $A$  and  $b$ , find  $s$ .

→ Very easy (e.g. Gaussian elimination) and in polynomial time

# Learning with errors (LWE)

Let  $n = 4$ ,  $m = 6$  and  $q = 17$ .

random		secret		noise																																										
$A \in \mathbb{Z}_q^{m \times n}$		$s \in \mathbb{Z}_q^n$		$e \in \mathbb{Z}_q^m$	$b \in \mathbb{Z}_q^m$																																									
<table border="1"><tr><td>14</td><td>12</td><td>2</td><td>5</td></tr><tr><td>5</td><td>3</td><td>1</td><td>7</td></tr><tr><td>14</td><td>7</td><td>2</td><td>5</td></tr><tr><td>0</td><td>9</td><td>8</td><td>4</td></tr><tr><td>8</td><td>11</td><td>5</td><td>12</td></tr><tr><td>5</td><td>1</td><td>3</td><td>14</td></tr></table>	14	12	2	5	5	3	1	7	14	7	2	5	0	9	8	4	8	11	5	12	5	1	3	14	$\times$	<table border="1"><tr><td>1</td></tr><tr><td>2</td></tr><tr><td>1</td></tr><tr><td>5</td></tr></table>	1	2	1	5	$+$	<table border="1"><tr><td>-3</td></tr><tr><td>-1</td></tr><tr><td>2</td></tr><tr><td>-3</td></tr><tr><td>3</td></tr><tr><td>-1</td></tr></table>	-3	-1	2	-3	3	-1	$=$	<table border="1"><tr><td>11</td></tr><tr><td>5</td></tr><tr><td>14</td></tr><tr><td>6</td></tr><tr><td>12</td></tr><tr><td>13</td></tr></table>	11	5	14	6	12	13
14	12	2	5																																											
5	3	1	7																																											
14	7	2	5																																											
0	9	8	4																																											
8	11	5	12																																											
5	1	3	14																																											
1																																														
2																																														
1																																														
5																																														
-3																																														
-1																																														
2																																														
-3																																														
3																																														
-1																																														
11																																														
5																																														
14																																														
6																																														
12																																														
13																																														

# Learning with errors (LWE)

Let  $n = 4$ ,  $m = 6$  and  $q = 17$ .

random		secret		noise																																										
$A \in \mathbb{Z}_q^{m \times n}$		$s \in \mathbb{Z}_q^n$		$e \in \mathbb{Z}_q^m$	$b \in \mathbb{Z}_q^m$																																									
<table border="1"><tr><td>14</td><td>12</td><td>2</td><td>5</td></tr><tr><td>5</td><td>3</td><td>1</td><td>7</td></tr><tr><td>14</td><td>7</td><td>2</td><td>5</td></tr><tr><td>0</td><td>9</td><td>8</td><td>4</td></tr><tr><td>8</td><td>11</td><td>5</td><td>12</td></tr><tr><td>5</td><td>1</td><td>3</td><td>14</td></tr></table>	14	12	2	5	5	3	1	7	14	7	2	5	0	9	8	4	8	11	5	12	5	1	3	14	$\times$	<table border="1"><tr><td></td></tr><tr><td></td></tr><tr><td></td></tr><tr><td></td></tr></table>					$+$	<table border="1"><tr><td></td></tr><tr><td></td></tr><tr><td></td></tr><tr><td></td></tr><tr><td></td></tr><tr><td></td></tr></table>							$=$	<table border="1"><tr><td>11</td></tr><tr><td>5</td></tr><tr><td>14</td></tr><tr><td>6</td></tr><tr><td>12</td></tr><tr><td>13</td></tr></table>	11	5	14	6	12	13
14	12	2	5																																											
5	3	1	7																																											
14	7	2	5																																											
0	9	8	4																																											
8	11	5	12																																											
5	1	3	14																																											
11																																														
5																																														
14																																														
6																																														
12																																														
13																																														

Given  $A$  and  $b$ , find  $s$ .

→ Suspected hard problem, even for quantum algorithms

# Learning with errors (LWE)

Let  $n, m, q \in \mathbb{Z}$  and  $\chi_e, \chi_s$  two distributions over  $\mathbb{Z}_q$ .

**LWE**( $n, m, q, \chi_e, \chi_s$ ): probability distribution on  $\mathbb{Z}_q^{m \times n} \times \mathbb{Z}_q^m$

- ▶ sample  $A \leftarrow U(\mathbb{Z}_q^{m \times n})$
- ▶ sample  $s \leftarrow \chi_s^n$
- ▶ sample  $e \leftarrow \chi_e^m$
- ▶ output  $(A, As + e)$ .

**Intuition:**  $As + e$  is **very close** to a uniform distribution.

# Learning with errors (LWE)

Let  $n, m, q \in \mathbb{Z}$  and  $\chi_e, \chi_s$  two distributions over  $\mathbb{Z}_q$ .

**LWE( $n, m, q, \chi_e, \chi_s$ )**: probability distribution on  $\mathbb{Z}_q^{m \times n} \times \mathbb{Z}_q^m$

- ▶ sample  $A \leftarrow U(\mathbb{Z}_q^{m \times n})$
- ▶ sample  $s \leftarrow \chi_s^n$
- ▶ sample  $e \leftarrow \chi_e^m$
- ▶ output  $(A, As + e)$ .

**Intuition:**  $As + e$  is **very close** to a uniform distribution.

**Search LWE problem:** given  $(A, b) \leftarrow \text{LWE}(n, m, q, \chi_e, \chi_s)$ , recover  $s$ .

**Decision LWE problem:**

distinguish  $\text{LWE}(n, m, q, \chi_e, \chi_s)$  from  $U(\mathbb{Z}_q^{m \times n} \times \mathbb{Z}_q^m)$ .

# Learning with errors (LWE)

Let  $n, m, q \in \mathbb{Z}$  and  $\chi_e, \chi_s$  two distributions over  $\mathbb{Z}_q$ .

**LWE( $n, m, q, \chi_e, \chi_s$ )**: probability distribution on  $\mathbb{Z}_q^{m \times n} \times \mathbb{Z}_q^m$

- ▶ sample  $A \leftarrow U(\mathbb{Z}_q^{m \times n})$
- ▶ sample  $s \leftarrow \chi_s^n$
- ▶ sample  $e \leftarrow \chi_e^m$
- ▶ output  $(A, As + e)$ .

**Intuition:**  $As + e$  is **very close** to a uniform distribution.

**Search LWE problem:** given  $(A, b) \leftarrow \text{LWE}(n, m, q, \chi_e, \chi_s)$ , recover  $s$ .

**Decision LWE problem:**

distinguish  $\text{LWE}(n, m, q, \chi_e, \chi_s)$  from  $U(\mathbb{Z}_q^{m \times n} \times \mathbb{Z}_q^m)$ .

**Lemma:** Search LWE is easy if and only if decision LWE is easy.



# Learning with errors (LWE)

$\text{LWE}(n, m, q, \chi_e, \chi_s)$ : probability distribution on  $\mathbb{Z}_q^{m \times n} \times \mathbb{Z}_q^m$

- ▶ sample  $A \leftarrow U(\mathbb{Z}_q^{m \times n})$
- ▶ sample  $s \leftarrow \chi_s^n$
- ▶ sample  $e \leftarrow \chi_e^m$
- ▶ output  $(A, As + e)$ .

# Learning with errors (LWE)

$\text{LWE}(n, m, q, \chi_e, \chi_s)$ : probability distribution on  $\mathbb{Z}_q^{m \times n} \times \mathbb{Z}_q^m$

- ▶ sample  $A \leftarrow U(\mathbb{Z}_q^{m \times n})$
- ▶ sample  $s \leftarrow \chi_s^n$
- ▶ sample  $e \leftarrow \chi_e^m$
- ▶ output  $(A, As + e)$ .

Secret distributions  $\chi_s$ :

- ▶ originally uniform in  $\mathbb{Z}_q$
- ▶ now some distribution of small deviation  $\sigma_s$  (e.g. discrete Gaussian/centered Binomial,  $\{-1, 0, 1\}$  whp)
- ▶ **Fact:** small secret is as hard as uniform secret
- ▶ small secret allows more efficient schemes

# Learning with errors (LWE)

$\text{LWE}(n, m, q, \chi_e, \chi_s)$ : probability distribution on  $\mathbb{Z}_q^{m \times n} \times \mathbb{Z}_q^m$

- ▶ sample  $A \leftarrow U(\mathbb{Z}_q^{m \times n})$
- ▶ sample  $s \leftarrow \chi_s^n$
- ▶ sample  $e \leftarrow \chi_e^m$
- ▶ output  $(A, As + e)$ .

Noise distributions  $\chi_e$ :

- ▶ usually discrete Gaussian/centered Binomial of deviation  $\sigma_e$
- ▶ most schemes (Kyber/Saber/...):  $\sigma_e$  small ( $\approx 1$ )

# LWE: security and attacks

LWE is **fundamental** to lattice-based cryptography:

- ▶ several lattice-based NIST PQC candidates rely on LWE
- ▶ extensive literature
- ▶ all evidence points to resistance against quantum attacks

# LWE: security and attacks

LWE is **fundamental** to lattice-based cryptography:

- ▶ several lattice-based NIST PQC candidates rely on LWE
- ▶ extensive literature
- ▶ all evidence points to resistance against quantum attacks

Two types of attacks:

- ▶ **Primal attacks:**
  - ▶ more efficient in most cases
- ▶ **Dual attacks:**
  - ▶ originally less efficient, now catching up

**Contribution:** improvement on dual attacks using ideas from codes

# Search to distinguish

Very naive attack:

$$\begin{array}{c} A \\ \begin{array}{|c|c|c|c|} \hline 8 & 9 & 10 & 12 \\ \hline 5 & 3 & 11 & 3 \\ \hline 0 & 15 & 10 & 4 \\ \hline 15 & 9 & 16 & 15 \\ \hline 1 & 2 & 10 & 8 \\ \hline 11 & 16 & 13 & 9 \\ \hline \end{array} \end{array} \times \begin{array}{c} s \\ \begin{array}{|c|} \hline \\ \hline \\ \hline \\ \hline \\ \hline \end{array} \end{array} + \begin{array}{c} e \\ \begin{array}{|c|} \hline \\ \hline \\ \hline \\ \hline \\ \hline \\ \hline \end{array} \end{array} = \begin{array}{c} b \\ \begin{array}{|c|} \hline 8 \\ \hline 3 \\ \hline 11 \\ \hline 15 \\ \hline 2 \\ \hline 15 \\ \hline \end{array} \end{array}$$

Attack:

►  $\text{get}(A, b)$

# Search to distinguish

Very naive attack: guess secret  $\tilde{s}$

$$\begin{array}{c} A \\ \begin{array}{|c|c|c|c|} \hline 8 & 9 & 10 & 12 \\ \hline 5 & 3 & 11 & 3 \\ \hline 0 & 15 & 10 & 4 \\ \hline 15 & 9 & 16 & 15 \\ \hline 1 & 2 & 10 & 8 \\ \hline 11 & 16 & 13 & 9 \\ \hline \end{array} \end{array} \times \left( \begin{array}{c} s \\ \begin{array}{|c|} \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \end{array} \end{array} - \begin{array}{c} \tilde{s} \\ \begin{array}{|c|} \hline 3 \\ \hline 11 \\ \hline 0 \\ \hline 14 \\ \hline \end{array} \end{array} \right) + \begin{array}{c} e \\ \begin{array}{|c|} \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \end{array} \end{array} = \begin{array}{c} b' \\ \begin{array}{|c|} \hline 7 \\ \hline 2 \\ \hline 3 \\ \hline 15 \\ \hline 11 \\ \hline 8 \\ \hline \end{array} \end{array}$$

Attack:

- ▶ get  $(A, b)$
- ▶ guess  $\tilde{s}$
- ▶ output  $b' = b - A\tilde{s}$

# Search to distinguish

Very naive attack: guess secret  $\tilde{s}$

$$\begin{array}{c} A \\ \begin{array}{|c|c|c|c|} \hline 8 & 9 & 10 & 12 \\ \hline 5 & 3 & 11 & 3 \\ \hline 0 & 15 & 10 & 4 \\ \hline 15 & 9 & 16 & 15 \\ \hline 1 & 2 & 10 & 8 \\ \hline 11 & 16 & 13 & 9 \\ \hline \end{array} \end{array} \times \left( \begin{array}{c} s \\ \begin{array}{|c|} \hline \phantom{0} \\ \hline \end{array} \\ \end{array} - \begin{array}{c} \tilde{s} \\ \begin{array}{|c|} \hline 3 \\ \hline 11 \\ \hline 0 \\ \hline 14 \\ \hline \end{array} \right) + \begin{array}{c} e \\ \begin{array}{|c|} \hline \phantom{0} \\ \hline \end{array} \end{array} = \begin{array}{c} b' \\ \begin{array}{|c|} \hline 7 \\ \hline 2 \\ \hline 3 \\ \hline 15 \\ \hline 11 \\ \hline 8 \\ \hline \end{array} \end{array}$$

Attack:

- ▶ get  $(A, b)$
- ▶ guess  $\tilde{s}$
- ▶ output  $b' = b - A\tilde{s}$

Good guess ( $s = \tilde{s}$ ):

$$b' = e$$

follows a discrete Gaussian  
of **small deviation**



# Search to distinguish

Very naive attack: guess secret  $\tilde{s}$

$$\begin{array}{c} A \\ \begin{array}{|c|c|c|c|} \hline 8 & 9 & 10 & 12 \\ \hline 5 & 3 & 11 & 3 \\ \hline 0 & 15 & 10 & 4 \\ \hline 15 & 9 & 16 & 15 \\ \hline 1 & 2 & 10 & 8 \\ \hline 11 & 16 & 13 & 9 \\ \hline \end{array} \end{array} \times \left( \begin{array}{c} s \\ \begin{array}{|c|} \hline \phantom{0} \\ \hline \end{array} \end{array} - \begin{array}{c} \tilde{s} \\ \begin{array}{|c|} \hline 3 \\ \hline 11 \\ \hline 0 \\ \hline 14 \\ \hline \end{array} \end{array} \right) + \begin{array}{c} e \\ \begin{array}{|c|} \hline \phantom{0} \\ \hline \end{array} \end{array} = \begin{array}{c} b' \\ \begin{array}{|c|} \hline 7 \\ \hline 2 \\ \hline 3 \\ \hline 15 \\ \hline 11 \\ \hline 8 \\ \hline \end{array} \end{array}$$

Attack:

- ▶ get  $(A, b)$
- ▶ guess  $\tilde{s}$
- ▶ output  $b' = b - A\tilde{s}$

Good guess ( $s = \tilde{s}$ ):

$$b' = e$$

follows a discrete Gaussian  
of **small deviation**

Bad guess ( $s \neq \tilde{s}$ ):

$$b' = e + A(s - \tilde{s})$$

follows a uniform<sup>1</sup> distribution  
( $A$  uniform in  $\mathbb{Z}_q^{m \times n}$ )

<sup>1</sup>Technically only true for fixed  $s$ , random  $A$  and  $\tilde{s}$

# Uniform/Gaussian distinguisher

Given a sampler for  $\chi^m$ , **decide** if  $\chi = U(\mathbb{Z}_q)$  or  $D_{\sigma,q}$  (discrete Gaussian)

# Uniform/Gaussian distinguisher

Given a sampler for  $\chi^m$ , **decide** if  $\chi = U(\mathbb{Z}_q)$  or  $D_{\sigma,q}$  (discrete Gaussian)

The entries are **independent**: given a sample from  $\chi^m$  we obtain  $m$  independent samples from  $\chi$ .

$\leadsto$  if  $m$  large enough, we know how to distinguish.

# Uniform/Gaussian distinguisher

Given a sampler for  $\chi$ , **decide** if  $\chi = U(\mathbb{Z}_q)$  or  $D_{\sigma,q}$  (discrete Gaussian)

# Uniform/Gaussian distinguisher

Given a sampler for  $\chi$ , **decide** if  $\chi = U(\mathbb{Z}_q)$  or  $D_{\sigma,q}$  (discrete Gaussian)

**Essentially optimal distinguisher:** use Fourier transform

$$\mathbb{E}_{x \leftarrow \chi}[e^{2i\pi x/q}], \text{Var}_{x \leftarrow \chi}[e^{2i\pi x/q}] \approx \begin{cases} 0, 0 & \text{if } \chi = U(\mathbb{Z}_q) \\ e^{-2\left(\frac{\pi\sigma}{q}\right)^2}, e^{-8\left(\frac{\pi\sigma}{q}\right)^2} & \text{if } \chi = D_{\sigma,q} \end{cases}$$

# Uniform/Gaussian distinguisher

Given a sampler for  $\chi$ , **decide** if  $\chi = U(\mathbb{Z}_q)$  or  $D_{\sigma,q}$  (discrete Gaussian)

**Essentially optimal distinguisher:** use Fourier transform

$$\mathbb{E}_{x \leftarrow \chi}[e^{2i\pi x/q}], \text{Var}_{x \leftarrow \chi}[e^{2i\pi x/q}] \approx \begin{cases} 0, 0 & \text{if } \chi = U(\mathbb{Z}_q) \\ e^{-2\left(\frac{\pi\sigma}{q}\right)^2}, e^{-8\left(\frac{\pi\sigma}{q}\right)^2} & \text{if } \chi = D_{\sigma,q} \end{cases}$$

**Attack:**

- ▶ sample  $N = \Omega(1/\varepsilon^2)$  values  $x_1, \dots, x_N$  from  $\chi$
- ▶ compute

$$S = \frac{1}{N} \sum_{j=1}^N e^{2i\pi x_j/q}$$

- ▶ Check if  $S > e^{-2\left(\frac{\pi\sigma}{q}\right)^2}$

The quantity  $\varepsilon = e^{-2\left(\frac{\pi\sigma}{q}\right)^2}$  is called the **advantage**.

# Very naive attack: summary

## Very naive attack:

- ▶ guess  $\tilde{s}$ :  $q^n$  possibilities
- ▶ compute  $1/\epsilon^2$  samples to check guess

# Very naive attack: summary

## Very naive attack:

- ▶ guess  $\tilde{s}$ :  $q^n$  possibilities
- ▶ compute  $1/\varepsilon^2$  samples to check guess

Complexity estimate:

$$q^n \cdot e^{4\left(\frac{\pi\sigma_e}{q}\right)^2} = \text{too much}$$



# Very naive attack: summary

## Very naive attack:

- ▶ guess  $\tilde{s}$ :  $q^n$  possibilities
- ▶ compute  $1/\varepsilon^2$  samples to check guess

Complexity estimate:

$$q^n \cdot e^{4\left(\frac{\pi\sigma_e}{q}\right)^2} = \text{too much}$$

Can do better by guessing  $s$  in decreasing order of probability<sup>1</sup>:

$$G(\chi_s^n) \cdot e^{4\left(\frac{\pi\sigma_e}{q}\right)^2} \leq (1.22\sqrt{2\pi}\sigma_s)^n \cdot e^{4\left(\frac{\pi\sigma_e}{q}\right)^2} = \text{too much}$$

where  $\sigma_s$  deviation of  $s$ ,  $G(\cdot)$  = guessing complexity

---

<sup>1</sup>The complexity is now the expected running time

# Very naive attack: summary

## Very naive attack:

- ▶ guess  $\tilde{s}$ :  $q^n$  possibilities
- ▶ compute  $1/\varepsilon^2$  samples to check guess

Complexity estimate:

$$q^n \cdot e^{4\left(\frac{\pi\sigma_e}{q}\right)^2} = \text{too much}$$

Can do better by guessing  $s$  in decreasing order of probability<sup>1</sup>:

$$G(\chi_s^n) \cdot e^{4\left(\frac{\pi\sigma_e}{q}\right)^2} \leq (1.22\sqrt{2\pi}\sigma_s)^n \cdot e^{4\left(\frac{\pi\sigma_e}{q}\right)^2} = \text{too much}$$

where  $\sigma_s$  deviation of  $s$ ,  $G(\cdot)$  = guessing complexity

Dual attacks: provide an efficient way to only guess a part of the secret

---


<sup>1</sup>The complexity is now the expected running time

# Search to Decision LWE

$$\begin{array}{ccccc} & A & & s & e & & b \\ \begin{array}{|c|c|c|c|c|} \hline 3 & 7 & 2 & 3 & 6 \\ \hline 4 & 1 & 5 & 8 & 4 \\ \hline 1 & 8 & 1 & 8 & 1 \\ \hline 5 & 2 & 5 & 6 & 0 \\ \hline 2 & 1 & 6 & 3 & 0 \\ \hline 8 & 2 & 7 & 3 & 6 \\ \hline 5 & 5 & 6 & 6 & 2 \\ \hline \end{array} & \times & \begin{array}{|c|} \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \end{array} & + & \begin{array}{|c|} \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \phantom{0} \\ \hline \end{array} & = & \begin{array}{|c|} \hline 1 \\ \hline 8 \\ \hline 6 \\ \hline 4 \\ \hline 1 \\ \hline 2 \\ \hline 1 \\ \hline \end{array} \end{array}$$

# Search to Decision LWE

Split secret:  $n = k_{\text{fft}} + k_{\text{lat}}$



# Search to Decision LWE

Split secret:  $n = k_{\text{fft}} + k_{\text{lat}}$

The diagram illustrates the equation for the Search to Decision LWE problem. It shows the multiplication of two matrices,  $A_{\text{fft}}$  and  $A_{\text{lat}}$ , by two vectors,  $s_{\text{fft}}$  and  $s_{\text{lat}}$ , followed by an addition of a vector  $e$  to produce a vector  $b$ .

The equation is represented as:

$$A_{\text{fft}} \times s_{\text{fft}} + A_{\text{lat}} \times s_{\text{lat}} + e = b$$

The components are visualized as follows:

- $A_{\text{fft}}$  is a tall blue rectangle.
- $s_{\text{fft}}$  is a short red rectangle.
- $A_{\text{lat}}$  is a tall blue rectangle.
- $s_{\text{lat}}$  is a short red rectangle.
- $e$  is a tall green rectangle.
- $b$  is a tall blue rectangle containing the values 1, 8, 6, 4, 1, 2, 1.

# Search to Decision LWE

Split secret:  $n = k_{\text{fft}} + k_{\text{lat}}$ , guess  $\tilde{s}_{\text{fft}}$ , output  $(A_{\text{lat}}, b' = b - A_{\text{fft}}\tilde{s}_{\text{fft}})$

The diagram illustrates the LWE equation using colored rectangles to represent vectors and matrices. Above the rectangles are labels:  $A_{\text{fft}}$  (blue),  $s_{\text{fft}}$  (red),  $\tilde{s}_{\text{fft}}$  (orange),  $A_{\text{lat}}$  (blue),  $s_{\text{lat}}$  (red),  $e$  (green), and  $b'$  (blue). The equation is shown as follows:

$$A_{\text{fft}} \times (s_{\text{fft}} - \tilde{s}_{\text{fft}}) + A_{\text{lat}} \times s_{\text{lat}} + e = b'$$

The result vector  $b'$  is shown as a column of six boxes containing the values 0, 5, 8, 7, 1, and 3 from top to bottom.

# Search to Decision LWE

Split secret:  $n = k_{\text{fft}} + k_{\text{lat}}$ , guess  $\tilde{s}_{\text{fft}}$ , output  $(A_{\text{lat}}, b' = b - A_{\text{fft}}\tilde{s}_{\text{fft}})$

$$A_{\text{fft}} \times (s_{\text{fft}} - \tilde{s}_{\text{fft}}) + A_{\text{lat}} \times s_{\text{lat}} + e = b'$$

0
5
8
7
1
3
5

Good guess ( $s_{\text{fft}} = \tilde{s}_{\text{fft}}$ ):

$$b' = A_{\text{lat}} s_{\text{lat}} + e$$

so  $(A_{\text{lat}}, b')$  follows an LWE distribution

# Search to Decision LWE

Split secret:  $n = k_{\text{fft}} + k_{\text{lat}}$ , guess  $\tilde{s}_{\text{fft}}$ , output  $(A_{\text{lat}}, b' = b - A_{\text{fft}}\tilde{s}_{\text{fft}})$

$$A_{\text{fft}} \times (s_{\text{fft}} - \tilde{s}_{\text{fft}}) + A_{\text{lat}} \times s_{\text{lat}} + e = b'$$

0
5
8
7
1
3
5

Good guess ( $s_{\text{fft}} = \tilde{s}_{\text{fft}}$ ):

$$b' = A_{\text{lat}} s_{\text{lat}} + e$$

so  $(A_{\text{lat}}, b')$  follows an LWE distribution

Bad guess ( $s_{\text{fft}} \neq \tilde{s}_{\text{fft}}$ ):

$$b' = A_{\text{fft}}(s_{\text{fft}} - \tilde{s}_{\text{fft}}) + \dots$$

so  $(A_{\text{lat}}, b')$  follows a uniform distribution ( $A_{\text{fft}}$  uniform)




# Uniform/LWE distinguisher

Given a sampler for  $\chi$ , **decide** if  $\chi = \text{uniform}$  or LWE.

# Uniform/LWE distinguisher

Given a sampler for  $\chi$ , **decide** if  $\chi = \text{uniform}$  or LWE.

- ▶ sample  $(A_{\text{lat}}, b')$  from  $\chi$
- ▶ compute  $x \in \mathbb{Z}_q^m$  such that  $x^T A_{\text{lat}} = 0$
- ▶ output  $x^T b'$



A diagram illustrating the dot product operation. On the left, a horizontal pink rectangle contains the text  $x^T$ . To its right is a black multiplication symbol  $\times$ . To the right of the symbol is a vertical blue rectangle containing the text  $b'$ .

# Uniform/LWE distinguisher

Given a sampler for  $\chi$ , **decide** if  $\chi = \text{uniform}$  or LWE.

- ▶ sample  $(A_{\text{lat}}, b')$  from  $\chi$
- ▶ compute  $x \in \mathbb{Z}_q^m$  such that  $x^T A_{\text{lat}} = 0$
- ▶ output  $x^T b'$

$$\boxed{x^T} \times \boxed{b'} = \boxed{x^T} \times \left( \boxed{A_{\text{lat}}} \times \boxed{s_{\text{lat}}} + \boxed{e} \right) = \boxed{x^T} \times \boxed{e}$$

# Uniform/LWE distinguisher

Given a sampler for  $\chi$ , **decide** if  $\chi = \text{uniform}$  or LWE.

- ▶ sample  $(A_{\text{lat}}, b')$  from  $\chi$
- ▶ compute  $x \in \mathbb{Z}_q^m$  such that  $x^T A_{\text{lat}} = 0$
- ▶ output  $x^T b'$

$$x^T \times b' = x^T \times \left( A_{\text{lat}} \times s_{\text{lat}} + e \right) = x^T \times e$$

When  $\chi = \text{LWE}$ :

$$x^T b' = x^T e$$

follows an approximate  
**Gaussian distribution**

# Uniform/LWE distinguisher

Given a sampler for  $\chi$ , **decide** if  $\chi = \text{uniform}$  or LWE.

- ▶ sample  $(A_{\text{lat}}, b')$  from  $\chi$
- ▶ compute  $x \in \mathbb{Z}_q^m$  such that  $x^T A_{\text{lat}} = 0$
- ▶ output  $x^T b'$

$$x^T \times b' = x^T \times \left( A_{\text{lat}} \times s_{\text{lat}} + e \right) = x^T \times e$$

When  $\chi = \text{LWE}$ :

$$x^T b' = x^T e$$

follows an approximate  
**Gaussian distribution**

When  $\chi = \text{Uniform}$ :

$$x^T b'$$

follows a uniform distribution ( $b'$   
uniform, independent from  $A_{\text{lat}}$ )

# Dual attack: naive complexity

## Naive dual attack:

- ▶ split secret  $n = k_{\text{fft}} + k_{\text{lat}}$
- ▶ compute dual vectors  $x$  and dot products  $x^T b$
- ▶ guess  $\tilde{s}_{\text{fft}}$ , subtract guess
- ▶ compute  $1/\epsilon^2$  samples to check guess

# Dual attack: naive complexity

## Naive dual attack:

- ▶ split secret  $n = k_{\text{fft}} + k_{\text{lat}}$
- ▶ compute dual vectors  $\mathbf{x}$  and dot products  $\mathbf{x}^T \mathbf{b}$
- ▶ guess  $\tilde{\mathbf{s}}_{\text{fft}}$ , subtract guess
- ▶ compute  $1/\varepsilon^2$  samples to check guess

## What is $\varepsilon$ ?

- ▶  $\mathbf{e}$  approx Gaussian deviation  $\sigma_e$
- ▶  $\mathbf{x}^T \mathbf{b} = \mathbf{x}^T \mathbf{e}$  approx Gaussian deviation  $\|\mathbf{x}\| \sigma_e$

# Dual attack: naive complexity

## Naive dual attack:

- ▶ split secret  $n = k_{\text{fft}} + k_{\text{lat}}$
- ▶ compute dual vectors  $x$  and dot products  $x^T b$
- ▶ guess  $\tilde{s}_{\text{fft}}$ , subtract guess
- ▶ compute  $1/\varepsilon^2$  samples to check guess

## What is $\varepsilon$ ?

- ▶  $e$  approx Gaussian deviation  $\sigma_e$
- ▶  $x^T b = x^T e$  approx Gaussian deviation  $\|x\| \sigma_e$

## Complexity estimate:

$$q^{k_{\text{fft}}} \cdot e^{4 \left( \frac{\pi \|x\| \sigma_e}{q} \right)^2} + (\text{time to compute many } x)$$



# Dual attack: naive complexity

## Naive dual attack:

- ▶ split secret  $n = k_{\text{fft}} + k_{\text{lat}}$
- ▶ compute dual vectors  $\mathbf{x}$  and dot products  $\mathbf{x}^T \mathbf{b}$
- ▶ guess  $\tilde{\mathbf{s}}_{\text{fft}}$ , subtract guess
- ▶ compute  $1/\varepsilon^2$  samples to check guess

## What is $\varepsilon$ ?

- ▶  $\mathbf{e}$  approx Gaussian deviation  $\sigma_e$
- ▶  $\mathbf{x}^T \mathbf{b} = \mathbf{x}^T \mathbf{e}$  approx Gaussian deviation  $\|\mathbf{x}\| \sigma_e$

## Complexity estimate:

$$q^{k_{\text{fft}}} \cdot e^{4 \left( \frac{\pi \|\mathbf{x}\| \sigma_e}{q} \right)^2} + (\text{time to compute many } \mathbf{x})$$

→ we want  $\mathbf{x}$  to be short

# Dual attack: naive complexity

## Naive dual attack:

- ▶ split secret  $n = k_{\text{fft}} + k_{\text{lat}}$
- ▶ compute dual vectors  $\mathbf{x}$  and dot products  $\mathbf{x}^T \mathbf{b}$
- ▶ guess  $\tilde{\mathbf{s}}_{\text{fft}}$ , subtract guess
- ▶ compute  $1/\varepsilon^2$  samples to check guess

## What is $\varepsilon$ ?

- ▶  $\mathbf{e}$  approx Gaussian deviation  $\sigma_e$
- ▶  $\mathbf{x}^T \mathbf{b} = \mathbf{x}^T \mathbf{e}$  approx Gaussian deviation  $\|\mathbf{x}\| \sigma_e$

## Complexity estimate:


$$q^{k_{\text{fft}}} \cdot e^{4 \left( \frac{\pi \|\mathbf{x}\| \sigma_e}{q} \right)^2} + (\text{time to compute many } \mathbf{x})$$

$\leadsto$  we want  $\mathbf{x}$  to be short  $\leadsto$  lattice reduction


# What is a (Euclidean) lattice?

## Definition

$\mathcal{L}(\mathbf{b}_1, \dots, \mathbf{b}_n) = \left\{ \sum_{i=1}^n x_i \mathbf{b}_i : x_i \in \mathbb{Z} \right\}$  where  $\mathbf{b}_1, \dots, \mathbf{b}_n$  is a basis of  $\mathbb{R}^n$ .




# Lattice-based cryptography: fundamental idea



- ▶ **good basis:** private information, makes problem easy
- ▶ **bad basis:** public information, makes problem hard

# Lattice-based cryptography: fundamental idea



- ▶ **good basis**: private information, makes problem easy
- ▶ **bad basis**: public information, makes problem hard

**Basis reduction**: transform a bad basis into a good one

**Main tool**: BKZ algorithm and its variants

Requires to solve the **(approx-)SVP problem** in smaller dimensions.

# An important optimization

- ▶  $b' = b - A_{\text{fft}} \tilde{s}_{\text{fft}}$  comes from search to distinguish reduction
- ▶  $x_1, \dots, x_N$  is a list of dual vectors
- ▶  $\alpha_j = x_j^T b'$  comes from uniform/LWE to uniform/Gaussian red.

To distinguish between unidimensional uniform/Gaussian, we compute

$$F(\tilde{s}_{\text{fft}}) = \sum_{j=1}^N e^{\frac{2i\pi}{q} \alpha_j}$$

# An important optimization

- ▶  $b' = b - A_{\text{fft}} \tilde{s}_{\text{fft}}$  comes from search to distinguish reduction
- ▶  $x_1, \dots, x_N$  is a list of dual vectors
- ▶  $\alpha_j = x_j^T b'$  comes from uniform/LWE to uniform/Gaussian red.

To distinguish between unidimensional uniform/Gaussian, we compute

$$F(\tilde{s}_{\text{fft}}) = \sum_{j=1}^N e^{\frac{2i\pi}{q} \alpha_j} = \sum_{j=1}^N e^{\frac{2i\pi}{q} x_j^T (b - A_{\text{fft}} \tilde{s}_{\text{fft}})} = \sum_{j=1}^N e^{\frac{2i\pi}{q} x_j^T b} \cdot e^{-\frac{2i\pi}{q} x_j^T A_{\text{fft}} \tilde{s}_{\text{fft}}}$$

Observation:  $F(\tilde{s}_{\text{fft}}) = \hat{T}(\tilde{s}_{\text{fft}})$  Fourier transform of  $T(x_j^T A_{\text{fft}}) = e^{\frac{2i\pi}{q} x_j^T b}$

# An important optimization

- ▶  $b' = b - A_{\text{fft}} \tilde{s}_{\text{fft}}$  comes from search to distinguish reduction
- ▶  $x_1, \dots, x_N$  is a list of dual vectors
- ▶  $\alpha_j = x_j^T b'$  comes from uniform/LWE to uniform/Gaussian red.

To distinguish between unidimensional uniform/Gaussian, we compute

$$F(\tilde{s}_{\text{fft}}) = \sum_{j=1}^N e^{\frac{2i\pi}{q} \alpha_j} = \sum_{j=1}^N e^{\frac{2i\pi}{q} x_j^T (b - A_{\text{fft}} \tilde{s}_{\text{fft}})} = \sum_{j=1}^N e^{\frac{2i\pi}{q} x_j^T b} \cdot e^{-\frac{2i\pi}{q} x_j^T A_{\text{fft}} \tilde{s}_{\text{fft}}}$$

Observation:  $F(\tilde{s}_{\text{fft}}) = \hat{T}(\tilde{s}_{\text{fft}})$  Fourier transform of  $T(x_j^T A_{\text{fft}}) = e^{\frac{2i\pi}{q} x_j^T b}$

Algorithm:

- ▶  $T \leftarrow k$ -dimensional array set to zero
- ▶  $T[x_j^T A_{\text{fft}}] \leftarrow e^{2i\pi x_j^T b/q}$  for all  $j$
- ▶ compute FFT  $\hat{T}$  of  $T$
- ▶ check all  $\hat{T}[\tilde{s}_{\text{fft}}]$  against threshold

Complexity: array filling time + FFT time + search time =  $O(N + q^{k_{\text{fft}}})$



## Dual attack: summary

- ▶ split secret  $n = k_{\text{fft}} + k_{\text{lat}}$
- ▶ compute many dual vectors  $\times$
- ▶ find  $\tilde{s}_{\text{fft}}$  using FFT

# Dual attack: summary

- ▶ split secret  $n = k_{\text{fft}} + k_{\text{lat}}$
- ▶ compute many dual vectors  $\mathbf{x}$
- ▶ find  $\tilde{\mathbf{s}}_{\text{fft}}$  using FFT

Pick  $\mathbf{x}$  short in lattice  $L$  using BKZ:

$$L = \left\{ \mathbf{x} \in \mathbb{Z}^m : \mathbf{x}^T \mathbf{A}_{\text{lat}} = 0 \bmod q \right\}$$

Complexity estimate:

$$q^{k_{\text{fft}}} + e^{4 \left( \frac{\pi \|\mathbf{x}\| \sigma_e}{q} \right)^2} + T_{\text{BKZ}}$$

## Dual attack: summary

- ▶ split secret  $n = k_{\text{fft}} + k_{\text{lat}}$
- ▶ compute many dual vectors  $\mathbf{x}$
- ▶ find  $\tilde{\mathbf{s}}_{\text{fft}}$  using FFT

Pick  $\mathbf{x}$  short in lattice  $L$  using BKZ:

$$L = \left\{ \mathbf{x} \in \mathbb{Z}^m : \mathbf{x}^T \mathbf{A}_{\text{lat}} = 0 \bmod q \right\}$$

Complexity estimate:

$$q^{k_{\text{fft}}} + e^{4 \left( \frac{\pi \|\mathbf{x}\| \sigma_e}{q} \right)^2} + T_{\text{BKZ}}$$

- ▶ BKZ trade-off: short  $\mathbf{x} \rightsquigarrow$  more expensive algorithm
- ▶ best dual attack parameters  $(k_{\text{fft}}, \dots)$  found by optimization

# Advanced dual attacks

**Modulo switching:** only guess part of secret modulo  $p$  ( $p \ll q$ )

- ▶ reduce guessing complexity
- ▶ increase distinguishing cost due to modulo remainders
- ▶ makes reduced secret dense

# Advanced dual attacks

**Modulo switching:** only guess part of secret modulo  $p$  ( $p \ll q$ )

- ▶ reduce guessing complexity
- ▶ increase distinguishing cost due to modulo remainders
- ▶ makes reduced secret dense

**Hybrid attack:** split secret into three parts

- ▶  $s_{\text{enum}}$ : brute force enumeration by decreasing probability
- ▶  $s_{\text{fft}}$ : guess by FFT
- ▶  $s_{\text{lat}}$ : removed by dual attack

# Advanced dual attacks

**Modulo switching:** only guess part of secret modulo  $p$  ( $p \ll q$ )

- ▶ reduce guessing complexity
- ▶ increase distinguishing cost due to modulo remainders
- ▶ makes reduced secret dense

**Hybrid attack:** split secret into three parts

- ▶  $s_{\text{enum}}$ : brute force enumeration by decreasing probability
- ▶  $s_{\text{fft}}$ : guess by FFT
- ▶  $s_{\text{lat}}$ : removed by dual attack

**BKZ with sieving**

- ▶ obtain many dual vectors at once
- ▶ reducing the number of BKZ reductions

# Hybrid dual attack

Combine enumeration with dual attack:

- ▶ enumerate  $s_{\text{enum}} \in \mathbb{Z}_q^{k_{\text{enum}}}$ 
  - ▶ enumerate all  $s_{\text{fft}} \in \mathbb{Z}_q^{k_{\text{fft}}}$ 
    - ▶ compute a DFT-like sum
    - ▶ check if it is above the threshold

sampled from  $\chi_s^{k_{\text{enum}}}$   
uniform in  $\mathbb{Z}_q^{k_{\text{fft}}}$

# Hybrid dual attack

Combine enumeration with dual attack:

- ▶ enumerate  $s_{\text{enum}} \in \mathbb{Z}_q^{k_{\text{enum}}}$ 
  - ▶ enumerate all  $s_{\text{fft}} \in \mathbb{Z}_q^{k_{\text{fft}}}$ 
    - ▶ compute a DFT-like sum
    - ▶ check if it is above the threshold
- ▶ guessing complexity: try  $s_{\text{enum}}$  in decreasing order of probability
- ▶ FFT: compute all DFT-sums in one go with a FFT
- ▶ dual vectors: compute them once, reuse for all  $s_{\text{enum}}$

sampled from  $\chi_s^{k_{\text{enum}}}$   
uniform in  $\mathbb{Z}_q^{k_{\text{fft}}}$

$$G(\chi_s^{k_{\text{enum}}}) \cdot \left( q^{k_{\text{fft}}} + e^{4 \left( \frac{\pi \|x\| \sigma_e}{q} \right)^2} \right) + T_{\text{BKZ}}$$



# Hybrid dual attack

Combine enumeration with dual attack:

- ▶ enumerate  $s_{\text{enum}} \in \mathbb{Z}_q^{k_{\text{enum}}}$ 
  - ▶ enumerate all  $s_{\text{fft}} \in \mathbb{Z}_q^{k_{\text{fft}}}$ 
    - ▶ compute a DFT-like sum
    - ▶ check if it is above the threshold
- ▶ guessing complexity: try  $s_{\text{enum}}$  in decreasing order of probability
- ▶ FFT: compute all DFT-sums in one go with a FFT
- ▶ dual vectors: compute them once, reuse for all  $s_{\text{enum}}$

sampled from  $\chi_s^{k_{\text{enum}}}$   
uniform in  $\mathbb{Z}_q^{k_{\text{fft}}}$

$$G(\chi_s^{k_{\text{enum}}}) \cdot \left( q^{k_{\text{fft}}} + e^{4 \left( \frac{\pi \|x\| \sigma_e}{q} \right)^2} \right) + T_{\text{BKZ}}$$

Gain: reduce  $k_{\text{lat}} \rightsquigarrow$  decrease BKZ cost

# Recall: split secret + dual vector

Combine: split secret

The diagram illustrates the reconstruction of a vector  $b$  from a split secret and a dual vector. It consists of two main parts connected by an equals sign. In the first part, a blue vector  $b$  is shown to be equal to the product of a blue matrix  $A$  and a red vector  $s$ , plus a green vector  $e$ . In the second part, the same result is shown as the product of a blue matrix  $A_{\text{fft}}$  and a red vector  $s_{\text{fft}}$ , plus a green vector  $e$ . The matrix  $A_{\text{fft}}$  is further decomposed into the product of a blue matrix  $A_{\text{lat}}$  and a red vector  $s_{\text{lat}}$ , plus the same green vector  $e$ . The labels  $b$ ,  $A$ ,  $s$ ,  $e$ ,  $A_{\text{fft}}$ ,  $s_{\text{fft}}$ ,  $A_{\text{lat}}$ ,  $s_{\text{lat}}$ , and  $e$  are placed above their respective blocks. The blocks are colored blue for matrices/vectors, red for split secrets, and green for error vectors.

$$b = A s + e = A_{\text{fft}} s_{\text{fft}} + e = A_{\text{lat}} s_{\text{lat}} + e$$

# Recall: split secret + dual vector

Combine: split secret

The diagram illustrates the combination of a split secret and a dual vector. It shows two equations side-by-side. The first equation is  $b = A s + e$ , where  $b$  is a blue vertical bar,  $A$  is a blue square,  $s$  is a red vertical bar, and  $e$  is a green vertical bar. The second equation is  $A_{\text{fft}} s_{\text{fft}} + A_{\text{lat}} s_{\text{lat}} = e$ , where  $A_{\text{fft}}$  and  $A_{\text{lat}}$  are blue squares,  $s_{\text{fft}}$  and  $s_{\text{lat}}$  are red vertical bars, and  $e$  is a green vertical bar. The equations are connected by an equals sign.

$$b = A s + e = A_{\text{fft}} s_{\text{fft}} + A_{\text{lat}} s_{\text{lat}} + e$$

With: dual vector  $x$  such that  $x^T A_{\text{lat}} = 0$

The diagram shows the application of a dual vector  $x$  to the combined equation. It shows the equation  $x^T b = x^T A_{\text{fft}} s_{\text{fft}} + x^T e$ . The terms  $x^T b$ ,  $x^T A_{\text{fft}}$ , and  $x^T e$  are shown in pink boxes, while  $b$ ,  $A_{\text{fft}}$ ,  $s_{\text{fft}}$ , and  $e$  are shown in their original colors (blue, blue, red, and green respectively).

$$x^T b = x^T A_{\text{fft}} s_{\text{fft}} + x^T e$$

# Fundamental equation of dual attack

- ▶ split secret, find  $(x, y)$  such that  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$

$$\boxed{x^T} \times \boxed{b} = \boxed{y^T} \times \boxed{s_{\text{fft}}} + \boxed{x^T} \times \boxed{e}$$

# Fundamental equation of dual attack

- ▶ split secret, find  $(x, y)$  such that  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$
- ▶ guess secret  $\tilde{s}$  and subtract

$$x^T \times b - y^T \times \tilde{s}_{\text{fft}} = y^T \times (s_{\text{fft}} - \tilde{s}_{\text{fft}}) + x^T \times e$$

# Fundamental equation of dual attack

- ▶ split secret, find  $(x, y)$  such that  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$
- ▶ guess secret  $\tilde{s}$  and subtract

$$x^T \times b - y^T \times \tilde{s}_{\text{fft}} = y^T \times (s_{\text{fft}} - \tilde{s}_{\text{fft}}) + x^T \times e$$

Good guess ( $s_{\text{fft}} = \tilde{s}_{\text{fft}}$ ):

$$x^T e$$

follows a discrete Gaussian of  
small deviation (depends on  $\|x\|$ )

# Fundamental equation of dual attack

- ▶ split secret, find  $(x, y)$  such that  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$
- ▶ guess secret  $\tilde{s}$  and subtract

$$x^T \times b - y^T \times \tilde{s}_{\text{fft}} = y^T \times (s_{\text{fft}} - \tilde{s}_{\text{fft}}) + x^T \times e$$

Good guess ( $s_{\text{fft}} = \tilde{s}_{\text{fft}}$ ):

$$x^T e$$

follows a discrete Gaussian of  
small deviation (depends on  $\|x\|$ )

Bad guess ( $s_{\text{fft}} \neq \tilde{s}_{\text{fft}}$ ):

$$y^T (s_{\text{fft}} - \tilde{s}_{\text{fft}}) + x^T e$$

follows a uniform distribution  
( $y \approx$  uniform in  $\mathbb{Z}_q^{k_{\text{fft}}}$ )

# Fundamental equation of dual attack

- ▶ split secret, find  $(x, y)$  such that  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$
- ▶ guess secret  $\tilde{s}$  and subtract

$$x^T \times b - y^T \times \tilde{s}_{\text{fft}} = y^T \times (s_{\text{fft}} - \tilde{s}_{\text{fft}}) + x^T \times e$$

Good guess ( $s_{\text{fft}} = \tilde{s}_{\text{fft}}$ ):

$$x^T e$$

follows a discrete Gaussian of  
small deviation (depends on  $\|x\|$ )

Bad guess ( $s_{\text{fft}} \neq \tilde{s}_{\text{fft}}$ ):

$$y^T (s_{\text{fft}} - \tilde{s}_{\text{fft}}) + x^T e$$

follows a uniform distribution  
( $y \approx$  uniform in  $\mathbb{Z}_q^{k_{\text{fft}}}$ )

**Problem:** cost of distinguishing grows as  $q^{k_{\text{fft}}}$

$\leadsto$  can we change to a modulo  $p \ll q$  to reduce the cost?



# Modulo switching

- split secret, find  $(x, y)$  s.t.  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$ , guess  $\tilde{s}$

$$\boxed{x^T} \cdot \boxed{b} - \boxed{y^T} \cdot \boxed{\tilde{s}_{\text{fft}}} = \boxed{y^T} \cdot \left( \boxed{s_{\text{fft}}} - \boxed{\tilde{s}_{\text{fft}}} \right) + \boxed{x^T} \cdot \boxed{e} \pmod{q}$$

# Modulo switching

- ▶ split secret, find  $(x, y)$  s.t.  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$ , guess  $\tilde{s}$
- ▶ change modulo to  $p$

$$\frac{p}{q} x^T \cdot b - \frac{p}{q} y^T \cdot \tilde{s}_{\text{fft}} = \frac{p}{q} y^T \cdot (s_{\text{fft}} - \tilde{s}_{\text{fft}}) + \frac{p}{q} x^T \cdot e \pmod{p}$$

# Modulo switching

- ▶ split secret, find  $(x, y)$  s.t.  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$ , guess  $\tilde{s}$
- ▶ change modulo to  $p$

$$\frac{p}{q} x^T \cdot b - \frac{p}{q} y^T \cdot \tilde{s}_{\text{fft}} = \frac{p}{q} y^T \cdot (s_{\text{fft}} - \tilde{s}_{\text{fft}}) + \frac{p}{q} x^T \cdot e \pmod{p}$$

Good guess ( $s_{\text{fft}} = \tilde{s}_{\text{fft}}$ ):

$$\frac{p}{q} x^T e$$

follows a discrete Gaussian of small deviation (depends on  $\|x\|$ )

Bad guess ( $s_{\text{fft}} \neq \tilde{s}_{\text{fft}}$ ):

$$\frac{p}{q} y^T (s_{\text{fft}} - \tilde{s}_{\text{fft}}) + \frac{p}{q} x^T e$$

follows a uniform distribution ( $y \approx$  uniform in  $\mathbb{Z}_q^{k_{\text{fft}}}$ )

# Modulo switching

- ▶ split secret, find  $(x, y)$  s.t.  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$ , guess  $\tilde{s}$
- ▶ change modulo to  $p$

$$\frac{p}{q} x^T \cdot b - \frac{p}{q} y^T \cdot \tilde{s}_{\text{fft}} = \frac{p}{q} y^T \cdot (s_{\text{fft}} - \tilde{s}_{\text{fft}}) + \frac{p}{q} x^T \cdot e \pmod{p}$$

Good guess ( $s_{\text{fft}} = \tilde{s}_{\text{fft}}$ ):

$$\frac{p}{q} x^T e$$

follows a discrete Gaussian of small deviation (depends on  $\|x\|$ )

Bad guess ( $s_{\text{fft}} \neq \tilde{s}_{\text{fft}}$ ):

$$\frac{p}{q} y^T (s_{\text{fft}} - \tilde{s}_{\text{fft}}) + \frac{p}{q} x^T e$$

follows a uniform distribution ( $y \approx$  uniform in  $\mathbb{Z}_q^{k_{\text{fft}}}$ )

**Problem:**  $\frac{p}{q} y^T$  is not integral

$\leadsto$  FFT distinguisher not applicable

# Modulo switching (cont)

Notation:  $[x]$  = integer part,  $\{x\}$  = fractional part,  $x = [x] + \{x\}$

$$\frac{p}{q} x^T \cdot b - \frac{p}{q} y^T \cdot \tilde{s}_{\text{fft}} = \frac{p}{q} y^T \cdot \left( s_{\text{fft}} - \tilde{s}_{\text{fft}} \right) + \varepsilon \pmod{p}$$

where  $\varepsilon = \frac{p}{q} x^T \cdot e$

# Modulo switching (cont)

Notation:  $[x]$  = integer part,  $\{x\}$  = fractional part,  $x = [x] + \{x\}$

$$\left\lfloor \frac{p}{q} x^T \right\rfloor \cdot b - \left\lfloor \frac{p}{q} y^T \right\rfloor \cdot \tilde{s}_{\text{fft}} = \left\lfloor \frac{p}{q} y^T \right\rfloor \cdot \left( s_{\text{fft}} - \tilde{s}_{\text{fft}} \right) + \varepsilon \pmod{p}$$

where  $\varepsilon = \left\{ \frac{p}{q} y^T \right\} \cdot s_{\text{fft}} + \frac{p}{q} x^T \cdot e$

# Modulo switching (cont)

Notation:  $[x]$  = integer part,  $\{x\}$  = fractional part,  $x = [x] + \{x\}$

$$\left\lfloor \frac{p}{q} x^T \right\rfloor \cdot b - \left\lfloor \frac{p}{q} y^T \right\rfloor \cdot \tilde{s}_{\text{fft}} = \left\lfloor \frac{p}{q} y^T \right\rfloor \cdot \left( s_{\text{fft}} - \tilde{s}_{\text{fft}} \right) + \varepsilon \pmod{p}$$

$$\text{where } \varepsilon = \left\{ \frac{p}{q} y^T \right\} \cdot s_{\text{fft}} + \left\{ \frac{p}{q} x^T \right\} \cdot e$$

Good guess ( $s_{\text{fft}} = \tilde{s}_{\text{fft}}$ ):

$$\varepsilon = \{ \frac{p}{q} x^T \} s_{\text{fft}} + \frac{p}{q} x^T e$$

follows an **almost** discrete  
Gaussian of small deviation (now  
depends on  $\|x\|$  and  $\|s_{\text{fft}}\|$ )

# Modulo switching (cont)

Notation:  $[x]$  = integer part,  $\{x\}$  = fractional part,  $x = [x] + \{x\}$

$$\left\lfloor \frac{p}{q} x^T \right\rfloor \cdot b - \left\lfloor \frac{p}{q} y^T \right\rfloor \cdot \tilde{s}_{\text{fft}} = \left\lfloor \frac{p}{q} y^T \right\rfloor \cdot \left( s_{\text{fft}} - \tilde{s}_{\text{fft}} \right) + \varepsilon \pmod{p}$$

$$\text{where } \varepsilon = \left\lfloor \frac{p}{q} y^T \right\rfloor \cdot s_{\text{fft}} + \left\lfloor \frac{p}{q} x^T \right\rfloor \cdot e$$

Good guess ( $s_{\text{fft}} = \tilde{s}_{\text{fft}}$ ):

$$\varepsilon = \left\{ \frac{p}{q} x^T \right\} s_{\text{fft}} + \frac{p}{q} x^T e$$

follows an **almost** discrete Gaussian of small deviation (now depends on  $\|x\|$  and  $\|s_{\text{fft}}\|$ )

Bad guess ( $s_{\text{fft}} \neq \tilde{s}_{\text{fft}}$ ):

$$\left\lfloor \frac{p}{q} y^T \right\rfloor (s_{\text{fft}} - \tilde{s}_{\text{fft}})$$

**not obviously** uniform, but saved by the hybrid search hinted at in this presentation



# Modulo switching (cont)

Notation:  $[x]$  = integer part,  $\{x\}$  = fractional part,  $x = [x] + \{x\}$

$$\left\lfloor \frac{p}{q} x^T \right\rfloor \cdot b - \left\lfloor \frac{p}{q} y^T \right\rfloor \cdot \tilde{s}_{\text{fft}} = \left\lfloor \frac{p}{q} y^T \right\rfloor \cdot \left( s_{\text{fft}} - \tilde{s}_{\text{fft}} \right) + \varepsilon \mod p$$

$$\text{where } \varepsilon = \left\lfloor \frac{p}{q} y^T \right\rfloor \cdot s_{\text{fft}} + \left\lfloor \frac{p}{q} x^T \right\rfloor \cdot e$$

Good guess ( $s_{\text{fft}} = \tilde{s}_{\text{fft}}$ ):

$$\varepsilon = \left\{ \frac{p}{q} x^T \right\} s_{\text{fft}} + \frac{p}{q} x^T e$$

follows an **almost** discrete Gaussian of small deviation (now depends on  $\|x\|$  and  $\|s_{\text{fft}}\|$ )

Bad guess ( $s_{\text{fft}} \neq \tilde{s}_{\text{fft}}$ ):

$$\left\lfloor \frac{p}{q} y^T \right\rfloor (s_{\text{fft}} - \tilde{s}_{\text{fft}})$$

**not obviously** uniform, but saved by the hybrid search hinted at in this presentation

**Conclusion:** it works but increases the number of samples:

$$\text{from } 4 \left( \frac{\pi \|x\| \sigma_e}{q} \right)^2 \quad \text{to} \quad 4 \left( \frac{\pi \|x\| \sigma_e}{q} \right)^2 + \frac{1}{3} \left( \frac{\pi \|s_{\text{fft}}\| q}{p} \right)^2$$

## Going further: using ideas from coding theory

Everything until this point is in the LWE report by the MATZOV group.

## Going further: using ideas from coding theory

Everything until this point is in the LWE report by the MATZOV group.

**Modulo switching:** approximate a vector  $x \in \mathbb{Z}_q^n$  by

$$x = \frac{q}{p} \cdot \left[ \frac{p}{q} x \right] + \frac{q}{p} \left\{ \frac{p}{q} x \right\} = \frac{q}{p} \cdot u + e$$

- ▶  $u \in \mathbb{Z}_p^n$ : smaller domain (field is smaller)
- ▶  $\|e\| \leq \frac{q}{p}$ : “small error”

## Going further: using ideas from coding theory

Everything until this point is in the LWE report by the MATZOV group.

**Modulo switching:** approximate a vector  $x \in \mathbb{Z}_q^n$  by

$$x = \frac{q}{p} \cdot \left[ \frac{p}{q} x \right] + \frac{q}{p} \left\{ \frac{p}{q} x \right\} = \frac{q}{p} \cdot u + e$$

- ▶  $u \in \mathbb{Z}_p^n$ : smaller domain (field is smaller)
- ▶  $\|e\| \leq \frac{q}{p}$ : “small error”

**Our observation:** this looks like a special case of **lattice codes**

$$x = Gu + t$$

- ▶  $G \in \mathbb{Z}_q^{n \times m}$ : defines a code
- ▶  $u \in \mathbb{Z}_q^m$ : smaller domain (dimension is smaller)
- ▶  $\|t\|$  is small (depends on  $G$ )

# Applying lattice codes

Recall: find  $(x, y)$  such that  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$

$$\boxed{x^T} \times \boxed{b} = \boxed{y^T} \times \boxed{s_{\text{fft}}} + \boxed{x^T} \times \boxed{e}$$

# Applying lattice codes

Recall: find  $(x, y)$  such that  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$

$$\boxed{x^T} \times \boxed{b} = \boxed{y^T} \times \boxed{s_{\text{fft}}} + \boxed{x^T} \times \boxed{e}$$

Choose a code  $G \in \mathbb{Z}_q^{k_{\text{fft}} \times k_{\text{cod}}}$ , decode  $y$  as

$$\boxed{y} = \boxed{G} \times \boxed{u} + \boxed{t}$$

# Applying lattice codes

Recall: find  $(x, y)$  such that  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$

$$x^T \times b = y^T \times s_{\text{fft}} + x^T \times e$$

Choose a code  $G \in \mathbb{Z}_q^{k_{\text{fft}} \times k_{\text{cod}}}$ , decode  $y$  as

$$y = G \times u + t$$

New fundamental equation:

$$x^T \cdot b = u^T \cdot G^T \cdot s_{\text{fft}} + t^T \cdot s_{\text{fft}} + x^T \cdot e$$

# Lattice codes: fundamental equation

- ▶ find  $(x, y)$  such that  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$
- ▶ choose a code  $G \in \mathbb{Z}_q^{k_{\text{fft}} \times k_{\text{cod}}}$ , decode  $y = Gu + t$

$$x^T \cdot b = u^T \cdot G^T \cdot s_{\text{fft}} + t^T \cdot s_{\text{fft}} + x^T \cdot e$$

The diagram illustrates the fundamental equation of lattice codes. It shows a sequence of operations: a pink box labeled  $x^T$  is multiplied by a light blue vertical box labeled  $b$ . This is equal to a light blue horizontal box labeled  $u^T$  multiplied by a light blue square box labeled  $G^T$ , which is then multiplied by a light red vertical box labeled  $s_{\text{fft}}$ . This is added to a green horizontal box labeled  $t^T$  multiplied by a light red vertical box labeled  $s_{\text{fft}}$ , which is then added to a pink horizontal box labeled  $x^T$  multiplied by a green vertical box labeled  $e$ .



# Lattice codes: fundamental equation

- ▶ find  $(x, y)$  such that  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$
- ▶ choose a code  $G \in \mathbb{Z}_q^{k_{\text{fft}} \times k_{\text{cod}}}$ , decode  $y = Gu + t$

$$\boxed{x^T} \cdot \boxed{b} = \boxed{u^T} \cdot \boxed{s_{\text{cod}}} + \boxed{\epsilon'}$$

where

$$\boxed{s_{\text{cod}}} = \boxed{G^T} \cdot \boxed{s_{\text{fft}}} \qquad \boxed{\epsilon'} = \boxed{t^T} \cdot \boxed{s_{\text{fft}}} + \boxed{x^T} \cdot \boxed{e}$$

# Lattice codes: fundamental equation

- ▶ find  $(x, y)$  such that  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$
- ▶ choose a code  $G \in \mathbb{Z}_q^{k_{\text{fft}} \times k_{\text{cod}}}$ , decode  $y = Gu + t$

$$\boxed{x^T} \cdot \boxed{b} = \boxed{u^T} \cdot \boxed{s_{\text{cod}}} + \boxed{\epsilon'}$$

where

$$\boxed{s_{\text{cod}}} = \boxed{G^T} \cdot \boxed{s_{\text{fft}}} \qquad \boxed{\epsilon'} = \boxed{t^T} \cdot \boxed{s_{\text{fft}}} + \boxed{x^T} \cdot \boxed{e}$$

Observations:

- ▶ we directly guess  $s_{\text{cod}}$  instead of  $s_{\text{fft}}$
- ▶  $s_{\text{cod}} = G^T s_{\text{fft}} \in \mathbb{Z}_q^{k_{\text{cod}}}$  has **smaller dimension**  $k_{\text{cod}} \ll k_{\text{fft}}$

# Lattice codes: fundamental equation

- ▶ find  $(x, y)$  such that  $x^T A_{\text{lat}} = 0$  and  $y^T = x^T A_{\text{fft}}$
- ▶ choose a code  $G \in \mathbb{Z}_q^{k_{\text{fft}} \times k_{\text{cod}}}$ , decode  $y = Gu + t$

$$x^T \cdot b = u^T \cdot s_{\text{cod}} + \epsilon'$$

where

$$s_{\text{cod}} = G^T \cdot s_{\text{fft}} \quad \epsilon' = t^T \cdot s_{\text{fft}} + x^T \cdot e$$

## Observations:

- ▶ we directly guess  $s_{\text{cod}}$  instead of  $s_{\text{fft}}$
- ▶  $s_{\text{cod}} = G^T s_{\text{fft}} \in \mathbb{Z}_q^{k_{\text{cod}}}$  has **smaller dimension**  $k_{\text{cod}} \ll k_{\text{fft}}$
- ▶  $\epsilon = t^T s_{\text{fft}} + x^T e$  follows a discrete Gaussian whose **deviation** depends on  $\|x\|$ ,  $\|s_{\text{fft}}\|$  and  $\|t\|$
- ▶  $\|t\|$  is **small** for a good code  $G$

# Lattice codes vs modulo switching

## Lattice codes

$$x^T \cdot b = u^T \cdot s_{\text{cod}} + \epsilon'$$

## Modulo switching

$$x^T \cdot b = \left[ \frac{p}{q} y^T \right] \cdot s_{\text{fft}} + \epsilon$$

# Lattice codes vs modulo switching

## Lattice codes

$$\boxed{x^T} \cdot \boxed{b} = \boxed{u^T} \cdot \boxed{s_{\text{cod}}} + \boxed{\epsilon'}$$

► FFT cost:  $q^{k_{\text{cod}}}$

► error  $\epsilon'$ : Gaussian of stddev

$$\tau_{\text{MS}}^2 = \|\mathbf{x}\|^2 \cdot \sigma_e^2 + \|\mathbf{s}_{\text{fft}}\|^2 \cdot \frac{q^{2-2\frac{k_{\text{cod}}}{k_{\text{fft}}}}}{2\pi e}$$

for an asymptotically optimal code

## Modulo switching

$$\boxed{x^T} \cdot \boxed{b} = \left[ \frac{p}{q} \boxed{y^T} \right] \cdot \boxed{s_{\text{fft}}} + \boxed{\epsilon}$$

► FFT cost:  $p^{k_{\text{fft}}}$

► error  $\epsilon$ : Gaussian of stddev

$$\tau_{\text{LC}}^2 = \|\mathbf{x}\|^2 \cdot \sigma_e^2 + \|\mathbf{s}_{\text{fft}}\|^2 \cdot \frac{q^2}{12p^2}$$

# Lattice codes vs modulo switching

## Lattice codes

$$\boxed{x^T} \cdot \boxed{b} = \boxed{u^T} \cdot \boxed{s_{\text{cod}}} + \boxed{\epsilon'}$$

► FFT cost:  $q^{k_{\text{cod}}}$

► error  $\epsilon'$ : Gaussian of stddev

$$\tau_{\text{MS}}^2 = \|\mathbf{x}\|^2 \cdot \sigma_e^2 + \|\mathbf{s}_{\text{fft}}\|^2 \cdot q^{2-2\frac{k_{\text{cod}}}{k_{\text{fft}}}} \cdot \frac{q^{2-2\frac{k_{\text{cod}}}{k_{\text{fft}}}}}{2\pi e}$$

for an asymptotically optimal code

## Modulo switching

$$\boxed{x^T} \cdot \boxed{b} = \left[ \frac{p}{q} \boxed{y^T} \right] \cdot \boxed{s_{\text{fft}}} + \boxed{\epsilon}$$

► FFT cost:  $p^{k_{\text{fft}}}$

► error  $\epsilon$ : Gaussian of stddev

$$\tau_{\text{LC}}^2 = \|\mathbf{x}\|^2 \cdot \sigma_e^2 + \|\mathbf{s}_{\text{fft}}\|^2 \cdot \frac{q^2}{12p^2}$$

Comparison for same FFT cost:  $q^{k_{\text{cod}}} = p^{k_{\text{fft}}}$

$$\frac{q^{2-2\frac{k_{\text{cod}}}{k_{\text{fft}}}}}{2\pi e} = \frac{q}{2\pi e p} \approx \frac{q}{17p} \ll \frac{q}{12p}$$

~> lattice codes are always better than modulo switching!

## Other important details

- ▶ FFT is more efficient for powers of two
- ▶  $q^{k_{\text{cod}}}$  has coarse granularity for big  $q$

↪ use modulo switching to change  $q$  to  $p = 2^m$  then use lattice codes:  
best of both, allow more “continuous” parameter choice

## Other important details

- ▶ FFT is more efficient for powers of two

- ▶  $q^{k_{\text{cod}}}$  has coarse granularity for big  $q$

↪ use modulo switching to change  $q$  to  $p = 2^m$  then use lattice codes:  
best of both, allow more “continuous” parameter choice

- ▶ optimal codes are expensive but we need a fast decoder

- ▶ we only need to decode to a close codeword, not the closest

↪ we suggest to use polar codes which are asymptotically optimal



# Other important details

- ▶ FFT is more efficient for powers of two

- ▶  $q^{k_{\text{cod}}}$  has coarse granularity for big  $q$

↪ use modulo switching to change  $q$  to  $p = 2^m$  then use lattice codes:  
best of both, allow more “continuous” parameter choice

- ▶ optimal codes are expensive but we need a fast decoder

- ▶ we only need to decode to a close codeword, not the closest

↪ we suggest to use **polar codes** which are asymptotically optimal

- ▶ many parameters to choose ( $p$ ,  $k_{\text{fft}}$ ,  $k_{\text{cod}}$ , BKZ block size, ...)

- ▶ no obvious way to choose them

↪ search for optimal parameters with an optimisation program

# Prange bet: motivation

Overall attack so far:

- ▶ enumerate  $s_{\text{enum}} \in \mathbb{Z}_q^{k_{\text{enum}}}$  sampled from  $\chi_s^{k_{\text{enum}}}$ 
  - ▶ perform dual attack with codes and modulo switching and check if  $s_{\text{enum}}$  was correct

# Prange bet: motivation

Overall attack so far:

- ▶ enumerate  $s_{\text{enum}} \in \mathbb{Z}_q^{k_{\text{enum}}}$  sampled from  $\chi_s^{k_{\text{enum}}}$ 
  - ▶ perform dual attack with codes and modulo switching and check if  $s_{\text{enum}}$  was correct

Expected complexity:  $G \cdot T$

- ▶  $G$  = expected number of guesses to find  $s_{\text{enum}}$
- ▶  $T$  = complexity of attack

# Prange bet: motivation

## Overall attack so far:

- ▶ enumerate  $s_{\text{enum}} \in \mathbb{Z}_q^{k_{\text{enum}}}$  sampled from  $\chi_s^{k_{\text{enum}}}$ 
  - ▶ perform dual attack with codes and modulo switching and check if  $s_{\text{enum}}$  was correct

## Expected complexity: $G \cdot T$

- ▶  $G$  = expected number of guesses to find  $s_{\text{enum}}$
- ▶  $T$  = complexity of attack

## Prange bet:

- ▶ some values of  $s_{\text{enum}}$  are much more likely than others (e.g. 0)
- ▶ only enumerate a few most likely values
- ▶ if it fails, retry with a permutation of the secret

# Prange bet: motivation

## Overall attack so far:

- ▶ enumerate  $s_{\text{enum}} \in \mathbb{Z}_q^{k_{\text{enum}}}$  sampled from  $\chi_s^{k_{\text{enum}}}$ 
  - ▶ perform dual attack with codes and modulo switching and check if  $s_{\text{enum}}$  was correct

## Expected complexity: $G \cdot T$

- ▶  $G$  = expected number of guesses to find  $s_{\text{enum}}$
- ▶  $T$  = complexity of attack

## Prange bet:

- ▶ some values of  $s_{\text{enum}}$  are much more likely than others (e.g. 0)
- ▶ only enumerate a few most likely values
- ▶ if it fails, retry with a permutation of the secret
- ▶ if we do not permute the lattice part ( $s_{\text{lat}}$ ), we can even reuse the BKZ computation just like in the “normal attack”

# Prange bet: implementation

New attack: fix betting set  $\text{Bet}$

- ▶ for each permutation  $\tau$  that leaves the “lat part ” fixed
  - ▶ enumerate  $s_{\text{enum}} \in \text{Bet}$ 
    - ▶ perform<sup>1</sup> dual attack on  $\tau$ -permuted instance with codes and modulo switching and check if  $s_{\text{enum}}$  was correct

---

<sup>1</sup>Not shown here: dual vectors reused accross iterations since lat part untouched

# Prange bet: implementation

New attack: fix betting set **Bet**

- ▶ for each permutation  $\tau$  that leaves the “lat part ” fixed
  - ▶ enumerate  $s_{\text{enum}} \in \text{Bet}$ 
    - ▶ perform<sup>1</sup> dual attack on  $\tau$ -permuted instance with codes and modulo switching and check if  $s_{\text{enum}}$  was correct

Expected complexity:  $P \cdot |\text{Bet}| \cdot T$

- ▶  $P$  = expected number of permutations needed
- ▶  $T$  = complexity of attack

---

<sup>1</sup>Not shown here: dual vectors reused accross iterations since lat part untouched

# Prange bet: implementation

New attack: fix betting set  $\text{Bet}$

- ▶ for each permutation  $\tau$  that leaves the “lat part ” fixed
  - ▶ enumerate  $s_{\text{enum}} \in \text{Bet}$ 
    - ▶ perform<sup>1</sup> dual attack on  $\tau$ -permuted instance with codes and modulo switching and check if  $s_{\text{enum}}$  was correct

Expected complexity:  $P \cdot |\text{Bet}| \cdot T$

- ▶  $P$  = expected number of permutations needed
- ▶  $T$  = complexity of attack

Which bet?  $\text{Bet} = \{0\}$  optimal in our case

---

<sup>1</sup>Not shown here: dual vectors reused accross iterations since lat part untouched



# Results

- ▶ **CC**: classical circuit model (most detailed cost)
- ▶ **CN**: intermediate model
- ▶ **C0**: “Core-SVP” cost model

Scheme	MATZOV			Codes w/o Prange			Codes w/ Prange		
	CC	CN	C0	CC	CN	C0	CC	CN	C0
Kyber 512	138.5	133.7	114.8	137.8	133.0	114.0	137.5	132.6	113.9
Kyber 768	195.7	190.4	173.1	192.5	187.2	170.2	191.9	186.7	169.8
Kyber 1024	261.4	255.4	240.7	256.2	250.5	235.7	255.5	249.5	235.5
LightSaber	137.1	132.3	113.1	136.8	131.5	112.3	136.7	131.8	112.2
Saber	201.1	195.1	178.3	199.7	194.9	177.0	199.0	193.8	176.9
FireSaber	263.6	257.7	242.8	259.9	254.4	239.4	259.3	253.9	239.0

- ▶ 1 to 5 bit gain without Prange over MATZOV
- ▶ further 1 bit gain with Prange bet