Dashboard / My courses / COSC264 / Week 6: Quiz (Local Area Networks and Medium Access Control) - moved to Week 7

/ Quiz: Local area networks and medium access control

Started on Wednesday, 15 September 2021, 1:57 PM

State Finished

Completed on Thursday, 16 September 2021, 4:57 PM

Time taken 1 day 2 hours

Marks 18.57/19.00

Grade 9.77 out of 10.00 (98%)

When working through the following quiz please keep the following points in mind:

- You are asked to implement a number of Python functions. The default language is Python3.
- Occasionally you will have to use mathematical functions from the Python 'math' package. You will need to add suitable 'import' statements to your solutions and when using such a function you will have to prefix them with the package name, e.g. to call the function 'floor' you will have to write 'math.floor' in your code.
- In many questions it is asked that you enter numerical answers in certain units. For example, we may ask you to enter your answer in milliseconds. If your answer is 0.050 seconds then you will have to enter '50', as this is the equivalent value in milliseconds.

Question 1		
Correct		
Mark 1.00 out of 1.00		

Suppose we are given a system with *N* stations. As per the FDMA scheme, the available channel bandwidth is sub-divided into *N* equal parts or sub-channels (we ignore the guard bands in between) and each station is allocated one of these sub-channels exclusively for its transmission. Suppose a particular station was idle for a long time and then gets handed over a packet from its higher layers for transmission. What is the access delay?

Select one:

2	1 /NI	seconds
a.	I/IN	seconas

b. 0 seconds



d. 1 second

Your answer is correct.

Correct

```
Question 2
Correct
Mark 1.00 out of 1.00
```

Suppose we have an overall system bandwidth of *B* Hz. The bandwidth required for a guard band is *G* Hz and the bandwidth required for one user channel (sub-channel) is *U* Hz. Please find an expression for the maximum number *N* of users that can be accommodated in the system and implement it as a Python function. You will need one of the functions floor / ceil. Note that there also have to be guard bands above the user on the highest channel and below the user on the lowest channel. In other words, *N* users require *N+1* guard bands.

For example:

Test	
<pre>print (number_fdma_channels(1000000, 200, 20000))</pre>	49

Answer: (penalty regime: 10, 20, ... %)

```
Reset answer
  1
    import math
  2 🔻
     def number_fdma_channels (b_hz, g_hz, u_hz):
  3
         return math.floor(b_hz/(g_hz + u_hz))
  5
  6
         # Also works below
  7
         # N_channel_and_guard_hz = b_hz - g_hz
  8
  9
         # N = math.floor(N_channel_and_guard_hz/ (g_hz + u_hz))
 10
 11
         # return N
```

	Test	Expected	Got	
~	print (number_fdma_channels(1000000, 200, 20000))	49	49	~
~	<pre>print (number_fdma_channels(1000000, 1000, 20000))</pre>	47	47	~

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **3**Correct
Mark 1.00 out of 1.00

Evaluate your expression for the number of FDMA channels assuming B = 1 MHz, G = 1 kHz, U = 30 kHz.

Answer: 32 ✓

Correct

```
Question 4
Correct
Mark 0.90 out of 1.00
```

Suppose we are operating with TDMA using a superframe length of *S* seconds, a guard time of *G* seconds, and the length of a user slot is *U* seconds. Please find an expression for the maximum number of users that the system can support and implement it as a Python function. You will need one of the functions ceil/floor.

For example:

Test	
print (number_tdma_users(1, 0.001, 0.0	908)) 111

Answer: (penalty regime: 10, 20, ... %)

```
Reset answer
```

```
import math
def number_tdma_users (s_s, g_s, u_s):

# N_channel_and_guard_hz = s_s - g_s

# N = math.floor(N_channel_and_guard_hz/ (g_s + u_s))

# return N + 1
return math.floor(s_s/(g_s + u_s))
```

	Test	Expected	Got	
~	print (number_tdma_users(1, 0.001, 0.008))	111	111	~
~	print (number_tdma_users(1.2, 0.002, 0.02))	54	54	~

Passed all tests! 🗸

Correct


Marks for this submission: 1.00/1.00. Accounting for previous tries, this gives 0.90/1.00.

Question 5
Correct
Mark 1.00 out of 1.00

Evaluate your expression for S = 100 ms, G = 1 ms, U = 5 ms.

Answer: 16

Correct



Assume again TDMA with a superframe length S = 100 ms, guard time G = 1 ms, and length of user slot U = 5 ms. What is the average access delay of a particular user, when this user has been idle for a long time before and a new packet arrives to this user from its higher layers at a random time? Please give the value in milliseconds.



For the questions in this unit please review discrete random variables, in particular the two different types of geometric random variables:

- In the first type we consider a series of repeated and independent Bernoulli trials, where each trial has success probability p, and a geometric random variable of the first kind counts the number of failed experiments before the first success. The probability mass function for the first formulation is $p(k) = p(1-p)^k$, for k in $\{0, 1, 2, 3, ...\}$, and the expectation is q/p, where q=1-p.
- In the second type we count the number of trials we have to make until we see the success (so the success has to be counted as well). The probability mass function is $p(k)=p^*(1-p)^{(k-1)}$ for k in $\{1, 2, 3, ...\}$, and the expectation is 1/p.

Question 7		
Correct		
Mark 1.00 ou	rt of 1.00	
Assume milliseco		oth of 1ms. How long is the vulnerable period of one packet? Please give the value in
Answer:	2	•
Correct Marks for	this submission: 1.00/1.00.	

Correct
Mark 1.00 out of 1.00

Assume Pure ALOHA. What is the access delay for a packet arriving to a station that is idle? Please give the value in milliseconds.



0, as station transmits immediately without carrier-sensing

Correct

Question 8

Answer: ₁

1, as both start immediately after the previous transmission ends

Correct

```
Question 12
Correct
Mark 1.00 out of 1.00
```

Consider the same setting as in the previous question, but now with p-persistent CSMA for some probability value 0 . Please find an expression for the probability that both contenders collide. Assume that they are statistically independent. You will need to:

- work out the probability that they collide in the first time slot, the probability that they collide in the second time slot, the probability that they collide in the *k*-th time slot etc.,
- · combine these probabilities using the law of total probability,
- and when calculating the end result you will need the sum formula for the (infinite) geometric series.

Implement your expression as a Python function.

For example:

Test	Result
<pre>print ("{:.3f}".format(p_persistent_csma_collision_probability(0.2)))</pre>	0.111

Answer: (penalty regime: 10, 20, ... %)

```
Reset answer
```

```
1 v def p_persistent_csma_collision_probability (p):
2    return (p**2) * (1/(2*p - p*p))
```

	Test		Got	
~	<pre>print ("{:.3f}".format(p_persistent_csma_collision_probability(0.2)))</pre>	0.111	0.111	~
~	<pre>print ("{:.3f}".format(p_persistent_csma_collision_probability(0.4)))</pre>	0.250	0.250	~

Passed all tests! 🗸

Correct

```
Question 13
Correct
Mark 1.00 out of 1.00
```

Consider *p*-persistent CSMA with a probability value 0 . Suppose an idle station gets a new packet to transmit, the medium is completely idle and no other station has a packet. Please find an expression for the average access delay (as a number of minislots) and implement it as a Python function.

For example:

Test	
<pre>print ("{:.3f}".format(p_persistent_csma_access_delay(0.1)))</pre>	9.000

Answer: (penalty regime: 10, 20, ... %)

```
Reset answer

1 v def p_persistent_csma_access_delay (p):
2     q = 1 - p
3     return q/p
```

	Test	Expected	Got	
~	<pre>print ("{:.3f}".format(p_persistent_csma_access_delay(0.1)))</pre>	9.000	9.000	~
~	<pre>print ("{:.3f}".format(p_persistent_csma_access_delay(0.4)))</pre>	1.500	1.500	~
~	<pre>print ("{:.3f}".format(p_persistent_csma_access_delay(0.6)))</pre>	0.667	0.667	~

Passed all tests! ✓

We need a geometric random variable of the first kind. Average access delay is (1-p)/p

Correct

Marks for this submission: 1.00/1.00.

Question 14
Correct
Mark 1.00 out of 1.00

Consider the Ethernet protocol as described in the slides. What is the total overhead of the Ethernet header (including preamble) and trailer in bytes?

Answer: 26

Preamble: 7 bytes Start-of-Frame: 1 byte

DstAddr: 6 bytes SrcAddr: 6 bytes

Length/Type field: 2 bytes

Trailer / checksum: 4 bytes

Correct

/09/2021	Quiz: Local area networks and medium access control: Attempt review
Question 15	5
Correct	
Mark 1.00 ou	ut of 1.00
Ethernet	t: what is the minimum payload size in bytes?
Answer:	46
Correct Marks for	r this submission: 1.00/1.00.
Question 16 Correct	;
Mark 1.00 ou	ut of 1.00
Suppos	e the length/type header field carries a value of 120. What is the total length of the Ethernet packet?
Answer:	146
Correct Marks for	r this submission: 1.00/1.00.
Correct	
Mark 1.00 ou	ut of 1.00
Suppose	e the length/type field carries a value of 0x0800. To which higher-layer protocol does the payload belong?
Select o	ne:
○ a.	HTTP
b.	AppleTalk
○ c.	UDP
d.	TCP
e.	IPv4 ✓
f.	IPv6
○ g.	IP-In-IP-encapsulation
Your ans	swer is correct.
Correct	
	r this submission: 1.00/1.00.

Question 18
Correct
Mark 1.00 out of 1.00

Switched Ethernet: Suppose we have one switch with N stations attached. Each station is attached via 10 Gbps Ethernet. What is the best aggregate throughput rate in Gbps that the switch can achieve? Please implement your answer as a Python function.

Answer: (penalty regime: 10, 20, ... %)

```
Reset answer

1 v def aggregate_throughput (n):
2 return 10 * n
```

	Test	Expected	Got	
~	<pre>print(aggregate_throughput(10))</pre>	100	100	~
~	<pre>print(aggregate_throughput(30))</pre>	300	300	~

Passed all tests! 🗸

N*10 Gbps, as in the ideal case all packets arriving at the same time are destined to different destinations and can be transmitted out of the switch concurrently.

Correct

Marks for this submission: 1.00/1.00.

Question **19**Correct
Mark 0.67 out of 1.00

Ethernet MAC: Suppose a station needs to go through four backoff operations before it can start its transmission without collision. What is the average **total** number of slot times that the station waits in the backoff state?

Answer: 13

0.5 + 1.5 + 3.5 + 7.5 = 13 slot times

Correct

Marks for this submission: 1.00/1.00. Accounting for previous tries, this gives 0.67/1.00.

■ Mid-term test 2020

Jump to...

Quiz: Routing ►