

Mathematics Methods for Computer Science

Instructor: Xubo Yang

SJTU-SE DALAB

Reference book: Solomon, Justin. Numerical Algorithms. Published by AK Peters/CRC Press, 2015.

① Numeric

- Stability and error analysis
- Floating-point representation

② Linear algebra

- Gaussian elimination and LU
- Column space and QR
- Eigenproblems
- Applications

③ Root-finding and optimization

- Single variable
- Multivariable
- Constrained optimization
- Iterative linear solvers; Conjugate gradients

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

④ Interpolation and quadrature

- Approximating integrals
- Approximating derivatives

⑤ Differential equations

- ODEs: time-stepping, discretization
- PDEs: Poisson equation, heat equation, waves
- Techniques: Differencing, finite elements (time-permitting)

Lecture

Numerics And Error Analysis

Prototypical Example

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

```
double x = 1.0;  
double y = x / 3.0;  
if (x == y*3.0) cout << "They are equal!";  
else cout << "They are NOT equal.";
```

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

```
double x = 1.0;
double y = x / 3.0;
if (fabs(x-y*3.0) <
    numeric_limits<double>::epsilon)
    cout << "They_are_equal!";
else cout << "They_are_NOT_equal.";
```

Mathematically correct
 \neq
Numerically sound

Rarely if ever should the operator `==` and its equivalents be used on fractional values. Instead, some tolerance should be used to check if they are equal.

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

$$463 = 256 + 128 + 64 + 8 + 4 + 2 + 1$$

$$= 2^8 + 2^7 + 2^6 + 2^3 + 2^2 + 2^1 + 2^0$$

↓

1	1	1	0	0	1	1	1	1
2^8	2^7	2^6	2^5	2^4	2^3	2^2	2^1	2^0

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

$$463.25 = 256 + 128 + 64 + 8 + 4 + 2 + 1 + 1/4$$

$$= 2^8 + 2^7 + 2^6 + 2^3 + 2^2 + 2^1 + 2^0 + 2^{-2}$$

↓

1	1	1	0	0	1	1	1	1	0	1
2^8	2^7	2^6	2^5	2^4	2^3	2^2	2^1	2^0	2^{-1}	2^{-2}

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

$$\frac{1}{3} = 0.0101010101..._2$$

Finite number of bits

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

1	1	...	0	0	...	1	1
2^ℓ	$2^{\ell-1}$...	2^0	2^{-1}	...	2^{-k+1}	2^{-k}

- Parameters: $k, \ell \in \mathbb{Z}$
- $k + \ell + 1$ digits total
- Can reuse integer arithmetic (fast; GPU possibility):

$$a + b = (a \cdot 2^k + b \cdot 2^k) \cdot 2^{-k}$$

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

$$0.1_2 \times 0.1_2 = 0.01_2 \cong 0.0_2$$

Multiplication and division easily change
order of magnitude!

$$9.11 \times 10^{-31} \rightarrow 6.022 \times 10^{23}$$

Desired: graceful transition

- Compactness matters:

$$6.022 \times 10^{23} =$$

602,200,000,000,000,000,000,000

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

- Compactness matters:

$$6.022 \times 10^{23} =$$

$$602,200,000,000,000,000,000,000$$

- Some operations are unlikely:


$$6.022 \times 10^{23} + 9.11 \times 10^{-31}$$

Store Significant digits

$$\underbrace{\pm}_{\text{sign}} \underbrace{(d_0 + d_1 \cdot b^{-1} + d_2 \cdot b^{-2} + \cdots + d_{p-1} \cdot b^{1-p})}_{\text{significantand}} \times \underbrace{b^e}_{\text{exponent}}$$


- Base: $b \in \mathbb{N}$
- Precision: $p \in \mathbb{N}$
- Range of exponents: $e \in [L, U]$

Properties of Floating Point




- Unevenly spaced
 - Machine precision ϵ_m : smallest ϵ_m with $1 + \epsilon_m \not\approx 1$

Properties of Floating Point



- Unevenly spaced
 - Machine precision ϵ_m : smallest ϵ_m with $1 + \epsilon_m \not\approx 1$
- Needs rounding rule (e.g. "round to nearest, ties to even")

Properties of Floating Point



- Unevenly spaced
 - Machine precision ϵ_m : smallest ϵ_m with $1 + \epsilon_m \not\approx 1$
- Needs rounding rule (e.g. "round to nearest, ties to even")
- Can remove leading 1

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

$$Q = \{a/b : a, b \in \mathbb{Z}\}$$

- Simple rules: $a/b + c/d = (ad + cb)/bd$
- Redundant: $1/2 = 2/4$
- Blowup:

$$\frac{1}{100} + \frac{1}{101} + \frac{1}{102} + \frac{1}{103} + \frac{1}{104} + \frac{1}{105} = \frac{188463347}{3218688200}$$

- Restricted operations: $2 \mapsto \sqrt{2}$

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

Store range $a \pm \epsilon$

- Keeps track of certainty and rounding decisions
- Easy bounds:

$$(x \pm \epsilon_1) + (y \pm \epsilon_2) = (x + y) \pm (\epsilon_1 + \epsilon_2 + \textit{error}(x + y))$$

- Implementation via operator overloading

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

- Rounding
- Discretization
- Modeling
- Input

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

What sources of error might affect planets
simulation?

Absolute Error

The difference between the approximate value and the underlying true value.

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

Absolute vs. Relative Error

Absolute Error

The difference between the approximate value and the underlying true value.

Relative Error

Absolute error divided by the true value.

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

Absolute vs. Relative Error

Absolute Error

The difference between the approximate value and the underlying true value.

Relative Error

Absolute error divided by the true value.

$$2 \text{ cm} \pm 0.02 \text{ cm}$$

$$2 \text{ cm} \pm 1\%$$

Problem: Generally not computable

Problem: Generally not computable
Common fix: Be conservative

Root-finding problem

For $f : \mathbb{R} \rightarrow \mathbb{R}$, find x^* such that $f(x^*) = 0$

Actual output: x_{est} with $|f(x_{est})| \ll 1$

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

Backward Error

The amount the problem statement would have to change to make the approximate solution exact

Backward Error

The amount the problem statement would have to change to make the approximate solution exact

Example 1: \sqrt{x}

Backward Error

The amount the problem statement would have to change to make the approximate solution exact

Example 1: \sqrt{x}

Example 2: $A\vec{x} = \vec{b}$

Well-conditioned:

Small backward error \implies small forward error

Poorly conditioned:

Otherwise

Example: Root-finding

Condition number

Ratio of forward to backward error

Condition number

Ratio of forward to backward error

Root-finding example:

$$\frac{1}{|f'(x^*)|}$$

Extremely careful implementation can be necessary

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

```
double normSquared = 0;
for (int i = 0; i < n; i++)
    normSquared += x[i]*x[i];
return sqrt(normSquared);
```

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

```
double maxElement = epsilon;
\\
for (int i = 0; i < n; i++)
maxElement = max(maxElement, fabs(x[i]));
for (int i = 0; i < n; i++) {
double scaled = x[i] / maxElement;
normSquared += scaled*scaled;
}
return sqrt(normSquared) * maxElement;
```

Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

```
double sum = 0;  
for (int i = 0; i < n; i++)  
    sum += x[i];
```


Motivation

Representing Numbers

Exotic Representation

Error

Practical Aspects

$$((a + b) - a) - b \stackrel{?}{=} 0$$

Store compensation value !