

Database Technology


Data Structures for Databases

Olaf Hartig

olaf.hartig@liu.se

Storage Hierarchy

Quiz




Which of the following statements *is correct*?

- 1) Secondary storage devices are usually faster than primary storage devices.
- 2) Data in a primary storage device may be lost when switching off the power.
- 3) The CPU may operate directly on data that is in a secondary storage device.
- 4) A piece of data (e.g., a record) may not be held both in a primary storage device and in a secondary storage device at the same time.

Record Allocation


(Allocating Records to File Blocks)

Quiz



- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- How many blocks are needed to store the file?
 - 1) $b = 1,000$
 - 2) $b = 2,000$
 - 3) $b = 8,000$
 - 4) $b = 10,000$

Quiz




- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- How many blocks are needed to store the file?
 - ~~$b = 1,000$~~
 - ~~$b = 2,000$~~
 - ~~$b = 8,000$~~
 - $b = 10,000$

$$bfr = \left\lfloor \frac{B}{R} \right\rfloor = \left\lfloor \frac{8,000}{400} \right\rfloor = 20 \quad b = \left\lceil \frac{r}{bfr} \right\rceil = \left\lceil \frac{200,000}{20} \right\rceil = 10,000$$

blocking factor

Quiz




- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- How many blocks are needed to store the file?
1) ~~$b = 1,000$~~ 2) ~~$b = 2,000$~~ 3) ~~$b = 8,000$~~ 4) $b = 10,000$

$$bfr = \left\lfloor \frac{B}{R} \right\rfloor = \left\lfloor \frac{8,000}{400} \right\rfloor = 20 \quad b = \left\lceil \frac{r}{bfr} \right\rceil = \left\lceil \frac{200,000}{20} \right\rceil = 10,000$$

- How much space is wasted per block?
1) 0 bytes 2) 10 bytes 3) 20 bytes 4) 100 bytes

Quiz



- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- How many blocks are needed to store the file?
1) ~~$b = 1,000$~~ 2) ~~$b = 2,000$~~ 3) ~~$b = 8,000$~~ 4) $b = 10,000$

$$bfr = \left\lfloor \frac{B}{R} \right\rfloor = \left\lfloor \frac{8,000}{400} \right\rfloor = 20 \quad b = \left\lceil \frac{r}{bfr} \right\rceil = \left\lceil \frac{200,000}{20} \right\rceil = 10,000$$

- How much space is wasted per block? $B - bfr * R$
1) 0 bytes 2) ~~10 bytes~~ 3) ~~20 bytes~~ 4) ~~100 bytes~~

File Organization

(Organizing Records in Files)

Exercise: Heap File

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed to store the file
- Assume we organize the file as a **heap file**
 - i.e., new records are always appended to the end of the file
- How many blocks do we need to read?

Name	ID	Salary	
Andersson	12	2000	} Block 1
Svensson	13	4000	
...			
...			
..			} Block 2
...			
...			
...			
..			} Block 3
...			
...			
...			

	search field = ID value = 43 (unique)	search field = Name value = Smith (non-unique)
worst case	?	
best case	?	
average case	?	

Exercise: Heap File

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed to store the file
- Assume we organize the file as a **heap file**
 - i.e., new records are always appended to the end of the file
- How many blocks do we need to read?

Name	ID	Salary	
Andersson	12	2000	Block 1
Svensson	13	4000	
...			
...			
..			Block 2
...			
...			
...			
..			Block 3
...			
...			
...			

	search field = ID value = 43 (unique)	search field = Name value = Smith (non-unique)
worst case	10,000	
best case	1	
average case	5,000	

Exercise: Heap File

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed to store the file
- Assume we organize the file as a **heap file**
 - i.e., new records are always appended to the end of the file
- How many blocks do we need to read?

Name	ID	Salary	
Andersson	12	2000	Block 1
Svensson	13	4000	
...			
...			
..			Block 2
...			
...			
...			
..			Block 3
...			
...			
...			

	search field = ID value = 43 (unique)	search field = Name value = Smith (non-unique)
worst case	10,000	?
best case	1	?
average case	5,000	?

Exercise: Heap File

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed to store the file
- Assume we organize the file as a **heap file**
 - i.e., new records are always appended to the end of the file
- How many blocks do we need to read?

Name	ID	Salary	
Andersson	12	2000	Block 1
Svensson	13	4000	
...			
...			
..			Block 2
...			
...			
...			
..			Block 3
...			
...			
...			

	search field = ID value = 43 (unique)	search field = Name value = Smith (non-unique)	
worst case	10,000	10,000	linear search until last block
best case	1	10,000	
average case	5,000	10,000	

Exercise: Sorted File (a.k.a. Sequential File)

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed for the file
- Assume we organize the file as a **sorted file** by using the ID field as the *sorting field*
 - i.e., records inserted based on their ID value

Name	ID	Salary	
Andersson	12	2000	Block 1
Svensson	13	4000	
...			
...			
..			Block 2
...			
...			
...			
..			Block 3
...			
...			
...			
⋮			⋮

	search field = ID value = 43 (unique)	search field = Name value = Smith (non-unique)
worst case	?	?
best case	?	?
average case	?	?

$\log_2(2)=1$	$\log_2(256)=8$
$\log_2(4)=2$	$\log_2(512)=9$
$\log_2(8)=3$	$\log_2(1024)=10$
$\log_2(16)=4$	$\log_2(2048)=11$
$\log_2(32)=5$	$\log_2(4096)=12$
$\log_2(64)=6$	$\log_2(8192)=13$
$\log_2(128)=7$	$\log_2(16384)=14$

Exercise: Sorted File (a.k.a. Sequential File)

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed for the file
- Assume we organize the file as a **sorted file** by using the ID field as the *sorting field*
 - i.e., records inserted based on their ID value

Name	ID	Salary	
Andersson	12	2000	Block 1
Svensson	13	4000	
...			
...			
..			Block 2
...			
...			
...			
..			Block 3
...			
...			
...			
⋮			⋮

	search field = ID value = 43 (unique)	search field = Name value = Smith (non-unique)
worst case	14	10,000
best case	1	10,000
average case	14	10,000

$\log_2(2)=1$	$\log_2(256)=8$
$\log_2(4)=2$	$\log_2(512)=9$
$\log_2(8)=3$	$\log_2(1024)=10$
$\log_2(16)=4$	$\log_2(2048)=11$
$\log_2(32)=5$	$\log_2(4096)=12$
$\log_2(64)=6$	$\log_2(8192)=13$
$\log_2(128)=7$	$\log_2(16384)=14$

$\log_2 b$

Exercise: Hash File (a.k.a. Random File Orga.)

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed for the file
- Assume we organize the file as a **hash file** by using the ID field as the *hash field*
 - i.e., find relevant bucket by applying hash function to the ID value; assume 5,000 buckets with 4 blocks per bucket

Name	ID	Salary	
Andersson	12	2000	Block 1
Svensson	13	4000	
...			
...			
..			Block 2
...			
...			
...			
..			Block 3
...			
...			
...			
⋮			⋮

	search field = ID value = 43 (unique)	search field = Name value = Smith (non-unique)
worst case	?	?
best case	?	?
average case	?	?

Exercise: Hash File (a.k.a. Random File Orga.)

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed for the file
- Assume we organize the file as a **hash file** by using the ID field as the *hash field*
 - i.e., find relevant bucket by applying hash function to the ID value; assume 5,000 buckets with 4 blocks per bucket

Name	ID	Salary	
Andersson	12	2000	Block 1
Svensson	13	4000	
...			
...			
..			Block 2
...			
...			
...			
..			Block 3
...			
...			
...			
⋮			⋮

	search field = ID value = 43 (unique)	search field = Name value = Smith (non-unique)	
worst case	4	$\geq 10,000$	scan all non-empty blocks of all buckets
best case	1	$\geq 10,000$	
average case	<u>depends</u>	$\geq 10,000$	

Exercise: Hash File (a.k.a. Random File Orga.)

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed for the file
- Assume we organize the file as a **hash file** by using the ID field as the *hash field*
 - i.e., find relevant bucket by applying hash function to the ID value; assume 5,000 buckets with 4 blocks per bucket
- What if we want to retrieve all records with an ID value smaller than 10? (assuming IDs cannot be smaller than 1)

Name	ID	Salary	
Andersson	12	2000	Block 1
Svensson	13	4000	
...			
...			
..			Block 2
...			
...			
...			
..			Block 3
...			
...			
...			
⋮			⋮

worst case	?
best case	?

Exercise: Hash File (a.k.a. Random File Orga.)

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed for the file
- Assume we organize the file as a **hash file** by using the ID field as the *hash field*
 - i.e., find relevant bucket by applying hash function to the ID value; assume 5,000 buckets with 4 blocks per bucket
- What if we want to retrieve all records with an ID value smaller than 10? (assuming IDs cannot be smaller than 1)

Name	ID	Salary	
Andersson	12	2000	} Block 1
Svensson	13	4000	
...			
...			
..			} Block 2
...			
...			
...			
..			} Block 3
...			
...			
...			
⋮			⋮

worst case	$9 \cdot 4 = 36$
best case	1

Single-Level Ordered Indexes

Summary of Single-Level Ordered Indexes

	Index field used for sorting the data records	Index field <i>not</i> used for sorting the data records
Index field is a key	Primary index	Secondary index (key)
Index field is not a key	Clustering index	Secondary index (non-key)

Quiz

	Index field used for sorting the data records	Index field <i>not</i> used for sorting the data records
Index field is a key	Primary index	Secondary index (key)
Index field is not a key	Clustering index	Secondary index (non-key)

Which of these four types of indexes has the *smallest number of index records*?

- 1) Primary index
- 2) Clustering index
- 3) Secondary index on a key field
- 4) Secondary index on a non-key field

Summary of Single-Level Indexes (cont'd)

	Index field used for sorting the data records	Index field <i>not</i> used for sorting the data records
Index field is a key	Primary index	Secondary index (key)
Index field is not a key	Clustering index	Secondary index (non-key)

Type of index	Number of index entries
Primary	Number of blocks in data file
Clustering	Number of distinct index field values
Secondary (key)	Number of records in data file
Secondary (non-key)	Number of records or number of distinct index field values


Quiz: Primary Index

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed for the file
- Assume we organize the file as a sorted file by using the ID field as the *sorting field*
- Assume we create a **primary index** on the ID field
 - same block size for the index file: $B_{idx} = B = 8,000$ bytes
 - but smaller records: $R_{idx} = 200$ bytes per index record
- How many index records does this index contain?
 - 1) 8,000
 - 2) 10,000
 - 3) 20,000
 - 4) 200,000

Name	ID	Salary	
Andersson	12	2000	Block 1
Svensson	13	4000	
...			
...			
..			Block 2
...			
...			
...			
..			Block 3
...			
...			
...			
⋮			⋮

Quiz: Primary Index


- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed for the file
- Assume we organize the file as a sorted file by using the ID field as the *sorting field*
- Assume we create a **primary index** on the ID field
 - same block size for the index file: $B_{idx} = B = 8,000$ bytes
 - but smaller records: $R_{idx} = 200$ bytes per index record
- How many index records does this index contain?




1) ~~8,000~~ 2) 10,000 3) ~~20,000~~ 4) ~~200,000~~

Quiz: Primary Index

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed for the file
- Assume we organize the file as a sorted file by using the ID field as the *sorting field*
- Assume we create a **primary index** on the ID field
 - same block size for the index file: $B_{idx} = B = 8,000$ bytes
 - but smaller records: $R_{idx} = 200$ bytes per index record
- How many blocks does the index file consist of?
 - 1) 100
 - 2) 250
 - 3) 1,000
 - 4) 8,000



Quiz: Primary Index



- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed for the file
- Assume we organize the file as a sorted file by using the ID field as the *sorting field*
- Assume we create a **primary index** on the ID field
 - same block size for the index file: $B_{idx} = B = 8,000$ bytes
 - but smaller records: $R_{idx} = 200$ bytes per index record
- How many blocks does the index file consist of?


1) ~~100~~ 2) 250 3) ~~1,000~~ 4) ~~8,000~~

$$b_{idx} = \left\lceil \frac{r_{idx}}{bfr_{idx}} \right\rceil = \left\lceil \frac{10,000}{40} \right\rceil = 250$$

$$bfr_{idx} = \left\lfloor \frac{B_{idx}}{R_{idx}} \right\rfloor = \left\lfloor \frac{8,000}{200} \right\rfloor = 40$$

Quiz: Primary Index

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed for the file
- Assume we organize the file as a sorted file by using the ID field as the *sorting field*
- Assume we create a **primary index** on the ID field
 - consisting of 250 blocks
- How many blocks do we need to read if we want to retrieve the record with ID = 43?




1) 7 2) 8 3) 9 4) 10

$$\begin{aligned}
 \log_2(2) &= 1 & \log_2(128) &= 7 \\
 \log_2(4) &= 2 & \log_2(256) &= 8 \\
 \log_2(8) &= 3 & \log_2(512) &= 9 \\
 \log_2(16) &= 4 & \log_2(1024) &= 10 \\
 \log_2(32) &= 5 & \log_2(2048) &= 11 \\
 \log_2(64) &= 6 & \log_2(4096) &= 12
 \end{aligned}$$

Quiz: Primary Index

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed for the file
- Assume we organize the file as a sorted file by using the ID field as the *sorting field*
- Assume we create a **primary index** on the ID field
 - consisting of 250 blocks
- How many blocks do we need to read if we want to retrieve the record with ID = 43?



1) ~~7~~ 2) ~~8~~ 3) 9 4) ~~10~~


$\log_2(2)=1$	$\log_2(128)=7$
$\log_2(4)=2$	$\log_2(256)=8$
$\log_2(8)=3$	$\log_2(512)=9$
$\log_2(16)=4$	$\log_2(1024)=10$
$\log_2(32)=5$	$\log_2(2048)=11$
$\log_2(64)=6$	$\log_2(4096)=12$

Multilevel Indexes

(Stacking indexes on top of one another)

Multilevel Index

- Assume a file with
 - $r = 200,000$ records,
 - $R = 400$ bytes per record, and
 - $B = 8,000$ bytes per block
- Hence, $b = 10,000$ blocks needed for the file
- Assume we organize the file as a sorted file by using the ID field as the *sorting field*
- Convert the primary index (on ID) into a **multilevel index**
 - still 250 blocks in the first level
 - second level: 250 index records \rightarrow 7 blocks (at $bfr_{idx} = 40$)
 - third level: 7 index records \rightarrow 1 block
- Retrieving a record by ID: $3 + 1 = 4$ block accesses




www.liu.se


Binary Search

key is 11

key < 50



key > 7



key == 11

