

[Description](#) [Solution](#) [Discuss \(999+\)](#) [Submissions](#)

242. Valid Anagram

Easy [8542](#) [279](#) [Add to List](#) [Share](#)

Given two strings *s* and *t*, return *true* if *t* is an anagram of *s*, and *false* otherwise.

An **Anagram** is a word or phrase formed by rearranging the letters of a different word or phrase, typically using all the original letters exactly once.

Example 1:

Input: *s* = "anagram", *t* = "nagaram"
Output: *true*

Example 2:

Input: *s* = "rat", *t* = "car"
Output: *false*

Constraints:

- $1 \leq s.length, t.length \leq 5 \times 10^4$
- s* and *t* consist of lowercase English letters.

Follow up: What if the inputs contain Unicode characters? How would you adapt your solution to such a case?

Accepted 2,044,807 Submissions 3,244,343

Seen this question in a real interview before?

Companies [🔒](#)

Related Topics [🔒](#)

Similar Questions [🔒](#)

i C++ Autocomplete *i* {} ↶ ⌚ ↷

```
1 class Solution {
2 public:
3     bool isAnagram(string s, string t) {
4     }
5 }
6
```

NEW

[Problems](#)

[Pick One](#)

[Prev](#)

242/2598

[Next](#)

Console

[Contribute](#)

[Run Code](#)

[Submit](#)