

### Exercise 5.3

(a)

j6 = j1/j2; (divide of long long int)

9d003028:	8fc60028	lw	a2,40(s8)
9d00302c:	8fc7002c	lw	a3,44(s8)
9d003030:	8fc40020	lw	a0,32(s8)
9d003034:	8fc50024	lw	a1,36(s8)
9d003038:	0f4008ae	jal	9d0022b8 <__divdi3>
9d00303c:	00000000	nop	
9d003040:	afc20078	sw	v0,120(s8)
9d003044:	afc3007c	sw	v1,124(s8)

All calculation of float

f3 = f1+f2;

9d003048:	8fc50034	lw	a1,52(s8)
9d00304c:	8fc40030	lw	a0,48(s8)
9d003050:	0f400d01	jal	9d003404 <__addsf3>
9d003054:	00000000	nop	
9d003058:	afc20080	sw	v0,128(s8)

f4 = f1-f2;

9d00305c:	8fc50034	lw	a1,52(s8)
9d003060:	8fc40030	lw	a0,48(s8)
9d003064:	0f400cff	jal	9d0033fc <__subsf3>
9d003068:	00000000	nop	
9d00306c:	afc20084	sw	v0,132(s8)

f5 = f1\*f2;

9d003070:	8fc50034	lw	a1,52(s8)
9d003074:	8fc40030	lw	a0,48(s8)
9d003078:	0f400e29	jal	9d0038a4 <__mulsf3>
9d00307c:	00000000	nop	

9d003080:	afc20088	sw	v0,136(s8)
f6 = f1/f2;			
9d003084:	8fc50034	lw	a1,52(s8)
9d003088:	8fc40030	lw	a0,48(s8)
9d00308c:	0f400d9d	jal	9d003674 <__divsf3>
9d003090:	00000000	nop	
9d003094:	afc2008c	sw	v0,140(s8)

All calculation of long double

d3 = d1+d2;

9d003098:	8fc60040	lw	a2,64(s8)
9d00309c:	8fc70044	lw	a3,68(s8)
9d0030a0:	8fc40038	lw	a0,56(s8)
9d0030a4:	8fc5003c	lw	a1,60(s8)
9d0030a8:	0f4009c0	jal	9d002700 <__adddf3>
9d0030ac:	00000000	nop	
9d0030b0:	afc20090	sw	v0,144(s8)
9d0030b4:	afc30094	sw	v1,148(s8)

d4 = d1-d2;

9d0030b8:	8fc60040	lw	a2,64(s8)
9d0030bc:	8fc70044	lw	a3,68(s8)
9d0030c0:	8fc40038	lw	a0,56(s8)
9d0030c4:	8fc5003c	lw	a1,60(s8)
9d0030c8:	0f4009be	jal	9d0026f8 <__subdf3>
9d0030cc:	00000000	nop	
9d0030d0:	afc20098	sw	v0,152(s8)
9d0030d4:	afc3009c	sw	v1,156(s8)

d5 = d1\*d2;

9d0030d8:	8fc60040	lw	a2,64(s8)
9d0030dc:	8fc70044	lw	a3,68(s8)

9d0030e0:	8fc40038	lw	a0,56(s8)
9d0030e4:	8fc5003c	lw	a1,60(s8)
9d0030e8:	0f400aca	jal	9d002b28 <__muldf3>
9d0030ec:	00000000	nop	
9d0030f0:	afc200a0	sw	v0,160(s8)
9d0030f4:	afc300a4	sw	v1,164(s8)
d6 = d1/d2;			
9d0030f8:	8fc60040	lw	a2,64(s8)
9d0030fc:	8fc70044	lw	a3,68(s8)
9d003100:	8fc40038	lw	a0,56(s8)
9d003104:	8fc5003c	lw	a1,60(s8)
9d003108:	0f400780	jal	9d001e00 <__divdf3>
9d00310c:	00000000	nop	
9d003110:	afc200a8	sw	v0,168(s8)
9d003114:	afc300ac	sw	v1,172(s8)

(b)

i3 = i1+i2;

9d002f3c:	8fc30014	lw	v1,20(s8)
9d002f40:	8fc20018	lw	v0,24(s8)
9d002f44:	00621021	addu	v0,v1,v0
9d002f48:	afc2004c	sw	v0,76(s8)

i4 = i1-i2;

9d002f4c:	8fc30014	lw	v1,20(s8)
9d002f50:	8fc20018	lw	v0,24(s8)
9d002f54:	00621023	subu	v0,v1,v0
9d002f58:	afc20050	sw	v0,80(s8)

i5 = i1\*i2;

9d002f5c:	8fc30014	lw	v1,20(s8)
9d002f60:	8fc20018	lw	v0,24(s8)

```
9d002f64:    70621002    mul    v0,v1,v0
9d002f68:    afc20054    sw     v0,84(s8)
```

Char does not involve in the smallest data type. It has an additional line shown below.

```
9d002f18:    304200ff    andi   v0,v0,0xff
```

andi transfer the data types back to char by comparing the calculated result with 0xff through & operator

(c)

	char	int	Long long	float	Long double
+	1.25(5)	1(4)	2.75(11)	2.25(5+4) J	3(8+4) J
-	1.25(5)	1(4)	2.75(11)	1.5(5+1) J	2.25(8+1) J
*	1.25(5)	1(4)	4.5(18)	2.25(5+4) J	3.5(8+6) J
/	1.75(7)	1.75(7)	70(8+272) J	2.25(5+4) J	5.25(15+6) J

(d)

```
j6 = j1/j2;
```

```
.text    0x000000009d0022b8    0x440
```

```
.text    0x000000009d0022b8    0x440 c:/program
files/microchip xc32/v4.00/bin/bin/../../lib/gcc/pic32mx/8.3.1/libgcc.a(_divdi3.o)
```

```
    0x000000009d0022b8    __divdi3
```

```
f3 = f1+f2; f4 = f1-f2;
```

```
.text.fpsubadd 0x000000009d0033fc    0x278
```

```
.text.fpsubadd
```

```
    0x000000009d0033fc    0x278 c:/program
files/microchip xc32/v4.00/bin/bin/../../lib/gcc/pic32mx/8.3.1/../../pic32mx/lib/libm.a(fp3
2subadd.o)
```

```
    0x000000009d0033fc    __subsf3
```

```
    0x000000009d0033fc    fpsub
```

```
    0x000000009d003404    __addsf3
```

```
    0x000000009d003404    fpadd
```

```
f5 = f1*f2;
```

```
.text.fp32mul 0x000000009d0038a4    0x1bc
```

.text.fp32mul 0x000000009d0038a4 0x1bc c:/program  
files/microchip xc32/v4.00/bin/bin/./../lib/gcc/pic32mx/8.3.1/./.././pic32mx/lib/libm.a(fp3  
2mul.o)

0x000000009d0038a4 \_mulsf3

0x000000009d0038a4 fpmul

f6 = f1/f2;

.text.fp32div 0x000000009d003674 0x230

.text.fp32div 0x000000009d003674 0x230 c:/program  
files/microchip xc32/v4.00/bin/bin/./../lib/gcc/pic32mx/8.3.1/./.././pic32mx/lib/libm.a(fp3  
2div.o)

0x000000009d003674 fpdiv

0x000000009d003674 \_divsf3

d3 = d1+d2; d4 = d1-d2;

.text.dp32subadd

0x000000009d0026f8 0x430

.text.dp32subadd

0x000000009d0026f8 0x430 c:/program  
files/microchip xc32/v4.00/bin/bin/./../lib/gcc/pic32mx/8.3.1/./.././pic32mx/lib/libm.a(dp3  
2subadd.o)

0x000000009d0026f8 dpsub

0x000000009d0026f8 \_subdf3

0x000000009d002700 \_adddf3

0x000000009d002700 dpadd

d5 = d1\*d2;

.text.dp32mul 0x000000009d002b28 0x32c

.text.dp32mul 0x000000009d002b28 0x32c c:/program  
files/microchip xc32/v4.00/bin/bin/./../lib/gcc/pic32mx/8.3.1/./.././pic32mx/lib/libm.a(dp3  
2mul.o)

0x000000009d002b28 \_muldf3

0x000000009d002b28 dpmul

d6 = d1/d2;

.text.dp32mul 0x000000009d001e00 0x4b8

```
.text.dp32mul 0x000000009d001e00 0x4b8 c:/program
files/microchip xc32/v4.00/bin/bin/./../lib/gcc/pic32mx/8.3.1/./.././pic32mx/lib\libm.a(dp3
2div.o)
```

```
0x000000009d001e00      dpdiv
0x000000009d001e00      _divdf3
```

#### kseg0 Program-Memory Usage for math subroutine

section	address	length [bytes]	(dec)	Description
-----	-----	-----	-----	-----
.text.dp32mul	0x9d001e00	0x4b8	1208	
.text	0x9d0022b8	0x440	1088	App's exec code
.text.dp32subadd	0x9d0026f8	0x430	1072	
.text.dp32mul	0x9d002b28	0x32c	812	
.text	0x9d002e54	0x5a8	1448	App's exec code
.text.fpsubadd	0x9d0033fc	0x278	632	
.text.fp32div	0x9d003674	0x230	560	
.text.fp32mul	0x9d0038a4	0x1bc	444	

Total kseg0\_program\_mem used for math subroutine: 0x1c60 7264

With 9 math subroutine, each of them has memory usage of 7264/9=807

#### Exercise 5.4

u3 = u1 & u2; // bitwise AND

```
9d00224c: 8fc30000 lw v1,0(s8)
9d002250: 8fc20004 lw v0,4(s8)
9d002254: 00621024 and v0,v1,v0
9d002258: afc20008 sw v0,8(s8)
```

#### 4 commands

u3 = u1 | u2; // bitwise OR

```
9d00225c: 8fc30000 lw v1,0(s8)
9d002260: 8fc20004 lw v0,4(s8)
9d002264: 00621025 or v0,v1,v0
```

9d002268:   afc20008       sw     v0,8(s8)

#### 4 commands

u3 = u2 << 4; // shift left 4 spaces, or multiply by  $2^4 = 16$

9d00226c:   8fc20004       lw     v0,4(s8)

9d002270:   00021100       sll     v0,v0,0x4

9d002274:   afc20008       sw     v0,8(s8)

#### 3 commands

u3 = u1 >> 3; // shift right 3 spaces, or divide by  $2^3 = 8$

9d002278:   8fc20000       lw     v0,0(s8)

9d00227c:   000210c2       srl     v0,v0,0x3

9d002280:   afc20008       sw     v0,8(s8)

#### 3 commands

### Exercise 6.1

Polling can only process at a regular interval. Interruption can happen in any given time.

#### Polling

Pros: simple program with fewer lines of assembly languages compare to interrupt, transmission reliability that takes place at maximum speed

Cons: standby time is shorter than the response time, need to apply another method of transmission

#### Interrupt

Pros: serves multiple devices, more flexible and efficient which eliminates nested loops, remove ambiguities in the code.

Cons: requirement for more complex hardware which store noncacheable memory for SFRs and loss of time, need to read data sheet to understand SFRs.

### Exercise 6.4

- (a) An IRQ is generated for an ISR at priority level 4, subpriority level 2 while the CPU is in normal execution, the CPU will attend the ISR and finished the interrupt then return to original task.
- (b) IRQ is generated while the CPU is executing a priority level 2, subpriority level 3 ISR, the CPU will attend the level 4 ISR since level 4 is have higher priority than level 2 and stop the priority level 2, subpriority level 3 ISR until it finished.

- (c) IRQ is generated while the CPU is executing a priority level 4, subpriority level 0 ISR, the CPU will attend priority level 4, subpriority level 0 ISR first since they have the same priority and we need to compare the subpriority and 2 has higher priority. However, we cannot interrupt the sequence and have to wait until the task is finished.
- (d) IRQ is generated while the CPU is executing a priority level 6, subpriority level 0 ISR, the CPU will continue attending the level 6 ISR since it has higher level compare to priority level 4.

#### Exercise 6.5

- (a) If an interrupt generated, the first thing the CPU does is save the contexts to RAM. Then, the CPU restores the contexts back from the RAM into the registers and the CPU reverts to its initial state. This process is called context save and restore.
- (b) Shadow register is an extra register of CPU, when called a particular priority level, CPU use the set of registers rather than context save and restore. By using shadow register, it can save processing time.

#### Exercise 6.8

- (a) `IEC0SET = 0x100;`                      // Enabling the Timer2 interrupt  
       `IFS0CLR = 0x100;`                    // Setting flag status to 0  
       `IPC2CLR = 0x1F;`                    // Clearing IPC2 Register  
       `IPC2SET = 0x16;`                    // Setting priority level to 5, sub priority level to 2
  
- (b) `IEC1SET = 0x8000;`                    // Enabling the Real-Time Clock and Calendar interrupt  
       `IFS1CLR = 0x8000;`                    // Setting flag status to 0  
       `IPC8CLR = 0x1F000000;`            // Clearing IPC8 Register  
       `IPC8SET = 0x19000000;`            // Setting priority level to 6, sub priority level to 1
  
- (c) `IEC2SET = 0x10;`                      // Enabling the UART4 Receiver interrupt  
       `IFS2CLR = 0x10;`                    // Setting flag status to 0  
       `IPC12CLR = 0x1F00;`                // Clearing IPC2 Register  
       `IPC12SET = 0x1F00;`                // Setting priority level to 7, sub priority level to 3
  
- (d) `IEC0SET = 0x800;`                    // Enabling the INT2 external input interrupt  
       `IFS0CLR = 0x800;`                    // Setting flag status to 0



```
IPC2CLR = 0x1F00000;    // Clearing IPC2 Register
IPC2SET = 0xE000000;    // Setting priority level to 3, sub priority level to 2
INTCONSET = 0x8;        // Configuring to trigger on rising edge
```

#### Exercise 6.9

The code is in 6-9 zip file

#### Exercise 6.16

The code is in 6-16 zip file

#### Exercise 6.17

The code is in 6-17 zip file