A model of hypothesis discovery and use in category learning

Abstract

[Abstract to be completed after the empirical results.]

Learning a category structure from feedback involves several related changes. A learner may discover a useful rule, accumulate evidence for a rule already under consideration, or apply a familiar rule more consistently. Each change can improve the probability of a correct response. A computational account of learning must therefore connect observable choices to the processes that make rules available, support them with evidence and determine their influence on behavior.

We formulate a model in which these processes operate over a limited, changing set of rule hypotheses. The model tracks the availability of each rule, its relative belief, its contribution to the current choice and the precision of its category predictions. Feedback updates these quantities and controls the introduction of new hypotheses. This formulation provides a basis for examining how rule discovery, evidence accumulation and persistent rule use contribute to individual learning trajectories across different feedback conditions.

Results

Category learning under binary and hierarchical feedback

The model is formulated for three category-learning conditions using stimuli defined by four normalized feature lengths. Condition 1 involves two categories and binary feedback; condition 2 involves four categories and binary feedback. Condition 3 also involves four categories, organized into two families containing two species each. Feedback in this condition distinguishes a correct species response, a response identifying the correct family but the wrong species, and a response identifying the wrong family. The learner is informed of the family–species structure and learns which response labels belong to the same family. These conditions vary the information available from a response and its feedback while retaining the same model architecture.

Individual learning trajectories

[Results to be added.]

A dynamic rule model links hypothesis discovery to choice

We formulated a dynamic rule model to describe how a learner discovers, evaluates and uses candidate explanations of the category structure. The model represents a rule as a partition of the stimulus space into labeled category regions. A learner begins with one candidate and can subsequently consider several rules, up to an individual capacity limit. Membership in this candidate set determines which rules are available for prediction and feedback learning. Each available rule has a relative belief that expresses the support it receives within the current set, and a precision that determines how concentrated its category predictions are. These quantities jointly define a possible internal learning state.

Choices depend on both the perceived stimulus and the influence of the available rules. Perception (P) introduces feature-specific uncertainty, calibrated by independent perceptual measurements. Each candidate uses this internal stimulus to predict categories from distances to its category regions. Higher rule precision concentrates the prediction on nearby regions. Choice readout (RC) combines these predictions using weights derived from rule beliefs and an additional preference for the previous trial's dominant rule. The dominant rule is the candidate with the largest choice weight. Its continued influence allows an established response policy to persist while evidence for alternatives accumulates. As beliefs and the candidate set change, contributions to choice can become more dispersed or more concentrated within the same participant (see Methods).

Feedback changes both the relative support for rules and the precision of their predictions. Evidence memory (M) combines the probability of the received feedback under each candidate with the evidence retained from preceding trials. Precision updating (B) uses the same predictions to evaluate whether the feedback was more or less probable than under uniform category predictions. Supporting feedback increases precision, whereas contradictory feedback lowers it. All available candidates undergo these updates, including candidates that contributed little to the response. Belief and precision consequently describe different aspects of learning: the former expresses support among competing explanations, and the latter controls the concentration of a particular rule's predictions.

Hypothesis updating (H) changes the set of explanations considered on the next trial. A state that summarizes recent failure controls the probability of searching and the balance between local and global search. Local search either edits a judgment in an existing rule or samples a rule with similar classification outcomes. Global search samples from the remaining rule catalogue. Rules with lower relative belief have a higher probability of leaving the candidate set. The number of candidates can therefore grow as new hypotheses enter and shrink as weak hypotheses are abandoned, within the participant's capacity limit. A new candidate receives a share of each retained rule's belief, with larger shares transferred from rules with more similar classification outcomes. This operation expresses the generalization of existing classification knowledge to a newly considered explanation (see Methods).

The feedback conditions also determine which latent relations are learned. In the hierarchical condition, the model maintains joint beliefs over classification rules and the three possible pairings of response labels into families. Fully correct, partially

correct and incorrect responses provide evidence about this joint state. When a new rule enters, it inherits the accumulated marginal belief about response pairings. This preserves learned family relations as the candidate classification rules change (see Methods).

The model thus defines several points at which learning can change. A useful rule can enter the candidate set before it receives substantial belief; increasing belief can precede its becoming dominant; and its predictions can become more precise while it remains dominant. Candidate-set size measures how many explanations are available, whereas effective participation measures how concentrated their contributions to choice are. These states provide separate quantities for examining rule discovery, belief accumulation, changes in rule use and increasing prediction precision (see Methods).

Participant-level parameters govern capacity, evidence retention, search, choice inertia and precision learning. They remain fixed within a participant, while the candidate set and its associated states evolve across trials. Particle filtering approximates the distribution of internal paths consistent with the available choice and feedback history. Predictions are averaged using path weights determined before the current choice and its feedback, defining the choice likelihood. Weighted states describe uncertainty about the inferred learning process (see Methods).

Behavioral prediction and model comparison

[Results to be added.]

Latent trajectories of hypothesis discovery and use

[Results to be added.]

Effects of feedback structure on learning

[Results to be added.]

Generative predictions and model identifiability

[Results to be added.]

Discussion

[Discussion to be completed after the empirical results.]

Methods

Task observations and rule representation

The model describes learning from category choices and subsequent feedback. For participant s on trial t, the observed stimulus is $\boldsymbol{x}_{s,t} \in [0,1]^4$, the response is

$y_{s,t} \in \{1, \ldots, C\}$, and the feedback is $r_{s,t}$. Stimulus coordinates encode normalized lengths of four anatomical features in the order used in the task. Condition 1 has two categories and binary feedback, $r_t \in \{0, 1\}$. Condition 2 has four categories and binary feedback. Condition 3 has four categories and graded feedback, $r_t \in \{0, 0.5, 1\}$: full credit denotes the correct species, partial credit another species in the correct family, and zero credit a species from the other family. Participants in condition 3 know that two families each contain two species, and learn which response labels belong together. Participant subscripts are retained for parameters and omitted for observations and states. Recruitment, sample sizes, task administration and exclusions: [To be specified].

Choices use a consistent response code across the observed data and model category probabilities. Feedback learning conditions on this response and its received feedback. The environment's true category is available for scoring and evaluating predictions. The two four-category conditions share the target classification structure and differ in feedback and instructed hierarchical knowledge. Reaction time is outside the present observation model.

A rule h assigns fixed category labels to regions $\mathcal{C}_{h,1}, \ldots, \mathcal{C}_{h,C}$ of stimulus space. The catalogue $\mathcal{H} = \{1, \ldots, J\}$ contains $J = 29$ rules for condition 1 and $J = 152$ rules for conditions 2 and 3. Table 1 gives the constituent families. Thresholds are 0.5 for single-feature judgments and 1 for two-feature sums; the tolerance for proximity judgments is 0.10. The catalogue includes overlapping feature use, conditional branches and disconnected category regions. Category labels remain fixed within each rule. The base prior is uniform over catalogue entries,

$$p_0(h) = \frac{1}{J}, \qquad h \in \mathcal{H}. \tag{1}$$

This prior supplies initial rule sampling and global search. Family-level prior mass consequently depends on the number of rules in each family.

Table 1: Rule families in the fixed catalogue. Crossed judgments combine two binary decisions into four categories; conditional rules use a first judgment to determine the subsequent branch. Feature indices follow the catalogue's fixed ordering.

Family	Decision structure	Count
Two-category catalogue		
Single-feature threshold	$x_i \leq 0.5$	4
Feature ordering	$x_i \leq x_j$	6
Feature sum	$x_i + x_j \leq 1$	6
Ordering of two sums	$x_i + x_j \leq x_k + x_l$, with disjoint pairs	3
Feature proximity	$\lvert x_i - x_j \rvert \leq 0.10$	6
Central feature interval	$\lvert x_i - 0.5 \rvert \leq 0.10$	4
Total		**29**
Four-category catalogue		
Two thresholds	Crossed single-feature thresholds	6

Family	Decision structure	Count
Ordering and sum	Crossed ordering and sum for the same feature pair	6
Threshold and ordering	One threshold crossed with ordering of two other features	12
Threshold and sum	One threshold crossed with the sum of two other features	12
Three thresholds	Conditional branches using three feature thresholds	24
Threshold, ordering and sum	A threshold branch followed by ordering or sum judgments	24
Two orderings	Crossed ordering judgments on disjoint feature pairs	3
Two sums	Crossed sum judgments on disjoint feature pairs	3
Ordering and thresholds	Ordering branches followed by thresholds on remaining features	12
Sum and thresholds	Sum branches followed by thresholds on remaining features	12
Feature extrema	Classification by the maximum or minimum feature	2
Threshold and overlapping ordering	Threshold crossed with an ordering that shares its feature	12
Two shared-feature comparisons	Two ordering judgments with one common feature	12
Proximity and disjoint threshold	Pairwise proximity crossed with a third-feature threshold	12
Total		**152**

Initial state and trial sequence

The learner maintains an active candidate set $\mathcal{A}_t \subset \mathcal{H}$, normalized rule beliefs π_t^-, rule-specific precisions $\beta_t(h)$, accumulated failure F_t, and the previous dominant rule $h_{t-1}^\star$. Condition 3 additionally maintains rule–pairing beliefs. Candidate count varies subject to

$$1 \le N_t = |\mathcal{A}_t| \le M_s^{\max}, \qquad 2 \le M_s^{\max} < J, \tag{2}$$

where $M_s^{\max}$ is an integer participant parameter. On the first trial, one rule is sampled from p_0, assigned belief 1 and precision $\beta_{0,s}$, and $F_1 = 0$. There is no previous dominant rule. Pairing beliefs initially assign probability $1/3$ to each possible pairing.

Each trial comprises perception, rule prediction and choice readout, followed by feedback learning. Rule beliefs and precisions are updated using the same predictions formed before feedback. Hypothesis updating then prepares the next trial's candidate set and initial beliefs. Superscripts $-$ and $+$ denote beliefs before choice and after feedback; ret and keep denote intermediate states after exits and capacity management. Feedback-induced changes affect subsequent choices. Failure state follows the complete chronological trial sequence across sessions. The pre-choice state z_t collects the internal stimulus and these latent variables, including the joint pairing distribution in condition 3.

Perception and rule-specific predictions

Perception (P) converts each physical feature into an internal observation,

$$\widetilde{x}_{t,j} = \mathrm{clip}(x_{t,j} + \varepsilon_{t,j}, 0, 1), \qquad \mathrm{clip}(v, 0, 1) = \min\{1, \max\{0, v\}\}. \tag{3}$$

The feature-specific error distribution and its parameters are determined by independent perceptual measurements obtained before category learning. The model accommodates the measured Gaussian or uniform error distribution. Distribution, measurement protocol and feature ordering for the reported analyses: [To be specified]. Within an internal trajectory, all rules use the same perceived stimulus on a given trial.

Rule predictions depend on the shortest Euclidean distance to each category region,

$$d_{t,h,c} = \inf_{\boldsymbol{\xi} \in \mathcal{C}_{h,c}} \|\widetilde{\boldsymbol{x}}_t - \boldsymbol{\xi}\|_2, \tag{4}$$

$$p_{t,h}(c) = \frac{\exp[-\beta_t(h) d_{t,h,c}]}{\sum_{a=1}^{C} \exp[-\beta_t(h) d_{t,h,a}]}. \tag{5}$$

Distance is zero inside a region and is taken to the nearest component for a disconnected region. Precision $\beta_t(h)$ determines how strongly distance differences influence category probabilities. These probabilities supply both choice readout and subsequent feedback evaluation.

Perceptual error changes the stimulus supplied to every candidate, while precision changes the conversion of that candidate's distances into probabilities. A rule can therefore generate a concentrated category prediction and still receive little relative belief when earlier feedback favors other candidates. The model tracks these quantities separately throughout learning.

Choice readout and rule-use inertia

Choice readout (RC) combines rule beliefs with persistence in rule use. The previous dominant rule receives a multiplicative advantage e^{λ_s}, yielding normalized choice weights

$$w_t(h) = \frac{\pi_t^-(h) e^{\lambda_s \mathbb{I}(h = h^\star_{t-1})}}{\sum_{v \in \mathcal{A}_t} \pi_t^-(v) e^{\lambda_s \mathbb{I}(v = h^\star_{t-1})}}, \qquad h \in \mathcal{A}_t. \tag{6}$$

The inertia parameter $\lambda_s \geq 0$ is constant within a participant. Weights vary with candidate membership, beliefs and the previous dominant rule. With $\lambda_s = 0$, weights equal beliefs. On trial 1, or when the previous dominant rule has left the active set, all inertia multipliers equal 1.

The trajectory-level response probability is

$$P(y_t = c \mid z_t) = \sum_{h \in \mathcal{A}_t} w_t(h) p_{t,h}(c). \tag{7}$$

Simulated responses are drawn from this categorical distribution. The dominant rule is recorded before the response as $h_t^\star \in \arg\max_{h \in \mathcal{A}_t} w_t(h)$. Ties preserve the previous

dominant rule when it belongs to the tied set; otherwise they are resolved uniformly. This record supplies inertia on the next trial. The lapse probability is fixed to zero. Choice variability arises from internal perception, candidate dynamics and the rule-specific category probabilities.

The inertia multiplier permits a previously dominant rule to retain the largest choice contribution after another rule has acquired greater evidence support. Dominance switches when a competitor's belief exceeds the inertia-adjusted belief of the previous dominant rule. Thus, belief changes and changes in the strongest contribution to choices can occur at different times within the same trajectory.

Feedback likelihood and evidence memory

Evidence memory (M) updates beliefs by evaluating how well each active rule predicts the feedback received after the observed response. For binary feedback,

$$\ell_t(h) = r_t p_{t,h}(y_t) + (1 - r_t)[1 - p_{t,h}(y_t)]. \tag{8}$$

Correct feedback supports the selected category; incorrect feedback supports the combined probability of the remaining categories. In the four-category binary task, the incorrect event therefore includes three alternatives.

Previous evidence is retained through exponent γ_s, and current evidence enters through the feedback likelihood:

$$\pi_t^+(h) = \frac{[\pi_t^-(h)]^{\gamma_s}\ell_t(h)}{\sum_{v\in\mathcal{A}_t}[\pi_t^-(v)]^{\gamma_s}\ell_t(v)}, \qquad 0 \le \gamma_s \le 1. \tag{9}$$

Larger γ_s retains more of the existing belief differences. At $\gamma_s = 0$, active candidates receive equal weight before incorporation of current feedback; at $\gamma_s = 1$, previous beliefs are retained in full. Nonactive rules have zero belief. Every active rule is evaluated, including candidates with small choice weights. Condition 3 applies this update to the joint distribution over rules and response pairings, as defined below.

Exponentiation compresses previous odds when $0 < \gamma_s < 1$, and multiplication by the likelihood incorporates the current observation. Normalization produces relative beliefs over the active set. A single active candidate has belief 1 because all relative support belongs to that explanation; its precision and the failure state continue to respond to feedback.

Feedback-dependent precision updating

Precision updating (B) adjusts the concentration of each rule's category predictions. For binary feedback, the neutral reference is the probability of the observed feedback under uniform category predictions,

$$\ell_{\text{chance}}(r_t) = \frac{r_t}{C} + (1 - r_t)\left(1 - \frac{1}{C}\right). \tag{10}$$

Correct and incorrect feedback have reference probabilities $1/C$ and $1 - 1/C$, respectively. The normalized support is

$$\kappa_t(h) = \begin{cases} \dfrac{\ell_t(h) - \ell_{\text{chance}}(r_t)}{1 - \ell_{\text{chance}}(r_t)}, & \ell_t(h) \geq \ell_{\text{chance}}(r_t), \\ \dfrac{\ell_t(h) - \ell_{\text{chance}}(r_t)}{\ell_{\text{chance}}(r_t)}, & \ell_t(h) < \ell_{\text{chance}}(r_t). \end{cases} \tag{11}$$

Positive support indicates that a rule explains the observed feedback better than the uniform reference, and negative support indicates poorer prediction. Thus, incorrect feedback can support a rule that assigns sufficient probability to other responses.

Every active rule updates precision according to

$$\beta_{t+1}(h) = \begin{cases} \min\{\beta_t(h) + \eta_{+,s}\kappa_t(h)[\beta_{\max} - \beta_t(h)], \beta_{\max}\}, & \kappa_t(h) \geq 0, \\ \max\{\beta_t(h) - \eta_{-,s}\beta_t(h)\min[1, -\kappa_t(h)], \beta_{\min}\}, & \kappa_t(h) < 0, \end{cases} \tag{12}$$

with shared bounds $\beta_{\min} = 0.1$ and $\beta_{\max} = 25$. Positive changes depend on the remaining distance to the upper bound; negative changes scale with current precision. The participant parameters $\eta_{+,s}$ and $\eta_{-,s}$ determine the respective rates. Support is computed from predictions made before feedback. Beliefs and precisions therefore update in parallel from the same evidence, and the new precision affects the next trial. Condition 3 uses its graded-feedback support measure in Eq. 12.

Hypothesis updating: search control and candidate retention

Hypothesis updating (H) regulates which explanations remain available. The trial's shortfall is $f_t = 1 - r_t$, and accumulated failure is

$$F_{t+1} = \delta_s F_t + (1 - \delta_s) f_t, \qquad F_1 = 0. \tag{13}$$

The retention parameter $\delta_s \in [0, 1)$ controls the persistence of past failures. Binary feedback contributes 0 or 1; graded feedback contributes 0, 0.5 or 1. This state governs both the probability of searching and the conditional probability of using a global source:

$$e_{t+1} = \text{sigmoid}[\text{logit}(e_{0,s}) + a_{e,s}F_{t+1}], \tag{14}$$

$$g_{t+1} = g_{0,s} + (1 - g_{0,s})a_{g,s}F_{t+1}. \tag{15}$$

Here $e_{0,s}$ and $g_{0,s}$ are baseline probabilities; $a_{e,s}$ and $a_{g,s}$ control their sensitivity to failure. We use $\text{sigmoid}(v) = 1/(1 + e^{-v})$ and $\text{logit}(p) = \log[p/(1 - p)]$.

Accumulated failure can increase opportunities to search and shift search toward the complete catalogue. Success reduces the accumulator toward zero, returning both probabilities toward their baselines. Failure retention δ_s determines the temporal persistence of performance information, while evidence retention γ_s determines the persistence of relative support for specific rules.

After feedback learning, each old rule independently proposes exit with probability

$$P(h \text{ proposes exit}) = \rho_s[1 - \pi_t^+(h)]. \tag{16}$$

Low-belief candidates are consequently more likely to leave. The dominant rule follows the same criterion. If all candidates exit, or survivors have zero total belief, a rule with the highest original belief is restored, with uniform tie-breaking. Denoting the actual exit set by $\mathcal{D}_t$, the retained set and beliefs are

$$\mathcal{A}_t^{\text{ret}} = \mathcal{A}_t \setminus \mathcal{D}_t, \qquad \pi_t^{\text{ret}}(h) = \frac{\pi_t^+(h)}{\sum_{v \in \mathcal{A}_t^{\text{ret}}} \pi_t^+(v)}. \tag{17}$$

One search event is drawn from Bernoulli(e_{t+1}). Without search, $\mathcal{A}_{t+1} = \mathcal{A}_t^{\text{ret}}$ and $\pi_{t+1}^- = \pi_t^{\text{ret}}$. With search, one new rule is generated. A lone candidate has belief 1 and zero exit probability, while subsequent search can expand the set.

Structural and functional rule proposals

An entrant is sampled from $\mathcal{U}_t = \mathcal{H} \setminus \mathcal{A}_t$. Eligibility excludes all rules active on the current trial, including those that have just exited. Global proposals use the base prior restricted to this set. Local proposals begin from a retained rule and combine structural editing with functional similarity.

A structural edit changes one feature, changes a comparison relation together with its standard reference, changes one reference value, or rewrites one lower judgment in a conditional tree. Their respective costs are 1, 1.5, 1 and 2. A branch edit preserves other judgments and the category-output layout. Equivalent judgments are placed in a common representation, and legal edits must yield another complete catalogue rule. The edit distance $d_{\text{edit}}(h, u)$ is the minimum cost of a legal single edit from h to u, or infinity when no such edit exists. For the eligible neighborhood $\mathcal{N}_t(h) = \{u \in \mathcal{U}_t : d_{\text{edit}}(h, u) < \infty\}$,

$$K_{\text{edit},t}(u \mid h) = \frac{\mathbb{I}[u \in \mathcal{N}_t(h)] e^{-d_{\text{edit}}(h,u)}}{\sum_{v \in \mathcal{N}_t(h)} e^{-d_{\text{edit}}(h,v)}}. \tag{18}$$

Functional distance quantifies disagreement between fixed-label classifications. Let $c_h(\boldsymbol{x})$ be a rule's deterministic category label and μ_X the uniform distribution on $[0, 1]^4$. The shared correspondence matrix, agreement and distance are

$$T_{cc'}(h, u) = \Pr_{\boldsymbol{x} \sim \mu_X}[c_h(\boldsymbol{x}) = c, c_u(\boldsymbol{x}) = c'], \tag{19}$$

$$S(h, u) = \sum_{c=1}^{C} T_{cc}(h, u), \qquad d_{\text{func}}(h, u) = 1 - S(h, u). \tag{20}$$

These quantities use 100,000 uniformly sampled reference stimuli with random seed 0, shared across participants. Agreement depends on the prevalence of each category

in the reference distribution. Functional proposals use

$$K_{\mathrm{func},t}(u \mid h) = \frac{\mathbb{I}(u \in \mathcal{U}_t) p_0(u) e^{-d_{\mathrm{func}}(h,u)/\tau_{\mathrm{prop}}}}{\sum_{v \in \mathcal{U}_t} p_0(v) e^{-d_{\mathrm{func}}(h,v)/\tau_{\mathrm{prop}}}}, \qquad \tau_{\mathrm{prop}} = 0.10. \tag{21}$$

The shared proposal scale determines how strongly local proposals favor classification agreement.

When $\mathcal{N}_t(h)$ is nonempty, the participant's local source preference gives $K_{\mathrm{loc},t} = \omega_s K_{\mathrm{edit},t} + (1-\omega_s) K_{\mathrm{func},t}$. If it is empty, $K_{\mathrm{loc},t} = K_{\mathrm{func},t}$. Retained beliefs weight the possible local starting points, and the global probability mixes the two sources:

$$Q_{\mathrm{loc},t}(u) = \sum_{h \in \mathcal{A}_t^{\mathrm{ret}}} \pi_t^{\mathrm{ret}}(h) K_{\mathrm{loc},t}(u \mid h), \tag{22}$$

$$Q_{\mathrm{glob},t}(u) = \frac{\mathbb{I}(u \in \mathcal{U}_t) p_0(u)}{\sum_{v \in \mathcal{U}_t} p_0(v)}, \tag{23}$$

$$Q_t(u) = (1 - g_{t+1}) Q_{\mathrm{loc},t}(u) + g_{t+1} Q_{\mathrm{glob},t}(u). \tag{24}$$

One entrant u is drawn from Q_t. Structural preference ω_s is constant within a participant; global-source probability g_{t+1} varies with accumulated failure.

Capacity management and belief transfer

After generating an entrant, all retained rules remain if there is unused capacity. At capacity, one rule with the lowest retained belief is removed, with uniform tie-breaking:

$$h_t^{\mathrm{drop}} \in \arg\min_{h \in \mathcal{A}_t^{\mathrm{ret}}} \pi_t^{\mathrm{ret}}(h), \qquad \mathcal{A}_t^{\mathrm{keep}} = \mathcal{A}_t^{\mathrm{ret}} \setminus \{h_t^{\mathrm{drop}}\}. \tag{25}$$

Otherwise $\mathcal{A}_t^{\mathrm{keep}} = \mathcal{A}_t^{\mathrm{ret}}$. The retained old beliefs are normalized within the final old set,

$$\pi_t^{\mathrm{keep}}(h) = \frac{\pi_t^{\mathrm{ret}}(h)}{\sum_{v \in \mathcal{A}_t^{\mathrm{keep}}} \pi_t^{\mathrm{ret}}(v)}, \qquad h \in \mathcal{A}_t^{\mathrm{keep}}. \tag{26}$$

Dominant rules receive the same capacity criterion, and the capacity bound leaves at least one old rule available for transfer.

Functional affinity determines the support transferred to the entrant:

$$\chi_s(h,u) = e^{-d_{\mathrm{func}}(h,u)/\tau_{\mathrm{tr},s}}, \tag{27}$$

$$\pi_{t+1}^{-}(h) = \frac{\pi_t^{\mathrm{keep}}(h)}{1 + \chi_s(h,u)}, \qquad h \in \mathcal{A}_t^{\mathrm{keep}}, \tag{28}$$

$$\pi_{t+1}^{-}(u) = \sum_{h \in \mathcal{A}_t^{\mathrm{keep}}} \frac{\pi_t^{\mathrm{keep}}(h) \chi_s(h,u)}{1 + \chi_s(h,u)}. \tag{29}$$

The participant scale $\tau_{\mathrm{tr},s} > 0$ controls the breadth of support generalization. Each old rule divides its belief in the ratio $1 : \chi_s(h,u)$ between itself and the entrant, conserving

total belief. Since $\chi_s \leq 1$, initial entrant belief is at most $1/2$. The next active set is $\mathcal{A}_{t+1} = \mathcal{A}_t^{\text{keep}} \cup \{u\}$. This allocation applies to every proposal source. Retained rules keep their updated precisions; new and re-entering rules start at $\beta_{0,s}$ and first learn from feedback on their next active trial.

Proposal probabilities determine which rule enters, and affinity determines its initial evidence support. Greater old-rule belief and greater functional agreement both increase the entrant's received support. The shared scale τ_{prop} governs selection under functional search; participant scale $\tau_{\text{tr},s}$ governs transfer after selection. Subsequent feedback updates the entrant together with the retained candidates.

Joint learning of rules and response pairings

Condition 3 represents the three possible response pairings as

$$\mathcal{G}_1 = \{\{1,2\},\{3,4\}\}, \quad \mathcal{G}_2 = \{\{1,3\},\{2,4\}\}, \quad \mathcal{G}_3 = \{\{1,4\},\{2,3\}\}. \tag{30}$$

For each rule, $q_t^-(k \mid h)$ denotes the conditional belief in pairing k, with initial value $1/3$. The joint prior is $\Pi_t^-(h,k) = \pi_t^-(h) q_t^-(k \mid h)$. Writing $\text{mate}_k(y)$ for the other response paired with y, graded-feedback likelihoods are

$$\ell_t(h,k) = \begin{cases} p_{t,h}(y_t), & r_t = 1, \\ p_{t,h}[\text{mate}_k(y_t)], & r_t = 0.5, \\ 1 - p_{t,h}(y_t) - p_{t,h}[\text{mate}_k(y_t)], & r_t = 0. \end{cases} \tag{31}$$

The three mutually exclusive events exhaust the predicted category probabilities. Joint evidence memory is

$$\Pi_t^+(h,k) = \frac{[\Pi_t^-(h,k)]^{\gamma_s} \ell_t(h,k)}{\sum_{v \in \mathcal{A}_t} \sum_{k'=1}^{3} [\Pi_t^-(v,k')]^{\gamma_s} \ell_t(v,k')}. \tag{32}$$

Rule beliefs are the marginals $\pi_t^+(h) = \sum_k \Pi_t^+(h,k)$, and $q_t^+(k \mid h) = \Pi_t^+(h,k)/\pi_t^+(h)$. A zero rule marginal receives a uniform conditional pairing. At $\gamma_s = 0$, active rule–pairing combinations receive equal pre-evidence weight.

When pairing beliefs are uniform, half-credit likelihood marginalized over pairings equals $[1 - p_{t,h}(y_t)]/3$, and zero-credit likelihood is twice this value. The common multiplier gives identical relative rule support after normalization, although the two outcomes can support different pairings. As pairing knowledge accumulates, graded feedback can provide more specific evidence about classification rules.

For precision learning, pairing probabilities are computed after evidence retention and before incorporation of current feedback:

$$\widetilde{q_t^-}(k \mid h) = \frac{[\Pi_t^-(h,k)]^{\gamma_s}}{\sum_{k'=1}^{3} [\Pi_t^-(h,k')]^{\gamma_s}}, \tag{33}$$

$$\ell_t(h) = \sum_{k=1}^{3} \widetilde{q_t^-}(k \mid h)\ell_t(h,k), \tag{34}$$

$$\kappa_t^{(3)}(h) = \frac{\ell_t(h) - \ell_{\text{chance}}(r_t)}{\ell_t(h) + \ell_{\text{chance}}(r_t)}. \tag{35}$$

Uniform conditional pairing is used when a rule has zero joint mass or $\gamma_s = 0$. The graded-feedback chance probabilities are 1/4, 1/4 and 1/2 for feedback 1, 0.5 and 0, respectively. This support enters Eq. 12; half-credit feedback can increase or decrease precision according to its predicted probability.

Before candidate exits or capacity removal, the model saves the overall posterior pairing marginal $\bar{q}_t^+(k) = \sum_{h \in \mathcal{A}_t} \Pi_t^+(h,k)$. Candidate updating retains each old rule's conditional pairing knowledge and assigns the saved overall distribution to an entrant:

$$\Pi_{t+1}^-(h,k) = \pi_{t+1}^-(h) \begin{cases} q_t^+(k \mid h), & h \text{ is retained,} \\ \bar{q}_t^+(k), & h \text{ is an entrant.} \end{cases} \tag{36}$$

This inheritance applies to local and global entrants and preserves accumulated response-pair knowledge during candidate changes.

Particle inference and choice likelihood

Particle filtering represents uncertainty about the learner's hidden trajectory. Particle n carries its own perceived observations, candidate set, beliefs, precisions, failure state, dominant rule and conditional pairing state. Its pre-choice weight $W_t^{(n),\text{pre}}$ describes the researcher's relative support for that trajectory, with $\sum_n W_t^{(n),\text{pre}} = 1$. The predictive choice probability and subsequent choice-conditioned weights are

$$\widehat{P}_t(c) = \sum_{n=1}^{N_{\text{PF}}} W_t^{(n),\text{pre}} p_t^{(n)}(c), \tag{37}$$

$$W_t^{(n),\text{choice}} = \frac{W_t^{(n),\text{pre}} p_t^{(n)}(y_t)}{\sum_{n'=1}^{N_{\text{PF}}} W_t^{(n'),\text{pre}} p_t^{(n')}(y_t)}, \tag{38}$$

where $p_t^{(n)}(c)$ is Eq. 7 evaluated in that particle. Each trajectory then learns from the observed response and feedback. Particle weights, learner rule beliefs and learner choice weights operate at their respective levels.

Effective particle sample size is $\text{ESS}_t = 1/\sum_n [W_t^{(n),\text{choice}}]^2$. Resampling below a prescribed threshold concentrates computation on trajectories supported by choices. Resampled particles inherit cognitive states and receive independent subsequent random streams. Particle count, ESS threshold, resampling scheme and random seeds: [To be specified].

The fitting objective is mean choice negative log-likelihood,

$$\mathrm{NLL}(\boldsymbol{\theta}_s) = -\frac{1}{T_{\mathrm{score}}} \sum_{t \in \mathcal{T}_{\mathrm{score}}} \log \widehat{P}_t(y_t; \boldsymbol{\theta}_s), \qquad T_{\mathrm{score}} = |\mathcal{T}_{\mathrm{score}}|. \tag{39}$$

Probabilities are evaluated before current feedback enters learning. For repeated independent filters, trial-level category probabilities are averaged before calculating the logarithm. Scoring trials, training and evaluation boundaries, repeat count, free versus fixed parameters, finite search ranges, optimization and stopping criteria: [To be specified]. Parameters selected using the evaluated sequence yield an in-sample fit. Parameter recovery, numerical stability checks, uncertainty estimation and inferential statistics: [To be specified].

Participant parameters and latent process measures

The full specification contains 14 participant-level behavioral parameters (Table 2). Parameters remain constant within a participant; beliefs, precision, failure, candidate membership and dominant-rule identity evolve across trials. Perceptual parameters are supplied by independent measurements.

The information available about these parameters depends on the learning trajectory. Weak failure sensitivity provides little information about δ_s; a global baseline near 1 limits information about $a_{g,s}$. Similar structural and functional proposal distributions reduce sensitivity to ω_s, and infrequent saturation limits information about capacity. Transfer, inertia, precision and evidence retention can have compensating effects on choices. Recovery and model comparison are therefore required to assess their practical identifiability.

Table 2: Participant parameters and mathematical domains.

Parameter	Function	Domain
$e_{0,s}$	Baseline search probability	$(0, 1)$
$a_{e,s}$	Failure sensitivity of search	$[0, \infty)$
δ_s	Retention of accumulated failure	$[0, 1)$
$g_{0,s}$	Baseline global-source probability	$[0, 1]$
$a_{g,s}$	Failure sensitivity of global-source probability	$[0, 1]$
$M_s^{\max}$	Maximum active candidate count	Integer, $2 \leq M_s^{\max} < J$
ρ_s	Candidate exit rate	$[0, 1]$
ω_s	Structural-source probability within local search	$[0, 1]$
$\tau_{\mathrm{tr},s}$	Functional belief-transfer scale	$(0, \infty)$
λ_s	Rule-use inertia	$[0, \infty)$
γ_s	Evidence retention	$[0, 1]$
$\beta_{0,s}$	Initial rule precision	$[0.1, 25]$
$\eta_{+,s}$	Precision increase rate	$[0, 1]$
$\eta_{-,s}$	Precision decrease rate	$[0, 1]$

Candidate availability is the probability that a rule belongs to the active set. Its pre-choice estimate and the expected candidate count are

$$\widehat{P}_t(h \in \mathcal{A}_t) = \sum_n W_t^{(n),\mathrm{pre}} \mathbb{I}(h \in \mathcal{A}_t^{(n)}), \tag{40}$$

$$\overline{N}_t = \sum_n W_t^{(n),\mathrm{pre}} |\mathcal{A}_t^{(n)}|. \tag{41}$$

The concentration of rule contributions within a trajectory is measured by

$$N_{\mathrm{eff},t} = \frac{1}{\sum_{h \in \mathcal{A}_t} w_t(h)^2}, \qquad 1 \le N_{\mathrm{eff},t} \le N_t. \tag{42}$$

This measure is averaged across particles after calculation within each trajectory. Dominant-rule probabilities similarly aggregate indicators of $h_t^\star$. Joint examination of candidate availability, rule belief, choice weight and precision separates when a rule is considered, supported, expressed in choices and sharpened through feedback. The delay from entry to dominance, transition edit types and functional distances provide additional process measures. Pairing concentration, pairing correctness and family-level categorization quantify distinct aspects of hierarchical learning. Each analysis identifies whether summaries use pre-choice weights or choice-conditioned weights, together with their trial timing.