

Assignment 4

Yuki Joyama (yj2803)

Problem 1

Problem 2

```
# import file
data <- read.table("./data.txt", header = TRUE, sep = " ", stringsAsFactors = FALSE)
```

PC algorithm

```
# Function to calculate log likelihood
compute_log_likelihood <- function(data, adj_matrix) {
  sample_cov <- cov(data) # Sample covariance matrix
  adj_cov <- sample_cov * adj_matrix # Adjust covariance for graph

  # Regularization for numerical stability
  p <- ncol(data)
  regularization <- diag(10, p)
  adj_cov <- adj_cov + regularization

  # Log-likelihood calculation
  tryCatch({
    log_det <- log(det(adj_cov)) # Log determinant
    inv_cov <- solve(adj_cov) # Inverse covariance
    log_likelihood <- -0.5 * nrow(data) * (log_det + sum(diag(inv_cov) %*% sample_cov))
    return(log_likelihood)
  }, error = function(e) {
    return(NA) # Return NA if numerical issues occur
  })
}

# Function to calculate BIC
compute_bic <- function(pc_fit, data) {
  adj_matrix <- as(pc_fit@graph, "matrix") # Adjacency matrix
```

```

num_params <- sum(adj_matrix) # Number of edges (parameters)
log_lik <- compute_log_likelihood(data, adj_matrix)

if (is.na(log_lik)) return(Inf) # Return infinite BIC for invalid graphs

n <- nrow(data) # Sample size
p <- ncol(data) # Number of variables
bic <- -2 * log_lik + log(n) * (num_params + p) # BIC formula
return(bic)
}

# Generate a sequence of alpha values
alphas <- seq(0.001, 0.1, by = 0.001)

# Fit PC algorithm and compute BIC for each alpha
bic_values <- sapply(alphas, function(alpha) {
  pc_fit <- pc(
    suffStat = list(C = cor(data), n = nrow(data)),
    indepTest = gaussCitest,
    alpha = alpha,
    labels = colnames(data),
    verbose = FALSE
  )
  compute_bic(pc_fit, data)
})

# Find optimal alpha
optimal_alpha <- alphas[which.min(bic_values)]
cat("Optimal alpha based on BIC:", optimal_alpha, "\n")


```

```
## Optimal alpha based on BIC: 0.008
```

```

# Plot BIC vs Alpha
plot(
  alphas, bic_values, type = "b", pch = 16, col = "blue",
  xlab = "Alpha", ylab = "BIC",
  main = "BIC vs Alpha"
)

```




```
# Run pc algorithm with alpha = 0.001
pc.fit.001 <- pc(suffStat = list(C = cor(data), n = nrow(data)),
  indepTest = gaussCitest,
  alpha=0.001, labels = colnames(data), verbose = TRUE)


# alpha = 0.008
pc.fit.008 <- pc(suffStat = list(C = cor(data), n = nrow(data)),
  indepTest = gaussCitest,
  alpha=0.008, labels = colnames(data), verbose = TRUE)

# alpha = 0.1
pc.fit.1 <- pc(suffStat = list(C = cor(data), n = nrow(data)),
  indepTest = gaussCitest,
  alpha=0.1, labels = colnames(data), verbose = TRUE)


# Plot CPDAG
plot(pc.fit.001@graph)
```



```
plot(pc.fit.008@graph)
```



```
plot(pc.fit.1@graph)
```



Check the number of edges

pc.fit.001

```
## Object of class 'pcAlgo', from Call:
## pc(suffStat = list(C = cor(data), n = nrow(data)), indepTest = gaussCitest,
##     alpha = 0.001, labels = colnames(data), verbose = TRUE)
## Number of undirected edges: 1
## Number of directed edges: 19
## Total number of edges: 20
```

pc.fit.008

```
## Object of class 'pcAlgo', from Call:
## pc(suffStat = list(C = cor(data), n = nrow(data)), indepTest = gaussCitest,
##     alpha = 0.008, labels = colnames(data), verbose = TRUE)
## Number of undirected edges: 2
## Number of directed edges: 23
## Total number of edges: 25
```

```
pc.fit.1
```

```
## Object of class 'pcAlgo', from Call:  
## pc(suffStat = list(C = cor(data), n = nrow(data)), indepTest = gaussCIttest,  
##      alpha = 0.1, labels = colnames(data), verbose = TRUE)  
## Number of undirected edges: 1  
## Number of directed edges: 28  
## Total number of edges: 29
```

I used the PC algorithm to estimate CPDAGs for a range of α values (0.001 to 0.1) to identify the optimal α that minimizes the Bayesian Information Criterion (BIC). For each α , the graph structure $G(\alpha)$ was used to compute the log-likelihood $-2\ell(\hat{\Sigma}_{G'}, \hat{\mu})$, where $\ell(\cdot)$ is the log-likelihood of a Gaussian model based on the graph-constrained covariance matrix. The BIC for each graph was computed as $-2\ell + \log(n)(k + p)$, with k representing the number of edges and p the number of variables.

The optimal $\alpha = 0.008$ was selected as the value minimizing BIC. This model is considered to have an optimal balance between complexity and fit.

Estimated CPDAGs were plotted for specific α values (0.001, 0.008, 0.1), and the number of edges was examined for each plot. We see that the smaller α value led to sparser graph with fewer edges, and the larger α value led to denser graphs with more edges.