



SUNG KYUN KWAN UNIVERSITY

성균관대 영어영문학과 4단계 BK21교육연구단

Workshop on Experimental Linguistics/Syntax (Day 3)

Experimental Syntax using IBEX: a walkthrough

January 22, 2021

Nayoun Kim

Department of Linguistics

University of Toronto

Guest



June Choe

yjunechoe.github.io

Ph.D. Student in Linguistics

University of Pennsylvania (Philadelphia, PA, USA)

Research: psycholinguistics, computational linguistics

Will be answering questions in the chat!

Presentation Outline



Introduction to IBEX

- Basic ideas
- Navigating the platform



Scripting an experiment

- Overview of critical components
- Code walkthrough



Analysis of the results

- Understanding the output format
- Importing into Excel and R


Link to the slides: <https://ibex-workshop-slides.netlify.app>

1. Introduction to IBEX


What is IBEX?

- Stands for (I)nternet-(B)ased (EX)periments
- **DOES:**
 - Host experiments on a webpage
 - Log user interactions with the experiment
 - Store data on a secure server
- **DOES NOT:**
 - Recruit participants (see Amazon Mechanical Turk)
 - Provide an analysis of the results (see R, Python)

Where does IBEX fit?



Where does IBEX fit?



Navigating IBEX

- Go to <https://spellout.net/ibexfarm>
- Click [create an account](#) (or [log in](#))
- Click [manage my experiments](#)
- Click [Create a new experiment](#)
- Give it a unique name like "*workshop_example*"
- Done!

Experiments

- [workshop_example](#) (ibex 0.3.9) ([delete](#) | [rename](#))


» [Create a new experiment](#)

Navigating Ibex

Ibex Farm

[home](#) | [login](#) | [create an account](#) | [ibex docs](#)

Welcome to the Ibex farm



This site provides free hosting for **ibex** experiments.

Upload data files in your browser, then send your participants a link to the experiment.

[View an example experiment](#)

Currently hosting **20564** experiments.

Have you found Ibex Farm useful? Buy me a coffee!
(Running costs are now covered for the foreseeable future. Thank you all.)

Contact a.d.drummond@gmail.com if you have any issues, or try the [google group](#).

The code for this site is BSD-licensed and available on [github](#).

▶ 0:00 / 0:25

🔊 🗨️ ⋮

Experiment file structure

chunk_includes

- Stand-alone files go here

css_includes

- Style specifications go here

data_includes

- Experiment scripts go here

js_includes

- Modules ("controllers") go here

results & server_state

- Automatically generated/updated

Experiment 'workshop_example' (ibex 0.3.9)

Update from git repo» [\(help\)](#)

chunk_includes ([upload a file to this directory](#) | [refresh](#))

example_intro.html ([delete](#) | [rename](#) | [upload new version](#) | [edit](#))

test1.mp3 ([delete](#) | [rename](#) | [upload new version](#) | [edit](#))

test2.mp3 ([delete](#) | [rename](#) | [upload new version](#) | [edit](#))

css_includes ([upload a file to this directory](#) | [refresh](#))

DashedSentence.css

FlashSentence.css

Form.css

global_main.css

Message.css

Question.css

Scale.css

Separator.css

data_includes ([upload a file to this directory](#) | [refresh](#))

example_data.js ([delete](#) | [rename](#) | [upload new version](#) | [edit](#))

js_includes ([upload a file to this directory](#) | [refresh](#))

AcceptabilityJudgment.js

DashedAcceptabilityJudgment.js

DashedSentence.js

FlashSentence.js

Form.js

Message.js

Question.js

Scale.js

Separator.js

VBox.js

results ([upload a file to this directory](#) | [refresh](#))

This directory is not present

server_state ([upload a file to this directory](#) | [refresh](#))

This directory is not present

Experiment file structure

chunk_includes

- Stand-alone files go here

css_includes

- Style specifications go here

data_includes

- Experiment scripts go here

js_includes

- Modules ("controllers") go here

results & server_state

- Automatically generated/updated

Experiment 'workshop_example' (ibex 0.3.9)

Update from git repo» [\(help\)](#)

chunk_includes ([upload a file to this directory](#) | [refresh](#))

example_intro.html ([delete](#) | [rename](#) | [upload new version](#) | [edit](#))

test1.mp3 ([delete](#) | [rename](#) | [upload new version](#) | [edit](#))

test2.mp3 ([delete](#) | [rename](#) | [upload new version](#) | [edit](#))

css_includes ([upload a file to this directory](#) | [refresh](#))

DashedSentence.css

FlashSentence.css

Form.css

global_main.css

Message.css

Question.css

Scale.css

Separator.css

data_includes ([upload a file to this directory](#) | [refresh](#))

example_data.js ([delete](#) | [rename](#) | [upload new version](#) | [edit](#))

js_includes ([upload a file to this directory](#) | [refresh](#))

AcceptabilityJudgment.js

DashedAcceptabilityJudgment.js

DashedSentence.js

FlashSentence.js

Form.js

Message.js

Question.js

Scale.js

Separator.js

VBox.js

results ([upload a file to this directory](#) | [refresh](#))

This directory is not present

server_state ([upload a file to this directory](#) | [refresh](#))

This directory is not present

2. Scripting an experiment

The script

Only need to modify **one file**: *example_data.js* (can also be renamed later)

At creation, the default file looks like this:

```
var shuffleSequence = seq("intro", sepWith("sep", seq("practice", rshuffle("s1", "s2"))),
  sepWith("sep", rshuffle("q1", "q2")));
var practiceItemTypes = ["practice"];

var defaults = [
  "Separator", {
    transfer: 1000,
    normalMessage: "Please wait for the next sentence.",
    errorMessage: "Wrong. Please wait for the next sentence."
  },
  "DashedSentence", {
    mode: "self-paced reading"
  },
  "AcceptabilityJudgment", {
    as: ["1", "2", "3", "4", "5", "6", "7"],
    presentAsScale: true,
    instructions: "Use number keys or click boxes to answer.",
    leftComment: "(Bad)", rightComment: "(Good)"
  },
];
```

The above script creates this self-paced reading experiment.

Writing your own script

The *example_data.js* script works, but is not very friendly.

We'll use **our own** - **template file** - to demonstrate how the script works.

```
// Defaults and other settings //
```

```
//// Generates random number assigned to participants (Participant ID)
var randomCode = Math.random().toString(36).substr(2,9)
//// A message to show to participants at completion (useful for confirmation, raffle entry, etc.)
var completionMessage = "Thank you for your participation. Your participation code is: " +
randomCode

//// Show a progress bar at the top? (true/false)
var showProgressBar = false

//// Override default settings for controllers (parameters go inside the curly braces { })
var defaults = [
  "AcceptabilityJudgment", {
    as: ["1", "2", "3", "4", "5", "6", "7"],
    presentAsScale: true,
    instructions: "Use number keys or click boxes to answer.",
    leftComment: "(Bad)",
    rightComment: "(Good)"
  }
]
```

The above script creates this acceptability rating experiment.

A simple layout

```
1 var randomCode = Math.random().toString(36).substr(2,8);
2
3 var completionCode = String("WFL" + randomCode);
4
5 var completionMessage = "Thank you for your participation. The results were successfully transmitted. Your participation code is: " + completionCode;
6
7 var showProgressbar = false;
8
9 var defaults = {"acceptabilityJudgment": {
10   seq: ["1", "2", "3", "4", "5", "6", "7"],
11   presentable: true,
12   instructions: "Use number keys or click boxes to answer.",
13   leftComment: "(easy)",
14   rightComment: "(good)"
15 }};
16
17 var shuffleSequence = seq({
18   "set_counter",
19   "main_graphics",
20   "intro",
21   "practice",
22   seqWith("sep", shuffle(seq(startWith("not"), startWith("filler"))))
23 });
24
25 var items = [
26   [{"setCounter", "_setCounter_", { }}],
27
28   [{"intro", "Message", {
29     consentRequired: false,
30     seq: ["seq",
31       ["p", "Welcome! Here are some instructions to the experiment."],
32       ["p", "Hope you have a great time! It'll be a blast."]
33     ]
34   }},
35   ],
36
37   [{"practice", "Message", {
38     transfer: "keypress",
39     seq: ["seq",
40       ["p", "Before starting the questionnaire, let's do a couple of examples to get a feel for the task."]
41     ]
42   }},
43   ],
44   [{"practice", "acceptabilityJudgment", {s: "The car drove like a dream."}},
45   [{"practice", "Message", {
46     transfer: "keypress",
47     seq: ["seq",
48       ["p", "How was that? Many people rate that sentence pretty good."]
49     ]
50   }},
51   ],
52   [{"practice", "Message", {
53     transfer: "keypress",
54     seq: ["seq",
55       ["p", "Let's try another one."]
56     ]
57   }},
58   [{"practice", "acceptabilityJudgment", {s: "The cat ever has eaten cheese the."}},
59   [{"practice", "Message", {
60     transfer: "keypress",
61     seq: ["seq",
62       ["p", "That sentence usually receives pretty poor ratings."],
63       ["p", "Oh! That's it. It's time to begin"]
64     ]
65   }},
66   ],
67
68   [{"sep", "separator", {}}],
69
70   [{"seq.gran", "acceptabilityJudgment", {s: "No duck that the goose chased has ever returned to our pond."}},
71   [{"seq.illus", "acceptabilityJudgment", {s: "The duck that no goose chased has ever returned to our pond."}},
72   [{"seq.ingran", "acceptabilityJudgment", {s: "The duck that the goose chased has ever returned to our pond."}},
73   [{"seq.gran", "acceptabilityJudgment", {s: "No bill that the Democratic senators supported has ever become law."}},
74   [{"seq.illus", "acceptabilityJudgment", {s: "The bill that no Democratic senators supported has ever become law."}},
75   [{"seq.ingran", "acceptabilityJudgment", {s: "The bill that the Democratic senators supported has ever become law."}},
76
77   [{"filler.seq-01", "acceptabilityJudgment", {s: "The bored schoolchild kicked dog without any apparent remorse."}},
78   [{"filler.seq-02", "acceptabilityJudgment", {s: "Pauline left her sweater the train on the way home."}},
79   [{"filler.seq-03", "acceptabilityJudgment", {s: "Margaret spent all night working at the camera and was tired."}},
80   [{"filler.seq-04", "acceptabilityJudgment", {s: "The way to happiness is never straightforward or obvious."}},
81
82   [{"filler.attention-check-01", "acceptabilityJudgment", {s: "Please select 4 for this sentence; do not rate it like other sentences."}}]
83 ];
```

Editing the script

When you open the **.js** file in the **data_includes** section of your experiment on Ibex, it will open up a text editor.

A simple layout

```
1 var randomCode = Math.random().toString(36).substr(2,8);
2
3 var completionCode = String("WFL-" + randomCode);
4
5 var completionMessage = "Thank you for your participation. The results were successfully transmitted. Your participation code is: " + completionCode;
6
7 var showProgressbar = false;
8
9 var defaults = {"acceptabilityJudgment": {
10   seq: ["1", "2", "3", "4", "5", "6", "7"],
11   presentable: true,
12   instructions: "Use number keys or click boxes to answer.",
13   leftComment: "1 (bad)",
14   rightComment: "7 (good)"
15 }};
16
17 var shuffleSequence = seq({
18   "set_counter",
19   "main_graphical",
20   "intro",
21   "practice",
22   seqWith("sep", shuffle(startWith("sep"), startWith("filler")))
23 });
24
25 var items = [
26   [{"setCounter", "_setCounter_", { }}],
27
28   [{"intro", "Message", {
29     consentRequired: false,
30     seq: ["seq",
31         ["p", "Welcome! Here are some instructions to the experiment."],
32         ["p", "Hope you have a great time! It'll be a blast."],
33       ]
34     }
35   }],
36
37   [{"practice", "Message", {
38     transfer: "keypress",
39     seq: ["seq",
40         ["p", "Before starting the questionnaire, let's do a couple of examples to get a feel for the task."],
41       ]
42     }
43   }],
44
45   [{"practice", "acceptabilityJudgment", {s: "The car drove like a dream."}],
46   [{"practice", "Message", {
47     transfer: "keypress",
48     seq: ["seq",
49         ["p", "How was that? Many people rate that sentence pretty good."],
50       ]
51     }
52   }],
53
54   [{"practice", "Message", {
55     transfer: "keypress",
56     seq: ["seq",
57         ["p", "Let's try another one."],
58       ]
59     }
60   }],
61   [{"practice", "acceptabilityJudgment", {s: "The cat ever has eaten cheese the."}],
62   [{"practice", "Message", {
63     transfer: "keypress",
64     seq: ["seq",
65         ["p", "That sentence usually receives pretty poor ratings."],
66         ["p", "Oh! That's it. It's time to begin!"],
67       ]
68     }
69   }],
70
71   [{"sep", "separator", {}}],
72
73   [{"seq.graph", "acceptabilityJudgment", {s: "No duck that the goose chased has ever returned to our pond."}],
74   [{"seq.graph", "acceptabilityJudgment", {s: "The duck that no goose chased has ever returned to our pond."}],
75   [{"seq.graph", "acceptabilityJudgment", {s: "The duck that the goose chased has ever returned to our pond."}],
76   [{"seq.graph", "acceptabilityJudgment", {s: "No bill that the Democratic senators supported has ever become law."}],
77   [{"seq.graph", "acceptabilityJudgment", {s: "The bill that no Democratic senators supported has ever become law."}],
78   [{"seq.graph", "acceptabilityJudgment", {s: "The bill that the Democratic senators supported has ever become law."}],
79
80   [{"filler.seq-01", "acceptabilityJudgment", {s: "The bored schoolchild kicked dog without any apparent remorse."}],
81   [{"filler.seq-02", "acceptabilityJudgment", {s: "Pauline left her sweater the train on the way home."}],
82   [{"filler.seq-03", "acceptabilityJudgment", {s: "Margaret spent all night working at the camera and was tired."}],
83   [{"filler.seq-04", "acceptabilityJudgment", {s: "The way to happiness is never straightforward or obvious."}],
84
85   [{"filler.attention-check-01", "acceptabilityJudgment", {s: "Please select 4 for this sentence; do not rate it like other sentences."}}]
86 ];
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
```

Editing the script

When you open the **.js** file in the **data_includes** section of your experiment on Ibex, it will open up a text editor.

Options for editing the file:

- Make changes directly on IBEX
- Download the file and open with an **editor** that supports **JavaScript** syntax checking (e.g., Atom)

A simple layout



Parts of the Script

Settings:

- Sets various options for the experiment


Sequence (shuffleSequence):

- Specifies the ordering of the different parts of the experiment

Body (items):

- Includes the actual material that will be shown to the participants

A simple layout



Body

Forms

- Introduction page, consent form, directions, language background, demographic information, etc.

Trials

- All stimuli for the experiment
- *Practice, Critical, Filler*
- Can be accompanied by messages, questions, etc.

Walkthrough of the components

template

```
1 var randomCode = Math.random().toString(36).substr(2,9);
2
3 var completionCode = String("MPI-" + randomCode);
4
5 var completionMessage = "Thank you for your participation. The results were successfully transmitted. Your participation code is: " + completionCode;
6
7 var showProgressBar = false;
8
9 var defaults = {"AcceptabilityJudgment", {
10   as: ["1", "2", "3", "4", "5", "6", "7"],
11   presentAsScale: true,
12   instructions: "Use number keys or click boxes to answer.",
13   leftComment: "(Bad)",
14   rightComment: "(Good)"
15 }};
16
17 var shuffleSequence = seq(
18   "set_counter",
19   "demographics",
20   "intro",
21   "practice",
22   sepwith("sep", rshuffle(startswith("mpi"), startswith("filler")))
23 );
24
25 var items = [
26   ["setcounter", "_setcounter_", ( )],
27
28   ["intro", "message", {
29     consentRequired: false,
30     html: ["div",
31       ["p", "Welcome! Here are some instructions to the experiment."],
32       ["p", "Hope you have a great time! It'll be a blast."]
33     ]
34   }],
35
36   ["practice", "message", {
37     transfer: "keypress",
38     html: ["div",
39       ["p", "Before starting the questionnaire, let's do a couple of examples to get a feel for the task."]
40     ]
41   }],
42   ["practice", "AcceptabilityJudgment", (s: "The car drove like a dream.")],
43   ["practice", "message", {
44     transfer: "keypress",
45     html: ["div",
46       ["p", "How was that? Many people rate that sentence pretty good."]
47     ]
48   }],
49   ["practice", "message", {
50     transfer: "keypress",
51     html: ["div",
52       ["p", "Let's try another one."]
53     ]
54   }],
55   ["practice", "AcceptabilityJudgment", (s: "The cat ever has eaten cheese the.")],
56   ["practice", "message", {
57     transfer: "keypress",
58     html: ["div",
59       ["p", "That sentence usually receives pretty poor ratings."],
60       ["p", "Ok! That's it. It's time to begin."]
61     ]
62   }],
63
64   ["sep", "separator", ( )],
65
66   ["mpi.gram.1", "AcceptabilityJudgment", (s: "No duck that the goose chased has ever returned to our pond.")],
67   ["mpi.illus.1", "AcceptabilityJudgment", (s: "The duck that no goose chased has ever returned to our pond.")],
68   ["mpi.ungram.1", "AcceptabilityJudgment", (s: "The duck that the goose chased has ever returned to our pond.")],
69
70   ["mpi.gram.2", "AcceptabilityJudgment", (s: "No bill that the Democratic senators supported has ever become law.")],
71   ["mpi.illus.2", "AcceptabilityJudgment", (s: "The bill that no Democratic senators supported has ever become law.")],
72   ["mpi.ungram.2", "AcceptabilityJudgment", (s: "The bill that the Democratic senators supported has ever become law.")],
73
74   ["filler-BAD-01", "AcceptabilityJudgment", (s: "The bored schoolchild kicked dog the without any apparent remorse.")],
75   ["filler-BAD-02", "AcceptabilityJudgment", (s: "Pauline left her suester the train on the way home.")],
76   ["filler-GOOD-01", "AcceptabilityJudgment", (s: "Margaret spent all night working at the cannerly and was tired.")],
77   ["filler-GOOD-02", "AcceptabilityJudgment", (s: "The way to happiness is never straightforward or obvious.")],
78
79   ["filler-ATTENTIONCHECK-01", "AcceptabilityJudgment", (s: "Please select 4 for this sentence; do not rate it like other sentences.")],
80
81 ];
```

Settings

Sequence

Body

Forms

Practice Trials

Critical Trials

Filler Trials

Discard changes

Save changes

Save and close

19 / 78

Our first experiment

Study: We are interested in how people recover from **garden-path sentences**.

"While Anna dressed the kitten paid attention."

... *[_{VP} dressed the kitten], ...

... ✓[_{VP} dressed], the kitten ...

Hypothesis: Verbs that are frequently **transitive** make recovery more difficult, compared to verbs that are frequently **intransitive**.

(transitive-biased) - "While Anna **trained** the kitten paid attention."

(intransitive-biased) - "While Anna **dressed** the kitten paid attention."

Prediction: Lower **acceptability ratings** in the transitive-biased condition (**gp.trans**) than in the intransitive-biased condition (**gp.intrans**).

Note: this is a *within-participant* design!

Trial Syntax

For each trial in our acceptability judgment experiment, we write this code:

`[["Trial name", Set #], "Trial Type", {s: "Sentence"}]`

This is a list (array) of three elements (clearer with spacing):

```
[  
  ["Trial name", Set # ],  
  "Trial Type",  
  {s: "Sentence"}  
]
```

```
[ ["Trial name", Set # ],  
  "Trial Type",  
  {s: "Sentence"} ]
```

We have one big bracket which contains **three elements**:

1. Another list, consisting of the *name of the trial* and *set number*
2. A string specifying the *type of the trial* (called **Controllers**)
3. A curly bracket (*braces*), which has "s" and the *sentence* separated by a colon

Translating the design to code

Example 1:

For the gp.trans condition, the first stimuli in our acceptability judgment experiment is the sentence "While Anna trained the kitten paid attention".

```
[  
  [ "gp.trans", 1 ],  
  "AcceptabilityJudgment",  
  {s: "While Anna trained the kitten paid attention."}  
]
```

Translating the design to code

Example 1:

For the **gp.trans condition**, the first stimuli in our acceptability judgment experiment is the sentence "While Anna trained the kitten paid attention".

```
[  
  [ "gp.trans", 1 ],  
  "AcceptabilityJudgment",  
  {s: "While Anna trained the kitten paid attention."}  
]
```

Translating the design to code

Example 1:

For the **gp.trans condition**, the **first stimuli** in our acceptability judgment experiment is the sentence "While Anna trained the kitten paid attention".

```
[  
  [ "gp.trans", 1 ],  
  "AcceptabilityJudgment",  
  {s: "While Anna trained the kitten paid attention."}  
]
```


Translating the design to code

Example 1:

For the **gp.trans condition**, the **first stimuli** in our **acceptability judgment experiment** is the sentence "While Anna trained the kitten paid attention".

```
[  
  [ "gp.trans", 1 ],  
  "AcceptabilityJudgment",  
  {s: "While Anna trained the kitten paid attention."}  
]
```

Translating the design to code

Example 1:

For the **gp.trans condition**, the **first stimuli** in our **acceptability judgment experiment** is the **sentence** "While Anna trained the kitten paid attention".

```
[  
  [ "gp.trans", 1 ],  
  "AcceptabilityJudgment",  
  {s: "While Anna trained the kitten paid attention."}  
]
```

Translating the design to code

Example 1:

For the **gp.trans condition**, the **first stimuli** in our **acceptability judgment experiment** is the **sentence** "While Anna trained the kitten paid attention".

```
[  
  [ "gp.trans", 1 ],  
  "AcceptabilityJudgment",  
  {s: "While Anna trained the kitten paid attention."}  
]
```

This can be put into a single line:

```
[["gp.trans",1], "AcceptabilityJudgment", {s: "While Anna trained the k-
```

Translating the design to code

Example 2:

For the **gp.intrans condition**, the **first stimuli** in our **acceptability judgment experiment** is the **sentence "While Anna dressed the kitten paid attention"**.

```
[  
  [ "gp.intrans", 1 ],  
  "AcceptabilityJudgment",  
  {s: "While Anna dressed the kitten paid attention."}  
]
```

This can be put into a single line:

```
[["gp.intrans",1], "AcceptabilityJudgment", {s: "While Anna dressed the
```

Practice

Item set #2:

(transitive) - "Since Dave improved the department was satisfied."

(intransitive) - "Since Dave worried the counselor devised a plan."

```
<code here>
```

Hover for answer

Putting together the stimuli

Wrap in `var items = []` and separate by a **comma**:

```
var item = [  
  
  //// Set #1  
  [{"gp.trans",1}, "AcceptabilityJudgment", {s: "While Anna trained the kitten paid attention."}],  
  [{"gp.intrans",1}, "AcceptabilityJudgment", {s: "While Anna dressed the kitten paid attention."}],  
  
  //// Set #2  
  [{"gp.trans",2}, "AcceptabilityJudgment", {s: "Since Dave improved the department was  
satisfied."}],  
  [{"gp.intrans",2}, "AcceptabilityJudgment", {s: "Since Dave worried the counselor devised a  
plan."}]  
]
```

Good scripting habits:

- Grouping item sets together and separating sets with new line
- Adding comments (starts with two or more slashes `//`)
- Saving often! (editing in IBEX not recommended)

Practice and Fillers

Practice Trials:

- Presented at the beginning, accompanied by instructions and feedback

Filler Trials:

- Mixed in with the critical trials

Both types of trials are invariant across conditions

This means that the first element of the big bracket can just be the *Trial Name*, without assigning it a *Set #*:

Practice	Filler-good	Filler-bad	Filler-catch
----------	-------------	------------	--------------

Practice #1: "The car drove like a dream"

```
["practice-1",  
"AcceptabilityJudgment",  
{s: "The car drove like a dream."}]
```

Practice and Fillers

Practice Trials:

- Presented at the beginning, accompanied by instructions and feedback

Filler Trials:

- Mixed in with the critical trials

Both types of trials are invariant across conditions

This means that the first element of the big bracket can just be the *Trial Name*, without assigning it a *Set #*:

Practice	Filler-good	Filler-bad	Filler-catch
----------	-------------	------------	--------------

Good Filler #1: "When Harry fell, the audience was shocked."

```
["filler-good-01",  
"AcceptabilityJudgment",  
{s: "When Harry fell, the audience was shocked."}]
```


Practice and Fillers

Practice Trials:

- Presented at the beginning, accompanied by instructions and feedback

Filler Trials:

- Mixed in with the critical trials

Both types of trials are invariant across conditions

This means that the first element of the big bracket can just be the *Trial Name*, without assigning it a *Set #*:

Practice	Filler-good	<u>Filler-bad</u>	Filler-catch
----------	-------------	-------------------	--------------

Bad Filler #1: "When Tyler sneezed the driver, he passed a tissue."

```
["filler-bad-01",  
"AcceptabilityJudgment",  
{s: "When Tyler sneezed the driver, he passed a tissue."}]
```

Practice and Fillers

Practice Trials:

- Presented at the beginning, accompanied by instructions and feedback

Filler Trials:

- Mixed in with the critical trials

Both types of trials are invariant across conditions

This means that the first element of the big bracket can just be the *Trial Name*, without assigning it a *Set #*:

Practice	Filler-good	Filler-bad	<u>Filler-catch</u>
----------	-------------	------------	---------------------

Catch Filler #1: "Please select 4 for this sentence."

```
["filler-catch-01",  
"AcceptabilityJudgment",  
{s: "Please select 4 for this sentence."}]
```

Putting together the Body

```
var items = [  
  
  //// Practice  
  ["practice-1", "AcceptabilityJudgment", {s: "The car drove like a dream."}],  
  
  // Critical Trials //  
  
  //// Set #1  
  [{"gp.trans",1}, "AcceptabilityJudgment", {s: "While Anna trained the kitten paid attention."}],  
  [{"gp.intrans",1}, "AcceptabilityJudgment", {s: "While Anna dressed the kitten paid attention."}],  
  
  //// Set #2  
  [{"gp.trans",2}, "AcceptabilityJudgment", {s: "Since Dave improved the department was  
satisfied."}],  
  [{"gp.intrans",2}, "AcceptabilityJudgment", {s: "Since Dave worried the counselor devised a  
plan."}],  
  
  //// Fillers (Good)  
  ["filler-good-01", "AcceptabilityJudgment", {s: "When Harry fell, the audience was shocked."}],  
  
  //// Fillers (Bad)  
  ["filler-bad-01", "AcceptabilityJudgment", {s: "When Tyler sneezed the driver, he passed a  
tissue."}],  
  
  //// Fillers (Catch)  
  ["filler-catch-01", "AcceptabilityJudgment", {s: "Please select 4 for this sentence."}]
```

Important: The ordering of the trials here is just for human readability. We haven't yet told the program what order to present them in!

Defining the Sequence

```
var items = [  
  
  //// Practice  
  ["practice-1", "AcceptabilityJudgment",  
   {s: "The car drove like a dream."}],  
  
  // Critical Trials //  
  
  //// Set #1  
  [{"gp.trans",1},  
   "AcceptabilityJudgment", {s: "While Anna  
   trained the kitten paid attention."}],  
  [{"gp.intrans",1},  
   "AcceptabilityJudgment", {s: "While Anna  
   dressed the kitten paid attention."}],  
  
  //// Set #2  
  [{"gp.trans",2},  
   "AcceptabilityJudgment", {s: "Since Dave  
   improved the department was satisfied."}],  
  [{"gp.intrans",2},  
   "AcceptabilityJudgment", {s: "Since Dave  
   worried the counselor devised a plan."}],  
  
  //// Fillers (Good)  
  ["filler-good-  
01", "AcceptabilityJudgment", {s: "When  
   Harry fell, the audience was shocked."}],
```

List the *names* of each trial in order:

```
"practice-1",  
"gp.trans",  
"gp.intrans",  
"gp.trans",  
"gp.intrans",  
"filler-good-01",  
"filler-bad-01",  
"filler-catch-01"
```

Defining the Sequence

```
var items = [  
    
  //// Practice  
  ["practice-1", "AcceptabilityJudgment",  
  {s: "The car drove like a dream."}],  
    
  // Critical Trials //  
    
  //// Set #1  
  [{"gp.trans",1},  
  "AcceptabilityJudgment", {s: "While Anna  
  trained the kitten paid attention."}],  
  [{"gp.intrans",1},  
  "AcceptabilityJudgment", {s: "While Anna  
  dressed the kitten paid attention."}],  
    
  //// Set #2  
  [{"gp.trans",2},  
  "AcceptabilityJudgment", {s: "Since Dave  
  improved the department was satisfied."}],  
  [{"gp.intrans",2},  
  "AcceptabilityJudgment", {s: "Since Dave  
  worried the counselor devised a plan."}],  
    
  //// Fillers (Good)  
  ["filler-good-  
  01","AcceptabilityJudgment", {s: "When  
  Harry fell, the audience was shocked."}],  
]
```

Wrap them in **seq()**:

```
seq(  
  "practice-1",  
  "gp.trans",  
  "gp.intrans",  
  "gp.trans",  
  "gp.intrans",  
  "filler-good-01",  
  "filler-bad-01",  
  "filler-catch-01"  
)
```

Defining the Sequence

```
var items = [  
  
  //// Practice  
  ["practice-1", "AcceptabilityJudgment",  
   {s: "The car drove like a dream."}],  
  
  // Critical Trials //  
  
  //// Set #1  
  [{"gp.trans",1},  
   "AcceptabilityJudgment", {s: "While Anna  
   trained the kitten paid attention."}],  
  [{"gp.intrans",1},  
   "AcceptabilityJudgment", {s: "While Anna  
   dressed the kitten paid attention."}],  
  
  //// Set #2  
  [{"gp.trans",2},  
   "AcceptabilityJudgment", {s: "Since Dave  
   improved the department was satisfied."}],  
  [{"gp.intrans",2},  
   "AcceptabilityJudgment", {s: "Since Dave  
   worried the counselor devised a plan."}],  
  
  //// Fillers (Good)  
  ["filler-good-  
01","AcceptabilityJudgment", {s: "When  
   Harry fell, the audience was shocked."}],
```

Assign to **shuffleSequence**:

```
var shuffleSequence = seq(  
  "practice-1",  
  "gp.trans",  
  "gp.intrans",  
  "gp.trans",  
  "gp.intrans",  
  "filler-good-01",  
  "filler-bad-01",  
  "filler-catch-01"  
)
```

Defining the Sequence

```
var items = [  
  
  //// Practice  
  ["practice-1", "AcceptabilityJudgment",  
   {s: "The car drove like a dream."}],  
  
  // Critical Trials //  
  
  //// Set #1  
  [{"gp.trans",1},  
   "AcceptabilityJudgment", {s: "While Anna  
   trained the kitten paid attention."}],  
  [{"gp.intrans",1},  
   "AcceptabilityJudgment", {s: "While Anna  
   dressed the kitten paid attention."}],  
  
  //// Set #2  
  [{"gp.trans",2},  
   "AcceptabilityJudgment", {s: "Since Dave  
   improved the department was satisfied."}],  
  [{"gp.intrans",2},  
   "AcceptabilityJudgment", {s: "Since Dave  
   worried the counselor devised a plan."}],  
  
  //// Fillers (Good)  
  ["filler-good-  
01", "AcceptabilityJudgment", {s: "When  
   Harry fell, the audience was shocked."}],
```

Assign to **shuffleSequence**:

```
var shuffleSequence = seq(  
  "practice-1",  
  "gp.trans",  
  "gp.intrans",  
  "gp.trans",  
  "gp.intrans",  
  "filler-good-01",  
  "filler-bad-01",  
  "filler-catch-01"  
)
```

The **shuffleSequence** variable handles the *order of presentation* of the **experiment materials** that are stored inside the **items** variable.

Defining the Sequence

```
var items = [  
  
  //// Practice  
  ["practice-1", "AcceptabilityJudgment",  
   {s: "The car drove like a dream."}],  
  
  // Critical Trials //  
  
  //// Set #1  
  [{"gp.trans",1},  
   "AcceptabilityJudgment", {s: "While Anna  
   trained the kitten paid attention."}],  
  [{"gp.intrans",1},  
   "AcceptabilityJudgment", {s: "While Anna  
   dressed the kitten paid attention."}],  
  
  //// Set #2  
  [{"gp.trans",2},  
   "AcceptabilityJudgment", {s: "Since Dave  
   improved the department was satisfied."}],  
  [{"gp.intrans",2},  
   "AcceptabilityJudgment", {s: "Since Dave  
   worried the counselor devised a plan."}],  
  
  //// Fillers (Good)  
  ["filler-good-  
01", "AcceptabilityJudgment", {s: "When  
   Harry fell, the audience was shocked."}],
```

Problems

```
var shuffleSequence = seq(  
  "practice-1",  
  "gp.trans",  
  "gp.intrans",  
  "gp.trans",  
  "gp.intrans",  
  "filler-good-01",  
  "filler-bad-01",  
  "filler-catch-01"  
)
```

1. A lot of typing ("-02", "-03", ...)

Defining the Sequence

```
var items = [  
  
  //// Practice  
  ["practice-1", "AcceptabilityJudgment",  
   {s: "The car drove like a dream."}],  
  
  // Critical Trials //  
  
  //// Set #1  
  [{"gp.trans",1},  
   "AcceptabilityJudgment", {s: "While Anna  
trained the kitten paid attention."}],  
  [{"gp.intrans",1},  
   "AcceptabilityJudgment", {s: "While Anna  
dressed the kitten paid attention."}],  
  
  //// Set #2  
  [{"gp.trans",2},  
   "AcceptabilityJudgment", {s: "Since Dave  
improved the department was satisfied."}],  
  [{"gp.intrans",2},  
   "AcceptabilityJudgment", {s: "Since Dave  
worried the counselor devised a plan."}],  
  
  //// Fillers (Good)  
  ["filler-good-  
01", "AcceptabilityJudgment", {s: "When  
Harry fell, the audience was shocked."}],
```

Problems

```
var shuffleSequence = seq(  
  "practice-1",  
  "gp.trans",  
  "gp.intrans",  
  "gp.trans",  
  "gp.intrans",  
  "filler-good-01",  
  "filler-bad-01",  
  "filler-catch-01"  
)
```

1. A lot of typing ("-02", "-03", ...)
2. Presentation order of some trials should be random

Defining the Sequence

```
var items = [  
  
  //// Practice  
  ["practice-1", "AcceptabilityJudgment",  
   {s: "The car drove like a dream."}],  
  
  // Critical Trials //  
  
  //// Set #1  
  [{"gp.trans",1},  
   "AcceptabilityJudgment", {s: "While Anna  
   trained the kitten paid attention."}],  
  [{"gp.intrans",1},  
   "AcceptabilityJudgment", {s: "While Anna  
   dressed the kitten paid attention."}],  
  
  //// Set #2  
  [{"gp.trans",2},  
   "AcceptabilityJudgment", {s: "Since Dave  
   improved the department was satisfied."}],  
  [{"gp.intrans",2},  
   "AcceptabilityJudgment", {s: "Since Dave  
   worried the counselor devised a plan."}],  
  
  //// Fillers (Good)  
  ["filler-good-  
01", "AcceptabilityJudgment", {s: "When  
   Harry fell, the audience was shocked."}],
```

Problems

```
var shuffleSequence = seq(  
  "practice-1",  
  "gp.trans",  
  "gp.intrans",  
  "gp.trans",  
  "gp.intrans",  
  "filler-good-01",  
  "filler-bad-01",  
  "filler-catch-01"  
)
```

1. A lot of typing ("-02", "-03", ...)
2. Presentation order of some trials should be random
3. How do we counterbalance critical trials?

1. Sequence: multiple selection

To save us from writing repetitive code, we use `startsWith()`

```
var shuffleSequence = seq(  
  "practice-1",  
  "gp.trans",  
  "gp.intrans",  
  "gp.trans",  
  "gp.intrans",  
  "filler-good-01",  
  "filler-bad-01",  
  "filler-catch-01"  
)
```

```
var shuffleSequence = seq(  
  startsWith("practice"),  
  startsWith("gp"),  
  startsWith("filler")  
)
```

The function `startsWith()` matches all names that starts with the given string.

2. Sequence: randomization

To mix critical and filler trials in random order, we use `rshuffle()`

```
var shuffleSequence = seq(  
  startsWith("practice"),  
  startsWith("gp"),  
  startsWith("filler")  
)
```

```
var shuffleSequence = seq(  
  startsWith("practice"),  
  rshuffle(  
    startsWith("gp"),  
    startsWith("filler")  
  )  
)
```

By wrapping both the critical trials (*gp...*) and the filler trials (*filler...*) in `rshuffle()`, they are mixed together and presented in random order.

We can also write this out more compactly:

```
var shuffleSequence = seq(  
  startsWith("practice"),  
  rshuffle(startsWith("gp"), startsWith("filler"))  
)
```

3. Sequence: counterbalancing

The **set number** in our critical trials automatically handles **counterbalancing**:

`[["gp.trans", 1], ...], [["gp.intrans", 1], ...], [["gp.trans", 2], ...], [["gp.intrans", 2], ...]`



`[“gp.trans”, 1]`

`[“gp.intrans”, 2]`



`[“gp.intrans”, 1]`

`[“gp.trans”, 2]`



`[“gp.trans”, 1]`

`[“gp.intrans”, 2]`



`[“gp.intrans”, 1]`

`[“gp.trans”, 2]`

We just need to add a **counter** inside **items** to track group assignment:

```
[“setcounter”, “__SetCounter__”, { }]
```

3. Sequence: counterbalancing

To use the counter, you need to modify both `items` and `shuffleSequence`:

```
var items = [  
  ...  
  ["setcounter", "__SetCounter__", { }], // The counter is defined  
  ...  
]  
  
var shuffleSequence = seq(  
  "setcounter", // The counter is incremented at the start  
  ...  
)
```

Note: Sometimes you want to place "setcounter" in the *middle* of the experiment

```
var shuffleSequence = seq(  
  "intro"  
  "consent",  
  "setcounter",  
  ...  
)
```

Body and Sequence together

```
// Presentation Order //
var shuffleSequence = seq(
  "setcounter",
  startsWith("practice"),
  rshuffle(startsWith("gp"), startsWith("filler"))
)

// Experiment Materials //
var items = [

  //// Counter
  ["setcounter", "__SetCounter__", { }],

  //// Practice
  ["practice-1", "AcceptabilityJudgment", {s: "The car drove like a dream."}],

  // Critical Trials //

  //// Set #1
  [["gp.trans",1], "AcceptabilityJudgment", {s: "While Anna trained the kitten paid attention."}],
  [["gp.intrans",1], "AcceptabilityJudgment", {s: "While Anna dressed the kitten paid attention."}],

  //// Set #2
  [["gp.trans",2], "AcceptabilityJudgment", {s: "Since Dave improved the department was
satisfied."}],
  [["gp.intrans",2], "AcceptabilityJudgment", {s: "Since Dave worried the counselor devised a
```

Just need one more step: **Settings**

Settings (Basic)

Consist of miscellaneous options that we can put at the top of the script.

At the very least, we want to do two things:

1. Generate unique **participant IDs**
2. Specify the parameters for the **method design**

Settings (Basic)

Consist of miscellaneous options that we can put at the top of the script.

At the very least, we want to do two things:

1. Generate unique **participant IDs** (`randomCode`)
2. Specify the parameters for the **method design** (`defaults`)

```
// Defaults and other settings //
```

```
//// Generates random number assigned to participants (Participant ID)
var randomCode = Math.random().toString(36).substr(2,9)
```

```
//// Override default settings for controllers (parameters go inside the curly braces { })
var defaults = [
  "AcceptabilityJudgment", {
    as: ["1", "2", "3", "4", "5", "6", "7"],
    presentAsScale: true,
    instructions: "Use number keys or click boxes to answer.",
    leftComment: "(Bad)",
    rightComment: "(Good)"
  }
]
```

More details in the **AcceptabilityJudgment** section of the [documentation](#).

The defaults variable

The specifications in `defaults` set the design of the trials:

```
var defaults = [  
  "AcceptabilityJudgment", {  
    as: ["1", "2", "3", "4", "5", "6", "7"],  
    presentAsScale: true,  
    instructions: "Use number keys or click boxes to answer.",  
    leftComment: "(Bad)",  
    rightComment: "(Good)"  
  }  
]
```

While Anna trained the kitten paid attention.

(Bad) (Good)

Use number keys or click boxes to answer.

Another defaults example

Suppose you'd like to show participants *multiple sentences* but have them only rate the acceptability of **one** of the sentences.

Code	Output
------	--------

```
var defaults = [  
  "AcceptabilityJudgment", {  
    ...  
    instructions: "Rate how natural Speaker B's response sounds.",  
    ...  
  }]  
}]
```

```
[["ConditionA", 1],  
 "AcceptabilityJudgment",  
 {s: ["div",  
     ["p", "Speaker A: Who left this sandwich on the table?"]  
     ["p", "Speaker B: Fred did."]  
   ]}]
```

Note: You can show multiple lines of text using **html** tags like "p" and "div" - more on that later

Another defaults example

Suppose you'd like to show participants *multiple sentences* but have them only rate the acceptability of **one** of the sentences.

Code

Output

Speaker A: Who left this sandwich on the table?

Speaker B: Fred did.

(Bad)

1

2

3

4

5

6

7

(Good)

Rate how natural Speaker B's response sounds.

Settings (Miscellaneous)

You can also change other options, such as showing a message at the end:

```
var completionMessage
```

```
//// A message to show to participants at completion (useful for confir  
var completionMessage = "Thank you for your participation. Your particip
```

And whether to show a progress bar:

```
var showProgressBar
```

```
//// Show a progress bar at the top? (true/false)  
var showProgressBar = false
```

You can learn more about these various elements in the **Miscellaneous options** section of the [documentation](#).

A minimal experiment

We now have a minimally working experiment!

```
// Defaults and other settings //
```

```
//// Generates random number assigned to participants (Participant ID)
var randomCode = Math.random().toString(36).substr(2,9)
//// A message to show to participants at completion (useful for confirmation, raffle entry, etc.)
var completionMessage = "Thank you for your participation. Your participation code is: " +
randomCode

//// Show a progress bar at the top? (true/false)
var showProgressBar = false

//// Override default settings for controllers (parameters go inside the curly braces { })
var defaults = [
  "AcceptabilityJudgment", {
    as: ["1", "2", "3", "4", "5", "6", "7"],
    presentAsScale: true,
    instructions: "Use number keys or click boxes to answer.",
    leftComment: "(Bad)",
    rightComment: "(Good)"
  }
]

// Presentation Order //

var shuffleSequence = seq(
  "setcounter",
```

Interim Summary #1

What we've covered:

- We use a special syntax to create stimuli
- We store all the materials for our experiment inside `items`
- We specify the order of presentation inside `shuffleSequence`
- We set various options at the top of the script, such as defaults for the experiment *method* and the assignment of *participant ID*

A few more things to know:

- How can we add *plain text*?
 - Introduction page, consent form, directions, etc.
- How can we extend this workflow for *other experimental designs*?
 - Self-paced reading, comprehension tasks, etc.

The "Message" controller

The **"Message"** controller shows text on a new page.

It is a list of 3 elements, similar to the "AcceptabilityJudgement" items:

`["Trial name", "Message", {html: text}]`

- ***Trial name*** is used to reference the trial in sequencing, as seen earlier
- **"Message"** tells IBEX that this trial just shows text on a new screen
- Inside of the curly braces **{}** we can add text in the **html** parameter:

```
["intro", "Message", {html: ["p", "Welcome to the experiment!"]}]
```

Notes on **html**:

The code `["p", "<your text here>"]` prints a single paragraph of text.

The "p" is called an **HTML tag** and there are many others (most common: "div", "strong", "em"), but usually these don't get very complicated.

Message examples

1-paragraph

n-paragraphs

consent

keypress

separator

A message composed of a single paragraph:

```
["intro", "Message", {html: ["p", "Welcome to the experiment!"]}]
```

Welcome to the experiment!

→ [Click here to continue.](#)

Message examples

1-paragraph

n-paragraphs

consent

keypress

separator

A message composed of multiple paragraphs must be combined inside a "div":

```
["intro", "Message", {html:  
  ["div",  
    ["p", "Welcome to the experiment!"],  
    ["p", "Here's another paragraph."],  
    ["p", "These paragraphs are all wrapped inside \"div\"."]  
  ]  
}]
```

Welcome to the experiment!

Here's another paragraph.

These paragraphs are all wrapped inside "div".

→ [Click here to continue.](#)

Note: You can **escape** special characters like quotes " with a backslash \

Message examples

1-paragraph

n-paragraphs

consent

keypress

separator

Ask for consent with a set of **consent...** parameters

```
[ "consent", "Message", {  
  html: ["p", "Do you consent?"],  
  consentRequired: true,  
  consentMessage: "I consent."  
}]
```

Do you consent?

☒ I consent.

[→ Click here to continue.](#)

Message examples

1-paragraph

n-paragraphs

consent

keypress

separator

Use the **transfer** argument to specify how the participant can move on.

Setting **transfer** to **"keypress"** removes the default **"Click here to continue."** message and allows participants to proceed with the press of any key.

```
["move_on", "Message", {  
  html: ["div",  
    ["p", "The option for \"transfer\" is \"keypress\""],  
    ["em", "Press any key to continue."]  
  ],  
  transfer: "keypress"  
}]
```

The option for "transfer" is "keypress"

Press any key to continue.

Message examples

1-paragraph

n-paragraphs

consent

keypress

separator

You might want to insert a page that separates the trials:

```
["sep", "Message", {  
  html: ["em", "Press any key to continue."],  
  transfer: "keypress"  
}]
```

Press any key to continue.

You can do so using `sepWith()` in `shuffleSequence`:

```
var shuffleSequence = seq(  
  "practice",  
  sepWith("sep", rshuffle(startsWith("gp"), startsWith("filler")))  
)
```

Putting everything together

Here's a complete experiment with several **Message** controllers added.

```
// Defaults and other settings //
```

```
//// Generates random number assigned to participants (Participant ID)
var randomCode = Math.random().toString(36).substr(2,9)
//// A message to show to participants at completion (useful for confirmation, raffle entry, etc.)
var completionMessage = "Thank you for your participation. Your participation code is: " +
randomCode

//// Show a progress bar at the top? (true/false)
var showProgressBar = false

//// Override default settings for controllers (parameters go inside the curly braces { })
var defaults = [
  "AcceptabilityJudgment", {
    as: ["1", "2", "3", "4", "5", "6", "7"],
    presentAsScale: true,
    instructions: "Use number keys or click boxes to answer.",
    leftComment: "(Bad)",
    rightComment: "(Good)"
  }
]

// Presentation Order //
```

```
var shuffleSequence = seq(
  "intro",
  "consent",
```

Getting the experiment up

So we have a new script, but how do we host the experiment?

1. Go to the IBEX website and log in.
2. Click on your experiment (or create one if you haven't already).
3. Click **edit** next to the *example_data.js* file in the **data_includes** section.
4. Delete its contents and copy paste your new code.
5. Click on the link at the top of the page.

/ibexexps/skku_ibex/workshop_acceptabilityJudgment/experiment.html

The URL shown in your browser is the link to your experiment!

 spellout.net/ibexexps/skku_ibex/workshop_acceptabilityJudgment/experiment.html

https://spellout.net/ibexexps/skku_ibex/workshop_minimal/experiment.html

A different experiment

Suppose that after a *pilot experiment*, we find acceptability judgments to be inappropriate for answering our research question.

We want a *finer-grained measure* of recovery difficulty, so we'd like to change the experiment to **self-paced reading** and look at differences in *reading time*.

Given our existing template, we take the following steps:

1. Go to the documentation and find a Controller for self-paced reading.
2. Specify the design of that controller in the `defaults` variable.
3. Change our trials in `items` from "**acceptabilityJudgment**" to that Controller.
4. Make changes to the text of the "**Messages**" items (e.g., directions).

Let's go look at the documentation!

"DashedSentence" Controller

The "**DashedSentence**" Controller creates self-paced reading trials.

We first re-write `defaults` to specify appropriate settings for "**DashedSentence**".

```
var defaults = [  
  "DashedSentence", {  
    mode: "self-paced reading",  
    display: "dashed"  
  }]  
]
```

Then, we replace "**acceptabilityJudgment**" with "**DashedSentence**" in `items`.

```
var items = [  
  ...  
  ["gp.trans",1], "DashedSentence", {s: "While Anna trained the kitten  
  ["gp.intrans",1], "DashedSentence", {s: "While Anna dressed the kitten  
  ["gp.trans",2], "DashedSentence", {s: "Since Dave improved the depart  
  ["gp.intrans",2], "DashedSentence", {s: "Since Dave worried the couns  
  ...  
]
```

Our second experiment

Finally, after re-writing some of the "**Message**" items, we have a new experiment!

```
// Defaults and other settings //
```

```
//// Generates random number assigned to participants (Participant ID)
var randomCode = Math.random().toString(36).substr(2,9)
//// A message to show to participants at completion (useful for confirmation, raffle entry, etc.)
var completionMessage = "Thank you for your participation. Your participation code is: " +
randomCode

//// Show a progress bar at the top? (true/false)
var showProgressBar = false

//// Override default settings for controllers (parameters go inside the curly braces { })
var defaults = [
  "DashedSentence", {
    mode: "self-paced reading",
    display: "dashed"
  }]

// Presentation Order //
```

```
var shuffleSequence = seq(
  "intro",
  "consent",
  "directions",
  startsWith("practice"),
  "setcounter",
```

Question and Form Controllers

Yes/No

Forced-Choice-1

Forced-Choice-2

Free-Response

You can use the **Question** controller to ask **Yes/No** comprehension questions:

```
[["YesNo_example",1],  
 "Question",  
 {q: "Was the kitten trained?", as: ["Yes", "No"]}]]
```

Was the kitten trained?

1. Yes

2. No

Question and Form Controllers

Yes/No

Forced-Choice-1

Forced-Choice-2

Free-Response

The **as** parameter sets the **answer choices** presented to participants.

```
[["FC1_example",1], "Question", {  
  instructions: "Choose the more natural sentence.",  
  as: ["Who did you see that ate bread?",  
       "What did you see the girl who ate?"]}]]
```

1. Who did you see that ate bread?
2. What did you see the girl who ate?

Choose the more natural sentence.

Question and Form Controllers

Yes/No

Forced-Choice-1

Forced-Choice-2

Free-Response

You can ask for **continuations** by modifying the **q** parameter.

```
[["FC2_example",1], "Question", {  
  q: "While Anna dressed the baby _____",  
  instructions: "Choose the more natural continuation.",  
  as: ["started to cry.", "he started to cry."]}]
```

While Anna dressed the baby _____

1. started to cry.
2. he started to cry.

Choose the more natural continuation for this sentence.

Question and Form Controllers

Yes/No

Forced-Choice-1

Forced-Choice-2

Free-Response

Use **Form** controller with the "**textarea**" HTML tag to collect a **free response**:

```
[["FR_example",1],  
 "Form", {html: ["div",  
   ["em", "Fill out a continuation for the sentence fragment:"],  
   ["p", "While Anna dressed the baby _____"],  
   ["textarea"]  
 ]}]
```

Fill out a continuation for the following sentence fragment:

While Anna dressed the baby _____

[→ Click here to continue](#)

3. Analysis of the results

Where to find the data


The data collected in the experiment can be found on the experiment page, under the **results** section.

```
results (upload a file to this directory | refresh)
raw_results (delete | rename | upload new version | edit)
results (delete | rename | upload new version | edit)
```

The section comprises of two files, of which *results* is the better formatted one.

The *results* file

results is a **csv** file (**c**omma **s**eparated **v**alues), meaning that each line contains a set of values that are separated by a comma.



```
1 #
2 # Results on Saturday January 02 2021 12:20:24 UTC.
3 # USER AGENT: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/87.0.4280.88 Safari/537.36
4 # Design number was non-random = 1
5 #
6 # Columns below this comment are as follows:
7 # 1. Time results were received.
8 # 2. MD5 hash of participant's IP address.
9 # 3. Controller name.
10 # 4. Item number.
11 # 5. Element number.
12 # 6. Type.
13 # 7. Group.
14 # 8. Word number.
15 # 9. Word.
16 # 10. Reading time.
17 # 11. Newline?
18 # 12. Sentence (or sentence MD5).
19 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,4,0,practice-1,NULL,1,The,143,False,The car drove like a dream.
20 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,4,0,practice-1,NULL,2,car,121,False,The car drove like a dream.
21 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,4,0,practice-1,NULL,3,drove,127,False,The car drove like a dream.
22 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,4,0,practice-1,NULL,4,like,123,False,The car drove like a dream.
23 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,4,0,practice-1,NULL,5,a,115,False,The car drove like a dream.
24 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,4,0,practice-1,NULL,6,dream,109,False,The car drove like a dream.
25 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,6,0,practice-2,NULL,1,The,242,False,The cat ever has eaten cheese the.
26 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,6,0,practice-2,NULL,2,cat,177,False,The cat ever has eaten cheese the.
27 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,6,0,practice-2,NULL,3,ever,142,False,The cat ever has eaten cheese the.
28 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,6,0,practice-2,NULL,4,has,121,False,The cat ever has eaten cheese the.
29 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,6,0,practice-2,NULL,5,eaten,130,False,The cat ever has eaten cheese the.
30 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,6,0,practice-2,NULL,6,cheese,118,False,The cat ever has eaten cheese the.
31 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,6,0,practice-2,NULL,7,the,273,False,The cat ever has eaten cheese the.
32 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,16,0,filler-catch-01,NULL,1,This,254,False,This sentence is an attention c
33 1609590025,a4da1f176adfea0b761238da725fd6e8,DashedSentence,16,0,filler-catch-01,NULL,2,sentence,124,False,This sentence is an attenti
34
```

The lines that start with a pound symbol "#" are **comments** that include *metadata*.

They tell us what **variables** each comma-separated values correspond to.

The variables

All IBEX experiments return these **7** variables:

1. **Time**
2. **Participant ID**
3. **Controller Name**
4. **Item number**
5. **Element number**
6. **Type**
7. **Group**

The variables

Generally, we only care about **4** of these:

1. Time
2. **Participant ID**: A unique ID for each participant.
3. **Controller Name**: The controller that the values are from.
4. Item number
5. Element number
6. **Type**: The name of the trial.
7. **Group**: The item group number.

The last two variables uniquely identify each trial created in **items**:

```
[["Type", Group], "Trial Type", {s: "Sentence"}]
```

```
[["gp.trans", 1], "DashedSentence", {s: "..."}]
```

The variables

Depending on the experiment, IBEX returns other variables specific to the design.

For self-paced reading with "**DashedSentence**", we get **5** more variables:

1. **Word number** - The index of the word in the sentence.
2. **Word** - The text of that word.
3. **Reading time** - Reading time for that word.
4. **Newline?** - 0 or 1 indicating whether there was a line break.
5. **Sentence** - The text of the sentence.

These are also outlined in the [documentation](#) for "**DashedSentence**", so you know what variables to expect beforehand.


For an actual analysis of the results, we need the results to be imported somewhere as a **data frame** (where every value is a cell and each variable forms a column).

Importing - Excel

Steps for importing the data into Excel:

1. Copy the text of the *results* file from IBEX
2. Paste into the first column of an Excel spreadsheet
3. Highlight that column and click **Data** tab -> **Filter**
4. Click on the dropdown arrow that appears at the top cell
5. Click **Text Filters** -> **Begins With...** and type in "#"
6. Go to **Home** tab -> **Find & Select**, check "Visible cells only", and click OK
7. Right click on any part of the sheet and select **Delete Row**
8. Click the first column again and go to **Data** tab -> **Text to Columns**
9. Check "Delimited", "Comma", then "General" for each prompt
10. Add an empty row at the top and manually type in the column names from the comments of the original *results* file

Importing - Excel



Complex results

Some Controllers return more than 1 line of results, making thing complicated.

For example, each **AcceptabilityJudgment** trial adds two lines to *results*:

```
results
-
6 # The lines below this comment are in groups of 2.
7 # The formats of the lines in each of these groups are as follows:
8 #
9 # Line 1:
10 # Col. 1: Time results were received.
11 # Col. 2: MD5 hash of participant's IP address.
12 # Col. 3: Controller name.
13 # Col. 4: Item number.
14 # Col. 5: Element number.
15 # Col. 6: Type.
16 # Col. 7: Group.
17 # Col. 8: Sentence (or sentence MD5).
18 # Line 2:
19 # Col. 1: Time results were received.
20 # Col. 2: MD5 hash of participant's IP address.
21 # Col. 3: Controller name.
22 # Col. 4: Item number.
23 # Col. 5: Element number.
24 # Col. 6: Type.
25 # Col. 7: Group.
26 # Col. 8: Question (NULL if none).
27 # Col. 9: Answer.
28 # Col. 10: Whether or not answer was correct (NULL if N/A).
29 # Col. 11: Time taken to answer.
30 1609648766,a4da1f176adfea0b761238da725fd6e8,AcceptabilityJudgment,4,0,practice-1,NULL,The car drove like a dream.
31 1609648766,a4da1f176adfea0b761238da725fd6e8,AcceptabilityJudgment,4,0,practice-1,NULL,NULL,5,NULL,1920
32 1609648766,a4da1f176adfea0b761238da725fd6e8,AcceptabilityJudgment,6,0,practice-2,NULL,The cat ever has eaten cheese the.
33 1609648766,a4da1f176adfea0b761238da725fd6e8,AcceptabilityJudgment,6,0,practice-2,NULL,NULL,4,NULL,513
34 1609648766,a4da1f176adfea0b761238da725fd6e8,AcceptabilityJudgment,14,0,filler-good-01,NULL,When Harry fell%2C the audience was shocked.
35 1609648766,a4da1f176adfea0b761238da725fd6e8,AcceptabilityJudgment,14,0,filler-good-01,NULL,NULL,4,NULL,252
36 1609648766,a4da1f176adfea0b761238da725fd6e8,AcceptabilityJudgment,10,0,gp.trans,1,While Anna trained the kitten paid attention.
37 1609648766,a4da1f176adfea0b761238da725fd6e8,AcceptabilityJudgment,10,0,gp.trans,1,NULL,4,NULL,272
38 1609648766,a4da1f176adfea0b761238da725fd6e8,AcceptabilityJudgment,15,0,filler-bad-01,NULL,When Tyler sneezed the driver%2C he passed a tissue.
39 1609648766,a4da1f176adfea0b761238da725fd6e8,AcceptabilityJudgment,15,0,filler-bad-01,NULL,NULL,4,NULL,284
40 1609648766,a4da1f176adfea0b761238da725fd6e8,AcceptabilityJudgment,13,0,gp.intrans,2,Since Dave worried the counselor devised a plan.
41 1609648766,a4da1f176adfea0b761238da725fd6e8,AcceptabilityJudgment,13,0,gp.intrans,2,NULL,4,NULL,306
42 1609648766,a4da1f176adfea0b761238da725fd6e8,AcceptabilityJudgment,16,0,filler-catch-01,NULL,Please select 4 for this sentence.
43 1609648766,a4da1f176adfea0b761238da725fd6e8,AcceptabilityJudgment,16,0,filler-catch-01,NULL,NULL,4,NULL,326
```

In cases like these, using a **processing script (R/Python)** is recommended

Importing - R

Steps for importing into R:

1. Download the *results* file from IBEX
2. Open it with the `read_ibex()` function from this [read_ibex.R](#) script

DashedSentence	AcceptabilityJudgment
----------------	-----------------------

```
source("read_ibex.R")
results <- read_ibex("SPR_results.txt")
```

```
##      Controller name      Type Group Word number      Word Reading time
## 92   DashedSentence      gp.intrans      2           8    plan.         261
## 75   DashedSentence      gp.trans       1           5   kitten         277
## 95   DashedSentence filler-bad-01  NULL           3 sneezed         339
##                                     Sentence (or sentence MD5)
## 92      Since Dave worried the counselor devised a plan.
## 75      While Anna trained the kitten paid attention.
## 95 When Tyler sneezed the driver%2C he passed a tissue.
```


Importing - R

Steps for importing into R:

1. Download the *results* file from IBEX
2. Open it with the `read_ibex()` function from this [read_ibex.R](#) script

DashedSentence	AcceptabilityJudgment
----------------	-----------------------

```
source("read_ibex.R")
results <- read_ibex("Acceptability_results.txt")
```

```
##           Controller name           Type Group
## 16 AcceptabilityJudgment      gp.intrans      2
##  5 AcceptabilityJudgment filler-catch-01  NULL
##  2 AcceptabilityJudgment      gp.intrans      2
##
##           Sentence (or sentence MD5) Answer
## 16 Since Dave worried the counselor devised a plan.      7
##  5           Please select 4 for this sentence.      4
##  2 Since Dave worried the counselor devised a plan.      4
```

Break

Exercise



Task

The experiment script incomplete.js has some missing pieces.

```
////////////////////
//// Exercise ////
//
// There are a total of EIGHT tasks for you to complete in this script.
// The instructions for each task are written out as comments.
// Some parts of the task are completed for you and your job is to fill in the blanks _____.
//
// Make sure to consult the IBEX manual! -
https://github.com/addrummond/ibex/blob/master/docs/manual.md
//
////////////////////

// Task #1: Send a completion message that says "Thank you for your participation!"
var _____ = "_____"

var showProgressBar = false

var defaults = [
  "AcceptabilityJudgment", {
    as: _____, // Task #2: Make the acceptability judgment scale from 1-5
    presentAsScale: true,
    instructions: "Use number keys or click boxes to answer.",
    leftComment: "(Bad)",
    rightComment: "(Good)"
  }
]
```

Task

Directions:

1. Download [incomplete.js](#)
2. Create a new experiment on your ibex account called "WorkshopExercise" and replace the contents of *example_data.js* in the **data_includes** section with *incomplete.js*.
3. Click **edit** and follow the directions in the script to fill in the blanks.
4. Complete as many of tasks as possible (**8 total**).

If you finish, save the edits and click on your experiment link at the top of the page. Check to see that your experiment looks similar to this [complete version](#).

Make sure to use the IBEX documentation!

<https://github.com/addrummond/ibex/blob/master/docs/manual.md>

Resources

Materials from this presentation are on Google Drive.

More resources from the community:

- The official IBEX documentation.
- The official IBEX google group to ask questions.

UPDATE (01/01/2021)

There is a **new version of IBEX** at a different link: <https://ibex.spellout.net>



Alex Drummond
to ibexperiments

Jan 1

Happy new year!

I'm announcing a complete rewrite of the Ibex Farm deployed at

<https://ibex.spellout.net>

The user-facing changes are conservative and incremental, but there are some significant improvements and new features. You can find an exhaustive list of these at

<https://gist.github.com/addrummond/b345d3d4f23436838e52afbe880ebbd9>. The first section should tell you

Resources


Materials from this presentation are on [Google Drive](#).

More resources from the community:

- The official [IBEX documentation](#).
- The official [IBEX google group](#) to ask questions.

UPDATE (01/01/2021)

New feature: results can be downloaded as a spreadsheet ([full list of changes](#)).

 **workshop_DashedSentence**

PUBLIC [make private](#)

Ibex version: 0.3.9 (imported from original Ibex Farm)
The counter is set to 2.

● 1 set of results.

Results for workshop_DashedSentence

This experiment has 1 set of results.

- [Results as CSV spreadsheet](#)
- [Results as Excel .xlsx spreadsheet](#)
- [Results in original Ibex format \(with no column name comments\)](#)
- [Results in original Ibex format \(with per-line column name comments\)](#)
- [Raw JSON results](#)

Resources

Materials from this presentation are on [Google Drive](#).

More resources from the community:

- The official [IBEX documentation](#).
- The official [IBEX google group](#) to ask questions.

Other platforms

- PCIBex (Penn Controller for IBEX): <https://www.pcibex.net>
- PsychoPy: <https://www.psychopy.org>
- _magpie (minimal architecture for the generation of portable interactive experiments): <https://magpie-ea.github.io/magpie-site>

Resources

Materials from this presentation are on [Google Drive](#).

More resources from the community:

- The official [IBEX documentation](#).
- The official [IBEX google group](#) to ask questions.

Platforms to recruit participants for your IBEX experiment

- MTurk (Amazon Mechanical Turk): <https://www.mturk.com>
- Prolific <https://www.prolific.co>

Acknowledgments

- Many thanks to June Choe for assistance with the slides (esp. interactive components)
- Thanks to Brian Dillon (University of Massachusetts Amherst) for permission to use materials from the LSA Minicourse "Doing Experiments for Linguists" (Brian Dillon & Rodica Ivan)