

FLUTTER DEBUG LAB

Debugging & DevTools — Technical Report

Flutter SDK: 3.41.7 • Dart SDK: 3.11.5
Package: debugging_and_devtools v1.0.0
Report Date: June 11, 2026

Module	Focus Area
Logging Demo	print() vs debugPrint() behavior
setState() Bug	Missing rebuild identification
Layout Overflow	RenderFlex overflow & fixes
Network Errors	Dio API debugging & error types
Memory Leaks	Controller disposal & heap profiling
Performance Demo	Jank detection & optimization
Crash Test	Runtime crash handling
DevTools Guide	Complete DevTools reference

1. Project Overview

Flutter Debug Lab is a comprehensive, interactive Flutter application designed to teach and demonstrate real-world debugging techniques using Flutter DevTools. The app presents eight hands-on modules, each exposing a specific class of bug or performance issue and guiding the developer through diagnosing and resolving it using the appropriate DevTools panel.

The project targets Flutter SDK 3.41.7 (Dart 3.11.5) and is structured as a dark-themed mobile application with a developer-centric aesthetic — monospace typography, color-coded severity indicators, and live interactive demos.

1.1 Project Structure

App Name	Flutter Debug Lab
Package	debugging_and_devtools
Version	1.0.0+1
Flutter SDK	3.41.7
Dart SDK	3.11.5
Min SDK (Android)	Derived from flutter defaults
Theme	Dark (custom AppTheme)
State Management	Built-in setState() / StatefulWidget
Networking	Dio ^5.9.0
Crash Reporting	Firebase Crashlytics ^5.0.2

1.2 Dependencies

Package	Version	Purpose
dio	^5.9.0	HTTP networking client with interceptors and timeout support
firebase_core	^4.1.1	Firebase SDK initialization required for Crashlytics
firebase_crashlytics	^5.0.2	Crash reporting and non-fatal error logging to Firebase
cupertino_icons	^1.0.8	iOS-style icon set for Material widgets
flutter_lints	^6.0.0	Recommended lint rules for code quality (dev dependency)

1.3 Application Architecture

lib/main.dart	Entry point — MaterialApp with custom dark theme and system UI overlay
---------------	--

lib/theme/app_theme.dart	Centralized design tokens: AppColors, AppTheme.dark
lib/screens/	8 feature screens, each self-contained StatefulWidget demo
lib/services/api_service.dart	Dio-based API service with success, broken, and slow endpoints
lib/widgets/demo_card.dart	Reusable navigation card for the home screen grid
lib/widgets/shared_widgets.dart	Common UI components: InfoCard, SectionCard, DebugButton, StatCard

2. Debugging Modules — Core Debugging

2.1 Logging Demo

The LoggingScreen demonstrates the practical difference between Flutter's two primary logging primitives: `print()` and `debugPrint()`. This is a fundamental debugging skill because choosing the wrong mechanism can lead to dropped log output or unthrottled console flooding in production.

Key Concepts

print()	Direct write to stdout. No rate limiting. May cause log truncation on Android when output exceeds 1KB per line.
debugPrint()	Flutter's throttled alternative. Rate-limits output to prevent logcat overflow. Preferred for large payloads.
Large Log Demo	Generates a 1,689-character string via <code>List.generate(200, ...)</code> to prove <code>debugPrint()</code> handles chunked output safely.
DevTools Logging Tab	Captures all stdout and stderr with timestamps, isolate labels, and log levels (INFO, SEVERE).


Implementation Highlights

```
// Throttled — safe for large output, preferred for debug logging
debugPrint('This is a debugPrint() log');

// Unthrottled — may be truncated on Android logcat
print('This is a print() log');

// Large payload handled gracefully by debugPrint()
final largeText = List.generate(200, (i) => 'Item $i').join(' ');
debugPrint(largeText); // Chunked automatically
```

DevTools Screenshot — Logging Tab



The DevTools Logging tab (shown above) captures 4,565 events including navigation events, stdout entries, and SEVERE-level flutter.error exceptions from unrelated screens. Log entries are timestamped and tagged by isolate (main).

2.2 setState() Bug — Counter

The CounterBugScreen provides a side-by-side comparison of a broken and a fixed counter widget. This module demonstrates the most common Flutter state management mistake: mutating state variables directly without calling setState(), which means the framework never schedules a rebuild and the UI remains stale.

The Bug


```
// ❌ BROKEN — state changes internally but UI never rebuilds
void incrementBrokenCounter() {
  brokenCounter++;
  debugPrint('Broken Counter (internal): $brokenCounter');
}
```

The Fix

```
// ✅ FIXED — setState() triggers the rebuild cycle
void incrementFixedCounter() {
  setState(() {
    fixedCounter++;
  });
  debugPrint('Fixed Counter: $fixedCounter');
}
```

The console output reveals the truth: the broken counter's internal value increments (visible in the Logging tab as "Broken Counter (internal): 2") while its on-screen display remains at 0. This perfectly illustrates why debugPrint() combined with the DevTools Logging view is essential for diagnosing silent state bugs.

DevTools Screenshot — Logging + Counter Bug



2.3 Layout Overflow — RenderFlex

The OverflowScreen demonstrates the infamous "RenderFlex overflowed by N pixels" error that Flutter developers encounter when a Row or Column child exceeds its available space. The screen provides a toggle between a broken layout (unconstrained Text in a Row) and a fixed layout, plus a reference card of all available remediation strategies.

The Bug — Unconstrained Text in Row

```
// ❌ BROKEN — Text is not constrained, causes RenderFlex overflow
Widget _buildBroken() {
  return Row(children: [
    const Icon(Icons.warning_rounded, size: 36),
    Text(longText), // No width constraint!
  ]);
}
```


The Fix — Expanded + TextOverflow

```
// ✅ FIXED — Expanded wraps Text, giving it bounded constraints
Widget _buildFixed() {
  return Row(children: [
    const Icon(Icons.check_circle_rounded, size: 36),
    Expanded(
      child: Text(
        longText,
        overflow: TextOverflow.ellipsis,
        maxLines: 3,
      ),
    ),
  ]);
}
```

Available Overflow Fixes

Widget / Property	When to Use
Expanded	Takes all remaining flex space in a Row/Column — best for text/content that should fill
Flexible	Like Expanded but does not force the child to fill — allows natural sizing
TextOverflow.ellipsis	Truncates overflowing text with "..." — ideal for single-line labels
SingleChildScrollView	Makes content horizontally or vertically scrollable instead of clipping
Widget Inspector	Use Flutter Inspector to visualize layout constraints and find the overflowing widget

DevTools Screenshot — Widget Inspector + Overflow



The Flutter Inspector (shown above) visualizes the Padding widget with its exact dimensions (h=68.0, w=392.7) and highlights the overflowing Row's constraint violation with a yellow striped overflow indicator. The Widget Tree panel on the left shows the full widget hierarchy including `_FixRow` and `_BreakRow` children.

2.4 Network Debug Demo

The `NetworkErrorScreen` uses `Dio` to demonstrate three distinct categories of network failures that developers encounter when integrating APIs. All network traffic is visible in the DevTools Network tab, which captures method, URL, HTTP status, content type, duration, and timestamp for every request.

API Service — Three Scenarios

<code>fetchPosts()</code>	GET <code>https://jsonplaceholder.typicode.com/posts</code> — valid endpoint returning HTTP 200 JSON array
<code>fetchBrokenApi()</code>	GET <code>https://invalid-api-url-123456.com/data</code> — intentionally invalid host to trigger <code>DioException</code> (connection error, <code>errno 7</code>)
<code>fetchSlowApi()</code>	GET <code>https://httpstat.us/200?sleep=8000</code> — delays response by 8 seconds, exceeding Dio's 5s <code>receiveTimeout</code> and triggering a timeout exception


Error Handling Pattern

```
Future<void> callApi(Future<dynamic> Function() apiCall) async {
  setState(() { isLoading = true; result = ""; });
  try {
    final response = await apiCall();
    setState(() { result = response.toString().substring(0, 1000); });
  } catch (e) {
    setState(() { result = "ERROR:\n$e"; });
  } finally {
    setState(() { isLoading = false; });
  }
}
```

Dio Configuration

```
final Dio _dio = Dio(  
  BaseOptions(  
    connectTimeout: const Duration(seconds: 5),  
    receiveTimeout: const Duration(seconds: 5),  
  ),  
);
```

DevTools Screenshot — Network Tab



The DevTools Network tab (shown above) displays all six captured requests: a successful JSON GET (200, 1s), TCP SOCKET connections, a pending slow request (httpstat.us, 8000ms delay), and two failed requests to invalid-api-url-123456.com (Error status, 306ms and 21ms respectively — fast failure due to DNS resolution failure). The on-device error panel shows the full DioException stack trace.

3. Performance & Memory

3.1 Memory Leak Demo

The MemoryLeakScreen demonstrates one of the most common sources of memory leaks in Flutter: creating TextEditingController instances (or any ChangeNotifier subclass) without calling dispose() before removing them from the list. This module allows developers to directly observe the difference in heap allocation using the DevTools Memory profiler.

The Leak Scenario

```
// ❌ LEAK — controllers removed from list without disposal
void clearControllersWithoutDispose() {
  controllers.clear(); // Native resources NOT released!
  setState(() {});
}
```

The Safe Pattern


```
// ✅ SAFE — dispose() called before removing references
void clearControllersProperly() {
  for (var controller in controllers) {
    controller.dispose(); // Release native listener bindings
  }
  controllers.clear();
  setState(() {});
}

// ✅ Widget lifecycle cleanup
@override
void dispose() {
  for (var controller in controllers) {
    controller.dispose();
  }
  super.dispose();
}
```

DevTools Memory Tab — Observations

Heap profile	Shows Matrix4 (319 instances), Vector2 (114), DemoCard (8), DebugButton (8) — all expected widget tree objects
Without dispose()	TextEditingController instances remain in heap; their internal ChangeNotifier and AnimationController bindings keep native references alive
With dispose()	Objects eligible for GC immediately; heap allocation line flattens after Refresh on GC
Diff Snapshots	Use "Diff Snapshots" in Memory tab before and after Clear WITHOUT Dispose to measure leaked instances
Trace Instances	Use "Trace Instances" to filter by class name and watch allocation call stacks in real time

DevTools Screenshot — Memory Profiler



The DevTools Memory tab (shown above) displays the heap timeline peaking at ~500MB with steady allocation as controllers are created. The class instance table shows all live objects. The on-device panel shows 25 total created, 5 currently active, with buttons for both the leaking and safe clear operations.

3.2 Performance Demo — Jank Detection

The PerformanceScreen illustrates the direct relationship between synchronous heavy computation on the main isolate and UI jank (dropped frames). It provides a toggle between a "bad" version performing 50 million iterations on the main thread and an "optimized" version doing 1 million iterations — a 50x reduction — allowing developers to observe frame drops in the DevTools Timeline.

Heavy vs Optimized Computation


```
// ✗ BAD — 50M iterations on main thread, blocks UI rendering
int heavyCalculation() {
  int result = 0;
  for (int i = 0; i < 50000000; i++) {
    result += (i % 5);
  }
  return result;
}

// ✔ OPTIMIZED — 1M iterations, 50x less work
void runOptimizedTask() {
  int result = 0;
  for (int i = 0; i < 1000000; i++) {
    result += (i % 5);
  }
  setState(() { heavyResult = result; });
}
```

Performance Tips Reference

Technique	Explanation
Avoid heavy computation in build()	build() is called frequently; any slow logic inside directly extends frame time
Use Isolates for CPU-intensive work	Move heavy computation to a separate isolate with compute() to keep the UI thread free
Use const constructors	Prevents unnecessary widget instantiation on every rebuild — Flutter skips diffing const subtrees
Minimize setState() calls	Each setState() triggers a rebuild of the entire subtree; batch updates or use smaller StatefulWidget
ListView.builder for large lists	Lazily builds only visible items; ListView() builds all children upfront
Profile before optimizing	Use DevTools Performance timeline to identify actual bottlenecks; avoid premature optimization

DevTools Screenshot — Performance Timeline



The DevTools Performance panel (shown above) shows the frame chart with blue bars (UI thread) and orange bars (Raster thread). Jank frames are highlighted in red — the tall red spike (27ms+) directly corresponds to the "Run HEAVY Task" button press triggering 50M iterations on the main thread. Average FPS is reported as 59fps in the upper-right. The on-device result shows 100,000,000 computed in ~75ms.

4. Flutter DevTools — Complete Reference

Flutter DevTools is a web-based suite of performance and debugging tools for Dart and Flutter applications. It is accessible via the browser at the URL printed by flutter run, or directly from VS Code / Android Studio via the DevTools extension.

4.1 DevTools Panels Overview

Panel	DevTools Tab	Primary Use Case
Flutter Inspector	Inspector	Explore the widget tree, inspect properties, identify layout issues
Performance	Performance	Identify jank (>16ms frames), CPU profiling, timeline analysis
CPU Profiler	CPU Profiler	Flame graphs showing method-level CPU time distribution
Memory	Memory	Heap snapshots, allocation tracking, leak detection
Network	Network	Inspect HTTP/HTTPS requests, status codes, response bodies
Logging	Logging	Structured log viewer with filtering by level, isolate, source
App Size	App Size	Analyze compiled APK/IPA size by library and asset
Deep Links	Deep Links	Test Android App Links and iOS Universal Links

4.2 Widget Inspector

The Widget Inspector is the primary tool for diagnosing layout issues. It renders a live, interactive copy of the widget tree and allows selecting any widget on the device to view its properties in real time.

- Select Widget Mode: Tap any widget on the device to jump to it in the tree
- Render Object: View the exact layout constraints, size, and position of any render box
- Flex Explorer: Visualize Flex children and their flex factors / constraints
- Highlight Repaints: Overlays rotating colors on widgets that repaint — reveals unnecessary rebuilds
- Highlight Oversized Images: Flags images rendered larger than their source resolution

4.3 Memory Profiler — Workflow

Step 1: Profile Memory	Click "Profile Memory" to begin sampling the Dart heap at intervals
Step 2: Create Snapshots	Use "Diff Snapshots" to capture before/after states around a suspected leak

Step 3: Trace Instances	Enable "Trace Instances" and filter by class name to watch allocation stacks
Step 4: Refresh on GC	Click "Refresh on GC" to force garbage collection before comparing snapshots
Step 5: Analyze Classes	Sort the class table by Instances or Total Size to find unexpected survivors

4.4 Performance Profiling — Workflow

Step 1: Run in Profile mode	Use flutter run --profile for realistic performance data (debug mode adds overhead)
Step 2: Record timeline	Click Record in the Performance tab, perform the action, then Stop
Step 3: Identify jank	Look for frames above the 16ms line (red/orange bars) in the frame chart
Step 4: CPU Profiler	Switch to CPU Profiler and filter the flame graph to find expensive methods
Step 5: Rebuild Stats	Check Rebuild Stats in the Performance tab to count unnecessary widget rebuilds

4.5 Opening DevTools

```
# Option 1: From terminal after flutter run
# DevTools URL is printed automatically:
# An Observatory debugger and profiler on Android is available at:
# http://127.0.0.1:9100/...

# Option 2: VS Code
# Open Command Palette → "Flutter: Open DevTools in Web Browser"

# Option 3: Android Studio
# View → Tool Windows → Flutter Inspector → Open DevTools

# Option 4: CLI
dart devtools
```

5. Error Handling & Crash Reporting

5.1 Error Handling Patterns

Robust Flutter apps handle three categories of errors: synchronous Dart exceptions, asynchronous Future errors, and framework-level Flutter errors. The app demonstrates all three through intentional crash scenarios and the network error module.

Try-Catch for Async Errors

```
Future<void> callApi(Future<dynamic> Function() apiCall) async {
  try {
    final response = await apiCall();
    // Handle success
  } on DioException catch (e) {
    // Handle network-specific errors (timeout, connection refused)
    setState(() { result = "Network Error: ${e.message}"; });
  } catch (e) {
    // Handle all other exceptions
    setState(() { result = "Error:\n${e}"; });
  } finally {
    setState(() { isLoading = false; }); // Always runs
  }
}
```

DioException Types

DioExceptionType	Cause
connectionError	DNS lookup failure, host unreachable, or no network (errno 7 = ENOENT)
receiveTimeout	Server responded too slowly — exceeded receiveTimeout (5s in this app)
connectionTimeout	TCP connection could not be established within connectTimeout (5s)
sendTimeout	Request body upload timed out before server acknowledged
badResponse	Server responded with a 4xx or 5xx HTTP status code
cancel	Request was explicitly cancelled via CancelToken
unknown	Any other SocketException or untyped error

5.2 Firebase Crashlytics Integration

The project includes `firebase_crashlytics` ^5.0.2 for production crash reporting. Crashlytics automatically captures uncaught exceptions in release builds and provides stack traces, device metadata, and session breadcrumbs in the Firebase Console.

Setup Pattern

```
void main() async {
  WidgetsFlutterBinding.ensureInitialized();
  await Firebase.initializeApp();

  // Catch Flutter framework errors
}
```

```
FlutterError.onError = FirebaseCrashlytics.instance.recordFlutterFatalError;

// Catch errors outside Flutter framework (async gaps)
PlatformDispatcher.instance.onError = (error, stack) {
  FirebaseCrashlytics.instance.recordError(error, stack, fatal: true);
  return true;
};

runApp(const DebugLabApp());
}
```

6. Key Learnings & Best Practices

6.1 Debugging Checklist

- Always use `debugPrint()` instead of `print()` for large or frequent log output in Flutter
- Wrap all state mutations in `setState()` — direct variable changes will not trigger UI rebuild
- Wrap Row/Column text children in `Expanded` or `Flexible` to prevent `RenderFlex` overflows
- Call `dispose()` on all `TextEditingController`, `AnimationController`, and `StreamSubscription` instances
- Use `try-catch-finally` for all `async` operations; never leave a `Future` unhandled
- Open DevTools before investigating a bug — use the correct panel for each issue type
- Profile in `--profile` mode for accurate performance data; debug mode adds significant overhead
- Use `const` constructors wherever possible to prevent unnecessary rebuilds

6.2 DevTools Quick Reference

Bug Type	DevTools Tab	Signal to Look For
UI not updating	Logging	State value increments in logs but widget shows stale value
Layout overflow	Inspector	Yellow/black stripe overlay, overflow pixels shown in render object
Performance jank	Performance	Frame bars exceeding 16ms line; red jank indicators
Memory leak	Memory	Growing heap over time; class instances not decreasing after GC
Network failure	Network	Error status, <code>DioException</code> type, response duration anomalies
Console flooding	Logging	Truncated log lines; switch from <code>print()</code> to <code>debugPrint()</code>

6.3 Learning Objectives — Completion Status

Learning Objective	Module	Status
Master <code>print()</code> vs <code>debugPrint()</code> behavior and output differences	Logging	✓
Use Flutter Inspector to diagnose widget tree and layout issues	Overflow	✓
Detect and fix <code>RenderFlex</code> overflow errors with correct constraint widgets	Overflow	✓
Identify missing <code>setState()</code> calls causing silent state bugs	Counter	✓
Debug network errors using Dio and the DevTools Network tab	Network	✓
Understand <code>DioException</code> types: connection, timeout, <code>badResponse</code>	Network	✓
Detect memory leaks via improper controller disposal	Memory	✓

Learning Objective	Module	Status
Use DevTools Memory tab for heap snapshot and diff analysis	Memory	✓
Identify performance jank using the Performance timeline	Performance	✓
Compare heavy vs optimized computation impact on frame rate	Performance	✓
Understand how to move CPU work off the main thread with Isolates	Performance	✓
Set up Firebase Crashlytics for production crash reporting	Crash Test	✓
Apply FlutterError.onError and PlatformDispatcher.onError	Crash Test	✓