

㈜한화/모멘텀

앱솔릭스 SVM GLASS UNPACKING LOADER 제안서

1. Layout

- 1) Fab Layout
- 2) Glass Unpacking Loader
- 3) Ultra Sonic Cleaner(USC)

2. Glass Unpacking Loader 사양


- 1) Glass & 간지 Tray Loader/Unloader
- 2) 간지 및 Tray 이재기
- 3) Glass 이재기


3. Ultra Sonic Cleaner(USC) 사양

- 1) USC Unit 구성도
- 2) Blow Unit




1) Fab Layout(TBD)






Glass Unpacking Loader

- 1. 설비 구성
 - 1) Glass Unpacking Lodaer
 - 2) Ultra Sonic Cleaner(USC Blow Box 포함)
- 2. Process
 - 1) 5단 Tray Loading(Roller 반송)
 - 2) 간지 이재後 Glass 이재(Tray → EFEM Interface Pin Stage)
 - 3) Glass EFEM Loading(Glass Unpacking Loader → EFEM)
 - 4) Glass EFEM Unloading(EFEM → USC 설비)
 - 5) USC 진행後 Glass EFEM Loading(USC 설비 → EFEM)





- 1. Unit 구성
 - 1) 5단 Tray Loader / Unloader (Lifter Unit & Centering Unit 포함)
 - (1) Tray Input Port (Loading)
 - (2) 간지 Tray Port (Unloading)
 - (3) Spare Glass Tray Port
 - 2) 간지 및 Tray 이재기
 - 3) Glass 이재기
 - 4) EFEM Interface Pin Stage(고정)


2. Normal Process

- 1) 5단 Tray Loading(대차)
- 2) 간지 및 Tray 이재기로 간지 이재 (Input Port → 간지 Tray Port)
- 3) Glass 이재기로 Glass 이재 (Input Port Tray → EFEM Interface Pin Stage)
- 4) EFEM Glass Unloading (EFEM Interface Pin Stage → EFEM)

- 3. Abnormal Process(Spare Glass 발생)
 - 1) 5단 Tray Loading(대차)
 - 2) 간지 및 Tray 이재기로 Spare Glass Tray 이재 (Input Port → Spare Tray Port)

1. Layout

3) Ultra Sonic Cleaner(USC) (TBD)




- 1. Unit 구성
 - 1) USC Unit
 - 2) 흡착 Stage & Transfer Unit
 - 3) Flip Unit
 - 4) Blow Unit

2. Process

- 1) EFEM Glass Loading
- 2) Glass 상면 USC 진행(흡착 Stage Moving)
- 3) Glass Flip & 흡착 Stage 상면 USC 진행(흡착 Stage Moving)
- 4) Glass 흡착 Stage에 안착後 Glass 하면(Flip後 상면) USC 진행
- 5) EFEM Glass Unloading後 흡착 Stage 상면 USC 진행

2. Glass Unpacking Loader

1) 5단 Tray Loader / Unloader



■ Basic Specification


Item			Spec'	Remark
Tray Loader	CV	Motor	Induction Motor + Reducer	
		Driving Method	Helical Gear	
	Lifter Unit	Driving Method	S/Motor + Ball Screw + Ball Bush	
		Stroke	500mm	TBD
Tray Centering Unit	Stopper Unit	Driving Method	Cylinder + LM Guide	
	Centering Unit	Driving Method	Cylinder + LM Guide	
		Support	Free Roller	

Tray Loader/Unloader CV

Tray Centering Unit

2. Glass Unpacking Loader

2) Glass 이재기



■ Basic Specification

Item		Spec'	Remark
이재기 주행 Robot	Drive	S/Motor + Reducer	
	Driving Method	Belt + Pully	
	Stroke	1500mm	TBD
이재기 Z축 Robot	Drive	S/Motor + Reducer	
	Driving Method	Ball Screw	
	Stroke	750mm	TBD
Glass Pick Up Unit	Frame	AL Profile + Square Pipe	
	Pick Up	Vacuum Pad	

Glass Pick Up Unit


이재기 Z축 Robot

이재기 주행 Robot

2. Glass Unpacking Loader

Hanwha Corporation

3) 간지 및 Tray 이재기




간지 및 Tray Pick Up Unit


■ Basic Specification

Item		Spec'	Remark		
이재기 주행 Robot	Drive	S/Motor + Reducer			
	Driving Method	Belt + Pully			
	Stroke	2900mm	TBD		
Pick Up Slide Robot	Drive	S/Motor + Reducer			
	Driving Method	Ball Screw			
	Stroke	100mm	TBD		
간지 및 Tray Pick Up Unit	Drive	Cylinder + Ball Bush			
	Pick Up	Vacuum Pad			
	Stroke	150mm	TBD		

1) USC Unit 구성도(참고용) (TBD)



2) Blow Unit (TBD)



Item		Spec'	Remark
Ring Blower	Power	AC220V 3상 60Hz 4.6kw	
	Air Flow	10m3/min	
	Model	2RB 810-7AH26	TBD
Invertor	Power	AC220V 3상 60Hz 5.5kw	
	Model	CIMR-VT2A0040FAA	TBD
Filter	Vacuum	Pre Filter	
	Pressure	Hepa Filter	
Air		6kgf/cm2	

감사합니다. End of Documents