Supplementary Material

This supplement provides the implementation and evaluation detail needed to reproduce GaitEval and to interpret its evidence boundary. The benchmark operationalizes gait reasoning as producing dataset-specified labels from pose-derived motion evidence. It does not evaluate diagnosis from complete clinical records. The benchmark comprises six datasets: ASD-Kinect, ATAXIA, CARE-PD, GMFCS, PARKINSONISM, and PATHOGAIT. The common evaluation uses the standardized subject-disjoint contract (S); accepted-protocol measurements (L) are retained where they exist, with missing configurations stated explicitly. All reported inputs are derived from skeleton sequences, all prompts are label-redacted, and every supervised split uses only training labels and training statistics.

S.1 Evaluation Scope, Resources, and Splits

S.1.1 Retained accepted-protocol measurements (L)

Table S1 records the accepted-protocol partition metadata for datasets with L measurements; this is an experiment archive, not a division of benchmark membership. This distinction is essential when interpreting external validity: ATAXIA and PATHOGAIT evaluate recognition of instructed or simulated gait patterns, not clinical diagnosis in patients with those disorders.

Table S1: Accepted-protocol partition archive (L). Counts are walking clips in the train/validation/test partitions used by the accepted-protocol evaluation. Splits and label definitions are dataset-specific. "–" means no L run is archived, not exclusion from GaitEval. The accepted files disagree on the GMFCS test count (899 main, 885 supplementary, 866 for some corrected-view cells); these values are not silently reconciled or called uniformly leakage-free.

Resource	Population/source	Task	Classes	Train	Val.	Test	Test subjects
GMFCS	cerebral-palsy cohort	ordinal severity	I–IV	1,574	473	885	174
ATAXIA	healthy volunteers performing ataxic gait	binary	normal / mimicked ataxia	7,004	1,627	1,647	3
PARKINSONISM	patient cohort	binary severity	mild / severe	420	58	120	5
PATHOGAIT	healthy volunteers performing six patterns	six-way pattern	normal + five abnormal patterns	7,361	1,327	2,181	2
ASD-Kinect	no L run	binary	ASD / typical	–	–	–	–
CARE-PD	no L run	UPDRS gait	0–3	–	–	–	–

Subject identity, rather than clip identity, is the resampling unit for uncertainty estimates. The ATAXIA test participants each contribute both normal and mimicked-ataxia clips and are therefore represented by one cluster per person across both classes. PATHOGAIT contains many clips but only two test participants; no population-level superiority or general transfer claim is made from that split. The official GMFCS partition contains three identities shared across partitions (14 test clips). These identities are retained for comparability with the published split, explicitly grouped by subject in uncertainty calculations, and treated as a limitation rather than as independent evidence.

S.1.2 Standardized same-model suite

The standardized contract applies one Qwen2.5-7B runner, prompt family, parser, and feature policy to every dataset in Table S2. All six datasets enter the common evaluation. CARE-PD is restricted to the four-level UPDRS gait item; heterogeneous labels from other tasks are outside the primary evaluation. The full source CARE-PD corpus has 362 patients and 8476 clips, but the evaluated primary-task test subset has 665 clips from 24 patients. ASD-Kinect has 100 participants (70/10/20 subject split); the source reports that some movements were simulated by other people without identifying affected sequences, so it is not a strictly verified patient-only cohort.

Table S2: Standardized evaluation contract. Feature counts reflect supported columns after skeleton-role mapping and removal of capture-quality variables. Test counts are the evaluable records in the released prediction files.

Resource	Train clips	Test clips	Test subjects	Features	Label space
ASD-Kinect	70	20	20	23	ASD / typical
ATAXIA	28	8	4	14	normal / mimicked ataxia
CARE-PD (UPDRS gait)	1,901	665	24	24	scores 0–3
GMFCS	914	255	149	16	levels 1–4
PARKINSONISM	83	29	5	16	mild / severe
PATHOGAIT	5,040	1,440	2	24	six gait patterns

The standardized ATAXIA split contains eight clips from four test participants and therefore supports descriptive conclusions only. Its L and S measurements concern different data constructions and are not interchangeable. For PARKINSONISM, 29 evaluable clips from five test participants enter the released same-model results. CARE-PD score 3 has only 18 test clips, which makes its class-specific estimates particularly uncertain.

S.2 Pose Preprocessing and Model-Visible Input Views

Each walking clip is converted into one model-visible view at a time. Views are never concatenated unless explicitly stated. Labels, diagnosis strings that directly reveal a candidate class, sample identifiers, subject identifiers, and split metadata are excluded from all prompts.

Table S3: Controlled input representations. GaitEval uses four input-view families. The z-scored named-feature representation is a derived scaling control within the named-feature family. Motion summaries and feature views are deterministic functions of the pose sequence.

View	Shape/format	Construction	Evaluation role
Raw coordinates	$124 \times J_d \times 3$	valid pose frames, zero-padded to fixed length	numeric-sequence stress test
Normalized coordinates	$32 \times 12 \times 3$	common joints, body-centered, scale/direction normalized	cross-layout coordinate view
Motion summary	fixed-section English text	deterministic verbalization of measured features	primary readable evidence view
Raw feature vector	named values	supported biomechanical measurements	exact-feature evidence test
Z-scored named feature vector	named standardized values	training-mean/SD normalization	scale-controlled evidence test

S.2.1 Raw and normalized coordinate views

accepted-protocol raw-coordinate clips use a fixed tensor of 124 frames by the dataset-specific joint count J_d and three channels. Shorter clips are zero-padded; feature and summary computation uses only valid frames. At the nominal 30 frames/s, 124 frames correspond to approximately 4.1 seconds. Temporal measurements are expressed per frame or as dimensionless ratios so that no label-dependent temporal normalization is introduced.

The normalized coordinate view maps each skeleton to 12 common joints in the fixed order shoulders, elbows, wrists, hips, knees, and ankles. For every frame, the midpoint of the hips is subtracted from all joints. Coordinates are divided by the mean shoulder-center–to–hip-center distance computed over valid frames. The principal direction of the hip-center trajectory is aligned with the positive x axis, and the remaining axes are defined by an orthogonal body-centered basis. Thirty-two frames are then selected at uniform temporal indices. The prompt contains a $32 \times 12 \times 3$ table rounded to two decimals. This view preserves relative motion while reducing differences in global location, scale, orientation, joint count, and clip duration.

S.2.2 Deterministic biomechanical features

For joint j, spatial channel c, and valid frame set T, range of motion is

$$R_{j,c} = \max_{t \in T} p_{t,j,c} - \min_{t \in T} p_{t,j,c}. \tag{1}$$

Confidence channels are never used as spatial coordinates. For paired nonnegative measurements v_L and v_R, unsigned asymmetry is

$$A(v_L, v_R) = \frac{|v_L - v_R|}{0.5(|v_L| + |v_R|) + 10^{-8}}. \tag{2}$$

The ratio lies in $[0, 2]$ but discards the direction of asymmetry; this is a known limitation for unilateral presentations. The jerk proxy is the mean absolute third finite difference of the relevant trajectory. Trajectory variability is the temporal variance of the specified joint path. The standardized value is

$$z_{i,f} = \frac{x_{i,f} - \mu_f^{\text{train}}}{\sigma_f^{\text{train}} + 10^{-8}}, \tag{3}$$

using training-split statistics only.

Table S4: Complete deterministic feature inventory. Braces denote separate left and right features. Skeleton layouts that do not support a semantic role leave the corresponding feature undefined.

Group	Released feature name	Definition
Amplitude	`ankle_{L,R}_vert_range`	vertical ankle range
Amplitude	`ankle_{L,R}_horiz_range`	horizontal ankle range
Amplitude	`knee_{L,R}_vert_range`	vertical knee range
Amplitude	`hip_{L,R}_vert_range`	vertical hip range
Asymmetry	`ankle_vert_asymmetry`	paired ankle vertical-range asymmetry
Asymmetry	`ankle_horiz_asymmetry`	paired ankle horizontal-range asymmetry
Asymmetry	`knee_vert_asymmetry`	paired knee vertical-range asymmetry
Asymmetry	`hip_vert_asymmetry`	paired hip vertical-range asymmetry
Stability	`trunk_lateral_sway`	lateral trunk range
Stability	`trunk_vert_range`	vertical trunk range
Stability	`hip_centre_lateral_std`	lateral hip-center standard deviation
Stability	`hip_centre_vert_std`	vertical hip-center standard deviation
Variability	`mean_joint_trajectory_var`	mean joint-path variance
Variability	`ankle_{L,R}_traj_var`	left/right ankle-path variance
Smoothness	`ankle_{L,R}_jerk`	left/right ankle jerk proxy
Smoothness	`ankle_mean_jerk`	mean of the ankle jerk proxies
Smoothness	`trunk_jerk`	trunk jerk proxy
Capture audit	`valid_frame_fraction`	fraction of valid frames in the fixed tensor

The 24-column inventory above documents the L extractor (23 motion measurements plus `valid_frame_fraction`), not a claim that every S layout has those identical columns. The S reference metadata reports 14/16/16/24/23/24 supported features for ATAXIA/GMFCS/PARKINSONISM/PATHOGAIT/ASD-Kinect/CARE-PD, respectively; the complete source S feature CSVs are not committed in the upstream snapshot. The accepted-protocol feature view retains the supported columns available for each dataset. The standardized suite excludes `valid_frame_fraction`, clip length, and other capture-quality variables by construction. Features unsupported by an entire skeleton layout are removed from both the LLM view and the matched linear reference. Residual missing values in supported columns are median-imputed using the training split for the references; undefined values are omitted from text prompts rather than filled with a numerical token.

S.2.3 Motion-summary provenance and template

Motion summaries are not dataset metadata, clinical notes, manual annotations, or outputs of another language model. They are generated deterministically from the feature vector above. The generator uses a fixed section order: MOTION AMPLITUDE, SYMMETRY/ASYMMETRY, STABILITY, TRAJECTORY VARIABILITY, and SMOOTHNESS. The accepted-protocol version also includes a CLIP QUALITY line; the standardized suite omits it together with the corresponding feature.

Raw amplitudes and ranges are printed to four decimals; variances and jerk proxies are printed to six decimals. A small set of fixed thresholds adds qualitative wording without using a label:

- asymmetry < 0.05: symmetric; $[0.05, 0.15)$: mild; $[0.15, 0.30)$: notable; ≥ 0.30: strong;
- trunk lateral sway < 0.04: mild; $[0.04, 0.09)$: moderate; ≥ 0.09: marked;
- ankle mean jerk $< 2 \times 10^{-4}$: smooth; $[2 \times 10^{-4}, 8 \times 10^{-4})$: moderately smooth; $\geq 8 \times 10^{-4}$: jerky.

The thresholds only select descriptive phrases; the underlying numerical values are retained. A typical summary is 150–300 words (approximately 320 tokens). The following schematic preserves the exact structure while using illustrative values:

```
MOTION AMPLITUDE
Left/right ankle vertical range:  0.0900 / 0.1400.
Left/right knee vertical range:  0.0710 / 0.0840.

SYMMETRY/ASYMMETRY
Ankle vertical asymmetry:  0.4350 (strong asymmetry).

STABILITY
Trunk lateral sway:  0.0400 (moderate sway).

TRAJECTORY VARIABILITY
```

```
Mean joint trajectory variance:  0.008000.

SMOOTHNESS
Mean ankle jerk:  0.000700 (moderately smooth).
```

The candidate label set is inserted only by the downstream classification prompt. It is never available to the summary generator, so the motion evidence and task instruction remain separate objects.

S.3 Exact Prompt Formats and Output Parsing

S.3.1 Flat zero-shot prompt

The primary prompt is instantiated verbatim as follows, where bracketed fields are filled with the selected evidence view and the dataset's complete candidate list:

```
You are classifying a gait clip from a compact biomechanical
[EVIDENCE_KIND] derived from a skeleton sequence.

[EVIDENCE]

Task: based ONLY on the [EVIDENCE_KIND] above, classify the gait
into exactly one of the following classes:
- [CLASS 1]
- [CLASS 2]
...

Return only one label, written exactly as listed above.
```

For motion summaries, `EVIDENCE_KIND` is "motion summary." For raw or standardized features it is "feature description." Candidate descriptions are task labels only; no prevalence, clinical definition, or example is supplied in zero-shot evaluation.

S.3.2 Reasoning-anchored prompt

The reasoning-anchored condition used the same label-redacted motion summary as the flat condition, but replaced the direct-answer instruction with the following structured prompt. No separate system message was used; the complete prompt was sent as a single user message. Bracketed fields below denote deterministic run-time substitutions.

```
You are a gait-analysis expert classifying a walking clip from a compact biomechanical motion summary derived from a 3D
↪  skeleton sequence. The summary reports motion amplitudes, left/right asymmetry, trunk/pelvis stability, trajectory
↪  variability, and movement smoothness (jerk).

[MOTION_SUMMARY]

Candidate classes:
[CANDIDATE_CLASS_LINES]

Reason step by step:
1. List the 2-3 most abnormal biomechanical signals in this summary (e.g. high asymmetry, high jerk, large trunk sway,
↪  reduced amplitude).
2. For EACH candidate class, briefly state whether those signals are consistent or inconsistent with it.
3. Do NOT default to the most common class; pick the class best supported by the specific signals.
Finally, on a new line, output exactly: FINAL: <one class name>
```

The candidate lines were inserted in ascending numeric-label order using the exact dataset label strings. This condition used Qwen2.5-72B-Instruct with temperature 0 and a maximum of 512 output tokens. For ATAXIA and PATHOGAIT, the test records were shuffled with seed 0 before selecting 150 clips. PARKINSONISM contains only 120 test clips, so all of its test clips were evaluated after the same seeded shuffle. The generated reasoning text was not treated as explanation supervision or scored for clinical correctness; only the parsed final class was evaluated.

For the three evaluated resources, the exact candidate strings were:

- ATAXIA: `normal gait`; `cerebellar ataxic gait`.
- PARKINSONISM: `low motor severity`; `high motor severity`.
- PATHOGAIT: `normal gait`; `antalgic gait`; `lurching gait`; `steppage gait`; `stiff-legged gait`; and `Trendelenburg gait`.

S.3.3 Few-shot prompt

Few-shot prompting was implemented as one user message containing a sequence of labeled textual reference blocks, followed by the unlabeled test query. It was not implemented as a multi-turn sequence of separate user and assistant messages. No separate system message was used. The literal template was:

```
You are classifying a gait clip from a compact biomechanical motion summary derived from a 3D skeleton sequence.
↪  Feature values (amplitudes, left/right asymmetry, stability, trajectory variability, smoothness) must be judged
↪  RELATIVE TO THIS DATASET, not by generic clinical intuition. Below are [N_SHOTS] labeled reference clips from the
↪  same dataset and feature pipeline; use them to calibrate what each class looks like here.

=== Reference example 1 ===
[REFERENCE_MOTION_SUMMARY_1]
Ground-truth class: [REFERENCE_CLASS_1]

=== Reference example 2 ===
[REFERENCE_MOTION_SUMMARY_2]
Ground-truth class: [REFERENCE_CLASS_2]

[ADDITIONAL_REFERENCE_BLOCKS]

=== Now classify this new clip ===
[QUERY_MOTION_SUMMARY]

Candidate classes:
[CANDIDATE_CLASS_LINES]

Return only one label, written exactly as listed above.
```

Reference examples were drawn only from the dataset's training split. For a requested context size k and C classes, the implementation grouped training examples by numeric class, shuffled each class pool with seed 0, selected $\max(1, \lfloor k/C \rfloor)$ examples from each class, and then shuffled the combined reference set using the same random-number generator. All reported context sizes were divisible by the corresponding number of classes, so the realized reference set contained exactly k examples and was class-balanced. One fixed reference set was reused for every test clip within a run.

Inference used Qwen2.5-72B-Instruct, temperature 0, a maximum of 64 output tokens, and the same exact-label parser used for the accepted-protocol flat-prompt experiments.

The reported settings were:

- ATAXIA: $k \in \{8, 16, 32\}$, corresponding to 4, 8, and 16 references per class, evaluated on the full test split.
- PARKINSONISM: $k = 16$, corresponding to 8 references per class, evaluated on the full test split.
- PATHOGAIT: $k = 12$, corresponding to 2 references per class. This run evaluated the first 600 records in the stored test-file order rather than the complete 2,181-clip test split.

S.3.4 Parser and invalid outputs

The reasoning condition did not use a dedicated parser for the `FINAL:` field. accepted-protocol reasoning and few-shot outputs were parsed with the same exact-label parser as the corresponding flat-prompt runs. Outputs were whitespace-normalized and lowercased, and candidate strings were matched with leading and trailing alphanumeric boundaries. When several complete candidate strings occurred, the latest occurrence was selected; positional ties favored the longer candidate string. Consequently, a compliant final `FINAL: <class>` line was normally selected because it was the last candidate mention, rather than because the parser explicitly recognized the `FINAL:` prefix.

If no complete candidate occurred, the accepted-protocol parser additionally accepted an output-ending substring only when it was a unique prefix of exactly one candidate label, providing a limited fallback for truncated generations. All other outputs were marked `UNPARSED`. Unparsed outputs were never discarded: they were counted as errors and contributed a false negative to the true class.

S.4 Models, Inference, and Adaptation

S.4.1 Zero-shot model roster

The primary accepted-protocol motion-summary evaluation uses five open-weight instruction-tuned families spanning 27B–72B parameters: Llama-3.3-70B-Instruct, Qwen2.5-72B-Instruct, Gemma-3-27B-IT, GLM-4-32B-0414, and DeepSeek-R1-Distill-Qwen-32B. Inference uses deterministic decoding (temperature 0) through vLLM. The generation cap is 64 tokens for the direct-answer models and 2,048 tokens for the reasoning-distilled model, followed by the same fixed parser.

Representation controls, prompt controls, and supervised adaptation use Qwen2.5-7B-Instruct so that changes can be attributed to the condition rather than to a model-family change. The S Qwen-7B and non-reasoning five-family runs use temperature 0 and a 48-token cap; the S DeepSeek run uses 2048 tokens. The archived L Qwen-7B view launcher sets a 16-token cap. These are recorded implementation differences, not matched-budget claims. The SFT evaluation prompt is byte-identical to the corresponding zero-shot motion-summary prompt.

S.4.2 LoRA supervised fine-tuning

LoRA-SFT is trained separately for each dataset on training-split motion summaries and their candidate labels. The configuration is rank $r = 16$, scaling $\alpha = 32$, dropout 0.05, and adapters on all linear projections. Training uses completion-only cross-entropy, three epochs, learning rate 10^{-4} with cosine decay, maximum sequence length 1,024, per-device batch size 8, and gradient accumulation 2 (effective batch size 16). The committed trainer reads only training examples, uses no evaluation dataset and no intermediate checkpoint selection (`save_strategy="no"`), and saves the final three-epoch adapter. A validation-selected checkpoint is not supported by this implementation. The configured test split is not used for training or normalization.

The standardized training-set sizes are 28 for ATAXIA, 914 for GMFCS, 83 for PARKINSONISM, 5,040 for PATHOGAIT, 70 for ASD-Kinect, and 1,901 for CARE-PD. CARE-PD training examples are restricted to the UPDRS gait task. SFT therefore measures recovery of an in-distribution, dataset-specific mapping from supplied evidence to the dataset label space; it is not interpreted as acquisition of a general diagnostic rule.

S.4.3 Few-shot sweep

Table S5: Few-shot motion-summary prompting. Qwen2.5-72B receives balanced labeled training examples. Cells report accuracy / macro-F1 / Cohen's κ. Bold marks the best tested context size within a dataset.

Dataset	Setting	Accuracy / macro-F1 / κ
ATAXIA	zero-shot	0.685 / 0.406 / -0.002
ATAXIA	$k = 8$	0.682 / 0.644 / 0.289
ATAXIA	$k = 16$	**0.740 / 0.697 / 0.395**
ATAXIA	$k = 32$	0.642 / 0.633 / 0.299
PARKINSONISM	zero-shot	0.575 / 0.472 / 0.035
PARKINSONISM	$k = 16$	**0.567 / 0.561 / 0.188**
PATHOGAIT	zero-shot	0.155 / 0.054 / -0.009
PATHOGAIT	$k = 12$	**0.268 / 0.185 / 0.081**

The ATAXIA curve is non-monotonic, so few-shot prompting is treated as an adaptation probe rather than a tuned final model. The PATHOGAIT context contains two examples per class at $k = 12$.

S.5 Matched Linear References

The supervised references are multinomial or binary logistic regression and a linear support-vector machine. Both receive exactly the supported deterministic feature columns available to the feature-view LLM condition. The supervised references use prespecified estimator settings: logistic regression is fitted with `max_iter=2000`, and the linear SVM with `max_iter=5000`. The class-balanced configuration is the primary reference, while the unweighted configuration is reported as a parallel sensitivity analysis rather than selected on validation performance. Missing values are imputed using training-set medians, and the imputer and standard scaler are fitted on the training split only before being applied to the held-out test split. No validation-based hyperparameter search is performed. Columns missing for an entire dataset are dropped, and residual missing values are imputed with the training median. These models are signal probes: they establish whether the deterministic pose representation contains label-relevant information under supervised learning, rather than representing the state of the art in clinical gait analysis.

Table S6: L-only archive; "–" denotes no L result. **accepted-protocol feature references.** Macro-F1 on the accepted-protocol test splits. "Balanced" uses inverse-frequency class weights; "none" uses the empirical training distribution.

Reference	ATAXIA	GMFCS	PARKINSONISM	PATHOGAIT
Logistic regression (balanced)	0.763	0.388	0.613	0.662
Logistic regression (none)	0.773	0.418	0.627	0.663
Linear SVM (balanced)	0.759	0.410	0.583	0.644
Linear SVM (none)	0.769	0.403	0.579	0.646
ASD-Kinect	–	–	–	–
CARE-PD	–	–	–	–

For the accepted-protocol PATHOGAIT analysis, removing `valid_frame_fraction` reduces balanced logistic-regression macro-F1 from 0.662 to 0.564 and linear-SVM macro-F1 from 0.644 to 0.560. The corresponding change is below 0.001 on the other three accepted-protocol resources. Consequently, PATHOGAIT accepted-protocol feature results are interpreted as using the supplied pose-derived feature set rather than as purely kinematic. The standardized suite excludes capture-quality variables for all methods.

S.6 Metrics and Statistical Analysis

Let C_{ab} denote the number of clips whose true class is a and predicted class is b, for a fixed candidate set of K classes. For class k, precision, recall, and F1 are

$$P_k = \frac{C_{kk}}{\sum_{a=1}^{K} C_{ak}}, \qquad R_k = \frac{C_{kk}}{\sum_{b=1}^{K} C_{kb}}, \tag{4}$$

and

$$F_{1,k} = \frac{2P_k R_k}{P_k + R_k}. \tag{5}$$

A metric is set to zero when its denominator is zero. Macro-F1 is the unweighted mean over the complete dataset-defined class set,

$$\mathrm{MacroF1} = \frac{1}{K} \sum_{k=1}^{K} F_{1,k}, \tag{6}$$

including classes that receive no predictions. Accuracy is

$$\mathrm{Accuracy} = \frac{1}{N} \sum_{k=1}^{K} C_{kk}. \tag{7}$$

These metrics are reported together because accuracy alone can obscure class-allocation failures on imbalanced tasks [16, 17].

For binary tasks, sensitivity is recall for the dataset-specified positive class, whereas specificity is recall for the complementary negative class. Balanced accuracy is

$$\mathrm{BalancedAccuracy} = \frac{\mathrm{Sensitivity} + \mathrm{Specificity}}{2}. \tag{8}$$

Cohen's agreement coefficient is

$$\kappa = \frac{p_o - p_e}{1 - p_e}, \qquad p_o = \frac{1}{N} \sum_{i=1}^{N} \mathbf{1}(y_i = \hat{y}_i), \tag{9}$$

where y_i and $\hat{y}_i$ are the true and parsed predicted labels for clip i. Chance agreement is computed from the empirical target and prediction marginals:

$$p_e = \sum_{k=1}^{K} \left(\frac{n_k^{(y)}}{N} \right) \left(\frac{n_k^{(\hat{y})}}{N} \right), \tag{10}$$

where $n_k^{(y)}$ and $n_k^{(\hat{y})}$ are the numbers of true and predicted instances of class k, respectively [65]. An unparsed output is assigned a prediction-only sentinel category outside the candidate set. It is therefore always incorrect, contributes a false negative to its true class, and cannot create a true positive for any candidate class.

For ordinal GMFCS and CARE-PD tasks, mean absolute error (MAE) is computed over the ordered class indices:

$$\mathrm{MAE} = \frac{1}{N}\sum_{i=1}^{N} \left| r(y_i) - r(\hat{y}_i) \right|, \tag{11}$$

where $r(\cdot)$ maps a class label to its ordinal level. We additionally report quadratic-weighted Cohen's κ. Let

$$w_{ab} = \frac{(a-b)^2}{(K-1)^2} \tag{12}$$

be the quadratic disagreement weight, $O_{ab} = C_{ab}$ the observed confusion matrix, and

$$E_{ab} = \frac{n_a^{(y)} n_b^{(\hat{y})}}{N} \tag{13}$$

the expected count under independent target and prediction marginals. Quadratic-weighted agreement is

$$\kappa_{\mathrm{q}} = 1 - \frac{\sum_{a=1}^{K}\sum_{b=1}^{K} w_{ab} O_{ab}}{\sum_{a=1}^{K}\sum_{b=1}^{K} w_{ab} E_{ab}}. \tag{14}$$

This metric gives larger penalties to errors spanning more ordinal levels. Per-class precision, recall, F1, and support, together with integer and row-normalized confusion matrices, are reported for every standardized condition.

Uncertainty is primarily quantified using a participant-cluster bootstrap with $B = 2{,}000$ draws. For each draw, the test participants are sampled with replacement, and all clips from each sampled participant are retained together. The metric is recomputed on every valid draw, and the 2.5th and 97.5th percentiles form the 95% confidence interval [66]. For a paired comparison, the same sampled participants and matched clips are used for both conditions. If

$$\Delta = T_A - T_B \tag{15}$$

is the observed macro-F1 difference, the paired confidence interval is obtained from the bootstrap distribution of Δ^*. The reported two-sided paired p value is estimated from the proportions of participant-bootstrap differences on the two sides of zero. These paired tests therefore evaluate changes between conditions while preserving within-participant dependence.

The per-cell permutation-against-chance values in the standardized grid use a separate row-level label-permutation test. The true labels are permuted relative to the fixed predictions while preserving their empirical marginal counts. With observed statistic T_{obs} and permuted statistics $T^{(b)}$, the one-sided Monte Carlo value is

$$p_{\mathrm{perm}} = \frac{1 + \sum_{b=1}^{B} \mathbf{1}\left(T^{(b)} \geq T_{\mathrm{obs}}\right)}{B+1}. \tag{16}$$

With $B = 2{,}000$, the minimum attainable value is approximately 0.0005. Because this permutation operates on individual records rather than participant clusters, it is treated as a descriptive null comparison and not as participant-level population inference. The participant-cluster intervals and paired participant-bootstrap contrasts provide the primary uncertainty analysis.

The limited numbers of independent participants constrain these analyses. The accepted-protocol ATAXIA and PARKINSONISM test sets contain three and five participants, respectively. PATHOGAIT contains only two test participants, for which participant-cluster resampling is degenerate; its frozen-split results are therefore reported as descriptive point estimates with participant-specific values and are not used to support population-level superiority. ASD-Kinect contains one clip per participant, so record-level and participant-level resampling coincide. The highest GMFCS and CARE-PD ordinal levels also have small supports and should be interpreted jointly with their per-class results and confusion matrices.

S.7 Primary accepted-protocol Zero-Shot Results

Table S7 gives the complete five-family motion-summary evaluation. Across the 20 L cells, Cohen's κ lies between -0.069 and 0.035; this range does not describe the S CARE-PD or ASD-Kinect results added below. The final column exposes the dominant prediction share, showing that high binary accuracy can coexist with near-single-class output.

Table S7: Five-family zero-shot motion-summary results. Cells report accuracy / macro-F1 / Cohen's κ; "top share" is the fraction assigned to the most frequent predicted class. Dataset superscripts identify L/S measurement contracts, not different dataset status. Standardized five-family reruns for the four L rows are missing.

Dataset	Model	Accuracy	Macro-F1	κ	Top share
ATAXIA^{L}	Llama-3.3-70B	0.686	0.407	0.000	1.00
	Qwen2.5-72B	0.685	0.406	-0.002	1.00
	Gemma-3-27B	0.686	0.407	0.000	1.00
	GLM-4-32B	0.686	0.407	0.000	1.00
	DeepSeek-R1-Distill-Qwen-32B	0.684	0.408	-0.002	1.00
GMFCS^{L}	Llama-3.3-70B	0.352	0.210	0.018	0.72
	Qwen2.5-72B	0.369	0.218	0.033	0.78
	Gemma-3-27B	0.301	0.158	0.025	0.87
	GLM-4-32B	0.259	0.123	0.000	0.93
	DeepSeek-R1-Distill-Qwen-32B	0.307	0.189	0.015	0.64
PARKINSONISM^{L}	Llama-3.3-70B	0.583	0.368	0.000	1.00
	Qwen2.5-72B	0.575	0.472	0.035	0.86
	Gemma-3-27B	0.583	0.368	0.000	1.00
	GLM-4-32B	0.583	0.368	0.000	1.00
	DeepSeek-R1-Distill-Qwen-32B	0.583	0.368	0.000	1.00
PATHOGAIT^{L}	Llama-3.3-70B	0.159	0.053	-0.010	0.94
	Qwen2.5-72B	0.155	0.054	-0.009	0.94
	Gemma-3-27B	0.165	0.047	-0.001	1.00
	GLM-4-32B	0.141	0.059	-0.069	0.51
	DeepSeek-R1-Distill-Qwen-32B	0.166	0.094	-0.007	0.48
ASD-Kinect^{S}	Llama-3.3-70B	0.500	0.451	0.000	0.80
	Qwen2.5-72B	0.450	0.373	-0.100	0.85
	Gemma-3-27B	0.450	0.310	-0.100	0.95
	GLM-4-32B	0.450	0.373	-0.100	0.85
	DeepSeek-R1-Distill-Qwen-32B	0.600	0.583	0.200	0.70
CARE-PD^{S}	Llama-3.3-70B	0.441	0.262	0.119	0.71
	Qwen2.5-72B	0.445	0.268	0.130	0.64
	Gemma-3-27B	0.439	0.249	0.113	0.72
	GLM-4-32B	0.441	0.350	0.124	0.56
	DeepSeek-R1-Distill-Qwen-32B	0.399	0.295	0.099	0.45

These results bound the primary claim: the evaluated off-the-shelf models do not consistently ground dataset labels in the supplied motion summaries. They do not imply that pose contains no signal or that every possible language-model representation must fail.

S.8 Representation and Prompt Controls

S.8.1 Same-model view comparison

Table S8 reports the completed zero-shot input-view comparisons using Qwen2.5-7B-Instruct on the accepted-protocol subject-disjoint splits. Changing the input view substantially alters the prediction patterns, but no view consistently recovers agreement across all four resources. In a separate standardized analysis, the PARKINSONISM z-scored feature view reaches 0.757 macro-F1 on 29 clips from five participants (Table S9). This result indicates that evidence use can depend on both the dataset and the input representation, although the small test cohort precludes a broad population-level conclusion.

Table S8: accepted-protocol same-model zero-shot input-view comparison. Results are obtained with Qwen2.5-7B-Instruct on the accepted-protocol subject-disjoint test splits. Cells report accuracy / macro-F1 / Cohen's κ. A dash indicates that the corresponding comparison was not completed. Dataset superscripts identify L/S; all-six S summary/z-feature results are given in the shared grid.

Dataset	Motion summary	Normalized coordinates	Raw feature view	Z-scored feature view
ATAXIA^{L}	0.692 / 0.452 / 0.046	0.316 / 0.244 / 0.002	0.382 / 0.347 / 0.057	0.583 / 0.495 / -0.008
GMFCS^{L}	0.249 / 0.110 / -0.008	0.282 / 0.110 / 0.000	0.343 / 0.245 / 0.007	0.185 / 0.100 / -0.049
PARKINSONISM^{L}	0.550 / 0.400 / -0.045	0.442 / 0.441 / -0.095	0.417 / 0.294 / 0.000	0.508 / 0.493 / -0.014
PATHOGAIT^{L}	0.142 / 0.087 / -0.024	0.110 / 0.034 / 0.000	–	0.150 / 0.130 / -0.011
ASD-Kinect^{S}	0.450 / 0.310 / -0.100	–	0.500 / 0.333 / 0.000	0.550 / 0.436 / 0.100
CARE-PD^{S}	0.433 / 0.321 / 0.152	–	0.332 / 0.221 / 0.039	0.233 / 0.133 / 0.020

A separate raw-coordinate stress test supplies Llama-3.3-70B with the $124 \times J_d \times 3$ sequence directly. Scoring invalid outputs as errors gives ATAXIA accuracy/macro-F1/κ of 0.573/0.323/0.009 with 6.0% unparsed outputs, and PATHOGAIT 0.093/0.083/0.038

with 59.3% unparsed outputs. Direct coordinate access therefore does not establish reliable zero-shot classification and creates a substantial formatting burden on the longer six-class task.

S.8.2 Reasoning-anchored prompt

Qwen2.5-72B is also tested with the explicit compare-then-answer prompt. On fixed 150-clip subsets of ATAXIA and PATHOGAIT and the complete 120-clip PARKINSONISM test set, the reasoning-anchored results are 0.687/0.427/0.028, 0.167/0.105/-0.018, and 0.583/0.368/0.000, respectively. These cells are not clip-matched to the full-split flat-prompt table and are treated as prompt-format diagnostics. The prompt changes some output distributions but does not establish beyond-chance agreement.

Table S9: Complete standardized subject-disjoint grid. All cells use Qwen2.5-7B-Instruct. Values are macro-F1 with 95% participant-cluster bootstrap intervals and permutation-against-chance p values where participant-level inference is supported. ‡PATHOGAIT contains only two test participants; its cells are descriptive point estimates, and the degenerate bootstrap intervals and row-level permutation p values are therefore omitted. The CARE-PD 12-class mixed-label cell combines different label tasks and is retained only as a diagnostic, not as a benchmark result.

Resource	Condition	n	Macro-F1	95% participant CI	Permutation p
CARE-PD	Summary	665	0.321	[0.262, 0.404]	0.0005
	Z-features	665	0.134	[0.086, 0.184]	0.68
	Labels reversed	665	0.252	[0.133, 0.293]	0.0005
	Labels shuffled	665	0.285	[0.217, 0.353]	0.0005
	Shuffled evidence	665	0.256	[0.217, 0.313]	0.23
	No evidence	665	0.133	[0.083, 0.183]	1.0
	LoRA-SFT summary	665	0.445	[0.260, 0.507]	0.0005
GMFCS	Summary	255	0.265	[0.217, 0.308]	0.042
	Z-features	255	0.150	[0.108, 0.197]	0.42
	Labels reversed	255	0.322	[0.271, 0.369]	0.006
	Labels shuffled	255	0.274	[0.225, 0.320]	0.13
	Shuffled evidence	255	0.212	[0.172, 0.252]	0.62
	No evidence	255	0.000	[0.000, 0.000]	1.0
	LoRA-SFT summary	255	0.467	[0.413, 0.624]	0.0005
PARKINSONISM	Summary	29	0.396	[0.222, 0.530]	0.52
	Z-features	29	0.757	[0.543, 0.906]	0.0075
	Labels reversed	29	0.356	[0.136, 0.617]	0.90
	Labels shuffled	29	0.356	[0.136, 0.617]	0.90
	Shuffled evidence	29	0.309	[0.104, 0.439]	1.0
	No evidence	29	0.326	[0.133, 0.462]	1.0
	LoRA-SFT summary	29	0.542	[0.255, 0.720]	0.29
ATAXIA	Summary	8	0.273	[0.111, 0.333]	1.0
	Z-features	8	0.333	[0.333, 0.333]	1.0
	Labels reversed	8	0.273	[0.111, 0.333]	1.0
	Labels shuffled	8	0.273	[0.111, 0.333]	1.0
	Shuffled evidence	8	0.273	[0.111, 0.333]	1.0
	No evidence	8	0.333	[0.333, 0.333]	1.0
	LoRA-SFT summary	8	0.333	[0.333, 0.333]	1.0
PATHOGAIT‡	Summary	1,440	0.069	–	–
	Z-features	1,440	0.139	–	–
	Labels reversed	1,440	0.121	–	–
	Labels shuffled	1,440	0.093	–	–
	Shuffled evidence	1,440	0.071	–	–
	No evidence	1,440	0.048	–	–
	LoRA-SFT summary	1,440	0.451	–	–
ASD-Kinect	Summary	20	0.310	[0.200, 0.394]	1.0
	Z-features	20	0.436	[0.259, 0.642]	0.50
	Labels reversed	20	0.341	[0.167, 0.524]	0.96
	Labels shuffled	20	0.341	[0.167, 0.524]	0.96
	Shuffled evidence	20	0.436	[0.259, 0.642]	0.51
	No evidence	20	0.333	[0.231, 0.412]	1.0
	LoRA-SFT summary	20	0.310	[0.200, 0.394]	1.0
CARE-PD	12-class mixed diagnostic	970	0.004	[0.001, 0.009]	1.0

The standardized table has two important qualifications. First, PARKINSONISM z-features reach 0.757 macro-F1 on only 29 clips from five subjects; the subject-cluster interval is 0.543–0.906 and overlaps the matched logistic-reference interval of 0.416–0.654. This is evidence that explicit standardized features can be usable by the model in a particular condition, not a population-level superiority result. Second, the ATAXIA standardized split contains eight clips and has insufficient power for model ranking.

S.8.3 Evidence and label-order controls

Table S10: Complete standardized paired contrasts. Each contrast is the macro-F1 of the first named condition minus that of the second. Parenthesized values are two-sided paired participant-cluster bootstrap p values computed from valid cluster draws as defined in Sec. S.6. Thus, a positive value favors the first condition and a negative value favors the second; for example, negative Summary−ZFeat favors Z-features, whereas positive SFT−Summary favors LoRA-SFT. A signed point difference alone is not interpreted as evidence of an effect without its paired uncertainty. ‡PATHOGAIT entries are point differences only because two participants do not support reliable participant-level inference.

Resource	Summary−NoEv	Summary−ShufEv	Summary−ZFeat	Summary−Rev.	Summary−Shuf.	SFT−Summary
CARE-PD	$+0.188$ (0.001)	$+0.065$ (0.029)	$+0.187$ (0.002)	$+0.068$ (0.028)	$+0.036$ (0.045)	$+0.124$ (0.43)
GMFCS	$+0.265$ (0.001)	$+0.052$ (0.089)	$+0.115$ (0.004)	-0.057 (0.030)	-0.009 (0.52)	$+0.202$ (0.001)
PARKINSONISM	$+0.070$ (0.62)	$+0.086$ (0.14)	-0.362 (0.001)	$+0.040$ (0.62)	$+0.040$ (0.62)	$+0.146$ (0.47)
ATAXIA	-0.061 (0.60)	0.000 (1.0)	-0.061 (0.60)	0.000 (1.0)	0.000 (1.0)	$+0.061$ (0.60)
PATHOGAIT‡	$+0.021$	-0.002	-0.050	-0.052	-0.024	$+0.382$
ASD-Kinect	-0.023 (0.70)	-0.125 (0.25)	-0.125 (0.24)	-0.030 (0.89)	-0.030 (0.89)	0.000 (1.0)

CARE-PD provides the clearest evidence that the summary contains clip-specific signal: the matched summary condition exceeds both the no-evidence and shuffled-evidence controls. It nevertheless remains below the 0.659 logistic-reference macro-F1. GMFCS improves under SFT but remains sensitive to candidate order. On PARKINSONISM, z-features are substantially better than summaries within the tested model, while the five-subject uncertainty remains wide. ASD-Kinect yields no detectable benefit from summary evidence or SFT in this small test.

S.9 In-Distribution Adaptation and Subject-Level Uncertainty

Table S11: accepted-protocol supervision ladder. Macro-F1 / Cohen's κ. Few-shot uses Qwen2.5-72B; zero-shot and LoRA-SFT cells use Qwen2.5-7B. The feature references are supervised signal probes on the matched deterministic measurements.

Condition	ATAXIA	GMFCS	PARKINSONISM	PATHOGAIT
Zero-shot summary, 7B	0.452 / 0.046	0.110 / -0.008	0.400 / -0.045	0.087 / -0.024
Best few-shot summary	0.697 / 0.395	–	0.561 / 0.188	0.185 / 0.081
LoRA-SFT summary, 7B	0.751 / 0.507	0.255 / 0.030	0.454 / 0.070	0.609 / 0.510
LoRA-SFT feature view, 7B	0.762 / 0.528	–	–	0.687 / 0.611
Logistic reference	0.763 / 0.533	0.388 / 0.229	0.613 / 0.226	0.662 / 0.589
Linear-SVM reference	0.759 / 0.524	0.410 / 0.271	0.583 / 0.168	0.644 / 0.585

Supervision recovers substantial in-distribution signal on ATAXIA and PATHOGAIT. On ATAXIA, feature-view SFT and logistic regression differ by -0.001 macro-F1 under a paired subject-cluster bootstrap, with 95% CI $[-0.044, 0.033]$ and $p = 0.97$ across the three test participants. This supports comparability on the tested split, not clinical equivalence. On GMFCS, summary SFT remains below logistic regression by -0.132 macro-F1, 95% CI $[-0.181, -0.082]$, $p = 0.001$ over 174 participants. PARKINSONISM's SFT interval is wide (0.298–0.659) because only five participants are tested.

PATHOGAIT cannot support a subject-level difference interval. The two participant-specific macro-F1 values for feature-view SFT versus logistic regression are 0.720 versus 0.608 for one participant and 0.661 versus 0.673 for the other. The direction therefore reverses across participants. The aggregate feature-SFT score of 0.687 is described as comparable in point estimate to the linear references, not as evidence of population-level superiority.

S.9.1 Standardized-Suite Participant-Level Reference Checks

Table S12: Standardized leave-one-subject-out reference checks. leave-one-subject-out (LOSO) trains the logistic reference on all but one subject and evaluates the held-out subject, repeating over the available cohort. These checks concern recoverable feature signal, not LLM performance.

Resource	Subjects	LOSO macro-F1	95% subject CI
ATAXIA	20	0.950	[0.874, 1.000]
PARKINSONISM	23	0.561	[0.448, 0.659]
PATHOGAIT	10	0.743	[0.672, 0.810]
ASD-Kinect	100	0.780	[0.690, 0.859]

The LOSO checks show that the deterministic feature representation carries subject-level signal beyond one frozen split on ATAXIA, PATHOGAIT, and ASD-Kinect. PARKINSONISM remains a boundary condition: its point estimate is modest and the interval is broad.

S.9.2 accepted-protocol Participant-Level Reference Checks

Table S13 reports the linear reference under two accepted-protocol evaluations. The frozen-test column uses the designated subject-disjoint test split and participant-cluster confidence intervals. The permutation test is applied to the frozen-test predictions. The LOSO column pools the available accepted-protocol cohort and holds out every participant once. These results use the accepted-protocol feature contract and must not be combined with the standardized-suite LOSO results below.

Table S13: L-only archive; "–" denotes no L result. **accepted-protocol linear-reference checks under frozen-test and leave-one-subject-out protocols.** Values are logistic-regression macro-F1 with 95% participant-level intervals. Permutation p values refer to the frozen-test analysis.

Resource	Frozen test	Permutation p	LOSO	Subjects: frozen / LOSO
GMFCS	0.395 [0.350, 0.438]	0.0002	0.406 [0.374, 0.436]	166 / 344
ATAXIA	0.763 [0.625, 0.902]	0.0002	0.823 [0.757, 0.879]	3 / 20
PARKINSONISM	0.613 [0.402, 0.713]	0.0120	0.586 [0.525, 0.627]	5 / 26
PATHOGAIT	0.662 [0.662, 0.662]†	–	0.609 [0.534, 0.674]	2 / 10
ASD-Kinect	–	–	–	–
CARE-PD	–	–	–	–

†PATHOGAIT has only two frozen-test participants. Its participant-cluster interval is degenerate and is reported for transparency rather than interpreted as population-level uncertainty. No frozen-test permutation claim is made for this condition.

S.10 Tested Cross-Condition Transfer

Transfer is evaluated only between ATAXIA and PATHOGAIT because both can be harmonized to the binary task normal versus abnormal gait. PATHOGAIT's normal class maps to normal and its five performed pathological patterns map to abnormal; the target test split then contains 240 normal and 1,941 abnormal clips. GMFCS is ordinal without a healthy class, and PARKINSONISM predicts severity rather than normality, so neither enters this experiment.

Source-dataset training statistics standardize the named features. No target labels, target moments, or target examples are used. ATAXIA uses MediaPipe pose conventions and PATHOGAIT uses Kinect conventions; thus the experiment jointly changes gait condition, sensing pipeline, skeleton layout, and cohort. It is a deliberately difficult dataset-pair transfer test, not an isolation of disease shift alone.

Table S14: Bidirectional ATAXIA–PATHOGAIT transfer. Accuracy / macro-F1 / Cohen's κ after harmonizing the task to normal versus abnormal. The target-majority baseline is computed in the target label distribution.

Training resource	Evaluation resource	Model result	Target-majority baseline
ATAXIA	ATAXIA (in distribution)	– / – / 0.549	–
ATAXIA	PATHOGAIT (transfer)	0.656 / 0.496 / 0.057	0.890 / 0.471 / 0.000
PATHOGAIT	PATHOGAIT (in distribution)	0.984 / 0.959 / 0.917	–
PATHOGAIT	ATAXIA (transfer)	0.686 / 0.407 / 0.000	0.686 / 0.407 / 0.000

ATAXIA-to-PATHOGAIT is 23.4 percentage points below the target majority baseline in accuracy and only 0.025 above it in macro-F1, with $\kappa = 0.057$. PATHOGAIT-to-ATAXIA exactly reproduces the target majority result. Reliable transfer is therefore not observed on this tested bidirectional dataset pair. The result does not establish a general inability to transfer across clinical gait conditions.

S.11 Per-Class Performance and Confusion Matrices

All tables and figures in this section are recomputed from the released standardized prediction files for Qwen2.5-7B-Instruct. They compare zero-shot motion summaries, zero-shot z-scored feature descriptions, and motion-summary LoRA-SFT. Rows of every confusion matrix are true classes; columns are predicted classes. Each cell shows the integer count and the percentage within its true class. The complete candidate set is used when computing macro-F1, even if a class is never predicted.

Table S15: Binary S metrics. Sensitivity is recall of the explicitly named positive class, and specificity is recall of its complement. Case-sensitive source label identities are preserved.

Dataset	Condition	Positive class	Sensitivity	Specificity	Balanced acc.
ASD-Kinect	Zero-shot summary	ASD	0.000	0.900	0.450
ASD-Kinect	Zero-shot z-features	ASD	0.100	1.000	0.550
ASD-Kinect	LoRA-SFT summary	ASD	0.900	0.000	0.450
ATAXIA	Zero-shot summary	mimicked_ataxia	0.000	0.750	0.375
ATAXIA	Zero-shot z-features	mimicked_ataxia	0.000	1.000	0.500
ATAXIA	LoRA-SFT summary	mimicked_ataxia	1.000	0.000	0.500
PARKINSONISM	Zero-shot summary	severe	0.067	1.000	0.533
PARKINSONISM	Zero-shot z-features	severe	0.667	0.857	0.762
PARKINSONISM	LoRA-SFT summary	severe	0.867	0.286	0.576

The binary tables expose clinically relevant asymmetries hidden by accuracy. PARKINSONISM zero-shot summary sensitivity to severe clips is only 0.067 despite 0.517 accuracy; the z-feature view increases severe sensitivity to 0.667 while retaining 0.857 specificity. ATAXIA and ASD-Kinect each show a condition-dependent single-class collapse on their small standardized splits, making a single accuracy value unsuitable for interpretation.

Table S16: Ordinal S error structure. MAE and quadratic-weighted κ use the ordered numeric labels.

Dataset	Condition	Macro-F1	MAE	Quadratic κ
CARE-PD	Zero-shot summary	0.321	0.717	0.217
CARE-PD	Zero-shot z-features	0.133	1.211	0.004
CARE-PD	LoRA-SFT summary	0.445	0.651	0.331
GMFCS	Zero-shot summary	0.265	0.906	0.129
GMFCS	Zero-shot z-features	0.150	1.141	0.057
GMFCS	LoRA-SFT summary	0.467	0.420	0.618

On GMFCS, SFT reduces MAE from 0.906 to 0.420 and raises quadratic-weighted κ from 0.129 to 0.618. Neither the zero-shot summary nor the LoRA-SFT summary condition correctly predicts a level-4 clip; the z-scored feature condition correctly predicts one of the three level-4 clips. This support remains too small for stable class-specific inference.

Table S17: ATAXIA per-class S results. Precision, recall, and F1 are recomputed from committed predictions; all task classes are retained.

Condition	Class	Support	Precision	Recall	F1
Zero-shot summary	mimicked_ataxia	4	0.000	0.000	0.000
Zero-shot summary	normal	4	0.429	0.750	0.545
Zero-shot z-features	mimicked_ataxia	4	0.000	0.000	0.000
Zero-shot z-features	normal	4	0.500	1.000	0.667
LoRA-SFT summary	mimicked_ataxia	4	0.500	1.000	0.667
LoRA-SFT summary	normal	4	0.000	0.000	0.000




Figure S1: ATAXIA standardized confusion matrices. Eight clips from four participants make these descriptive rather than rank-defining.

Table S18: GMFCS per-class S results. Precision, recall, and F1 are recomputed from committed predictions; all task classes are retained.

Condition	Class	Support	Precision	Recall	F1
Zero-shot summary	1	98	0.420	0.347	0.380
Zero-shot summary	2	97	0.361	0.134	0.195
Zero-shot summary	3	57	0.352	0.772	0.484
Zero-shot summary	4	3	0.000	0.000	0.000
Zero-shot z-features	1	98	0.000	0.000	0.000
Zero-shot z-features	2	97	0.293	0.124	0.174
Zero-shot z-features	3	57	0.237	0.772	0.362
Zero-shot z-features	4	3	0.036	0.333	0.065
LoRA-SFT summary	1	98	0.611	0.592	0.601
LoRA-SFT summary	2	97	0.514	0.557	0.535
LoRA-SFT summary	3	57	0.745	0.719	0.732
LoRA-SFT summary	4	3	0.000	0.000	0.000




Figure S2: GMFCS standardized confusion matrices. SFT improves levels 1–3 but the three level-4 clips are all predicted as level 3.

Table S19: PARKINSONISM per-class S results. Precision, recall, and F1 are recomputed from committed predictions; all task classes are retained.

Condition	Class	Support	Precision	Recall	F1
Zero-shot summary	mild	14	0.500	1.000	0.667
Zero-shot summary	severe	15	1.000	0.067	0.125
Zero-shot z-features	mild	14	0.706	0.857	0.774
Zero-shot z-features	severe	15	0.833	0.667	0.741
LoRA-SFT summary	mild	14	0.667	0.286	0.400
LoRA-SFT summary	severe	15	0.565	0.867	0.684




Figure S3: PARKINSONISM standardized confusion matrices. The z-feature view provides the most balanced class recovery in this five-subject test.

Table S20: PATHOGAIT per-class S results. Precision, recall, and F1 are recomputed from committed predictions; all task classes are retained.

Condition	Class	Support	Precision	Recall	F1
Zero-shot summary	antalgic	240	0.000	0.000	0.000
Zero-shot summary	lurch	240	0.027	0.004	0.007
Zero-shot summary	normal	240	0.184	1.000	0.310
Zero-shot summary	steppage	240	0.000	0.000	0.000
Zero-shot summary	stiff_legged	240	0.000	0.000	0.000
Zero-shot summary	trendelenburg	240	0.174	0.067	0.096
Zero-shot z-features	antalgic	240	0.038	0.004	0.008
Zero-shot z-features	lurch	240	0.114	0.017	0.029
Zero-shot z-features	normal	240	0.173	0.700	0.278
Zero-shot z-features	steppage	240	0.117	0.087	0.100
Zero-shot z-features	stiff_legged	240	0.000	0.000	0.000
Zero-shot z-features	trendelenburg	240	0.428	0.408	0.418
LoRA-SFT summary	antalgic	240	0.462	0.350	0.398
LoRA-SFT summary	lurch	240	0.379	0.371	0.375
LoRA-SFT summary	normal	240	0.720	0.558	0.629
LoRA-SFT summary	steppage	240	0.319	0.438	0.369
LoRA-SFT summary	stiff_legged	240	0.640	0.808	0.715
LoRA-SFT summary	trendelenburg	240	0.239	0.204	0.220




Figure S4: PATHOGAIT standardized confusion matrices. Zero-shot summary predictions concentrate on normal; SFT distributes predictions across all six patterns but remains uneven, particularly for Trendelenburg gait. The z-feature condition contains one unparsed lurch output, shown as an error.

Table S21: ASD-Kinect per-class S results. Precision, recall, and F1 are recomputed from committed predictions; all task classes are retained.

Condition	Class	Support	Precision	Recall	F1
Zero-shot summary	ASD	10	0.000	0.000	0.000
Zero-shot summary	typically_developing	10	0.474	0.900	0.621
Zero-shot z-features	ASD	10	1.000	0.100	0.182
Zero-shot z-features	typically_developing	10	0.526	1.000	0.690
LoRA-SFT summary	ASD	10	0.474	0.900	0.621
LoRA-SFT summary	typically_developing	10	0.000	0.000	0.000




Figure S5: ASD-Kinect standardized confusion matrices. One clip per participant yields 20 independent observations, but the small class supports make all estimates coarse.

Table S22: CARE-PD per-class S results. Precision, recall, and F1 are recomputed from committed predictions; all task classes are retained.

Condition	Class	Support	Precision	Recall	F1
Zero-shot summary	0	240	0.528	0.471	0.498
Zero-shot summary	1	247	0.455	0.490	0.472
Zero-shot summary	2	160	0.292	0.338	0.313
Zero-shot summary	3	18	0.000	0.000	0.000
Zero-shot z-features	0	240	0.000	0.000	0.000
Zero-shot z-features	1	247	0.310	0.073	0.118
Zero-shot z-features	2	160	0.275	0.856	0.416
Zero-shot z-features	3	18	0.000	0.000	0.000
LoRA-SFT summary	0	240	0.519	0.683	0.590
LoRA-SFT summary	1	247	0.414	0.441	0.427
LoRA-SFT summary	2	160	0.304	0.150	0.201
LoRA-SFT summary	3	18	1.000	0.389	0.560




Figure S6: CARE-PD UPDRS-gait confusion matrices. The evaluation is restricted to scores 0–3 from one task. Score 3 has 18 clips and should not be interpreted as a precise severity-specific estimate.

The six confusion analyses refine the aggregate conclusion. Zero-shot failure is frequently a class-allocation failure rather than uniformly low recall: ATAXIA, ASD-Kinect, and PARKINSONISM each approach a single-class decision under at least one view. GMFCS and CARE-PD errors are predominantly adjacent or near-adjacent under SFT, which is reflected by improved ordinal metrics even when macro-F1 remains below the feature references. PATHOGAIT SFT recovers substantial normal and stiff-legged performance but not a balanced six-class mapping.

S.12 Reproducibility Contract and Evidence Limits

The S data model expects records and subject-level split manifests, native/canonical poses, raw and train-scaled features, label-free summaries, prompts, and per-clip predictions. The reorganized repository actually contains 55 prediction files with raw outputs, their summaries, scoring/control/training code, reference and statistical JSONs, the accepted manuscript snapshot, and this revision. Complete source poses, S records/feature/summary input tables, split-generation inputs, LoRA weights, and complete training logs are not present in the upstream commit and are not claimed to be bundled. Their absence limits end-to-end reproduction; the shipped audit regenerates prediction metrics and validates within-dataset record alignment without those assets.

The following boundaries apply to all reported conclusions:

1. GaitEval measures dataset-specified classification grounded in pose-derived evidence; it does not validate autonomous diagnosis, treatment choice, or clinical deployment.
2. ATAXIA and PATHOGAIT contain performed rather than patient gait; CARE-PD uses a task-specific clinical subset, and ASD-Kinect has the source-provenance caveat stated above. These are population limitations within one six-dataset benchmark.
3. Skeleton estimation removes appearance cues but introduces sensor-, estimator-, and layout-specific noise. The deterministic feature set is interpretable but incomplete, and unsigned asymmetry loses laterality.

4. Test cohorts are small for ATAXIA, PARKINSONISM, PATHOGAIT, ASD-Kinect, and the highest ordinal severity classes. Subject-level intervals, per-class support, and confusion matrices must accompany point estimates.
5. In-distribution SFT demonstrates learning of supplied task mappings. It does not by itself show acquisition of transferable clinical knowledge.
6. Cross-condition evidence is restricted to the harmonized ATAXIA–PATHOGAIT pair and combines condition, cohort, sensor, and representation shift. No broader cross-disease transfer conclusion follows.

S.13 Six-Dataset Coverage and Contract Reconciliation

All six datasets are benchmark members. S/L identify measurement provenance. A complete same-contract seven-condition Qwen-7B grid exists across the six datasets (42 cells). Two S raw-feature runs and ten S five-family runs exist for ASD-Kinect and CARE-PD; their corresponding S runs for the other datasets are missing. The 12-class CARE-PD union contributes one separate diagnostic. Thus the archive has 55 prediction files, not a fully evaluated Cartesian product.

Table S23: Completed and missing experiments across six datasets. S = standardized prediction-backed result; L only = retained accepted-protocol result with no S counterpart; "–" = not executed in either applicable result lineage. All datasets have S summary/z-feature zero-shot, summary SFT, LR/SVM, and four evidence/order controls. The five-family column excludes the separate Qwen-7B anchor. Coordinate coverage is model/view-specific; see Table S8.

Dataset	Five families	ZS summary/z	ZS raw feat.	Summary SFT	LR/SVM+controls	Few-shot	Feature SFT	Coordinates	Transfer
ASD-Kinect	S	S	S	S	S	–	–	–	–
ATAXIA	L only	S	–	S	S	L only	L only	L only	L pair
CARE-PD	S	S	S	S	S	–	–	–	–
GMFCS	L only	S	–	S	S	–	–	L norm.	–
PARKINSONISM	L only	S	–	S	S	L only	–	L norm.	–
PATHOGAIT	L only	S	–	S	S	L only	L only	L only	L pair

Table S24: Task-matched standardized references for all six datasets (S). Unlike retained L cells, every row uses the same S feature/split contract. CARE-PD is four-class UPDRS gait with 665 clips, not the 970-clip mixed-task diagnostic. LR/SVM use the same features as the S named-feature LLM views.

Dataset	n	Subjects	Chance mF1	LR Acc.	LR mF1	LR κ	SVM Acc.	SVM mF1	SVM κ
ASD-Kinect	20	20	0.490	0.700	0.697	0.400	0.750	0.744	0.500
ATAXIA	8	4	0.488	0.875	0.873	0.750	0.875	0.873	0.750
CARE-PD	665	24	0.250	0.621	0.659	0.437	0.621	0.650	0.435
GMFCS	255	149	0.250	0.639	0.579	0.458	0.647	0.571	0.469
PARKINSONISM	29	5	0.494	0.586	0.561	0.187	0.586	0.574	0.183
PATHOGAIT	1440	2	0.166	0.881	0.881	0.858	0.897	0.897	0.877

Table S25: Shared-contract six-dataset input views (S, Qwen2.5-7B). Cells report accuracy / macro-F1 / κ on identical test records within each dataset. Raw-feature runs exist only where shown; "–" is an unexecuted configuration, not zero performance. Coordinates have no S LLM runs.

Dataset	Motion summary	Raw named features	Z-scored named features
ASD-Kinect	0.450 / 0.310 / −0.100	0.500 / 0.333 / 0.000	0.550 / 0.436 / 0.100
ATAXIA	0.375 / 0.273 / −0.250	–	0.500 / 0.333 / 0.000
CARE-PD	0.433 / 0.321 / 0.152	0.332 / 0.221 / 0.039	0.233 / 0.133 / 0.020
GMFCS	0.357 / 0.265 / 0.099	–	0.224 / 0.150 / −0.003
PARKINSONISM	0.517 / 0.396 / 0.065	–	0.759 / 0.757 / 0.520
PATHOGAIT	0.178 / 0.069 / 0.014	–	0.203 / 0.139 / 0.043

Known accepted-version discrepancies. The archived L GMFCS split descriptions are internally inconsistent: the main tables use 899 clips, a supplementary resource table lists 885, and corrected-view cells refer to 866. These L values are preserved as historical measurements and are not relabeled leakage-free or substituted for the fully subject-disjoint S GMFCS evaluation (255 clips, 149 participants). CARE-PD task-matched references use 665 clips and four labels; the archived 970-clip, 12-label reference is a different task and is excluded from the primary comparisons. The master result Markdown in the upstream archive contains this old reference and stale participant counts; normalized JSONs and generated audits take precedence.

Prompt and parser differences. The L flat prompt in `view_run.py` includes a 3D-skeleton and biomechanical-dimension preamble. The S prompt in `v21_llm_runner.py` uses a shorter skeleton-sequence preamble and separately renders named features. The L parser has a unique truncated-label-prefix fallback; S accepts complete boundary-anchored candidate labels only. These are implementation differences even where model identifiers and deterministic decoding match. Missing S experiments cannot be reconstructed by merely copying L scores.

Evidence assets still unavailable. The collection contains committed results and code, not a new execution of the experiments. Recovering the original S records, pose/feature/summary layers and training artifacts is necessary to independently rerun the end-to-end pipeline. The canonical 19-joint data layer is not itself evidence that the 12-joint L coordinate-input experiment was run under S. No extra experiments were executed for this manuscript revision.

Recomputed binary-label identity. ASD-Kinect uses the positive label `ASD`. Recomputing from the committed S predictions gives summary sensitivity/specificity 0.000/0.900, z-feature 0.100/1.000, and summary-SFT 0.900/0.000. These numerical values agree with the accepted binary-metric table; the regenerated table preserves them and standardizes the displayed label identity. This is a consistency check, not a correction to the accepted binary scores or an extra experiment.

S Detailed protocol-scoped tables retained from the expanded draft

Table S26: Primary zero-shot motion-summary benchmark. Cells report accuracy / macro-F1 / Cohen's κ. Superscripts identify the measurement contract (L or S), not dataset status. L/S rows have different preprocessing and splits and are not a single homogeneous six-dataset rerun. Parentheses retain the accepted L majority convention; S uses the training-majority predictor evaluated on test. The S majority convention is not assumed identical to the archived L definition. Gray sub-rows report the proportion of predictions assigned to the model's most frequently predicted class. Bold marks the highest macro-F1 within each dataset. Unparsable outputs are counted as errors.

Dataset (Maj. Acc.)	Llama-3.3-70B	Qwen2.5-72B	Gemma-3-27B	GLM-4-32B	DeepSeek-R1-32B
ASD-Kinect^S (0.500)	0.500 / 0.451 / 0.000	0.450 / 0.373 / −0.100	0.450 / 0.310 / −0.100	0.450 / 0.373 / −0.100	0.600 / **0.583** / 0.200
top-class share	0.80	0.85	0.95	0.85	0.70
ATAXIA^L (0.686)	0.686 / 0.407 / 0.000	0.685 / 0.406 / −0.002	0.686 / 0.407 / 0.000	0.686 / 0.407 / 0.000	0.684 / **0.408** / −0.002
top-class share	1.00	1.00	1.00	1.00	0.997
CARE-PD^S (0.361)	0.441 / 0.262 / 0.119	0.445 / 0.268 / 0.129	0.439 / 0.249 / 0.113	0.441 / **0.350** / 0.124	0.398 / 0.295 / 0.099
top-class share	0.71	0.64	0.72	0.56	0.45
GMFCS^L (0.364)	0.352 / 0.210 / 0.018	0.369 / **0.218** / 0.033	0.301 / 0.158 / 0.025	0.259 / 0.123 / 0.000	0.307 / 0.189 / 0.015
top-class share	0.72	0.78	0.87	0.93	0.64
PARKINSONISM^L (0.583)	0.583 / 0.368 / 0.000	0.575 / **0.472** / 0.035	0.583 / 0.368 / 0.000	0.583 / 0.368 / 0.000	0.583 / 0.368 / 0.000
top-class share	1.00	0.86	1.00	1.00	1.00
PATHOGAIT^L (0.226)	0.159 / 0.053 / −0.010	0.155 / 0.054 / −0.009	0.165 / 0.047 / −0.001	0.141 / 0.059 / −0.069	0.166 / **0.094** / −0.007
top-class share	0.94	0.94	1.00	0.51	0.48

Table S27: Comparison of four core input-view families. Raw coordinates, normalized coordinates, motion summaries, and named feature vectors constitute the four core views. The named-feature view is evaluated in both its original scale and a training-statistics z-scored form; the latter is a derived scaling control rather than a fifth modality. All cells report accuracy / macro-F1 / κ. Dataset superscripts identify L/S contracts. †Raw-coordinate cells use Llama-3.3-70B on 150-clip subsets, not Qwen-7B. ^{s}Retained corrected-split L GMFCS cells. "–" means not evaluated, including both coordinate views for ASD-Kinect and CARE-PD.

Input view	ASD-Kinect^S	ATAXIA^L	CARE-PD^S	GMFCS^L	PARKINSONISM^L	PATHOGAIT^L
Raw coordinates†	–	0.573 / 0.323 / 0.009	–	–	–	0.093 / 0.083 / 0.038
Normalized coordinates	–	0.316 / 0.244 / 0.002	–	0.282 / 0.110 / 0.000^s	0.442 / 0.441 / −0.095	0.110 / 0.034 / 0.000
Motion summary	0.450 / 0.310 / −0.100	0.692 / 0.452 / 0.046	0.433 / 0.321 / 0.152	0.249 / 0.110 / −0.008^s	0.550 / 0.400 / −0.045	0.142 / 0.087 / −0.024
Named feature vector	0.500 / 0.333 / 0.000	0.382 / 0.347 / 0.057	0.332 / 0.221 / 0.039	0.343 / **0.245** / 0.007^s	0.417 / 0.294 / 0.000	–
Z-scored named feature vector	0.550 / 0.436 / 0.100	0.583 / **0.495** / −0.008	0.233 / 0.133 / 0.020	0.185 / 0.100 / −0.049^s	0.508 / **0.493** / −0.014	0.150 / **0.130** / −0.011

Table S28: Shared-contract six-dataset input views (S, Qwen2.5-7B). Cells report accuracy / macro-F1 / κ on identical test records within each dataset. Raw-feature runs exist only where shown; "–" is an unexecuted configuration, not zero performance. Coordinates have no S LLM runs.

Dataset	Motion summary	Raw named features	Z-scored named features
ASD-Kinect	0.450 / 0.310 / −0.100	0.500 / 0.333 / 0.000	0.550 / 0.436 / 0.100
ATAXIA	0.375 / 0.273 / −0.250	–	0.500 / 0.333 / 0.000
CARE-PD	0.433 / 0.321 / 0.152	0.332 / 0.221 / 0.039	0.233 / 0.133 / 0.020
GMFCS	0.357 / 0.265 / 0.099	–	0.224 / 0.150 / −0.003
PARKINSONISM	0.517 / 0.396 / 0.065	–	0.759 / 0.757 / 0.520
PATHOGAIT	0.178 / 0.069 / 0.014	–	0.203 / 0.139 / 0.043

Table S29: Same-feature linear references. Chance mF1 is the simulated stratified-chance macro-F1. The reference cells report accuracy, macro-F1, and Cohen's κ. Bold marks the stronger linear reference for each metric. Superscripts identify L/S measurement contracts; matched S references for every dataset also appear in Table S30.

Dataset	Classes	Maj. Acc.	Chance mF1	LR Acc.	LR mF1	LR κ	SVM Acc.	SVM mF1	SVM κ	n_{te}
ASD-Kinect^S	2	0.500	0.490	0.700	0.697	0.400	0.750	0.744	0.500	20
ATAXIA^L	2	0.686	0.498	**0.778**	**0.763**	**0.533**	0.774	0.759	0.524	1647
CARE-PD^S	4	0.361	0.250	0.621	0.659	0.437	0.621	0.650	0.435	665
GMFCS^L	4	0.364	0.249	0.452	0.387	0.229	**0.492**	**0.410**	**0.271**	899
PARKINSONISM^L	2	0.583	0.499	**0.625**	**0.613**	**0.226**	0.600	0.583	0.168	120
PATHOGAIT^L	6	0.226	0.166	**0.659**	**0.662**	**0.589**	0.656	0.644	0.585	2181

Table S30: Task-matched standardized references for all six datasets (S). Unlike retained L cells, every row uses the same S feature/split contract. CARE-PD is four-class UPDRS gait with 665 clips, not the 970-clip mixed-task diagnostic. LR/SVM use the same features as the S named-feature LLM views.

Dataset	n	Subjects	Chance mF1	LR Acc.	LR mF1	LR κ	SVM Acc.	SVM mF1	SVM κ
ASD-Kinect	20	20	0.490	0.700	0.697	0.400	0.750	0.744	0.500
ATAXIA	8	4	0.488	0.875	0.873	0.750	0.875	0.873	0.750
CARE-PD	665	24	0.250	0.621	0.659	0.437	0.621	0.650	0.435
GMFCS	255	149	0.250	0.639	0.579	0.458	0.647	0.571	0.469
PARKINSONISM	29	5	0.494	0.586	0.561	0.187	0.586	0.574	0.183
PATHOGAIT	1440	2	0.166	0.881	0.881	0.858	0.897	0.897	0.877

Table S31: Task-specific adaptation ladder. LLM cells report macro-F1 / Cohen's κ; reference columns report macro-F1. Zero-shot and few-shot use Qwen2.5-72B. The scale-matched zero-shot anchor and SFT columns use Qwen2.5-7B-Instruct. Bold SFT values match or exceed the stronger linear-reference point estimate. "–" denotes configurations not evaluated. Superscripts identify L/S measurements; S few-shot and feature-view SFT are unavailable for all six datasets. No missing S rerun is filled using an L result. The L PATHOGAIT few-shot cell uses a 600-clip subset; the zero-shot and SFT cells use their stated full test partitions, so its gain is not a paired full-test estimate.

Dataset	Zero-shot	Zero-shot (7B)	Few-shot	SFT: summary	SFT: features	SVM	LogReg
ASD-Kinect^S	0.373 / −0.100	0.310 / −0.100	–	0.310 / −0.100	–	0.744	0.697
ATAXIA^L	0.406 / −0.002	0.452 / 0.046	0.697 / 0.395	0.751 / 0.507	**0.762 / 0.528**	0.759	0.763
CARE-PD^S	0.268 / 0.129	0.321 / 0.152	–	0.445 / 0.168	–	0.650	0.659
GMFCS^L	0.218 / 0.033	0.110 / −0.008	–	0.255 / 0.030	–	0.410	0.387
PARKINSONISM^L	0.472 / 0.035	0.400 / −0.045	0.561 / 0.188	0.454 / 0.070	–	0.583	0.613
PATHOGAIT^L	0.054 / −0.009	0.087 / −0.024	0.185 / 0.081	0.609 / 0.510	**0.687 / 0.611**	0.644	0.662

Table S32: Bidirectional ATAXIA–PATHOGAIT transfer. Models use z-scored feature descriptions. The target-majority column reports accuracy / macro-F1. PATHOGAIT in-distribution κ is computed on the binarized task and is not comparable with its six-class result in Table S31. OOD denotes out-of-distribution evaluation. This is an L two-dataset probe; S transfer is not executed for any pair.

Train → Test	In-dist. κ	OOD Acc. / mF1 / κ	Target majority
ATAXIA → PATHOGAIT	0.549	0.656 / 0.496 / 0.057	0.890 / 0.471
PATHOGAIT → ATAXIA	0.917	0.686 / 0.407 / 0.000	0.686 / 0.407

S Source examples and release boundary

Figure 1 illustrates source resources rather than the evaluated test clips. No RGB images are supplied to the text-only models. The source publications and their original references in the main paper remain the attribution basis. Derived plots and vector diagrams are newly drawn; source-example crops retain their separate attribution and license notes in the project repository.

The six-dataset S scoring package reproduces point estimates from committed predictions. Reported reference scores and archived cluster-bootstrap outputs are preserved as source measurements, not claimed to be retrained or independently regenerated without their inputs. Full source pose, feature, summary, and split files and adapters are required for end-to-end inference/training reproduction. The code validates participant separation when those split files are supplied and fails on missing, empty, or overlapping inputs.

Resource-example credits. ASD-Kinect uses a cropped frame at 0.5 s from the original `Svideo.avi`, child-ASD/1/video, in the official Zenodo archive. ATAXIA uses captured-video illustrations from Khalil et al., *Diagnosis of Cerebellar Ataxia Based on Gait Analysis Using Human Pose Estimation*, IEEE IECBES2022 (DOI:10.1109/IECBES54088.2022.10079396). CARE-PD uses a crop of the official benchmark input-mesh example. GMFCS uses a newly rendered skeleton from mobile-gaitlab's public demo keypoints (frame60), not confirmed as an evaluated participant. PARKINSONISM uses a cropped recording illustration from Deng et al., *npj Parkinson's Disease*10,122(2024), DOI:10.1038/s41531-024-00742-x (CC BY4.0). PATHOGAIT renders recorded joints from the official source repository. Crops and skeleton renderings were made for this overview. These are resource illustrations, not clip-matched model evidence. Source-paper image reuse terms and any unlicensed derived display must be confirmed before final distribution; dataset availability alone does not establish image permission.

S Reviewer-requested qualitative examples

Table S33: Prediction-backed qualitative decisions across all six datasets. Outputs are verbatim from committed logs. No matching pose or prompt is inferred.

Dataset / view	True label	Raw output	Correct
asd_kinect / zs	typically_developing	typically_developing	yes
asd_kinect / zs	ASD	typically_developing	no
ataxia / zs	normal	normal	yes
ataxia / zs	mimicked_ataxia	normal	no
care_pd / zs	0	UPDRS gait score 0	yes
care_pd / zs	1	UPDRS gait score 0	no
gmfcs / zs	3	GMFCS level 3	yes
gmfcs / zs	2	GMFCS level 1	no
parkinsonism / zs	severe	severe	yes
parkinsonism / zs	severe	mild	no
pathogait / zs	normal	normal	yes
pathogait / zs	antalgic	normal	no

For each dataset, the examples are deterministic selections from the committed predictions, showing one correct and one incorrect summary or z-feature decision where available. Raw model outputs are shown verbatim; true labels are evaluation annotations, not model-visible metadata. These diagnostics are not representative sampling and do not establish reasoning faithfulness. The original S input prompts and matching pose records are absent, so no numerical evidence is reconstructed or invented for these cases. This part of the qualitative request remains incomplete pending those records.

References

[1] Jacquelin Perry. *Gait Analysis: Normal and Pathological Function*. SLACK Incorporated, 1992.

[2] Richard Baker. Gait analysis methods in rehabilitation. *Journal of NeuroEngineering and Rehabilitation*, 3:4, 2006.

[3] Alberto Muro-de-la Herran, Begonya Garcia-Zapirain, and Amaia Mendez-Zorrilla. Gait analysis methods: An overview of wearable and non-wearable systems, highlighting clinical applications. *Sensors*, 14(2):3362–3394, 2014.

[4] Zhe Cao, Tomas Simon, Shih-En Wei, and Yaser Sheikh. Realtime multi-person 2D pose estimation using part affinity fields. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 7291–7299, 2017.

[5] Camillo Lugaresi, Jiuqiang Tang, Hadon Nash, Chris McClanahan, Esha Uboweja, Michael Hays, Fan Zhang, Chuo-Ling Chang, Ming Guang Yong, Juhyun Lee, Wan-Teh Chang, Wei Hua, Manfred Georg, and Matthias Grundmann. MediaPipe: A framework for building perception pipelines. *arXiv preprint arXiv:1906.08172*, 2019.

[6] Valentin Bazarevsky, Ivan Grishchenko, Karthik Raveendran, Tyler Zhu, Fan Zhang, and Matthias Grundmann. BlazePose: On-device real-time body pose tracking. *arXiv preprint arXiv:2006.10204*, 2020.

[7] Jan Stenum, Kendra M. Cherry-Allen, Connor O. Pyles, Rachel D. Reetzke, Michael F. Vignos, and Ryan T. Roemmich. Applications of pose estimation in human health and performance across the lifespan. *Sensors*, 21(21):7315, 2021.

[8] Jan Stenum, Melody M. Hsu, Alexander Y. Pantelyat, and Ryan T. Roemmich. Clinical gait analysis using video-based pose estimation: Multiple perspectives, clinical populations, and measuring change. *PLOS Digital Health*, 3(3):e0000467, 2024.

[9] David A. Winter. *Biomechanics and Motor Control of Human Movement*. John Wiley & Sons, 4th edition, 2009.

[10] Michael H. Schwartz and Adam Rozumalski. The gait deviation index: A new comprehensive index of gait pathology. *Gait & Posture*, 28(3):351–357, 2008.

[11] Hisham Khalil, Ahmed Mohamed Saad Emam Saad, and Uswah Khairuddin. Diagnosis of cerebellar ataxia based on gait analysis using human pose estimation: A deep learning approach. In *2022 IEEE-EMBS Conference on Biomedical Engineering and Sciences (IECBES)*, pages 201–206, 2022.

[12] Daniel Deng, Jill L. Ostrem, Vy Nguyen, Daniel D. Cummins, Julia Sun, Anupam Pathak, Simon Little, and Reza Abbasi-Asl. Interpretable video-based tracking and quantification of parkinsonism clinical motor states. *npj Parkinson's Disease*, 10:122, 2024.

[13] Łukasz Kidziński, Bryan Yang, Jennifer L. Hicks, Apoorva Rajagopal, Scott L. Delp, and Michael H. Schwartz. Deep neural networks enable quantitative movement analysis using single-camera videos. *Nature Communications*, 11:4054, 2020.

[14] Mandy Lu, Kathleen L. Poston, Adolf Pfefferbaum, Edith V. Sullivan, Li Fei-Fei, Kilian M. Pohl, Juan Carlos Niebles, and Ehsan Adeli. Vision-based estimation of MDS-UPDRS gait scores for assessing parkinson's disease motor severity. In *Medical Image Computing and Computer Assisted Intervention (MICCAI)*, pages 637–647, 2020.

[15] Kooksung Jun, Yongwoo Lee, Sanghyub Lee, Deok-Won Lee, and Mun Sang Kim. Pathological gait classification using Kinect v2 and gated recurrent neural networks. *IEEE Access*, 8:139881–139891, 2020.

[16] Juri Opitz and Sebastian Burst. Macro F1 and Macro F1. *arXiv preprint arXiv:1911.03347*, 2019.

[17] Marina Sokolova and Guy Lapalme. A systematic analysis of performance measures for classification tasks. *Information Processing & Management*, 45(4):427–437, 2009.

[18] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D. Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 1877–1901, 2020.

[19] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022.

[20] Sheldon R. Simon. Quantification of human motion: Gait analysis—benefits and limitations to its application to clinical problems. *Journal of Biomechanics*, 37(12):1869–1880, 2004.

[21] Alexander Mathis, Pranav Mamidanna, Kevin M. Cury, Taiga Abe, Venkatesh N. Murthy, Mackenzie Weygandt Mathis, and Matthias Bethge. DeepLabCut: Markerless pose estimation of user-defined body parts with deep learning. *Nature Neuroscience*, 21(9):1281–1289, 2018.

[22] Scott D. Uhlrich, Antoine Falisse, Łukasz Kidziński, Julie Muccini, Michael Ko, Akshay S. Chaudhari, Jennifer L. Hicks, and Scott L. Delp. OpenCap: Human movement dynamics from smartphone videos. *PLOS Computational Biology*, 19(10): e1011462, 2023.

[23] Tanmay T. Verlekar, Henri De Vroey, Kurt Claeys, Hans Hallez, Luís D. Soares, and Paulo L. Correia. Estimation and validation of temporal gait features using a markerless 2D video system. *Computer Methods and Programs in Biomedicine*, 175:45–51, 2019.

[24] Masataka Yamamoto, Koji Shimatani, Masaki Hasegawa, Yuichi Kurita, Yuto Ishige, and Hiroshi Takemura. Accuracy of temporo-spatial and lower limb joint kinematics parameters using OpenPose for various gait patterns with orthosis. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, 29:2666–2675, 2021.

[25] Andrea Sabo, Carolina Gorodetsky, Alfonso Fasano, Andrea Iaboni, and Babak Taati. Concurrent validity of Zeno instrumented walkway and video-based gait features in adults with parkinson's disease. *IEEE Journal of Translational Engineering in Health and Medicine*, 10:2100511, 2022.

[26] Sijie Yan, Yuanjun Xiong, and Dahua Lin. Spatial temporal graph convolutional networks for skeleton-based action recognition. In *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence (AAAI)*, pages 7444–7452, 2018.

[27] Lei Shi, Yifan Zhang, Jian Cheng, and Hanqing Lu. Two-stream adaptive graph convolutional networks for skeleton-based action recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 12026–12035, 2019.

[28] Ziyu Liu, Hongwen Zhang, Zhenghao Chen, Zhiyong Wang, and Wanli Ouyang. Disentangling and unifying graph convolutions for skeleton-based action recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 143–152, 2020.

[29] Elham Dolatabadi, Babak Taati, and Alex Mihailidis. An automated classification of pathological gait using unobtrusive sensing technology. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, 25(12):2336–2346, 2017.

[30] Tanmay T. Verlekar, Luís D. Soares, and Paulo L. Correia. Automatic classification of gait impairments using a markerless 2D video-based system. *Sensors*, 18(9):2743, 2018.

[31] Javier Ortells, María Trinidad Herrero-Ezquerro, and Ramón A. Mollineda. Vision-based gait impairment analysis for aided diagnosis. *Medical & Biological Engineering & Computing*, 56(9):1553–1564, 2018.

[32] Jung Hwan Shin, Ri Yu, Jed Noel Ong, Chan Young Lee, Seung Ho Jeon, Hwanpil Park, Han Joon Kim, Jehee Lee, and Beomseok Jeon. Quantitative gait analysis using a pose-estimation algorithm with a single 2D-Video of Parkinson's Disease patients. *Journal of Parkinson's Disease*, 11(3):1271–1283, 2021.

[33] Andrea Sabo, Sina Mehdizadeh, Kimberley-Dale Ng, Andrea Iaboni, and Babak Taati. Assessment of Parkinsonian Gait in older adults with dementia via human pose tracking in video data. *Journal of NeuroEngineering and Rehabilitation*, 17:97, 2020.

[34] Qingyi Zeng, Peipei Liu, Ningbo Yu, Jialing Wu, Weiguang Huo, and Jianda Han. Video-based quantification of gait impairments in Parkinson's Disease using skeleton–silhouette fusion convolution network. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*, 31:2912–2922, 2023.

[35] Evelina Pantzar-Castilla, Andrea Cereatti, Giulio Figari, Nicolò Valeri, Gabriele Paolini, Ugo Della Croce, Anders Magnuson, and Jacques Riad. Knee joint sagittal plane movement in cerebral palsy: A comparative study of 2-dimensional markerless video and 3-dimensional gait analysis. *Acta Orthopaedica*, 89(6):656–661, 2018.

[36] Luca Lonini, Yaejin Moon, Kyle Embry, R. James Cotton, Kelly McKenzie, Sophia Jenz, and Arun Jayaraman. Video-based pose estimation for gait analysis in stroke survivors during clinical assessments: A proof-of-concept study. *Digital Biomarkers*, 6(1):9–18, 2022.

[37] Wasifur Rahman, Masum Hasan, Md Saiful Islam, Titilayo Olubajo, Jeet Thaker, Abdelrahman R. Abdelkader, Phillip Yang, Henry Paulson, Gulin Oz, Alexandra Durr, Thomas Klockgether, Tetsuo Ashizawa, READISCA Investigators, and Ehsan Hoque. Auto-Gait: Automatic ataxia risk assessment with computer vision from gait task videos. *Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies*, 7(1):26:1–26:19, 2023.

[38] Katsuki Eguchi, Hiroaki Yaguchi, Hisashi Uwatoko, Yuki Iida, Shinsuke Hamada, Sanae Honma, Asako Takei, Fumio Moriwaka, and Ichiro Yabe. Feasibility of differentiating gait in Parkinson's Disease and spinocerebellar degeneration using a pose estimation algorithm in two-dimensional video. *Journal of the Neurological Sciences*, 464:123158, 2024.

[39] Rahm Ranjan, David Ahmedt-Aristizabal, Mohammad Ali Armin, and Juno Kim. Computer vision for clinical gait analysis: A gait abnormality video dataset. *arXiv preprint arXiv:2407.04190*, 2024.

[40] Tanmay T. Verlekar, Paulo L. Correia, and Luís D. Soares. Using transfer learning for classification of gait pathologies. In *2018 IEEE International Conference on Bioinformatics and Biomedicine (BIBM)*, pages 2376–2381, 2018.

[41] Pedro Albuquerque, Tanmay Tulsidas Verlekar, Paulo Lobato Correia, and Luís Ducla Soares. A spatiotemporal deep learning approach for automatic pathological gait classification. *Sensors*, 21(18):6202, 2021.

[42] Vida Adeli, Ivan Klabučar, Javad Rajabi, Benjamin Filtjens, Soroush Mehraban, Diwei Wang, Hyewon Seo, Trung-Hieu Hoang, Minh N. Do, Candice Muller, Claudia Neves de Oliveira, Daniel Boari Coelho, Pieter Ginis, Moran Gilat, Alice Nieuwboer, et al. CARE-PD: A multi-site anonymized clinical dataset for Parkinson's Disease gait assessment. In *Advances in Neural Information Processing Systems*, 2025. Datasets and Benchmarks Track.

[43] Biao Jiang, Xin Chen, Wen Liu, Jingyi Yu, Gang Yu, and Tao Chen. MotionGPT: Human motion as a foreign language. In *Advances in Neural Information Processing Systems*, pages 20067–20079, 2023.

[44] Ling-Hao Chen, Shunlin Lu, Ailing Zeng, Hao Zhang, Benyou Wang, Ruimao Zhang, and Lei Zhang. MotionLLM: Understanding human behaviors from human motions and videos. *arXiv preprint arXiv:2405.20340*, 2024.

[45] Jiawei Mo, Yixuan Chen, Rifen Lin, Yongkang Ni, Min Zeng, Xiping Hu, and Min Li. MoChat: Joints-grouped spatio-temporal grounding LLM for multi-turn motion comprehension and description. *arXiv preprint arXiv:2410.11404*, 2024.

[46] Shaopeng Yang, Jilong Wang, Saihui Hou, Xu Liu, Chunshui Cao, Liang Wang, and Yongzhen Huang. Bridging gait recognition and large language models sequence modeling. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3460–3469, 2025.

[47] Diwei Wang, Cédric Bobenrieth, and Hyewon Seo. AGIR: Assessing 3D gait impairment with reasoning based on LLMs. *arXiv preprint arXiv:2503.18141*, 2025.

[48] Ruize Yang, Ann Kennedy, and R. James Cotton. BiomechGPT: Towards a biomechanically fluent multimodal foundation model for clinically relevant motion tasks. *arXiv preprint arXiv:2505.18465v1*, 2025.

[49] Erdong Chen, Yuyang Ji, Jacob K. Greenberg, Benjamin Steel, Faraz Arkam, Abigail Lewis, Pranay Singh, and Feng Liu. BioGait-VLM: A tri-modal vision-language-biomechanics framework for interpretable clinical gait assessment. *arXiv preprint arXiv:2603.08564*, 2026.

[50] Carlo Dindorf, Jonas Dully, Rebecca Keilhauer, Michael Lorenz, and Michael Fröhlich. Evaluating large language models for gait classification using text-encoded kinematic waveforms. *arXiv preprint arXiv:2603.13317*, 2026.

[51] Xi Fang, Weijie Xu, Fiona Anting Tan, Jiani Zhang, Ziqing Hu, Yanjun Qi, Scott Nickleach, Diego Socolinsky, Srinivasan Sengamedu, and Christos Faloutsos. Large language models (LLMs) on tabular data: Prediction, generation, and understanding—a survey. *Transactions on Machine Learning Research*, 2024.

[52] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. In *Advances in Neural Information Processing Systems*, pages 34892–34916, 2023.

[53] Shukang Yin, Chaoyou Fu, Sirui Zhao, Ke Li, Xing Sun, Tong Xu, and Enhong Chen. A survey on multimodal large language models. *National Science Review*, 11(12):nwae403, 2024.

[54] Catalin Ionescu, Dragos Papava, Vlad Olaru, and Cristian Sminchisescu. Human3.6M: Large scale datasets and predictive methods for 3D human sensing in natural environments. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 36(7):1325–1339, 2014.

[55] Robert Palisano, Peter Rosenbaum, Stephen Walter, Dianne Russell, Ellen Wood, and Barbara Galuppi. Development and reliability of a system to classify gross motor function in children with cerebral palsy. *Developmental Medicine & Child Neurology*, 39(4):214–223, 1997.

[56] Hisham Khalil, Ahmed Saad, and Uswah Khairuddin. Dataset for gait analysis of cerebellar ataxic patients and healthy adults using MediaPipe pose. Mendeley Data, 2023. Version 1.

[57] Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

[58] Qwen Team. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.

[59] Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, et al. Gemma 3 technical report. *arXiv preprint arXiv:2503.19786*, 2025.

[60] Team GLM, Aohan Zeng, Bin Xu, Bowen Wang, Chenhui Zhang, Da Yin, Dan Zhang, Diego Rojas, Guanyu Feng, Hanlin Zhao, et al. ChatGLM: A family of large language models from GLM-130B to GLM-4 all tools. *arXiv preprint arXiv:2406.12793*, 2024.

[61] Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, et al. DeepSeek-R1 incentivizes reasoning in LLMs through reinforcement learning. *Nature*, 645:633–638, 2025.

[62] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc V. Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 24824–24837, 2022.

[63] Corinna Cortes and Vladimir Vapnik. Support-vector networks. *Machine Learning*, 20(3):273–297, 1995.

[64] Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, et al. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

[65] Jacob Cohen. Weighted kappa: Nominal scale agreement with provision for scaled disagreement or partial credit. *Psychological Bulletin*, 70(4):213–220, 1968.

[66] Bradley Efron and Robert J. Tibshirani. *An Introduction to the Bootstrap*. Chapman & Hall, 1993.

[67] Ahmed A. Al-Jubouri, Israa Hadi Ali, and Yasen Rajihy. Gait and full body movement dataset of autistic children classified by rough set classifier. *Journal of Physics: Conference Series*, 1818(1):012201, 2021.