References

[1] Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J.D., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems.* 33, (2020), 1877–1901.

[2] Clip studio PAINT: *https://www.clipstudio.net/*[1]. Accessed: 2023-01-26.

[3] Furusawa, C., Hiroshiba, K., Ogaki, K. and Odagiri, Y. 2017. Comicolorization: Semi-automatic manga colorization[2]. *SIGGRAPH asia 2017 technical briefs* (New York, NY, USA, 2017).

[4] Goodfellow, I., Pouget-Abadie, J., Mirza, M., Xu, B., Warde-Farley, D., Ozair, S., Courville, A. and Bengio, Y. 2014. Generative adversarial nets[3]. *Advances in neural information processing systems* (2014).

[5] Hensman, P. and Aizawa, K. 2017. cGAN-based manga colorization using a single training image[4]. *2017 14th IAPR international conference on document analysis and recognition (ICDAR)* (Los Alamitos, CA, USA, Nov. 2017), 72–77.

[6] Ho, J., Jain, A. and Abbeel, P. 2020. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems.* 33, (2020), 6840–6851.

[7] Kandinsky, W. and Sadleir, M. 1977. *Concerning the spiritual in art.* Dover Publications.

[8] Kingma, D.P. and Welling, M. 2013. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114.* (2013).

[9] Le Cun, Y. 2019. *Quand la machine apprend: La révolution des neurones artificiels et de l'apprentissage profond*[5]. Odile Jacob.

[10] Mumford, M., Medeiros, K. and Partlow, P. 2012. Creative thinking: Processes, strategies, and knowledge. *The Journal of Creative Behavior.* 46, (Mar. 2012). DOI:https://doi.org/10.1002/jocb.003[6].

[11] Newell, A., Shaw, J.C. and Simon, H.A. 1959. *The processes of creative thinking*[7]. RAND Corporation.

[12] Paintman: *http://www.retasstudio.net/products/paintman/*[8]. Accessed: 2023-01-26.

[13] Photoshop: *https://www.adobe.com/products/photoshop.html*[9]. Accessed: 2023-01-26.

[14] Rumelhart, D.E., Hinton, G.E. and Williams, R.J. 1986. Learning representations by back-propagating errors. *Nature.* 323, 6088 (Oct. 1986), 533–536. DOI:https://doi.org/10.1038/323533a0[10].

[15] Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A.N., Kaiser, Ł. and Polosukhin, I. 2017. Attention is all you need. *Advances in neural information processing systems.* 30, (2017).

[16] Zhang, R., Zhu, J.-Y., Isola, P., Geng, X., Lin, A.S., Yu, T. and Efros, A.A. 2017. Real-time user-guided image colorization with learned deep priors. *ACM Trans. Graph.* 36, 4 (Jul. 2017). DOI:https://doi.org/10.1145/3072959.3073703[11].

AI-Assisted Creative Expression: a Case for Automatic Lineart Colorization

Yliess Hati

January 26, 2023

Conclusion

Ethical and Societal Impact

Contents

Abstract . . . 1
Introduction . . . 2
- Motivations . . . 2
- Problem Statement . . . 3
- Contributions . . . 3
- Concerns . . . 3
- Outline . . . 3

Background . . . 4
- History of Artificial Intelligence . . . 4
- Neural Networks . . . 4
- Autoencoders . . . 4
- Variational Autoencoders . . . 4
- Generative Adversarial Networks . . . 4
- Denoising Diffusion Models . . . 4

Methodology . . . 5
- Implementation . . . 5
- Objective Evaluation . . . 5
- Subjective Evaluation . . . 5
- Reproducibility . . . 5

Contrib I (Find Catchy Explicit Name) . . . 6
- State of the Art . . . 6
- Method . . . 6
- Setup . . . 6
- Results . . . 6
- Summary . . . 6

Contrib II (Find Catchy Explicit Name) . . . 7
- State of the Art . . . 7
- Method . . . 7
- Setup . . . 7
- Results . . . 7
- Summary . . . 7

Contrib III (Find Catchy Explicit Name) . . . 8
- State of the Art . . . 8
- Method . . . 8
- Setup . . . 8
- Results . . . 8
- Summary . . . 8

Contrib IV (Find Catchy Explicit Name) . . . 9

State of the Art 9
Method 9
Setup 9
Results 9
Summary 9
Ethical and Societal Impact 10
Conclusion 11
References 12

Contrib IV (Find Catchy Explicit Name)

State of the Art

Method

Setup

Results

Summary

Contrib III (Find Catchy Explicit Name)

State of the Art

Method

Setup

Results

Summary

Abstract

Introduction

Humans possess the ability to perceive and understand the world allowing us to accomplish a wide range of complex tasks through the combination of visual recognition, scene understanding, and communication. The ability to quickly and accurately extract information from a single image is a testament to the complexity and sophistication of the human brain and is often taken for granted. One of the Artificial Intelligence (AI) field's ultimate goals is to empower computers with such human-like abilities, one of them being creativity, being able to produce something original and worthwhile [10].

Computational creativity is the field at the intersection of AI, cognitive psychology, philosophy, and art, which aims at understanding, simulating, replicating, or in some cases enhancing human creativity. One definition of computational creativity [11] is the ability to produce something that is novel and useful, demands that we reject common beliefs, results from intense motivation and persistence, or comes from clarifying a vague problem. Top-down approaches to this definition use a mix of explicit formulations of recipes and randomness such as procedural generation. On the opposite, bottom-up approaches use Artificial Neural Networks (ANNs) to learn patterns and heuristics from large datasets to enable non-linear generation.

We, as a species, are currently witnessing the beginning of a new era where the gap between machines and humans is starting to blur. Current breakthroughs in the field of AI, more specifically in Deep Learning (DL), are giving computers the ability to perceive and understand our world, but also to interact with our environment using natural interactions such as speech and natural language. ANNs, once mocked by the AI community [9], are now trainable using Gradient Descent (GD) [14] thanks to the massive availability of data and the processing power of modern hardware accelerators such as Graphical Processing Units (GPUs), Tensor Processing Units (TPUs), and Neural Processing Units (NPUs).

Neural Networks (NNs), those trainable general function approximators, gave rise to the field of generative NN. Specialized DL architectures such as Variational Autoencoders (VAEs) [8], Generative Adversarial Networks (GANs) [4], Denoising Diffusion Models (DDMs) [6], and Large Language Models (LLMs) [1, 15] are used to generate artifacts such as text, audio, images, and videos of unprecedented quality and complexity.

This thesis aims at exploring how one could train and use generative NN to create AI-powered tools capable of enhancing human creative expression. The task of automatic lineart colorization act as the example case used to illustrate this process throughout the entire thesis.

Motivations

Lineart colorization is an essential aspect of the work of artists, illustrators, and animators. The task of manually coloring lineart can be time-consuming, repetitive, and exhausting, particularly in the animation industry, where every frame of an animated product must be colored and shaded. This process is typically done using image editing softwares such as Photoshop [13], Clip Studio PAINT [2], and PaintMan [12]. Automating the colorization process through

Contrib II (Find Catchy Explicit Name)

State of the Art

Method

Setup

Results

Summary

Contrib I (Find Catchy Explicit Name)

State of the Art

Method

Setup

Results

Summary

the implementation of pipeline systems can greatly improve the workflow of these creative professionals. Such a system has recently been integrated into ClipStudio, demonstrating the growing significance of automatic colorization in the field.

The most common digital illustration process can be broken down into four distinct stages: sketching, inking, coloring, and post-processing. As demonstrated by the work of Kandinsky [7], the colorization process can greatly impact the overall meaning of a piece of art through the introduction of various color schemes, shading, and textures. These elements of the coloring process present significant challenges for the Computer Vision (CV) task of automatic lineart colorization, particularly in comparison to its grayscale counterpart [3, 5, 16]. Without the added semantic information provided by textures and shadows, inferring materials and 3D shapes from black and white linearts only is difficult. They can only be deduced from silhouettes.

Problem Statement

- Black & White Lineart VS Gray Scale
- Incomplete Information Challenge fo Computer Vision
- Natural Artisitic Control Back to the User

Contributions

- Recipe for curating datasets for the task of automatic colorization
- 3 Models exploring different aspect of the topic:
  - PaintsTorch: High Quality, User-Guided, Fast Realtime Feedback
  - StencilTorch: Human-Machine Collaboration, Human-in-the-Loop
  - StableTorch: Variance and Iterative Exploration
- A reflexion on Current Generative AI Ethical and Societal Impact in our Society

Concerns

- Raise awareness about
  - Deepfakes
  - Model Fabulations
  - Ownership & Copyright Ambiguities
  - Biases & Discrimination
- About this work
  - Images used only for Educational and Research Purposes
  - Only describe recipes for reproducibility
  - Dataset and Weights are not Distributed (Only Code)

Outline

- Plain Language Expanded TOC

Background

History of Artificial Intelligence

Neural Networks

Autoencoders

Variational Autoencoders

Generative Adversarial Networks

Denoising Diffusion Models

Methodology

Implementation

Objective Evaluation

Subjective Evaluation

Reproducibility