

latextool

DR. YIHSIANG LIOW (FEBRUARY 21, 2024)

Contents

1	tikz stuff	9
2	Creating tikz node, point, small circles	10
3	Notes and API and TODOs	14
4	Enumerate	19
4.1	Basic enumerate	19
4.2	tightlist	20
4.3	axioms	21
5	Text Color	22
6	Python	23
7	execute	26
8	console	31
9	verbatim	34
10	shell	44
11	Plot	47
12	Scaling	48
13	Grid	49
14	Point and text placement	52
15	coordinate	61
16	Code	62
16.1	Cell size	64

16.2	<code>border linewidth</code>	65
16.3	distance of border to rect	66
16.4	<code>codirect</code>	67
16.5	Substitution	68
16.6	Long division example	69
17	Tables	70
17.1	<code>table</code> function	70
17.2	<code>table2</code> function	79
17.2.1	Change row and column index values/names	80
17.2.2	No row and column indices/values	81
17.2.3	Change row/column names	82
17.2.4	No row and no column names	83
17.2.5	<code>border linewidth</code>	84
17.2.6	Adding things beneath <code>table2</code> : background	85
17.2.7	Using cells	86
17.2.8	Rect for cells	88
17.2.9	Using rect to change the background	90
17.3	<code>table3</code>	91
17.3.1	Example: 2-by-2 case	92
17.3.2	Example: 2-by-2 case with top and left for labels	93
17.3.3	Example: 2-by-1 case	94
17.3.4	Specify topleft coordinates	95
17.3.5	Example: 2-by-1 case with title	96
17.3.6	Example: 1-by-2 case	97
17.3.7	<code>table3</code> : accessing cells	98
17.3.8	Coloring a cell under the table manually	99
17.3.9	Coloring a cell under the table using <code>table3</code>	100
17.3.10	Cells of different widths (<code>table2</code>)	101
17.3.11	Cells of different widths (<code>table3</code>)	102
17.3.12	ragged arrays (error - to fix)	103
17.3.13	Justification	104
17.3.14	title	105
17.3.15	Title distance	106
17.4	<code>table4</code>	107
17.5	helper for 2d arrays	110
18	diamond	111
19	Circle	115
19.1	boundary	115
19.2	boundary	116
19.3	background	117

19.4 s: minipage text in circle	118
19.5 label anchor	119
19.6 foreground	121
19.7 Center and boundary	122
19.8 tikz name	123
20 Ellipse	125
21 arc	127
22 Polygon	132
23 Relative node placement	133
24 Bounding nodes	137
25 Axes	140
26 Lines	143
26.1 linecolor and linewidth	144
26.2 startstyle and endstyle	145
26.3 points parameter	148
26.4 boundary points	149
26.5 Midpoints	151
26.6 tikz names	155
26.7 bend	156
26.8 label and anchor	157
26.9 Using midpoint to place labels	160
26.10Two control points	161
26.11One control point	162
26.12loop	163
26.13bend	165
26.14Orthogonal lines; organization chart	168
27 Rect class	171
27.1 No background	171
27.2 Background	171
27.3 border, background, foreground	172
27.4 border, background, foreground	173
27.5 align	174
27.6 innersep	175
27.7 rounded corners	176
27.8 linestyle	177
27.9 label	178

27.10tikz name	179
28 RectContainer	180
28.1 Using []	181
29 name	182
30 positions	193
31 vphantom	195
32 Trees	196
32.1 tree	197
32.2 Parse tree example	199
32.3 Binary tree	200
32.4 bintree function	203
32.5 BinTree class	206
33 Graphs	208
34 Graphs	209
34.1 The graph function	209
34.2 The graph function:nodes and labels	210
34.3 The graph function: isoceles triangle as subtree	211
34.4 The graph function: edge labels	212
34.5 Graph class	213
34.6 Edge label anchor	214
34.7 Cycle graphs	215
34.8 Name of nodes	216
34.9 Petersen graph	219
34.10Complete graphs	220
34.11Star graphs	222
34.12Bipartite graphs	223
35 Frame	225
36 Test Verbatim Spacing	226
37 2D vector diagram	227
38 Line Graph	232
39 Bar chart, line chart	238
40 TEST ISOCELES TRIANGLE	240



41 ER diagrams	241
41.1 Attribute	241
41.2 Entity	242
41.3 Relation	254
41.4 Entity and relation with different arrows	257
41.5 Entity and relation with attributes	260
41.6 Weak entity sets and partial keys	261
41.7 Associative entity	262
41.8 Crow's foot	263
42 UML diagrams	265
42.1 UML: class diagram	265
42.2 UML: sequence diagram	276
42.3 UML: use case diagram	277
43 Matrix	278
44 Board games	280
44.1 Chess	280
44.2 Othello	282
44.3 Tic-tac-toe	287
45 Proof Trees	293
46 K-maps	294
46.1 kmap: specify term(s) to circle	305
46.2 kmap: 2-by-4	307
46.3 kmap: force choice of prime implicant	311
46.4 kmap: style selector	313
46.5 kmap: change distance of implicant boundary to rect	314
46.6 kmap: decimal notation	316
46.7 kmap: decimal notation 2	317
46.8 kmap: using coordinates of rects in the kmap cells	318
47 Logic design	320
47.1 AND gate	320
47.2 OR gate	321
47.3 NOT gate	322
47.4 NAND gate	323
47.5 NOR gate	324
47.6 XOR gate	325
47.7 Orthogonal paths	326
47.8 Orthogonal path with gates	330

47.9 POINT	331
47.10 Linecolor for gate	332
47.11 Label for gate	333
47.12 Rotation	343
47.13 Example: SR latch	358
47.14 layout function	362
47.15 Logic blocks	368
47.16 Logic blocks: full adder	371
47.17 Two NOTs	372
48 Data structures	373
48.1 Singly Linked List	375
48.2 Doubly linked list	378
48.3 Stack	383
48.4 Adjacency list	391
48.5 Heap file	398
49 B+ tree	404
49.1 Node	404
49.2 Directed edge	406
50 Intervals	414
51 Automatas	415
51.1 State	416
51.2 Tape and head	417
51.3 Label for tape	417
51.4 Position	418
51.5 Body-tape distance	422
51.6 No drawing	423
51.7 Sequence of automatas	424
51.8 PDA	425
51.9 PDA: bounding rect	427
51.10 Sequence of PDA	429
51.11 CYK	432
51.11.1 Word being parsed	432
51.11.2 Background	433
51.11.3 Height and width	434
52 Automata	435
53 Longtable of minipages	442



TODO: Shape location: Right now specify x0,y0,x1,y1 or center. Need to add “left= of a”, “left=1cm of a”, “below left=1cm and 3cm of a”,etc. Maybe `{pos = "below 1cm, left 1cm, a"` or `{pos = {'direction':{'below':"1cm", "left":"1cm"}, 'node':'a'}}`

TODO: Point, POINT, coordinate are similar. Clean up.

1 tikz stuff



Angle of bend:



2 Creating tikz node, point, small circles

Something is wrong with the library for drawing very small circles. (Probably error with inner sep: if circle is radius r , innersep should be $r/\sqrt{2}$ – correct and test circle class.) The following is a temporary manual fix using tikz strings.

```
from latextool_basic import *
p = Plot()

p += r"\node[draw,shape=circle,minimum size=0.1cm,fill=blue,inner sep=0] (A)
at (0,0){};"

print(p)
```




A node with the shape drawn or not drawn

```
from latextool_basic import *
p = Plot()

p += r"\node[draw,shape=circle,minimum size=1cm,inner sep=0](A) at (0,0){};"
p += r"\node[draw,shape=circle,minimum size=1cm,inner sep=0](D) at (0,1){};"
p += r"\node[draw=none,shape=circle,minimum size=1cm,inner sep=0](B) at (3,0){};"
p += r"\node[draw,shape=circle,minimum size=1cm,inner sep=0](C) at (6,0){};"

p += Line(names=['A', 'B'])
p += Line(names=['D', 'B'])
p += Line(names=['C', 'B'])
p += Grid(-1, -1, 3, 3)
print(p)
```




Create tikz node without shape (basically just to have a coordinate with name):

```
from latextool_basic import *
p = Plot()

p += Point(x=0, y=0, name='A')
p += Point(x=5, y=1, name="B")

p += Graph.arc(names=['B', 'A'])
p += Grid(x0=-1, y0=-1, x1=6, y1=2)
print(p)
```




Creating node wrt to another:

```
from latextool_basic import *
p = Plot()
p += diamond(center=(0, 0), name='a')
p += diamond(center=(6, 1), name='b')

p += r'\node[right=0.0cm of a, inner sep=0.0cm, outer sep=0.0cm] (c) {};'
p += r'\node[below left=0.0cm of b, inner sep=0.0cm, outer sep=0.0cm] (d) {'
};'

p += Line(names=['c','d'])
print(p)
```



DR. YIHSIANG LIOW yliow@ccis.edu

ISSUE: The label in the rect is centered. The problem is the font for a character with greater height will appear lower than another. So for an array of rects of character, the base line of the labels are not the same.

ISSUE: The boundary line are drawn within the bounding box. So joining up rects would mean the common line will look thicker. DONE. See Rect2.

ISSUE:

- Joining rects in a uniform way to get hor and ver arrays and 2d arrays. Allows for containers with finite area, infinite horizontally, infinite vertically.
- Where to put first rect? What's the API? For hor array that grows to the right, only need top-left corner or bottom-left.or center-left. Maybe just specify the absolute corners of the first rect?
- Allow each element of array to be any shape. Use BaseNode of course.

CLEAN UP OF PYTHON-LATEX DRAWING LIBRARY

latextool.py
latextool_basic.py

automata

courses/book/graph.py -----> projects/latextool/latextool.py
courses/ciss362-automata/resources/dfa/dfa-backup.py
courses/ciss362-automata/resources/dfa/dfa.py
courses/ciss362-automata/resources/dfa/graph/graph.py
projects/automata/dfa/dfa.py

linked list

courses/math325/n/latex_ds.py
projects/test-latex/xxx/latex_ds.py

array sorting

2d graphs:

courses/math325/n/makegraph/plot.py

=====

automata

1d shapes: line or things made up of lines (broom?...) They have

- color
- style
- starting tip: dot, arrow (and arrow style)
- ending tip: dot, arrow (and arrow style)

2d shapes: rect, circle, They have

- boundary is a line. So it has boundary color and boundary style
- interior: color
- minipage

4.2 tightlist

This is the same as mylist except that the vertical spacing before and after the environment is removed. This does not work quite right if the environment is in a paragraph of its own – there will be a little extra vertical spacing before the environment.

Testing tightlist:

- line 1
- line 2
- line 3

After environment.

This is with paragraphing within items:

- Line 1. This is a test. This is a test. This is a test. This is a test. This is a test. This is a test. This is a test. This is a test.
Next paragraph. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.
- line 2.
- line 3.

A new paragraph after above environment. The next environment is in a new paragraph.

- line 1
- line 2
- line 3

4.3 axioms

The label horizontal spacing is larger.

(GROUP-C) $\forall g, g' \in G, gg' \in G$

(GROUP-A) $\forall g, g', g'' \in G,$

5 Text Color

Testing `\textred`: hello world ... $x = 1$... $\int x \, dx = \frac{1}{2}x^2 + C$

$$\sin \theta = 0$$

Black again.

```
Testing \verb!\textred!:
\textred{hello world ... $x = 1$ ... $\int x \, dx = \frac{1}{2}x^2 + C$}
\sin \theta = 0
Black again.
```

Testing `\textblue`: hello world ... $x = 1$... $\int x \, dx = \frac{1}{2}x^2 + C$

$$\sin \theta = 0$$

Black again.

Testing `\textwhite`:

Black again.

Using `\underline`/`\textbox` with `\textwhite`:

$$\int x \, dx = \frac{1}{2}x^2 + C$$

$$\int x \, dx =$$

$$\int x \, dx = \text{\textbox[0pt]{0pt}{0pt}}$$

6 Python

There are vertical spacing issues with the python environment. Vertical spacing before and after the python environment has been removed from the python environment in `mypython.tex`.

TEST 1. Python environment with console function call. Line before python environment.

```
hello world
```

Line after the python environment.

TEST 2. One python environment with two console function calls. Line before python environment.

```
hello world 1
```

```
hello world 2
```

Line after the python environment. ISSUE: Note that the two frames are joined up. For the time being do not put two console environment immediately next to each other.

TEST 3. One python environment with two console function calls with one blank line between the console function calls. Line before python environment.

```
hello world 1
```

```
hello world 2
```

Line after the python environment. ISSUE: Note that the two frames are joined up. For the time being do not put two console environment immediately next to each other.

TEST 4. Two python environments with one console function call each. Line before python environment.

```
hello world 1
```

Line between the python environments.

```
hello world 2
```

Line after the second python environment.

TEST 5. This is the console environment in latex (no python).

```
hello world 1
```

Line after.

TEST 6. 1 console environment in latex (no python).

```
hello world 1
```

Line between.

```
hello world 2
```

Line after.

TEST 7. 2 console environments in latex next to each other.

```
hello world 1
```

```
hello world 2
```

Line after.

TEST 8. 1 verbatim environment in latex (no python).


```
hello world 1
```

Line after.

TEST 9. This is 2 Verbatim environments in latex (no python).

```
hello world 1
```

Line between.

```
hello world 2
```

Line after.

TEST 10. 2 Verbatim environments next to each.

```
hello world 1
```

```
hello world 2
```

Line after.

7 execute

The `execute` (in `latexbasic_tool.py`) function executes a python string as a program and the stdout is inserted into the latex file:

```
\begin{python}
from latextool_basic import execute
execute(r"""
print("hello world")
""")
\end{python}
```

Here's the result: hello world

Note that there's some extra whitespace before the hello world. TODO: Need to figure a way to remove the whitespace.

The following does the same except that it first prints the python source in a framed verbatim box:

```
Result:
\begin{python}
from latextool_basic import execute
execute(r"""
print("hello world")
""", print_source=True)
\end{python}
```

If `debug` is set to `True`, there are three outputs: the python source, the stderr, and the stdout, all in framed verbatim boxes.

```
Result:
\begin{python}
from latextool_basic import execute
execute(r"""
print("hello world")
""", debug=True)
\end{python}
```

If there's an error in the python source, the output will be the same as if `debug` is set to `True`.

TEST: `debug=True`

```
from latextool_basic import execute
execute("print('hello world')", debug=True)
```

Result: PYTHON ERROR. See source, stderr, stdout below

```
print('hello world')
```

```
hello world
```

TEST: debug=False

```
from latextool_basic import execute
execute("print('hello world')", debug=False)
```

Result: hello world

TEST: print source=True, debug=False

```
from latextool_basic import execute
execute("print('hello world')", print_source=True, debug=False)
```

Result:

```
print('hello world')
```

hello world

TEST: Error in source

```
from latextool_basic import execute
execute("print(hello world)")
```

Result: PYTHON ERROR. See source, stderr, stdout below

```
print(hello world)
```

```
File "znzddpzs.tmp.py", line 1
    print(hello world)
          ^
```

```
SyntaxError: invalid syntax
```



```
from latextool_basic import console
print(console(r'''
line 1 ... hello world hello world hello world
line 2 ... hello world hello world hello world hello world hello world hell
o world hello world hello world hello world hello world hello world hello w
orld hello world hello world hello world hello world hello world hello worl
d hello world hello world hello world
'''.strip()))
```

```
line 1 ... hello world hello world hello world
line 2 ... hello world hello world hello world hello world hello world hell
o world hello world hello world hello world hello world hello world hello w
orld hello world hello world hello world hello world hello world hello worl
d hello world hello world hello world
```

You can control the window width:

```
from latextool_basic import console
print(console(r'''
line 1 ... hello world hello world hello world
line 2 ... hello world hello world hello world hello world hello world hell
o world hello world hello world hello world hello world hello world hello w
orld hello world hello world hello world hello world hello world hello worl
d hello world hello world hello world
'''.strip(), width=40))
```

```
line 1 ... hello world hello world hello
world
line 2 ... hello world hello world hello
world hello world hello world hello wor
ld hello world hello world hello world h
ello world hello world hello world hello
world hello world hello world hello wor
ld hello world hello world hello world h
ello world hello world
```

You can specify the `wrapmarker` that is used to indicate a line wrap:

```
from latextool_basic import console
print(console(r'''
line 1 ... hello world hello world hello world
line 2 ... hello world hello world hello world hello world hello world hell
o world hello world hello world hello world hello world hello world hello w
orld hello world hello world hello world hello world hello world hello worl
d hello world hello world hello world
'''.strip(), width=40, wrapmarker='---> '))
```



```
line 1 ... hello world hello world hello
---> world
line 2 ... hello world hello world hello
---> world hello world hello world hello wor
---> ld hello world hello world hello world h
---> ello world hello world hello world hello
---> world hello world hello world hello wor
---> ld hello world hello world hello world h
---> ello world hello world
```

TODO: Fix non-pagebreak.

How to insert \rightarrow symbol into verbatim area?

9 verbatim

The `verbatim` function allows you to create verbatim environments. Executing tex commands in the environment can be easier.

Example:

```
from latextool_basic import verbatim
print(verbatim("hello world\nlorem ipsum"))
```

```
hello world
lorem ipsum
```

You can have no frame:

```
from latextool_basic import verbatim
print(verbatim("hello world\nlorem ipsum", frame=None))
```

```
hello world
lorem ipsum
```

You have line numbers on the left:

```
from latextool_basic import verbatim
print(verbatim("hello world\nlorem ipsum", numbers='left'))
```

```
1 hello world
2 lorem ipsum
```

You have line numbers on the right:

```
from latextool_basic import verbatim
print(verbatim("hello world\nlorem ipsum", numbers='right'))
```

```
hello world
lorem ipsum
```

```
1
2
```

You can escape to a tex command:

```
t = r"""
#include <iostream>

int main()
{
    std::cout << "hello world" << std::endl;
    return 0;
}
"""
from latextool_basic import verbatim
print(verbatim(t.strip(), command=['redtext', 'iostream']))
```

```
#include <iostream>

int main()
{
    std::cout << "hello world" << std::endl;
    return 0;
}
```

You can specify a list of words for each tex command:

```
t = r"""
#include <iostream>

int main()
{
    std::cout << "hello world" << std::endl;
    return 0;
}
"""
from latextool_basic import verbatim
print(verbatim(t.strip(), command=['redtext', ['iostream', 'std']]))
```

```
#include <iostream>

int main()
{
    std::cout << "hello world" << std::endl;
    return 0;
}
```

You can use regular expressions:

```
t = r"""
#include <iostream>

int main()
{
    std::cout << "hello world" << std::endl;
    return 0;
}"""
from latextool_basic import verbatim
print(verbatim(t.strip(), command=['redtext', '"[a-z ]*"']))
```

```
#include <iostream>

int main()
{
    std::cout << "hello world" << std::endl;
    return 0;
}
```

WARNING. Since search is by regular expression, be careful to escape metacharacters:

```
from latextool_basic import verbatim
t = r"""
#include <iostream>

int main()
{
    std::cout << "hello world" << std::endl;
    return 0;
}
"""

print(verbatim(t.strip(), command=['textbox', r'main\(\)']))
```

```
#include <iostream>

int main()
{
    std::cout << "hello world" << std::endl;
    return 0;
}
```

You can also specify which part of the text should be escaped by specifying 3 numbers: the line number, the starting column number, and the ending column number.

```
t = r"""
#include <iostream>

int main()
{
    std::cout << "hello world" << std::endl;
    return 0;
}
"""
from latextool_basic import verbatim
print(verbatim(t.strip(), command=['underline', [4, 4, 13]]))
```

```
#include <iostream>

int main()
{
    std::cout << "hello world" << std::endl;
    return 0;
}
```

You can also specify a linenumber and a text:

```
t = r"""
#include <iostream>

int main()
{
    std::cout << "hello world" << std::endl;
    std::cout << "hello world" << std::endl;
    std::cout << "hello world" << std::endl;
    return 0;
}
"""
from latextool_basic import verbatim
print(verbatim(t.strip(), command=['textred', [5, 'std::cout']]))
```

```
#include <iostream>

int main()
{
    std::cout << "hello world" << std::endl;
    std::cout << "hello world" << std::endl;
    std::cout << "hello world" << std::endl;
    return 0;
}
```

You can have a list of tex commands:

```
from latextool_basic import verbatim
print(verbatim("the answer is 42",
               commands=[
                   ['underline', 'the'],
                   ['textbox', ['answer', '42']],
               ]
       ))
```

the answer is 42

You can also use the contents of a file like this:

```
from latextool_basic import verbatim
print(verbatim(filename='helloworld.cpp'))
```


`verbatim` is not exactly a verbatim function: there's line wrap. By default the width is set to 75. You can set the width to 40:

```
from latextool_basic import verbatim
print(verbatim("abcdeabcdeabcdeabcdeabcdeabcdeabcdeabcde", width=10))
```

```
abcdeabcde
abcdeabcde
abcdeabcde
abcdeabcde
abcde
```

You can also specify a string to indicate line wrap like this:

```
from latextool_basic import verbatim
print(verbatim("abcdeabcdeabcdeabcdeabcdeabcdeabcdeabcde", width=10,
               wrapmarker='---> '))
```

```
abcdeabcde
---> abcdeabcde
---> abcdeabcde
---> abcdeabcde
---> abcde
```

TEST 1. Test vertical spacing before and after verbatim(). Before.

```
hello world 1  
hello world 2
```

After.

TEST 2. Test vertical spacing between two verbatim() in 1 python environment. Before.

```
frame 1  
hello world 1  
hello world 2
```

```
frame 2  
hello world 1  
hello world 2
```

After.

TEST 3. Same as before but print a blank line between the 2 verbatim()s. Before.

```
frame 1  
hello world 1  
hello world 2
```

```
frame 2  
hello world 1  
hello world 2
```

After.

TEST 4. Test vertical spacing between 2 python environments, each containing 1 verbatim(), no blank line between the python environments. Before.

```
frame 1  
hello world 1  
hello world 2
```

```
frame 2
hello world 1
hello world 2
```

After.

TEST 5. For user input in verbatim environment. Before.

```
Please enter x: 42
Please enter y and z: 43 44
Please enter login: jdoe
```

After.

10 shell

The following are 3 ways to draw a framed verbatim environment.

METHOD 1. The following is a console latex environment:

```
[student@localhost latextool] pwd  
home/student
```

Line after the console environment. Here are two such:

```
[student@localhost latextool] pwd  
home/student
```

```
[student@localhost latextool] pwd  
home/student
```

METHOD 2. The following is a python environment that prints a shell function call:

```
[student@localhost doc] pwd  
/home/student/yliow/Documents/work/projects/latextool/doc
```

Line after python environment with shell function call. Here are two such:

```
[student@localhost doc] pwd  
/home/student/yliow/Documents/work/projects/latextool/doc
```

```
[student@localhost doc] pwd  
/home/student/yliow/Documents/work/projects/latextool/doc
```

METHOD 3. The following is a python environment that prints an execute function call:

```
[student@localhost doc] pwd  
/home/student/yliow/Documents/work/projects/latextool/doc
```

Line after python environment with execute function call. Here are two such:

```
[student@localhost doc] pwd  
/home/student/yliow/Documents/work/projects/latextool/doc
```

```
[student@localhost doc] pwd
/home/student/yliow/Documents/work/projects/latextool/doc
```

Notice the vertical spacing before and after the framed window is smaller for 1. The verbatim spacing before and after the framed window for 2 and 3 are the same.

METHOD 4. The following is a python environment that prints an execute function call:

```
from latextool_basic import shell
print(shell('pwd'))
```

```
[student@localhost doc] pwd
/home/student/yliow/Documents/work/projects/latextool/doc
```

Line after python environment with execute function call.

Another example:

```
from latextool_basic import shell
print(shell('ls -la c*.py'))
```

```
[student@localhost doc] ls -la c*.py
-rwxrwxrwx. 1 root root 62 Feb 21 18:25 cobhhaxf.tmp.py
-rwxrwxrwx. 1 root root 1810 Jul 22 2020 crowfoot.py
```

Line after python environment with execute function call.

Execute command in another directory

```
from latextool_basic import shell
print(shell('pwd; ls -la .b*', dir='/home/student'))
```

```
[student@localhost ~] pwd; ls -la .b*
/home/student
-rw-----. 1 student student 8315 Feb 21 18:25 .bash_history
-rw-r--r--. 1 student student 18 Dec 6 2019 .bash_logout
-rw-r--r--. 1 student student 141 Dec 6 2019 .bash_profile
lrwxrwxrwx. 1 root root 54 Feb 18 20:15 .bashrc -> /home/student/shares/
yliow/Documents/work/unix/.bashrc
-rwx-----. 1 student student 2813 Sep 22 2021 .bashrc~
-rwxrwxrwx. 1 student student 3029 Sep 28 2022 .bashrc.backup
lrwxrwxrwx. 1 root root 54 Feb 16 20:44 .bashrc.old -> /home/student/sha
res/yliow/Documents/work/unix/.bashrc
```

no execution

```
from latextool_basic import shell
print(shell('ls -la', execute=False))
```

```
[student@localhost doc] ls -la
```

Executing with error: PYTHON ERROR. See source, stderr, stdout below

```
print(x)
```

```
Traceback (most recent call last):
  File "cgcarbvx.tmp.py", line 1, in <module>
    print(x)
NameError: name 'x' is not defined
```

11 Plot

All drawing go into a `Plot` object. The following should be in a python environment:

```
from latextool_basic import Plot, Circle
p = Plot()
p += Circle(x=1, y=1, r=1)
print(p)
```

or run in the `execute` function in a python environment:

```
s = r"""
from latextool_basic import Plot, Circle
p = Plot()
p += Circle(x=1, y=1, r=1)
print(p)
"""

from latextool_basic import execute
execute(s)
```

A centered `tikzpicture` environment is then inserted.


You can also add a `pgf/tikz` string to plot:

```
from latextool_basic import Plot, Circle
p = Plot()
p += Circle(x=1, y=1, r=1)
p.add("\draw ...")
print(p)
```

You can create and store a pdf image in the `tmp/` subdirectory. See next section.

12 Scaling

```
from latextool_basic import *  
p = Plot(scale=0.5)  
p.add(grid, x0=-5, y0=-2, x1=5, y1=2)  
print(p)
```



tmp/f28b8b883e26656944de79b8bc132e5f.pdf

XS

13 Grid


Plot with default grid.

```
from latextool_basic import *  
p = Plot()  
p += Grid()  
print(p)
```

$$\begin{matrix} 0 & . \\ & 0 \end{matrix}$$


With object grid and bounding box:

```
from latextool_basic import *  
p = Plot()  
p += Grid(x0=-5, y0=-2, x1=5, y1=2)  
print(p)
```




With label_axis set to false.

```
from latextool_basic import *  
p = Plot()  
p += Grid(x0=-5, y0=-2, x1=5, y1=2, label_axes=False)  
print(p)
```



Example. $dx = 2$, $dy = 2$.

```
from latextool_basic import *  
p = Plot()  
p += Grid(x0=-5, y0=-2, x1=5, y1=2, dx=2, dy=2)  
print(p)
```




Example. $dx = 1.3$, $dy = 0.7$.

```
from latextool_basic import *  
p = Plot()  
p += Grid(x0=-5, y0=-2, x1=5, y1=2, dx=1.3, dy=0.7)  
print(p)
```


14 Point and text placement

[See section on logic design]


```
from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=0, label='$abcde$')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)
```



```

from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=0, r=0, label='$abcde$')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)


```



```

from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=0, label='$abcde$', anchor='east')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)


```




```

from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=0, label='$abcde$', anchor='west')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)


```



```
from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=0, label='$abcde$', anchor='north')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)
```




```
from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=0, label='$abcde$', anchor='south')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)
```



```

from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=0, label='$abcde$', anchor='north east')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)


```



```


from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=0, label='$abcde$', anchor='north west')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)

```



radius 0 cases:


```
from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=0, r=0, label='$abcde$', anchor='north')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)
```




```

from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=0, r=0, label='$abcde$', anchor='flushtopleft')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)


```



```

from latextool_basic import *
from latexcircuit import *
p = Plot()
p += Rect(x0=0, y0=0, x1=3, y1=1, linewidth=0.1)
X = POINT(x=0, y=1.1, r=0, label='$abcde$', anchor='flushtopleft')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)


```



```

from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=0, r=0, label='$abcde$', anchor='flushtoprigh')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)


```



```

from latextool_basic import *
from latexcircuit import *
p = Plot()
p += Rect(x0=0, y0=0, x1=3, y1=1, linewidth=0.1)
X = POINT(x=3, y=1.1, r=0, label='$abcde$', anchor='flushtoprigh')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)


```



```

from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=0, r=0, label='$abcde$', anchor='flushbottomleft')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)


```



```

from latextool_basic import *
from latexcircuit import *
p = Plot()
p += Rect(x0=0, y0=0, x1=3, y1=1, linewidth=0.1)
X = POINT(x=3, y=-0.1, r=0, label='$abcde$', anchor='flushbottomleft')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)


```



```

from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=-0.1, r=0, label='$abcde$', anchor='flushbottomright')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)


```



```


from latextool_basic import *
from latexcircuit import *
p = Plot()
p += Rect(x0=0, y0=0, x1=3, y1=1, linewidth=0.1)
X = POINT(x=0, y=0, r=0, label='$abcde$', anchor='flushbottomright')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)

```



15 coordinate

```
from latextool_basic import *
p = Plot()
p += coordinate(0, 0, 'a')
p += coordinate(2, 1, 'b')
p += Line(names=['a', 'b'], endstyle='>')
p += Grid(-1, -1, 3, 2)
print(p)
```



16 Code

The `code` function creates a table based on the string passed in. The linewidths of the cells are set to 0.

```
from latextool_basic import *
p = Plot()

M = r"""
twice (fun x -> x * x) 42
(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42
""".strip()

code(p, M)

print(p)
```

```
twice (fun x -> x * x) 42
(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42
```

Position:


```
from latextool_basic import *
p = Plot()


M = r"""
twice (fun x -> x * x) 42
(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42
""".strip()

p += Circle(x=0, y=0, r=0.5)
code(p, M, x=0, y=0)

p += Circle(x=2, y=2, r=0.5, linecolor='red')
code(p, M, x=2, y=2)

print(p)
```

 twice (fun x -> x * x) 42
(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42

 twice (fun x -> x * x) 42
(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42

16.1 Cell size

```
from latextool_basic import *
p = Plot()

M = r"""
twice (fun x -> x * x) 42
(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42
""".strip()

code(p, M, width=0.3, height=1)

print(p)
```

```
twice (fun x -> x * x) 42
```

```
(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42
```


16.2 border linewidth

```
from latextool_basic import *
p = Plot()

M = r"""
twice (fun x -> x * x) 42
(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42
""".strip()

code(p, M, border_linewidth=0.05)

print(p)
```

```
twice (fun x -> x * x) 42
(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42
```

16.3 distance of border to rect

```
from latextool_basic import *
p = Plot()

M = r"""
twice (fun x -> x * x) 42
(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42
""".strip()

code(p, M, border_linewidth=0.05, innersep=0.8)

print(p)
```

```
twice (fun x -> x * x) 42
(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42
```

16.4 coderec

The return of `code` is just a rect. `coderec` takes in a `code` rect and starting row and column indices and ending row and column indices and returns a rect. The `linecolor` of this rect is red.


```
from latextool_basic import *
p = Plot()

M = r"""
twice (fun x -> x * x) 42

(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42
""".strip()

N = code(p, M)
r0 = coderec(N, 0, 0, 0, 4)
p += r0
r1 = coderec(N, 3, 0, 3, 27)
r1.linecolor='blue'
p += r1

p0 = r0.bottom()
p1 = r1.top(); p1 = (p0[0], p1[1])
p += Line(points=[p0,p1], endstyle='>', linecolor='red')
print(p)
```



twice (fun x -> x * x) 42

(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42

16.5 Substitution

If you want to print ρ which takes more than one character, you can use an unused character in the string and then pass in a dictionary to replace the character to the actual string that you need.

```
from latextool_basic import *
p = Plot()

M = r"""
twice (fun x -> x * x) 42      #

(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42
""".strip()

code(p, M, d={'#':r'\textred{\rho$'}})
print(p)
```

twice (fun x -> x * x) 42 ρ

(fun f -> (fun x -> f(f x))) (fun x -> x * x) 42

16.6 Long division example

`linebelow` is used to draw lines in code. `divlinebelow` is used for long division line.

```
from latextool_basic import *
p = Plot()

M = r"""
.    01
1101 101010101010
    -0000
      10101
      -1101
        10000
          1101
""".strip()

N = code(p, M)
divlinebelow(p, N, 0, 5, 16)
linebelow(p, N, 2, 4, 8)
linebelow(p, N, 4, 5, 9)
print(p)
```

```

      01
1101)101010101010
     -0000
      10101
      -1101
        10000
          1101
```

17 Tables

17.1 `table` function

```
from latextool_basic import table
print(table({0:0, 1:1, 2:4, 3:9, 4:16}))
```

0	0
1	1
2	4
3	9
4	16

Too few row headings:

```
from latextool_basic import table
print(table([(' ', 2, 5, 8),
            (' ', ' ', 3, 6),
            (' ', ' ', ' ', 3),
            (' ', ' ', ' ', ' ')]
            ],
            col_headings = ['0', '2', '5', '8'],
            row_headings = ['0', '2'],
            topleft_heading = r'$\Delta X$',
            ))
```

ΔX	0	2	5	8
0		2	5	8
2			3	6
				3

Too few col headings

```
from latextool_basic import table
print(table([(' ', 2, 5, 8),
            (' ', ' ', 3, 6),
            (' ', ' ', ' ', 3),
            (' ', ' ', ' ', ' ')]
            ],
            col_headings = ['0', '2'],
            row_headings = ['0', '2', '5', '8'],
            topleft_heading = r'$\Delta X$',
            ))
```

ΔX	0	2		
0		2	5	8
2			3	6
5				3
8				

Too few rows of data

```
from latextool_basic import table
print(table([('0', 2, 5, 8),
            ('2', '3', 6),
            ],
            col_headings = ['0', '2', '5', '8'],
            row_headings = ['0', '2', '5', '8'],
            topleft_heading = r'$\Delta X$',
            ))
```

ΔX	0	2	5	8
0		2	5	8
2			3	6
5				
8				

Too few rows of data

```
from latextool_basic import table
print(table([('0', 2, 5, 8),
            ('2', '3', 6),
            ],
            col_headings = ['0', '2', '5', '8'],
            row_headings = ['0', '2', '5', '8'],
            topleft_heading = r'$\Delta X$',
            ))
```

ΔX	0	2	5	8
0		2	5	8
2			3	6
5				
8				

Column headings only (no row headings). Note that topleft heading does not show.

```
from latextool_basic import table
print(table([(' ', 2, 5, ),
            (' ', ' ', 3, ),
            (' ', ' ', ' ', ),
            (' ', ' ', ' ', )
            ],
            col_headings = ['0', '2', '5', '8'],
            topleft_heading = r'$\Delta X$',
            ))
```

0	2	5	8
	2	5	
		3	

Row headings only (no column headings). Note that topleft heading does not show.

```
from latextool_basic import table
print(table([('0', 2, 5),
            ('2', '3', 3),
            ('5', '5', '5'),
            ('8', '5', '5')
            ],
            row_headings = ['0', '2', '5', '8'],
            topleft_heading = r'$\Delta X$',
            ))
```

0		2	5
2			3
5			
8			

Setting column justification.

```
from latextool_basic import table
print(table([('AAAAAAAAAA', 'BBBBBBBBBB', 'CCCCCCCCC'),
            ('1', '2', 3),
            ('', '', ''),
            ('', '', '')],
            ],
            row_headings = ['0', '2', '5', '8'],
            col_headings = ['a', 'b', 'c'],
            topleft_heading = r'$\Delta X$',
            style='|c|l|r|c|',
            ))
```

ΔX	a	b	c
0	AAAAAAAAAA	BBBBBBBBBB	CCCCCCCCC
2	1	2	3
5			
8			

Right row headings

```
from latextool_basic import table
print(table([(' ', 2, 5),
            (' ', ' ', 3),
            (' ', ' ', ' '),
            (' ', ' ', ' ')],
            ],
            right_row_headings = ['0', '2', '5', '8'],
            col_headings = ['a', 'b', 'c'],
            ))
```

a	b	c
	2	5
		3

17.2 table2 function

```
from latextool_basic import *
p = Plot()

m = [['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '3', ''],
      ['', '', '', '', '', ''],
      []]

table2(p, m, width=0.7, height=0.7, rowlabel='x', collabel='y')
print(p)
```

				3		

17.2.1 Change row and column index values/names


```

from latextool_basic import *
p = Plot()

m = [['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '3', ''],
      ['', '', '', '', '', ''],
      []]

table2(p, m, width=0.7, height=0.7, rowlabel='x', collabel='y',
        rownames=[r'\texttt{%s}' % _ for _ in "ABCDE"],
        colnames=[r'\texttt{%s}' % _ for _ in "abcdef"])
print(p)

```



	y					
x	a	b	c	d	e	f
A						
B						
C						
D					3	
E						

17.2.2 No row and column indices/values


```

from latextool_basic import *
p = Plot()

m = [['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '3', ''],
      ['', '', '', '', '', ''],
      []]

table2(p, m, width=0.7, height=0.7, rowlabel='x', collabel='y',
        rownames=[],
        colnames=[])
print(p)

```



17.2.3 Change row/column names

```

from latextool_basic import *

p = Plot()

m = [[0,1,1,0],
      [0,1,0,1],
      [1,0,1,1],
      [0,1,1,1],
      ]

table2(p, m, width=0.7, height=0.7,
        rownames=['00','01','11','10'],
        colnames=['00','01','11','10'],
        rowlabel='$WX$', collabel='$YZ$')
print(p)

```

WX \ YZ	YZ			
	00	01	11	10
00	0	1	1	0
01	0	1	0	1
11	1	0	1	1
10	0	1	1	1

17.2.4 No row and no column names

```

from latextool_basic import *
p = Plot()

m = [['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '3', ''],
      ['', '', '', '', '', ''],
      []]

table2(p, m, width=0.7, height=0.7,
        rownames=[],
        colnames=[],
        rowlabel=None, collabel=None)
print(p)

```

				3	

17.2.5 border_linewidth

```

from latextool_basic import *
p = Plot()

m = [['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '3', ''],
      ['', '', '', '', '', '']]

table2(p, m, x=0, y=0, width=0.7, height=0.7,
        rownames=[],
        colnames=[],
        rowlabel=None, collabel=None, border_linewidth=0)
table2(p, m, x=8, y=0, width=0.7, height=0.7,
        rownames=[],
        colnames=[],
        rowlabel=None, collabel=None, border_linewidth=0.5)
print(p)

```

				3	

				3	

17.2.6 Adding things beneath table2: background

The `do_not_plot` can be used to compute the coordinate of the cells. `table2` will then return the `RectContainer` object but the table is not drawn. So one way to change the background is to do `do_not_plot` to get the coordinates, draw a rect with background color, then call `table2` to draw the contents of the table. (Also, see `rect` parameter later.)

```
from latextool_basic import *

m = [['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '3', ''],
      ['0', '', ''],          # OK to have jagged arrays
      ]


p = Plot()
C = table2(p, m, rowlabel='x', collabel='y', do_not_plot=True)

# Draw over C[1][4]
x0,y0 = C[1][4].bottomleft()
x1,y1 = C[1][4].topright()
p += Rect(x0=x0, y0=y0, x1=x1, y1=y1,
          background='blue!20', label='A', linewidth=0)

# Draw table one more time to get border of C[1][4] correct
table2(p, m, rowlabel='x', collabel='y')


p += Line(points=[C[0][1].center(), C[2][3].center()], endstyle='>')

print(p)
```



17.2.7 Using cells

Drawing arrows between cells using `shorten` function for arrows using a shortening factor:



```
x = "    "
y = "    "
m = [['' for i in range(len(y))] for j in range(len(x))]
m[3][2] = 15
m[2][1] = 26
from latextool_basic import *
p = Plot()
C = table2(p, m, width=0.7, height=0.7,
           rowlabel=r'\texttt{x}', collabel=r'\texttt{y}')


p0 = C[3][2].center()
p1 = C[2][1].center()
p0, p1 = shorten(p0, p1, factor=0.5)
p += Line(points=[p0, p1], endstyle='>')

p0 = C[3][2].center()
p1 = C[2][2].center()
p0, p1 = shorten(p0, p1, factor=0.5)
p += Line(points=[p0, p1], endstyle='>')

p0 = C[3][2].center()
p1 = C[3][1].center()
p0, p1 = shorten(p0, p1, factor=0.5)
p += Line(points=[p0, p1], endstyle='>')

print(p)
```

Drawing arrows between cells using `shorten` function for arrows using a shortening amount:



```
x = "      "
y = "      "
m = [['' for i in range(len(y))] for j in range(len(x))]
from latextool_basic import *
p = Plot()
C = table2(p, m, width=0.7, height=0.7,
           rowlabel=r'\texttt{x}', collabel=r'\texttt{y}')

p0 = C[1][1].center()
p1 = C[3][1].center()
p += Line(points=[p0, p1], endstyle='>', linecolor='red')


p0 = C[1][2].center()
p1 = C[3][2].center()
p0, p1 = shorten(p0, p1, start_by=0.5)
p += Line(points=[p0, p1], endstyle='>', linecolor='green')

p0 = C[1][3].center()
p1 = C[3][3].center()
p0, p1 = shorten(p0, p1, end_by=0.5)
p += Line(points=[p0, p1], endstyle='>', linecolor='blue')

print(p)
```

17.2.8 Rect for cells

You can specify a rect function of your own:




```

from latextool_basic import *

c = RectContainer(x=0, y=0)
xs = 'ABA'; shadedbackground='black!10'
for i,x in enumerate(xs):
    if i in [1,2]:
        c += Rect2(x0=0, y0=0, x1=0.4, y1=0.4,
                    background=shadedbackground,
                    linewidth=0.01, label=r'\texttt{%s}' % x)
    else:
        c += Rect2(x0=0, y0=0, x1=0.4, y1=0.4,
                    background='white',
                    linewidth=0.01, label=r'\texttt{%s}' % x)
q = Plot(); q += c
m = [[str(q),'', '', '', '', ''],
     ['', '', '', '', '', ''],
     ['', '', '', '', '3', ''],
     []]

p = Plot()

def rect(x):
    return Rect(x0=0, y0=0, x1=2, y1=2, radius=0.2, innersep=0.2,
                linecolor='red!30!white', linewidth=0.1,
                background='blue!20!white!', foreground='blue!90!white!',
                s='%s' % x, align='t')

table2(p, m, width=0.7, height=0.7, rowlabel='x', collabel='y', rect=rect)
print(p)

```

17.2.9 Using rect to change the background

You can use the rect to for instance change the background. In the following, the rects at column 2 are given larger width and a different background, and the contents are placed in a minipage with tiny fontsize.

```
from latextool_basic import *
m = [['1','primes: 2, 3, 5, 7, 11, 13, 19, ...',' ',' ',' ',' '],
      [' ',' ',' ',' ',' ',' '],
      [' ',' ',' ',' ',' ',' '],
      [' ',' ',' ',' ','3',' '],
      ]
def get_rect():
    i = [0]
    def rect(x):
        if i[0] % 6 == 1:
            i[0] += 1
            return Rect(x0=0, y0=0, x1=2, y1=1,
                        background='blue!20!white!',
                        innersep=0.1,
                        s=r'\tiny %s' % x, align='t')
        else:
            i[0] += 1
            return Rect(x0=0, y0=0, x1=1, y1=1, label=x)
    return rect
p = Plot()
table2(p, m, rowlabel='x', collabel='y', rect=get_rect())
print(p)
```

	0	1	2	3	4	5
0	1	primes: 2, 3, 5, 7, 11, 13, 19, ...				
1						
2						
3					3	

17.3 table3

table3 ... TABLE OF 2d arrays of 2d arrays:

Use this for truth tables.

17.3.1 Example: 2-by-2 case

```

from latextool_basic import *
p = Plot()

m00 = [['$w$', '$x$', '$y$', '$z$']]
m10 = [['$0$', '', '', ''],
        ['', '', '', ''],
        ['', '', '', ''],
        ['', '', '', ''],
        ['', '', '', '']]
m01 = [['$f$', '$g$'],
        ]
m11 = [['$1$', ''],
        ['', ''],
        ['', ''],
        ['', ''],
        ['', '']]
M = [[m00, m01],
      [m10, m11]]
N = table3(p, M, width=1, height=0.8)
print(p)

```

w	x	y	z	f	g
0				1	

17.3.2 Example: 2-by-2 case with top and left for labels

```

from latextool_basic import *
p = Plot()

rowlabels = ['A', 'B', 'C', 'D', 'E']
collabels = ['a', 'b', 'c']
data = [['00', '01', '02'],
        ['10', '11', '12'],
        ['20', '21', '22'],
        ['30', '31', '32'],
        ['40', '41', '42']]

m00 = [['']]
m10 = [[x] for x in rowlabels]
m01 = [collabels]
m11 = data
M = [[m00, m01],
      [m10, m11]]
N = table3(p, M, width=1, height=0.8)
print(p)

```

	a	b	c
A	00	01	02
B	10	11	12
C	20	21	22
D	30	31	32
E	40	41	42

17.3.3 Example: 2-by-1 case

```

from latextool_basic import *
p = Plot()

m00 = [['$w$', '$x$', '$y$', '$z$'],
        ]
m10 = [['$0$', '', '', ''],
        ['', '', '', ''],
        ['', '', '', ''],
        ['', '', '', ''],
        ['', '', '', ''],
        ]
M = [[m00],
      [m10]]
N = table3(p, M, width=1, height=0.8)
print(p)

```

w	x	y	z
0			

17.3.4 Specify topleft coordinates

```

from latextool_basic import *
p = Plot()

m00 = [['$w$', '$x$', '$y$', '$z$'],
       ]
m10 = [['$0$', '', '', ''],
       ['', '', '', ''],
       ['', '', '', ''],
       ['', '', '', ''],
       ['', '', '', ''],
       ]
M = [[m00],
      [m10]]
table3(p, x0=0, y0=0, M=M, width=1, height=0.8)
table3(p, x0=8, y0=1, M=M, width=1, height=0.8)
print(p)

```

w	x	y	z
0			

w	x	y	z
0			

17.3.5 Example: 2-by-1 case with title

```

from latextool_basic import *
p = Plot()

m00 = [['$w$', '$x$', '$y$', '$z$'],
       ]
m10 = [['$0$', '', '', ''],
       ['', '', '', ''],
       ['', '', '', ''],
       ['', '', '', ''],
       ['', '', '', ''],
       ]
M = [[m00],
      [m10]]
table3(p, M, width=1, height=0.8, title='This is the title')
print(p)

```

This is the title

w	x	y	z
0			

17.3.6 Example: 1-by-2 case

```

from latextool_basic import *
p = Plot()

m00 = [['$w$'], ['$x$'], ['$y$'], ['$z$'],
        ]
m01 = [['0'], ['1'], ['2'], ['3'],
        ]
M = [[m00, m01],
      ]
N = table3(p, M, width=1, height=0.8)
print(p)

```

w	0
x	1
y	2
z	3

17.3.7 table3: accessing cells

```


from latextool_basic import *
p = Plot()

m00 = [['$w$', '$x$', '$y$', '$z$'],
       ]
m10 = [['$0$', '', '', ''],
       ['', '', '', ''],
       ['', '', '', ''],
       ['', '', '', ''],
       ['', '', '', ''],
       ]
m01 = [['$f$', '$g$'],
       ]
m11 = [['$1$', ''],
       ['', ''],
       ['', ''],
       ['', ''],
       ['', ''],
       ]
M = [[m00, m01],
      [m10, m11]]
N = table3(p, M, width=1, height=0.8)
p0 = x0, y0 = N[1][0][3][2].center()
p1 = x1, y1 = x0 + 5, y0 + 1
p += Line(points=[p1, p0], endstyle='>', linecolor='red', linewidth=0.1)
x2, y2 = x1+0.5, y1+0.5
p += Rect(x0=x2, y0=y0, x1=x2, y1=y2, s='look', linewidth=0)
print(p)

```

w	x	y	z	f	g
0				1	

look



17.3.8 Coloring a cell under the table manually

```

from latextool_basic import *
p = Plot()

m00 = [['$w$', '$x$', '$y$', '$z$'],
        ]
m10 = [['$0$', '', '', ''],
        ['', '', '', ''],
        ['', '', '', ''],
        ['', '', '', ''],
        ['', '', '', ''],
        ]
M = [[m00],
      [m10]]

N = table3(p, M, width=1, height=0.8)

r = N[1][0][2][3]
x0,y0 = r.bottomleft()
x1,y1 = r.topright()
p += Rect(x0=x0, y0=y0, x1=x1, y1=y1, background='blue!20', label='42',
          linewidth=0)

N = table3(p, M, width=1, height=0.8)

print(p)

```

w	x	y	z
0			
			42

17.3.9 Coloring a cell under the table using table3

```

from latextool_basic import *
p = Plot()

m00 = [['$w$', '$x$', '$y$', '$z$'],
        ]
m10 = [['$0$', '', '', ''],
        ['', '', '', ''],
        ['', '', '', '42'],
        ['', '', '', ''],
        ['', '', '', ''],
        ]
M = [[m00],
      [m10]]

N = table3(p, M, width=2, height=0.5,
           background={(1,0,2,3): 'blue!20'})

print(p)

```

w	x	y	z
0			
			42

17.3.10 Cells of different widths (table2)

```
from latextool_basic import *
p = Plot()

i = 0
def rect(x):
    global i
    if i % 2 == 0:
        i += 1
        return Rect(x0=0, y0=0, x1=1, y1=0.7, s=x)
    else:
        i += 1
        return Rect(x0=0, y0=0, x1=3, y1=0.7, s=x)

m = [[0,1,2,3],
      [4,5,6,7],
      [8,9,10,11],
      [12,13,14,15],
      ]

table2(p, m, rect=rect)
print(p)
```

17.3.11 Cells of different widths (table3)

```

from latextool_basic import *
p = Plot()

i = 0
def rect(x):
    global i
    if i in [0,3,6,8,10,13,16,19,21,23]:
        i += 1; return Rect(x0=0, y0=0, x1=1, y1=0.7, label=x)
    elif i in [1,4,7,9,11,14,17,20,22,24]:
        i += 1; return Rect(x0=0, y0=0, x1=3, y1=0.7, label=x)
    else:
        i += 1; return Rect(x0=0, y0=0, x1=5, y1=0.7, label=x)

m00 = [[0,1,2],
        [3,4,5]]
m01 = [[6,7],
        [8,9]]
m10 = [[10,11,12],
        [13,14,15],
        [16,17,18]]
m11 = [[19,20],
        [21,22],
        [23,24]]
M = [[m00, m01],
      [m10, m11]]
table3(p, M, rect=rect)
print(p)

```

0	1	2	6	7
3	4	5	8	9
10	11	12	19	20
13	14	15	21	22
16	17	18	23	24

17.3.12 ragged arrays (error - to fix)

```

from latextool_basic import *
p = Plot()

i = 0
def rect(x):
    global i
    if i in [0,3,6,8,10,13,16,19,21,23]:
        i += 1; return Rect(x0=0, y0=0, x1=1, y1=0.7, label=x)
    elif i in [1,4,7,9,11,14,17,20,22,24]:
        i += 1; return Rect(x0=0, y0=0, x1=3, y1=0.7, label=x)
    else:
        i += 1; return Rect(x0=0, y0=0, x1=5, y1=0.7, label=x)

m00 = [[0,1,2],
        [3,4,5]]
m01 = [[6,7],
        [8,9]]
m10 = [[10,11,12],
        [13,14,15],
        [16,17,18]]
m11 = [[19,20],
        [21,22],
        [23,24]]
M = [[m00, m01],
      [m10, m11]]
table3(p, M, rect=rect)
print(p)

```

0	1	2	6	7
3	4	5	8	9
10	11	12	19	20
13	14	15	21	22
16	17	18	23	24

17.3.13 Justification

```

from latextool_basic import *
p = Plot()

i = 0
def rect(x):
    global i
    if i in [0,3,6,8,10,13,16,19,21,23]:
        i += 1; return Rect(x0=0, y0=0, x1=1, y1=0.7, label=x)
    elif i in [1,4,7,9,11,14,17,20,22,24]:
        i += 1; return Rect(x0=0, y0=0, x1=3, y1=0.7, label=x)
    else:
        i += 1; return Rect(x0=0, y0=0, x1=5, y1=0.7, label=x)

m00 = [[0,1,2],
        [3,4,5]]
m01 = [[6,7],
        [8,9]]
m10 = [[10,11,12],
        [13,14,15],
        [16,17,18]]
m11 = [[19,20],
        [21,22],
        [23,24]]
M = [[m00, m01],
      [m10, m11]]
table3(p, M, rect=rect)
print(p)

```

0	1	2	6	7
3	4	5	8	9
10	11	12	19	20
13	14	15	21	22
16	17	18	23	24

17.3.14 title

```

from latextool_basic import *
p = Plot()

i = 0
def rect(x):
    global i
    i += 1
    return Rect(x0=0, y0=0, x1=1.8, y1=0.8, label=x)

m00 = [['A', 'B', 'C']]

s = r"""
1 2 3
4 5 6
7 8 9
"""
X = str_to_2darray(s)
M = [[[X[0]]],
      [X[1:]],
      ]
table3(p, M, rect=rect, title='This is a title')
print(p)

```

This is a title

1	2	3
4	5	6
7	8	9

17.3.15 Title distance

```

from latextool_basic import *
p = Plot()

i = 0
def rect(x):
    global i
    i += 1
    return Rect(x0=0, y0=0, x1=1.8, y1=0.8, label=x)

m00 = [['A', 'B', 'C']]

s = r"""
1 2 3
4 5 6
7 8 9
"""
X = str_to_2darray(s)
M = [[[X[0]]],
      [X[1:]],
      ]
table3(p, M, rect=rect, title='This is a title', title_distance=0.8)
print(p)

```

This is a title

1	2	3
4	5	6
7	8	9

17.4 table4

```
from latextool_basic import *
p = Plot()
M = [['a', 'b', 'c'],
      [0, 1, 2],
      [3, 4, 5],
      [6, 7, 8]]
widths=[0.8, 1.5, 3]
N = table4(p=p, M=M, widths=widths)
print(p)
```

a	b	c
0	1	2
3	4	5
6	7	8

title distance:

```
from latextool_basic import *
p = Plot()
M = [['a', 'b', 'c'],
      [0, 1, 2],
      [3, 4, 5],
      [6, 7, 8]]
widths=[0.8, 1.5, 3]
N = table4(p=p, M=M, widths=widths, title='This is the title')
print(p)
```

This is the title

a	b	c
0	1	2
3	4	5
6	7	8

make caption:

```
from latextool_basic import *
from latexcircuit import *
p = Plot()
M = [['a', 'b', 'c'],
      [0, 1, 2],
      [3, 4, 5],
      [6, 7, 8]]
widths=[0.8, 1.5, 3]
N = table4(p=p, M=M, widths=widths, title='This is the title')
x0,y0 = N[-1][0].bottomleft()
x1,y1 = N[-1][-1].bottomright()
y = y0
x = (x0 + x1) / 2
p += POINT(x=x, y=y, r=0, label='This is the caption', anchor='north')
print(p)
```

This is the title

a	b	c
0	1	2
3	4	5
6	7	8


17.5 helper for 2d arrays

```
from latextool_basic import *
p = Plot()
M = r"""
a b c
0 1 2
3 4 5
6 7 8
"""
M = str_to_2darray(M)
widths=[0.8, 1.5, 3]
N = table4(p=p, M=M, widths=widths)
print(p)
```

a	b	c
0	1	2
3	4	5
6	7	8


18 diamond

```
from latextool_basic import *  
p = Plot()  
p += Grid(-2,-2,2,2)  
p += diamond(center=(0,0))  
print(p)
```




Width, height:

```
from latextool_basic import *
p = Plot()
p += Grid(-2,-1,2,1)
p += diamond(center=(0,0), width=2, height=1)
print(p)
```




```
from latextool_basic import *
p = Plot()
p += Grid(-2,-1,2,1)
p += diamond(center=(0,0), width=1, height=2)
print(p)
```



double line:

```
from latextool_basic import *
p = Plot()


p += Grid(-2,-2,2,2)
p += diamond(center=(0,0), double=True)
print(p)
```



double line with double distance


```
from latextool_basic import *
p = Plot()

p += Grid(-3,-2,3,2)
p += diamond(center=(0,0), double=True, double_distance=0.5)
print(p)
```




double and label

```
from latextool_basic import *  
p = Plot()  
  
p += Grid(-2,-2,2,2)  
p += diamond(center=(0,0), double=True, label='test')  
print(p)
```



```
from latextool_basic import *  
p = Plot()  
  
p += Grid(-2,-2,2,2)  
p += diamond(center=(0,0), double=True, label='this is a long string')  
print(p)
```



19 Circle

19.1 boundary


```
from latextool_basic import *
from latexcircuit import *

p = Plot()
p += Circle(x=0, y=0, r=0.5, background='black')
p += Circle(x=3, y=0, r=0.08, background='black', name=None)

p += str(OrthogonalPath([(0,-2), (5,-1)]))

p += POINT(x=0, y=-3)
p += '%s' % Circle(x=0, y=-5, r=0.08, background='black', name=None)


p += Grid()
print(p)
```



•


19.2 boundary

```
from latextool_basic import *
p = Plot()
p += Circle(x=0.5, y=0.5, r=0.5)
p += Circle(x=2.5, y=0.5, r=0.5, linewidth=0)
p += Circle(x=4.5, y=0.5, r=0.5, linewidth=0.05)
p += Circle(x=6.5, y=0.5, r=0.5, linewidth=0.05, linestyle='dashed')
p += Circle(x=8.5, y=0.5, r=0.5, linewidth=0.1, linestyle='dashed',
            linecolor='red')
p += Circle(x=10.5, y=0.5, r=0.5, linewidth=0.1, linestyle='double',
            linecolor='red')
p += Grid()
print(p)
```



19.3 background

```
from latextool_basic import *
p = Plot()
p += Circle(x=0.5, y=0.5, r=0.5)
p += Circle(x=2.5, y=0.5, r=0.5, linewidth=0, background='green')
p += Circle(x=4.5, y=0.5, r=0.5, linewidth=0.05, background='green')
p += Circle(x=6.5, y=0.5, r=0.5, linewidth=0.05, linestyle='dashed',
            background='green')
p += Circle(x=8.5, y=0.5, r=0.5, linewidth=0.1, linestyle='dashed',
            linecolor='red', background='green')
p += Circle(x=10.5, y=0.5, r=0.5, linewidth=0.1, linestyle='double',
            linecolor='red', background='green')
p += Grid()
print(p)
```




19.4 s: minipage text in circle

```

from latextool_basic import *
p = Plot()
s = 'a b c d e f'
p += Circle(x=0, y=0, r=1, linecolor='green!50!white', linewidth=0.3,
            background='blue!20!white', foreground='red', innersep=0, s=s)
p += Circle(x=5, y=0, r=1, linecolor='green!50!white', linewidth=0.2,
            background='blue!20!white', foreground='red', innersep=0, s=s)
p += Circle(x=10, y=0, r=1, linecolor='green!50!white', linewidth=0.1,
            background='blue!20!white', foreground='red', innersep=0, s=s)
p += Circle(x=0, y=-3, r=1, linecolor='green!50!white', linewidth=0,
            background='blue!20!white', foreground='red', innersep=0, s=s)
p += Circle(x=5, y=-3, r=1, linecolor='green!50!white', linewidth=0,
            background='blue!20!white', foreground='red',
            innersep=0.2, s=s)
p += Circle(x=10, y=-3, r=1, linecolor='green!50!white', linewidth=0,
            background='blue!20!white', foreground='red',
            innersep=0.4, s=s)
p += Grid()
print(p)

```



19.5 label anchor

```
from latextool_basic import *
p = Plot()
label = 'a'
p += Circle(x=0, y=0, r=1, label=label, anchor='above')
p += Grid()
print(p)
```

PYTHON ERROR. See source, stderr, stdout below

```
from latextool_basic import *
p = Plot()
label = 'a'
p += Circle(x=0, y=0, r=1, label=label, anchor='above')
p += Grid()
print(p)
```

```
Traceback (most recent call last):
  File "/usr/lib64/python3.7/site-packages/latextool_basic.py", line 715, i
n __str__
    shape, arg, karg = value
TypeError: cannot unpack non-iterable Circle object
```

During handling of the above exception, another exception occurred:


```
Traceback (most recent call last):
  File "/usr/lib64/python3.7/site-packages/latextool_basic.py", line 722, i
n __str__
    s += str(value)
  File "/usr/lib64/python3.7/site-packages/latextool_basic.py", line 1215,
in __str__
    name=name,
  File "/usr/lib64/python3.7/site-packages/latextool_basic.py", line 1154,
in circle
    % d1
KeyError: 'anchor'
```

During handling of the above exception, another exception occurred:

```
Traceback (most recent call last):
  File "ixilbqpe.tmp.py", line 6, in <module>
    print(p)
  File "/usr/lib64/python3.7/site-packages/latextool_basic.py", line 724, i
n __str__
    raise ValueError("str method in Plot error: %s, type:%s" % (value, type
(value)))
  File "/usr/lib64/python3.7/site-packages/latextool_basic.py", line 1215,
in __str__
    name=name,
  File "/usr/lib64/python3.7/site-packages/latextool_basic.py", line 1154,
in circle
    % d1
KeyError: 'anchor'
```


19.6 foreground

```
from latextool_basic import *
p = Plot()
p += Circle(x=0, y=0, r=1, foreground='red', label='a')
p += Circle(x=3, y=0, r=1, background='blue!20!white',
            foreground='red', label='$q_0$')
p += Grid()
print(p)
```



19.7 Center and boundary

```
s='1 2 3 4 5 6 7 8 9 10 11'
b1 = 'blue!50!white'
b2 = 'red!50!white'

from latextool_basic import *
p = Plot()

c1 = Circle(x=0, y=0, r=1, background=b1, s=s)
c2 = Circle(center=c1.center(), r=0.5, background=b2)
p += c1; p += c2

c1 = Circle(x=3, y=0, r=1, background=b1, s=s)
c2 = Circle(center=c1.left(), r=0.5, background=b2)
p += c1; p += c2

c1 = Circle(x=6, y=0, r=1, background=b1, s=s)
c2 = Circle(center=c1.right(), r=0.5, background=b2)
p += c1; p += c2


c1 = Circle(x=9, y=0, r=1, background=b1, s=s)
c2 = Circle(center=c1.top(), r=0.5, background=b2)
p += c1; p += c2

c1 = Circle(x=12, y=0, r=1, background=b1, s=s)
c2 = Circle(center=c1.bottom(), r=0.5, background=b2)
p += c1; p += c2

p += Grid()
print(p)
```


19.8 tikz name

```
from latextool_basic import *  
p = Plot()  
  
p += Circle(center=(0,0), r = 1, label=r'$a$', name='a')  
p += Circle(center=(5,0), r = 1, label=r'$b$', name='b')  
  
p += Line(names=['a', 'b'], linewidth=0.05, endstyle='>')  
  
print(p)
```



Test with and without name:

```
from latextool_basic import *  
p = Plot()  
  
p += Circle(center=(0,0), r = 1, label=r'$a$', name='a')  
p += Circle(center=(5,0), r = 1, label=r'$b$')  
  
p += r"\draw[->,line width=2] (a) -- (b);"  
  
print(p)
```




20 Ellipse

```
from latextool_basic import *
p = Plot()

p += Grid(-2,-2,2,2)
p += ellipse(-2,-1,2,1)
print(p)
```

```
from latextool_basic import *
p = Plot()


p += Grid(-2,-2,2,2)
p += ellipse(-2,-1,2,1)
print(p)
```



```
from latextool_basic import *
p = Plot()

p += Grid(-2,-2,2,2)
p += ellipse(-2,-1,2,1,double=True)
print(p)
```


```
from latextool_basic import *  
p = Plot()  
  
p += Grid(-2,-2,2,2)  
p += ellipse(-2,-1,2,1,double=True)  
print(p)
```



21 arc


Draw part of a circle. The x, y is the starting point, NOT the center.

```
from latextool_basic import Plot, Grid, arc
p = Plot()
p += arc(x=0, y=0, r=1, angle0=0, angle1=45)
p += Grid(x0=-1, y0=0, x1=1, y1=1)
print(p)
```




Linewidth:

```
from latextool_basic import Plot, Grid, arc
p = Plot()
p += arc(x=0, y=0, r=1, angle0=0, angle1=45, linewidth=0.2)
p += Grid(x0=-1, y0=0, x1=1, y1=1)
print(p)
```




Color:

```
from latextool_basic import Plot, Grid, arc
p = Plot()
p += arc(x=0, y=0, r=1, angle0=0, angle1=45,
         linewidth=0.2, linecolor='red')
p += Grid(x0=-1, y0=0, x1=1, y1=1)
print(p)
```




Linestyle:

```
from latextool_basic import Plot, Grid, arc
p = Plot()
p += arc(x=0, y=0, r=1, angle0=0, angle1=45,
         linewidth=0.2, linecolor='red', linestyle='dashed')
p += Grid(x0=-1, y0=0, x1=1, y1=1)
print(p)
```




Change starting point of arc:

```
from latextool_basic import Plot, Grid, arc
p = Plot()
p += arc(x=1, y=0, r=1, angle0=0, angle1=45,
         linewidth=0.2, linecolor='red', linestyle='dashed')
p += Grid(x0=-1, y0=0, x1=1, y1=1)
print(p)
```




Arrow:


```
from latextool_basic import Plot, Grid, arc
p = Plot()
p += arc(x=1, y=0, r=1, angle0=0, angle1=45,
         linewidth=0.2, endstyle='>')
p += Grid(x0=-1, y0=0, x1=1, y1=1)
print(p)
```


```
from latextool_basic import Plot, Grid, arc
p = Plot()
p += arc(x=1, y=0, r=1, angle0=0, angle1=90,
         linewidth=0.2, endstyle='>')
p += Grid(x0=-1, y0=0, x1=1, y1=1)
print(p)
```




```
from latextool_basic import Plot, Grid, arc
p = Plot()
p += arc(x=1, y=0, r=1, angle0=0, angle1=350,
         linewidth=0.2, endstyle='>')
p += Grid(x0=-1, y0=0, x1=1, y1=1)
print(p)
```



```
from latextool_basic import Plot, Grid, arc
p = Plot()
p += arc(x=1, y=0, r=1, angle0=0, angle1=360,
         linewidth=0.2, endstyle='>')
p += Grid(x0=-1, y0=0, x1=1, y1=1)
print(p)
```




```
from latextool_basic import Plot, Grid, arc
p = Plot()
p += arc(x=1, y=0, r=1, angle0=90, angle1=360+80,
         linewidth=0.2, endstyle='>')
p += Grid(x0=-1, y0=0, x1=1, y1=1)
print(p)
```



Start style

```
from latextool_basic import Plot, Grid, arc
p = Plot()
p += arc(x=1, y=0, r=1, angle0=90, angle1=360+80,
         linewidth=0.2, startstyle='>')
p += Grid(x0=-1, y0=0, x1=1, y1=1)
print(p)
```




Start and end style

```

from latextool_basic import Plot, Grid, arc
p = Plot()
p += arc(x=1, y=0, r=1, angle0=10, angle1=350,
        linewidth=0.2, startstyle='>', endstyle='>')
p += Grid(x0=-2, y0=-2, x1=2, y1=2)
print(p)

```




With center:

```

from latextool_basic import Plot, Grid, arc
p = Plot()
p += arc(center=(0,0), r=1, angle0=0, angle1=90,
        linewidth=0.2, endstyle='>')
p += Grid(x0=-1, y0=0, x1=1, y1=1)
print(p)

```



22 Polygon

```




import random; random.seed()
from latextool_basic import *

def IFELSE(b, x, y):
    if b: return x
    else: return y

def polygon(points,
            background=None, # if background is None, no fill
            linewidth=None,
            linecolor=None,
            ):
    if points[-1] != points[0]: points.append(points[0])
    points_str = " -- ".join(["(%s,%s)" % (x,y) for (x,y) in points])
    interior = IFELSE(background, "fill=%s" % background, '')
    boundary = ''
    if linewidth or linecolor:
        if not linecolor: linecolor='black'
        if not linewidth: linewidth=0.02
        boundary = 'draw=%s, line width=%scm' % (linecolor, linewidth)
    return r"\path [%s, %s] %s;" % (interior, boundary, points_str)

p = Plot()
points = [(0,2)] + \
    [(i/2.0, random.randrange(3*2,5*2)/4.0) for i in range(1, 5)] + \
    [(i/2.0, random.randrange(0,3*2)/4.0) for i in range(5,1,-1)]
p += polygon(points=points, background='blue!20')
p += polygon(points=[(x+4,y) for (x,y) in points], linewidth=0.02)
p += polygon(points=[(x+8,y) for (x,y) in points], linewidth=0.02,
            background='blue!20')
p += polygon(points=[(x+12,y) for (x,y) in points], linewidth=0.1,
            background='blue!20', linecolor='red')
print(p)

```



23 Relative node placement

Temporary fix to relative node placement: use the `next_to` function.

<http://tex.stackexchange.com/questions/69439/how-can-i-achieve-relative-positioning-i>

```
from latextool_basic import *
p = Plot()
p += ellipse(1, 1, 4, 2, name='a', label='a')
b = str(ellipse(5, 2, 7, 3, name='b', label='b'))
p += b
print(p)
```



```
from latextool_basic import *
p = Plot()
p += ellipse(1, 1, 4, 2, name='a', label='a')
b = str(ellipse(5, 2, 7, 3, name='b', label='b'))
b = next_to(b, name='a', directions=('right', 0))
p += b
print(p)
```



```
from latextool_basic import *
p = Plot()
p += ellipse(1, 1, 4, 2, name='a', label='a')
b = str(ellipse(5, 2, 7, 3, name='b', label='b'))
b = next_to(b, name='a', directions=('left', 1))
p += b
print(p)
```



```
from latextool_basic import *
p = Plot()
p += ellipse(1, 1, 4, 2, name='a', label='a')

x = str(ellipse(5, 2, 7, 3, name='b', label='b'))
x = next_to(x, name='a', directions=('right', 1))
p += x

x = str(ellipse(5, 2, 7, 3, name='c', label='c'))
x = next_to(x, name='b', directions=('right', 1))
p += x

x = str(ellipse(5, 2, 7, 3, name='d', label='d'))
x = next_to(x, name='c', directions=('right', 1))
p += x

print(p)
```



Example that uses both =of and anchor:

```
from latextool_basic import *
p = Plot()
p += r'\node[minimum width=5cm, draw, rectangle] (basis) {};'
p += r'\node[above=of basis.north west, anchor=south west, draw, rectangle,
minimum width=1cm] (a) {A};'
p += r'\node[above=of basis, draw, rectangle,minimum width=1cm] (b) {B};'
p += r'\node[above=of basis.north east, anchor=south east, draw, rectangle,
minimum width=1cm] (c) {C};'
print(p)
```

A B C

Example that uses both =of and anchor and labeling a rect. Basically flushing left on two nodes.

```
from latextool_basic import *
p = Plot()
p += r'\node[minimum width=5cm, draw, rectangle] (basis) {};'
p += r'\node[above=0.2cm of basis.north west, anchor=south west, rectangle,
  minimum width=1cm, inner sep=0cm] (a) {This is the title};'
print(p)
```


This is the title



24 Bounding nodes


Bounding box (rectangle) for a group of tikz nodes:

```
from latextool_basic import *
p = Plot()
p += Rect(0,0,1,1,name='a')
p += Rect(2,0,3,1,name='b')
p += ellipse(center=(5,2), width=2, height=1, name='c')
p += r'\node [draw=black, fit=(a) (b) (c), line width=0.1cm, inner sep=0.0cm] {};'
print(p)
```



Bounding ellipse for a group of tikz nodes:

```
from latextool_basic import *
p = Plot()
p += Rect(0,0,1,1,name='a')
p += Rect(2,0,3,1,name='b')
p += ellipse(center=(5,2), width=2, height=1, name='c')
p += r'\node [ellipse, draw=black, fit=(a) (b) (c), line width=0.1cm, inner sep=0.0cm] {};'
print(p)
```




Put a node below a group of nodes:

```

from latextool_basic import *
p = Plot()
p += Rect(0,0,1,1,name='a')
p += Rect(2,0,3,1,name='b')
p += ellipse(center=(5,2), width=2, height=1, name='c')
p += r'\node [draw=black, fit=(a) (b) (c), inner sep=0.0cm, dashed] (X) {};
'
p += r'\node [draw=black, rectangle, minimum width=1cm, below=1cm of X, minimum height=1cm, distance=2cm] (Y) {Y};'
print(p)

```




fit function:

```

from latextool_basic import *
p = Plot()
p += Rect(0,0,1,1,name='a')
p += Rect(2,0,3,1,name='b')
p += ellipse(center=(5,2), width=2, height=1, name='c')
p += fit(name='X', names=['a', 'b', 'c'], linecolor='red')
print(p)

```




fit function with label:

```

from latextool_basic import *
p = Plot()
p += Rect(0,0,1,1,name='a')
p += Rect(2,0,3,1,name='b')
p += ellipse(center=(5,2), width=2, height=1, name='c')
p += fit(name='X', names=['a', 'b', 'c'], linecolor='red', label='XYZ')
print(p)

```




fit function with shape:

```

from latextool_basic import *
p = Plot()
p += Rect(0,0,1,1,name='a')
p += Rect(2,0,3,1,name='b')
p += ellipse(center=(5,2), width=2, height=1, name='c')
p += fit(name='X', names=['a', 'b', 'c'], shape='ellipse', linecolor='red')
print(p)

```




25 Axes


```
from latextool_basic import *  
p = Plot()  
axes(p, x0=0, y0=0, x1=10, y1=3)  
print(p)
```




```
from latextool_basic import *  
p = Plot()  
p += Grid(x0=0, y0=0, x1=10, y1=3)  
axes(p, x0=0, y0=0, x1=10, y1=3)  
print(p)
```



```
from latextool_basic import *  
p = Plot()  
p += Grid(x0=0, y0=0, x1=10, y1=3, label_axes=False)  
axes(p, x0=0, y0=0, x1=10, y1=3)  
print(p)
```




```
from latextool_basic import *  
p = Plot()  
p += Grid(x0=-2, y0=-1, x1=8, y1=2, label_axes=False)  
axes(p, x0=-2, y0=-1, x1=8, y1=2)  
print(p)
```



NEW VERSION

```
from latextool_basic import *
p = Plot()
xaxis = XAxis(x0=0, y0=0,
              start=5.0, end=20.0,
              xscale=1.0,
              start_tick=0.2, end_tick=12.25,
              tick_gap=0.25,
              tick_len=0.05,
              start_label=6.0, end_label=18.0,
              label_gap=1,
              label_anchor_gap=0,
              label_fontsize=r'\small',
              arrowhead=None)


p += Circle(x=0, y=0, r=0.1, background='red')
p += Circle(x=1, y=0, r=0.1, background='blue')
p += str(xaxis)
print(p)
```



26 Lines

26.1 linecolor and linewidth

```
from latextool_basic import *
p = Plot()
p += Line(x0=0, y0=0, x1=1, y1=1)
p += Line(x0=3, y0=0, x1=6, y1=2, linecolor='red', linewidth=0.1)
p += Line(x0=6, y0=0, x1=9, y1=2, linecolor='red', linewidth=0.2,
          linestyle='dashed')
p += Grid()
print(p)
```




26.2 startstyle and endstyle

```

from latextool_basic import *
p = Plot()
p += Line(x0=0, y0=0, x1=1, y1=1, startstyle='>')
p += Line(x0=3, y0=0, x1=6, y1=2, linecolor='red', linewidth=0.1,
          endstyle='>')
p += Line(x0=6, y0=0, x1=9, y1=2, linecolor='red', linewidth=0.2,
          linestyle='dashed',
          startstyle='>', endstyle='>')
p += Line(x0=9, y0=0, x1=12, y1=2, linecolor='blue', linewidth=0.1,
          startstyle='>|', endstyle='>|')
p += Line(x0=12, y0=0, x1=15, y1=2, linecolor='blue', linewidth=0.05,
          startstyle='>>', endstyle='>>')
p += Grid()
print(p)


```



arrowstyle=triangle.


```
from latextool_basic import *
p = Plot()
p += Line(x0=0, y0=0, x1=1, y1=1, startstyle='->', arrowstyle='triangle')
p += Line(x0=3, y0=0, x1=6, y1=2, linecolor='red', linewidth=0.1,
          endstyle='->', arrowstyle='triangle')
p += Line(x0=6, y0=0, x1=9, y1=2, linecolor='red', linewidth=0.2,
          linestyle='dashed',
          startstyle='->', endstyle='->',
          arrowstyle='triangle')

p += Grid()
print(p)
```




```
startstyle='dot'.
```

```
from latextool_basic import *
p = Plot()
p += Line(x0=0, y0=0, x1=1, y1=1, startstyle='->',
          arrowstyle='triangle', endstyle='dot')
p += Line(x0=3, y0=0, x1=6, y1=2, linecolor='red', linewidth=0.02,
          endstyle='->', arrowstyle='triangle',
          startstyle='dot', r=0.2)
p += Line(x0=6, y0=0, x1=9, y1=2, linecolor='black', linewidth=0.05,
          linestyle='dashed', startstyle='dot',
          endstyle='->', arrowstyle='triangle')
p += Grid()
print(p)
```



26.3 points parameter

```
from latextool_basic import *
p = Plot()
p += Line(points=[(1,4), (0,0), (5,0), (6,3)],
          linecolor='blue', linewidth=0.1,
          startstyle='->', arrowstyle='triangle', endstyle='dot')
p += Grid()
print(p)
```




26.4 boundary points

```

from latextool_basic import *
p = Plot()

aline = Line(points=[(1,4), (0,0), (5,0), (6,3)],
              linecolor='blue', linewidth=0.1,
              startstyle='->', arrowstyle='triangle', endstyle='dot')
p += aline
p += Circle(center=aline.top(), r=0.25, background='red')
p += Circle(center=aline.bottom(), r=0.25, background='red')
p += Circle(center=aline.left(), r=0.25, background='red')
p += Circle(center=aline.right(), r=0.25, background='red')
p += Circle(center=aline.topleft(), r=0.25, background='red')
p += Circle(center=aline.topright(), r=0.25, background='red')
p += Circle(center=aline.bottomleft(), r=0.25, background='red')
p += Circle(center=aline.bottomright(), r=0.25, background='red')
p += Grid()
print(p)

```




Test points

```
from latextool_basic import *
p = Plot()

aline = Line(points=[(1,4), (0,0), (5,0), (6,3)],
              linecolor='blue', linewidth=0.1,
              startstyle='->', arrowstyle='triangle', endstyle='dot')
for point in aline.points:
    p += Circle(center=point, r=0.3, background='red')

p += aline
p += Grid()
print(p)
```




26.5 Midpoints

Test midpoint (can be useful for weighted graphs and network flows).


```
from latextool_basic import *
p = Plot()
points = [(0,-1), (10,3)]
aline = Line(points=points, endstyle='>', linewidth=0.1)
p += aline

p += Circle(center=aline.midpoint(), r=0.4,
            background='white', label=r'\texttt{%s}' % 42)
p += Grid()
print(p)
```




Test midpoint with different ratios.

```
from latextool_basic import *
p = Plot()
def linewidthpoints(p, points, color1, color2):
    aline = Line(points=points, linecolor=color1, linewidth=0.2,
        startstyle='dot', arrowstyle='triangle', endstyle='->')
    p += aline
    for i in [0, 0.2, 0.4, 0.6, 0.8, 1.0]:
        p += Circle(center=aline.midpoint(ratio=i), r=0.4,
            background=color2, label=r'\texttt{%s}' % i)
linewidthpoints(p, [(0, 0), (10, 0)], 'red', 'red!20')
linewidthpoints(p, [(10, -1), (0, -1)], 'red', 'red!20')
linewidthpoints(p, [(0, -2), (10, -3)], 'blue', 'red!20')
linewidthpoints(p, [(10, -4), (0, -3)], 'blue', 'red!20')
linewidthpoints(p, [(0, -6), (10, -5)], 'blue', 'red!20')
linewidthpoints(p, [(10, -6), (0, -7)], 'blue', 'red!20')
linewidthpoints(p, [(11, -7), (11, 0)], 'green', 'red!20')
linewidthpoints(p, [(12, 0), (12, -7)], 'green', 'red!20')
p += Grid()
print(p)
```




Test midpoint for 1 segment.

```
from latextool_basic import *
p = Plot()
points = [(0,-1), (10,3), (12,-2), (5,-1), (5,-2), (1,-2)]
aline = Line(points=points, linecolor='blue', linewidth=0.2,
             startstyle='dot', arrowstyle='triangle', endstyle='->')
p += aline
for i in [0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0]:
    p += Circle(center=aline.midpoint(ratio=i), r=0.4,
               background='red!20', label=r'\texttt{%s}' % i)
p += Grid()
print(p)
```



Test short line with arrow tip (basically to test arrow tip).

```
from latextool_basic import *
p = Plot()
for i, x in enumerate([0.2, 0.15, 0.1, 0.05, 0.01]):
    p += Line(points=[(1-x, i), (1, i)], linecolor='blue', linewidth=x,
               endstyle='->')
    p += Line(points=[(4-x, i), (4, i)], linecolor='blue', linewidth=x,
               endstyle='->', arrowstyle='triangle')
#p += Grid()
print(p)
```



For arrows with line width x , it seems enough to have a length of x .


26.6 tikz names

line from tikz name to tikz name:

```
from latextool_basic import *
p = Plot()
p += Rect(x0=1, y0=0, x1=2, y1=1, label='a', name='a')
p += Rect(x0=5, y0=1, x1=6, y1=2, label='b', name='b')

p += Line(names=['a', 'b'], endstyle='>')

print(p)
```




26.7 bend

```
from latextool_basic import *
p = Plot()

p += Circle(x=0, y=0, r=1, name='a', label='a')
p += Circle(x=4, y=0, r=1, name='b', label='b')
p += Circle(x=8, y=3, r=1, name='c', label='c')

p += Line(names=['a','b','c'], bend_left=30, endstyle='>', linewidth=0.1)


print(p)
```



26.8 label and anchor


anchor = below

```
from latextool_basic import *
p = Plot()
p += Circle(x=0, y=0, r=0.3, name='a', label='a')
p += Circle(x=10, y=0, r=0.3, name='b', label='b')
p += Line(names=['a', 'b'], anchor='below', label='hello')
print(p)
```




anchor = below with bend

```
from latextool_basic import *
p = Plot()
p += Circle(x=0, y=0, r=0.3, name='a', label='a')
p += Circle(x=10, y=0, r=0.3, name='b', label='b')
p += Line(names=['a', 'b'], bend_left=30, anchor='below', label='hello')
print(p)
```




anchor = above

```
from latextool_basic import *
p = Plot()
p += Circle(x=0, y=0, r=0.3, name='a', label='a')
p += Circle(x=10, y=0, r=0.3, name='b', label='b')
p += Line(names=['a', 'b'], bend_left=30, anchor='above', label='hello')
print(p)
```




anchor = above with bend

```
from latextool_basic import *
p = Plot()
p += Circle(x=0, y=0, r=0.3, name='a', label='a')
p += Circle(x=10, y=0, r=0.3, name='b', label='b')
p += Line(names=['a', 'b'], bend_left=30, anchor='above', label='hello')
print(p)
```



anchor = left with bend

```
from latextool_basic import *
p = Plot()
p += Circle(x=0, y=0, r=0.3, name='a', label='a')
p += Circle(x=0, y=3, r=0.3, name='b', label='b')
p += Line(names=['a', 'b'], bend_left=30, anchor='left', label='hello')
print(p)
```



anchor = right with bend

```
from latextool_basic import *
p = Plot()
p += Circle(x=0, y=0, r=0.3, name='a', label='a')
p += Circle(x=0, y=3, r=0.3, name='b', label='b')
p += Line(names=['a', 'b'], bend_left=30, anchor='right', label='hello')
print(p)
```




26.9 Using midpoint to place labels

```
from latextool_basic import *
p = Plot()
aline = Line(points=[(0,0), (3,0)])
p += aline
x,y = aline.midpoint(ratio=0.2)

from latexcircuit import *
p += Circle(x=x, y=y, r=0.05, background='red')
X = POINT(x=x, y=y, label='$abcde$', anchor='south')
p += str(X)

print(p)
```




26.10 Two control points

```
from latextool_basic import *
p = Plot()
L = 0.03
C = 'blue!50'

p += Circle(x=2, y=2, r=0.2, background=C, name='a', linewidth=L)
p += Circle(x=1, y=1.5, r=0.05, background='black')
p += Circle(x=1.5, y=1, r=0.05, background='black')

p += Line(names=['a','a'], controls=[(1,1.5),(1.5,1)], linewidth=L)
p += Grid(0, 0, 3, 3)
print(p)
```



26.11 One control point

```

from latextool_basic import *
p = Plot()
C = 'blue!50'


p += Circle(x=2, y=2, r=0.2, background=C, name='22', linewidth=L)
p += Circle(x=0, y=0, r=0.2, background=C, name='00', linewidth=L)

p += Circle(x=0, y=2, r=0.05, background='black')

p += Line(names=['22','00'], controls=[(0,2)], linewidth=0.03)
p += Grid(x0=-1,y0=-1,x1=3,y1=3)

print(p)

```



1 control point and label

```

from latextool_basic import *
p = Plot()
L = 0.03
C = 'blue!50'


p += Circle(x=2, y=2, r=0.2, background=C, name='22', linewidth=L)
p += Circle(x=0, y=0, r=0.2, background=C, name='00', linewidth=L)

p += Circle(x=0, y=2, r=0.05, background='black')

p += Line(names=['22','00'], controls=[(0,2)], linewidth=L, label='test', a
nchor='below')

p += Grid(x0=-1,y0=-1,x1=3,y1=3)
print(p)

```



26.12 loop

Example uses Graph.

xxx


```

from latextool_basic import *
p = Plot()
L = 0.03
C = 'blue!50'

p += Graph.node(x=0, y=0, name='a')
p += Line(names=['a','a'], label='test', anchor='below', loop='loop above')

p += Grid(x0=-1,y0=-1,x1=3,y1=3)
print(p)


```



26.13 bend


Basically used for drawing swaps in array sorting.

```
from latextool_basic import Plot, Grid, bend
p = Plot()
p += bend([0,0], [1, 0], dy=1, linecolor='red')
p += bend([2,0], [5, 0], dy=1, linecolor='green')
p += bend([6,1], [8, 1], dy=-1, linecolor='blue')
p += Grid(x0=0, y0=0, x1=8, y1=2)
print(p)
```



You can specify linewidth, linecolor, linestyle:

```
from latextool_basic import Plot, Grid, bend
p = Plot()
p += bend([0,0], [1, 0], dy=1, linewidth=0.1)
p += bend([2,0], [5, 0], dy=1, linewidth=0.1, linecolor='red')
p += bend([6,1], [8, 1], dy=-1, linewidth=0.1, linecolor='red',
          linestyle='dashed')
p += Grid(x0=0, y0=0, x1=8, y1=2)
print(p)
```




The y values can be different:

```

from latextool_basic import Plot, Grid, bend
p = Plot()
p += bend([0,0], [1, -1], dy=1)
p += bend([2,-1], [3, 0], dy=1)
p += bend([4,0], [5, -1], dy=-1)
p += bend([6,-1], [7, 0], dy=-1)
p += Grid(x0=0, y0=-2, x1=7, y1=2)
print(p)

```




default radius (dy too large):

```


from latextool_basic import Plot, Grid, bend
p = Plot()
s0 = bend([0,0], [0.25,0], dy=1)
s1 = bend([3,1], [3.25,1], dy=-1)
p.add(s0)
p.add(s1)
p += Grid(x0=0, y0=0, x1=7, y1=2)
print(p)

```




default radius (dx too large):

```
from latextool_basic import Plot, Grid, bend
p = Plot()
s0 = bend([0,0], [4,0], dy=0.5)
s1 = bend([5,0.5], [9,0.5], dy=-0.5)
p.add(s0)
p.add(s1)
p += Grid(x0=0, y0=0, x1=10, y1=2)
print(p)
```



26.14 Orthogonal lines; organization chart

```
from latextool_basic import *
p = Plot()
points = get_points(0, 0, 3, 2, 'vbroom')
p += Line(points = points)
print(p)
```



With adjustment:

```
from latextool_basic import *
p = Plot()


x = 0
points = get_points(x, 0, x+3, 2, 'vbroom', delta=0.5)
p += Line(points = points)

x = 5
points = get_points(x, 0, x+3, 2, 'vbroom', delta=-0.5)
p += Line(points = points)

print(p)
```




```
from latextool_basic import *
p = Plot()
points = get_points(0, 0, 3, 2, 'hbroom')
p += Pointer(points = points)
print(p)
```



With adjustment:

```
from latextool_basic import *
p = Plot()

x = 0
points = get_points(x, 0, x+3, 2, 'hbroom', delta=-0.5)
p += Pointer(points = points)

x = 5
points = get_points(x, 0, x+3, 2, 'hbroom', delta=+0.5)
p += Pointer(points = points)

print(p)
```



```

from latextool_basic import *
p = Plot()
d = positions(r'''
    A


B   C   D

    E   F   G
''')
label = {'A':'CC TT Club',      'B':'RPPC',      'C':'Columbia',
         'D':'CC TT Academy', 'E':'Elementary', 'F':'Middle', 'G':'High'}
WIDTH = 2.6; HEIGHT = 0.5
rect = {}
for lab, pos in d.items():
    x, y = pos
    rect[lab] = Rect(x0=x-WIDTH/2, y0=y-HEIGHT/2,
                    x1=x+WIDTH/2, y1=y+HEIGHT, label=r'\scriptsize{%s}' % la
bel[lab],
                    linewidth=0.05)
    p += rect[lab]

for lab0, lab1s in [(('A', ('B','C','D')),
                    ('D', ('E','F','G'))),
                    ]:
    x0,y0 = rect[lab0].bottom()
    for lab1 in lab1s:
        x1,y1 = rect[lab1].top()
        points = get_points(x0,y0,x1,y1,'vbroom')
        p += Line(points=points, linewidth=0.05)

print(p)

```




27 Rect class

27.1 No background

TEST: Background is '', i.e., totally transparent.


```
from latextool_basic import *
p = Plot()
p += Rect(x0=0.5, y0=0.5, x1=1.5, y1=1.5)
p += Rect(x0=0.75, y0=0.75, x1=1.75, y1=1.75)
p += Grid()
print(p)
```



27.2 Background

TEST: Background is white

```
from latextool_basic import *
p = Plot()
p += Rect(x0=0.5, y0=0.5, x1=1.5, y1=1.5, background='white')
p += Rect(x0=0.75, y0=0.75, x1=1.75, y1=1.75, background='white')
p += Grid()
print(p)
```




27.3 border, background, foreground

```

from latextool_basic import *
p = Plot()
p += Rect(x0=1, y0=1, x1=5, y1=3,
          radius=0.25, innersep=0.25,
          linecolor='red!30!white', linewidth=0.1,
          background='blue!20!white!', foreground='blue!90!white',
          s='hello world! hello world!', align='t')
p += Rect(x0=6, y0=1, x1=10, y1=3,
          radius=0.25, innersep=0.25,
          linecolor='red!20!white', linewidth=0.1,
          background='blue!20!white!', foreground='blue!90!white',
          s='hello world! hello world!', align='c')
p += Rect(x0=11, y0=1, x1=15, y1=3,
          radius=0.25, innersep=0.25,
          linecolor='red!20!white', linewidth=0.1,
          background='blue!20!white!', foreground='blue!90!white',
          s='hello world! hello world!', align='b')
p += Grid()
print(p)

```



27.4 border, background, foreground


```

from latextool_basic import *
p = Plot(radius=0.25, innersep=0.25,
          linecolor='red!50!white', linewidth=0.1,
          background='blue!20!white', foreground='blue!90!white',
          align='t')
p += RectAdaptor(env=p.env, x0= 1, y0=1, x1= 4, y1=3, s='hello world!')
p.env['linewidth'] = 0
p += RectAdaptor(env=p.env, x0= 5, y0=1, x1= 8, y1=3, s='hello world!')
p.env['background'] = ''
p += RectAdaptor(env=p.env, x0= 9, y0=1, x1= 12, y1=3, s='hello world!')

p.env['background'] = ''
p.env['linecolor'] = 'red'
p.env['linewidth'] = 0.2
p += RectAdaptor(env=p.env, x0= 13, y0=1, x1= 16, y1=3, s='hello world!')


p += Grid()
print(p)

```




27.5 align

```
from latextool_basic import *
p = Plot()
p += Rect(x0=0.25, y0=0.25, x1=1.75, y1=1.75, s='abc', align='t',
          linecolor='red', foreground='black')
p += Rect(x0=3.25, y0=0.25, x1=4.75, y1=1.75, s='abc', align='c',
          linecolor='red')
p += Rect(x0=6.25, y0=0.25, x1=7.75, y1=1.75, s='abc', align='b',
          linecolor='red')
p += Grid()
print(p)
```



27.6 innersep


```
from latextool_basic import *
p = Plot()
p += Rect(x0=0.5, y0=0.5, x1=1.5, y1=1.5)
p += Rect(x0=3, y0=0, x1=6, y1=2, linecolor='red', linewidth=0.1, s='hello'
)
p += Rect(x0=7, y0=0, x1=10, y1=2, linecolor='red', background='blue',
          linewidth=0.2, s='hello')
p += Rect(x0=11, y0=0, x1=14, y1=2, linecolor='red', linewidth=0.2,
          background='green',
          innersep=0.5, s='hello')
p += Grid()
print(p)
```



27.7 rounded corners


(radius of corner is set to innersep by default):

```
from latextool_basic import *
p = Plot()
p += Rect(x0=3, y0=4, x1=6, y1=6, linecolor='red', linewidth=0.1,
          innersep=0.5, radius=0.5,
          s=r'\tiny this is a test ... this is a test ...}')
p += Rect(x0=0.5, y0=0.5, x1=5, y1=3,
          background='blue!10!white',
          innersep=0.2, radius=0.2,
          s=r'\tiny this is a test ... this is a test ...}')
p += Rect(x0=6.5, y0=0.5, x1=10, y1=3,
          background='green!10!white',
          innersep=0.01, radius=0.01,
          s=r'\tiny this is a test ... this is a test ...}')
p += Grid()
print(p)
```




27.8 linestyle

```
from latextool_basic import *
p = Plot()
p += Rect(x0=1, y0=1, x1=3, y1=3,
          linewidth=0.1, linecolor='red',
          radius=0.5, linestyle='dashed')
p += Grid()
print(p)
```



27.9 label

```
from latextool_basic import *
p = Plot()
p += Rect(x0=1, y0=1, x1=5, y1=4,
          linewidth=0.1, linecolor='red',
          radius=0.5, linestyle='dashed', label='hello')
p += Rect(x0=6, y0=0, x1=12, y1=4,
          linewidth=0.1, linecolor='red',
          foreground='blue',
          radius=0.5, linestyle='dashed', label='hello')
p += Grid()
print(p)
```




27.10 tikz name

Rect with tikz name:

```
from latextool_basic import *
p = Plot()
p += Rect(x0=1, y0=0, x1=2, y1=1, label='a', name='a')
p += Rect(x0=5, y0=1, x1=6, y1=2, label='b', name='b')

p += r"\draw[->,line width=2] (a) -- (b);"

print(p)
```




28 RectContainer

Horizontal array:

```
from latextool_basic import *
p = Plot()

c = RectContainer(x=1, y=1)
for x in '1234578':
    c += Rect2(x0=0, y0=0, x1=1, y1=1,
               linewidth=0.2, linecolor='red!30!white',
               label=r'\textttt{%s}' % x)

p += c
p += Grid()
print(p)
```




28.1 Using []

```

from latextool_basic import *
p = Plot()

c = RectContainer(x=1, y=1)
for x in 'abcdefgh':
    c += Rect2(x0=0, y0=0, x1=1, y1=1,
               linewidth=0.2, linecolor='red!30!white',
               label=x)
p += c
p += bend(c[2].top(), c[5].top())
p += Grid()
print(p)

```



tmp/68973ebe2b61653d167302cb3541f346.pdf

29 name

```

from latextool_basic import *
p = Plot()

c = RectContainer(x=1, y=1, name='A')
for x in '12':
    c += Rect2(x0=0, y0=0, x1=1, y1=1,
               linewidth=0.2, linecolor='red!30!white',
               label=r'\textttt{%s}' % x)


p += c

d = RectContainer(x=3, y=4, name='B')
for x in '34':
    d += Rect2(x0=0, y0=0, x1=1, y1=1,
               linewidth=0.2, linecolor='blue!30!white',
               label=r'\textttt{%s}' % x)

p += d

p += Line(names=['A', 'B'], endstyle='>')
print(p)

```




Left-to-right, align bottom:

```
from latextool_basic import *
p = Plot()

c = RectContainer(x=1, y=1)
for i, x in enumerate([1,2,3,4,5,6]):
    c += Rect2(x0=0, y0=0, x1=1+i/4.0, y1=1+i/4.0, linecolor='red', linewidth=0.2,
               label=r'\texttt{%s}' % x)
c.layout()
p += c

# boundary of container
p += Rect2(x0=c.x0, y0=c.y0, x1=c.x1, y1=c.y1, linewidth=0.1, linecolor='green')

p += Grid()
print(p)
```



tmp/9fd9b7ae23523bc3e06b3bbc7b45a579.pdf


Align top, left-to-right:

```
from latextool_basic import *
p = Plot()

c = RectContainer(x=1, y=1, align='top')
for i, x in enumerate([1,2,3,4,5,6]):
    c += Rect2(x0=0, y0=0, x1=1+i/4.0, y1=1+i/4.0, linecolor='red', linewidth
th=0.2,
                label=r'\texttt{%s}' % x)
p += c

# boundary of container
p += Rect2(x0=c.x0, y0=c.y0, x1=c.x1, y1=c.y1, linewidth=0.1, linecolor='green')

p += Grid()
print(p)
```



tmp/eb7c36a72aa7aeb861f538cf2fb3873a.pdf


top-to-bottom, align left:

```
from latextool_basic import *
p = Plot()

c = RectContainer(x=1, y=1, align='left', direction='top-to-bottom')
for i, x in enumerate([1,2,3,4,5,6]):
    c += Rect2(x0=0, y0=0, x1=1+i/4.0, y1=1+i/4.0, linecolor='red', linewidth
th=0.2,
                label=r'\texttt{%s}' % x)
p += c

# boundary of container
p += Rect2(x0=c.x0, y0=c.y0, x1=c.x1, y1=c.y1, linewidth=0.1, linecolor='green')

p += Grid()
print(p)
```



tmp/2d34561aacc7e24c12eb38c0e1a86e63.pdf


top-to-bottom, align right:

```
from latextool_basic import *
p = Plot()

c = RectContainer(x=1, y=1, align='right', direction='top-to-bottom')
for i, x in enumerate([1,2,3,4,5,6]):
    c += Rect2(x0=0, y0=0, x1=1+i/4.0, y1=1+i/4.0, linecolor='red', linewidth
th=0.2,
                label=r'\texttt{%s}' % x)
p += c

# boundary of container
p += Rect2(x0=c.x0, y0=c.y0, x1=c.x1, y1=c.y1, linewidth=0.1, linecolor='green')

p += Grid()
print(p)
```



tmp/13dfef2a97de09e644bcad0509714efa.pdf

2-d stack

```

from latextool_basic import *
p = Plot()


c0 = RectContainer(x=1, y=1, align='bottom', direction='left-to-right')
for i, x in enumerate([1,2,3,4,5,6]):
    c0 += Rect2(x0=0, y0=0, x1=1+i/4.0, y1=1+i/4.0, linecolor='red', linewidth=0.1,
                label=r'\texttt{%s}' % x)

c1 = RectContainer(x=1, y=1, align='bottom', direction='left-to-right')
for i, x in enumerate([7,8,9,10]):
    c1 += Rect2(x0=0, y0=0, x1=1+i/4.0, y1=1+i/4.0, linecolor='red', linewidth=0.1,
                label=r'\texttt{%s}' % x)

C = RectContainer(x=1, y=1, align='left', direction='top-to-bottom')
C += c0; c0.x = c0.x0; c0.y = c0.y0; c0.layout()
C += c1; c1.x = c1.x0; c1.y = c1.y0; c1.layout()

p += C;
p += Grid()
print(p)

```



tmp/7a07ae3f99f9db0a91132bf36a69be62.pdf


```

from latextool_basic import *
p = Plot()

c = RectContainer(x=1, y=1)
for i, x in enumerate([1,2,3,4,5,6]):
    if i % 2 == 0:
        c += Rect2(x0=0, y0=0, x1=1, y1=1, linecolor='red', linewidth=0.1,
                    label=r'\texttt{%s}' % x)
    else:
        c += Circle(x=0.5, y=0.5, r=0.5 + i/2, label=x, linecolor='red', li
newwidth=0.1)

p += c
p += Grid()
print(p)

```



tmp/70352fdaf4f31a18b51eb36cf58500fa.pdf

Vertical array and pointers

```

L = 0.1 # line width
from latextool_basic import *
p = Plot()

v = RectContainer(x=0, y=0, align='left', direction='top-to-bottom')
for i in ['', '', '', '']:
    v += Rect2(0,0,1,1,s=i, linewidth=0.1, linecolor='red')

p += v


h = RectContainer(x=5, y=0, align='bottom', direction='left-to-right')
for i in ['', '', '', '']:
    h += Rect2(0,0,1,1,s=i, linewidth=0.1, linecolor='green')

p += h

p += Line(x0=v[0].centerx(), y0=v[0].centery(),
          x1=h[0].leftx(), y1=h[0].centery(),
          linewidth=0.1, linecolor='blue',
          endstyle='->', startstyle='dot', r=0.01)

p += Grid()
print(p)

```



DFA/NFA:

```

from latextool_basic import *
p = Plot()

h = RectContainer(x=0, y=0, align='bottom', direction='left-to-right')
for i in ['a','b','a','a','$\sqcup$', '$\sqcup$', '$\sqcup$',]:
    h += Rect2(0,0,1,1,
               label= r'\texttt{%s}' % i,
               linewidth=0.1, linecolor='red')
p += h

p += Line(x0=h[-1].x1, y0=h[-1].y1, x1=h[-1].x1+0.5, y1=h[-1].y1,
          linewidth=0.1, linecolor='red')


p += Line(x0=h[-1].x1, y0=h[-1].y0, x1=h[-1].x1+0.5, y1=h[-1].y0,
          linewidth=0.1, linecolor='red')

dfa = Rect2(0,-4,3,-2, linewidth=0.1, linecolor='blue', label='$q_0$')
p += dfa

p += Line(x0=dfa.centerx(), y0=dfa.y1,
          x1=h[0].centerx(), y1=h[0].bottomy(),
          linewidth=0.1, linecolor='blue', endstyle='->')

p += Grid()
print(p)

```



PDA:

```

from latextool_basic import *
p = Plot()
h = RectContainer(x=0, y=0, align='bottom', direction='left-to-right')
for i in ['a', 'b', 'a', 'a', '$\sqcup$', '$\sqcup$', '$\sqcup$', ]:
    h += Rect2(0,0,1,1,
               label= r'\texttt{%s}' % i,
               linewidth=0.1, linecolor='red')
p += h

p += Line(x0=h[-1].x1, y0=h[-1].y1, x1=h[-1].x1+0.5, y1=h[-1].y1,
          linewidth=0.1, linecolor='red')
p += Line(x0=h[-1].x1, y0=h[-1].y0, x1=h[-1].x1+0.5, y1=h[-1].y0,
          linewidth=0.1, linecolor='red')

pda = Rect2(0,-4,3,-2, linewidth=0.1, linecolor='blue', label='$q_0$')
p += pda


p += Line(x0=pda.centerx(), y0=pda.y1,
          x1=h[0].centerx(), y1=h[0].bottomy(),
          linewidth=0.1, linecolor='blue', endstyle='->')

v = RectContainer(x=4, y=-4, align='left', direction='top-to-bottom')
for i in ['a', '$', ]:
    v += Rect2(0,0,1,1,
               label= r'\texttt{%s}' % i, linewidth=0.1, linecolor='red')
p += v

p += Line(x0=pda.x1,y0=pda.centery(), x1=v[0].centerx(), y1=pda.centery(),
          linewidth=0.1, linecolor='blue')
p += Line(x0=v[0].centerx(),y0=pda.centery(),x1=v[0].centerx(),y1=v[0].topy
          (),
          linewidth=0.1, linecolor='blue')

p += Grid()
print(p)

```




30 positions

The `positions` function computes positions.

```
from latextool_basic import positions
d = positions(r'''
  A
B C D
  E F
G
''')

from latextool_basic import Plot, Circle
p = Plot()
for label, pos in d.items():
    x, y = pos
    p += Circle(x=x, y=y, r=0.4, label=label)
print(p)
```



tmp/07c19dd4cef2ae30b3195b0606a336b3.pdf

You can scale the x and y axes:

```
from latextool_basic import positions
d = positions(r'''
  A
B C D
  E F
G
''', xscale=2.0, yscale=0.5)

from latextool_basic import Plot, circle
p = Plot()
for label, pos in d.items():
    x, y = pos
    p.add(circle, x=x, y=y, r=0.25, label=label)
print(p)
```



tmp/b7c17c07a4629b0fe6760a1021dfe9a4.pdf

31 vphantom

no vphantom:

b	g
---	---

```
from latextool_basic import *
p = Plot()
p += Rect(x0=0, y0=0, x1=1, y1=1,
          label=r'\textsf{%s}' % "b")
p += Rect(x0=1, y0=0, x1=2, y1=1,
          label=r'\textsf{%s}' % "g")
print(p)
```




with vphantom:

b	g
---	---

```
from latextool_basic import *
p = Plot()
p += Rect(x0=0, y0=0, x1=1, y1=1,
          label=r'\vphantom{bg}\textsf{%s}' % "b")
p += Rect(x0=1, y0=0, x1=2, y1=1,
          label=r'\vphantom{bg}\textsf{%s}' % "g")
print(p)
```

32 Trees

32.1 tree





Auto adjust node position

32.2 Parse tree example

```

<expr> => <factor>
=> <bin> * <expr>
=> 1 * <expr>
=> 1 * <factor> + <factor>
=> 1 * <bin> + <factor>
=> 1 * 1 + <factor>
=> 1 * 1 + <bin>
=> 1 * 1 + 0

```



32.3 Binary tree

```

from latextool_basic import *

p = Plot()
edges={'A':['B','C'],
      'B':['E','F'],
      'E':['G','H'],
      'F':['I'],
      'C':['K','L'],
      'K':['M','N'],
      'L':['','P']}


pos = bintreepositions(edges=edges)

Graph.r = 0.3
for k,(x,y) in pos.items():
    p += Graph.node(x=x, y=y, name=k, label=k)

for k,v in edges.items():
    for x in v:
        if x in [None,'']: continue
        p += Graph.arc(names=[k,x])

print(p)

```



Changing separation between nodes:

```
from latextool_basic import *


p = Plot()
edges={'A':['B','C'],
      'B':['E','F'],
      'E':['G','H'],
      'F':['I'],
      'C':['K','L'],
      'K':['M','N'],
      'L':['','P']}

pos = bintreepositions(edges=edges, node_hsep=1, node_vsep=1)

Graph.r = 0.3
for k,(x,y) in pos.items():
    p += Graph.node(x=x, y=y, name=k, label=k)

for k,v in edges.items():
    for x in v:
        if x in [None,'']: continue
        p += Graph.arc(names=[k,x])

print(p)
```



Changing separation between nodes:

```
from latextool_basic import *


p = Plot()
edges={'A':['B','C'],
      'B':['E','F'],
      'E':['G','H'],
      'F':['I'],
      'C':['K','L'],
      'K':['M','N'],
      'L':['','P']}

pos = bintreepositions(edges=edges, node_hsep=0.5, node_vsep=1)

Graph.r = 0.3
for k,(x,y) in pos.items():
    p += Graph.node(x=x, y=y, name=k, label=k)

for k,v in edges.items():
    for x in v:
        if x in [None,'']: continue
        p += Graph.arc(names=[k,x])

print(p)
```




32.4 bintree function

```
from latextool_basic import *

p = Plot()
edges={'A':['B','C'],
      'B':['E','F'],
      'E':['G','H'],
      'F':['I'],
      'C':['K','L'],
      'K':['M','N'],
      'L':['','P']}

bintree(p, edges=edges)

print(p)
```




bintree function with edge function

```
from latextool_basic import *

p = Plot()
edges={'A':['B','C'],
      'B':['E','F'],
      'E':['G','H'],
      'F':['I'],
      'C':['K','L'],
      'K':['M','N'],
      'L':['','P']}

def edge(names):
    if names=='A','B':
        return Graph.arc(names=names, linecolor='red')
    else:
        return Graph.arc(names=names)
bintree(p, edges=edges, edge=edge)

print(p)
```




32.5 BinTree class

```
from latextool_basic import *

p = Plot()
edges={'A':['B','C'],
      'B':['E','F'],
      'E':['G','H'],
      'F':['I'],
      'C':['K','L'],
      'K':['M','N'],
      'L':['','P']}

BinTree.run(p, edges=edges)

print(p)
```




Using the BinTree class with label function

```
from latextool_basic import *

p = Plot()
edges={'A':['B','C'],
      'B':['E','F'],
      'E':['G','H'],
      'F':['I'],
      'C':['K','L'],
      'K':['M','N'],
      'L':['','P']}
def label(x): return r'\footnotesize \texttt{%s}}' % x
BinTree.run(p, edges=edges, label=label)

print(p)
```




33 Graphs

34 Graphs


34.1 The graph function

```
\begin{python}  
from latextool_basic import graph  
print(graph(layout="""  
A  
B C  
"""))  
\end{python}
```




34.2 The graph function:nodes and labels

```
\begin{python}
from latextool_basic import graph
print(graph(layout=''
    X1 C1
    X2 C2
    X3 C3
    X4 C4
    '' ,
    minimum_size='8mm',
    edges='X1-C1,X2-C2,X1-C3,X2-C3,X1-C4,X2-C4,X3dashedC4',
    X1='label=$X_1$',
    X2='label=$X_2$',
    X3='label=$X_3$',
    X4='label=$X_4$',
    C1='shape=rectangle, label=$C_1$',
    C2='shape=rectangle, label=$C_2$',
    C3='shape=rectangle, label=$C_3$',
    C4='shape=rectangle, label=$C_4$',
    ))
\end{python}
```



34.3 The graph function: isoceles triangle as subtree




34.4 The graph function: edge labels

```

from latextool_basic import graph
print(graph(layout='''
    A
  B   C   D
    E   F
    G   H
    I
''',
minimum_size='8mm',
edges='A-B,A-C,A-D,C-E,C-F,F-G,F-H,G-I',
A=r'label=$\alpha$',
B=r'label=$\beta$',
edge_label={('A','B'):{'label':'X'},
            ('A','C'):{'label':'Y', 'style':'pos=0.25,fill=white'},
            ('A','D'):{'label':'a very very long label'},
            ('C','E'):{'label':'5', 'style':'pos=0.5,above'},
            ('C','F'):{'label':'5', 'style':'pos=0.5,below'},
            ('F','G'):{'label':'5', 'style':'pos=0.5,above,inner sep=1mm,circle'},
            ('F','H'):{'label':'5', 'style':'pos=0.5,below,inner sep=1mm,circle'},
            ('G','I'):{'label':'abcdef', 'style':'sloped'},
            },
))

```



<http://tex.stackexchange.com/questions/86386/edge-nodes-auto-and-node-distance>

34.5 Graph class

```

from latextool_basic import *
p = Plot()
for i in [1,2,3]:
    p += Graph.node(p, x=i, y=1, name='a%s' % i)
    p += Graph.node(p, x=i, y=-1, name='c%s' % i)


for i in range(5):
    p += Graph.node(p, x=i, y=0, name='b%s' % i)

p += Graph.edge(names=['b%s' % i for i in range(5)])
for i in [1,2,3]:
    p += Graph.edge(names=['a%s' % i, 'b%s' % i])
    p += Graph.edge(names=['c%s' % i, 'b%s' % i])

p += Graph.arc(names=['c3', 'b4'])

print(p)

```




34.6 Edge label anchor

```
from latextool_basic import *
p = Plot()
p += Graph.node(x=0, y=0, label='a', name='0')
p += Graph.node(x=5, y=0, label='b', name='1')
p += Graph.edge(names=['0', '1'], label='d', anchor='above')

print(p)
```

```
from latextool_basic import *
p = Plot()
p += Graph.node(x=0, y=0, label='a', name='0')
p += Graph.node(x=5, y=0, label='b', name='1')
p += Graph.edge(names=['0', '1'], label='d', anchor='above')

print(p)
```




34.7 Cycle graphs

Odd Cycle.


The node name is of the form `[radius]_[i]` where `i` is the index of node going in an anticlockwise direction, starting at degree `startdegree`.

By default, the first node is at `startdegree=90` degrees.

```
from latextool_basic import *
p = Plot()
cyclegraph(p, num=3, radius=1)
print(p)
```



```
from latextool_basic import *
p = Plot()
cyclegraph(p, num=7, radius=2, drawline=False)
print(p)
```




34.8 Name of nodes

Name of the nodes:


The nodes are names '0', '1', etc. in the anticlockwise direction where '0' is the node with angle `startdegree`. You can specify the `startdegree` in the `cyclegraph`. By default, when the number of nodes is even, the `startdegree` is 0 and when the number of nodes is odd, the `startdegree` is 90.

```
from latextool_basic import *
p = Plot()
cyclegraph(p, num=7, radius=1, drawline=True)
p += Circle(x=5, y=2, r=0.25, background='red', name='A')
p += Circle(x=0, y=-2, r=0.25, background='blue', name='B')
p += Line(names=['A', '0'])
p += Line(names=['B', '3'])
print(p)
```




You can change the pgf/tikz name of the nodes by setting `names` dictionary in the `cyclegraph`. For instance if you want the first node to be named 'a' instead of 0, then `0:'a'` should be a key-value pair in `names`.

```
from latextool_basic import *
p = Plot()
cyclegraph(p, num=7, radius=1, drawline=True,
            names={0:'a',
                  3:'d',
                  })
p += Circle(x=5, y=2, r=0.25, background='red', name='A')
p += Circle(x=0, y=-2, r=0.25, background='blue', name='B')
p += Line(names=['A', 'a'])
p += Line(names=['B', 'd'])
print(p)
```





Even Cycle. By default, the starting degree is 0.


```
from latextool_basic import *  
p = Plot()  
cyclegraph(p, num=4, radius=1)  
print(p)
```



```
from latextool_basic import *  
p = Plot()  
cyclegraph(p, num=4, radius=1, startdegree=45)  
print(p)
```




```
from latextool_basic import *  
p = Plot()  
cyclegraph(p, num=6, radius=2)  
print(p)
```



34.9 Petersen graph


```
from latextool_basic import *  
p = Plot()  
petersen(p)  
print(p)
```



34.10 Complete graphs


K_4 :

```
from latextool_basic import *  
p = Plot()  
completegraph(p, num=4)  
print(p)
```




K_4 :

```
from latextool_basic import *  
p = Plot()  
completegraph(p, num=4, startdegree=45)  
print(p)
```




K_5 :

```
from latextool_basic import *  
p = Plot()  
completegraph(p, num=5)  
print(p)
```



K_6 :

```
from latextool_basic import *  
p = Plot()  
completegraph(p, num=6, radius=1.5)  
print(p)
```



34.11 Star graphs

The name of the center node is 'center'.

```
from latextool_basic import *
p = Plot()
stargraph(p, num=5)
print(p)
```


```
from latextool_basic import *
p = Plot()
stargraph(p, num=4)
print(p)
```

When there are two stars, you need to give the centers different names:

```
from latextool_basic import *
p = Plot()
stargraph(p, x=0, y=0, num=4, radius=1, names={'center':'c0'})
stargraph(p, x=2, y=0, num=4, radius=1, names={'center':'c1'})
print(p)
```

34.12 Bipartite graphs


$K_{3,3}$:



```
from latextool_basic import *
p = Plot()
completebipartite(p=p, num1=3, num2=3)
print(p)
```


$K_{3,3}$ without edges:

```
from latextool_basic import *
p = Plot()
completebipartite(p=p, num1=3, num2=3, drawline=False)
print(p)
```




$K_{3,4}$:

```
from latextool_basic import *
p = Plot()
completebipartite(p=p, num1=3, num2=4, horsep=2)
print(p)
```




$K_{3,4}$:

```
from latextool_basic import *
p = Plot()
completebipartite(p=p, num1=3, num2=4, versep=2)
print(p)
```



35 Frame

```
from latextool_basic import *
p = Plot()
env = [('x', 1), ('y', 2), ('z', 3.14), ('w', 'a')]
p.add(frame(env, top="main()"))
print(p)
```



tmp/676f2b6ad3cb833fe368eb4fd38f509d.pdf

36 Test Verbatim Spacing

First here's the vertical spacing between paragraphs. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

TEST 1. Text, console environment, text:

```
hello world
```

Line after.

TEST 2. Text, console environment, console environment, text:

```
hello world
```

```
hello world
```

Line after. Probably won't be used. Probably too much spacing between the two environments.


TEST 3. Text, python environment with console function, text:

```
hello world
```

Line after.


37 2D vector diagram

```
from latextool_basic import *  
p, q = (-1,-1), (-4,-3)  
print(plot(vector=[p,q]))  
v = vec(p, q)  
print(answer(answer=''))
```




ANSWER:

```
from latextool_basic import *  
plot = Plot()  
p, q = (-1,-1), (-4,-3); vector = [p, q]; vectors = [vector]  
vec2dplot(plot, vectors=[vector])  
print(plot)
```




Without axes:

```
from latextool_basic import *
plot = Plot()
p, q = (-1,-1), (-4,-3); vector = [p, q]; vectors = [vector]
vec2dplot(plot, vectors=[vector], draw_axes=False)
print(plot)
```




Without axes and vector with non integer endpoints:

```
from latextool_basic import *  
plot = Plot()  
p, q = (-1.5, 4.2), (-4.1, -3.8); vector = [p, q]; vectors = [vector]  
vec2dplot(plot, vectors=[vector], draw_axes=False)  
print(plot)
```




With axes and vector with non integer endpoints:

```
from latextool_basic import *  
plot = Plot()  
p, q = (-1.5, 4.2), (-4.1, -3.8); vector = [p, q]; vectors = [vector]  
vec2dplot(plot, vectors=[vector])  
print(plot)
```



With axes and multiple vectors with non integer endpoints:

```
from latextool_basic import *
plot = Plot()
p, q = (-1.5, 4.2), (-4.1, -3.8); v0 = [p, q];
p, q = (2.5, 3.2), (-1, 2.5); v1 = [p, q];
p, q = (0.5, 2.5), (-1, 2.5); v2 = [p, q];
vectors = [v0, v1, v2]
vec2dplot(plot, vectors=vectors)
print(plot)
```




38 Line Graph

```

from math import sin
from latextool_basic import *
plot = FunctionPlot()


data = ((1, 1), (2, 2), (2.5, 0), (3, 0.5))
data2 = ((0, 0), (1, 1), (2.5, 5), (3, 7))
data3 = [(x/10.0, (x/10.0)**2) for x in range(0, 100)]
data4 = [(x/10.0, 100 * sin(x/10.0)) for x in range(0, 200)]
plot.add(data, line_width='3', color='red')
plot.add(data2, line_width='3', color='blue')
plot.add(data3, line_width='3', color='green')
plot.add(data4, line_width='3', color='black')
print(plot)

```




Line width and color:

```
from latextool_basic import *  
plot = FunctionPlot()  
plot.add(((1, 1), (2, 2), (3, 0.5))), line_width='2', color='red')  
print(plot)
```




Width and height:

```
from latextool_basic import *  
plot = FunctionPlot(width="3in", height="2in")  
plot.add(((1, 1), (2, 2), (3, 0.5))), line_width='2', color='blue')  
print(plot)
```




Multiple lines:

```
from latextool_basic import *
plot = FunctionPlot(width="3in", height="2in")
plot.add(((1, 1), (2, 2), (3, 0.5)), line_width='2', color='red')
plot.add(((1, 5), (2, 3), (3, 7)), line_width='2', color='green')
plot.add(((1, 5), (2, -3), (3, -5)), line_width='2', color='blue')
print(plot)
```



Legend:


```
from latextool_basic import *
plot = FunctionPlot(width="3in", height="2in")
plot.add(((1, 1), (2, 2), (3, 0.5)), line_width='2', color='red', legend='Graph 1')
plot.add(((1, 5), (2, 3), (3, 7)), line_width='2', color='green', legend='Graph 2')
plot.add(((1, 5), (2, -3), (3, -5)), line_width='2', color='blue', legend='Graph 3')
print(plot)
```





Legend:


```
from math import sin
domain = [x / 10.0 for x in range(-100, 101)]
y_sinx = [(x, 5 * sin(x)) for x in domain]
y_x = [(x, x) for x in domain]

from latextool_basic import *
plot = FunctionPlot(width="6in", height="3in")
plot.add(y_sinx, line_width='2', color='red', legend=r'$y = 5 \sin(x)$')
plot.add(y_x, line_width='2', color='green', legend='$y = x$')
print(plot)
```




39 Bar chart, line chart





40 TEST ISOCELES TRIANGLE




<http://tex.stackexchange.com/questions/7862/triangle-node-with-adjustable-height>

<http://tex.stackexchange.com/questions/37462/placing-a-triangle-around-nodes-in-a-tree>


41 ER diagrams

41.1 Attribute


```
from latextool_basic import *; p = Plot()
p += ER.attrib(center=(0,0), name='sid', label=r'\texttt{sid}')
print(p)
```



```
from latextool_basic import *; p = Plot()
p += ER.attrib(center=(0,0), name='sid', label=r'\texttt{sid}',
               double=True)
print(p)
```




```
from latextool_basic import *; p = Plot()
p += ER.attrib(center=(0,0), name='sid', label=r'\texttt{sid}', linestyle='
dashed')
print(p)
```




41.2 Entity

```
from latextool_basic import *; p = Plot()
p += ER.entity(center=(6,0), name='Student')
print(p)
```




Entity with double lines:

```
from latextool_basic import *; p = Plot()
p += ER.entity(center=(6,0), name='Student', double=True)
print(p)
```



Entity with double lines:

```
from latextool_basic import *; p = Plot()
p += ER.entity(center=(6,0), name='Student', double=['Student'])
print(p)
```




Entity name is a tikz node name:

```
from latextool_basic import *; p = Plot()
p += ER.entity(center=(6,0), name='Student')
p += Rect(0,0,4,1,name='r',label='this is an entity')
p += ER.line(names=['r', 'Student'], endstyle='>')
print(p)
```



Entity name can be difference from label:


```
from latextool_basic import *; p = Plot()
p += ER.entity(center=(6,0), name='s', label='Student')
p += Rect(0,0,4,1,name='r',label='this is an entity')
p += Line(names=['r', 's'], endstyle='>')
print(p)
```



```
from latextool_basic import *
p = Plot()


p += ER.attrib(center=(4,2), name='sid', label=r'\texttt{\underline{sid}}')
p += ER.attrib(center=(8,2), name='name', label=r'\texttt{name}')
p += ER.entity(center=(6,0), name='Student', label=r'\texttt{Student}')

p += Line(names=['sid', 'Student'])
p += Line(names=['name', 'Student'])
print(p)
```




Entity with attributes (primary key and partial key):

```
from latextool_basic import *; p = Plot()
p += ER.entity(center=(0,0),
               name='Student',
               attribs=['sid', 'name', 'partial'], keys=['sid'], dasheds=['partial'])
print(p)
```




```
from latextool_basic import *; p = Plot()
p += ER.entity(center=(0,0),
               name='Student',
               attribs=['sid', 'name', 'gpa', 'age', 'gender'],
               keys=['sid'])
print(p)
```




Entity with attribs on north (even number):

```
from latextool_basic import *; p = Plot()
p += ER.entity(center=(0,0),
               name='Student',
               attribs=['sid', 'name'], keys=['sid'])
print(p)
```




```
from latextool_basic import *; p = Plot()
p += ER.entity(center=(0,0),
               name='Student',
               attribs=['sid', 'name', 'gpa', 'age'], keys=['sid'])
print(p)
```




Even number of attributes on south:

```
from latextool_basic import *
p = Plot()
p += ER.entity(center=(0,0),
               name='Student',
               attribs=['sid', 'name', 'gpa', 'age'],
               keys=['sid'],
               anchor={'sid':'south', 'name':'south', 'gpa':'south', 'age':'south'
})
p += Grid(-5,-3,5,1)
print(p)
```




Odd number of attributes on south:

```
from latextool_basic import *
p = Plot()
p += ER.entity(center=(0,0),
               name='Student',
               attribs=['sid', 'name', 'gpa', 'age', 'gender'],
               keys=['sid'],
               anchor={'sid':'south', 'name':'south', 'gpa':'south', 'age':'south'
, 'gender':'south'})
print(p)
```




```
from latextool_basic import *
p = Plot()
p += ER.entity(center=(0,0),
               name='Student',
               attribs=['sid', 'name', 'gpa', 'age', 'gender'],
               keys=['sid'],
               anchor={'name':'south', 'gender':'south'})
print(p)
```




Attributes on east:

```
from latextool_basic import *
p = Plot()
p += ER.entity(center=(0,0),
               name='Student',
               attribs=['sid', 'name', 'gpa', 'age', 'gender'],
               keys=['sid'],
               anchor={'sid':'east', 'name':'east', 'gpa':'east',
                      'age':'east',
                      'gender':'east'})
p += Grid(-1, -3, 5, 3)
print(p)
```




Attributes on west:

```
from latextool_basic import *
p = Plot()
p += ER.entity(center=(0,0),
               name='Student',
               attribs=['sid', 'name', 'gpa', 'age', 'gender'],
               keys=['sid'],
               anchor={'sid':'west', 'name':'west', 'gpa':'west',
                     'age':'west', 'gender':'west'})
p += Grid(-4, -3, 2, 3)
print(p)
```




All directions:

```
from latextool_basic import *
p = Plot()
p += ER.entity(center=(0,0),
               name='Student',
               attribs=['sid', 'name', 'gpa', 'age', 'gender', 'dob'],
               keys=['sid'],
               double=['name'],
               anchor={'name':'east', 'gpa':'west',
                      'age':'west', 'gender':'south'})
print(p)
```




All directions and double:

```
from latextool_basic import *
p = Plot()
p += ER.entity(center=(0,0),
               name='Student',
               attribs=['sid', 'name', 'gpa', 'age', 'gender', 'dob'],
               keys=['sid'],
               double=['name', 'gpa', 'Student'],
               anchor={'name':'east', 'gpa':'west',
                      'age':'west', 'gender':'south'})
print(p)
```




All directions and double and derived

```
from latextool_basic import *
p = Plot()
ER.attrib_dist = 1.5
p += ER.entity(center=(0,0),
               name='Student',
               attribs=['sid', 'name', 'gpa', 'age', 'gender', 'dob', 'a', 'b',
                       'c', 'd'],
               keys=['sid'],
               derived=['age', 'a', 'b', 'c'],
               double=['name', 'gpa', 'Student', 'd'],
               anchor={'name': 'east', 'gpa': 'west', 'b': 'east', 'c': 'south',
                       'age': 'west', 'gender': 'south'})
print(p)
```




41.3 Relation

```
from latextool_basic import *
p = Plot()
p += ER.relation(center=(0,0), name='Registers', label='')
p += Grid(-3, -2, 3, 2)
print(p)
```




```
from latextool_basic import *
p = Plot()
p += ER.relation(center=(0,0), name='Registers', label='Registers')
p += Grid(-3, -2, 3, 2)
print(p)
```



```

from latextool_basic import *
p = Plot()
p += ER.relation(center=(0,0), name='Registers', label='a very long string'
)
p += Grid(-3, -2, 3, 2)
print(p)

```



```

from latextool_basic import *
p = Plot()
p += ER.relation(center=(4,0), double=True,
                 name='Registers', label='Registers')
print(p)


```



```

from latextool_basic import *
p = Plot()
p += ER.relation(center=(0,0),
                 name='Registers',
                 attribs=['date','a','b','c','d'])
p += Grid(-6, -1, 6, 3)
print(p)


```



```


from latextool_basic import *
p = Plot()
p += ER.relation(center=(4,0),
                 name='Registers',
                 attribs=['date','a','b','c','d'],
                 anchor={'date':'south', 'c':'south'})
print(p)

```




41.4 Entity and relation with different arrows


```
from latextool_basic import *
p = Plot()
p += ER.entity(center=(0,0), name='A')
p += ER.relation(center=(4,0), name='B')
p += ER.line(names=['A', 'B'],
             linewidth=ER.boldlinewidth)
print(p)
```



```
from latextool_basic import *
p = Plot()
p += ER.entity(center=(0,0), name='A')
p += ER.relation(center=(4,0), name='B')
p += ER.line(names=['A', 'B'],
             linewidth=ER.boldlinewidth, endstyle='>')
print(p)
```




```
from latextool_basic import *
p = Plot()
p += ER.entity(center=(0,0), name='A')
p += ER.relation(center=(4,0), name='B')
p += ER.line(names=['A', 'B'],
             linewidth=ER.boldlinewidth, endstyle='>',
             arrowstyle='triangle')
print(p)
```



```

from latextool_basic import *
p = Plot()
p += ER.entity(center=(0,0), name='A')
p += ER.relation(center=(4,0), name='B')
p += ER.edge(names=['A', 'B'])
print(p)


```



```

from latextool_basic import *
p = Plot()
p += ER.entity(center=(0,0), name='A')
p += ER.relation(center=(4,0), name='B')
p += ER.boldedge(names=['A', 'B'])
print(p)


```




```

from latextool_basic import *
p = Plot()
p += ER.entity(center=(0,0), name='A')
p += ER.relation(center=(4,0), name='B')
p += ER.arc(names=['A', 'B'])
print(p)

```



```
from latextool_basic import *  
p = Plot()  
p += ER.entity(center=(0,0), name='A')  
p += ER.relation(center=(4,0), name='B')  
p += ER.boldarc(names=['A', 'B'])  
print(p)
```




41.5 Entity and relation with attributes

```

from latextool_basic import *
p = Plot()
p += ER.entity(center=(0,0),
               name='Student',
               attrs=['sid', 'name', 'gpa'], keys=['sid'])
ER.attr_width = 3
p += ER.entity(center=(8,0),
               name='Section',
               attrs=['sectionid', 'instructor'], keys=['sectionid'])
ER.attr_width = 1.5
p += ER.relation(center=(4,0), name='Registers',
                 attrs=['date'],
                 anchor={'date': 'south'})
p += ER.line(names=['Student', 'Registers'])
p += ER.line(names=['Section', 'Registers'])
print(p)


```




41.6 Weak entity sets and partial keys

41.7 Associative entity


```
from latextool_basic import *  
p = Plot()  
p += ER.associative_entity_only(center=(0,0), name='a')  
print(p)
```



```
from latextool_basic import *  
p = Plot()  
p += ER.associative_entity_only(center=(0,0), name='a', label='a')  
print(p)
```



```
from latextool_basic import *  
p = Plot()  
p += ER.associative_entity_only(center=(0,0), name='a', label='long string'  
)  
print(p)
```



41.8 Crow's foot

```

from latextool_basic import *
p = Plot()
ER.attrib_width=0.9
ER.attrib_height=0.5
ER.attrib_dist=0.4
ER.attrib_sep=0.4
ER.entity_width=1.8
ER.entity_height=0.5
ER.relation_width=1.8
ER.relation_height=0.5

p += ER.entity(center=(0,0), name='A', attribs=[], keys=[])
p += ER.relation(center=(3,0), name='R', attribs=[], label=r'\scriptsize R')
p += ER.entity(center=(6,0), name='B', attribs=[], keys=[])
p += ER.line(names=['B', 'R'])
p += ER.line(names=['A', 'R'])
crowfoot(p, x=3 + 0.9, y=0, kind="0..1", direction="west")
crowfoot(p, x=6 - 0.9, y=0, kind="1", direction="east")

# Test "west"
p += Line(points=[(0,-1),(2, -1)])
crowfoot(p, x=0, y=-1, kind="1", direction="west")

p += Line(points=[(0,-1.5),(2, -1.5)])
crowfoot(p, x=0, y=-1.5, kind="0..1", direction="west")

p += Line(points=[(0,-2),(2, -2)])
crowfoot(p, x=0, y=-2, kind="*", direction="west")

p += Line(points=[(0,-2.5),(2, -2.5)])
crowfoot(p, x=0, y=-2.5, kind="1..*", direction="west")

# Test "east"
p += Line(points=[(3,-1),(5, -1)])
crowfoot(p, x=5, y=-1, kind="1", direction="east")

p += Line(points=[(3,-1.5),(5, -1.5)])
crowfoot(p, x=5, y=-1.5, kind="0..1", direction="east")

p += Line(points=[(3,-2),(5, -2)])


```

```
crowfoot(p, x=5, y=-2, kind="*", direction="east")

p += Line(points=[(3,-2.5),(5, -2.5)])
crowfoot(p, x=5, y=-2.5, kind="1..*", direction="east")

# Test changing dx
x = 0
y = -4
p += Line(points=[(x,-5),(x + 2, -5)])
crowfoot(p, x=x+2, y=y, dx=0.25, kind="1", direction="east")
x += 3
p += Line(points=[(x, y),(x + 2, y)])
crowfoot(p, x=x+2, y=y, dx=0.25, kind="0..1", direction="east")
x += 3
p += Line(points=[(x, y),(x + 2, y)])
crowfoot(p, x=x+2, y=y, dx=0.25, kind="*", direction="east")
x += 3
p += Line(points=[(x, y),(x + 2, y)])
crowfoot(p, x=x+2, y=y, dx=0.25, kind="1..*", direction="east")

print(p)
```



42 UML diagrams

42.1 UML: class diagram

```

from latextool_basic import *
p = Plot()


uml_class(p, 1, 1,
          classname='Student',
          attributes=['- firstName:\ String',
                     '- lastName:\ String'],
          methods=['+ getFirstName():\ String',
                  '+ getLastName():\ String'])

uml_class(p, 8, 1,
          width=4,
          classname='Student')

uml_class(p, 13, 1,
          width=4,
          classname='Student',
          showempty=False)

p += Grid()
print(p)

```



Relevant arrow tips:

```
from latextool_basic import *
p = Plot()

#p += r'\draw[->>] (1,-5) -- (10,-5);'
#p += r'\draw[->] (1,-5.5) -- (10,-5.5);'
#p += r'\draw[-diamond] (1,-6) -- (10,-6);'
#p += r'\draw[-open diamond] (1,-6.5) -- (10,-6.5);'
#p += r'\draw[-open triangle 45] (1,-7) -- (10,-7);'

p += Line(points=[(0,0),(2,0)], endstyle='diamond', linewidth='0.02')
p += Line(points=[(0,-1),(2,-1)], endstyle='open diamond', linewidth='0.02')
)
p += Line(points=[(0,-2),(2,-2)], endstyle='>', linewidth='0.02')
p += Line(points=[(0,-3),(2,-3)], endstyle='>>', linewidth='0.02')
p += Line(points=[(0,-4),(2,-4)], endstyle='open triangle 45', linewidth='0.02')


print(p)
```



Associations:


Go right:

```
from latextool_basic import *
p = Plot()
A = uml_class(p, 0, 0, width=3, classname='A')
B = uml_class(p, 7, 0, width=3, classname='B')
association(p, p0=A.right(), p1=B.left(), s='plays', c0='a', c1='b')
print(p)
```




Go left:

```
from latextool_basic import *
p = Plot()
A = uml_class(p, 7, 0, width=3, classname='A')
B = uml_class(p, 0, 0, width=3, classname='B')
association(p, p0=A.left(), p1=B.right(), s='plays', c0='a', c1='b')
print(p)
```




Go down:

```
from latextool_basic import *
p = Plot()
A = uml_class(p, 0, 3, width=3, classname='A')
B = uml_class(p, 0, 0, width=3, classname='B')
association(p, p0=A.bottom(), p1=B.top(), s='plays', c0='a', c1='b')
print(p)
```



Go up:

```
from latextool_basic import *
p = Plot()
A = uml_class(p, 0, -3, width=3, classname='A')
B = uml_class(p, 0, 0, width=3, classname='B')
association(p, p0=A.top(), p1=B.bottom(), s='plays', c0='a', c1='b')
print(p)
```



Go right-up (long-short):

```
from latextool_basic import *
p = Plot()
A = uml_class(p, 0, 0, width=3, classname='A')
B = uml_class(p, 5, 1, width=3, classname='B')
p0 = A.right()
p1 = B.bottom()
association(p, p0=p0, p1=p1, s='plays', c0='a', c1='b',
            moves=[('x',p1),('y',p1)])
print(p)
```

Go right-up (short-long):


```
from latextool_basic import *
p = Plot()
A = uml_class(p, 0, 0, width=3, classname='A')
B = uml_class(p, 2, 4, width=3, classname='B')
p0 = A.right()
p1 = B.bottom()
association(p, p0=p0, p1=p1, s='plays', c0='a', c1='b',
            moves=[('x',p1),('y',p1)])
print(p)
```


Go left-down (long-short):

```
from latextool_basic import *
p = Plot()
A = uml_class(p, 0, 0, width=3, classname='A')
B = uml_class(p, -5, -1, width=3, classname='B')
p0 = A.left()
p1 = B.top()
association(p, p0=p0, p1=p1, s='plays', c0='a', c1='b',
            moves=[('x',p1),('y',p1)])
print(p)
```

Go left-down (short-long):

```
from latextool_basic import *
p = Plot()
A = uml_class(p, 0, 0, width=3, classname='A')
B = uml_class(p, -2, -4, width=3, classname='B')
p0 = A.left()
p1 = B.top()
association(p, p0=p0, p1=p1, s='plays', c0='a', c1='b',
            moves=[('x',p1),('y',p1)])
print(p)
```




```

from latextool_basic import *
p = Plot()

player = uml_class(p, 0, 0, width=3, classname='Player')
die = uml_class(p, 7, 0, width=3, classname='Die')
dicegame = uml_class(p, 0, -4, width=3, classname='DiceGame')
test = uml_class(p, 10, 3, width=3, classname='Test')


association(p, p0=player.bottom(), p1=dicegame.top(), s='plays',
            c0='1', c1='1', layout='n')
association(p, p0=player.right(), p1=die.left(), s='rolls',
            c0='1', c1='2', layout='e')
association(p, p0=dicegame.right(), p1=die.bottom(), s='includes',
            c0='1', c1='2', layout='en')
association(p, p0=die.top(), p1=test.left(), s='this is a test',
            c0='1..2', c1='2..*', layout='ne')
print(p)

```




Reflexive associations:

```
from latextool_basic import *
p = Plot()
player = uml_class(p, 0, 0, width=3, classname='', showempty=False)
p0 = player.left()
p1 = player.top()
association(p, p0=p0, p1=p1, s='test',
            c0='1..2', c1='foo', moves=['w','n',('x',p1),('y',p1)])
print(p)
```



```
from latextool_basic import *
p = Plot()
player = uml_class(p, 0, 0, width=3, classname='Player', showempty=False)
p0 = player.right()
p1 = player.top()
association(p, p0=p0, p1=p1, s='test',
            c0='1..2', c1='2..*', moves=['e','n',('x',p1),('y',p1)])
print(p)
```



```
from latextool_basic import *
p = Plot()
person = uml_class(p, 0, 0, width=3, classname='Person', showempty=False)
room = uml_class(p, 5, 0, width=3, classname='Room', showempty=False)
knife = uml_class(p, 2.5, -2, width=3, classname='Knife', showempty=False)

association(p, p0=person.right(), p1=room.left(), s='in',
            c0='*', c1='1', layout='e')
association(p, p0=person.left(), p1=person.top(), s='talks to',
            c0='1', c1='1', layout='wnes')

p0 = knife.right()
p1 = room.bottom()
association(p, p0=p0, p1=p1, s='in',
            c0='0', c1='*', moves=[('x',p1),('y',p1)])

p0 = person.bottom()
p1 = knife.left()
association(p, p0=p0, p1=p1, s='holds',
            c0='*', c1='0', moves=[('y', p1), ('x', p1)])

print(p)
```

debug: uml-
sequencediag

42.2 UML: sequence diagram

PYTHON ERROR. See source, stderr, stdout below

```

from latextool_basic import *
p = Plot()

klsnames = ['main:Main', ':DiceGame', 'die1:Die', 'die2:Die']

messages = [(':DiceGame','play()'),
             ('die1:Die', 'roll()'),
             ('return',''),
             ('die1:Die', 'getFaceValue()'),
             ('return','faceValue'),
             ('die2:Die', 'roll()'),
             ('return',''),
             ('die2:Die', 'getFaceValue()'),
             (None,''), # no return line
             ('return',''),
             (None,''),
            ]

X,Y = 0,0
dY = -1
width = 2.5
hsep = 1.5
worldlinelength = 5
activationbarwidth = 0.4

def kls(p, x, y, s):
    return uml_class(p, x, y, width=width, classname=s, showempty=False)

k = {}
x = X
for klsname in klsnames:
    k[klsname] = kls(p, x, Y, klsname)
    x += width + hsep

def activationbar(klsname, y0, y1):
    p0 = k[klsname].bottom()
    x0 = p0[0] - activationbarwidth / 2.0
    x1 = p0[0] + activationbarwidth / 2.0
    return Rect(x0=x0, y0=y0, x1=x1, y1=y1, background='white')

Y = k.values()[0].bottom()[1] # start y coordinate at the bottom of the class
ss
                                # boxes

Y += dY

f = 'main:Main'
stack = [(f, Y)]
activationbars = [] # to be drawn AFTER the timeline
display_return = True


for x in messages:
    Y += dY
    s = x[1]
    g, Y1 = stack.pop()
    if s != '' or display_return:
        a, b = uml_functioncall(k, klsname0=f, klsname1=g, y=Y, s=s,
                                activationbarwidth=activationbarwidth

```

```
Traceback (most recent call last):
  File "pppikubs.tmp.py", line 41, in <module>
    Y = k.values()[0].bottom()[1] # start y coordinate at the bottom of the
    class
TypeError: 'dict_values' object is not subscriptable
```

debug: uml-
usecasediagra

42.3 UML: use case diagram



43 Matrix

```

from latextool_basic import *

m = Matrix([[1,2],[3,4]])

print(latex_inverse(m))

```

$$\begin{aligned}
\left[\begin{array}{cc|cc} 1 & 2 & 1 & 0 \\ 3 & 4 & 0 & 1 \end{array} \right] &\xrightarrow{R_2 \rightarrow R_2 + (-3) R_1} \left[\begin{array}{cc|cc} 1 & 2 & 1 & 0 \\ 0 & -2 & -3 & 1 \end{array} \right] \\
&\xrightarrow{R_2 \rightarrow (-0.5) R_2} \left[\begin{array}{cc|cc} 1 & 2 & 1 & 0 \\ -0.0 & 1.0 & 1.5 & -0.5 \end{array} \right] \\
&\xrightarrow{R_1 \rightarrow R_1 + (-2) R_2} \left[\begin{array}{cc|cc} 1.0 & 0.0 & -2.0 & 1.0 \\ -0.0 & 1.0 & 1.5 & -0.5 \end{array} \right]
\end{aligned}$$

$$\begin{aligned}
\left[\begin{array}{cc|cc} 1 & 2 & 1 & 0 \\ 3 & 4 & 0 & 1 \end{array} \right] &\xrightarrow{R_2 \rightarrow R_2 + (-3) R_1} \left[\begin{array}{cc|cc} 1 & 2 & 1 & 0 \\ 0 & -2 & -3 & 1 \end{array} \right] \\
&\xrightarrow{R_2 \rightarrow (-0.5) R_2} \left[\begin{array}{cc|cc} 1 & 2 & 1 & 0 \\ -0.0 & 1.0 & 1.5 & -0.5 \end{array} \right] \\
&\xrightarrow{R_1 \rightarrow R_1 + (-2) R_2} \left[\begin{array}{cc|cc} 1.0 & 0.0 & -2.0 & 1.0 \\ -0.0 & 1.0 & 1.5 & -0.5 \end{array} \right]
\end{aligned}$$

??? What's wrong with this??? Check again CISS380.

44 Board games

44.1 Chess

The chess function read image data from image files stored at `data/chess/png/`. The names of the files are `bp.png` for black pawn and `wp.png` for white pawn. Etc. The directory `data/` must be in the same directory as the directory containing `latextool_basic.py`.





[Note that the chess images for pawns are slightly to the right.]

```
from latextool_basic import *
p = Plot()

xs = [list('rnbqkbnr'),
      list('pppppppp'),
      list(''),
      list(''),
      list(''),
      list(''),
      list(''),
      list('PPPPPPPP'),
      list('RNBQKBNR'),
      ]
C = chess(p, x=0, y=0, xs=xs)

p += Line(points=[C[6][4].center(), C[4][4].center()], linecolor='red',
           linewidth=0.1, endstyle='>')

print(p)
```

debug: othell

44.2 Othello

```
from latextool_basic import *
p = Plot()

m = [['', '', '', ''],
      ['', '@', '0', ''],
      ['', '0', '@', ''],
      ['', '', '', '']]
board = othello(p=p, m=m)
print(p)
```

	0	1	2	3
a				
b		●	○	
c		○	●	
d				

Specify row and column labels:

```
from latextool_basic import *
p = Plot()


m = [['', '', '', ''],
      ['', '@', '0', ''],
      ['', '0', '@', ''],
      ['', '', '', '']]
board = othello(p=p, m=m,
                rownames=range(4),
                colnames=range(4),
                )
print(p)
```

	0	1	2	3
0				
1		●	○	
2		○	●	
3				

No row, col labels:

```
from latextool_basic import *
p = Plot()

m = [['', '', '', ''],
      ['', '@', '0', ''],
      ['', '0', '@', ''],
      ['', '', '', '']]
board = othello(p=p, m=m, rownames=[], colnames=[])
print(p)
```




Position:

```

from latextool_basic import *
p = Plot()
X = r'$\times$'
m = [['', X, '', ''],
      [X, '@', 'O', ''],
      ['', 'O', '@', X],
      ['', '', X, '']]
board0 = othello(p=p, m=m, x=0, y=0)
m = [['', 'O', '', ''],
      ['', 'O', 'O', ''],
      ['', 'O', '@', ''],
      ['', '', '', '']]
board1 = othello(p=p, m=m, x=6, y=0)
x0,y0 = board0.right(); x0 += 1; p0 = (x0,y0)
x1,y1 = board1.left(); x1 -= 1; p1 = (x1,y1)
p += Line(points=[p0, p1], linewidth=0.2, endstyle='>')
print(p)

```



Highlighting a cell:

```
from latextool_basic import *
p = Plot()
X = r'$\times$'
m = [['', 'O', '', ''],
      ['', 'O', 'O', ''],
      ['', 'O', '@', ''],
      ['', ' ', ' ', '']]
board = othello(p=p, m=m, x=6, y=0, do_not_plot=True)

def highlight(p, row, col):
    x0,y0 = board[row][col].bottomleft()
    x1,y1 = board[row][col].topright()
    p += Rect(x0=x0, y0=y0, x1=x1, y1=y1,
              background='black!15',label='', linewidth=0)

highlight(p, 2, 1)
highlight(p, 3, 1)
highlight(p, 2, 2)

board = othello(p=p, m=m, x=6, y=0)
print(p)
```

	0	1	2	3
a		○		
b		○	○	
c		○	●	
d				

debug: ttt.tex

44.3 Tic-tac-toe

```
from latextool_basic import *
p = Plot()

X = 'X'; O = 'O'; s = ''

m = [[X, s, s, s],
      [s, X, O, s],
      [s, O, O, s],
      [s, s, s, s]]
board = ttt(p=p, m=m)
print(p)
```

	0	1	2	3
a	X			
b		X	O	
c		O	O	
d				

no row and column labels:

```
from latextool_basic import *
p = Plot()

X = 'X'; O = 'O'; s = ''

m = [[X, s, s, s],
      [s, X, O, s],
      [s, O, O, s],
      [s, s, s, s]]
board = ttt(p=p, m=m,
            rownames=['',' ',' ',' '], colnames=['',' ',' ',' '])
print(p)
```


X			
	X	O	
	O	O	

position:

```
from latextool_basic import *
p = Plot()

X = 'X'; O = 'O'; s = ''

m = [[X, s, s, s],
      [s, X, O, s],
      [s, O, O, s],
      [s, s, s, s]]
board = ttt(p=p, x=0, y=0,
            m=m,
            rownames=['',' ',' ',' '], colnames=['',' ',' ',' '])
board = ttt(p=p, x=5, y=1,
            m=m,
            rownames=['',' ',' ',' '], colnames=['',' ',' ',' '])
p += Grid(x0=-1, y0=-4, x1=9, y1=2)
print(p)
```




cell size:

```
from latextool_basic import *
p = Plot()

X = 'X'; O = 'O'; s = ' '

m = [[X, s, s, s],
      [s, X, O, s],
      [s, O, O, s],
      [s, s, s, s]]
board = ttt(p=p, x=0, y=0,
            m=m,
            rownames=['', '', '', ''], colnames=['', '', '', ''],
            width=0.4)
board = ttt(p=p, x=5, y=1,
            m=m,
            rownames=['', '', '', ''], colnames=['', '', '', ''])
p += Grid(x0=-1, y0=-3, x1=9, y1=2)
print(p)
```




border:

```
from latextool_basic import *
p = Plot()

X = 'X'; O = 'O'; s = ''

m = [[X, s, s, s],
      [s, X, O, s],
      [s, O, O, s],
      [s, s, s, s]]
board = ttt(p=p, x=0, y=0,
            m=m,
            rownames=['',' ',' ',' '], colnames=['',' ',' ',' '],
            border_linewidth=0.2)
print(p)
```



using the board

```

from latextool_basic import *
from latexcircuit import *

p = Plot()

X = 'X'; O = 'O'; s = ''

m = [[X, s, s, s],
      [s, X, O, s],
      [s, O, O, s],
      [s, s, s, s]]
board0 = ttt(p=p, x=0, y=0,
             m=m,
             rownames=['',' ',' ',' '], colnames=['',' ',' ',' '])
x,y = board0.topleft()
X = POINT(x=x, y=y, r=0, label='Tic-tac-toe', anchor='south west')
p += str(X)


m[0][1] = 'X'
board1 = ttt(p=p, x=6, y=0,
             m=m,
             rownames=['',' ',' ',' '], colnames=['',' ',' ',' '])

p += Line(points=[board0.right(), board1.left()], endstyle='>', linewidth=0.4)

p += Line(points=[board0[0][1].center(),
                  board1[0][1].left()], endstyle='>', linewidth=0.1)

print(p)


```



45 Proof Trees

46 K-maps

Drawing closed rect groups. Specify 2 rects: the bottom-left rect and the top-right rect.



```
from latextool_basic import *


p = Plot()
p += Grid(-2, -3, 3, 1)
m = [[0,1,1,1],
      [0,0,1,0],
      [0,0,0,0],
      [0,1,1,0],
      ]

C = table2(p, m, width=0.7, height=0.7,
           rownames=['00','01','11','10'],
           colnames=['00','01','11','10'],
           rowlabel='WX', collabel='YZ')

#p += kmap_rect(C[3][0], C[2][1], linecolor='red')
#p += kmap_rect(C[1][1], C[0][1], linecolor='blue')
#p += kmap_rect(C[1][0], C[0][0], linecolor='green')
#p += kmap_rect(C[3][2], C[0][2], linecolor='green')
#p += kmap_rect(C[3][0], C[3][3], linecolor='yellow')
#p += kmap_rect(C[0][3], linecolor='cyan')
#p += kmap_rect(C[2][2], C[2][3], linecolor='magenta')

print(p)
```

K-map groups with 1 open side.



```

from latextool_basic import *

p = Plot()
p += Grid(-2, -3, 6, 1)
m = [[0,1,1,0,0,1,1,1],
      [0,1,0,1,1,1,1,1],
      [1,0,1,1,0,0,0,0],
      [0,1,1,1,1,0,1,0],
      ]

C = table2(p, m, width=0.7, height=0.7,
           rownames=['00','01','11','10'],
           colnames=['00','01','11','10'],
           rowlabel='WX', collabel='YZ')

kmap_WW(p, C[0][4], linecolor='red')
kmap_WW(p, C[2][4], C[1][6], linecolor='red')
kmap_WW(p, C[3][4], C[3][6], linecolor='red')

kmap_EE(p, C[0][7], linecolor='yellow')
kmap_EE(p, C[1][7], C[1][7], linecolor='yellow')
kmap_EE(p, C[3][6], C[2][7], linecolor='yellow')


kmap_SS(p, C[3][0], linecolor='pink')
kmap_SS(p, C[3][1], C[3][2], linecolor='pink')
kmap_SS(p, C[3][2], C[2][3], linecolor='pink')

kmap_NN(p, C[0][0], linecolor='green')
kmap_NN(p, C[0][1], C[0][2], linecolor='green')
kmap_NN(p, C[1][2], C[0][3], linecolor='green')

print(p)

```

K-map groups with two open sides.



```
from latextool_basic import *

p = Plot()
p += Grid(-2, -3, 3, 1)
m = [[0,1,1,0],
      [0,1,0,1],
      [1,0,1,1],
      [0,1,1,1],
      ]

C = table2(p, m, width=0.7, height=0.7,
           rownames=['00','01','11','10'],
           colnames=['00','01','11','10'],
           rowlabel='WX', collabel='YZ')

kmap_NW(p, C[0][0], linecolor='magenta')
kmap_NW(p, C[1][0], C[0][1], linecolor='magenta')


kmap_NE(p, C[0][3], linecolor='cyan')
kmap_NE(p, C[1][2], C[0][3], linecolor='cyan')

kmap_SW(p, C[3][0], linecolor='yellow')
kmap_SW(p, C[3][0], C[2][1], linecolor='yellow')

kmap_SE(p, C[3][3], linecolor='red')
kmap_SE(p, C[3][2], C[2][3], linecolor='red')
kmap_SE(p, C[3][1], C[3][3], linecolor='blue')

print(p)
```


K-maps.




```
from latextool_basic import *

p = Plot()
p += Grid(-2, -3, 3, 1)
m = [[0,1,1,0],
      [0,1,0,1],
      [1,0,1,1],
      [0,1,1,1],
      ]

C = kmap(p, m, width=0.7, height=0.7,
         rowlabel='$wx$', collabel='$yz$')

print(p)
```



```


from latextool_basic import *

p = Plot()
p += Grid(-2, -3, 3, 1)
m = [[0,1,0,0],
      [0,1,0,1],
      [1,1,0,1],
      [0,1,0,1],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$wx$', collabel='$yz$')

print(p)

```



```


from latextool_basic import *

p = Plot()
p += Grid(-2, -3, 3, 1)
m = [[0,1,0,1],
      [0,1,0,0],
      [1,1,1,1],
      [0,1,0,0],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$wx$', collabel='$yz$')

print(p)

```




```

from latextool_basic import *

p = Plot()
p += Grid(-2, -3, 3, 1)
m = [[0,1,0,1],
      [0,0,0,0],
      [1,0,0,1],
      [0,1,0,0],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$wx$', collabel='$yz$')
print(p)

```




```

from latextool_basic import *

p = Plot()
p += Grid(-2, -3, 3, 1)
m = [[0,1,0,0],
      [1,0,0,1],
      [1,0,0,1],
      [0,1,0,0],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$wx$', collabel='$yz$')
print(p)

```




```

from latextool_basic import *

p = Plot()
p += Grid(-2, -3, 3, 1)
m = [[1,1,0,1],
      [1,0,0,1],
      [1,0,0,1],
      [1,1,0,1],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$wx$', collabel='$yz$')
print(p)

```




```

from latextool_basic import *

p = Plot()
p += Grid(-2, -3, 3, 1)
m = [[1,1,0,1],
      [1,0,0,1],
      [1,1,0,1],
      [1,1,0,1],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$wx$', collabel='$yz$')
print(p)

```





```

from latextool_basic import *

p = Plot()
p += Grid(-2, -3, 3, 1)
m = [[1,1,1,1],
      [0,0,0,0],
      [0,1,0,0],
      [1,1,1,1],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$wx$', collabel='$yz$')
print(p)

```



```

from latextool_basic import *

p = Plot()
m = [[1,1,1,1],
      [1,1,1,1],
      [1,1,1,1],
      [1,1,1,1],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$wx$', collabel='$yz$')
print(p)

```

		yz	00	01	11	10
wx	00	0	0	1	0	
	01	1	1	1	0	
	11	0	1	1	1	
	10	0	0	1	0	

```

from latextool_basic import *

p = Plot()
m = [[0,0,1,0],
      [1,1,1,0],
      [0,1,1,1],
      [0,0,1,0],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$wx$', collabel='$yz$')
print(p)

```

		<i>abc</i>							
<i>de</i>		000	001	011	010	100	101	111	110
00	0	1	1	0	1	1	1	1	1
01	0	1	0	1	1	0	1	0	0
11	0	1	1	0	0	1	0	1	1
10	1	0	1	0	1	1	0	1	1

```

from latextool_basic import *

p = Plot()
#p += Grid(-2, -3, 3, 1)
m = [[0,1,1,0,1,1,1,1],
      [0,1,0,1,1,0,1,0],
      [0,1,1,0,0,1,0,1],
      [1,0,1,0,1,1,0,1],
      ]

C = kmap(p, m, width=1, height=1,
         rowlabel='$de$', collabel='$abc$')
print(p)

```


46.1 kmap: specify term(s) to circle

	yz	00	01	11	10
wx	00	0	0	d	0
	01	1	1	1	0
	11	d	1	1	0
	10	0	0	1	0

```
from latextool_basic import *

p = Plot()
m = [[0,0,'d',0],
      [1,1,1,0],
      ['d',1,1,0],
      [0,0,1,0],
      ]

C = kmap(p, m, width=0.7, height=0.7,
         circle_terms=[1, 'd'],
         rowlabel='$wx$', collabel='$yz$')
print(p)
```

	yz	00	01	11	10
wx	00	0	0	x	0
	01	1	1	1	0
	11	x	1	1	0
	10	0	0	1	0

```
from latextool_basic import *

p = Plot()
m = [[0,0,'x',0],
      [1,1,1,0],
      ['x',1,1,0],
      [0,0,1,0],
      ]

C = kmap(p, m, width=0.7, height=0.7,
         circle_terms=[0, 'x'],
         rowlabel='$wx$', collabel='$yz$')
print(p)
```

46.2 kmap: 2-by-4

		yz			
		00	01	11	10
x	0	0	0	1	0
	1	0	1	0	1

```
from latextool_basic import *

p = Plot()
m = [[0,0,1,0],
      [0,1,0,1],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$x$', collabel='$yz$')

print(p)
```

		yz			
		00	01	11	10
x	0	0	0	0	0
	1	1	1	1	1

```
from latextool_basic import *

p = Plot()
m = [[0,0,0,0],
      [1,1,1,1],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$x$', collabel='$yz$')

print(p)
```

	yz	00	01	11	10
x	0	1	1	0	0
	1	1	1	0	0

```
from latextool_basic import *

p = Plot()
m = [[1,1,0,0],
      [1,1,0,0],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$x$', collabel='$yz$')

print(p)
```

	yz	00	01	11	10
x	0	1	0	0	1
	1	0	0	0	0

```
from latextool_basic import *

p = Plot()
m = [[1,0,0,1],
      [0,0,0,0],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$x$', collabel='$yz$')

print(p)
```

	yz	00	01	11	10
x	0	1	0	0	1
	1	1	0	0	1

```

from latextool_basic import *

p = Plot()
m = [[1,0,0,1],
      [1,0,0,1],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$x$', collabel='$yz$')

print(p)

```

A 2x4 Karnaugh map with row labels x (0, 1) and column labels yz (00, 01, 11, 10). The map contains the following values:

$x \backslash yz$	00	01	11	10
0	1	0	1	1
1	1	1	0	1

Prime implicants are highlighted with colored loops: a green loop covers the four 1s in the first column ($x=0, yz=00$ and $x=1, yz=00$); a yellow loop covers the two 1s in the first row ($x=0, yz=00$ and $x=0, yz=11$); a pink loop covers the two 1s in the second row ($x=1, yz=00$ and $x=1, yz=11$); and a green loop covers the two 1s in the fourth column ($x=0, yz=10$ and $x=1, yz=10$).

```

from latextool_basic import *

p = Plot()
m = [[1,0,1,1],
      [1,1,0,1],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$x$', collabel='$yz$')

print(p)

```

A 2x4 Karnaugh map with row labels x (0, 1) and column labels yz (00, 01, 11, 10). The map contains the following values:

$x \backslash yz$	00	01	11	10
0	0	0	0	0
1	1	1	0	1

Prime implicants are highlighted with colored loops: a green loop covers the two 1s in the first row ($x=1, yz=00$ and $x=1, yz=01$); a pink loop covers the two 1s in the second row ($x=1, yz=00$ and $x=1, yz=10$); and a green loop covers the two 1s in the fourth column ($x=1, yz=01$ and $x=1, yz=10$).

```
from latextool_basic import *

p = Plot()
m = [[0,0,0,0],
      [1,1,0,1],
      ]

C = kmap(p, m, width=0.7, height=0.7,
          rowlabel='$x$', collabel='$yz$')

print(p)
```



```
from latextool_basic import *

p = Plot()
p += Grid(-2, -3, 3, 1)
m = [[0,0,1,1],
      [0,1,1,0],
      [1,1,0,0],
      [1,0,0,1],
      ]

C = kmap(p, m, width=0.7, height=0.7,
         rowlabel='$wx$', collabel='$yz$',
         donotremove=[((0,0),(2,3))])
print(p)
```


46.4 kmap: style selector

You can select color and linewidth for the implicants:

46.5 kmap: change distance of implicant boundary to rect

d = 0.1:

$d = 0.3$

46.6 kmap: decimal notation

	yz	00	01	11	10
wx	00	0 0	0 1	1 3	1 2
	01	0 4	1 5	1 7	0 6
	11	1 12	1 13	0 15	0 14
	10	1 8	0 9	0 11	1 10

```

from latextool_basic import *

p = Plot()
m = [[0,0,1,1],
      [0,1,1,0],
      [1,1,0,0],
      [1,0,0,1],
      ]


C = kmap(p, m, width=1.1, height=1.1,
         rowlabel='$wx$', collabel='$yz$',
         decimal=True
        )

print(p)

```

46.7 kmap: decimal notation 2

You can specify offset of decimal notation and the formatting string:



```
from latextool_basic import *

p = Plot()
m = [[0,0,1,1],
      [0,1,1,0],
      [1,1,0,0],
      [1,0,0,1],
      ]

C = kmap(p, m, width=1.1, height=1.1,
         rowlabel='$wx$', collabel='$yz$',
         d = 0.3,
         decimal=True,
         decimal_offset=0.1,
         decimal_format=r'\textred{\textsl{%s}}}')


print(p)
```

46.8 kmap: using coordinates of rects in the kmap cells

I use a slightly large d value so that the implicant boundaries avoid the decimal notation.

47 Logic design

47.1 AND gate



```
from latextool_basic import *
from latexcircuit import *


p = Plot()
g = AND_GATE(x=0, y=0, inputs=2)
p += str(g)

for x,y in g.inputs():
    p += Line(points=[(x - 1, y), (x, y)])

x,y = g.output()
p += Line(points=[(x, y), (x + 1,y)])

p += Grid(x0=-2, y0=-1, x1=2, y1=1)
print(p)
```


47.2 OR gate



```

from latextool_basic import *
from latexcircuit import *

p = Plot()
g = OR_GATE()
p += str(g)


for x,y in g.inputs():
    p += Line(points=[(x - 1, y), (x, y)])

x,y = g.output()
p += Line(points=[(x, y),(x+1,y)])

p += Grid(x0=-2, y0=-1, x1=2, y1=1)
print(p)

```

47.3 NOT gate



```

from latextool_basic import *
from latexcircuit import *

p = Plot()
g = NOT_GATE()
p += str(g)


x,y = g.input()
p += Line(points=[(x,y),(x - 1,y)])

x,y = g.output()
p += Line(points=[(x,y),(x + 1,y)])

p += Grid(x0=-2, y0=-1, x1=2, y1=1)
print(p)

```

47.4 NAND gate



```

from latextool_basic import *
from latexcircuit import *

p = Plot()
g = NAND_GATE()
p += str(g)


for x,y in g.inputs():
    p += Line(points=[(x-1,y),(x,y)])

x,y = g.output()
p += Line(points=[(x,y),(x+1,y)])

p += Grid(x0=-2, y0=-1, x1=2, y1=1)
print(p)

```

47.5 NOR gate



```

from latextool_basic import *
from latexcircuit import *

p = Plot()
g = NOR_GATE()
p += str(g)


for x,y in g.inputs():
    p += Line(points=[(x-1,y),(x,y)])

x,y = g.output()
p += Line(points=[(x,y),(x+1,y)])

p += Grid(x0=-2, y0=-1, x1=2, y1=1)
print(p)

```

47.6 XOR gate



```

from latextool_basic import *
from latexcircuit import *

p = Plot()
g = XOR_GATE()
p += str(g)

for x,y in g.inputs():
    p += Line(points=[(x-1,y),(x,y)])


x,y = g.output()
p += Line(points=[(x,y),(x+1,y)])

p += Grid(x0=-2, y0=-1, x1=2, y1=1)
print(p)

```


47.7 Orthogonal paths

For drawing orthogonal paths between two points.




```
from latextool_basic import *
from latexcircuit import *
p = Plot()
p += str(OrthogonalPath([(0,0), (5,1)]))
p += Grid(x0=-1, y0=-1, x1=6, y1=1)
print(p)
```

Orthogonal path with arrow head:




```
from latextool_basic import *
from latexcircuit import *
p = Plot()
p += str(OrthogonalPath([(0,0), (5,1)], endstyle='>', arrowstyle='triangle'))
p += Grid(x0=-1, y0=-1, x1=6, y1=1)
print(p)
```

Orthogonal paths – no bend case:




```
from latextool_basic import *
from latexcircuit import *
p = Plot()
p += str(OrthogonalPath([(0,0), (5,0)]))
p += Grid(x0=-1, y0=-1, x1=6, y1=1)
print(p)
```

with a positive horizontal shift of the bend:



```
from latextool_basic import *
from latexcircuit import *
p = Plot()
p += str(OrthogonalPath([(0,0), (5,1)], shifts=[1]))
p += Grid(x0=-1, y0=-1, x1=6, y1=1)
print(p)
```


with a negative horizontal shift of the bend:



```
from latextool_basic import *
from latexcircuit import *
p = Plot()
p += str(OrthogonalPath([(0,0), (5,1)], shifts=[-1]))
p += Grid(x0=-1, y0=-1, x1=6, y1=1)
print(p)
```


TODO: shifts for vertical case

orthogonal path, direction='vh' (vertical-horizontal):




```
from latextool_basic import *
from latexcircuit import *
p = Plot()
p += str(OrthogonalPath(points=[(0,0), (5,1)], direction='vh'))
p += Grid(x0=-1, y0=0, x1=6, y1=1)
print(p)
```

orthogonal path, direction='vh':



```
from latextool_basic import *
from latexcircuit import *
p = Plot()
p += str(OrthogonalPath(points=[(0,1), (5,0)], direction='vh'))
p += Grid(x0=-1, y0=0, x1=6, y1=1)
print(p)
```


47.8 Orthogonal path with gates




```
from latextool_basic import *
from latexcircuit import *
p = Plot()
AND = AND_GATE(x=0, y=0); p += str(AND)
OR = OR_GATE(x=5, y=1); p += str(OR)
opath = OrthogonalPath(gate0=AND, gate1=OR, input_index=0)
p += str(opath)
print(p)
```

47.9 POINT

POINT:



```
from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=0, label='$x$')
p += str(X)
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)
```



```
from latextool_basic import *
from latexcircuit import *
p = Plot()
X = POINT(x=0, y=0, label='$x$', anchor='north')
p += str(X)
p += str(OrthogonalPath([X.output(), (3,1)]))
p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)
```

47.10 Linecolor for gate



```
from latextool_basic import *
from latexcircuit import *


p = Plot()
g0 = AND_GATE(linewidth=5, linecolor='blue')
p += str(g0)

print(p)
```

47.11 Label for gate



Test 2 inputs and output



```
from latextool_basic import *
from latexcircuit import *

p = Plot()
g0 = AND_GATE(linewidth=5, linecolor='blue'); p += str(g0)

inputs = g0.inputs()


# Test input 0
x0,y0 = inputs[0]; p0 = (x0, y0)
x1,y1 = x0 - 2, y0; p1 = (x1, y1)
p += Line(points=[p0,p1], linewidth=0.1, linecolor='red')
x0 = x1 - 0.3
p += Rect(x0=x0, y0=y0, x1=x0, y1=y0, linewidth=0, s = '$x$')

# test input 1
x0,y0 = inputs[1]; p0 = (x0, y0)
x1,y1 = x0 - 1, y0; p1 = (x1, y1)
p += Line(points=[p0,p1], linewidth=0.1, linecolor='green')

# test output
x0,y0 = g0.output(); p0 = x0,y0
x1,y1 = x0 + 3, y0; p1 = (x1, y1)
p += Line(points=[p0,p1], linewidth=0.1, linecolor='black')

p += Grid()
print(p)
```

Test 3 inputs and output



```

from latextool_basic import *
from latexcircuit import *

p = Plot()
g0 = AND_GATE(linewidth=5, linecolor='blue', inputs=3)
p += str(g0)


for x0,y0 in g0.inputs():
    p0 = (x0, y0)
    x1,y1 = x0 - 1, y0
    p1 = (x1, y1)
    p += Line(points=[p0,p1], linewidth=0.1, linecolor='red')

x0,y0 = g0.output()
p0 = (x0, y0)
x1,y1 = x0 + 1, y0
p1 = (x1, y1)
p += Line(points=[p0,p1], linewidth=0.1, linecolor='green')

p += Grid()
print(p)

```

Test different size (height = 2)



```

from latextool_basic import *
from latexcircuit import *

p = Plot()
g0 = AND_GATE(x=0, y=0, h=2,
              linewidth=5, linecolor='magenta', inputs=3)
p += str(g0)


for x0,y0 in g0.inputs():
    p0 = (x0, y0)
    x1,y1 = x0 - 1, y0
    p1 = (x1, y1)
    p += Line(points=[p0,p1], linewidth=0.1, linecolor='red')

x0,y0 = g0.output()
p0 = (x0, y0)
x1,y1 = x0 + 1, y0
p1 = (x1, y1)
p += Line(points=[p0,p1], linewidth=0.1, linecolor='green')

p += Grid()
print(p)

```

Test height = 2, 4 inputs:



```

from latextool_basic import *
from latexcircuit import *

p = Plot()
g0 = AND_GATE(x=0, y=0, h=2,
              linewidth=5, linecolor='blue', inputs=4)
p += str(g0)


for x0,y0 in g0.inputs():
    p0 = (x0, y0)
    x1,y1 = x0 - 1, y0
    p1 = (x1, y1)
    p += Line(points=[p0,p1], linewidth=0.1, linecolor='red')

x0,y0 = g0.output()
p0 = (x0, y0)
x1,y1 = x0 + 1, y0
p1 = (x1, y1)
p += Line(points=[p0,p1], linewidth=0.1, linecolor='green')

p += Grid()
print(p)

```

Test height = 2, 5 inputs:




```

from latextool_basic import *
from latexcircuit import *

p = Plot()
g0 = AND_GATE(x=0, y=0, h=2,
              linewidth=5, linecolor='blue', inputs=5)
p += str(g0)


for x0,y0 in g0.inputs():
    p0 = (x0, y0)
    x1,y1 = x0 - 1, y0
    p1 = (x1, y1)
    p += Line(points=[p0,p1], linewidth=0.1, linecolor='red')

x0,y0 = g0.output()
p0 = (x0, y0)
x1,y1 = x0 + 1, y0
p1 = (x1, y1)
p += Line(points=[p0,p1], linewidth=0.1, linecolor='green')

p += Grid()
print(p)

```

OR gate:



```


from latextool_basic import *
from latexcircuit import *

p = Plot()
g0 = OR_GATE(linewidth=2, linecolor='blue')
p += str(g0)

p += Grid(x0=-1,y0=-1,x1=3,y1=1)

print(p)

```



```

from latextool_basic import *
from latexcircuit import *


p = Plot()
g0 = OR_GATE(linewidth=2, linecolor='blue', label='$z$')
p += str(g0)

p += Grid(x0=-1,y0=-1,x1=3,y1=1)

print(p)

```

OR gate testing 2 inputs



```

from latextool_basic import *
from latexcircuit import *

p = Plot()
g0 = OR_GATE(linewidth=2, linecolor='blue')
p += str(g0)

for x0,y0 in g0.inputs():
    p0 = (x0, y0)
    x1,y1 = x0 - 1, y0
    p1 = (x1, y1)
    p += Line(points=[p0,p1], linewidth=0.1, linecolor='red')


x0,y0 = g0.output()
p0 = (x0, y0)
x1,y1 = x0 + 1, y0
p1 = (x1, y1)
p += Line(points=[p0,p1], linewidth=0.1, linecolor='green')

p += Grid(x0=-1,y0=-1,x1=3,y1=1)

print(p)

```

OR gate testing 2 inputs



```
from latextool_basic import *
from latexcircuit import *

p = Plot()
g0 = OR_GATE(linewidth=2, x=0, y=0, linecolor='blue')
p += str(g0)


for x0,y0 in g0.inputs():
    p0 = (x0, y0)
    x1, y1 = - 1, y0
    p1 = (x1, y1)
    p += Line(points=[p0,p1], linewidth=0.1, linecolor='red')

x0, y0 = g0.output(); p0 = (x0, y0)
x1, y1 = x0 + 1, y0; p1 = (x1, y1)
p += Line(points=[p0,p1], linewidth=0.1, linecolor='green')

p += Grid(x0=-1,y0=-2,x1=3,y1=2)

print(p)
```

OR gate testing 3 inputs



```
from latextool_basic import *
from latexcircuit import *

p = Plot()
g0 = OR_GATE(linewidth=2, x=0,y=0,h=3, inputs=3, linecolor='blue')
p += str(g0)


for x0,y0 in g0.inputs():
    p0 = (x0, y0)
    p1 = (-1, y0)
    p += Line(points=[p0,p1], linewidth=0.1, linecolor='red')

x0,y0 = g0.output(); p0 = (x0, y0)
x1,y1 = x0 + 1, y0; p1 = (x1, y1)
p += Line(points=[p0, p1], linewidth=0.1, linecolor='green')

p += Grid(x0=-1,y0=-2,x1=3,y1=2)

print(p)
```

OR gate testing 4 inputs



```
from latextool_basic import *
from latexcircuit import *

p = Plot()
g0 = OR_GATE(linewidth=2, x=0,y=0,h=3, inputs=4,linecolor='blue')
p += str(g0)

for x0,y0 in g0.inputs():
    p0 = (x0, y0); x1, y1 = -1, y0; p1 = (x1, y1)
    p += Line(points=[p0,p1], linewidth=0.1, linecolor='red')


x0,y0 = g0.output()
p0 = (x0, y0); p1 = (x0 + 1, y0)
p += Line(points=[p0,p1], linewidth=0.1, linecolor='green')

p += Grid(x0=-1, y0=-2, x1=5, y1=2)

print(p)
```

47.12 Rotation

AND gate rotate by $\pi/4$:




```
from math import pi
from latextool_basic import *
from latexcircuit import *
p = Plot()
g = AND_GATE(x=0, y=0, inputs=2, angle=pi/2)
p += str(g)

for x,y in g.inputs():
    p += Line(points=[(x, y - 1), (x, y)])

x,y = g.output()
p += Line(points=[(x, y),(x, y + 1)])

p += Grid(x0=-1, y0=-1, x1=1, y1=2)
print(p)
```

AND gate rotate by π :




```
from math import pi
from latextool_basic import *
from latexcircuit import *
p = Plot()
g = AND_GATE(x=0, y=0, inputs=2, angle=pi)
p += str(g)

for x,y in g.inputs():
    p += Line(points=[(x + 1, y), (x, y)])

x,y = g.output()
p += Line(points=[(x, y),(x - 1, y)])

p += Grid(x0=-2, y0=-1, x1=1, y1=1)
print(p)
```


AND gate rotate by $3\pi/2$:




```
from math import pi
from latextool_basic import *
from latexcircuit import *
p = Plot()
g = AND_GATE(x=0, y=0, inputs=2, angle=3*pi/2)
p += str(g)

for x,y in g.inputs():
    p += Line(points=[(x, y + 1), (x, y)])

x,y = g.output()
p += Line(points=[(x, y), (x, y - 1)])

p += Grid(x0=-1, y0=-2, x1=1, y1=1)
print(p)
```

OR gate rotate by $\pi/4$:



```
from math import pi
from latextool_basic import *
from latexcircuit import *
p = Plot()


g = OR_GATE(x=0, y=0, inputs=2, angle=pi/2)
p += str(g)

for x,y in g.inputs():
    p += Line(points=[(x, y - 1), (x, y)])

x,y = g.output()
p += Line(points=[(x, y), (x, y + 1)])

p += Grid(x0=-1, y0=-1, x1=1, y1=2)
print(p)
```

OR gate rotate by π :



```

from math import pi
from latextool_basic import *
from latexcircuit import *
p = Plot()
g = OR_GATE(x=0, y=0, inputs=2, angle=pi)
p += str(g)


for x,y in g.inputs():
    p += Line(points=[(x + 1, y), (x, y)])

x,y = g.output()
p += Line(points=[(x, y),(x - 1, y)])

p += Grid(x0=-2, y0=-1, x1=1, y1=1)
print(p)

```

OR gate rotate by $3\pi/2$:




```
from math import pi
from latextool_basic import *
from latexcircuit import *
p = Plot()
g = OR_GATE(x=0, y=0, inputs=2, angle=3*pi/2)
p += str(g)

for x,y in g.inputs():
    p += Line(points=[(x, y + 1), (x, y)])

x,y = g.output()
p += Line(points=[(x, y), (x, y - 1)])

p += Grid(x0=-1, y0=-2, x1=1, y1=1)
print(p)
```

NOT gate rotate by $\pi/4$:




```
from math import pi
from latextool_basic import *
from latexcircuit import *
p = Plot()
g = NOT_GATE(x=0, y=0, inputs=2, angle=pi/2)
p += str(g)

x,y = g.input()
p += Line(points=[(x, y - 1), (x, y)])

x,y = g.output()
p += Line(points=[(x, y), (x, y + 1)])

p += Grid(x0=-1, y0=-1, x1=1, y1=2)
print(p)
```

NOT gate rotate by π :




```
from math import pi
from latextool_basic import *
from latexcircuit import *
p = Plot()
g = NOT_GATE(x=0, y=0, inputs=2, angle=pi)
p += str(g)

x,y = g.input()
p += Line(points=[(x + 1, y), (x, y)])

x,y = g.output()
p += Line(points=[(x, y),(x - 1, y)])

p += Grid(x0=-2, y0=-1, x1=1, y1=1)
print(p)
```

NOT gate rotate by $3\pi/2$:




```
from math import pi
from latextool_basic import *
from latexcircuit import *
p = Plot()
g = NOT_GATE(x=0, y=0, inputs=2, angle=3*pi/2)
p += str(g)

x,y = g.input()
p += Line(points=[(x, y + 1), (x, y)])

x,y = g.output()
p += Line(points=[(x, y), (x, y - 1)])

p += Grid(x0=-1, y0=-2, x1=1, y1=1)
print(p)
```


Test OUTPUT POINT



```
from latextool_basic import *
from latexcircuit import *
p = Plot()

NOR = NOR_GATE(x=0, y=3)
P = OUTPUT_POINT(gate=NOR)

p += str(NOR)
p += str(P)
print(p)
```




```
from latextool_basic import *
from latexcircuit import *
p = Plot()

AND = AND_GATE(x=0, y=3)
P = OUTPUT_POINT(gate=AND, output_length=4, label='z', anchor='west')

p += str(AND)
p += str(P)
print(p)
```


Test INPUT POINT



Example:


```

from latextool_basic import *
from latexcircuit import *
p = Plot()

AND = AND_GATE(x=0, y=3, inputs=3)
P0 = INPUT_POINT(gate=AND, input_index=2, label='$x$', input_length=1)
P1 = INPUT_POINT(gate=AND, input_index=1, label='$y$', input_length=1)
P2 = INPUT_POINT(gate=AND, input_index=0, label='$z$', input_length=1)
P3 = OUTPUT_POINT(gate=AND, label='$xyz$', anchor='west', output_length=1)

p += str(AND)
p += str(P0)
p += str(P1)
p += str(P2)
p += str(P3)
print(p)

```



Example:

```
from latextool_basic import *
from latexcircuit import *
p = Plot()

and0 = AND_GATE(x=0, y=0, h=1, inputs=3)

x, y = and0.inputs()[2]; x -= 1
X = POINT(x=x, y=y, label='$x$')

x, y = and0.inputs()[1]; x -= 1
Y = POINT(x=x, y=y, label='$y$')

x, y = and0.inputs()[0]; x -= 1
Z = POINT(x=x, y=y, label='$z$')

x, y = and0.output(); x += 1
XYZ = POINT(x=x, y=y, label='$xyz$', anchor='west')


p += str(and0)
p += str(X); p += str(Y); p += str(Z)
p += str(XYZ)

p += '%s' % OrthogonalPath([X.output(), and0.inputs()[2]])
p += '%s' % OrthogonalPath([Y.output(), and0.inputs()[1]])
p += '%s' % OrthogonalPath([Z.output(), and0.inputs()[0]])

p += '%s' % OrthogonalPath([XYZ.output(), and0.output()])

p += Grid(x0=-2, y0=-1, x1=4, y1=1)
print(p)
```

Example:



```

from latextool_basic import *
from latexcircuit import *
p = Plot()

and0 = AND_GATE(x=0,y=0,h=1, inputs=3)
and1 = AND_GATE(x=0,y=2,h=1, inputs=3)
and2 = AND_GATE(x=0,y=4,h=1, inputs=3)

x,y = and1.output(); x += 4
or0 = OR_GATE(x=x, y=y,h=1, inputs=3)

x, y = and1.inputs()[1]; x -= 4
A = POINT(x=x, y=y + 1, label='$A$')
B = POINT(x=x, y=y + 0, label='$B$')
C = POINT(x=x, y=y + -1, label='$C$')
notA = NOT_GATE(x=A.x()+1, y=A.y()-0.5)
notB = NOT_GATE(x=B.x()+1, y=B.y()-0.5)
notC = NOT_GATE(x=C.x()+1, y=C.y()-0.5)

x0,y0 = or0.output()
Z = POINT(x=x0+1, y=y0, label='$z$', anchor='west')

p += str(A); p += str(B); p += str(C)
p += str(notA); p += str(notB); p += str(notC)
p += str(and0); p += str(and1); p += str(and2)
p += str(or0)

p += str(Z)

OP = OrthogonalPath
# Join A to notA, ...
p += '%s' % OP([A.output(), notA.input()])
p += '%s' % OP([B.output(), notB.input()])
p += '%s' % OP([C.output(), notC.input()])

# Join inputs to AND gates
p += '%s' % OP([A.output(), and0.inputs()[2]])
p += '%s' % OP([A.output(), and1.inputs()[2]], shifts=[0.3])
p += '%s' % OP([A.output(), and2.inputs()[2]])
p += '%s' % OP([notB.output(), and2.inputs()[0]])

# Join AND gates to OR
p += '%s' % OP([and0.output(), or0.inputs()[0]])
p += '%s' % OP([and1.output(), or0.inputs()[1]])
p += '%s' % OP([and2.output(), or0.inputs()[2]])


# Join OR to z
p += '%s' % OP([or0.output(), Z.input()])

p += Grid(x0=-6, y0=-1, x1=9, y1=5)
print(p)

```


47.13 Example: SR latch

SR latch:



```

from latextool_basic import *
from latexcircuit import *
p = Plot()

NOR1 = NOR_GATE(x=0, y=3)
R = INPUT_POINT(gate=NOR1, input_index=1, label='$R$', input_length=1)
R0 = INPUT_POINT(gate=NOR1, input_index=0, input_length=1)
OUT1 = OUTPUT_POINT(gate=NOR1, output_length=1)
x,y = OUT1.output()
OUT11 = POINT(x=x+2, y=y, label='$Q$', anchor='west')

NOR2 = NOR_GATE(x=0, y=0)
S = INPUT_POINT(gate=NOR2, input_index=0, label='$S$', input_length=1)
S0 = INPUT_POINT(gate=NOR2, input_index=1, input_length=1)
OUT2 = OUTPUT_POINT(gate=NOR2, output_length=1)
x,y = OUT2.output()
OUT22 = POINT(x=x+2, y=y, label='$\overline{Q}$', anchor='west')

OP = OrthogonalPath

p += str(NOR1)
p += str(R)
p += str(R0)
p += str(OUT1); p += str(OUT11)

p += str(NOR2)
p += str(S)
p += str(S0)
p += str(OUT2); p += str(OUT22)

p += str(OP([OUT1.output(), OUT11.input()]))
p += str(OP([OUT2.output(), OUT22.input()]))


# Cross
x0,y0 = R0.input()
x1,y1 = OUT2.input()
p += Line(points=[(x0,y0),(x0,y0-1),(x1,y1+1),(x1,y1)])
p += str(POINT(x=x0,y=y0-1))
p += str(POINT(x=x1,y=y1+1))

x0,y0 = S0.input()
x1,y1 = OUT1.input()
p += Line(points=[(x0,y0),(x0,y0+1),(x1,y1-1),(x1,y1)])
p += str(POINT(x=x0,y=y0+1))
p += str(POINT(x=x1,y=y1-1))

print(p)

```

Test angle = $3.14159/4$:




```

from latextool_basic import *
from latexcircuit import *
p = Plot()

NOR1 = NOR_GATE(x=0, y=3, angle=3.14159/4)
R = INPUT_POINT(gate=NOR1, input_index=1, label='$R$', input_length=1)
R0 = INPUT_POINT(gate=NOR1, input_index=0, input_length=1)
OUT1 = OUTPUT_POINT(gate=NOR1, output_length=1)
x,y = OUT1.output()
OUT11 = POINT(x=x+2, y=y, label='$Q$', anchor='west')

NOR2 = NOR_GATE(x=0, y=0)
S = INPUT_POINT(gate=NOR2, input_index=0, label='$S$', input_length=1)
S0 = INPUT_POINT(gate=NOR2, input_index=1, input_length=1)
OUT2 = OUTPUT_POINT(gate=NOR2, output_length=1)
x,y = OUT2.output()
OUT22 = POINT(x=x+2, y=y, label='$\overline{Q}$', anchor='west')

OP = OrthogonalPath

p += str(NOR1)
p += str(R)
p += str(R0)
p += str(OUT1); p += str(OUT11)

p += str(NOR2)
p += str(S)
p += str(S0)
p += str(OUT2); p += str(OUT22)

p += str(OP([OUT1.output(), OUT11.input()]))
p += str(OP([OUT2.output(), OUT22.input()]))

# Cross
x0,y0 = R0.input()
x1,y1 = OUT2.input()
p += Line(points=[(x0,y0),(x0,y0-1),(x1,y1+1),(x1,y1)])
p += str(POINT(x=x0,y=y0-1))
p += str(POINT(x=x1,y=y1+1))


x0,y0 = S0.input()
x1,y1 = OUT1.input()
p += Line(points=[(x0,y0),(x0,y0+1),(x1,y1-1),(x1,y1)])
p += str(POINT(x=x0,y=y0+1))
p += str(POINT(x=x1,y=y1-1))

print(p)

```


47.14 layout function

SOP example:



```
from latextool_basic import *
from latexcircuit import *
p = Plot()
expr = [["a", "b"], ["a'", "b'"], ["a", "c"], ["a", "b'"]]
layout(p, expr, AND_GATE, OR_GATE)
print(p)
```

layout with scale and font for label:




```

from latextool_basic import *
from latexcircuit import *
p = Plot(scale=0.5)
expr = [["a", "b"], ["a'", "b'"], ["a", "c"], ["a", "b'"]]
layout(p, expr, AND_GATE, OR_GATE, font='footnotesize')
print(p)


```

POS example:




```
from latextool_basic import *
from latexcircuit import *
p = Plot()
expr = [["a", "b", "c"], ["a'", "b'", "c'"], ["a", "c"], ["a", "b'"]]
layout(p, expr, OR_GATE, AND_GATE)
print(p)
```

POS example:



```
from latextool_basic import *
from latexcircuit import *
p = Plot()
expr = [["a", "b", "c", "d"], ["a'", "b'", "c'", "d'"],
        ["a", "b"], ["a", "c"], ["b", "c"], ["c", "d"]]
layout(p, expr, OR_GATE, AND_GATE)
print(p)
```

POS example:



```
from latextool_basic import *
from latexcircuit import *
p = Plot()
expr = [
    ["A_1'", "A_0", "B_1'", "B_0"],
    ["A_1'", "A_0", "B_1", "B_0"],
    ["A_1", "A_0", "B_1'", "B_0"],
    ["A_1", "A_0", "B_1", "B_0"],
]
layout(p, expr, AND_GATE, OR_GATE)
print(p)
```

SOP example: PYTHON ERROR. See source, stderr, stdout below

```
from latextool_basic import console
from latexcircuit import SOP2
s = SOP("a'bcd + a'bc'd + abc'd + abcd")
print(s)
```

```
Traceback (most recent call last):
  File "myviytlb.tmp.py", line 3, in <module>
    s = SOP("a'bcd + a'bc'd + abc'd + abcd")
NameError: name 'SOP' is not defined
```


```
from latextool_basic import console
from latexcircuit import SOP2
s = SOP("a'bcd + a'bc'd + abc'd + abcd")
print(s)
```

47.15 Logic blocks

`points` argument is a dictionary.

`points[k]` is (label, coordinates). `label` is used to label the point in the block. `coordinate` is the coordinates of the point related to the block.

You can get the coordinates of a point by calling the `block.point(k)`.




```
from latextool_basic import *
from latexcircuit import *
p = Plot()
g = LOGIC_BLOCK(x=0, y=0, w=2, h=3, s='half adder',
                points={'s':('$s$', (2,2.5)),
                       'c':('$c$', (2,0.5)),
                       'x':('', (0,2.5)),
                       'y':('', (0,0.5))})

p += str(g)


x,y = g.point('x'); P0 = POINT(x=x-2, y=y, label='$x$', anchor='east')
p += str(OrthogonalPath([P0.output(), (x,y)]))

x,y = g.point('y'); P1 = POINT(x=x-2, y=y, label='$y$', anchor='east')
p += str(OrthogonalPath([P1.output(), (x,y)]))

x,y = g.point('s'); P2 = POINT(x=x+2, y=y, label='$s$', anchor='east')
p += str(OrthogonalPath([P2.output(), (x,y)]))

x,y = g.point('c'); P2 = POINT(x=x+2, y=y, label='$c$', anchor='east')
p += str(OrthogonalPath([P2.output(), (x,y)]))

p += Grid(-3, -1, 5, 4)
print(p)
```



```

from latextool_basic import *
from latexcircuit import *
p = Plot()
g = LOGIC_BLOCK(x=0, y=0, w=2, h=3, s='half adder',
                points={'s':('$s$', (2,2.5)),
                        'c':('$c$', (2,0.5)),
                        'x':(' ', (0,2.5)),
                        'y':(' ', (0,0.5))})

p += str(g)

x,y = g.point('x'); P0 = POINT(x=x-2, y=y, label='$x$', anchor='east')
p += str(OrthogonalPath([P0.output(), (x,y)]))

x,y = g.point('y'); P1 = POINT(x=x-2, y=y, label='$y$', anchor='east')
p += str(OrthogonalPath([P1.output(), (x,y)]))

x,y = g.point('s'); P2 = POINT(x=x+2, y=y, label='$s$', anchor='east')
p += str(OrthogonalPath([P2.output(), (x,y)]))


x,y = g.point('c'); P2 = POINT(x=x+2, y=y, label='$c$', anchor='east')
p += str(OrthogonalPath([P2.output(), (x,y)]))

p += '%s' % LOGIC_BLOCK(x=6, y=1, h=3, s='half adder',
                        points={'s':('$s$', (2,2.5)),
                                'c':('$c$', (2,0.5)),
                                'x':(' ', (0,2.5)),
                                'y':(' ', (0,0.5))})


p += Grid(-3, -1, 5, 4)
print(p)

```

47.16 Logic blocks: full adder



47.17 Two NOTs



```

from latextool_basic import *
from latexcircuit import *
p = Plot()

g0 = NOT_GATE(x=0, y=0)
x,y = g0.output()
g1 = NOT_GATE(x=2, y=y)

p += str(g0)
p += str(g1)

p += Line(points=[g0.output(), g1.input()], label="$Q'$", anchor='below')

x0, y0 = g1.output()
x5, y5 = g0.input()

dx = 0.25
dy = 0.75

x1, y1 = x0+dx, y0
x2, y2 = x1, y1+dy
x4, y4 = x5-dx, y5
x3, y3 = x4, y2
p += Line(points=[(x0, y0),
                  (x1, y1),
                  (x2, y2),
                  (x3, y3),
                  (x4, y4),
                  (x5, y5)])
X = POINT(x=x1, y=y1, r=0, label='$Q$', anchor='west')
p += str(X)
print(p)

```

48 Data structures

debug:
singlylinkedli

48.1 Singly Linked List

```
from latextool_basic import *
p = Plot()


SLLNode = SinglyLinkedListNode

n5 = SLLNode(x=0, y=0, label=5)
p += n5

n6 = SLLNode(x=5, y=0, label=6, next=None)
p += n6

p += Pointer(points = [n5[1].center(), n6[0].left()])

print(p)
```



```

from latextool_basic import *
p = Plot()

DLLNode = DoublyLinkedListNode


n5 = DLLNode(x=0, y=0, prev=None, label=5)
p += n5

n6 = DLLNode(x=5, y=0, label=6, next=None)
p += n6

p += Pointer(points = [n5[2].center(), n6[0].left()])

p0 = n6[0].center()
p1 = n5[1].top()
p2 = p0[0], p0[1] + 0.5
p3 = p1[0], p2[1]
p += Pointer(points = [p0, p2, p3, p1])
print(p)

```



debug:
doublylinkedl

48.2 Doubly linked list

```

from latextool_basic import *
class DLNodeRect:
    L = 0.05 # linewidth
    def __init__(self, x0=0, y0=0, w=0, h=0, label='',
                  prev=None, next=None):
        L = DLNodeRect.L
        self.x0, self.y0 = x0, y0
        self.w, self.h = w, h
        self.label = label
        self.prev, self.next = prev, next
        c = RectContainer(x0=x0, y0=y0)
        c += Rect2(x0=0, y0=0, x1=w, y1=h, linewidth=L, label='')
        c += Rect2(x0=0, y0=0, x1=w, y1=h, linewidth=L, label=label)
        c += Rect2(x0=0, y0=0, x1=w, y1=h, linewidth=L, label='')
        self.c = c
    def next_rect(self): return self.c[2]
    def key_rect(self): return self.c[1]
    def prev_rect(self): return self.c[0]
    def __str__(self):
        L = DLNode.L
        s = str(self.c)
        if self.next != None:
            a = self.next_rect().center()
            b = self.next.prev_rect().left()
            s += line(points=[a, b], linewidth=L,
                      endstyle='->', startstyle='dot', arrowstyle='triangle
')
        else: # self.next is None
            r = self.next_rect()
            s += line(points=[r.topleft(), r.bottomright()], linewidth=L)
            s += line(points=[r.topright(), r.bottomleft()], linewidth=L)
        if self.prev != None:
            a = self.prev_rect().center()
            b = self.prev.key_rect().bottom()
            c = a[0], a[1] - 1
            d = b[0], c[1]
            s += line(points=[a, c, d, b], linewidth=L,
                      endstyle='->', startstyle='dot', arrowstyle='triangle
')
        else: # self.prev is None
            r = self.prev_rect()
            s += line(points=[r.topleft(), r.bottomright()], linewidth=L)
            s += line(points=[r.topright(), r.bottomleft()], linewidth=L)
        return s

class DLNode:
    def __init__(self, key, prev=None, next=None):
        self.key = key
        self.prev, self.next = prev, next
    def __str__(self):
        return "<DLNode: %s, %s, %s>" % (self.prev, self.key, self.next)

c = DLNode(x0=1, y0=1, w=1, h=1, label=r'\texttt{0}')
d = DLNode(x0=5, y0=1, w=1, h=1, label=r'\texttt{1}')
e = DLNode(x0=9, y0=1, w=1, h=1, label=r'\texttt{2}')
c.next = d; d.prev = c; d.next = e; e.prev = d

p = Plot()
p += str(c); p += str(d); p += str(e)
print(p)

```

PYTHON ERROR. See source, stderr, stdout below

```

from latextool_basic import *
class DLNodeRect:
    L = 0.05 # linewidth
    def __init__(self, x0=0, y0=0, w=0, h=0, label='',
                  prev=None, next=None):
        L = DLNodeRect.L
        self.x0, self.y0 = x0, y0
        self.w, self.h = w, h
        self.label = label
        self.prev, self.next = prev, next
        c = RectContainer(x0=x0, y0=y0)
        c += Rect2(x0=0, y0=0, x1=w, y1=h, linewidth=L, label='')
        c += Rect2(x0=0, y0=0, x1=w, y1=h, linewidth=L, label=label)
        c += Rect2(x0=0, y0=0, x1=w, y1=h, linewidth=L, label='')
        self.c = c
    def next_rect(self): return self.c[2]
    def key_rect(self): return self.c[1]
    def prev_rect(self): return self.c[0]
    def __str__(self):
        L = DLNode.L
        s = str(self.c)
        if self.next != None:
            a = self.next_rect().center()
            b = self.next.prev_rect().left()
            s += line(points=[a, b], linewidth=L,
                      endstyle='->', startstyle='dot', arrowstyle='triangle
')
        else: # self.next is None
            r = self.next_rect()
            s += line(points=[r.topleft(), r.bottomright()], linewidth=L)
            s += line(points=[r.topright(), r.bottomleft()], linewidth=L)
        if self.prev != None:
            a = self.prev_rect().center()
            b = self.prev.key_rect().bottom()
            c = a[0], a[1] - 1
            d = b[0], c[1]
            s += line(points=[a, c, d, b], linewidth=L,
                      endstyle='->', startstyle='dot', arrowstyle='triangle
')
        else: # self.prev is None
            r = self.prev_rect()
            s += line(points=[r.topleft(), r.bottomright()], linewidth=L)
            s += line(points=[r.topright(), r.bottomleft()], linewidth=L)
        return s

class DLNode:
    def __init__(self, key, prev=None, next=None):
        self.key = key
        self.prev, self.next = prev, next
    def __str__(self):
        return "<DLNode: %s, %s, %s>" % (self.prev, self.key, self.next)

c = DLNode(x0=1, y0=1, w=1, h=1, label=r'\texttt{0}')
d = DLNode(x0=5, y0=1, w=1, h=1, label=r'\texttt{1}')
e = DLNode(x0=9, y0=1, w=1, h=1, label=r'\texttt{2}')
c.next = d; d.prev = c; d.next = e; e.prev = d


p = Plot()
p += str(c); p += str(d); p += str(e)
print(p)

```

```
Traceback (most recent call last):
  File "arwyorcf.tmp.py", line 51, in <module>
    c = DLNode(x0=1, y0=1, w=1, h=1, label=r'\texttt 0}')
TypeError: __init__() got an unexpected keyword argument 'x0'
```


48.3 Stack

```
from latextool_basic import *  
p = Plot()  
drawstack(p,  
    xs=['a', 'b'],  
    )  
p += Grid(-1, -3, 2, 1)  
print(p)
```




Extra height for container:

```
from latextool_basic import *
p = Plot()
drawstack(p,
  xs=['a', 'b'],
  extra_h=0.5
)
p += Grid(-1, -3, 2, 1)
print(p)
```




Minimum number of values:

```
from latextool_basic import *  
p = Plot()  
drawstack(p,  
  xs=['a', 'b'],  
  min_size=4  
)  
p += Grid(-1, -3, 2, 1)  
print(p)
```




Position:

```
from latextool_basic import *
p = Plot()
drawstack(p,
  x=2, y=0,
  xs=['a', 'b'],
)
p += Grid(-1, -3, 3, 1)
print(p)
```




Width and height:

```
from latextool_basic import *  
p = Plot()  
drawstack(p,  
    w=2, h=1,  
    xs=['a', 'b'],  
    )  
p += Grid(-1, -3, 3, 1)  
print(p)
```



Distance of walls to values:


```
from latextool_basic import *
p = Plot()
drawstack(p,
  xs=['a', 'b'],
  sep=0.5,
)
p += Grid(-1, -3, 2, 1)
print(p)
```



To make bottom right of container at (0,0):

```
from latextool_basic import *
p = Plot()

sep = 0.1
w = 1; h = 0.6
x = sep; y = sep + 4*h
drawstack(p,
  x=x, y=y, w=w, h=h, extra_h=0.5,
  xs=['a', 'b'],
  sep=sep,
)
p += Grid(-1, -1, 2, 3)
print(p)
```



Return value is a RectContainer:

```
from latextool_basic import *
p = Plot()


r0 = drawstack(p,
    x=0, y=0,
    xs=['a', 'b'],
    min_size=4
)
x0,y0 = r0[2].right()
x1,y1 = x0 + 1, y0
p += Line(points=[(x0,y0),(x1,y1)])
p += Rect(x0=x1+0.5,y0=y0,x1=x1+0.5,y1=y0,label='top', linewidth=0)

x0,y0 = r0[1].top(); y0 + 0.5
x1,y1 = x0,y0+1
p += Rect(x0=x1, y0=y1, x1=x1,y1=y1,label='push z', linewidth=0)

y1 -= 0.5
p += Line(points=[(x1,y1),(x0,y0)], endstyle='>')

r1 = drawstack(p,
    x=5, y=0,
    xs=['z', 'a', 'b'],
    min_size=4
)
x0,y0 = r1[1].right()
x1,y1 = x0 + 1, y0
p += Line(points=[(x0,y0),(x1,y1)])
p += Rect(x0=x1+0.5,y0=y0,x1=x1+0.5,y1=y0,label='top', linewidth=0)

print(p)
```



48.4 Adjacency list

Even number of linked lists:

```
from latextool_basic import *
p = Plot()

r, crosses, nodes, lines = adjlist(xs=[[0],[4,5],[1,2,3],[1,4], [5],[7,7,7]
],
                                nodevspace=0.5, nodehspace=0.7,
                                nodewidth=1, nodeheight=0.8)


p += r

for k,v in crosses.items():
    for _ in v: p += _

for k,v in nodes.items():
    for _ in v: p += _

for k,v in lines.items():
    for _ in v: p += _

print(p)
```



```

from latextool_basic import *
p = Plot()

r, crosses, nodes, lines = adjlist(xs=[[0],[4,5],[1,2,3],[1,4], [5],[7,7,7]
],
                                nodevspace=0.5, nodehspace=0.3,
                                nodewidth=0.7, nodeheight=0.4)

p += r


for k,v in crosses.items():
    for _ in v: p += _

for k,v in nodes.items():
    for _ in v: p += _

for k,v in lines.items():
    for _ in v: p += _

print(p)

```




```
from latextool_basic import *
p = Plot()

r, crosses, nodes, lines = adjlist(xs=[[1,2,3],[1,4],],
                                   nodevspace=0.2, nodehspace=0.3,
                                   nodewidth=1, nodeheight=1)


p += r

for k,v in crosses.items():
    for _ in v: p += _

for k,v in nodes.items():
    for _ in v: p += _

for k,v in lines.items():
    for _ in v: p += _

print(p)
```



```

from latextool_basic import *
p = Plot()

r, crosses, nodes, lines = adjlist(xs=[[0],[4,5],[], [1,4], [5],[]])
p += r

r0 = r[1] # redraw r[1] with 'blue!20'
r0.background = 'blue!20'
r0.linecolor = 'blue'
p += r0

for k,v in crosses.items():
    for _ in v: p += _

for k,v in nodes.items():
    for _ in v: p += _


# redraw nodes[1]
for _ in nodes[1]:
    _[0].background = 'blue!20'
    _[0].linecolor = 'blue'
    p += _[0]

for k,v in lines.items():
    for _ in v: p += _

# redraw lines[1]
for _ in lines[1]:
    _.linecolor = 'blue'
    p += _

print(p)

```



Test odd number of pointers

```


from latextool_basic import *
p = Plot()

r, crosses, nodes, lines = adjlist(xs=[[0,5,4]],
                                   nodevspace=0.2, nodehspace=0.3,
                                   nodewidth=1, nodeheight=1)

p += r
for k,v in crosses.items():
    for _ in v: p += _
for k,v in nodes.items():
    for _ in v: p += _
for k,v in lines.items():
    for _ in v: p += _

print(p)

```



```


from latextool_basic import *
p = Plot()

r, crosses, nodes, lines = adjlist(xs=[[0,5,4],[1,2,3],[1,2,3]],
                                   nodevspace=0.2, nodehspace=0.3,
                                   nodewidth=1, nodeheight=1)

p += r
for k,v in crosses.items():
    for _ in v: p += _
for k,v in nodes.items():
    for _ in v: p += _
for k,v in lines.items():
    for _ in v: p += _

print(p)

```



```


from latextool_basic import *
p = Plot()

r, crosses, nodes, lines = adjlist(xs=[[0,5,4]],
                                   nodevspace=0.2, nodehspace=0.3,
                                   nodewidth=1, nodeheight=2)

p += r
for k,v in crosses.items():
    for _ in v: p += _
for k,v in nodes.items():
    for _ in v: p += _
for k,v in lines.items():
    for _ in v: p += _

print(p)

```



```

from latextool_basic import *
p = Plot()

r, crosses, nodes, lines = adjlist(xs=[[0,5,4]],
                                   nodevspace=0.2, nodehspace=0.3,
                                   nodewidth=1, nodeheight=1)

)
p += r
for k,v in crosses.items():
    for _ in v: p += _
for k,v in nodes.items():
    for _ in v: p += _
for k,v in lines.items():
    for _ in v: p += _

print(p)

```


```

from latextool_basic import *
p = Plot()

r, crosses, nodes, lines = adjlist(xs=[[0,5,4],[4,5,3,4],[1, 2, 3], [1,4,2]
, [5,7,6]])
p += r
for k,v in crosses.items():
    for _ in v: p += _
for k,v in nodes.items():
    for _ in v: p += _
for k,v in lines.items():
    for _ in v: p += _

print(p)

```




48.5 Heap file

```
from latextool_basic import *
p = Plot()

nrows = 5
ncols = 20
slots = [(0,12)]

heapfilepage(p, nrows, ncols, slots)
print(p)
```




```
from latextool_basic import *
p = Plot()

nrows = 5
ncols = 20
slots = [(0, 12), (12, 11), (23, 10)]

heapfilepage(p, nrows, ncols, slots)
print(p)
```

record space



```
from latextool_basic import *
```

```
p = Plot()
```

```
nrows = 5
```


```
ncols = 20
```

```
slots = [(0,12), (12,5), (17,5), (22,5), (27,5), (32,5), (37,5)]
```

```
heapfilepage(p, nrows, ncols, slots)
```

```
print(p)
```

record space




Test with holes:

```
from latextool_basic import *
p = Plot()

nrows = 5
ncols = 20
slots = [(0,12), (15, 7)]

heapfilepage(p, nrows, ncols, slots)
print(p)
```

record space




free_offset:

```
from latextool_basic import *
p = Plot()

nrows = 5
ncols = 20
slots = [(0,12), (15, 7)]
free_offset = 30

heapfilepage(p, nrows, ncols, slots, free_offset)
print(p)
```

record space




deleted records:

```
from latextool_basic import *
p = Plot()

nrows = 5
ncols = 20
slots = [(0,12), (15, 7), (-1, 5), (30, 6), (-1, 3), (42, 10)]

heapfilepage(p, nrows, ncols, slots)
print(p)
```

record space




deleted records:

```
from latextool_basic import *
p = Plot()

nrows = 5
ncols = 20
slots = [(0,12), (15, 7), (-1, 5), (30, 6), (-1, 3), (42, 10)]

heapfilepage(p, nrows, ncols, slots)
print(p)
```

record space



49 B+ tree

49.1 Node

```
from latextool_basic import *
p = Plot()

widths= [0.15, 0.4]; height = 0.4

def f(M):
    return [r'{{\scriptsize\texttt{%s}}}' % _ for _ in M]

M0 = f([5, 10])

Y = 0
N0 = bpt_node(x=4.5, y=Y, M=M0, widths=widths, height=height)

p += N0
print(p)
```

5	10
---	----

Key width:

```
from latextool_basic import *
p = Plot()

widths= [0.15, 2]; height = 0.4

def f(M):
    return [r'\scriptsize\texttt{%s}'] % _ for _ in M]

M0 = f([5, 10])

Y = 0
N0 = bpt_node(x=4.5, y=Y, M=M0, widths=widths, height=height)

p += N0
print(p)
```

5	10
---	----

49.2 Directed edge

```

from latextool_basic import *
p = Plot()
widths= [0.15, 0.4]; height = 0.4

def f(M):
    return [r'{{\scriptsize\texttt{%s}}}' % _ for _ in M]

M0, M1, M2, M3 = f([5, 10]), f([0, 1]), f([5, 6]), f([7, 8])


N0 = bpt_node(x=4.5, y=0, M=M0, widths=widths, height=height)
N1 = bpt_node(x=0, y=-2, M=M1, widths=widths, height=height)
N2 = bpt_node(x=5, y=-2, M=M2, widths=widths, height=height)
N3 = bpt_node(x=10, y=-2, M=M3, widths=widths, height=height)

arc0 = bpt_arc(N0, N1, 0);
arc1 = bpt_arc(N0, N2, 1, linecolor='red')
arc2 = bpt_arc(N0, N3, 2, linecolor='blue')

p += N0; p += N1; p += N2; p += N3
p += arc0; p += arc1; p += arc2

print(p)

```



Changing height of the bend.

```
from latextool_basic import *
p = Plot()
widths= [0.15, 0.4]; height = 0.4

def f(M):
    return [r'\scriptsize\texttt{%s}'] % _ for _ in M]


M0, M1, M2, M3 = f([5, 10]), f([0, 1]), f([5, 6]), f([7, 8])

N0 = bpt_node(x=4.5, y=0, M=M0, widths=widths, height=height)
N1 = bpt_node(x=0, y=-2, M=M1, widths=widths, height=height)
N2 = bpt_node(x=5, y=-2, M=M2, widths=widths, height=height)
N3 = bpt_node(x=10, y=-2, M=M3, widths=widths, height=height)

arc0 = bpt_arc(N0, N1, 0);
arc1 = bpt_arc(N0, N2, 1, linecolor='red', delta=0.2)
arc2 = bpt_arc(N0, N3, 2, linecolor='blue', delta=0.4)

p += N0; p += N1; p += N2; p += N3
p += arc0; p += arc1; p += arc2

print(p)
```



Labels

```

from latextool_basic import *
p = Plot()
widths= [0.15, 0.4]; height = 0.4

def f(M):
    return [r'{{\scriptsize\texttt{\%s}}}' % _ for _ in M]

M0 = f([5, 10]); M1 = f([0, 1]); M2 = f([5, 6])

Y = 0
N0 = bpt_node(x=4.5, y=Y, M=M0, widths=widths, height=height)

Y = -2
N1 = bpt_node(x=0, y=Y, M=M1, widths=widths, height=height)
N2 = bpt_node(x=5, y=Y, M=M2, widths=widths, height=height)

arc0 = bpt_arc(N0, N1, 0); arc1 = bpt_arc(N0, N2, 1, linecolor='red')


p += N0; p += N1; p += N2
p += arc0; p += arc1

from latexcircuit import *
x,y = arc0.midpoint()
p += Circle(x=x, y=y, r=0.05, background='red')
X = POINT(x=x, y=y, label='${-\infty,5}$', anchor='south')
p += str(X)

x,y = arc1.midpoint(ratio=0.7)
p += Circle(x=x, y=y, r=0.05, background='blue')
X = POINT(x=x, y=y, label='${5,10}$', anchor='west')
p += str(X)

print(p)

```



```

from latextool_basic import *
from latexcircuit import *

def f(M): return tuple(r'{{\scriptsize\texttt{\%s}}}' % _ for _ in M)

```



```

p = Plot()
widths = [0.1, 0.4]
height = 0.4
node_sep = 0.1
vsep = 1.5 # vertical separation -- from bottom of root to top of child

keyss = [(10, 30, 65, 80), (1, 5, 7, 9), (10, 14, 15, 28), (35, 42, 45, 57),
          (68, 72, 75, 79), (80, 89, 90, 92)]
Ms = [f(keys) for keys in keyss]

Y = -(height + vsep)
children = bptree_get_siblings(0, Y, Ms[1:], widths, height, node_sep)
root = bptree_get_root(0, keyss[0], children, widths, height)

for _ in [root] + children: p += _

arcs = bptree_get_arcs(root, children, vsep, height)
for _ in arcs: p += _

labels = bptree_get_labels(keyss, arcs)
for label in labels:
    p += label

"""
      A
    B  C  D  E
   H I    F G
      J K
"""
edges = {'A': ['B', 'C', 'D', 'E'],
         'D': ['F', 'G'],
         'B': ['H', 'I'],
         'G': ['J', 'K'],
         }
nodes = {'A': f([0,1,2,3]),
         'B': f([4,'',' ','']),
         'C': f([8,9,10,11]),
         'D': f([12,'',' ','']),
         'E': f([16,17,18,19]),
         'F': f([20,21,22,23]),

```

```
        'G':f([24,24,24,'']),
        'H':f([28,29,30,31]),
        'I':f([32,33,34,35]),
        'J':f([36,37,38,39]),
        'K':f([40,41,42,43]),
    }
bptree(p, edges=edges, nodes=nodes)

print(p)
```

Width is 0 for pointers:

```

from latextool_basic import *
p = Plot()

widths= [0, 0.4]
height = 0.4

def f(M):
    return [r'\scriptsize\texttt{%s}'] % _ for _ in M]

M0 = f([5, 10, 17, 22])
M1 = f([0, 1, 3, 4])
M2 = f([6, 7, 8, 9])
M3 = f([12, 13, 14, 15])
M4 = f([17, 18, 19, 20])
M5 = f([22, 30, 50, 60])


N0 = bpt_node(x=5, y=0, M=M0, widths=widths, height=height)

N1 = bpt_node(x=0, y=-2, M=M1, widths=widths, height=height)
N2 = bpt_node(x=2.5, y=-2, M=M2, widths=widths, height=height)
N3 = bpt_node(x=5, y=-2, M=M3, widths=widths, height=height)
N4 = bpt_node(x=7.5, y=-2, M=M4, widths=widths, height=height)
N5 = bpt_node(x=10, y=-2, M=M5, widths=widths, height=height)
p += N0; p += N1; p += N2; p += N3; p += N4; p += N5

p += bpt_arc(N0, N1, 0, delta=0.2, r=0)
p += bpt_arc(N0, N2, 1, r=0)
p += bpt_arc(N0, N3, 2, r=0)
p += bpt_arc(N0, N4, 3, r=0)
p += bpt_arc(N0, N5, 4, delta=0.2, r=0)

print(p)

```



Width for keys is 0. Might be easier to read (when width of pointer is 0) if the linewidth of rects is thicker:

```
from latextool_basic import *
p = Plot()

widths= [0, 0.4]
height = 0.4

def f(M):
    return [r'\scriptsize\texttt{%s}'] % _ for _ in M]


M0,M1,M2,M3,M4,M5 = (f([5, 10, 17, 22]), f([0, 1, 3, 4]), f([6, 7, 8, 9]),
                    f([12, 13, 14, 15]), f([17, 18, 19, 20]), f([22, 30, 50, 60]))

def bpt_node_(x, y, M):
    return bpt_node(x=x, y=y, M=M, widths=widths, height=height,
                    linewidth=0.04)

N0 = bpt_node_(x=5, y=0, M=M0)
N1 = bpt_node_(x=0, y=-2, M=M1)
N2 = bpt_node_(x=2.5, y=-2, M=M2)
N3 = bpt_node_(x=5, y=-2, M=M3)
N4 = bpt_node_(x=7.5, y=-2, M=M4)
N5 = bpt_node_(x=10, y=-2, M=M5)
p += N0; p += N1; p += N2; p += N3; p += N4; p += N5

p += bpt_arc(N0, N1, 0, delta=0.2, r=0)
p += bpt_arc(N0, N2, 1, r=0)
p += bpt_arc(N0, N3, 2, r=0)
p += bpt_arc(N0, N4, 3, r=0)
p += bpt_arc(N0, N5, 4, delta=0.2, r=0)

print(p)
```




debug: interv

50 Intervals

For interval scheduling problems.


```
from latextool_basic import *
p = Plot()

intervals(p,
    dy=0.8,
    axislength=10,
    xss=[[0, 4.25, '$I_1$'), (4.75, 9, '$I_2$', 'red')],
        [(4, 5, '$I_0$')]],
)
print(p)
```




51 Automatas

```
from latextool_basic import *  
p = Plot()  
  
dfa(p)  
print(p)
```



51.1 State


```
from latextool_basic import *  
p = Plot()  
  
dfa(p,  
    state=r'$q_5$')  
print(p)
```



51.2 Tape and head

```
from latextool_basic import *
p = Plot()


dfa(p,
    tape=['a','b','a','a',r'\SPACE',r'\SPACE',r'\SPACE'],
    head_index=3,
)
print(p)
```



51.3 Label for tape

```
from latextool_basic import *
p = Plot()


dfa(p,
    tape=['a','b','a','a',r'\SPACE',r'\SPACE',r'\SPACE'],
    input_tape_str=True,
)
print(p)
```



51.4 Position

```
from latextool_basic import *
p = Plot()

dfa(p, x0=0, y0=0,
    tape=['a', 'b'],
)
dfa(p, x0=5, y0=0,
    tape=['c', 'd'],
)
p += Grid(x0=-1, y0=-4, x1=10, y1=1)
print(p)
```




Bounding rect

The return value of `dfa` is a Rectangle object.


```
from latextool_basic import *
p = Plot()

r = dfa(p, tape=['' for i in range(10)],)
x0,y0 = r.bottomleft()
x1,y1 = r.topright()
p += Rect(x0=x0,y0=y0,x1=x1,y1=y1,linecolor='red')
print(p)
```




```
from latextool_basic import *
p = Plot()

r = dfa(p, tape=[''])
x0,y0 = r.bottomleft()
x1,y1 = r.topright()
p += Rect(x0=x0,y0=y0,x1=x1,y1=y1,linecolor='red')
print(p)
```



Dimensions of automata:


```
from latextool_basic import *  
p = Plot()  
  
r = dfa(p,  
    body_w = 1.5,  
    body_h = 1,  
    )  
print(p)
```



Cell width and height


```
from latextool_basic import *
p = Plot()

dfa(p,
    tape=['',' ',''],
    w=2, h=1,
)
print(p)
```



51.5 Body-tape distance

```
from latextool_basic import *  
p = Plot()  
  
dfa(p, vsep=5)  
print(p)
```




51.6 No drawing

No drawing (just to compute bounding rect):

```
from latextool_basic import *
p = Plot()

r = dfa(p, no_draw=True)
x0,y0 = r.bottomleft()
x1,y1 = r.topright()
p += Rect(x0=x0, y0=y0, x1=x1, y1=y1, linecolor='red')
print(p)
```



51.7 Sequence of automatas


```

from latextool_basic import *
p = Plot()

def rect(index, p, x0, y0, no_draw=False):
    data = [(r'$q_0$',
             ['0', 'b', 'a', 'a'],
             0),
             (r'$q_1$',
              ['1', 'b', 'a', 'a', r'\SPACE', r'\SPACE', r'\SPACE'],
              1),
             (r'$q_2$',
              ['2', 'b', 'a', 'a', r'\SPACE', r'\SPACE', r'\SPACE'],
              2),
             (r'$q_3$',
              ['3', 'b', 'a', 'a', r'\SPACE', r'\SPACE', r'\SPACE'],
              3),
             (r'$q_4$',
              ['4', 'b', 'a', 'a', r'\SPACE', r'\SPACE', r'\SPACE'],
              2),
             (r'$q_5$',
              ['5', 'b', 'a', 'a', r'\SPACE', r'\SPACE', r'\SPACE'],
              2),
             (r'$q_6$',
              ['6', 'b', 'a', 'a', r'\SPACE', r'\SPACE', r'\SPACE'],
              2),
             (r'$q_7$',
              ['7', 'b', 'a', 'a', r'\SPACE', r'\SPACE', r'\SPACE'],
              2),
            ]
    if index < len(data):
        state, tape, head_index = data[index]
        return dfa(p,
                    x0=x0, y0=y0,
                    tape=tape,
                    state=state,
                    head_index=head_index,
                    vsep=0.5, hsep=0.25,
                    body_w=1, body_h=0.7, w=0.4,
                    no_draw=no_draw,
                    )
    else:
        return None

sequence(p, rect=rect)
print(p)

```

debug: pda.t

51.8 PDA




```

from latextool_basic import *
p = Plot()

pda(p,
    stackvalues = ['a','\$',],
    tape = ['a','b','a','a',r'\SPACE',r'\SPACE',r'\SPACE'],
    state = r'$q_0$',
    head_index = 0,
    body_w = 3,
    body_h = 2,
    vsep = 1,
    hsep = 1,
    input_tape_str=True,
    stack_str=True,
)
print(p)

```

input tape



stack

51.9 PDA: bounding rect


```

from latextool_basic import *
p = Plot()

r = pda(p,
    stackvalues = ['a','$'],
    tape = ['a','b','a','a',r'\SPACE',r'\SPACE',r'\SPACE'],
    state = r'$q_0$',
    head_index = 0,
    body_w = 3,
    body_h = 2,
    vsep = 1,
    hsep = 1,
    input_tape_str=True,
    stack_str=True,
)
x0,y0 = r.bottomleft()
x1,y1 = r.topright()
p += Rect(x0=x0,y0=y0,x1=x1,y1=y1,linecolor='red')
print(p)

```

input tape



51.10 Sequence of PDA

```


from latextool_basic import *
p = Plot()

def rect(index, p, x0, y0, no_draw=False):
    data = [(r'$q_0$',
              ['a','b','a','a',r'\SPACE',r'\SPACE',r'\SPACE'],
              0,
              []),
             (r'$q_1$',
              ['a','b','a','a',r'\SPACE',r'\SPACE',r'\SPACE'],
              1,
              ['a',]), # 'b','c','d','e', r'\$']),
             (r'$q_2$',
              ['a','b','a','a',r'\SPACE',r'\SPACE',r'\SPACE'],
              2,
              ['a', r'\$']),
             (r'$q_3$',
              ['a','b','a','a',r'\SPACE',r'\SPACE',r'\SPACE'],
              3,
              ['b', 'a', r'\$']),
             (r'$q_2$',
              ['a','b','a','a',r'\SPACE',r'\SPACE',r'\SPACE'],
              2,
              ['a', r'\$']),
             (r'$q_2$',
              ['a','b','a','a',r'\SPACE',r'\SPACE',r'\SPACE'],
              2,
              [r'\$']),
             (r'$q_2$',
              ['a','b','a','a',r'\SPACE',r'\SPACE',r'\SPACE'],
              2,
              [r'\$']),
             (r'$q_2$',
              ['a','b','a','a',r'\SPACE',r'\SPACE',r'\SPACE'],
              2,
              [r'\$']),
             (r'$q_2$',
              ['a','b','a','a',r'\SPACE',r'\SPACE',r'\SPACE'],
              2,
              [r'\$']),
             ]

    if index < len(data):
        state, tape, head_index, stackvalues = data[index]
        return pda(p,
                    x0=x0,y0=y0,
                    stackvalues = stackvalues,
                    tape= tape,
                    state = state,
                    head_index = head_index,
                    vsep=0.5, hsep=0.25,
                    body_w=1, body_h=0.7, w=0.4,
                    no_draw=no_draw,
                    )
    else:
        return None

sequence(p, rect=rect)

```



51.11 CYK

```
from latextool_basic import *
m = [['?', '$A$', '$B$', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      []]
p = Plot()
cyk(p, m)
print(p)
```

		i					
j		1	2	3	4	5	6
	1	?	A	B			
	2						
	3						
	4						
	5						
	6						

51.11.1 Word being parsed

```
from latextool_basic import *
m = [['?', '$A$', '$B$', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      []]
p = Plot()
cyk(p, m, w='baaaab')
print(p)
```


$i \backslash j$	b	a	a	a	a	b
	1	2	3	4	5	6
1	?	A	B			
2						
3						
4						
5						
6						

51.11.2 Background

You can set the background using the (row, col) index values. If it's set, the cell is also drawn with a larger linewidth.

```
from latextool_basic import *
m = [['?', '$A$', '$B$', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      ['', '', '', '', '', ''],
      []]
p = Plot()
cyk(p, m, background={(0,0):'blue!10',
                      (0,1):'red!10',})
print(p)
```

$i \backslash j$	1	2	3	4	5	6
1	?	A	B			
2						
3						
4						
5						
6						

51.11.3 Height and width

52 Automata

The `automata` function (in the `latextool_basic` module) spits out latex code for state diagrams which can then be modified by hand.

Here are some examples.

If you execute the following python code:

```
print(automata(layout="""
A
""",
A="initial|label=$q'_0$",
))
```

you will get this latex code as output:

```
\begin{center}
\begin{tikzpicture}[shorten >=1pt,node distance=2cm,auto,initial text=]
\node[state,initial] (A) at ( 4, 0) {$q'_0$};

\path[->]

;
\end{tikzpicture}
\end{center}
```


When you paste the above output into a latex document, you will get this picture:



The `layout` parameter is a string for placing the nodes. When you execute this:

```
from latextool_basic import *
automata(layout="""
A B   C
D
E   F
""",
)
```


you get this output:



You can then put decorate each node.

```
from latextool_basic import *
print(automata(layout="""
A B   C
D
E   F
""",
A = "initial|label=$q_0$",
B = "label=$q_1$",
C = "accept|label=$q_2$"
))
```

gives this picture




For the rest of the examples, I will just give you the python code and the corresponding picture.

DFA for “starts with 0 and has odd length”:

```

from latextool_basic import *
print(automata(layout="""
A D B C
""",
edges="A,$0$,B|B,$0,1$,C|C,$0,1$,B|A,$1$,D|D,$0,1$,D",
A="initial|label=$q'_0$",
B="accept|label=$q'_2$",
C="label=$q'_3$",
D="label=$q'_1$",
))

```



Sipser 1.7c


Sipser 1.7d

Sipser 1.7e

```

from latextool_basic import *
print(automata(layout="""
A B C
""",
edges="A,$\epsilon$,B|A,$0$,A|B,$1$,B|B,$0$,C|C,$0$,C",
A="initial|label=$q_0$",
B="label=$q_1$",
C="label=$q_2$",
))

```




NFA for at least three 1s:

```

from latextool_basic import *
print(automata(layout="""
A B C D
""",
edges="A,1,B|B,1,C|C,1,D|A,$0,1$,A|D,$0,1$,D|B,0,B|C,0,C",
A="initial|label=$q'_0$",
B="label=$q'_1$",
C="label=$q'_2$",
D="accept|label=$q'_3$",
))

```



NFA for \emptyset :

```

from latextool_basic import *
print(automata(layout="""
A
""",
A="initial|label=$q''_0$",
))

```




NFA for concat of “contains at least 3 1s” and \emptyset :

```


from latextool_basic import *
print(automata(layout="""
A B C D   E
""",
edges="A,1,B|B,1,C|C,1,D|A,$0,1$,A|D,$0,1$,D|B,0,B|C,0,C|D,$\epsilon$,E",
A="initial|label=$q'_0$",
B="label=$q'_1$",
C="label=$q'_2$",
D="label=$q'_3$",
E="label=$q''_0$",
))

```




NFA for concat of “length ≤ 5 ” and “every odd position is a 1”:

```
from latextool_basic import *
print(automata(layout="""
A B C D E F
""",
edges="A,$0,1$,B|B,$0,1$,C|C,$0,1$,D|D,$0,1$,E|E,$0,1$,F",
A="accept|initial|label=$q'_0$",
B="accept|label=$q'_1$",
C="accept|label=$q'_2$",
D="accept|label=$q'_3$",
E="accept|label=$q'_4$",
F="accept|label=$q'_5$",
))
```



NFA for “every odd position is a 1”:

```
from latextool_basic import *
print(automata(layout="""
A B
""",
edges="A,$1$,B|B,$0,1$,A",
A="accept|initial|label=$q''_0$",
B="accept|label=$q''_1$",
))
```




NFA for concat of “length ≤ 5 ” and “every odd position is a 1”:

```

from latextool_basic import *
print(automata(layout="""
A B C D E F G H
""",
edges="A,$0,1$,B|B,$0,1$,C|C,$0,1$,D|D,$0,1$,E|E,$0,1$,F"+\
      "|F,$\epsilon$,G"+\
      "|A,$\epsilon$,G"+\
      "|B,$\epsilon$,G"+\
      "|C,$\epsilon$,G"+\
      "|D,$\epsilon$,G"+\
      "|E,$\epsilon$,G"+\
      "|G,$1$,H|H,$0,1$,G",
A="initial|label=$q'_0$",
B="label=$q'_1$",
C="label=$q'_2$",
D="label=$q'_3$",
E="label=$q'_4$",
F="label=$q'_5$",
G="accept|label=$q''_0$",
H="accept|label=$q''_1$",
))

```




NFA with vectors as Σ :


```

from latextool_basic import *
print(automata(layout="""
A      B
""",
edges=r"A,$\begin{bmatrix}0\\0\\0\end{bmatrix},\begin{bmatrix}0\\1\\1\end{bmatrix}\end{bmatrix},\begin{bmatrix}1\\0\\1\end{bmatrix}$,A"+\
r"|A,$\begin{bmatrix}1\\1\\0\end{bmatrix}$,B"+\
r"|B,$\begin{bmatrix}0\\1\\0\end{bmatrix},\begin{bmatrix}1\\0\\0\end{bmatrix}\end{bmatrix},\begin{bmatrix}1\\1\\1\end{bmatrix}$,B"+\
r"|B,$\begin{bmatrix}0\\0\\1\end{bmatrix}$,A"+\
r""",
A="initial|accept|label=carry=0",
B="label=carry=1",
))

```



53 Longtable of minipages

abc	def
<code>v.size()</code>	return size of v etc.
<code>v.size()</code>	return size of v abc def
abc def def def def def def def def def	return size of v abc def

54 Solutions

This is not part of latextool.

See `projects/solutions`

Put symlink `/usr/lib64/python3.7/site-packages/solutions.py` to point to `projects/solutions`.

How to use: In a section (or chapter) of latex notes with exercises put

```

\section{Natural numbers  $\mathbb{N}$ }
\begin{python0}
from solutions import *; clear()
\end{python0}

\begin{ex}
  \label{ex:succ-onto-nonzero}
  What is  $1 + 1$ ?
  \solutionlink{sol:succ-onto-nonzero}
  \qed
\end{ex}
\begin{python0}
label = "succ-onto-nonzero"
s = r'''
\proof
 $1 + 1 = 2$ 
\qed
'''
from solutions import *; add(label, s)
\end{python0}

\begin{prop}
  \label{prop:N-is-commutative-monoid}
  What is  $1 + 1$ ?
\end{prop}

\proof
Exercise.
\solutionlink{sol:N-is-commutative-monoid}
\qed
\begin{python0}
from solutions import *
add(label="prop:N-is-commutative-monoid",
    srcfilename='proof-N-is-commutative-monoid.tex')
\end{python0}

\newpage
\subsection{Solutions}

\input{solutions.tex}

```