

07-IF-PART1

Y. LIOW (JUNE 19, 2026)

Contents

1	if and if-else: Part 1	7
1.1	if statements debug: 0-07-if-part1.tex	8
1.2	Mental picture: flow of execution for if debug: 1-07-if-part1.tex	19
1.3	Gotchas debug: 2-07-if-part1.tex	21
1.4	Multiplication game: Part 1 debug: 3-07-if-part1.tex	24
1.5	Blocks debug: 4-07-if-part1.tex	27
1.6	Random integers debug: 5-07-if-part1.tex	30
1.7	The important swap “trick” debug: 6-07-if-part1.tex	37
1.8	First sorting example debug: 7-07-if-part1.tex	39

Chapter 1

`if` and `if-else`: Part 1

Objectives

- Write `if` statements (including blocks)
- Write `if-else` statements (including blocks)
- Write nested `if-else` statements

We will now talk about writing statements that make decisions. In other words, statements that decide whether to run other statements or not.

This is significant . . . we are now embarking on writing program with intelligence . . .

ONWARD!!!

1.1 if statements debug: 0-07-if-part1.tex

So far you know that C++ can do arithmetic, print integer values, print string values, accept integer values from the keyboards, create and update variables.

You should expect more! (Otherwise C++ is pretty dumb.)

For instance you would expect programs to make decisions. Now wouldn't it be nice if C++ can do this:

```
if alien is killed:
    score = score + 10
```

or

```
if my ship' s energy is 0:
    end the game
```

or

```
if plane' s left engine has failed and
plane' s right engine has failed:
    activate seat ejection!!!
```

Note that for the first case, if the alien is not killed, you do *not* want to execute the statement `score = score + 10`. Otherwise everyone would keep getting the same score! What kind of dumb game is that?

In fact C++ *does* understand the `if` statement.

Run this program

```
int x = 0;
std::cin >> x;
if (x > 0)
    std::cout << "spam!" << std::endl;
std::cout << "eggs" << std::endl;
```

Run the program several time, entering different values for `x`. Note that the statement printing "spam!" is controlled by the `if`. However the statement that prints "eggs" is not.

For readability, the `if` statement is written like this:

```
int x = 0;
std::cin >> x;
if (x > 0)
    std::cout << "spam!" << std::endl;
std::cout << "eggs" << std::endl;
```

Big picture: The format of the `if` statement looks like this

if ([bool expr])
[stmt]

where `[bool expr]` is a **boolean expression** – this means that it's an expression that can be evaluated to a boolean value – and `[stmt]` is a C++ statement (of course there's a semi-colon at the end). Since we need boolean expressions it's a good time now to recall the following:

!	"not"
&&	"and"
	"or"
==	"is equal to"
!=	"is not equal to"
<	"is less than"
<=	"is less than or equal to"
>	"is greater than"
>=	"is greater than or equal to"

An example of a boolean expression is

[variable] [bool op] [value]

where `[variable]` is a variable of `int` or `double` or `float` type, `[bool op]` is one of the above boolean operators and `[value]` is an `int` or `double` or `float`. Don't forget that if there is a type mismatch, C++ will try to

type promote one value to match the type of the other. For instance if `x` is an `int` variable and the boolean expression is

```
x < 1.23
```

then C++ will use the `double` of `x` (i.e., `x` is automatically promoted to a `double`):

```
double(x) < 1.23
```

Exercise 1.1.1. Modify the above program so that "spam!" is printed when the integer entered is 42. Test your program.

debug: exercises/0-07-if-part1/question.tex

([Go to solution](#), page 17)



Exercise 1.1.2. Modify the above program so that the program prompts the user for his/her favorite number and print "you don't like 42?!?" if the integer entered is not 42. Here's an execution:

debug: exercises/1-07-if-part1/question.tex

```
what' s your favorite number? 42
```

Here's another:

```
what' s your favorite number? 1
you don't like 42?!?
```

([Go to solution](#), page 17)



Exercise 1.1.3. Write a program that prompts the user for an integer and prints "That's even. Am I smart?" if the integer entered is even. Here's an execution

debug: exercises/2-07-if-part1/question.tex

```
100
```

```
That' s even. Am I smart?
```

Here' s another

```
101
```

([Go to solution](#), page 17)



Exercise 1.1.4. Write a program that prompts the user for his/her age and prints “You’ re lying! Think you can fool me???” if the value entered is less than 18. Here’ s an execution:

debug: exercises/3-07-if-part1/question.tex

```
Enter your age: 16
```

```
You' re lying! Think you can fool me???
```

Here’ s another:

```
Enter your age: textbf100
```

Of course this is another boolean expression:

[var1] [bool op] [var2]

In this case you’ re comparing two (integer or double) variables.

([Go to solution](#), page 17)



Exercise 1.1.5. Write a program that prompts the user for two integer values and prints “First is bigger” if the first integer entered is larger than the second. Here’s an execution of the program:

debug: exercises/4-07-if-part1/question.tex

```
1 2
```

Here’s another

```
2 -1
First is bigger
```

Here’s yet another boolean expression:

[expr] [bool op] [value]

where [expr] is an (integer or double) expression.

([Go to solution](#), page 17)



Exercise 1.1.6. Write a program that prompts the user for his/her height (in ft) and weight (in lbs) and prints “you will live more than 100 years!!!” if the product of the height and weight is at least 200.45. (This is not supported by any form of research.) Here’s an execution of the program:

debug: exercises/5-07-if-part1/question.tex

```
6.1 180.180
```

```
you will live more than 100 years!!!!
```

Here' s another

```
3.4 23.4
```

([Go to solution](#), page 17)



Exercise 1.1.7. Write a program that prompts the user for the year of his/her date of birth and the current year and prints his/her approximate age and then prints “you must have watched lots of movies by now” if the difference of the two values is at least 20.

debug: exercises/6-07-if-part1/question.tex

Here' s an execution:

```
1900 2000

you are about 100 years old

you must have watched lots of movies by now
```

Here' s another:

```
2000 2006

you are about 6 years old
```

One last one ... here' s one more boolean expression:

[expr1] [bool op] [expr2]

([Go to solution](#), page 17)



Now, we're comparing two expressions.

Exercise 1.1.8. Write a program that prompts the user for the month, day of his/her date of birth and also his/her height (in ft) and weight (in lbs). Print the approximate number of days from January 1 of the year he/she was born and the sum of his/her height and weight. If the first printed number is greater than the second, print "According to the theory of relativity, you are going to win the next powerball."

debug: exercises/7-07-if-part1/question.tex

```
Enter the month, day of your DOB: 1 1
Enter your height and weight: 6 100
1 106
```

Here's another:

```
Enter the month, day of your DOB: 12 25
Enter your height and weight: 6 200
355 206
According to the theory of relativity,
you are going to win the next powerball.
```

(You may assume the number of days in a month is 30.)

([Go to solution](#), page 17)



Exercise 1.1.9. Try this:

debug: exercises/8-07-if-part1/question.tex

```
int numHeads = 0;

std::cout << "How many heads do you have? ";

std::cin >> numHeads;

if (numHeads == 2)

    std::cout << "Are you Zaphod?" << std::endl;
```

And then this:

```
int numHeads = 0;

std::cout << "How many heads do you have? ";

std::cin >> numHeads;

if (numHeads != 2)

    std::cout << "You are not Zaphod" << std::endl;
```

Combine both into one program so that I get the following execution:

```
How many heads do you have?1

You are not Zaphod
```

And here's an execution of the same program:

How many heads do you have?**2**

Are you Zaphod?

Next modify the program so that, in addition to the above requirements,

if the number of heads entered is greater than 2, the program prints "No

kidding!". Finally, modify the program so that, in addition to the

above, if the number of heads is 1, the program prints "Let me introduce

you to our surgeons." Test your program by entering 0, 1, 2, 3.

(There' s a better way to do this exercise ...)

([Go to solution](#), page 18)



Solutions

Solution to Exercise [1.1.1.](#)

debug: exercises/0-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.1.2.](#)

debug: exercises/1-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.1.3.](#)

debug: exercises/2-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.1.4.](#)

debug: exercises/3-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.1.5.](#)

debug: exercises/4-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.1.6.](#)

debug: exercises/5-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.1.7.](#)

debug: exercises/6-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.1.8.](#)

debug: exercises/7-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.1.9](#).

debug: exercises/8-07-if-part1/answer.tex

Solution not provided.


1.2 Mental picture: flow of execution for `if`

debug: 1-07-if-part1.tex

The `if` statement is difficult for some beginning programmers because it alters the flow of execution of a program.


Before this set of notes, C++ executes one statement at a time from top to bottom; it executes every statement.

The `if` statement is different because it has a statement **inside** the `if` statement.



The statement in the `if` statement is executed only when the `x > 0` is true. If the condition is not true, the statement in the `if` statement is not executed.

In the following diagram, you can follow the arrows to get a sense of the flow of execution:



Of course the program is still executing one statement at a time from the top to the bottom if you view the `if` statement as a statement (i.e. forget about the internals of the `if` statement).

1.3 Gotchas debug: 2-07-if-part1.tex

Exercise 1.3.1. Try this:

debug: exercises/9-07-if-part1/question.tex

```
int x = 0;

std::cin >> x;

if x > 0

    std::cout << "spam!" << std::endl;

std::cout << "eggs" << std::endl;
```

Fix it.

([Go to solution](#), page 23)



Exercise 1.3.2. Try this:

debug: exercises/10-07-if-part1/question.tex

```
int x = 0;

std::cin >> x;

if (x > 0);

    std::cout << "spam!" << std::endl;

std::cout << "eggs" << std::endl;
```

What do you learn from this example?

([Go to solution](#), page 23)



Exercise 1.3.3. Here's another wacky example ...

debug: exercises/11-07-if-part1/question.tex

```
int x = 0;

std::cin >> x;

if (x > 0);

std::cout << "eggs" << std::endl;
```

([Go to solution](#), page [23](#))



Solutions

Solution to Exercise [1.3.1](#).

debug: exercises/9-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.3.2](#).

debug: exercises/10-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.3.3](#).

debug: exercises/11-07-if-part1/answer.tex

Solution not provided.

1.4 Multiplication game: Part 1

debug: 3-07-if-part1.tex

Exercise 1.4.1. Write a program that tests if the user can do two digit multiplication. Right now we will just ask the one question: the product

debug: exercises/12-07-if-part1/question.tex

of 97 and 94. The program congratulates the user if the right answer is

entered. Otherwise the program stops immediately. Here's an execution of the program:

```
What is the product of 97 and 94? 1
```

Here's another execution of the program:

```
What is the product of 97 and 94? 9118
You smart dawg!
```

([Go to solution](#), page 26)



This is kind of a dumb program because it asks the same question again and again.

Here's the **pseudocode** (pseudocode = informal description of

steps in a program):

```
Declare integer variable guess
Print a prompt string to user
Prompt user for integer value for guess
If guess is 9118
    print congratulatory message
```

Note that this is not a C++ program yet!!! You can't run it!!!

Complete the program using the above pseudocode. Test your program.

Solutions

Solution to Exercise [1.4.1](#).

debug: exercises/12-07-if-part1/answer.tex

Solution not provided.

1.5 Blocks debug: 4-07-if-part1.tex

What if you want to execute **several** statements when a boolean expression is true? Here's one way:

```
int x = 0;
std::cin >> x;
if (x > 0)
    std::cout << "spam!" << std::endl;
if (x > 0)
    std::cout << "ham!" << std::endl;
std::cout << "eggs" << std::endl;
```

It does work ...but ...that's the **BAD** way of executing two statements when a condition holds.

This is the right way:

```
int x = 0;
std::cin >> x;
if (x > 0)
{
    std::cout << "spam!" << std::endl;
    std::cout << "ham!" << std::endl;
}
std::cout << "eggs" << std::endl;
```

The **{...}** is called a **block** or **block of statements**. (You've actually seen this already. Look at your `main()` ...) You can have as many statements as you like in a block, not just two.

Exercise 1.5.1. Here's part of a game that you're writing ... complete it. If the missile hits the alien, increment the `score` by 100, set `play_explosion` to `true`, increment your `energy` by the alien's energy (i.e. `alien_energy`), and set the alien's energy to 0. Test your code with different inputs.

debug: exercises/13-07-if-part1/question.tex

```
int score = 1234;
int energy = 6789;
int alien_energy = 42;
bool play_explosion = false;
bool missile_hit_alien;
std::cin >> missile_hit_alien;

std::cout << "score: " << score << '\n'
           << "energy: " << energy << '\n'
           << "alien_energy: " << alien_energy << '\n'
           << "play_explosion: " << score << '\n';
```

([Go to solution](#), page 29)



Solutions

Solution to Exercise [1.5.1](#).

debug: exercises/13-07-if-part1/answer.tex

Solution not provided.

1.6 Random integers debug: 5-07-if-part1.tex

Generating a random integer occurs commonly in computer programs. For instance if you want to write a strategy role-playing game, you might have different rooms in a mansion and you want to put different things in different rooms. Suppose you have a magic potion in a bottle. Now suppose the rooms are numbered from 1 to 1000. You don't want your magic potion bottle to be in room 5 whenever you start the game. You want each game to be different.

At a more complex level you might want to randomly make doors between two rooms. This creates a random maze.

So you'd better learn how to generate random things.

Try this:

```
#include <iostream>

int main()
{
    std::cout << "the potion is in room " << rand()
               << std::endl;
    std::cout << "the potion is in room " << rand()
               << std::endl;
    std::cout << "the potion is in room " << rand()
               << std::endl;
    std::cout << "total number of rooms: "
               << RAND_MAX << std::endl;

    return 0;
}
```

(Note: You might need `#include <cstdlib>` just after `#include <iostream>`. This depends on your compiler.)

Looks like you're getting random integers. But wait ... run the program a second time ... a third time ... a fourth time. Notice something?

OK. Let's modify the program:

```
#include <iostream>
#include <ctime>
int main()
{
    srand((unsigned int) time(NULL));
    std::cout << "the potion is in room " << rand()
               << std::endl;
    std::cout << "the potion is in room " << rand()
               << std::endl;
    std::cout << "the potion is in room " << rand()
               << std::endl;
    std::cout << "total number of rooms: "
               << RAND_MAX << std::endl;
    return 0;
}
```

Run this program several times. Notice that the room number is different each time you run the program.

I will not go into details on the statement

```
srand((unsigned int) time(NULL));
```

The only thing I will say is that it “seeds” the random generator so as to make it “more random”. The important thing to remember is that you must execute this statement and furthermore you execute it **once** (usually) and **before** you call the `rand()` function. The standard practice is to execute the seeding in `main()` and at the beginning:

```
#include <iostream>
#include <ctime>
int main()
{
    srand((unsigned int) time(NULL));
    . . .
    return 0;
}
```

Since `rand()` gives you a random number from 0 to `RAND_MAX`,

```
rand() / RAND_MAX
```

will give you a random `double` between 0.0 and 1.0. But this is not right because the `/` is an **integer** division. Therefore we do this:

```
double(rand()) / RAND_MAX
```

to get a random double from 0.0 to 1.0.

Exercise 1.6.1. Check that I was not lying by printing 10 random doubles from 1.0 to 0.0. By the way, if the numbers are truly random, you would expect their average to be close to 0.5. Check that too.

debug: exercises/14-07-if-part1/question.tex

There are times when you need to generate a random *integer* between two bounds. For instance if you have a maze game and the rooms are numbered 1 to 100, you want a random room number for a magic potion. How many values are there from 1 to 100? You have 100. Since `rand()` gives you a random integer from 0 to `RAND_MAX`, if you do

```
rand() % 100
```

you get 100 numbers, from 0 to 99. You add 1 to it and you get a random

integer from 1 to 100. In other words

```
1 + rand() % 100
```

does the trick.

([Go to solution](#), page 35)



Exercise 1.6.2. How do you generate random integers from 1,..., 6? (For instance to simulate a dice roll.) Verify with a C++ program.

debug: exercises/15-07-if-part1/question.tex

([Go to solution](#), page 35)



Exercise 1.6.3. How do you generate random integers from 1,..., 10? Verify with a C++ program.

debug: exercises/16-07-if-part1/question.tex

([Go to solution](#), page 35)



What about generating random integers from 5,..., 20? In this case the the lower bound is 5 and not 1. You use the same idea. Note that if you do something like

```
rand() % 10
```

or

```
rand() % 18
```

the range of numbers starts from 0. So if you want to generate random numbers in the range of 5,..., 20, the first thing you do is to think about the range

$$0, \dots, 15$$

first. In other words move the given range 5, ..., 20 so that the lower bound of the range becomes 0. That means subtracting 5 from the range. To generate a number in the range of 0, ..., 15, you do

$$\text{rand}() \% 16$$

This gives a number in the range 0, ..., 15. You then add 5 to it:

$$5 + \text{rand}() \% 10$$

Exercise. Verify that the expression

$$5 + \text{rand}() \% 10$$

does give you numbers in the range of 5, ..., 20. .

Exercise 1.6.4. How do you generate random integers from 9,...142? Verify with a C++ program.

debug: exercises/17-07-if-part1/question.tex

([Go to solution](#), page 35)



Exercise 1.6.5. How do you generate random integers from -5,...,5? Verify with a C++ program.

debug: exercises/18-07-if-part1/question.tex

([Go to solution](#), page 35)



Exercise 1.6.6. How do you generate random `double` from 0,...,2.0? Verify with a C++ program.

debug: exercises/19-07-if-part1/question.tex

([Go to solution](#), page 35)



Exercise 1.6.7. How do you generate random double from -1.0,...,1.0? Verify with a C++ program.

debug: exercises/20-07-if-part1/question.tex

([Go to solution](#), page 35)



Exercise 1.6.8. How do you generate random double from 0,...,3.5?
Verify with a C++ program.

debug: exercises/21-07-if-part1/question.tex

([Go to solution](#), page 35)



Exercise 1.6.9. How do you generate random double from -2.0,...,2.0?
Verify with a C++ program.

debug: exercises/22-07-if-part1/question.tex

([Go to solution](#), page 36)



Solutions

Solution to Exercise [1.6.1](#).

debug: exercises/14-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.6.2](#).

debug: exercises/15-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.6.3](#).

debug: exercises/16-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.6.4](#).

debug: exercises/17-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.6.5](#).

debug: exercises/18-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.6.6](#).

debug: exercises/19-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.6.7](#).

debug: exercises/20-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.6.8](#).

debug: exercises/21-07-if-part1/answer.tex

Solution not provided.

Solution to Exercise [1.6.9](#).

debug: exercises/22-07-if-part1/answer.tex

Solution not provided.

1.7 The important swap “trick”

debug: 6-07-if-part1.tex

Recall the following extremely important “trick” that you must know. It allows you to swap the values in two variables:

```
int a = 42, b = 24;
std::cout << a << " " << b << std::endl;
int t = a;
a = b;
b = t;
std::cout << a << " " << b << std::endl;
```

Exercise 1.7.1. Write a program that declares two doubles, initializing them with 1.234 and 4.567. Print the values of the variables. Swap their values. Print the values of the variables.

debug: exercises/23-07-if-part1/question.tex

([Go to solution](#), page 38)



Solutions

Solution to Exercise [1.7.1](#).

debug: exercises/23-07-if-part1/answer.tex

Solution not provided.

1.8 First sorting example debug: 7-07-if-part1.tex

Here's your first sorting problem:

- Prompt the user for two integer values and assign them to x and y.
- Sort the values so that the value of x is less than or equal to the value of y