


Description

Purpose: The purpose of this audit is to run a query to return the *last person* who modified a table.

Details: This audit can essentially be run from almost every single table because every table contains the appropriate fields to join to the person table (updt_id and updt_dt_tm). The idea is that to link to the tables, you set the primary key of that table (person_id, product_id, task_assay_cd, order_catalog_cd etc. equal to the updt_id.

In query builder, you can tell what your primary key is by a red key.

 If multiple people have modified the item you are looking at there is pretty much no way of telling the first person who modified it because the data gets overwritten after the last person modifies it.

Dates

All of the audit examples listed below contain a date range qualification that looks similar to:

curdate = current date

2300 = 24hr time (11pm)

Since curdate is the current date curdate-1 means yesterday, curdate-2 would be two days ago etc. By modifying the dates accordingly, it is easy to quality your audit during the correct time range. A lot more on dates can be found [here](#).


Orderables

The following audit returns all orderables that have been modified within the defined date range and who modified them.

| UPDT_ID | ORDERABLE | PERSON_ID | NAME_FULL_FORMATTED | UPDT_DT_TM | UPDT_APPLCTX |
|-----------|---------------|-----------|---------------------|-----------------------------|--------------|
| 744099.00 | acetaminophen | 744099.00 | Francisco, Tony | August 27, 2013 09:09:00 | 2923153.00 |
| 589923.00 | linezolid | 589923.00 | TEST, DBA CERNER | August 28, 2013 23:28:47 | 2925553.00 |
| 589923.00 | albuterol | 589923.00 | TEST, DBA CERNER | September 03, 2013 12:22:57 | 2933282.00 |



As you can see in the screen shot, there is no qualification on the activity_type_cd, meaning that the audit returns every single order within the given time range. To qualify on activity_type_cd insert the following code after the date range qualification

where *code_value* is the appropriate code_value. To find the appropriate code_value run the following script:

 Most of the time returning data from an entire data range won't be really useful. The following audit shows how to look at a specific order.

| UPDT_ID | ORDERABLE | PERSON_ID | NAME_FULL_FORMATTED | UPDT_DT_TM | UPDT_APPLCTX |
|-----------|-----------|-----------|---------------------|------------------------|--------------|
| 907962.00 | ABO/Rh | 907962.00 | Townsend, Christin | July 19, 2012 08:44:49 | 2141707.00 |

The catalog_cd of an order can be found in DORC.



Products

The following audit is an example of querying the product_index table to return products that have been modified within the given time range.

i The product_index table is the product reference table (products built in Bedrock). Products received in inventory are located on the Products table.

| UPDT_ID | PRODUCT | PERSON_ID | NAME_FULL_FORMATTED | UPDT_DT_TM | UPDT_APPLCTX |
|-----------|----------------|-----------|---------------------|--------------------------|--------------|
| 589923.00 | RBC AS1 LR Irr | 589923.00 | TEST, DBA CERNER | August 29, 2013 16:24:24 | 2926516.00 |
| 589923.00 | RBC AS1 LR Irr | 589923.00 | TEST, DBA CERNER | August 29, 2013 16:24:29 | 2926516.00 |
| 589923.00 | PLT ACDA Irr | 589923.00 | TEST, DBA CERNER | August 29, 2013 15:38:22 | 2926437.00 |

To add a qualification to find a specific product remove the date code and add the following code:

where the product_cd can be found by running the following audit:



Assays

The following audit queries the discrete_task_assay table to return who modified an assay.

i The modification of an assay refers to modifying the actual assay - changing the name, result type, result processing type etc. The following examples show how to query who changed what order an assay was associated to.

| UPDT_ID | DTA | PERSON_ID | NAME_FULL_FORMATTED | UPDT_DT_TM | UPDT_APPLCTX |
|-----------|--------|-----------|---------------------|-----------------------|--------------|
| 589923.00 | Anti-A | 589923.00 | TEST, DBA CERNER | May 15, 2013 13:16:55 | 2772088.00 |

The task_assay_cd can be found in DORC.



Assay Association

The following audit queries the `profile_task_r` table to determine who modified a task assay association between an assay and an orderable.

| UPDT_ID | DTA | ORDERABLE | PERSON_ID | NAME_FULL_FORMATTED | UPDT_DT_TM | UPDT_APPLCTX |
|-----------|--------|-----------|-----------|---------------------|-----------------------|--------------|
| 589923.00 | Anti-A | ABO/Rh | 589923.00 | TEST, DBA CERNER | May 15, 2013 08:03:53 | 2771594.00 |

The `task_assay_cd` and the `catalog_cd` can be found in DORC as shown by the previous screen shots.

Digging Deeper...

There are ways in which you can find even more information that just who the last person to modify a table was. By using a front end security application and by querying the security tables, a number of useful pieces of information can be found: the application the update was made with, the date/time range in which the user was logged into the application for, the username of the individual who made the modification, the position or role of the individual and even additional modifications they made during that single session.

This can be done in two ways as stated above: querying the security table `Application_Context` or by using the front end application `appcmtx.exe`.


Querying the Application_Context Table

Notice in all of the previous screen shots the `updt_applctx` field was included on all of the audits. It was included because this is the field used to query the `application_context` table.

Using the assay association example above, we can take the `updt_applctx` and use it in the qualification of the following audit:

The following screenshots show the information returned by that audit.

| APP_CTX_ID | APPLCTX | PERSON_ID | NAME | USERNAME | APPLICATION_NUMBER | POSITION_CD | START_DT_TM | END_DT_TM | APPLICATION_IMAGE | |
|---|--------------------|--------------------|----------------|---------------------------|--------------------|--------------------------|-------------|-------------------|---------------------|-----------|
| 402017.00 | 2771594.00 | 589923.00 | Cerner, DBA | CERDBA | 15000 | 441.00 | 05/15/13 | 05/15/13 | deptorcwizard | |
| APPLICATION_DIR | | APPLICATION_STATUS | PARMS_FLAG | DEVICE_LOCATION | | DEVICE_ADDRESS | | AUTHORIZATION_IND | APPLICATION_VERSION | |
| C:\Program Files\CERNER\deptorcwizard.exe | | 0.00 | 0.00 | Device Location Not Found | | Device Address Not Found | | 1 | 2012.07.1.3 | |
| DEFAULT_LOCATION | CLIENT_START_DT_TM | CLIENT_NODE_NAME | TCPIP_ADDRESS | LOGDIRECTORY | UPDT_APPLCTX | UPDT_DT_TM | UPDT_ID | UPDT_CNT | UPDT_TASK | CLIENT_TZ |
| Default Location Not Found | 05/15/13 | SCTESTCTX2 | 10.190.130.180 | C:\TEMP\ym025465 | 2771594.00 | 05/15/13 | 589923.00 | 1 | 15000 | 75 |

 All information made during the same session will have the same updt_applctx. Therefore, if you were querying the product_index table for example and you created two-hundred products at one time, all two-hundred would pull in the previous audit.

Integrating with Appctnxt.exe

Again, the *applctx* field in the screen shot above is the *updt_applctx*. The useful piece of information in regards to inserting into the front-end application is the *app_ctx_id*. Entering it into the application provides some of the same information the audit of the application_context table showed.

Start Date
09/04/2010
End Date
09/04/2013
User:
Application Number:
Application Context ID:
402017

Contexts

| Application | User | Started | Finish | App Ctx ID |
|-------------------------|----------------------|--------------------------|--------------------------|------------|
| ✓ 15000 - deptorcwizard | CERDBA - Cerner, DBA | 5/15/2013 8:03:13 AM CDT | 5/15/2013 8:03:56 AM CDT | 402017 |

Because we have the application used to make the update and the time range (Started and Finished) the user was logged into the application, we can see all changes made in that time range using this application.

Start Date
09/04/2010
End Date
09/04/2013
User:
Application Number:
15000

Contexts

| Application | User | Started | Finish | App Ctx ID |
|-------------------------|-------------------------------|--------------------------|--------------------------|------------|
| ✓ 15000 - deptorcwizard | DG010984 - Greer, Dustin | 8/9/2012 9:03:13 AM CDT | 8/9/2012 5:41:56 PM CDT | 136070 |
| ✓ 15000 - deptorcwizard | DG010984 - Greer, Dustin | 8/9/2012 10:03:01 PM CDT | 8/9/2012 11:11:52 PM CDT | 138447 |
| ✓ 15000 - deptorcwizard | CT013999 - Townsend, Christin | 8/8/2012 5:43:45 PM CDT | 8/8/2012 5:51:32 PM CDT | 135819 |
| ✓ 15000 - deptorcwizard | CT013999 - Townsend, Christin | 8/8/2012 11:58:54 AM CDT | 8/8/2012 1:16:22 PM CDT | 133744 |
| ✓ 15000 - deptorcwizard | LD017805 - Deabler, Lisa | 8/7/2012 3:12:39 PM CDT | 8/7/2012 3:14:47 PM CDT | 131985 |
| ✓ 15000 - deptorcwizard | Pw017512 - Brown, Penny | 8/7/2012 11:01:15 AM CDT | 8/7/2012 11:37:30 AM CDT | 130651 |
| ✓ 15000 - deptorcwizard | LD017805 - Deabler, Lisa | 8/6/2012 9:06:58 AM CDT | 8/6/2012 11:29:15 AM CDT | 127566 |
| ✓ 15000 - deptorcwizard | DG010984 - Greer, Dustin | 8/3/2012 1:21:05 PM CDT | 8/3/2012 3:17:05 PM CDT | 126228 |
| ✓ 15000 - deptorcwizard | RH2446 - Simcox, Renee | 8/23/2012 6:02:54 AM CDT | 8/23/2012 6:19:20 AM CDT | 204866 |
| ✓ 15000 - deptorcwizard | DG010984 - Greer, Dustin | 8/23/2012 8:13:44 AM CDT | 8/23/2012 5:33:04 PM CDT | 204994 |

It is possible to view all modifications by a user in a given session. Take for instance the first item on our list with an *app_ctx_id* = 136070. We can use this to query the application_context table again.

| APP_CTX_ID | APPLCTX | PERSON_ID | NAME | USERNAME | APPLICATION_NUMBER | POSITION_CD | START_DT_TM | END_DT_TM | APPLICATION_IMAGE |
|------------|------------|-----------|---------------|----------|--------------------|-------------|-------------|-----------|-------------------|
| 136070.00 | 2305851.00 | 939935.00 | Greer, Dustin | DG010984 | 15000 | 441.00 | 08/09/12 | 08/09/12 | deptorcwizard |

By running this query we get our *applctx* value.

 Remember, the *applctx* is equivalent to the *updt_applctx* on any table

The *updt_applctx* can now be used to determine exactly what updates were made to the system. The next step is a bit of a process of elimination because you have to search a table for the *updt_applctx*. But, which table do you search? We can use a process of elimination - the only tables that can be updated are the ones in which modifications can be made via deptorcwizard (application ID 1500).

Several of the modifications:

orderables - order_catalog table
assays - discrete_task_r table

The version of the page that you are viewing is a draft version or a supporting document.

© Cerner Corporation. All rights reserved. This document contains confidential and/or proprietary information belonging to Cerner Corporation and/or its related affiliates which may not be reproduced or transmitted in any form or by any means without the express written consent of Cerner.

assay associations - profile_task_r table
reference range associations - reference_range_factor_id
routing - several tables

By going through the list of tables available the following query pulls data:

| REFERENCE_RANGE_FACTOR_ID | TASK_ASSAY_CD | UPDT_DT_TM | UPDT_ID | UPDT_TASK | UPDT_CNT | UPDT_APPLCTX |
|---------------------------|---------------|------------|-----------|-----------|----------|--------------|
| 21812551.00 | 21777066.00 | 08/09/12 | 939935.00 | 15001 | 0 | 2305851.00 |
| 21812552.00 | 21777066.00 | 08/09/12 | 939935.00 | 15001 | 0 | 2305851.00 |
| 21812553.00 | 21777066.00 | 08/09/12 | 939935.00 | 15001 | 0 | 2305851.00 |
| 21812554.00 | 21777066.00 | 08/09/12 | 939935.00 | 15001 | 0 | 2305851.00 |
| 21812555.00 | 21777066.00 | 08/09/12 | 939935.00 | 15001 | 0 | 2305851.00 |
| 21812568.00 | 21777068.00 | 08/09/12 | 939935.00 | 15001 | 0 | 2305851.00 |
| 21812569.00 | 21777068.00 | 08/09/12 | 939935.00 | 15001 | 0 | 2305851.00 |
| 21812570.00 | 21777068.00 | 08/09/12 | 939935.00 | 15001 | 0 | 2305851.00 |
| 21812571.00 | 21777068.00 | 08/09/12 | 939935.00 | 15001 | 0 | 2305851.00 |
| 21812572.00 | 21777068.00 | 08/09/12 | 939935.00 | 15001 | 0 | 2305851.00 |
| 21777072.00 | 21777066.00 | 08/09/12 | 939935.00 | 15001 | 1 | 2305851.00 |
| 21777074.00 | 21777066.00 | 08/09/12 | 939935.00 | 15001 | 1 | 2305851.00 |
| 21777076.00 | 21777066.00 | 08/09/12 | 939935.00 | 15001 | 1 | 2305851.00 |
| 21777080.00 | 21777068.00 | 08/09/12 | 939935.00 | 15001 | 1 | 2305851.00 |
| 21777082.00 | 21777068.00 | 08/09/12 | 939935.00 | 15001 | 1 | 2305851.00 |
| 21777088.00 | 21777066.00 | 08/09/12 | 939935.00 | 15001 | 1 | 2305851.00 |
| 21777090.00 | 21777068.00 | 08/09/12 | 939935.00 | 15001 | 1 | 2305851.00 |
| 21777078.00 | 21777068.00 | 08/09/12 | 939935.00 | 15001 | 1 | 2305851.00 |
| 21777086.00 | 21777068.00 | 08/09/12 | 939935.00 | 15001 | 1 | 2305851.00 |
| 21777084.00 | 21777066.00 | 08/09/12 | 939935.00 | 15001 | 1 | 2305851.00 |

This screen shot shows all of the data that was added/modified during a given session in the application (same *updt_applctx* value)

Page History

| Version | Date | Comment |
|------------------------|--------------------|---|
| Current Version (v. 3) | Sep 19, 2013 15:57 | Magoon,Yitzhak: Included a new version of the following page: Digging Deeper |
| v. 2 | Sep 19, 2013 15:50 | Magoon,Yitzhak: Included the Digging Deeper page |
| v. 1 | Sep 19, 2013 14:53 | Magoon,Yitzhak |