

⚠

Embedded database should be used for evaluation purposes only. It doesn't support scaling, upgrading to a new SonarQube Server version, or migration to another database engine.

Learn more

Issues

7 issues

Projecto-python-acm-master/.....

Refactor this function to reduce its Cognitive Complexity from 17 to the 15 allowed.

10 locations

+1

+2 (incl 1 for nesting)

+1

+2 (incl 1 for nesting)

+3 (incl 2 for nesting)

+4 (incl 3 for nesting)

+1

+1

+1

+1

Navigate locations Alt + ▲ ▼

Replace the unused local variable "status" with "_".

1 location

Replace the unused local variable "result" with "_".

Projecto-python-acm-master/.....

Refactor this function to reduce its Cognitive Complexity from 33 to the 15 allowed.

16 locations

Replace the unused local variable "nombre" with "_".

Projecto-python-acm-master/.....

Replace this map call with a comprehension.

Rename this local variable "correosLimpio" to match the regular expression `^[a-z][a-z0-9_]*$`.

7 of 7 shown

Refactor this function to reduce its Cognitive Complexity from 17 to the 15 allowed.

Cognitive Complexity of functions should not be too high **python:S3776**

Line affected: **L37** • Effort: **7min** • Introduced: **23 minutes ago**

Open Not assigned brain-overload +

- Where is the issue?
- Why is this an issue?
- How can I fix it?
- Activity
- More info

Software qualities impacted

Maintainability High

Code attribute

Adaptability | Not focused

malas_practicas > Proyecto-python-acm-master/src/Control/ControlCorreo.py

Open in IDE See all issues in this file

Show previous few lines of code Show all lines

32
33
34
35
36
37

"""
self.mail = imaplib.IMAP4_SSL(self.server)
self.mail.login(self.email_account, self.password)
self.mail.select("inbox") # Selecciona bandeja de entrada

def leer_todos(self):

Refactor this function to reduce its Cognitive Complexity from 17 to the 15 allowed.

38
39
40
41
42
43
44
45
46

"""
Lee todos los correos del buzón de entrada y retorna una lista con la información relevante de cada mensaje.

Returns:
list: Lista de diccionarios con ID, remitente, asunto y contenido del mensaje.
"""
self.conectar()
status, messages = self.mail.search(None, "ALL") # IDs de todos los correos

Replace the unused local variable "status" with "_".

47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88

email_ids = messages[0].split()
correos = []

• for num in email_ids:
Obtiene el correo completo en formato RFC822
status, msg_data = self.mail.fetch(num, "(RFC822)")
raw_email = msg_data[0][1]
msg = email.message_from_bytes(raw_email)

---- Decodificar asunto ----
subject, encoding = decode_header(msg.get("Subject", ""))[0]
• if isinstance(subject, bytes):
subject = subject.decode(encoding • or "utf-8", errors="ignore")

Obtener remitente
sender = msg.get("From")

Obtenemos la fecha
date = msg.get("Date")

---- Obtener cuerpo del mensaje ----
body = ""
• if msg.is_multipart(): # Mensaje con varias partes
• for part in msg.walk():
Solo texto plano y sin adjuntos
• if part.get_content_type() == "text/plain" • and \
"attachment" not in str(part.get("Content-Disposition", "")):

body = part.get_payload(decode=True).decode(
part.get_content_charset() • or "utf-8",
errors="ignore"
)
break
• else:
Mensaje simple
body = msg.get_payload(decode=True).decode(
msg.get_content_charset() • or "utf-8",
errors="ignore"
)

correos.append({
"id": num,

Show next few lines of code Show all lines

