

API Specification Doc

(Music Search Engine Project)

Version	Date	Author	Description
1.0	03-Nov-2016	Yash Miriyala Gordon Chiarizzio	Initial draft

Index

1. get Tweet

[Request](#)

[Response](#)

2. get Top Track

[Request](#)

[Response](#)

3. get Wiki

[Request](#)

[Response](#)

4. get Info

[Request](#)

[Response](#)

Conventions

Status Codes

Methods

1. get Tweet

Obtain tweets about a given artist.

Request

Method	URL
GET	api/getTweet/

Type	Params	Values
URL_PARAM	artist	string

artist

artist must be sent with all client requests. The artist is whom we wish to retrieve a tweet about.

Response

Status	Response
200	Tweet JSON
400	Bad request
500	Server Error

2. get Top Track

Get the top track of a given artist

Request

Method	URL
GET	api/getTopTrack/

Type	Params	Values
URL_PARAM	artist	string

artist

The `artist` that you wish to get the top album of.

Response

Status	Response
200	<p>Response will be a string representing the top album of the artist. Below is an example</p> <p>Endpoint: /getTopTrack?artist=u2</p> <p>The response is: The Joshua Tree (Deluxe Edition Remastered)</p>
400	Bad request
500	Server Error

3. get Wiki

Get the wikipedia excerpt of a given artist

Request

Method	URL
--------	-----

GET	api/getWiki/
------------	--------------

Type	Params	Values
URL_PARAM	artist	string

artist

The **artist** that you wish to get the top album of.

Response

Status	Response
200	Response will be a string that represents the content of the corresponding wikipedia article
400	Bad request
500	Server Error

4. get Info

Get the top track, a random tweet, and the wikipedia excerpt of a given artist.

Request

Method	URL
GET	api/getInfo/

Type	Params	Values
URL_PARAM	artist	string

artist

The `artist` that you wish to get the top album of.

Response

Status	Response
200	Response will be a JSON object with keys “Tweet”, “Top Track”, and “Wiki” in the form <code>{“Tweet”: Tweet object, “Top Track”: string, “Wiki”: string</code>
400	Bad request
500	Server Error

Glossary

Conventions

- **Client** - Client application.
- **Status** - HTTP status code of response.
- All the possible responses are listed under 'Responses' for each method. Only one of them is issued per request server.
- All response are in JSON format.
- All request parameters are mandatory unless explicitly marked as [optional]
- The type of values accepted for a *request* parameter are shown the the values column like this [**10**|<any number>] .The | symbol means OR. If the parameter is [optional], the default value is shown in blue bold text, as **10** is written in [**10**|<any number>].

Status Codes

All status codes are standard HTTP status codes. The below ones are used in this API.

2XX - Success of some kind

4XX - Error occurred in client's part

5XX - Error occurred in server's part

Status Code	Description
200	OK
400	Bad request
500	Server Error