

I217: Functional Programming

10. A Programming Language Processor – Compiler

Kazuhiro Ogata

Roadmap

- Compiler

Compiler

The compiler translates programs written in Minila into lists of instructions that can be executed by the virtual machine.

We first describe how to generate lists of instructions for expressions and then how to generate lists of instructions for statements.

Compiler

Given an expression e , `genForExp` generates a list of instructions for e such that executing the instruction list makes the result of e left at the top of the stack.

`op genForExp : Exp -> IList .`

In what follows, the following variables are used:

```
vars E E1 E2 : Exp .  
vars S S1 S2 : Stm .  
var V : Var .  
var N : Nat .  
var IL : IList .
```

Compiler

$\text{eq genForExp}(n(N)) = \text{push}(N) \mid \text{iln} .$  the empty list of instructions

Executing $\text{push}(N)$ leaves N at the top of the stack.

$\text{eq genForExp}(V) = \text{load}(V) \mid \text{iln} .$

Executing $\text{load}(V)$ leaves the natural number associated with V in a given environment at the top of the stack. If the environment does not have any entries whose key is V , then errNat is push onto the stack that will become errStack .


Compiler

$\text{eq genForExp}(E1 + E2)$
 $\quad = \text{genForExp}(E1) @ \text{genForExp}(E2) @ (\text{add} \mid \text{iln}) .$


Executing the instruction list generated by $\text{genForExp}(E1)$ leaves the result n_1 of calculating $E1$ at the top of the stack.



Executing the instruction list generated by $\text{genForExp}(E2)$ leaves the result n_2 of calculating $E2$ at the top of the stack.



Executing add leaves the result of calculating $n_1 + n_2$ at the top of the stack.



Compiler

For the remaining expressions, equations can be described likewise for `genForExp`.

Compiler

Given a program in Minila, `compile` generates the list of instructions for the program (a statement) with `generate` and adds `quit` to the list at the end.

```
op compile : Stm -> IList .  
eq compile(S) = generate(S) @ (quit | iln) .
```

```
op generate : Stm -> IList .
```

```
eq generate(estm) = iln .
```

If the program is `estm`, then it generates the empty list of instructions.

Compiler

If the program is $V := E$;, then it generates the list of instructions for E and adds $\text{store}(V)$ to the list at the end.


the list of instructions for E	$\text{store}(V)$
----------------------------------	-------------------

$\text{generate}(x := n(3) + n(4) * n(5) ;)$ generates the following:

$(\text{push}(3) \mid (\text{push}(4) \mid (\text{push}(5) \mid (\text{multiply} \mid (\text{add} \mid (\text{store}(x) \mid \text{iln})))))):\text{IList}$
└──┘
 $n(3) + n(4) * n(5)$

Compiler

If the program is $\text{if } E \{S1\} \text{ else } \{S2\}$, then it generates the following list of instructions:



Compiler

generate(if tmp * tmp > x { z := tmp - n(1) ; } else { y := tmp ; })
generates the following:

```
(load(tmp) | (load(tmp) | (multiply | (load(x) | (greaterThan |
└──────────────────────────────────────────────────────────┘
                        tmp * tmp > x
(jumpOnCond(2) | (jump(6) |
(load(tmp) | (push(1) | (minus | (store(z) | (jump(3) |
└──────────────────────────────────────────────────────────┘
                        z := tmp - n(1) ;
(load(tmp) | (store(y) | iln))))))))))))):IList
└──────────────────┘
                    y := tmp ;
```


Compiler

generate(if ((z - y) % n(2)) === n(0) { tmp := y + (z - y) / n(2) ; }
else { tmp := y + ((z - y) / n(2)) + n(1) ; })
generates the following:

```
(load(z) | (load(y) | (minus | (push(2) | (mod | (push(0) | (equal |
└──────────────────────────────────────────────────────────┘
                        ((z - y) % n(2)) === n(0)
(jumpOnCond(2) | (jump(10) |
(load(y) | (load(z) | (load(y) | (minus | (push(2) | (divide | (add | (store(tmp) | (jump(11) |
└──────────────────────────────────────────────────────────┘
                        tmp := y + (z - y) / n(2) ;
(load(y) | (load(z) | (load(y) | (minus | (push(2) | (divide | (add | (push(1) | (add | (store(tmp) |
└──────────────────────────────────────────────────────────┘
                        tmp := y + ((z - y) / n(2)) + n(1) ;
iln))))))))))))))))))))))))):IList
```

Compiler

If the program is `while E {S1}`, then it generates the following list of instructions:



Compiler

`generate(while y < n(10) || y === n(10) {x := x * y ; y := y + n(1) ;})`

generates the following:

```

(load(y) | (push(10) | (lessThan | (load(y) | (push(10) | (equal | (or |
  y < n(10) || y === n(10)
  (jumpOnCond(2) | (jump(10) |
  (load(x) | (load(y) | (multiply | (store(x) |
    x := x * y ;
  (load(y) | (push(1) | (add | (store(y) | (bjump(17) | iln))))))))))))))):IList
  y := y + n(1) ;
  
```

Compiler

`for V E1 E2 {S1}`

is equivalent to

```
V := E1 ;  
while V < E2 || V === E2 {  
  S1  
  V := V + s(1) ;  
}
```

This can be used to describe the equation to generate the list of instructions for the `for` statement.

Compiler

If the program is `for V E1 E2 {S1}`, then it generates the following list of instructions:

the list of instructions for `V := E1 ;`

the list of instructions for

`while V < E2 || V === E2 { S1 V := V + s(1) ; }`

Compiler

generate(for y n(1) n(10) { x := y * x ; })

generates the following:

```
(push(1) | (store(y) |
  y := n(1) ;
  while y < n(10) || y === n(10)
  { x := y * x ; y := y + n(1) ; }
  (load(y) | (push(10) | (lessThan | (load(y) | (push(10) | (equal | (or |
    y < n(10) || y === n(10)
    jumpOnCond(2) | (jump(10) | (load(y) | (load(x) | (multiply | (store(x) | (load(y)
    x := y * x ;
    (push(1) | (add | (store(y) | (bjump(17) | iln))))))))))))))))):IList
  y := y + n(1) ;
```

Compiler

If the program is **S1 S2**, then it generates the following list of instructions:

the list of instructions for S1	the list of instructions for S2
--	--

Compiler

`generate(x := y * x ; y := y + n(1) ;)` generates the following:

```
(load(y) | (load(x) | (multiply | (store(x) |
  x := y * x ;
  (load(y) | (push(1) | (add | (store(y) | iln))))))):IList
  y := y + n(1) ;
```

Compiler

`generate(y := n(1) ; while y < n(10) || y === n(10) { x := y * x ; y := y + n(1) ; })` generates the following:

```
(push(1) | (store(y) |
  y := n(1) ;
  while y < n(10) || y === n(10)
  { x := y * x ; y := y + n(1) ; }
  (load(y) | (push(10) | (lessThan | (load(y) | (push(10) | (equal | (or |
    y < n(10) || y === n(10)
    (jumpOnCond(2) | (jump(10) | (load(y) | (load(x) | (multiply | (store(x) | (load(y)
      x := y * x ;
      (push(1) | (add | (store(y) | (bjump(17) | iln))))))))))))))))):IList
    y := y + n(1) ;
```

Exercises

1. Complete the compiler and do some tests for the compiler.

Appendices

The compiler translates the program

```
x := n(1) ;  
for y n(1) n(10) {  
  x := y * x ;  
}
```

into the lists of instructions

```
(push(1) | (store(x) | (push(1) | (store(y) | (load(y) | (push(10) |  
(lessThan | (load(y) | (push(10) | (equal | (or | (jumpOnCond(2) |  
(jump(10) | (load(y) | (load(x) | (multiply | (store(x) | (load(y) | (push(1)  
| (add | (store(y) | (bjump(17) | (quit | iln))))))))))))))))))):IList
```

Appendices

The compiler translates the program

```
x := n(24) ; y := n(30) ;  
while y != n(0) {  
  z := x % y ; x := y ; y := z ;  
}
```

into the lists of instructions

```
(push(24) | (store(x) | (push(30) | (store(y) | (load(y) | (push(0) |  
(notEqual | (jumpOnCond(2) | (jump(10) | (load(x) | (load(y) | (mod |  
(store(z) | (load(y) | (store(x) | (load(z) | (store(y) | (bjump(13) | (quit |  
iln))))))))))))))):IList
```

Appendices

The compiler translates the program

```
x := n(2000000000000000000) ;  
y := n(0) ;  
z := x ;  
while y != z {  
  if ((z - y) % n(2)) == n(0) {  
    tmp := y + (z - y) / n(2) ;  
  } else { tmp := y + ((z - y) / n(2)) + n(1) ; }  
  if tmp * tmp > x { z := tmp - n(1) ; }  
  else { y := tmp ; }  
}
```

into the lists of instructions

```
(push(200000000000000000)) | (store(x) | (push(0) | (store(y) | (load(x) |  
| (store(z) | (load(y) | (load(z) | (notEqual | (jumpOnCond(2) | (jump(44)  
| (load(z) | (load(y) | (minus | (push(2) | (mod | (push(0) | (equal |  
| jumpOnCond(2) | (jump(10) | (load(y) | (load(z) | (load(y) | (minus |  
| (push(2) | (divide | (add | (store(tmp) | (jump(11) | (load(y) | (load(z) |  
| (load(y) | (minus | (push(2) | (divide | (add | (push(1) | (add | (store(tmp)  
| (load(tmp) | (load(tmp) | (multiply | (load(x) | (greaterThan | |
| jumpOnCond(2) | (jump(6) | (load(tmp) | (push(1) | (minus | (store(z) |  
| jump(3) | (load(tmp) | (store(y) | (bjump(47) | (quit |  
iln)))))))))))))))))))))))))))))))))))))))))):IList
```