Dropshipping Product DBMS – Group 53

```
Yahya Muhammad (500968266)
Hana Gorikhan (500871926)
Moiz Kharodawala (500968133)
```

```
create table supplier (
  "supplierID" INTEGER check ("supplierID" >= 0),
  name varchar2(30) NOT NULL UNIQUE,
  email varchar2(50) DEFAULT NULL,
  phone# varchar2(12) DEFAULT NULL,
  street varchar2(20) DEFAULT NULL,
  city varchar2(20) DEFAULT 'Toronto',
  country varchar2(5) DEFAULT 'CA',
  postalcode varchar2(10) DEFAULT NULL,
  PRIMARY KEY ("supplierID")
);
CREATE TABLE productcategory (
  "categoryID" SMALLINT CHECK ("categoryID" >= 0),
  name VARCHAR2(20) NOT NULL UNIQUE,
  description varchar2(100) DEFAULT NULL,
  PRIMARY KEY ("categoryID")
);
CREATE TABLE product (
  "productID" INTEGER CHECK ("productID" >= 0),
  "categoryID" SMALLINT REFERENCES productcategory("categoryID") ON DELETE CASCADE,
  name VARCHAR2(25) NOT NULL UNIQUE,
  description varchar2(100) DEFAULT NULL,
```

```
price DOUBLE PRECISION NOT NULL,
  cost DOUBLE PRECISION NOT NULL,
  profit DOUBLE PRECISION DEFAULT 0,
  PRIMARY KEY ("productID")
);
CREATE TABLE supplies (
  "supplierID" INTEGER REFERENCES supplier("supplierID"),
  "productID" INTEGER REFERENCES product("productID") ON DELETE CASCADE,
  PRIMARY KEY ("supplierID", "productID")
);
CREATE TABLE inventory(
  "inventoryID" INTEGER CHECK ("inventoryID" >= 0),
  "productID" INTEGER REFERENCES product("productID") ON DELETE CASCADE,
  quantity INTEGER DEFAULT 0 NOT NULL,
  warehouse# INTEGER DEFAULT 0 NOT NULL,
  aisle# INTEGER DEFAULT 0 NOT NULL,
  section# INTEGER DEFAULT 0 NOT NULL,
  PRIMARY KEY ("inventoryID", "productID")
);
CREATE TABLE discount(
  "discountID" INTEGER CHECK ("discountID" >= 0),
  "productID" INTEGER REFERENCES product("productID") ON DELETE CASCADE,
  discount DOUBLE PRECISION DEFAULT 0 NOT NULL,
  description varchar2(100) DEFAULT NULL,
  expiry DATE DEFAULT sysdate NOT NULL,
  active SMALLINT DEFAULT 0 NOT NULL CHECK (active = 0 or active = 1),
```

```
PRIMARY KEY ("discountID", "productID")
);
INSERT INTO supplier("supplierID", name) VALUES (0, 'Apple Inc.');
SELECT * FROM supplier;
INSERT INTO productcategory("categoryID", name) VALUES (0, 'Phones');
SELECT * FROM productcategory;
INSERT INTO product("productID", "categoryID", name, price, cost) VALUES (0, 0, 'Iphone', 1000, 500);
SELECT * FROM product;
insert into supplies("supplierID", "productID") values (0,0);
select * from supplies;
INSERT INTO inventory("inventoryID", "productID", quantity) values (0, 0, 10);
SELECT * FROM inventory;
INSERT INTO discount("discountID", "productID", discount) values (0, 0, 10);
SELECT * FROM discount;
DELETE FROM product WHERE "productID" = 0;
DELETE FROM supplier WHERE "supplierID" = 0;
DELETE FROM productcategory WHERE "categoryID" = 0;
```